NORMALIZATION OF LANGUAGE EMBEDDINGS FOR CROSS-LINGUAL ALIGNMENT

ABSTRACT

Learning a good transfer function to map the word vectors from two languages into a shared cross-lingual word vector space plays a crucial role in cross-lingual NLP. It is useful in translation tasks and important in allowing complex models built on a high-resource language like English to be directly applied on an aligned low resource language. While Procrustes and other techniques can align language models with some success, it has recently been identified that structural differences (for instance, due to differing word frequency) create different profiles for various monolingual embedding. When these profiles differ across languages, it correlates with how well languages can align and their performance on cross-lingual downstream tasks. In this work, we develop a very general language embedding normalization procedure, building and subsuming various previous approaches, which removes these structural profiles across languages without destroying their intrinsic meaning. We demonstrate that meaning is retained and alignment is improved on similarity, translation, and cross-language classification tasks. Our proposed normalization clearly outperforms all prior approaches like centering and vector normalization on each task and with each alignment approach.

1 INTRODUCTION

The standard multilingual NLP approaches typically do not jointly learn a single embedding, since words tend to cluster by language, and thus are not useful for translation and cross-lingual learning tasks. Rather, after learning individual embeddings, the usual approach is to map word vectors from multiple languages into a shared cross-lingual word vector space (Glavaš et al., 2019). This shared space creates a cross-lingual word embedding (CLWE) (Karan et al., 2020; Wang et al., 2019). These serve as a valuable tool for transferring data across different languages, understanding cross-linguistic differences, and cross-lingual transfer for downstream tasks, such as direct translation (Gouws et al., 2015; Heyman et al., 2017; Lample et al., 2018), cross-lingual information retrieval (Vulic & Moens, 2015), cross-lingual document classification (Klementiev et al., 2012), and cross-lingual dependency parsing (Guo et al., 2015; Ahmad et al., 2019).

A common element of almost all CLWE methods is the use of a rigid, orthogonal transformation mapping one embedding onto another so they inhabit a shared linguistic space. An orthogonal transformation is a special class of transformations that can be interpreted as the space of (in our case, high-dimensional) rotations around the origin, and allowing a mirror flip. This family of transformations preserves (a) linear and (b) angular properties. By linear properties, we mean that the straight-line Euclidean distance between elements is preserved, as are more powerful properties like analogies (e.g., Paris - France + Italy ≈ Rome). Angular properties refer to measuring angles between pairs of points (from the origin), and as a result, cosine distance is preserved. Given a correspondence between pairs of objects across two embeddings, the classic Procrustes method, provides a closed-form solution which minimizes the sum of Euclidean distances. If the vectors are all first normalized, then this also maximizes the sum of cosine similarities (Dev et al., 2021).

Under this framework, there has been a flurry of work significantly improving CLWE model performance along with two directions. Semi-supervised and unsupervised models make these approaches require less input, and more amenable to lower-resource languages. For example Bootstrap Procrustes (PROC-B) (Glavaš et al., 2019; Vulić et al., 2019) is semi-supervised in that it starts with a small pairwise correspondence (of 500-1000 words), aligns those to infer a larger correspondence,

and repeats applying Procrustes alignment. Methods like MUSE (Conneau et al., 2018a) are unsupervised, and use a GAN to estimate a correspondence before applying a Procrustes procedure.

The second direction is preprocessing the embeddings before applying the Procrustes alignment. These involve methods like removing the mean, removing principal components, and normalization which we will discuss in depth later. In principle, these methods aim to remove the geometry of data intrinsic to particular languages (but not shared across languages) while preserving similarity properties as assured by orthogonal alignment. The space of transformations allowed under orthogonal alignments is quite large, and we make the point that unless this data geometry is "normalized" it inhibits the alignment from optimizing over the entirety of this large space.

Finally, we note that methods like Canonical Correlation Analysis (CCA) (Faruqui & Dyer, 2014), Discriminative Latent Variable (DLV) (Ruder et al., 2018), and Ranking-based optimization (RC-SLS) (Joulin et al., 2018) have also been applied towards finding an orthogonal alignment (or pair of alignments) which minimizes a different optimization function – since the objective function may not align with sums of squared Euclidean of cosine distance (Conneau et al., 2018a; Smith et al., 2017). Unlike the others, the RCSLS method notably does not require a rigid transformation.

This paper is on embedding *preprocessing*, and is agnostic to the alignment used afterward.

Our contribution. This work proposes a new and general approach to preprocessing word embeddings, subsuming many previous approaches. The key is *Spectral Normalization* which regularizes the spectral properties of monolingual embeddings by setting all of the top singular vectors to have the same singular value. It leaves alone the smaller singular value; these capture important information and cannot be zeroed out, but making them the same value as the top singular vectors introduces too much noise. Spectral normalization already performs as well as the best previous approaches on alignment and translation tasks, and since it applies a fairly uniform stretching to the embeddings it does not distort monolingual similarity performance. Moreover, we show layering Spectral Normalization within an iterative sequence with also centering and vector length normalization improves results further. We demonstrate this improvement on the standard translation tasks, as well as on downstream cross-lingual uses cases of document classification and natural language inference.

Beyond CLWE. This paper focuses on normalization for alignment of word vector embeddings. This is for a couple of reasons. First, most relevant prior work does the same in the context of language translation, and so it allows for direct comparison. Second, these contexts have generally the largest embeddings, are trained on the most data, and are easy to interpret. However, as foundation models (Bommasani et al., 2021) become ubiquitous, many other settings induce similar challenges. For instance, alignment of various models from different data sources allows for improved ensemble embeddings (Dev et al., 2021), and this could extend to image (Frome et al., 2013; Kiela & Bottou, 2014) or graph embeddings (Grover & Leskovec, 2016; Perozzi et al., 2014). Or in aligning embeddings of spatial data (Jenkins et al., 2019) or of merchants (Wang et al., 2021), one may want to align data from different geographic regions for tasks in transfer learning and domain adaptation. As a concrete example of the generality, we demonstrate an improvement via our normalization approaches in aligning genomic data embeddings (Demetci et al., 2020) in Appendix F.

2 EXISTING METHODS FOR ORTHOGONAL VECTOR SPACES ALIGNMENT

Given a language L, our starting point is an embedded representation of a set of n words. Indexing words from $i = 1 \ldots n$, each is associated with a vector $x_L^i \in \mathbb{R}^d$. And let $X_L = \{x_L^1, \ldots, x_L^n\}$ be the set of n words as their vector representation. These vector representations (derived by methods like word2vec (Mikolov et al., 2013a), GloVe (Pennington et al., 2014), or FastText (Bojanowski et al., 2017)) are chosen so words with similar pairwise cosine similarity are found in the similar local context in large text corpora on which they are trained. Higher-level linear structure is shown to emerge, such as concept subspaces and analogies (Mikolov et al., 2013).

The focus of this paper is on aligning embeddings of two languages L_1 and L_2. Each embedding X_{L_1} and X_{L_2}, only is designed to ensure pairwise relationships between its word vectors, but the actual coordinates of those vectors do not have any explicit meaning. Yet, previous work has clearly demonstrated that there exists significant overall structural similarity, and alignment seeks to make correspondences between those structures for translation and joint understanding.

Most methods start with a known correspondence (or build one) between a set of K words in two languages, wlog let these be the same first K indexed words in those languages, denoted $X_{L_1}^K = \{x_{L_1}^1 \ldots x_{L_1}^K\}$ and $X_{L_2}^K = \{x_{L_2}^1 \ldots x_{L_2}^K\}$. Then the *Procrustes Problem* solve for an orthogonal matrix $W^* = \arg\min_W \|X_{L_1}^K W - X_{L_2}^K\|_2^2$. There exists a simple solution (Artetxe et al., 2016; Smith et al., 2017; Xing et al., 2015; Dev et al., 2021) as $W^* = UV^\top$ where $U\Sigma V^\top = \mathsf{svd}(X_{L_1}^K (X_{L_2}^K)^\top)$. Dev et al. (2021) also points out that if all vectors are normalized first, then this procedure also maximizes the sum of cosine similarities.

2.1 Pre-processing Embeddings before Orthogonal Alignment

It turns out directly aligning embeddings from two languages (even using the "optimal" Procrustes solution) does not provide the best possible joint embedding for translation tasks. While word meaning appears to hold a similar structure, languages have other properties such as differing word frequency, and this for instance leads to more frequent words having longer vectors in embeddings. This extra language-specific structure tends to interfere with alignment. As a result, a number of techniques have been developed to "normalize" the embeddings before Procrustes (or other) alignment. This in some sense allows the word meaning to dominate the optimization tasks without other confounding factors. We review the most common normalization approaches.

Mean Centering (C) subtracts the mean of all vectors in an embedding from each vector in that embedding. The result is that the mean of all vectors is 0. This is a rigid transformation, and so does not change the Euclidean distance between any pair of points in an embedding, and also preserves any linear property like analogies (e.g., Paris - France + Italy $\approx$ Rome). Dev et al. (2021) points out that this is the first step (followed by the Procrustes orthogonal transformation) to minimize the sum of squared Euclidean distances among paired words, under any rigid transformation. However, this *does change* the cosine distance between pairs of points.

Length Normalization (L) makes each vector have a 2-norm equal to 1, but retains its direction from the origin (Artetxe et al., 2016; Xing et al., 2015). This preprocessing step does not change the cosine distance between any pair of points in an embedding. But, it *does change* the Euclidean distance between pairs of points.

Despite these contrasting goals, these two normalizations each turn out to be individually effective in regularizing the geometry of the embeddings, and allow for better CLWE. Zhang et al. (2019), realized doing both was even more effective, and showed that iterating these two steps achieves the state-of-the-art way to preprocess, we denote as **I-C+L**. Iterative Normalization eventually transforms monolingual word embeddings to have unit-length and zero-mean simultaneously (in practice they terminate this iterative process after a few steps before it achieves these two goals exactly).

PCA Removal (PR) computes the principal component analysis (PCA) of an embedding, and then projects away from the direction of the top principal component, removing it. Mu & Viswanath (2018) observed that the top singular values typically do not encode essential semantic relationships between words but rather align strongly with word frequency. Also, the top principal values are much larger than the other values. After eliminating $d/100$ principal components, where d is the dimension of a word representation, they achieve better performance on both intrinsic and extrinsic tasks. Sachidananda et al. (2021) applied this simple pre-processing approach to their Filtered Inner Product Projection (FIPP) alignment method, and they significantly improve on the BLI task.

2.2 Spectral Statistics of Embeddings

Dubossarsky et al. (2020) recently documented how cross-lingual alignment is strongly affected by the spectral statistics of monolingual embeddings. We stack the embedded vectors $x_L^i \in \mathbb{R}^d$ as rows in a $n \times d$ matrix $A \in \mathbb{R}^{n \times d}$. The SVD decomposes A into $U\Sigma V^\top$ where U and V contain the left and right singular vectors, and the singular values $\sigma_1 \geq \sigma_2 \geq \ldots \geq \sigma_d \geq 0$ are on the diagonal of Σ. The *effective rank* of A is a smoother analog to rank (when there is noise in low rank components), defined $\mathsf{er}(A) = e^{H(\Sigma)}$ where $H(\Sigma) = -\sum_{i=1}^d \bar{\sigma}_i \log \bar{\sigma}_i$ with $\bar{\sigma}_i = \sigma_i / \sum_{i=1}^d \sigma_i$. The *effective condition number* $\kappa_{\mathsf{eff}}(A) = \sigma_1 / \sigma_{\mathsf{er}(A)}$, which replaces the numerator (of condition number, σ_d) with the more robust singular value at the effective rank. This is desired to be small in stable data

sets. The *joint effective condition number* measures the harmonic mean of the effective condition number across two matrices A, A' as ECOND-HM$(A, A') = \frac{2\kappa_{\text{eff}}(A)\kappa_{\text{eff}}(A')}{\kappa_{\text{eff}}(A)+\kappa_{\text{eff}}(A')}$. The *singular value gap* measures how similar the singular value sequences are between two matrices as SVG$(A, A') = \sum_{i=1}^{d}(\log \sigma_i - \log \sigma'_i)^2$. These should both be smaller, for more comparable data sets.

Dubossarsky et al. (2020) applied these to monolingual embeddings and demonstrated that the performances of several CLWE methods were closely tied to these spectral properties. Basically embeddings align better if they are better jointly conditioned, especially measured via joint effective condition number and the singular value gap. Motivated by this idea, we propose methods that spectrally normalize embeddings improving these statistics while retaining intra-embedding meaning.

3 NEW METHOD: SPECTRAL NORMALIZATION

The predominant effect of unit-length and zero-mean normalization on monolingual word embeddings is that it makes embedding vectors from a language lie on a hypersphere with the center of the hypersphere centered at the origin. However, this does not take into account how the word embeddings vectors are spread out or clustered on the hypersphere. Approaches like PCA removal and mean centering have the effect of reducing the top principal component or top singular vector. As a result, if the spectral properties are extreme, it can help regularize them. However, this approach can be blunt. PCA removal makes the top singular value exactly 0, so the condition number becomes infinite. Other quantities like the effective condition number, $\kappa_{\text{eff}}(A)$, do however, tend to decrease.

To this effect, we propose a new algorithm Spectral Normalization that more gently regularizes the spectral properties of word embeddings; see Algorithm 1. We will then combine it with other approaches to again ensure the embedding vectors lie on the unit sphere.

Algorithm 1 Spectral Normalization (SpecNorm(A, β))

1: Compute svd$(A) = U\Sigma V^{\top}$; Let $D \in \mathbb{R}^d$ be a diagonal matrix.
2: Compute $\eta = \sqrt{\|A\|_F^2/d}$, where d is the dimension of the word embedding
3: **for** $i = 1, \ldots, d$ **do**
4:    **if** $(\Sigma_{ii} > \beta\eta)$ **then** $D_{ii} \leftarrow \Sigma_{ii}/(\beta\eta)$
5:    **else** $D_{ii} = 1$.
6: **return** AVD^{-1}

Given a monolingual word embedding A it updates part of the spectral properties of A as a whole, using on a parameter $\beta \geq 0$ (which we fix later as $\beta = 2$ via cross-validation). Based on an average of singular values $\eta = \sqrt{\|A\|_F^2/d}$, if a value is above β times that average, it adjusts it to $\beta\eta$. Hence, all of the top directions are given the same singular value. Otherwise, if it is below $\beta\eta$, it is considered a minor effect (some are quite small, and fairly noisy), and it is left alone. If these small ones are completely zeroed out, the critical information within is destroyed. However, if these small ones are also given the same value (i.e., $\beta\eta$) then components which do not contribute to the most prevalent aspects of a vectors similarity are given more importance, and we observe (see Section 4.1) that the usefulness of the embedding decreases.

Iterative Spectral Normalization.   Spectral normalization makes the most sense (see Appendix I) in a setting where the vectors are already centered, and also unit length. While SpecNorm does not change the center of the data, it does not maintain the length of individual vectors. As such, we advocate combining these methods into a single iterative algorithm: I-C+SN+L as in Algorithm 2.

Algorithm 2 Iterative Spectral Normalization with C+L normalization (I-C+SN+L$(A, \#\text{Iter})$)

1: **for** #Iter steps **do**
2:    $A \leftarrow$ Center A
3:    $A \leftarrow$ SpecNorm(A)
4:    $A \leftarrow$ Unit length normalization of A
5: **return** A

We observe in Figure 1 that this process significantly improves the spectral properties, compare to any other approach. Without preprocessing (None), the languages (EN: English, DE: German, HI: Hindi, JA: Japanese shown) have large effective condition numbers – indicating that there is a large disparity between meaningful singular values. Note the y-axis is in the log scale. Hence, aligning these languages without normalization would likely restrict alignment among top singular vectors, not allowing enough degree of freedom to align corresponding words.

In contrast, after preprocessing when these values are more uniform, rotations among the dimensions containing the top principal components will not have an influence on the data distribution, and can fully optimize the alignment between words. Moreover, Figure 1 shows that I-C+SN+L most decreases the effective condition number, joint effective condition number, and singular value gap. Further, these values are fairly uniform across languages, despite great variation beforehand (as shown with None). In fact, I-C+SN+L is much more effective than other methods.

Figure 1: Spectral Measures of four (4) monolingual word embeddings, before (None) and after applying various normalization methods.

Is Iteration Necessary? While alternating optimization is a common paradigm, is it necessary or useful to achieve these normalization goals? There may be many solutions which achieve length, center, and spectral normalization simultaneously. In fact, we observe that "centering" with the geometric median (Chatelon et al., 1978; Eyster et al., 1973; Overton, 1983) and then length normalizing vectors (we call this GeoMediaN, and detail it in Appendix A) achieves length and center normalization without iteration. However, as we observe, it under-performs I-C+L. We hypothesize that the more gradual changes to the embedding, which keep some aspects preserved each step, the less distortion of the pairwise and group-wise similarity, and thus preserves a more global structure.

4 EXPERIMENTAL ANALYSIS

We provide an evaluation of our proposed preprocessing methods using 8 language embeddings pretrained on Wikipedia (Bojanowski et al., 2017) of each language: Croatian (HR), English (EN), Finnish (FI), French (FR), German (DE), Italian (IT), Russian (RU), and Turkish (TR). We use the 300-dimensional fastText (Bojanowski et al., 2017)[1] embeddings, and all vocabularies are trimmed to the 200K most frequent words.

Alignment evaluation tasks: BLI We evaluate and compare our proposed preprocessing methods mostly on the Bilingual Lexicon Induction (BLI) task, a word translation task. We discuss two more global applications Cross-lingual document classification (CLDC), and Cross-lingual transfer for natural language inference (XNLI) later. BLI is more direct, and has become the de facto evaluation task for CLWE models. For words in the source language, this task retrieves the nearest neighbors in the target language after alignment to check if it contains the translation. It reports the mean average precision (MAP) (Glavaš et al., 2019), which is equivalent to the mean reciprocal rank (MRR), of the translation. Unless stated otherwise, reported values on baseline methods are taken from (Glavaš et al., 2019), and use the Google Translate (GTrans) dictionary from (Glavaš et al., 2019)[2]. We trained (aligned) using 1k, 3k and 5k source words and evaluated (tested) on separate 2k source test queries, unless noted otherwise.

---

[1] https://github.com/facebookresearch/fastText
[2] https://github.com/codogogo/xling-eval?utm_source=catalyzex.com

Alignment Algorithms. We evaluated and compared the result of several supervised rigid-transformation CLWE models on the evaluation benchmarks using our proposed methods. All have publically available code, links are found in the reference citation. These include Canonical Correlation Analysis (CCA) (Faruqui & Dyer, 2014), Procrustes (PROC) (Artetxe et al., 2016; Smith et al., 2017; Xing et al., 2015; Dev et al., 2021), Bootstrapping Procrustes (PROC-B) (Glavaš et al., 2019), and Discriminative Latent-Variable (DLV) (Ruder et al., 2018), as discussed in Section 1. We also consider Ranking-Based Optimization (RCSLS) (Joulin et al., 2018) which is not a rigid alignment. In a few places, we also compare with VECMAP (Artetxe et al., 2018) as an example of an unsupervised alignment process. This should only use the geometry of the global embedding structure, e.g., derived from the natural ontology, and our normalization method still helps when using this approach.

4.1 Hyperparameter Tuning

Our main proposed algorithm I-C+SN+L has a few simple parameters. To avoid overfitting, we choose these through cross-validation on English (EN) and a held-out set of 5 languages Hindi (HI), Russian (RU), Chinese (ZH), Japanese (JA), Turkish (TR). Ten (10) Language pairs of the form EN-X and X-EN were considered. The hyperparameters $\beta \in \{1, 2, 3, 4, 5\}$ and #Iter (number of iterations) $\in \{1, 2, 3, 4, 5\}$ were fine-tuned for I-C+SN+L.

We used the publically available MUSE[3] translation dictionary (Conneau et al., 2018a) for hyperparameter tuning. The Procrustes alignment algorithm was trained on 5k source words and evaluated on 1.5k source test queries. We reported the mean average precision (MAP) in Table 1 for $\beta \in \{1, 2, 3, 4, 5\}$ and with #Iter $\in \{1, 2, 3, 4, 5\}$. We observe the value of $\beta = 2$ was consistently the best threshold (although any $\beta \geq 2$ performed similarly). However, the result did not change much with respect to the number of iterations.

Table 1: Cross-Validation for Hyperparameter Tuning: MAP after Procrustes for 10 language pairs.

β	#Iter=1	#Iter=2	#Iter=3	#Iter=4	#Iter=5
1	0.363	0.340	0.328	0.322	0.317
2	0.385	**0.386**	**0.386**	**0.386**	**0.386**
3	0.381	0.384	0.384	0.384	0.384
4	0.381	0.382	0.382	0.382	0.382
5	0.380	0.381	0.381	0.381	0.381

The tie between the #Iter hyperparameter was broken using their performance on thirteen English word similarity benchmarks; details in Appendix C. In Table 2 reports the average Spearman rank coefficient score on the tasks (None means no normalization). $(\beta, \#\text{Iter}) = (2, 5)$ achieved the highest score. So hereafter, we applying I-C+SN+L with the hyperparameter $(\beta, \#\text{Iter}) = (2, 5)$.

Table 2: Monolingual word similarity task; Average Spearman rank coefficient

None	$(\beta, \#\text{Iter}) = (2, 2)$	$(\beta, \#\text{Iter}) = (2, 3)$	$(\beta, \#\text{Iter}) = (2, 4)$	$(\beta, \#\text{Iter}) = (2, 5)$
0.651	0.67077	0.67101	0.67108	**0.67111**

Note that the proposed approach (I-C+SN+L) only increased this score for these similarity tasks, so showed no signs of distorting inherent information. Although Spectral Normalization does not exactly preserve the linear properties or angular properties (as centering and length normalization do, one each, respectively), it does not suffer ill effects. We hypothesize this is because it is somewhat uniformly stretching words along the major modes of variation, and is effectively removing information not relevant to meaning, like frequency. This benign effect is in contrast to other spectral adjustments (removing small singular values, or setting all to the same value) shown in Appendix C.

---

[3] https://github.com/facebookresearch/MUSE

4.2 BLI Performance across Normalization and Alignment Algorithms

We compare and evaluate the BLI performance (MAP) of various normalization algorithms from previous works to our proposed algorithms. Using the MUSE translation dictionary, we trained CCA, PROC, PROC-B and RCSLS on 5k source words and evaluated on 1.5k source test queries. The following normalization algorithms were used in the comparison analysis: PR (PCA Removal) (Mu & Viswanath, 2018), GeoMediaN (Geometric Median Normalization), C+L (Mean centering and Length normalization, 1 round), I-C+L (Iterative Mean centering and Length normalization, 5 rounds) (Zhang et al., 2019), SN (Spectral Normalization, 1 round), C+SN+L (Mean centering, Spectral Normalization and Length normalization, 1 round), and I-C+SN+L (Iterative Mean centering, Spectral Normalization and Length normalization, 5 rounds). Specifically, we evaluated 18 language pairs, i.e., English (EN) from/to Bulgarian (BG), Catalan (CA), Czech (CS), German (DE), Spanish (ES), Korean (KO), Thai (TH) and Chinese (ZH), separate from hyperparameter tuning. The average is reported in Table 3, all results are in Appendix I. For almost all algorithms I-C+SN+L achieves the best scores (and especially on $\mathbf{X}_{L_2}-\mathbf{EN}$, often considerably better). The only exceptions are on non-rigid RCSLS when C+SN+L (with no iteration) or just SN (with C+L) performs slightly better. So, Spectral Normalization, and in particular I-C+SN+L, is shown as the best way to normalize languages before alignment.

Table 3: BLI performance (MAP) on aligning $\mathbf{EN}-\mathbf{X}_{L_2}$ and $\mathbf{X}_{L_2}-\mathbf{EN}$

	Methods : $\mathbf{EN}-\mathbf{X}_{L_2}$				Methods : $\mathbf{X}_{L_1}-\mathbf{EN}$			
Normalization	CCA	PROC	PROC-B	RCSLS	CCA	PROC	PROC-B	RCSLS
None	0.358	0.365	0.377	0.394	0.398	0.399	0.405	0.428
PR	0.394	0.391	0.404	0.373	0.434	0.430	0.442	0.425
GeoMediaN	0.393	0.391	0.400	0.379	0.433	0.432	0.440	0.429
C+L	0.393	0.394	0.408	0.404	0.439	0.437	0.445	0.464
I-C+L	0.394	0.395	0.410	0.406	0.439	0.438	0.448	0.460
SN	0.391	0.394	0.408	0.405	0.440	0.438	0.451	**0.468**
C+SN+L	0.395	0.396	0.413	**0.407**	0.444	0.444	0.458	0.466
I-C+SN+L	**0.396**	**0.398**	**0.414**	0.406	**0.445**	**0.446**	**0.461**	0.466

We also compute the average BLI MAP score across all 28 language pairs for more direct comparison to prior work (Glavaš et al., 2019), summarized in Table 4 and Appendix D. All results are in Appendix J. We compare I-C+SN+L (denoted with SN) against no normalization on various dictionary sizes: 1k, 3k and 5k source words and evaluated on 2k source test queries. *In all cases, I-C+SN+L significantly improves over the baseline.* This includes improvement over RCSLS which is non-rigid, so in principle could "learn" adjustments similar to our normalization in the process of alignment. We also tested on VECMAP, an unsupervised approach; I-C+SN+L preprocessing also improves this result from 0.375 to 0.410.

Table 4: Summary of BLI performance (MAP), average scores for all 28 language pairs. No normalization results from (Glavaš et al., 2019), against I-C+SN+L (denoted SN).

Dict	CCA	CCA^{SN}	PROC	PROC^{SN}	PROC-B	PROC-B^{SN}	DLV	DLV^{SN}	RCSLS	RCSLS^{SN}
1K	.289	**.314**	.299	**.326**	.379	**.407**	.289	**.332**	.331	.331
3K	.378	**.401**	.384	**.408**	.398	**.415**	.381	**.429**	.415	**.427**
5K	.400	**.423**	.405	**.429**	–	–	.403	**.452**	.437	**.460**

Table 5: BLI performance (MAP) on aligning Cross-lingual Contextual Embedding, $\mathbf{EN}-\mathbf{X}_{L_2}$

Embedding	Normalization	EN-AR	EN-DE	EN-NL	Avg
FastText	None	0.256	0.357	0.477	0.363
Type-level	None	0.501	0.441	0.540	0.494
FastText	I-C+L	0.284	0.372	0.493	0.383
Type-level	I-C+L	0.510	0.449	0.543	0.501
FastText	I-C+SN+L	0.280	0.375	0.499	0.385
Type-level	I-C+SN+L	**0.525**	**0.450**	**0.544**	**0.506**

Normalizing contextual type-level embeddings. Table 5 compares the impact of Iterative Normalisation and Spectral Normalisation on the BLI performance on aligning Cross-lingual Contextual Embedding. We follow the implementation details from Xu & Koehn (2021) for learning representatives within BERT. Then the learned normalization can be viewed as a composition to the functional embedding, so is compatible with downstream uses. Our proposed normalization algorithm, Iterative Spectral Normalization, clearly outperforms Iterative Normalisation on the BLI task for aligning Contextual Embeddings. This buttresses the claim made by Xu & Koehn (2021) that improving the degree of isomorphism between contextual embeddings spaces enhances the quality of learned alignment and subsequently a better performance on the BLI task.

4.3 DOWNSTREAM TASKS

We conclude by demonstrating that Spectral Normalization not only improves in direct translation tasks, but also captures an important global structure that generalizes from a high resource language (i.e., English, EN) to lower resource languages. In both examples, a powerful classifier is trained on the EN embedding (after normalization), and then we demonstrate that after a lower resource language (e.g., German, DE) has been normalized and align the analysis task can be directly applied to that language. And in particular, adding the simple process of our normalization (I-C+SN+L) dramatically improves the results over not doing that step.

Cross-lingual Document Classification (CLDC). The CLDC task builds a topic classification using a language model on a high resource language (in our case English EN) across 15 topics. The TED CLDC corpus assembled by (Hermann & Blunsom, 2014) was used for training and evaluation. Following (Glavaš et al., 2019) a simple CNN was used to train. Table 6 summarizes the average F1-score for all topic classifiers on 5 language pairs. The CLWEs induced by PROC[SN], PROC-B[SN], DLV[SN], and RCSLS[SN] (using I-C+SN+L) outperformed the baseline result (with no normalization) on the CLDC task, significantly improving the best average score from 0.421 to 0.461. Glavaš et al. (2019) used only 12 of 15 topics, but could not confirm which, so we re-ran all baselines using all 15 topics.

Table 6: CLDC performance (micro-averaged F_1 scores). Cross-lingual transfer EN–X

Model	Dict	EN-DE	EN-FR	EN-IT	EN-RU	EN-TR	Avg
PROC	5K	.366	.258	.338	.288	.278	.306
PROC[SN]	5K	.436	.366	.427	.517	.511	**.451**
PROC-B	3K	.364	.304	.299	.336	.317	.324
PROC-B[SN]	3K	.448	.396	.423	.522	.517	**.461**
DLV	5K	.419	.336	.397	.493	.458	.421
DLV[SN]	5K	.433	.323	.406	.499	.472	**.427**
RCSLS	5K	.466	.397	.403	.403	.406	.415
RCSLS[SN]	5K	.468	.500	.443	.488	.394	**.459**

Cross-lingual Natural Language Inference (XNLI). We evaluated the CLWE on a cross-lingual natural language inference (XNLI) task. We used a multi-lingual XNLI corpus created by (Conneau et al., 2018b), which is a collection of sentence pairs from the English MultiNLI corpus (Williams et al., 2018) translated into 14 languages. The MultiNLI corpus contains 433k sentence pairs with the labels entailment, contradiction, and neutral. The intersection between XNLI languages and BLI languages results in four XNLI evaluation pairs: EN-DE, EN-FR. EN-TR and EN-RU. We use the training setup in (Glavaš et al., 2019) with the Enhanced Sequential Inference Model (Chen et al., 2017) on English after normalization. First, we aligned normalized versions of each language onto the normalized EN embedding to obtain the shared cross-lingual embedding. Then we used the 5k test pairs from the XNLI corpus to evaluate each language alignment. Table 7 shows the result for PROC, PROC-B, and RCSLS alignments (DLV and VECMAP transform the EN embedding in the process, so were omitted). We compare against the same procedure *without* normalization from Glavaš et al. (2019) (I-C+SN+L normalization denoted ^{SN}). As in other experiments, our normalization improves the average test accuracy with each alignment approach.

Table 7: XNLI performance (test set accuracy)

Model	Dict	EN-DE	EN-FR	EN-TR	EN-RU	Avg
PROC	5K	.607	.534	.568	.585	.574
PROC^{SN}	5K	.611	.638	.542	.596	**.597**
PROC-B	3K	.615	.532	.573	.599	.580
PROC-B^{SN}	3K	.624	.638	.548	.601	**.603**
RCSLS	5K	.390	.363	.387	.399	.385
RCSLS^{SN}	5K	.499	.482	.504	.556	**.510**

5 CONCLUSION & DISCUSSION

We introduce a new way to normalize embeddings, based on spectral normalization, for use in creating cross-lingual word embeddings. Our approach generalizes previous approaches, and effectively removes much of the clumping of words based on properties other than the pair-wise similarity which encodes meaning. When used to individually preprocess monolingual embeddings, our approach allows any alignment procedure to find better alignments: resulting in improved performance on direct translation tasks as well as cross-lingual topic classification and natural language inference tasks. Moreover, we demonstrate this improvement is very broadly useful; it holds in contextual embeddings as well as on embeddings of non-language data (on genomic data in Appendix F).

Limitations. Our proposed preprocessing method heavily relies on the *approximately isomorphic* assumption of the two monolingual embedding spaces to be aligned (Mikolov et al., 2013b; Ruder et al., 2019). Under this condition, it is easier to learn a robust linear map between two monolingual embedding spaces that are *approximately isomorphic* than spaces that are not. Recent, lines of work (Søgaard et al., 2018; Nakashole & Flauger, 2018; Patra et al., 2018) have questioned this *approximately isomorphic* assumption and have shown that it does not hold in general and also it hinders the performance of some CLWE methods. The goal of our proposed preprocessing method is to canonically preprocess the two monolingual embedding spaces to improve their isomorphism, and we show it generally effective. However, if this approximate isomorphism is not present since the language structure is too different, or the embedding spaces are too noisy, then our proposed preprocessing method may not be effective.

CLWE methods such as Joint CLWE methods (Wang et al., 2019) and Cross-lingual Anchoring (Ormazabal et al., 2021) departs from the *approximately isomorphic* assumption. They learn new embeddings from scratch, using a different objective function that encourages alignment of representations or the vector embeddings of the words. As such our proposed preprocessing method do not apply. These methods, however, are less flexible and portable than alignment-based approaches, since they need to learn a new embedding for each pair of languages, and would need to re-train if only one is updated or a different or multiple pairs are considered. We have a preliminary comparison with Ormazabal et al. (2021) in Appendix E and show our methods are competitive.

6 ETHICS STATEMENT

The vast majority of NLP research and cutting-edge advancements are in English. This disadvantages those who primarily operate in other languages, with less developed models, or less data to train models. As large language models are the cornerstone of most NLP research and development in English, one of this work's main goals is to inexpensively port these advances to other languages, and those who use them. This will help unlock this technology to many around the world. As with most models, this accuracy and improvement may vary across tasks and languages.

While language models have many positive use cases including improving accessibility, better recommendations, and increased automation, they have some negative effects as well. These include requiring potentially large computational and hence environmental costs, encoding and exacerbating bias, and aiding in automatically generating fake or deceitful content. While this paper is unlikely to change the *desire* to use embeddings, it aims to reduce the burden of use and increase the effectiveness in lower-resource settings. And in particular to port models trained in English to other languages. This would reduce the cost of retraining in other languages if the English model can be reused, easing environmental costs. We support the maturing efforts in attenuating bias in all such embeddings. And while we acknowledge the possibility of this work aiding in the creation of deceitful content and the harm it can cause, we believe the many benefits outweigh the harms.

7 REPRODUCIBILITY STATEMENT

All existing methods are compared with publicly available code with publicly available data, with links above or in references. The exception is code for CLDC and XNLI is shared by Glavaš et al. (2019). Everything is run with default parameters; the exception is RCSLS were we follow the suggested hyperparameter selection strategy (Joulin et al., 2018) (with learning rate in $\{1, 10, 25, 50\}$ and epoch number in $\{10, 20\}$). Our new code for SpecNorm is in Appendix G.

REFERENCES

Eneko Agirre, Enrique Alfonseca, Keith Hall, Jana Kravalova, Marius Paşca, and Aitor Soroa. A study on similarity and relatedness using distributional and WordNet-based approaches. In *Proceedings of Human Language Technologies: The 2009 Annual Conference of the North American Chapter of the Association for Computational Linguistics*, pp. 19–27, Boulder, Colorado, June 2009. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/N09-1003`.

Wasi Uddin Ahmad, Zhisong Zhang, Xuezhe Ma, Eduard H. Hovy, Kai-Wei Chang, and Nanyun Peng. On difficulties of cross-lingual transfer with order differences: A case study on dependency parsing. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 2440–2452, 2019.

Mikel Artetxe, Gorka Labaka, and Eneko Agirre. Learning principled bilingual mappings of word embeddings while preserving monolingual invariance. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 2289–2294, Austin, Texas, November 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1250. URL `https://www.aclweb.org/anthology/D16-1250`.

Mikel Artetxe, Gorka Labaka, and Eneko Agirre. A robust self-learning method for fully unsupervised cross-lingual mappings of word embeddings. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 789–798, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1073. `https://github.com/artetxem/vecmap`.

Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135–146, 2017. doi: 10.1162/tacl_a_00051. URL `https://www.aclweb.org/anthology/Q17-1010`.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

Elia Bruni, Gemma Boleda, Marco Baroni, and Nam-Khanh Tran. Distributional semantics in technicolor. In *Proceedings of the 50th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 136–145, 2012.

Kai Cao, Xiangqi Bai, Yiguang Hong, and Lin Wan. Unsupervised topological alignment for single-cell multi-omics integration. *bioRxiv*, 2020. doi: 10.1101/2020.02.02.931394. URL `https://www.biorxiv.org/content/early/2020/02/03/2020.02.02.931394`.

Jacques Antonin Chatelon, Donald W Hearn, and Timothy J Lowe. A subgradient algorithm for certain minimax and minisum problems. *Mathematical Programming*, 15(1):130–145, 1978.

Qian Chen, Xiaodan Zhu, Zhen-Hua Ling, Si Wei, Hui Jiang, and Diana Inkpen. Enhanced LSTM for natural language inference. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1657–1668, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1152. URL `https://www.aclweb.org/anthology/P17-1152`.

Song Chen, Blue B Lake, and Kun Zhang. High-throughput sequencing of the transcriptome and chromatin accessibility in the same cell. *Nature Biotechnology*, 37(12):1452–1457, 2019.

Lih Feng Cheow, Elise T Courtois, Yuliana Tan, Ramya Viswanathan, Qiaorui Xing, Rui Zhen Tan, Daniel S W Tan, Paul Robson, Yuin-Han Loh, Stephen R Quake, and William F Burkholder. Single-cell multimodal profiling reveals cellular epigenetic heterogeneity. *Nature Methods*, 13 (10):833–836, 2016.

Alexis Conneau, Guillaume Lample, Marc'Aurelio Ranzato, Ludovic Denoyer, and Hervé Jégou. Word translation without parallel data, 2018a.

Alexis Conneau, Ruty Rinott, Guillaume Lample, Adina Williams, Samuel Bowman, Holger Schwenk, and Veselin Stoyanov. XNLI: Evaluating cross-lingual sentence representations. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2475–2485, Brussels, Belgium, October-November 2018b. Association for Computational Linguistics. doi: 10.18653/v1/D18-1269. URL https://www.aclweb.org/anthology/D18-1269.

Pinar Demetci, Rebecca Santorella, Bjorn Sandstede, William Stafford Noble, and Ritambhara Singh. Gromov-wasserstein optimal transport to align single-cell multi-omics data. *bioRxiv*, 2020.

Sunipa Dev, Safia Hassan, and Jeff M Phillips. Absolute orientation for word embedding alignment. *Knowledge and Information Systems*, 2021.

Haim Dubossarsky, Ivan Vulić, Roi Reichart, and Anna Korhonen. The secret is in the spectra: Predicting cross-lingual task performance with spectral similarity measures. In *EMNLP*, 2020.

James W Eyster, John A White, and Walter W Wierwille. On solving multifacility location problems using a hyperboloid approximation procedure. *AIIE Transactions*, 5(1):01–06, 1973.

Manaal Faruqui and Chris Dyer. Improving vector space word representations using multilingual correlation. In *Proceedings of the 14th Conference of the European Chapter of the Association for Computational Linguistics*, pp. 462–471, Gothenburg, Sweden, April 2014. Association for Computational Linguistics. doi: 10.3115/v1/E14-1049. URL https://www.aclweb.org/anthology/E14-1049.

Lev Finkelstein, Evgeniy Gabrilovich, Yossi Matias, Ehud Rivlin, Zach Solan, Gadi Wolfman, and Eytan Ruppin. Placing search in context: The concept revisited. In *Proceedings of the 10th international conference on World Wide Web*, pp. 406–414, 2001.

Andrea Frome, Greg Corrado, Jonathon Shlens, Samy Bengio, Jeffrey Dean, Marc'Aurelio Ranzato, and Tomas Mikolov. Devise: A deep visual-semantic embedding model. 2013.

Goran Glavaš, Robert Litschko, Sebastian Ruder, and Ivan Vulić. How to (properly) evaluate cross-lingual word embeddings: On strong baselines, comparative analyses, and some misconceptions. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 710–721, 2019. https://github.com/codogogo/xling-eval?utm_source=catalyzex.com.

Stephan Gouws, Yoshua Bengio, and Greg Corrado. Bilbowa: Fast bilingual distributed representations without word alignments. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 748–756, Lille, France, 07–09 Jul 2015. PMLR. URL http://proceedings.mlr.press/v37/gouws15.html.

Edouard Grave, Armand Joulin, and Quentin Berthet. Unsupervised alignment of embeddings with wasserstein procrustes. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1880–1890, 2019.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 855–864, 2016.

Jiang Guo, Wanxiang Che, David Yarowsky, Haifeng Wang, and Ting Liu. Cross-lingual dependency parsing based on distributed representations. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 1234–1244, Beijing, China, July 2015. Association for Computational Linguistics. doi: 10.3115/v1/P15-1119. URL https://www.aclweb.org/anthology/P15-1119.

Guy Halawi, Gideon Dror, Evgeniy Gabrilovich, and Yehuda Koren. Large-scale learning of word relatedness with constraints. In *Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 1406–1414, 2012.

Mareike Hartmann, Yova Kementchedjhieva, and Anders Sø gaard. Comparing unsupervised word translation methods step by step. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/d15426b9c324676610fbb01360473ed8-Paper.pdf.

Karl Moritz Hermann and Phil Blunsom. Multilingual models for compositional distributed semantics. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 58–68, Baltimore, Maryland, June 2014. Association for Computational Linguistics. doi: 10.3115/v1/P14-1006. URL https://www.aclweb.org/anthology/P14-1006.

Geert Heyman, Ivan Vulić, and Marie-Francine Moens. Bilingual lexicon induction by learning to combine word-level and character-level representations. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pp. 1085–1095, Valencia, Spain, April 2017. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/E17-1102.

Porter Jenkins, Ahmad Farag, Suhang Wang, and Zhenhui Li. Unsupervised representation learning of spatial data via multimodal embedding. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, pp. 1993–2002, 2019.

Armand Joulin, Piotr Bojanowski, Tomas Mikolov, Hervé Jégou, and Edouard Grave. Loss in translation: Learning bilingual word mapping with a retrieval criterion. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2979–2984, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1330. https://github.com/facebookresearch/fastText/tree/master/alignment.

Mladen Karan, Ivan Vulić, Anna Korhonen, and Goran Glavaš. Classification-based self-learning for weakly supervised bilingual lexicon induction. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 6915–6922, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.618. URL https://www.aclweb.org/anthology/2020.acl-main.618.

Douwe Kiela and Léon Bottou. Learning image embeddings using convolutional neural networks for improved multi-modal semantics. In *Proceedings of the 2014 Conference on empirical methods in natural language processing (EMNLP)*, pp. 36–45, 2014.

Alexandre Klementiev, Ivan Titov, and Binod Bhattarai. Inducing crosslingual distributed representations of words. In *Proceedings of COLING 2012*, pp. 1459–1474, Mumbai, India, December 2012. The COLING 2012 Organizing Committee. URL https://www.aclweb.org/anthology/C12-1089.

Guillaume Lample, Myle Ott, Alexis Conneau, Ludovic Denoyer, and Marc'Aurelio Ranzato. Phrase-based & neural unsupervised machine translation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 5039–5049, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1549. URL https://www.aclweb.org/anthology/D18-1549.

Jie Liu, Yuanhao Huang, Ritambhara Singh, Jean-Philippe Vert, and William Stafford Noble. Jointly embedding multiple single-cell omics measurements. *bioRxiv*, 2019. doi: 10.1101/644310. URL https://www.biorxiv.org/content/early/2019/05/20/644310.

Robert F. Love, James G. Morris, and George O. Wesolowsky. *FACILITIES LOCATION: MODELS AND METHODS*. 1988.

Minh-Thang Luong, Richard Socher, and Christopher D Manning. Better word representations with recursive neural networks for morphology. In *Proceedings of the seventeenth conference on computational natural language learning*, pp. 104–113, 2013.

EA Maxwell. 100 great problems of elementary mathematics: their history and solution. By Heinrich Dorme, translated by David. Ustin Pp. x, 393. $2.00. 1965.(Dover). *The Mathematical Gazette*, 50(372):213–213, 1966.

Tomas Mikolov, Kai Chen, Greg S. Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. In *ICLR (Workshop Poster)*, 2013a.

Tomas Mikolov, Quoc V. Le, and Ilya Sutskever. Exploiting similarities among languages for machine translation. *arXiv preprint arXiv:1309.4168*, 2013b.

Tomáš Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In *Proceedings of the 2013 conference of the north american chapter of the association for computational linguistics: Human language technologies*, pp. 746–751, 2013.

George A Miller and Walter G Charles. Contextual correlates of semantic similarity. *Language and cognitive processes*, 6(1):1–28, 1991.

Jiaqi Mu and Pramod Viswanath. All-but-the-top: Simple and effective postprocessing for word representations. In *6th International Conference on Learning Representations, ICLR 2018*, 2018.

Ndapa Nakashole and Raphael Flauger. Characterizing departures from linearity in word translation. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, volume 2, pp. 221–227, 2018.

Aitor Ormazabal, Mikel Artetxe, Aitor Soroa, Gorka Labaka, and Eneko Agirre. Beyond offline mapping: Learning cross-lingual word embeddings through context anchoring. In *ACL 2021: 59th annual meeting of the Association for Computational Linguistics*, pp. 6479–6489, 2021.

Michael L Overton. A quadratically convergent method for minimizing a sum of euclidean norms. *Mathematical Programming*, 27(1):34–63, 1983.

Barun Patra, Joel Ruben Antony Moniz, Sarthak Garg, Matthew R Gormley, and Graham Neubig. Bliss in non-isometric embedding spaces. 2018.

Jeffrey Pennington, Richard Socher, and Christopher Manning. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1532–1543, Doha, Qatar, October 2014. Association for Computational Linguistics. doi: 10.3115/v1/D14-1162. URL https://www.aclweb.org/anthology/D14-1162.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 701–710, 2014.

Kira Radinsky, Eugene Agichtein, Evgeniy Gabrilovich, and Shaul Markovitch. A word at a time: computing word relatedness using temporal semantic analysis. In *Proceedings of the 20th international conference on World wide web*, pp. 337–346, 2011.

Herbert Rubenstein and John B Goodenough. Contextual correlates of synonymy. *Communications of the ACM*, 8(10):627–633, 1965.

Sebastian Ruder, Ryan Cotterell, Yova Kementchedjhieva, and Anders Søgaard. A discriminative latent-variable model for bilingual lexicon induction. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 458–468, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1042. https://github.com/sebastianruder/latent-variable-vecmap.

Sebastian Ruder, Ivan Vulić, and Anders Søgaard. A survey of cross-lingual word embedding models. *Journal of Artificial Intelligence Research*, 65:569–631, 2019.

Vin Sachidananda, Ziyi Yang, and Chenguang Zhu. Filtered inner product projection for multilingual embedding alignment. In *ICLR 2021: The Ninth International Conference on Learning Representations*, 2021.

Samuel L. Smith, David H. P. Turban, Steven Hamblin, and Nils Y. Hammerla. Offline bilingual word vectors, orthogonal transformations and the inverted softmax. In *ICLR (Poster)*, 2017.

Anders Søgaard, Sebastian Ruder, and Ivan Vulić. On the limitations of unsupervised bilingual dictionary induction. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 778–788, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1072. URL https://aclanthology.org/P18-1072.

Ivan Vulic and Marie-Francine Moens. Monolingual and cross-lingual information retrieval models based on (bilingual) word embeddings. *Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2015.

Ivan Vulić, Goran Glavaš, Roi Reichart, and Anna Korhonen. Do we really need fully unsupervised cross-lingual embeddings? In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4406–4417, 2019.

Yuwei Wang, Yan Zheng, Yanqing Peng, Michael Yeh, Zhongfang Zhuang, Das Mahashweta, Bendre Mangesh, Feifei Li, Wei Zhang, and Jeff M. Phillips. Constrained non-affine alignment of embeddings. In *Proceedings of the International Conference on Data Mining (ICDM)*, 2021.

Zirui Wang, Jiateng Xie, Ruochen Xu, Yiming Yang, Graham Neubig, and Jaime G. Carbonell. Cross-lingual alignment vs joint training: A comparative study and A simple unified framework. *CoRR*, abs/1910.04708, 2019. URL http://arxiv.org/abs/1910.04708.

Adina Williams, Nikita Nangia, and Samuel Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1112–1122, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1101. URL https://www.aclweb.org/anthology/N18-1101.

Chao Xing, Dong Wang, Chao Liu, and Yiye Lin. Normalized word embedding and orthogonal transform for bilingual word translation. In *Proceedings of the 2015 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 1006–1011, Denver, Colorado, May–June 2015. Association for Computational Linguistics. doi: 10.3115/v1/N15-1104. URL https://www.aclweb.org/anthology/N15-1104.

Haoran Xu and Philipp Koehn. Cross-lingual bert contextual embedding space mapping with isotropic and isometric conditions. *arXiv preprint arXiv:2107.09186*, 2021.

Dongqiang Yang and David Martin Powers. *Verb similarity on the taxonomy of WordNet*. Masaryk University, 2006.

Mozhi Zhang, Keyulu Xu, Ken-ichi Kawarabayashi, Stefanie Jegelka, and Jordan Boyd-Graber. Are girls neko or shōjo? cross-lingual alignment of non-isomorphic embeddings with iterative normalization. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3180–3189, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1307. URL https://www.aclweb.org/anthology/P19-1307. https://github.com/zhangmozhi/iternorm?utm_source=catalyzex.com.

APPENDIX

A   GEOMETRIC MEDIAN NORMALIZATION

Iterative Normalization converges towards individual word embeddings having a unit length and each monolingual embedding having a zero mean. Zhang et al. (2019) showed that iterating solutions for these distinct goals will eventually converge to a solution which satisfies both.

In this paper, we observe that both goals can be done in one shot without iterating – by solving the Fermat-Weber problem (Maxwell, 1966; Love et al., 1988). This dates to the 17th century, and corresponds with identifying the geometric median of a point set. Formally, the goal is a point $x^* \in \mathbb{R}^d$ that minimizes the sum of distances from n anchor points $\{a_1, \ldots, a_n\} \subset \mathbb{R}^d$ which are not colinear: $x^* = \min_x \sum_{i=1}^n \|x - a_i\|$. Several methods (Chatelon et al., 1978; Eyster et al., 1973; Overton, 1983) have been proposed; the most popular is the Weiszfeld's algorithm (Weiszfeld, see below for details). It is folklore that the solution x^* satisfies that $0 = \sum_{i=1}^n \frac{a_i - x^*}{\|a_i - x^*\|}$; we do not know of a written proof, so we prove this for completeness.

Theorem A.1. *If $\mathbf{x} \in \mathbb{R}^d$ is distinct from all the given anchor points, $\mathbf{a}_i$, then $\mathbf{x}$ is the geometric median is true if and only if ($\Longleftrightarrow$)*

$$\mathbf{0} = \sum_{i=1}^n \frac{\mathbf{a}_i - \mathbf{x}}{\|\mathbf{a}_i - \mathbf{x}\|} \tag{1}$$

Proof. ($\Rightarrow$) Suppose $\mathbf{x} \in \mathbb{R}^d$ is distinct from all the given anchor points, $\mathbf{a}_i$ and $\mathbf{x}$ is the geometric median such that $\mathbf{x} = \widetilde{T}(\mathbf{x})$ then

$$\nabla f(\mathbf{x}) = \sum_{i=1}^n \frac{\mathbf{a}_i - \mathbf{x}}{\|\mathbf{a}_i - \mathbf{x}\|} = 0.$$

($\Leftarrow$) Suppose $\mathbf{x} \in \mathbb{R}^d$ is distinct from all the given anchor points, $\mathbf{a}_i$ and $\mathbf{x}$ is the unique optimal solution of equation A such that $\nabla f(\mathbf{x}) = 0$ then solving for $\mathbf{x}$ while ignoring the dependency $\mathbf{x}$ in $\|\mathbf{a}_i - \mathbf{x}\|$ yields:

$$\mathbf{x} = \frac{\sum\limits_{i=1}^n \|\mathbf{a}_i - \mathbf{x}\|^{-1} \mathbf{a}_i}{\sum\limits_{i=1}^n \|\mathbf{a}_i - \mathbf{x}\|^{-1}}$$

which is the geometric median. $\qquad\square$

Using this characteristic of the geometric median, we can simultaneously enforce monolingual word embeddings to have unit-length and zero-mean in just one step. This can be done using the Geometric Median normalization (GeoMediaN) algorithm (as Algorithm 3). Given a monolingual word embedding A, we compute the geometric median x^*, and "center" the data on this point, and unit length normalizes the centered embedding.

Algorithm 3 Geometric Median Normalization: GeoMediaN(A)

1: $x^* \leftarrow$ Weiszfeld(A)
2: **for all** $a_i \in A$ **do** $a_i \leftarrow \frac{a_i - x^*}{\|a_i - x^*\|}$
3: **return** A

After these steps, all vectors are unit length, and because of the folklore property (Theorem A.1), the mean of those points is also 0. As a result, we can state the following property.

Theorem A.2. *The output of GeoMediaN(A) is centered and length normalized.*

Despite the Geometric Median Normalization algorithm's ability to enforce unit-length and zero-mean in just one step, we observe that it does not perform especially well on the BLI task. Both GeoMediaN and I-C+L achieve one of many solutions which achieve these joint goals.

A.1 WEISZFELD ALGORITHM

The Weiszfeld algorithm is an iterative method for finding the geometric median of a set of points in Euclidean space based on the reformulation of a stationary point that satisfies $\nabla f(\mathbf{x}) = 0$.

If iteration function $T : \mathbb{R}^d \to \mathbb{R}^d$ is defined by:

$$T(\mathbf{x}) = \begin{cases} \widetilde{T}(\mathbf{x}) = \dfrac{\sum\limits_{i=1}^{n} \|\mathbf{a}_i - \mathbf{x}\|^{-1} \mathbf{a}_i}{\sum\limits_{i=1}^{n} \|\mathbf{a}_i - \mathbf{x}\|^{-1}} & \text{if } \mathbf{x} \notin \{\mathbf{a}_1, \dots \mathbf{a}_n\} \\ \\ \mathbf{a}_i & \text{if } \mathbf{x} = \mathbf{a}_i \ , i = 1, \dots, n \end{cases} \tag{2}$$

then the Weiszfeld algorithm is:

$$\mathbf{x}_{k+1} = T(\mathbf{x}_k), \ k \in \mathbb{N} \tag{3}$$

where $\mathbf{x}_0 \in \mathbb{R}^d$ is a starting point. When the current iterate, $\mathbf{x}_k \notin \{\mathbf{a}_1, \dots \mathbf{a}_n\}$, $T(\mathbf{x}_k) = \widetilde{T}(\mathbf{x}_k)$; else, if $\mathbf{x}_k = \mathbf{a}_i$, then $T(\mathbf{x}_k) = \mathbf{a}_i$.

The Weiszfeld algorithm is presented in Algorithm 4 below:

Algorithm 4 Weiszfeld algorithm (WA)

Input: Anchor points, $(\mathbf{a}_1, \dots \mathbf{a}_n)$, $\mathbf{x}_0 \in \mathbb{R}^d$ and $\epsilon > 0$
1: $k \leftarrow 0$
2: **while** True **do**
3:     $\mathbf{x}_{k+1} \leftarrow T(\mathbf{x}_k)$
4:     **if** $\|\mathbf{x}_{k+1} - \mathbf{x}_k\|_2 < \epsilon$ **then**
5:        **return** $\mathbf{x}_{k+1}$
6:     $k \leftarrow k + 1$

B SPECTRAL STATISTICS AND SPECTRAL ISOMORPHISM MEASURES

We also explored other spectral statistics on monolingual embeddnigs. The *numeric rank* of A is a smoother analog to rank (where there is noise in low rank components), defined $\eta(A) = \|A\|_F^2 / \|A\|_2^2$. The *condition number* of A is $\kappa(A) = \sigma_1/\sigma_d$, and measures how close the matrix is to being truly full rank, smaller is more stable. For two matrices A_1 and A_2, the *condition number harmonic mean* is COND-HM$(A_1, A_2) = \frac{2\kappa(A_1)\kappa(A_2)}{\kappa(A_1)+\kappa(A_2)}$. Smaller means the matrices are more comparable. Figure 2 plots these measures, and again demonstrates that I-C+SN+L improves these measures on matrices.

Figure 2: Spectral Measures of four (4) monolingual word embeddings.

We also show the raw numbers used to generate the charts in Figure 1 in the tables below.

Table 8: Effective Rank

	Normalization Algorithms					
Languages	None	PR	GeoMediaN	C+L	I-C+L	I-C+SN+L
EN	268	277	278	279	279	283
DE	264	273	273	274	274	278
HI	258	270	269	269	269	282
JA	39	96	171	253	255	276

Table 9: Effective Condition Number

	Normalization Algorithms					
Langauges	None	PR	GeoMediaN	C+L	I-C+L	I-C+SN+L
EN	13.1	6.7	5.4	5.3	5.3	3.3
DE	14.8	5.9	6.2	6.1	6.1	3.7
HI	16.1	9.4	9.1	8.9	8.9	3.2
JA	175.0	113.3	73.1	16.4	15.0	3.4

Table 10: Effective Condition Number Harmonic Mean

	Normalization Algorithms					
Langauges Pairs	None	PR	GeoMediaN	C+L	I-C+L	I-C+SN+L
EN-DE	13.9	6.3	5.8	5.7	5.7	3.5
EN-HI	14.4	7.8	6.8	6.6	6.6	3.2
EN-JA	24.4	12.7	10.0	8.0	7.8	3.3

Table 11: Singular Value Gap

	Normalization Algorithms					
Langauges Pairs	None	PR	GeoMediaN	C+L	I-C+L	I-C+SN+L
EN-DE	2.3	2.4	2.2	2.2	2.2	2.2
EN-HI	49.0	48.6	12.2	12.2	12.2	5.2
EN-JA	44.1	45.8	404.0	17.7	14.8	2.2

C   Word Similarity Task

The word similiarity task was conducted using the following English word similarity benchmarks: WS-3533 (Finkelstein et al., 2001), WS-SIM and WSREL (Agirre et al., 2009), RG-65 (Rubenstein & Goodenough, 1965), MC-30 (Miller & Charles, 1991), MTurk-2875 (Radinsky et al., 2011), MTurk-771 (Halawi et al., 2012), MEN7 (Bruni et al., 2012), YP-130 (Yang & Powers, 2006), Rare Words (Luong et al., 2013).

In addition to a baseline (None, which means no normalization), Tabel 12 shows results comparing against our proposed normalization (I-C+SN+L) and the state of the art (I-C+L). Note that both of these improves the accuracy of the similarity tests. This indicates that they are not distorting the critical information contained in the original embeddings. And our proposed approach (I-C+SN+L) increases the score the most.

In contrast, we show the results of two other spectral adjustments we considered. SSV (SSV means Same Singular Values), performs the SVD on the original embedding and then sets all the singular values to $\eta = \sqrt{\|A\|_F^2/d}$. Then we compute U@S@VT to get the new word embedding. So similar to SpecNorm, but it never reaches the else condition. This slightly decreases the scores on the similarity tests. This is a result of accentuating the noise directions. In the other direction, SSVZ (SSVZ means Set Singular Values to Zero) only keeps the top 40 singular values and then sets the rest to zero. Then we compute U@S@VT to get the new word embedding. This drastically reduces the similarity score. This shows those noise directions, which tend to be well below the average singular value, are still important and cannot just be removed.

Table 12: Monolingual Word Similarity Score (Spearman rank coefficient)

Dataset	Normalization Algorithms				
	None	SSV	SSVZ	I-C+L	I-C+SN+L
EN_WS-353-ALL	0.7388	0.7127	0.5395	0.7433	0.7555
EN_VERB-143	0.3973	0.4283	0.2635	0.4231	0.4346
EN_YP-130	0.5333	0.5534	0.3904	0.5514	0.5631
EN_MTurk-771	0.6689	0.6583	0.5540	0.6838	0.6926
EN_RG-65	0.7974	0.7640	0.6390	0.8082	0.8087
EN_RW-STANFORD	0.5080	0.5569	0.3873	0.5125	0.5258
EN_SEMEVAL17	0.7216	0.7478	0.5779	0.7288	0.7366
EN_MEN-TR-3k	0.7637	0.7506	0.6581	0.7720	0.7792
EN_WS-353-SIM	0.7811	0.7678	0.6162	0.7897	0.7888
EN_MTurk-287	0.6773	0.6439	0.6016	0.6864	0.6864
EN_WS-353-REL	0.6820	0.6363	0.4824	0.6905	0.7081
EN_MC-30	0.8123	0.8203	0.6754	0.8352	0.8494
EN_SIMLEX-999	0.3823	0.4069	0.2276	0.3899	0.3955
Avg	0.6511	0.6498	0.5087	0.6627	**0.6711**

D   Summary of Model Performance

Table 13: Summary of Model Performance on I-C+SN+L (denoted SN)

Dict	CCA^{SN}	PROC^{SN}	PROC–B^{SN}	DLV^{SN}	RCSLS^{SN}	VECMAP^{SN}
			Models			
1K	28/28	28/28	25/28	28/28	13/28	
3K	28/28	28/28	25/28	28/28	25/28	
5K	28/28	28/28		28/28	28/28	
–						27/28

Table 13 summarizes the performance of I-C+SN+L on several supervised and unsupervised projection-based CLWE models across all the 28 language pairs as presented in J . After preprocessing the monolingual word embeddings with I-C+SN+L, CCA^{SN}, PROC^{SN} and DLV^{SN} outperformed CCA, PROC and DLV respectively on 28 of 28 language pairs across all the translation dictionaries. PROC-B^{SN} outperformed PROC-B on 25 of 28 language pairs across 1k and 3k translation dictionaries. The performance of RCSLS^{SN} supersede RCSLS on 25 of 28 language pairs and 28 of 28 language pairs trained on 3k and 5k translation dictionaries respectively. The unsupervised projection-based CLWE model, VECMAP^{SN} outperformed VECMAP on 27 of 28 language pairs. The lowest performing model was RCSLS^{SN} trained on 1k translation dictionary.

E   P@1 PERFORMANCE FOR MAPPING BASED CLWE METHODS VS JOINT TRAINING

Joint training methods.   The CLWE methods proposed by Wang et al. (2019) and Ormazabal et al. (2021) learn a new embedding from scratch including words from both languages. They does so with a different objective function than standard approaches so that it prevents words entirely clustering by language, and so cross-lingual synonyms are encouraged to be embedded close to each other. Wang et al. (2019) accomplished this by encouraging alignment of representations of words. This was enhanced by Ormazabal et al. (2021) via a mechanism (Cross-lingual Anchoring) that extended the skip-gram to have bilingual target embeddings. Ultimately, these can learn a cross-lingual embedding that preserves synonyms, and is optimized over the entire source language data.

Results.   Both Ormazabal et al. (2021) and Wang et al. (2019) reported P@1 (precision of the 1st nearest neighbor) BLI results for their method – as opposed to the more robust MAP evaluation we use in the remainder of the paper. So we report the BLI performance on the MUSE dataset on 4 languages before and after I-C+SN+L for a variety of alignment techniques in Table 14. We include their published numbers directly for comparison. We also include reported numbers from various other papers, denoted with ∗. The work of Ormazabal et al. (2021) slightly outperforms I-C+SN+L (with RCSLS (Joulin et al., 2018)) on EN-DE, EN-ES, and EN-FR, but under-performs on EN-RU and as a result has a lower overall average.

The result of Ormazabal et al. (2021) are certainly intriguing, and we hope to be able to compare on a broader set of languages and using the MAP evaluation in future work. We remark however, that such approaches are less flexible than using a post-processing alignment as they require re-training, so it is less clear how to apply for multiple languages, would need to be re-trained for other languages pairs (e.g., DE-FR), and how it will work for lower resource languages were less training data is available.

After applying our proposed I-C+SN+L normalization, ADV (Conneau et al., 2018b) failed to align EN-DE, EN-ES, EN-RU. This method uses a Generative Adversarial Network (GAN), and this phenomenon is explained by Hartmann et al. (2019). In their work they showed that unit length normalization makes GAN based CLWE method unstable and deteriorates their performance but other supervised alignments are not affected by it. This explains why the performance on PROC (Conneau

et al., 2018a), RCSLS (Joulin et al., 2018) and Wasserstein Procrustes (WP) (Grave et al., 2019) are not affected by I-C+SN+L, and in fact it leads to an improvement in the BLI performance.

Table 14: BLI performance (P@1) on 4 languages from MUSE. ∗ are scores reported from published papers; others are ones we computed.

Model	Normalization	EN-DE	EN-ES	EN-FR	EN-RU	Avg
Embed then Align Methods						
PROC (Conneau et al., 2018a)∗	None	73.5	81.4	81.1	51.7	71.9
PROC (Conneau et al., 2018a)	I-C+SN+L	75.7	82.7	83.2	51.8	73.3
RCSLS (Joulin et al., 2018)	None	43.6	50.5	53.1	26.6	43.4
RCSLS (Joulin et al., 2018)	I-C+SN+L	77.9	83.7	83.7	**57.8**	**75.7**
ADV (Conneau et al., 2018a)∗	None	74.0	81.7	82.3	44.0	70.5
ADV (Conneau et al., 2018a)	I-C+SN+L	0.00	0.00	82.9	0.07	20.7
WP (Grave et al., 2019)∗	None	75.6	82.8	82.3	45.2	71.5
WP (Grave et al., 2019)	I-C+SN+L	77.4	82.9	83.6	47.8	72.9
Joint Training Methods						
(Wang et al., 2019)∗	None	74.2	81.4	82.8	45.0	70.9
(Ormazabal et al., 2021)∗	None	**78.1**	**84.2**	**84.9**	51.5	74.7

F ALIGNMENT OF SINGLE-CELL MULTI-OMICS DATA

Single-cell measurements allows scientist to study the various properties of the genome such as gene expression, chromatin accessibility, DNA methylation etc. Therefore there is the need for data integration of these single-cell measurements so that scientist can understand cell development over time and disease. However, due to the lack of cell-to-cell correspondence between the different types of measurements it make the process of data integration a challenging task. Motivated by this, (Demetci et al., 2020) proposed an Single-Cell alignment using Optimal Transport (SCOT), an unsupervised learning algorithm that uses Gromov Wasserstein-based optimal transport to recover the cell-to-cell correspondence between two sequencing domains. * represents results taken directly from (Demetci et al., 2020). MMD-MA (Liu et al., 2019) and UnionCom (Cao et al., 2020) are two other unsupervised single-cell alignment methods.

Table 15: Alignment Performance (FOSCTTM) on Single-cell Sequencing Dataset

		scGEM	SNAREseq
Alignment methods	Normalization	FOSCTTM	FOSCTTM
Before Normalization			
MMD-MA ∗	None	0.2014	**0.15**
UnionCom ∗	None	0.296	0.265
SCOT ∗	None	0.198	**0.15**
After Normalization			
SCOT	I-C+L	0.201	0.395
SCOT	I-C+SN+L	**0.184**	**0.15**

We follow the implementation details from (Demetci et al., 2020). * represents results taken directly from (Demetci et al., 2020). We used two single-cell multi-omics datasets: 1) scGEM assay (Cheow et al., 2016) and 2) SNAREseq assay (Chen et al., 2019). The fraction of samples closer than the true match, (FOSCTTM) was used to evaluate the alignment performance. A

low average FOSCTTM scores indicates the ability of SCOT to recover the correct correspondences.

Table 15 summaries the before and after I-C+L and I-C+SN+L SCOT performance based on FOS-CTTM. On the SNAREseq dataset SCOT with I-C+SN+L outperformed SCOT with I-C+L but achieved the same performance as SCOT with no normalization. However, proprcessing the scGEM dataseT with I-C+SN+L before alignment achieved the highest FOSCTTM score of 0.184 followed by SCOT with no normalization.

G   CODE FOR SPECNORM

The code implementing our new algorithm Spectral Normalization is quite simple, as such we just present it below. We will provide public links to the code online after double blind review.

Spectral Normalization (SpecNorm) is below, referred to as **SVDConX.py**. Similarly, the code implementation of Iterative Spectral Normalization (I-C+SN+L) referred to as **Iter_SVDConX.py** is also shown below.

Spectral Normalization (SVDConX.py)

```python
import numpy as np

def computeSVD(embeds):
    """
    Args:
        embeds: Monolingual Embedding

    Returns:
        Singular Value Decompostion
    """
    U, S, VT = np.linalg.svd(embeds,full_matrices=False)
    return U, S, VT

def SVDConX(embeds, beta):
    """
    Args:
        emdeds: Monolingual Embedding
        beta: Use to determine smaller (noisy)
        singular values to be removed

    Returns:
        Spectral Normalised Embedding
    """
    # Perform SVD on the Monolingual Embedding
    _, S, VT = computeSVD(embeds)
    # Compute eta
    eta = np.sqrt(np.sum(S**2)/len(S))
    # Transform  diagonal matrix
    S_prime = 1 / S
    for idx, sigma in enumerate(S):
        if sigma > beta*eta:
            S_prime[idx] = S_prime[idx] * (beta*eta)
        else:
            S_prime[idx] = 1
    S_prime = np.eye(len(S)) * S_prime
    # Compute new monolingual embedding
    embeds = embeds @ VT.T @ S_prime
    return embeds
```

Iterative Spectral Normalization (Iter_SVDConX.py)

```python
import numpy as np
from SVDConX import SVDConX
from argparse import ArgumentParser

def load_embed(filename, max_vocab=-1):
    words, embeds = [], []
    with open(filename, 'r') as f:
        next(f)
        for line in f:
            word, vector = line.rstrip().split(' ', 1)
            vector = np.fromstring(vector, sep=' ')
            words.append(word)
            embeds.append(vector)
            if len(embeds) == max_vocab:
                break
    return words, np.array(embeds)

def saveEmbed(path, words, word_embeds):
    with open(path, 'w') as f:
        print(word_embeds.shape[0], word_embeds.shape[1], file=f)
        for word, embed in zip(words, word_embeds):
            vector_str = ' '.join(str(x) for x in embed)
            print(word, vector_str, file = f)

def main():
    parser = ArgumentParser()
    parser.add_argument('--input_file')
    parser.add_argument('--output_file')
    parser.add_argument('--niter', default=5, type=int)
    parser.add_argument('--max_vocab', default=200000, type=int)
    parser.add_argument('--beta', default=2, type=int)
    args = parser.parse_args()

    words, embeds = load_embed(args.input_file, max_vocab=args.max_vocab)
    embeds /= np.linalg.norm(embeds, axis=1)[:, np.newaxis] + 1e-8

    for i in range(args.niter):
        # Center Monoligual Embedding
        embeds -= embeds.mean(axis=0)[np.newaxis, :]
        # Perform Spectral Normalization
        embeds =  SVDConX(embeds, args.beta)
        # Unit Length Normalization
        embeds /= np.linalg.norm(embeds, axis=1)[:, np.newaxis] + 1e-8
    saveEmbed(args.output_file, words, embeds)

if __name__ == '__main__':
    main()
```

H RUNTIME

Most of the alignment algorithms run on a CPU except for VecMap, which requires a GPU for faster computation. It takes about 91 seconds to run Iterative Spectral Normalization on a CPU with a $\beta = 2$ and five iterations. Hardware specifications are NVIDIA GeForce GTX Titan Xp 12GB, AMD Ryzen 7 1700 eight-core processor, and 62.8GB RAM. All alignment approaches completed in under 15 minutes, and most less than 5 minutes. Each evaluation (BLI, CLDC, or XNLI) takes under 2 minutes, but the training step for CLDC and XNLI takes about a day each; hence our approach aims only to need to do this once (on a high resource language like English), and then use the faster alignment step to transfer this to other languages.

Table 16: BLI performance (MAP) on aligning $\mathbf{EN}-\mathbf{X}_{L_2}$. We compare all the normalization techniques: None (No normalization), PR (PCA Removal) (Mu & Viswanath, 2018), GeoMediaN (Geometric Median Normalization), C+L (Mean centering and Length normalization, 1 round), I-C+L (Iterative Mean centering and Length normalization, 5 rounds) (Zhang et al., 2019), SN (Spectral Normalization, 1 round), C+SN+L (Mean centering, Spectral Normalization and Length normalization, 1 round), I-C+SN+L (Iterative Mean centering, Spectral Normalization and Length normalization, 5 rounds).

Method	Normalization	BG	CA	CS	DE	ES	FR	KO	TH	ZH	Avg
CCA	None	0.298	0.556	0.364	0.358	0.514	0.485	0.242	0.209	0.198	0.358
	PR	0.316	0.583	0.389	0.374	0.523	0.492	0.283	0.224	0.362	0.394
	GeoMediaN	0.316	0.580	0.383	0.376	0.524	0.492	0.277	0.226	0.362	0.393
	C+L	0.326	0.582	0.387	0.375	0.521	0.491	0.267	0.227	0.359	0.393
	I-C+L	0.326	0.582	0.387	0.375	0.521	0.492	0.267	0.226	0.371	0.394
	SN	0.314	0.580	0.384	0.370	0.519	0.494	0.259	0.223	0.378	0.391
	C+SN+L	0.329	0.586	0.389	0.374	0.523	0.495	0.262	0.225	0.376	0.395
	I-C+SN+L	0.328	0.585	0.388	0.374	0.524	0.496	0.258	0.229	0.378	**0.396**
PROC	None	0.296	0.553	0.363	0.357	0.509	0.481	0.255	0.212	0.255	0.365
	PR	0.316	0.575	0.386	0.371	0.524	0.492	0.285	0.223	0.343	0.391
	GeoMediaN	0.317	0.578	0.384	0.376	0.521	0.491	0.281	0.225	0.346	0.391
	C+L	0.327	0.582	0.390	0.373	0.520	0.490	0.279	0.227	0.354	0.394
	I-C+L	0.327	0.582	0.390	0.372	0.520	0.490	0.280	0.228	0.366	0.395
	SN	0.319	0.580	0.384	0.369	0.520	0.493	0.277	0.227	0.378	0.394
	C+SN+L	0.331	0.586	0.380	0.374	0.524	0.495	0.273	0.227	0.378	0.396
	I-C+SN+L	0.330	0.586	0.389	0.375	0.525	0.495	0.287	0.224	0.374	**0.398**
PROC-B	None	0.326	0.587	0.400	0.382	0.528	0.497	0.236	0.218	0.221	0.377
	PR	0.340	0.605	0.425	0.395	0.536	0.505	0.259	0.227	0.341	0.404
	GeoMediaN	0.304	0.605	0.425	0.395	0.538	0.507	0.260	0.219	0.352	0.400
	C+L	0.354	0.607	0.423	0.396	0.536	0.507	0.257	0.223	0.366	0.408
	I-C+L	0.354	0.608	0.424	0.396	0.536	0.508	0.257	0.224	0.380	0.410
	SN	0.347	0.602	0.421	0.392	0.533	0.504	0.257	0.229	0.389	0.408
	C+SN+L	0.358	0.613	0.427	0.396	0.539	0.501	0.261	0.229	0.397	0.413
	I-C+SN+L	0.358	0.619	0.426	0.397	0.538	0.510	0.258	0.227	0.393	**0.414**
RCSLS	None	0.347	0.601	0.404	0.392	0.530	0.503	0.317	0.227	0.227	0.394
	PR	0.337	0.591	0.387	0.385	0.529	0.498	0.290	0.234	0.107	0.373
	GeoMediaN	0.337	0.592	0.391	0.384	0.530	0.499	0.284	0.231	0.167	0.379
	C+L	0.345	0.599	0.400	0.391	0.530	0.502	0.288	0.221	0.361	0.404
	I-C+L	0.346	0.598	0.400	0.391	0.530	0.502	0.288	0.221	0.382	0.406
	SN	0.341	0.597	0.395	0.394	0.533	0.504	0.282	0.217	0.385	0.405
	C+SN+L	0.348	0.601	0.403	0.393	0.533	0.506	0.285	0.215	0.377	**0.407**
	I-C+SN+L	0.348	0.601	0.401	0.392	0.533	0.506	0.280	0.214	0.376	0.406

Table 17: BLI performance (MAP) on aligning $\mathbf{X}_{L_1}-\mathbf{EN}$. We compare all the normalization techniques: None (No normalization), PR (PCA Removal) (Mu & Viswanath, 2018), GeoMediaN (Geometric Median Normalization), C+L (Mean centering and Length normalization, 1 round), I-C+L (Iterative Mean centering and Length normalization, 5 rounds) (Zhang et al., 2019), SN (Spectral Normalization, 1 round), C+SN+L (Mean centering, Spectral Normalization and Length normalization, 1 round), I-C+SN+L (Iterative Mean centering, Spectral Normalization and Length normalization, 5 rounds).

Method	Normalization	BG	CA	CS	DE	ES	FR	KO	TH	ZH	Avg
CCA	None	0.448	0.673	0.514	0.444	0.576	0.568	0.199	0.086	0.078	0.398
	PR	0.465	0.684	0.523	0.450	0.581	0.578	0.230	0.099	0.292	0.434
	GeoMediaN	0.467	0.688	0.523	0.449	0.582	0.583	0.231	0.098	0.279	0.433
	C+L	0.471	0.692	0.526	0.449	0.582	0.585	0.235	0.102	0.306	0.439
	I-C+L	0.471	0.692	0.526	0.449	0.582	0.585	0.234	0.102	0.313	0.439
	SN	0.467	0.689	0.527	0.455	0.587	0.581	0.230	0.114	0.310	0.440
	C+SN+L	0.472	0.693	0.527	0.458	0.586	0.590	0.238	0.115	0.319	0.444
	I-C+SN+L	0.473	0.692	0.526	0.459	0.586	0.590	0.236	0.115	0.324	**0.445**
PROC	None	0.450	0.669	0.510	0.440	0.573	0.569	0.203	0.081	0.096	0.399
	PR	0.465	0.679	0.519	0.447	0.578	0.579	0.235	0.099	0.273	0.430
	GeoMediaN	0.468	0.685	0.519	0.449	0.581	0.582	0.236	0.100	0.267	0.432
	C+L	0.475	0.688	0.523	0.451	0.582	0.583	0.240	0.101	0.293	0.437
	I-C+L	0.475	0.688	0.523	0.451	0.582	0.583	0.240	0.103	0.301	0.438
	SN	0.470	0.687	0.523	0.452	0.584	0.580	0.234	0.116	0.298	0.438
	C+SN+L	0.475	0.692	0.526	0.457	0.586	0.589	0.245	0.115	0.315	0.444
	I-C+SN+L	0.476	0.694	0.527	0.458	0.586	0.589	0.245	0.115	0.321	**0.446**
PROC-B	None	0.453	0.675	0.531	0.458	0.576	0.579	0.211	0.077	0.085	0.405
	PR	0.477	0.693	0.546	0.465	0.585	0.587	0.253	0.110	0.261	0.442
	GeoMediaN	0.476	0.691	0.545	0.469	0.585	0.590	0.251	0.107	0.242	0.440
	C+L	0.483	0.698	0.550	0.468	0.584	0.590	0.259	0.111	0.264	0.445
	I-C+L	0.483	0.698	0.550	0.469	0.583	0.590	0.255	0.113	0.290	0.448
	SN	0.479	0.697	0.553	0.470	0.588	0.590	0.251	0.133	0.302	0.451
	C+SN+L	0.489	0.702	0.555	0.474	0.591	0.598	0.261	0.127	0.325	0.458
	I-C+SN+L	0.491	0.703	0.558	0.475	0.592	0.599	0.258	0.130	0.341	**0.461**
RCSLS	None	0.509	0.721	0.556	0.463	0.612	0.607	0.265	0.120	0.003	0.428
	PR	0.505	0.724	0.548	0.464	0.611	0.611	0.249	0.077	0.035	0.425
	GeoMediaN	0.504	0.725	0.549	0.462	0.611	0.611	0.250	0.108	0.041	0.429
	C+L	0.510	0.728	0.549	0.462	0.612	0.613	0.259	0.116	0.327	0.464
	I-C+L	0.510	0.728	0.549	0.463	0.612	0.613	0.260	0.118	0.285	0.460
	SN	0.510	0.732	0.553	0.467	0.613	0.615	0.253	0.119	0.349	**0.468**
	C+SN+L	0.505	0.729	0.549	0.466	0.612	0.610	0.251	0.118	0.354	0.466
	I-C+SN+L	0.505	0.727	0.549	0.466	0.612	0.610	0.251	0.118	0.352	0.466

J Full BLI results for all 28 language pairs, translation dictionaries, and models.

Table 18: BLI performance (MAP) for the first batch (14) of language pairs. We compared the Baseline result from (Glavaš et al., 2019) to I-C+SN+L (denoted SN) result on the BLI task.

Model	Dict	DE-FI	DE-FR	DE-HR	DE-IT	DE-RU	DE-TR	EN-DE	EN-FI	EN-FR	EN-HR	EN-IT	EN-RU	EN-TR	FI-FR	Avg
CCA	1K	0.241	0.422	0.206	0.414	0.308	0.153	0.458	0.259	0.582	0.218	0.538	0.336	0.218	0.230	0.327
CCA^{SN}	1K	0.259	0.456	0.224	0.445	0.326	0.179	0.486	0.286	0.609	0.244	0.560	0.362	0.259	0.260	**0.354**
CCA	3K	0.328	0.494	0.298	0.491	0.399	0.251	0.531	0.351	0.642	0.299	0.613	0.434	0.314	0.332	0.413
CCA^{SN}	3K	0.345	0.518	0.314	0.511	0.413	0.278	0.554	0.377	0.657	0.335	0.634	0.455	0.348	0.360	**0.436**
CCA	5K	0.353	0.509	0.318	0.506	0.411	0.280	0.542	0.383	0.652	0.325	0.624	0.454	0.327	0.362	0.432
CCA^{SN}	5K	0.371	0.528	0.340	0.527	0.426	0.303	0.568	0.410	0.665	0.356	0.648	0.476	0.372	0.387	**0.455**
PROC	1K	0.264	0.428	0.225	0.421	0.323	0.169	0.458	0.271	0.579	0.225	0.535	0.352	0.225	0.239	0.336
PROC^{SN}	1K	0.280	0.459	0.244	0.458	0.346	0.194	0.490	0.293	0.611	0.255	0.566	0.378	0.263	0.268	**0.365**
PROC	3K	0.340	0.499	0.308	0.495	0.413	0.260	0.532	0.365	0.642	0.307	0.611	0.449	0.320	0.333	0.420
PROC^{SN}	3K	0.354	0.522	0.326	0.516	0.423	0.283	0.558	0.385	0.659	0.346	0.637	0.472	0.357	0.362	**0.443**
PROC	5K	0.359	0.511	0.329	0.510	0.425	0.284	0.544	0.396	0.654	0.336	0.625	0.464	0.335	0.362	0.438
PROC^{SN}	5K	0.378	0.531	0.350	0.531	0.440	0.312	0.570	0.421	0.670	0.366	0.650	0.490	0.380	0.388	**0.463**
PROC-B	1K	0.354	0.511	0.306	0.507	0.392	0.250	0.521	0.360	0.633	0.296	0.605	0.419	0.301	0.329	0.413
PROC-B^{SN}	1K	0.347	0.531	0.321	0.518	0.359	0.283	0.543	0.411	0.66	0.346	0.628	0.414	0.354	0.373	**0.435**
PROC-B	3K	0.362	0.514	0.324	0.508	0.413	0.278	0.532	0.380	0.642	0.336	0.612	0.449	0.328	0.350	0.431
PROC-B^{SN}	3K	0.359	0.535	0.342	0.524	0.378	0.293	0.545	0.415	0.657	0.362	0.631	0.443	0.368	0.376	**0.445**
DLV	1K	0.259	0.384	0.222	0.420	0.325	0.167	0.454	0.271	0.546	0.225	0.537	0.353	0.221	0.209	0.328
DLV^{SN}	1K	0.260	0.472	0.239	0.458	0.333	0.198	0.503	0.305	0.632	0.274	0.584	0.389	0.287	0.274	**0.372**
DLV	3K	0.341	0.496	0.306	0.494	0.411	0.261	0.533	0.365	0.636	0.307	0.611	0.444	0.320	0.321	0.418
DLV^{SN}	3K	0.361	0.540	0.339	0.537	0.414	0.300	0.571	0.418	0.677	0.381	0.651	0.471	0.393	0.399	**0.461**
DLV	5K	0.357	0.506	0.328	0.510	0.423	0.284	0.545	0.396	0.649	0.334	0.625	0.467	0.335	0.351	0.436
DLV^{SN}	5K	0.384	0.549	0.365	0.548	0.424	0.326	0.582	0.449	0.684	0.404	0.661	0.488	0.407	0.431	**0.479**
RCSLS	1K	0.288	0.459	0.262	0.453	0.361	0.201	0.501	0.306	0.612	0.267	0.565	0.401	0.275	0.269	0.373
RCSLS^{SN}	1K	0.282	0.465	0.247	0.459	0.347	0.197	0.508	0.305	0.635	0.266	0.577	0.403	0.273	0.271	**0.374**
RCSLS	3K	0.373	0.524	0.337	0.518	0.442	0.296	0.568	0.404	0.665	0.357	0.637	0.491	0.364	0.367	0.453
RCSLS^{SN}	3K	0.366	0.543	0.336	0.533	0.448	0.302	0.612	0.421	0.696	0.375	0.668	0.523	0.395	0.374	**0.471**
RCSLS	5K	0.395	0.536	0.359	0.529	0.458	0.324	0.580	0.438	0.675	0.375	0.652	0.510	0.386	0.395	0.472
RCSLS^{SN}	5K	0.404	0.569	0.370	0.550	0.480	0.345	0.636	0.465	0.713	0.419	0.687	0.557	0.439	0.416	**0.504**
VECMAP	-	0.302	0.505	0.300	0.493	0.322	0.253	0.521	0.292	0.626	0.268	0.600	0.323	0.288	0.368	0.390
VECMAP^{SN}	-	0.343	0.539	0.326	0.533	0.337	0.293	0.559	0.355	0.660	0.333	0.635	0.368	0.352	0.400	**0.431**

Table 19: BLI performance (MAP) for second batch (14) of language pairs.

Model	Dict	FI-HR	FI-IT	FI-RU	HR-FR	HR-IT	HR-RU	IT-FR	RU-FR	RU-IT	TR-FI	TR-FR	TR-HR	TR-IT	TR-RU	Avg
CCA	1K	0.167	0.232	0.214	0.238	0.240	0.256	0.612	0.344	0.352	0.151	0.213	0.134	0.202	0.146	0.250
CCA^{SN}	1K	0.193	0.257	0.236	0.273	0.265	0.274	0.638	0.380	0.379	0.157	0.236	0.148	0.227	0.164	**0.273**
CCA	3K	0.264	0.328	0.306	0.346	0.345	0.348	0.659	0.452	0.449	0.232	0.308	0.211	0.309	0.252	0.343
CCA^{SN}	3K	0.289	0.359	0.331	0.375	0.377	0.366	0.672	0.476	0.469	0.257	0.332	0.240	0.329	0.269	**0.367**
CCA	5K	0.288	0.353	0.340	0.372	0.366	0.367	0.668	0.469	0.474	0.260	0.337	0.250	0.331	0.285	0.369
CCA^{SN}	5K	0.311	0.384	0.362	0.403	0.393	0.389	0.681	0.491	0.492	0.284	0.364	0.269	0.357	0.299	**0.391**
PROC	1K	0.187	0.247	0.233	0.248	0.247	0.269	0.615	0.352	0.360	0.169	0.215	0.148	0.211	0.168	0.262
PROC^{SN}	1K	0.217	0.271	0.252	0.285	0.276	0.285	0.641	0.387	0.391	0.178	0.243	0.166	0.239	0.182	**0.287**
PROC	3K	0.269	0.328	0.310	0.346	0.350	0.353	0.659	0.455	0.455	0.241	0.312	0.219	0.312	0.262	0.348
PROC^{SN}	3K	0.296	0.365	0.337	0.381	0.384	0.371	0.671	0.474	0.472	0.262	0.336	0.248	0.336	0.279	**0.372**
PROC	5K	0.294	0.355	0.342	0.374	0.364	0.372	0.669	0.470	0.474	0.269	0.338	0.259	0.335	0.290	0.372
PROC^{SN}	5K	0.316	0.385	0.364	0.407	0.396	0.393	0.679	0.491	0.495	0.290	0.368	0.275	0.360	0.305	**0.395**
PROC-B	1K	0.263	0.328	0.315	0.335	0.343	0.348	0.665	0.467	0.466	0.247	0.305	0.210	0.298	0.230	0.344
PROC-B^{SN}	1K	0.296	0.365	0.337	0.408	0.392	0.371	0.678	0.486	0.483	0.280	0.357	0.255	0.346	0.246	**0.379**
PROC-B	3K	0.293	0.348	0.327	0.365	0.368	0.365	0.664	0.478	0.476	0.270	0.333	0.244	0.330	0.262	0.366
PROC-B^{SN}	3K	0.303	0.374	0.337	0.403	0.399	0.377	0.678	0.488	0.491	0.286	0.360	0.267	0.356	0.264	**0.384**
DLV	1K	0.184	0.244	0.225	0.214	0.245	0.264	0.585	0.320	0.358	0.161	0.194	0.144	0.209	0.161	0.251
DLV^{SN}	1K	0.217	0.275	0.249	0.290	0.286	0.286	0.645	0.398	0.393	0.174	0.266	0.164	0.252	0.182	**0.291**
DLV	3K	0.269	0.331	0.307	0.331	0.348	0.353	0.653	0.446	0.452	0.243	0.306	0.219	0.311	0.261	0.345
DLV^{SN}	3K	0.324	0.390	0.364	0.417	0.415	0.394	0.684	0.495	0.495	0.294	0.373	0.276	0.361	0.288	**0.398**
DLV	5K	0.294	0.356	0.342	0.364	0.366	0.374	0.665	0.466	0.475	0.268	0.333	0.255	0.336	0.289	0.370
DLV^{SN}	5K	0.357	0.420	0.392	0.445	0.440	0.422	0.695	0.515	0.513	0.320	0.401	0.311	0.391	0.322	**0.425**
RCSLS	1K	0.214	0.272	0.257	0.281	0.275	0.291	0.637	0.381	0.383	0.194	0.247	0.170	0.246	0.191	**0.289**
RCSLS^{SN}	1K	0.217	0.271	0.253	0.284	0.279	0.286	0.645	0.388	0.393	0.179	0.243	0.168	0.239	0.185	0.288
RCSLS	3K	0.296	0.362	0.341	0.384	0.382	0.379	0.673	0.477	0.472	0.272	0.348	0.256	0.340	0.290	0.377
RCSLS^{SN}	3K	0.301	0.372	0.345	0.392	0.388	0.382	0.684	0.489	0.482	0.270	0.363	0.259	0.348	0.291	**0.383**
RCSLS	5K	0.321	0.388	0.376	0.412	0.399	0.404	0.682	0.494	0.491	0.300	0.375	0.285	0.368	0.324	0.401
RCSLS^{SN}	5K	0.331	0.403	0.392	0.431	0.417	0.417	0.700	0.520	0.509	0.304	0.397	0.302	0.385	0.335	**0.417**
VECMAP	-	0.280	0.355	0.312	0.402	0.389	0.376	0.667	0.463	0.463	0.246	0.341	0.223	0.332	0.200	0.361
VECMAP^{SN}	-	0.289	0.398	0.350	0.438	0.431	0.407	0.689	0.497	0.487	0.270	0.386	0.251	0.365	0.194	**0.389**