Divide and Contrast: Source-free Domain Adaptation via Adaptive Contrastive Learning

Abstract

We investigate a practical domain adaptation task, called source-free unsupervised domain adaptation (SFUDA), where the source pretrained model is adapted to the target domain without access to the source data. Existing techniques mainly leverage self-supervised pseudo-labeling to achieve class-wise *global* alignment [1] or rely on *local* structure extraction that encourages the feature consistency among neighborhoods [2]. While impressive progress has been made, both lines of methods have their own drawbacks – the "global" approach is sensitive to noisy labels while the "local" counterpart suffers from the source bias. In this paper, we present *Divide and Contrast (DaC)*, a new paradigm for SFUDA that strives to connect the good ends of both worlds while bypassing their limitations. Based on the prediction confidence of the source model, DaC divides the target data into source-like and target-specific samples, where either group of samples is treated with tailored goals under an adaptive contrastive learning framework. Specifically, the source-like samples are utilized for learning *global* class clustering thanks to their relatively clean labels. The more noisy target-specific data are harnessed at instance level for learning the intrinsic *local* structures. We then further align the source-like domain with the target-specific samples using a memory bank-based maximum mean discrepancy (MMD) loss to reduce the distribution mismatch. Extensive experiments on VisDA, Office-Home, and the more challenging DomainNet have verified the superior performance of DaC over current state-of-the-art approaches.

1   Introduction

Deep neural networks have brought impressive advances to the cutting edges of vast machine learning tasks. However, the leap of performance often comes at the cost of large-scale labeled data. To ease the process of laborious data annotation, domain adaptation (DA) provides an attractive option that transfers the knowledge learned from label-rich source domain to the unlabeled target data. Though most DA approaches require the availability of source data during adaptation, in real-world scenarios, one may only access a source trained model instead of source data due to the privacy issues. Hence, this work studies a more practical task, coded source-free unsupervised domain adaptation (SFUDA), that seeks to adapt a source model to a target domain in the absence of source data.

There are two mainstream strategies to tackle the SFUDA problem. One line of approaches focuses on class-wise *global* adaptation. The key idea is to mitigate domain shift either by pseudo-labeling the target data [1, 3] or generating images with target styles [4]. However, either the pseudo images or labels can be noisy due to the domain discrepancy, which would compromise the training procedure and lead to erroneous classifications (Figure 1 (a)). The other direction of research strives to exploit the intrinsic *local* structure [2, 5] by encouraging consistent predictions between neighboring samples. Nonetheless, the closeness of features may be biased by the source hypothesis which could render

(a) Global adaptation method (b) Local consistency method (c) Divide and contrast (ours)

Figure 1: UMAP [6] visualizations of target features trained for 60 epochs on the randomly selected 6 VisDA classes. The results are compared with two types of baselines, global adaption based CPGA [3] and neighborhood consistency based NRC [2]. CPGA can achieve clear global-scale clusters but suffer from false predictions inside each class. NRC can only maintain the intrinsic local consistency but fail to generate clear intra-class boundaries. In contrast, our method inherits the merits of both methods – clear global clusters and strong local consistency, while bypassing their limitations.

false predictions. Further, as it fails to consider the global context, it may generate spurious local clusters that are detrimental to the discriminability of the trained model (Figure 1 (b)).

To address the above issues, we propose *Divide and Contrast* (*DaC*), a dedicated framework for SFUDA that aims to combine the merits of existing technique, i.e. taking full advantage of both global and local structures, while sidestepping their limitations. Our key observation is that the "global" approach based on self-training can form clear clusters in the feature landscape (Figure 1 (a)). Its prediction artifacts are mainly caused by noisy labels with low prediction confidence. Hence, after self-training by pseudo labels, we propose to divide the target data into *source-like* and *target-specific* samples, based on the prediction confidence of the source classifier [1]. The two groups of samples are then fully exploited with tailored learning strategies under a unified *adaptive contrastive learning* framework with memory bank. Specifically, thanks to the high prediction confidence, the memory bank generates robust class centroids as positive prototype for source-like samples. This ensures DaC can obtain a discrinimative *global* structure without affected by noisy labels. In contrast, for the low-confidence target-specific samples, we ignore their noisy class-level supervisory signals, and use the memory bank to generate positive prototype via the *local* structure. This encourages network to exploit the intrinsic local structures by contrastive learning.

To prevent the local clustering from forming spurious clusters as shown in Figure 1 (b), we further transfer the cluster structure from the source-like domain to the target-specific samples. In particular, we propose a maximum mean discrepancy (MMD) based on memory bank for measuring the distribution mismatch between the source-like and target-specific data. Since the set of source-like and target-specific samples are dynamically updated in our framework, the introduction of memory bank can effectively alleviate the instability and batch bias caused by mini batches. As seen in Figure 1 (c), the proposed DaC framework can generate to clearer and cleaner clusters than both the class-wise and instance discrimination methods. Finally, we provide rigorous theoretical analysis on the upper bound of the task risk of target model (Sec. 3) that justifies the soundness of our proposed framework. Extensive experiments demonstrate that our proposed DaC framework has set a new state of the art on a number of challenging datasets, including VisDA, Office-Home, and DomainNet.

We summarize our contributions as follows: 1) a novel divide-and-contrast paradigm for SFUDA that can fully exploit both the global and local structures of target data via data segmentation and customized learning strategies for data subsets; 2) a unified adaptive contrastive learning framework that achieves class-wise adaptation for source-like samples and local consistency for target-specific data; 3) a memory bank based MMD loss to reduce the batch bias in batch training and an improved MMD loss with non-negative exponential form; 4) new state-of-the-art performance on VisDA, Office-Home, and DomainNet.

2 Related Work

Unsupervised Domain Adaptation. Conventional UDA methods alleviate the domain discrepancy between source domain and target domain by leveraging the Maximum Mean Discrepancy (MMD) [7]

to match high-order moments of distributions [8, 9, 10] or by adversarial training to learn domain invariant features [11, 12]. In addition, some methods [13, 14] utilize contrastive learning to enhance the global class-level structure by minimizing intra-class distance and maximizing inter-class distance, and others [15, 16] use memory bank to provide class-level information from source domain and instance-level information from target domain for contrastive learning. However, the absence of source data makes these methods cannot be applied directly.

Source-free Unsupervised Domain Adaptation. Source-free Unsupervised Domain Adaptation(SFUDA) aims to adapt the well-trained source model to the target domain without the annotated source data. Some methods focus on generating target-style images [4] or reconstructing fake source images via source model [17]. Another stream of SFUDA methods is exploiting the information provided by the source model. Some methods [1, 18, 19, 3] only leverage the class-level information from source model and adapt source model to target domain by pseudo-labeling, while the other [2, 5] only exploit the neighborhood information and encourage the consistent predictions among samples with highly local affinity.

Contrastive Learning. Contrastive learning achieves the promising improvement on unsupervised visual representation learning [20, 21, 22, 23, 24] by learning instance discriminative representations. Although the instance-level contrastive learning has well generalization capability in downstream tasks, it does not perform well on the source-free domain adaptation tasks which demand correct measurement of inter-class affinities on the unsupervised target domain.

3   Preliminaries and Analysis

Preliminary. Only with a well-trained model on source domain, the goal of the SFUDA task is to learn a model h which minimizes the task risk $\epsilon_{\mathcal{D}_T}(h)$ in the target domain, $i.e.\epsilon_{\mathcal{D}_T}(h) = \mathbb{P}_{\mathcal{D}_T}[h(x) \neq h^*(x))]$, where $\mathcal{D}_T$ is our available n_t unlabeled $i.i.d$ samples from target domain, and h^* is the ideal model in all model space $\mathcal{H}$. Specifically, we consider a C-way classification task, where the source and target domain share the same label space. The model h consists of a feature extractor ϕ and a classifier g, $i.e.$ $h(x) = g(\phi(x))$, and the source model is defined as: $h_s = g_s \circ \phi_s$. The feature from the feature extractor is denoted as $\boldsymbol{f}_i = \phi(x_i)$. For the training stage, the batch data randomly sampled from $\mathcal{D}_T$ is denoted as $\mathcal{B}_T$, and δ is the softmax function.

Denote by $\mathcal{D}_{T_i}$ the conditional distribution of target data $\mathcal{D}_T$ given the ground-truth $y = i$, and further assume $\mathcal{D}_{T_i} \cap \mathcal{D}_{T_j} = \emptyset$ for all $i \neq j$. Following [25, 26], we define that the suitable set of input transformations $\mathcal{B}(x)$ takes the general form $\mathcal{B}(x) = \{x' : \exists A \in \mathcal{A} \ s.t. ||x' - A(x)|| < r\}$ for a small radius $r > 0$ and a set of data augmentations $\mathcal{A}$. Then, the neighborhood of a point x is defined by $\mathcal{B}(x)$ as $\mathcal{N}(x) := \mathcal{D}_{T_i} \cap \{x'|\mathcal{B}(x) \cap \mathcal{B}(x') \neq \emptyset\}$, as well as that of a set $S \subset \mathcal{D}_T$ as: $\mathcal{N}(S) := \cup_{x \in S}\mathcal{N}(x)$. The consistency error of h on domain $\mathcal{D}_T$ is defined as : $\mathcal{R}_{\mathcal{D}_T}(h) = \mathbb{E}_{\mathcal{D}_T}[\mathbb{1}(\exists x' \in \mathcal{B}(x) \ s.t. \ h(x') \neq h(x))]$, which indicates the model stability of local structure and input transformations. To this end, we introduce the expansion property [27] to study the target domain.

Definition 3.1 ((q, γ)-**constant expansion** [25, 27])). *We say Q satisfies (q, γ)-constant expansion for some constant $q, \gamma \in (0, 1)$, if for any set $S \subset Q$ with $\mathbb{P}_Q[S] > q$, we have $\mathbb{P}_Q[\mathcal{N}(S) \setminus S] > \min\{\gamma, \mathbb{P}_Q[S]\}$.*

Our *Divide and Contrast* paradigm mainly divides the target data into source-like and target-specific samples via the source classifier. Specifically, by freezing the source classifier *i.e.* $h = g_s \circ \phi$ [1], we select confident samples with prediction probability greater than a threshold τ, and regard them as source-like samples: $\mathcal{D}_S = \{x_i| \max_c \delta(h(x_i)) \geq \tau, x_i \in \mathcal{D}_T\}$, and the rest target data is target-specific samples $\mathcal{D}_O = \mathcal{D}_T \setminus \mathcal{D}_S$. Denote by $\mathcal{D}_{S_i}$ the conditional distribution of $\mathcal{D}_S$ where $\mathcal{D}_{S_i} = \mathcal{D}_S \cap \mathcal{D}_{T_i}$. The definition is similar for $\mathcal{D}_{O_i}$. The following claim guarantee the existence of τ and consistency robustness of source-like samples:

Claim 3.1. *Suppose h is L_h-Lipschitz w.r.t the L_1 distance, there exists threshold $\tau \in (0, 1)$ such that the source-like set $\mathcal{D}_S$ is consistency robust, i.e. $\mathcal{R}_{\mathcal{D}_S}(h) = 0$. More specifically,*

$$\tau \geq \frac{L_h r}{4} + \frac{1}{2}.$$

Remark 1. *Claim 3.1 illustrates the source-like set with small consistency error, as long as the τ is large enough. Moreover, we empirically claim that model predictions on $\mathcal{D}_S$ are more robust,*

125 *i.e. $\epsilon_{\mathcal{D}_S}(h) \leq \epsilon_{\mathcal{D}_T}(h)$ [18]. The great properties of the source-like set, consistency and robustness,*
126 *motivates us to transfer knowledge from source-like samples to target-specific samples, by constrastive*
127 *learning and distribution matching.*

128 Assume we have a pseudo-labeler h_{pl} based on the source model. The following theorem establishes
129 upper bound on the target risks and states the key idea behind our method. The proofs of both the
130 claim and theorem are provided in the supplementary materials.

Theorem 3.2. *Suppose the condition of Theorem 3.1 holds and $\mathcal{D}_T, \mathcal{D}_S$ satisfies (q, γ)-constant expansion. Then the expected error of model $h \in \mathcal{H}$ on target domain $\mathcal{D}_T$ is bounded,*

$$\epsilon_{\mathcal{D}_T}(h) \leq (\mathbb{P}_{\mathcal{D}_T}[h(x) \neq h_{pl}(x)] - \epsilon_{\mathcal{D}_S}(h_{pl}) + q) \frac{\mathcal{R}_{\mathcal{D}_T}(h)(1 + \gamma)}{\gamma \cdot \min\{q, \gamma\}} + \max_{i \in [C]}\{d_{\mathcal{H}\Delta\mathcal{H}}(\mathcal{D}_{S_i}, \mathcal{D}_{O_i})\} + \lambda,$$

131 where constant λ *w.r.t* the expansion constant q and task risk of the optimal model.

Remark 2. *The Theorem 3.2 states that the target risk is bounded by the following three main parts,*
133 *the fitting accuracy between model h and pseudo-labeler $\mathbb{P}_{\mathcal{D}_T}[h(x) \neq h_{pl}(x)]$, the consistency regu-*
134 *larization $\mathcal{R}_{\mathcal{D}_T}(h)$, and the $\mathcal{H}$-divergence between the source-like samples target-specific samples*
135 $d_{\mathcal{H}\Delta\mathcal{H}}(\mathcal{D}_{S_i}, \mathcal{D}_{O_i})$. *To constrain the above three parts, the theoretical insight of our method lies in*
136 *class-wise adaptation, consistency of local structure, and alignment between target-specific and*
137 *source-like samples.*

138 Based on the theoretical analysis, our method consists of three parts: 1) achieves preliminary
139 class-wise adaptation by $\mathcal{L}_{self}$, which fits h to pseudo-labels; 2) leverages adaptive contrastive loss
140 $\mathcal{L}_{con}$ to jointly achieve robust class-wise adaptation for source-like samples and local consistency
141 regularization for target-specific samples; 3) minimizes the discrepancy between the source-like set
142 and target-specific ouliers by $\mathcal{L}_{EMMD}$. The entire loss is defined as:

$$\mathcal{L} = \mathcal{L}_{con} + \alpha\mathcal{L}_{self} + \beta\mathcal{L}_{EMMD}. \tag{1}$$

143 # 4 Divide and Contrast for Source-free Unsupervised Domain Adaptation

Figure 2: The illustration of the proposed *DaC* framework.

144 In this section, we introduce *DaC*, our proposed method for source-free unsupervised domain
145 adaptation. As the overview shown in Figure 2, our method consists of three parts, self-training by
146 pseudo-labels, an adaptive contrastive learning framework, and the distribution alignment.

147 ## 4.1 Data Segmentation and Self-Training

148 The class-wise alignment is non-trivial due to the lack of target annotations. In order to achieve
149 preliminary class-wise adaptation, we generate pseudo-labels to supervise the transformation set

of input $\mathcal{B}(x)$. In practice, we consider two different augmentation strategies in augmentation set: $\mathcal{A} = \{\mathcal{A}_w, \mathcal{A}_s\}$, where weak augmentation $\mathcal{A}_w$ refers to random cropping and flipping, and strong augmentation $\mathcal{A}_s$ refers to the automatically learned augmentation strategy in [28].

Pseudo-labeling. We apply the strategy proposed in [1] to update pseudo-labels in each epoch. Denote by $p_i = \delta(g_s(\boldsymbol{f}_i))$ the prediction from source classifier. The initial centroid for each class k is attained by: $\mathbf{c}_k = \frac{\sum_i^{n_t} \boldsymbol{f}_i p_i[k]}{\sum_i^{n_t} p_i[k]}$. The centroids helps to estimate the centers of different categories, and the samples are labeled identically with its nearest initial centroid:

$$\tilde{\mathcal{Y}} = \{\tilde{y}_i | \tilde{y}_i = \arg\max_k \cos(\phi(x_i), \mathbf{c}_k), x_i \in \mathcal{D}_T\}, \tag{2}$$

where $\cos(\cdot, \cdot)$ is the cosine similarity. During the training process, the k-th centroid is further modified by: $\mathbf{c}_k = \frac{\sum_i^{n_t} \mathbb{1}(\tilde{y}_i=k)\boldsymbol{f}_i}{\sum_i^{n_t} \mathbb{1}(\tilde{y}_i=k)}$, where $\mathbb{1}(\cdot)$ is the indicator function, and pseudo-labels are further updated by the modified centroids $\mathbf{c}_k$ based on Eqn. 2 in each epoch.

Self-training for Consistency Regularization. During the training iteration, we transfer each sample x_i into two views: $\mathcal{A}_w(x_i), \mathcal{A}_s(x_i)$. Network predictions on the two views are denoted as p_i^w and p_i^s respectively. To obtain more robust supervision signals, we perform label refinement by network's prediction: $\hat{y}_i = \omega \cdot (\bar{y}_i) + (1-\omega)p_i^w$, where $\bar{y}_i = \text{onehot}(\tilde{y}_i)$ is one-hot coding of pseudo-labels and ω is a hyper-parameter emperically set as 0.1. Since the same semantic content of the two augmented views, we encourage consistent predictions between two types ouputs by the following loss:

$$\mathcal{L}_{self} = -\mathbb{E}_{x_i \in \mathcal{B}_T} \left[\sum_{c=1}^{C} \hat{y}_i^c \log(p_i^w[c]) + \hat{y}_i^c \log(p_i^s[c]) \right] + \sum_{c=1}^{C} \text{KL}(\bar{p}_c || \frac{1}{C}), \tag{3}$$

where $\bar{p}_c = \mathbb{E}_{\mathcal{D}_T}[p_i^w[c]]$ is regularized by uniform distribution to encourage output diversity.

Dataset Division. As the analysis before, we divide all samples in $\mathcal{D}_T$ into the source-like set and target-specific outliers. During the training process, samples are dynamically grouped into source-like set by the threshold τ:

$$\tilde{\mathcal{D}}_S^k = \{x_i | \max_c(p_i^w[c]) \geq \tau, \arg\max_c(p_i^w[c]) = k, x_i \in \mathcal{D}_T\}, \tag{4}$$

and the target-specific samples are the rest target data, i.e. $\tilde{\mathcal{D}}_O = \mathcal{D}_T \setminus \tilde{\mathcal{D}}_S$, where $\tilde{\mathcal{D}}_S = \cup_{k=1}^C \tilde{\mathcal{D}}_S^k$. More specifically, $\tilde{\mathcal{D}}_O^k = \{x_i | x_i \in \tilde{\mathcal{D}}_O, \tilde{y}_i = k, \tilde{y}_i \in \tilde{\mathcal{Y}}\}$. To this end, we design an adaptive contrastive learning framework jointly adapt source-like features to class-wise prototypes and optimize target-specific features by local structures.

4.2 Adaptive Contrastive Learning

Similar to [20, 15], we employ a momentum updated memory bank to store all target features $\mathcal{F} = \{\boldsymbol{z}_i\}_{i=1}^{n_t}$. The memory bank dynamically generates C source-like class centroids $\{\boldsymbol{w}_c\}_{c=1}^C$ and n_o target-specific features $\{\boldsymbol{v}_j\}_{j=1}^{n_o}$, where $n_o = |\tilde{\mathcal{D}}_O|$ is the current number of target-specific samples, which dynamically changes in the training stage.

For a general anchor feature during training time $\boldsymbol{f}_i = \phi(\mathcal{A}_w(x_i))$, $x_i \in \tilde{\mathcal{D}}_S \cup \tilde{\mathcal{D}}_O$, we conduct prototype contrastive loss with similarity measured by inner product:

$$\mathcal{L}_{con} = -\mathbb{E}_{x_i \in \mathcal{B}_T} \log \frac{\exp(\boldsymbol{f}_i \cdot \boldsymbol{k}^+ / \tau)}{\exp(\boldsymbol{f}_i \cdot \boldsymbol{k}^+ / \tau) + \sum_{j=1}^{C+n_o-1} \exp(\boldsymbol{f}_i \cdot \boldsymbol{k}_j^- / \tau)}, \tag{5}$$

where the sum is over one positive pair $(\boldsymbol{f}_i, \boldsymbol{k}^+)$ and $C + n_o - 1$ negative pairs $\{(\boldsymbol{f}_i, \boldsymbol{k}^-)\}$, the temperature τ is a hyper-parameter and is empirically set as 0.05.

4.2.1 Prototype Generation

The contrastive loss tries to classify anchor feature $\boldsymbol{f}$ as its positive prototype $\boldsymbol{k}^+$ from all negative samples. Memory bank generates $C + n_o$ features, including the class-level signals, i.e. C class centroids $\{\boldsymbol{w}\}$ as well as n_o target-specific instance features $\{\boldsymbol{v}\}$. The source-like and target specific samples are jointly optimized by generating corresponding positive prototypes.

For the source-like anchor, $i.e.$ $x_i \in \tilde{\mathcal{D}}_S^k$, since the network prediction k (in Eqn. 4) is relatively reliable [18], we encourage contrastive learning to achieve class-wise adaptation by designating the positive prototype as class centroid $\boldsymbol{w}_k$, $i.e.$ $\boldsymbol{k}^+ = \boldsymbol{w}_k$. The rest $C - 1$ class centroids and n_o target-specific features are used to form negative pairs.

For the target specific anchor, due to its noisy class-level supervisory signal, we generate positive prototype $\boldsymbol{k}^+$ by introducing *Local Structure*, including neighborhood consistency and transformation stability. Specifically, we enhance the semantic consistency with the strongly augmented features $\boldsymbol{f}_i^s = \phi(\mathcal{A}_s(x_i))$ and the K-nearest features $\mathcal{N}_K(\boldsymbol{f}_i)$, that can be easily found in memory bank via cosine similarity: $\mathcal{N}_K(\boldsymbol{f}_i) = \{\boldsymbol{z}_j | top\text{-}K\left(\cos(\boldsymbol{f}_i, \boldsymbol{z}_j)\right), \forall \boldsymbol{z}_k \in \mathcal{F}\}$. To this end, the positive prototype $\boldsymbol{k}^+$ is generated as: $\boldsymbol{k}^+ = \frac{1}{K+1}\left(\boldsymbol{f}_i^s + \sum_{k=1}^{K}\boldsymbol{z}_k\right)$, where $\boldsymbol{z}_k \in \mathcal{N}_K(\boldsymbol{f}_i)$. Note that $\boldsymbol{k}^+$ depicts the local information of its corresponding feature $\boldsymbol{v}_i$, and we use the rest $n_o - 1$ target-specific features $\{\boldsymbol{v}_j\}_{j \neq i}$ and C class centroids to form negative pairs.

Discussion. For the source-like anchor, the positive prototype $\boldsymbol{k}^+ = \boldsymbol{w}_k$ is the mean of all source-like features with confident and consistent predictions, which makes the class-wise adaptation more robust to noisy pseudo-labels. For the i-th target-specific anchor, its corresponding memory bank feature $\boldsymbol{z}_i \in \mathcal{F}$ should be found in $\mathcal{N}_K(\boldsymbol{f}_i)$, and the contrastive loss plays the role of consistency regularization, which constrains the consistency error in Thm 3.2. Unlike the previous prototype contrastive method [3], Eqn. 5 jointly achieves class-wise adaptation and instance-wise adaptation. The source-like and target-specific samples are dynamically updated, and the contrastive framework adaptively benefits the representation learning.

4.2.2 Memory Bank

One of the most important reasons to utilize memory bank is to conserve source information by momentum updating features. Therefore, the memory bank is initialized with the features by performing forward computation of source feature extractor ϕ_s: $\mathcal{F} = \{\boldsymbol{z}_i | \boldsymbol{z}_i = \phi_s(x_i), x_i \in \mathcal{D}_T\}$. At each iteration, the memory bank features are updated via momentum strategy, for the i-th input feature: $\boldsymbol{z}_i = m\boldsymbol{z}_i + (1 - m)\boldsymbol{f}_i$, where $m \in [0, 1]$ is the momentum coefficient and is empirically set as 0.2.

The memory bank provides source-like centroids and target-specific features for contrastive learning. The target-specific features can be directly accessed in memory bank: $\{\boldsymbol{v}_i | \boldsymbol{v}_i = \boldsymbol{z}_i, x_i \in \tilde{\mathcal{D}}_O\}$. We initialize the source-like set before initializing the source-like centroids. Samples with confident predictions from source classifier are termed as source-like. To guarantee sufficient samples in source-like set in the early training stage, we initialize the source-like set by drawing samples with top 5% predictions in each class. The c-th source-like set is initialized as:

$$\tilde{\mathcal{D}}_S^c = \underset{|\mathcal{X}|=N, \hat{\mathcal{X}} \subseteq \mathcal{D}_t}{\arg\max} \sum_{x_i \in \mathcal{X}} p_i^w[c], \tag{6}$$

where $N = 5\% n_t$ is the number of samples in each class. And $\tilde{\mathcal{D}}_S^c$ is updated in training stage by Eqn. 4. After updating the source-like set $\tilde{\mathcal{D}}_S$ $(= \bigcup_{c=1}^{C} \tilde{\mathcal{D}}_S^c)$, the c-th class centroids $\boldsymbol{w}_c$ is generated by the mean of all source-like features:

$$\boldsymbol{w}_c = \frac{1}{|\tilde{\mathcal{D}}_S^c|} \sum_{x_i \in \mathcal{D}_S^c} \boldsymbol{z}_i. \tag{7}$$

4.3 Distribution Alignment

To obtain better adaptation performance, we further achieve alignment by minimize the $\mathcal{H}$-divergence between source-like set and target-specific samples, $i.e.$ $d_{\mathcal{H}\Delta\mathcal{H}}(\mathcal{D}_{S_i}, \mathcal{D}_{O_i})$, where the kernel-based Max Mean Discrepancy (MMD) [7] is widely used. We use $\tilde{\mathcal{D}}_S^i, \tilde{\mathcal{D}}_O^i$ to estimate $\mathcal{D}_{S_i}, \mathcal{D}_{O_i}$, the related optimization target is: $\min_{h \in \mathcal{H}} d_{MMD}^\kappa(\tilde{\mathcal{D}}_S^i, \tilde{\mathcal{D}}_O^i)$, where κ is kernel function. MMD depicts the domain discrepancy by embedding two distribution into reproducing kernel Hilbert space. Considering the MMD between two domain $\mathcal{S}, \mathcal{T}$ with linear kernel function in mini-batch (batch size B):

$$d_{MMD}(\mathcal{S}, \mathcal{T}) = \frac{1}{m}\sum_{i=1}^{m}\boldsymbol{s}_i\left(\frac{1}{m}\sum_{i'=1}^{m}\boldsymbol{s}_{i'} - \frac{1}{n}\sum_{j'=1}^{n}\boldsymbol{t}_{j'}\right) + \frac{1}{n}\sum_{i=1}^{n}\boldsymbol{t}_i\left(\frac{1}{n}\sum_{j'=1}^{n}\boldsymbol{t}_{j'} - \frac{1}{m}\sum_{i'=1}^{m}\boldsymbol{s}_{i'}\right). \tag{8}$$

where $\boldsymbol{s}, \boldsymbol{t}$ represent the features of two domain, m, n are their corresponding amounts in mini-batch ($m+n = B$). The previous UDA methods regard $\mathcal{S}, \mathcal{T}$ as source and target domain, and take an equal number of samples from two domains (*i.e.* $m = n = B/2$). Since the absence of source data, we use MMD to measure the discrepancy of source-like set and target-specific outliers, whose amounts m, n are uncertain in the random batch sampling. The vanilla MMD is not applicable in our setting because samples in mini-batch have estimation bias of the whole distribution, especially when the m or n is small. To this end, we use features in memory bank to estimate the whole distribution and reduce batch bias. Specifically, for $\mathcal{S} = \tilde{\mathcal{D}}_S^c, \mathcal{T} = \tilde{\mathcal{D}}_O^c$, we replace $\frac{1}{m}\sum_{i'=1}^m \boldsymbol{s}_{i'}$ with $\mathbb{E}_{\tilde{\mathcal{D}}_S^c}[\boldsymbol{z}] = \boldsymbol{w}_c$, $\frac{1}{n}\sum_{j'=1}^n \boldsymbol{t}_{j'}$ with $\mathbb{E}_{\tilde{\mathcal{D}}_O^c}[\boldsymbol{z}]$, and rewrite Eqn. 8 as our linear memory bank based MMD:

$$\mathcal{L}_{LMMD} = \mathbb{E}_{x_i \in \mathcal{B}_T} \boldsymbol{f}_i (\boldsymbol{q}_i^- - \boldsymbol{q}_i^+), \tag{9}$$

where $\boldsymbol{q}_i^-$ is the correlating prototype in memory bank at the same domain. For example, if $\boldsymbol{f}_i$ is from the source-like set, $\boldsymbol{q}_i^- = \boldsymbol{w}_c, \boldsymbol{q}_i^+ = \mathbb{E}_{\tilde{\mathcal{D}}_O^c}[\boldsymbol{z}]$. To avoid negative term in Eq. 9, we improve it as an non-negative form. By simply clipping $\max\{0, \boldsymbol{f}\boldsymbol{q}^- - \boldsymbol{f}\boldsymbol{q}^+\}$, we have:

$$\max\{0, \boldsymbol{f}\boldsymbol{q}^- - \boldsymbol{f}\boldsymbol{q}^+\} = \max\{\boldsymbol{f}\boldsymbol{q}^+, \boldsymbol{f}\boldsymbol{q}^-\} - \boldsymbol{f}\boldsymbol{q}^+ \leq \log\left(\exp(\boldsymbol{f}\boldsymbol{q}^+) + \exp(\boldsymbol{f}\boldsymbol{q}^-)\right) - \boldsymbol{f}\boldsymbol{q}^+,$$

the inequality holds by the log-sum-exp bound. And the last term above can be organized into our Exponential-MMD loss as:

$$\mathcal{L}_{EMMD} = -\mathbb{E}_{x_i \in \mathcal{B}_T} \log \frac{\exp(\boldsymbol{f}_i \boldsymbol{q}_i^+)}{\exp(\boldsymbol{f}_i \boldsymbol{q}_i^+) + \exp(\boldsymbol{f}_i \boldsymbol{q}_i^-)}. \tag{10}$$

5 Experiments

5.1 Experimental Setup

Datasets and benchmarks. We conduct experiments on three benchmark datasets: **Office-Home** [29] contains 65 classes from four distinct domains (Real, Clipart, Art, Product) and a total of 15,500 images. **VisDA-2017** [30] is a large-scale dataset, with 12-class synthetic-to-real object recognition tasks. The dataset consists of 152k synthetic images from source domain while 55k real object images from target domain. **DomainNet** [31] is originally a large-scale multi-source domain adaptation benchmark, which contains 6 domains with 345 classes. Similar with the setting of [32, 33], we select 4 domains (Real, Clipart, Painting and Sketch) with 126 classes as the single-source unsupervised domain adaptation benchmark, and construct 7 single-source adaptation scenarios from the selected 4 domains. All results are the average of three random runs.

Implementation Details. We adopt the Resnet-50[34] as backbone for Office-Home and ResNet-101 for VisDA, and conduct ResNet-34 for DomainNet similar to previous work [32, 33]. For fair comparison, we use the same basic experimental setting in [1, 2]. For the network architecture, the feature extractor consists of the backbone and a full-connected layer with batch normalization, and the classification head is full-connected with weight normalization. Following SHOT, the source model is supervised by smooth labels, and the network is initialized by the source model and we only trains the feature extractor. The training details are delineated in supplementary materials.

5.2 Comparison with State-of-the-arts

We compare our method with the state-of-the-art methods on the Office-Home, VisDA, and Domain-Net. As the results for **VisDA** shown in Table 1, our method surpasses all baselines in terms of average accuracy, including the recent source-present method BCDM and the most recent source-free method CPGA (87.3% *v.s.* 86.0%). For the **DomainNet**, Table 2 illustrates the proposed *DaC* achieves the best performance compared with all source-free methods, and outperforms all source-present and source-free methods *w.r.t* average accuracy. Similar observation on the results of **Office-Home** can be found in Table 3. The reported results indicate the superiority of our method.

Table 1: Accuracy (%) on the VisDA dataset (ResNet-101).

Method	SF	plane	bicycle	bus	car	horse	knife	mcycl	person	plant	sktbrd	train	truck	Avg.
ResNet-101 [34]	✗	55.1	53.3	61.9	59.1	80.6	17.9	79.7	31.2	81.0	26.5	73.5	8.5	52.4
CDAN [35]	✗	85.2	66.9	83.0	50.8	84.2	74.9	88.1	74.5	83.4	76.0	81.9	38.0	73.9
SWD [36]	✗	90.8	82.5	81.7	70.5	91.7	69.5	86.3	77.5	87.4	63.6	85.6	29.2	76.4
MCC [37]	✗	88.7	80.3	80.5	71.5	90.1	93.2	85.0	71.6	89.4	73.8	85.0	36.9	78.8
STAR [38]	✗	95.0	84.0	84.6	73.0	91.6	91.8	85.9	78.4	94.4	84.7	87.0	42.2	82.7
BCDM [39]	✗	95.1	87.6	81.2	73.2	92.7	95.4	86.9	82.5	95.1	84.8	88.1	39.5	83.4
3C-GAN [4]	✓	94.8	73.4	68.8	74.8	93.1	95.4	88.6	84.7	89.1	84.7	83.5	48.1	81.6
SHOT [1]	✓	94.3	88.5	80.1	57.3	93.1	94.9	80.7	80.3	91.5	89.1	86.3	58.2	82.9
G-SFDA [5]	✓	96.1	88.3	85.5	74.1	97.1	95.4	89.5	79.4	95.4	92.9	89.1	42.6	85.4
NRC [2]	✓	**96.8**	**91.3**	82.4	62.4	96.2	95.9	86.1	80.6	94.8	94.1	90.4	59.7	85.9
CPGA [3]	✓	95.6	89.0	75.4	64.9	91.7	**97.5**	89.7	**83.8**	93.9	93.4	87.7	**69.0**	86.0
DaC	✓	96.6	86.8	**86.4**	**78.4**	96.4	96.2	**93.6**	83.8	**96.8**	95.1	89.6	50.0	**87.3**

Table 2: Accuracy (%) on the DomainNet dataset (ResNet-34). The * baselines are implemented by the official codes.

Method	SF	Rw→Cl	Rw→Pt	Pt→Cl	Cl→Sk	Sk→Pt	Rw→Sk	Pt→Rw	Avg.
ResNet-34 [34]	✗	58.4	62.5	56.0	50.1	41.9	48.2	70.1	56.7
MME [32]	✗	70.0	67.7	69.0	56.3	64.8	61.0	76.1	66.4
CDAN [35]	✗	65.0	64.9	63.7	53.1	63.4	54.5	73.2	62.5
VDA* [37]	✗	63.5	65.7	62.6	52.7	53.6	62.0	74.9	62.1
GVB* [40]	✗	68.2	**69.0**	63.2	56.6	63.1	**62.2**	73.8	65.2
BAIT* [41]	✓	64.7	65.4	62.1	57.1	61.8	56.7	73.2	63
SHOT* [1]	✓	67.1	65.1	67.2	60.4	63	56.3	76.4	65.1
G-SFDA* [5]	✓	63.4	67.5	62.5	55.3	60.8	58.3	75.2	63.3
NRC* [2]	✓	67.5	68.0	67.8	57.6	59.3	58.7	74.3	64.7
DaC	✓	**70.0**	68.8	**70.9**	**62.4**	**66.8**	60.3	**78.6**	**68.3**

Table 3: Accuracy (%) on the Office-Home dataset (ResNet-50).

Method	SF	Ar→Cl	Ar→Pr	Ar→Rw	Cl→Ar	Cl→Pr	Cl→Rw	Pr→Ar	Pr→Cl	Pr→Rw	Rw→Ar	Rw→Cl	Rw→Pr	Avg.
ResNet-50 [34]	✗	34.9	50.0	58.0	37.4	41.9	46.2	38.5	31.2	60.4	53.9	41.2	59.9	46.1
MCD [12]	✗	48.9	68.3	74.6	61.3	67.6	68.8	57.0	47.1	75.1	69.1	52.2	79.6	64.1
CDAN [35]	✗	50.7	70.6	76.0	57.6	70.0	70.0	57.4	50.9	77.3	70.9	56.7	81.6	65.8
BNM [42]	✗	52.3	73.9	80.0	63.3	72.9	74.9	61.7	49.5	79.7	70.5	53.6	82.2	67.9
BDG [43]	✗	51.5	73.4	78.7	65.3	71.5	73.7	65.1	49.7	81.1	**74.6**	55.1	84.8	68.7
SHOT [1]	✓	56.9	78.1	81.0	67.9	78.4	78.1	67.0	54.6	81.8	73.4	58.1	84.5	71.6
G-SFDA [5]	✓	57.9	78.6	81.0	66.7	77.2	77.2	65.6	56.0	82.2	72.0	57.8	83.4	71.3
CPGA [3]	✓	**59.3**	78.1	79.8	65.4	75.5	76.4	65.7	**58.0**	81.0	72.0	**64.4**	83.3	71.6
NRC [2]	✓	57.7	**80.3**	**82.0**	68.1	**79.8**	78.6	65.3	56.4	**83.0**	71.0	58.6	**85.6**	72.2
DaC	✓	59.1	79.5	81.2	**69.3**	78.9	**79.2**	**67.4**	56.4	82.4	74.0	61.4	84.4	**72.8**

5.3 Ablation Analysis

Role of *Divide and Contrast* paradigm. To study the effectiveness of our proposed *Divide and Contrast* paradigm, we conduct contrastive learning without splitting target data. We strengthen either the local structure or the class-level global structure by two contrastive learning schemes. *Scheme-S* focuses on obtaining dicriminative class-wise clusters using a contrastive learning method in a similar manner with CPGA [3]. Specifically, the positive prototype is the class centroid $w.r.t$ the anchor's pseudo label, while the rest centroids are the negative samples. *Scheme-T* only enhances the local structure by instance discrimination learning following [22, 20], the positive prototype is the anchor's corresponding feature in memory bank, and the negative samples are the rest features in memory bank.

As shown in Table 4, both schemes improve the performance of self-training thanks to the contrastive framework. However, *Scheme-S* is vulnerable to the noisy pseudo labels while the *Scheme-T* can not further transfer the robust class-level classification into target outliers. Our method, in comparison, outperforms all the alternatives by a large margin.

Table 4: Comparison with different contrastive learning schemes in the best accuracy over 60 epochs on VisDA.

SHOT	Scheme-S	Scheme-T	DaC	Avg. (%)
✓				82.9
✓	✓			84.1
✓		✓		84.4
			✓	**87.3**

We further compare the effectiveness of our framework with the state-of-the-art SFUDA methods, in which CPGA [3] focuses on the class-level supervisions while NRC [2] focuses on the neighborhood consistency. We show the UMAP visualization results in Fig. 1, and the accuracy curve in Fig. 3. While CPGA suffers false prediction within each cluster, NRC source bias local clusters due to the loss of global context causing target error amplification. Our method can achieve fast convergence speed and stable high classification performance thanks to the effectiveness of the proposed divide and contrast scheme.

Component-wise Analysis. we conduct our ablation study by isolating each part of our method on VisDA. As the results shown in Table 5, each component of our methods helps to enhance the performance, in which the adaptive contrastive learning framework makes the most contributions to the promotion of accuracy (over 3% points). Besides, both strong augmentation and local structure enhance the local neighborhood information for each sample, which benefit the theoretical consistency $\mathcal{R}_{\mathcal{D}_T}(h)$ and im-

Figure 3: Average accuracy curve on VisDA over 60 epochs.

prove the performance. Last but not least, removing the distribution alignment degrades the average accuracy to 86.5%, which means both our linear and exponential memory-bank-based MMD are helpful. The $\mathcal{L}_{EMMD}$ outperforms $\mathcal{L}_{LMMD}$ because the non-negative exponential form is upper bound of the other, and is stable in batch training.

Table 5: Ablation study of different losses (**left**) and different modules (**right**) on VisDA.

BackBone	$\mathcal{L}_{self}$	$\mathcal{L}_{con}$	$\mathcal{L}_{LMMD}$	$\mathcal{L}_{EMMD}$	Avg.
✓					59.5
✓	✓				83.3
✓	✓	✓			86.5
✓	✓	✓	✓		87.0
✓	✓	✓		✓	**87.3**

Method	Acc
DaC	**87.3**
DaC w/o Local Structure	86.7
DaC w/o Strong Augmentation	85.6

6 Conclusion

In this paper, we have presented Divide and Contrast (DaC), a novel learning paradigm for the SFUDA problem that can inherit the advantages of (global) class-wise and (local) neighbors consistency approaches while sidestepping their limitations. The key idea is to divide the target data according to the prediction confidence of the source hypothesis (source-like v.s. target-specific) and apply customized learning strategies that can best fit the data property. We achieve this goal via a proposed adaptive contrastive learning where different groups of data samples are learned under a unified framework. We also proposed a MMD loss based on memory bank to transfer the knowledge from the source-like domain to the target-specific data. While promising performance has been achieved using our proposed approach, it would be an interesting future avenue to investigate how to extend the DaC framework to more DA tasks, e.g. semi-supervised SFUDA or source-free open-set DA.

References

[1] Jian Liang, Dapeng Hu, and Jiashi Feng. Do we really need to access the source data? source hypothesis transfer for unsupervised domain adaptation. In *International Conference on Machine Learning (ICML)*, pages 6028–6039, 2020.

[2] Shiqi Yang, Yaxing Wang, Joost van de weijer, Luis Herranz, and SHANGLING JUI. Exploiting the intrinsic neighborhood structure for source-free domain adaptation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[3] Zhen Qiu, Yifan Zhang, Hongbin Lin, Shuaicheng Niu, Yanxia Liu, Qing Du, and Mingkui Tan. Source-free domain adaptation via avatar prototype generation and adaptation. In *International Joint Conference on Artificial Intelligence*, 2021.

[4] Rui Li, Qianfen Jiao, Wenming Cao, Hau-San Wong, and Si Wu. Model adaptation: Unsupervised domain adaptation without source data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9641–9650, 2020.

[5] Shiqi Yang, Yaxing Wang, Joost van de Weijer, Luis Herranz, and Shangling Jui. Generalized source-free domain adaptation. *ICCV*, 2021.

[6] Leland McInnes, John Healy, Nathaniel Saul, and Lukas Grossberger. Umap: Uniform manifold approximation and projection. *The Journal of Open Source Software*, 3(29):861, 2018.

[7] Karsten M Borgwardt, Arthur Gretton, Malte J Rasch, Hans-Peter Kriegel, Bernhard Schölkopf, and Alex J Smola. Integrating structured biological data by kernel maximum mean discrepancy. *Bioinformatics*, 22(14):e49–e57, 2006.

[8] Eric Tzeng, Judy Hoffman, Ning Zhang, Kate Saenko, and Trevor Darrell. Deep domain confusion: Maximizing for domain invariance. *arXiv preprint arXiv:1412.3474*, 2014.

[9] Baochen Sun, Jiashi Feng, and Kate Saenko. Correlation alignment for unsupervised domain adaptation. In *Domain Adaptation in Computer Vision Applications*, pages 153–171. Springer, 2017.

[10] Werner Zellinger, Thomas Grubinger, Edwin Lughofer, Thomas Natschläger, and Susanne Saminger-Platz. Central moment discrepancy (cmd) for domain-invariant representation learning. *arXiv preprint arXiv:1702.08811*, 2017.

[11] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International conference on machine learning*, pages 1180–1189. PMLR, 2015.

[12] Kuniaki Saito, Kohei Watanabe, Yoshitaka Ushiku, and Tatsuya Harada. Maximum classifier discrepancy for unsupervised domain adaptation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3723–3732, 2018.

[13] Shuyang Dai, Yu Cheng, et al. Contrastively smoothed class alignment for unsupervised domain adaptation. In *ACCV*, 2020.

[14] Guoliang Kang, Lu Jiang, et al. Contrastive adaptation network for unsupervised domain adaptation. *CVPR*, 2019.

[15] Kuniaki Saito, Donghyun Kim, Stan Sclaroff, and Kate Saenko. Universal domain adaptation through self-supervision. In *NeurIPS*, 2020.

[16] Yixiao Ge, Feng Zhu, Dapeng Chen, Rui Zhao, and hongsheng Li. Self-paced contrastive learning with hybrid memory for domain adaptive object re-id. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 11309–11321. Curran Associates, Inc., 2020.

[17] Jiayi Tian, Jing Zhang, Wen Li, and Dong Xu. VDM-DA: virtual domain modeling for source data-free domain adaptation. *CoRR*, 2021.

[18] Youngeun Kim, Donghyeon Cho, et al. Progressive domain adaptation from a source pre-trained model. *ArXiv*, 2020.

[19] Weijie Chen, Luojun Lin, Shicai Yang, Di Xie, Shiliang Pu, Yueting Zhuang, and Wenqi Ren. Self-supervised noisy label learning for source-free unsupervised domain adaptation. *CoRR*, 2021.

[20] Aron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *CoRR*, abs/1807.03748, 2018.

[21] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. *arXiv preprint arXiv:1911.05722*, 2019.

[22] Ting Chen, Simon Kornblith, et al. A simple framework for contrastive learning of visual representations. In *ICML*, 2020.

[23] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *ECCV*, 2020.

[24] Chengxu Zhuang, Alex Lin Zhai, and Daniel Yamins. Local aggregation for unsupervised learning of visual embeddings. *CoRR*, 2019.

[25] Tianle Cai, Ruiqi Gao, Jason Lee, and Qi Lei. A theory of label propagation for subpopulation shift. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, Proceedings of Machine Learning Research. PMLR, 18–24 Jul 2021.

[26] Hong Liu, Jianmin Wang, and Mingsheng Long. Cycle self-training for domain adaptation. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 22968–22981. Curran Associates, Inc., 2021.

[27] Colin Wei, Kendrick Shen, Yining Chen, and Tengyu Ma. Theoretical analysis of self-training with deep networks on unlabeled data. *ICLR*, 2021.

[28] Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation strategies from data. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 113–123, 2019.

[29] Hemanth Venkateswara, Jose Eusebio, et al. Deep hashing network for unsupervised domain adaptation. *CVPR*, 2017.

[30] Xingchao Peng, Ben Usman, et al. Visda: The visual domain adaptation challenge. *ArXiv*, 2017.

[31] Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1406–1415, 2019.

[32] Kuniaki Saito, Donghyun Kim, Stan Sclaroff, Trevor Darrell, and Kate Saenko. Semi-supervised domain adaptation via minimax entropy. *ICCV*, 2019.

[33] Jichang Li, Guanbin Li, Yemin Shi, and Yizhou Yu. Cross-domain adaptive clustering for semi-supervised domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2505–2514, June 2021.

[34] Kaiming He, Xiangyu Zhang, et al. Deep residual learning for image recognition. *CVPR*, 2016.

[35] Mingsheng Long, Zhangjie Cao, et al. Conditional adversarial domain adaptation. In *NeruIPS*, 2018.

[36] Chen-Yu Lee, Tanmay Batra, Mohammad Haris Baig, and Daniel Ulbricht. Sliced wasserstein discrepancy for unsupervised domain adaptation. In *CVPR*, 2019.

[37] Ying Jin, Ximei Wang, et al. Minimum class confusion for versatile domain adaptation. In *ECCV*, 2020.

[38] Zhihe Lu, Yongxin Yang, Xiatian Zhu, Cong Liu, Yi-Zhe Song, and Tao Xiang. Stochastic classifiers for unsupervised domain adaptation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

[39] Shuang Li, Fangrui Lv, Binhui Xie, Chi Harold Liu, Jian Liang, and Chen Qin. Bi-classifier determinacy maximization for unsupervised domain adaptation. In *Thirty-Fifth AAAI Conference on Artificial Intelligence (AAAI-21)*, 2021.

[40] Shuhao Cui, Shuhui Wang, Junbao Zhuo, Chi Su, Qingming Huang, and Tian Qi. Gradually vanishing bridge for adversarial domain adaptation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

[41] Shiqi Yang, Yaxing Wang, Joost van de Weijer, Luis Herranz, and Shangling Jui. Casting a bait for offline and online source-free domain adaptation. *arXiv preprint arXiv:2010.12427*, 2020.

[42] Shuhao Cui, Shuhui Wang, et al. Towards discriminability and diversity: Batch nuclear-norm maximization under label insufficient situations. *CVPR*, 2020.

[43] Guanglei Yang, Haifeng Xia, et al. Bi-directional generation for unsupervised domain adaptation. In *AAAI*, 2020.