Most Activation Functions Can Win the Lottery Without Excessive Depth

Abstract

The strong lottery ticket hypothesis has highlighted the potential for training deep neural networks by pruning, which has inspired interesting practical and theoretical insights into how neural networks can represent functions. For networks with ReLU activation functions, it has been proven that a target network with depth L can be approximated by the subnetwork of a randomly initialized neural network that has double the target's depth $2L$ and is wider by a logarithmic factor. We show that a depth $L + 1$ network is sufficient. This result indicates that we can expect to find lottery tickets at realistic, commonly used depths while only requiring logarithmic overparametrization. Our novel construction approach applies to a large class of activation functions and is not limited to ReLUs.

1 Introduction

The Lottery Ticket Hypothesis [13] and, in particular, its strong version [36] postulate that pruning deep neural networks might provide a promising alternative to training large, overparameterized neural networks with Stochastic Gradient Descent (SGD). Pruning has the potential to not only identify small scale neural networks that possess a meaningful, task-specific neural network structure and generalize better due to regularization [49], but also to reduce the computational burden associated with deep learning [48, 10, 27].

Also from a theoretical perspective, it has been shown that for every small enough target network a sufficiently large, randomly initialized neural network, the source network, contains a subnetwork, the lottery ticket (LT), that can approximate the target up to acceptable accuracy with high probability. [30] has been the first to provide a probabilistic lower bound on the required network width of the larger random network. This bound has been improved by [35, 34] to a width that is larger than a target's width only by a logarithmic factor. The limitations of these works are that they all are restricted to ReLU activation functions and assume that the larger random network has twice the depth of the target network $L_s = 2L_t$.

However, it is well known that deeper networks tend to have a higher expressiveness, as they can approximate certain function classes with significantly fewer parameters than their shallow counterparts [31, 47]. It could therefore reduce the overall sparsity of the target and the LT to allow the target to utilize more of the source depth L_s for a sparser representation. A lower depth requirment could also [11] have therefore derived lower bounds for the width of the random network of depth $L_s = L_t + 1$, but these can only cover extremely sparse target networks, as the width requirement is polynomial in the inverse approximation error $1/\epsilon$.

In contrast, we derive a novel construction that only requires a logarithmic factor. While we utilize subset sum approximation results like [35], we allow a target network to have almost the same depth

as the source network with depth $L_s \geq L_t + 1$ instead of $L_s = 2L_t$. Our derivations further apply to a large class of activation functions that includes but is not limited to ReLUs.

The reduced depth requirement and flexibility in the activation function of our construction can result in significantly sparser neural network target networks and thus also LTs. For example, $f(x) = x^2$ can be approximated up to error ϵ by a shallow ReLU network with $O(1/\epsilon)$ parameters, while a deep enough network only needs $O(\log(1/\epsilon))$ parameters [31]. Also the activation function determines the possible target sparsity, e.g., x^2 can be represented with only 4 parameters for all $\epsilon > 0$ if $\phi(x) = (\max\{x, 0\})^2$. Therefore, the potential sparsity of the final lottery ticket depends critically on the choice of activation functions and architecture of the source network, including its depth and width. We provide a theoretical foundation that provides flexibility regarding these choices.

Contributions 1) We prove the existence of strong lottery tickets as subnetworks of a larger randomly initialized source neural network for a large class of activation functions, including ReLUs. 2) We derive a novel construction that requires the source network to have almost the same depth ($L + 1$) as the target network, thus, allowing it to leverage the potential representational benefits associated with larger depth. 3) Despite the reduced depth requirement we keep the width requirement logarithmic in the approximation error ϵ. 4) Our proofs are constructive and define an algorithm that approximates a given target network by pruning a source network. We verify in experiments that this algorithm is successful under realistic conditions.

Related Literature Many pruning methods have been proposed to reduce the number of neural network parameters during training [20, 33, 17, 13, 41, 22, 48, 14, 37, 26, 25, 46, 38, 6] or thereafter [39, 21, 18, 9, 24, 32, 50] and have been applied in different contexts, including graph neural networks [5] and GANs [4]. Furthermore, pruning can have provable regularization and generalization properties [49]. The algorithms are most useful for structure learning at lower sparsity levels [42, 22] but at least Iterative Magnitude Pruning (IMP) [17, 13] can fail in identifying LTs that perform superior to random or smaller dense networks [29]. It can therefore be beneficial to start pruning from a sparse random architecture rather than a dense network [10, 27], which saves computational resources. Other options to achieve the latter are to identify and train on core sets [51] and focus on pruning before training [45, 23, 44, 43, 36]. Yet, iterative pruning methods often perform better [15, 29] but all face challenges in finding highly sparse LTs [11].

Most of the discussed pruning methods try to find LTs in a 'weak' (but powerful) sense by identifying a sparse neural network architecture that is well trainable starting from its initial parameters. Strong LTs are sparse subnetworks that perform well with the initial parameters and, hence, do not need further training [52, 36]. Their existence has been proven for fully-connected feed forward networks with ReLU activation functions by providing lower bounds on the width of the large, randomly initialized source network [30, 35, 34, 12, 3]. In addition, it was shown that multiple candidate tickets exist that are also robust to parameter quantization [8]. Our first objective is to extend the known theory to other activation functions beyond ReLUs. While this approach has been transferred to convolutional and residual architectures [1], we focus here on fully-connected networks to develop the main construction ideas.

2 Constructing Lottery Tickets

Informally, our goal is to show that any deep neural network of width n_t and depth L_t or smaller can be approximated with probability $1 - \delta$ up to error ϵ by pruning a larger randomly initialized neural network of width $O(n_t \log[n_t L_t / \min\{\delta, \epsilon\}])$ and depth $2L_t$ or a network of smaller depth $L_t + 1$ and width $O(n_t \log[n_t L_t \log(1/\delta) / \min\{\delta, \epsilon\}])$, as long as the target network and the large random network rely on the same activation functions. Note that we often omit the dependence on δ in our discussions because we usually care about cases when $\epsilon < \delta$. Next we explain the required background to formalize and prove our claims.

Background and Notation Let a fully-connected feed forward neural network $f : \mathcal{D} \subset \mathbb{R}^{n_0} \to \mathbb{R}^{n_L}$ be defined on a compact domain $\mathcal{D}$ and have architecture $\bar{n} = [n_0, n_1, ..., n_L]$, i.e., depth L and width n_l in layer $l \in (0, ..., L)$, with continuous activation function $\phi(x)$. On the relevant compact domain let $\phi(x)$ have Lipschitz constant T. It maps an input vector $\boldsymbol{x}^{(0)}$ to neurons $x_i^{(l)}$ as $\boldsymbol{x}^{(l)} = \phi\left(\boldsymbol{h}^{(l)}\right)$ with $\boldsymbol{h}^{(l)} = \boldsymbol{W}^{(l)} \boldsymbol{x}^{(l-1)} + \boldsymbol{b}^{(l)}$, where $\boldsymbol{h}^{(l)}$ is the pre-activation, $\boldsymbol{W}^{(l)} \in \mathbb{R}^{n_l \times n_{l-1}}$

is the weight matrix, and $\boldsymbol{b}^{(l)} \in \mathbb{R}^{n_l}$ is the bias vector of layer l. Without loss of generality, let us assume that each parameter (weight or bias) θ is bounded as $|\theta| \leq 1$. Primarily, we distinguish three networks. First, we want to approximate a target network f_t with architecture $\bar{n}_t$ of depth L_t consisting of N_t total nonzero parameters. Second, this approximation is performed by a lottery ticket (LT) f_ϵ that is obtained by pruning a larger source network f_s, which we indicate by writing $f_\epsilon \subset f_s$. Third, this source network is a larger fully-connected feed-forward, randomly initialized neural network with architecture $\bar{n}_s$ and depth L_s. While most LT existence results require exactly $L_s = 2L_t$, we show that any $L_s \geq L_t + 1$ is sufficient.

To simplify the presentation, like most works, we assume a convenient parameter initialization that we have to choose with respect to the activation function if we approximate a target layer with two source network layers. In most cases, we make the following assumption.

Assumption 2.1 (Convenient initialization). We assume that the parameters of the source network f_s are independently distributed as $w_{ij}^{(l)} \sim U([-1, 1])$, $b_i^{(1)} \sim U([-1, 1])$ and $b_i^{(l)} = 0$ for $l > 1$.

Note that also other parameter distributions, e.g. normal distributions, are covered as long as they contain a uniform distribution [35], since this allows us to solve subset sum approximation problems (see appendix for a formal definition). While most works assume zero biases ($b_i^{(l)} = 0$), as they focus on target networks without biases [30, 35], we initialize the biases in the first layer as nonzero. This is sufficient to approximate nonzero target biases, since we can always construct constant neurons in each layer (see pink blocks in Fig. 1 (c)).

The convenient parameter initialization can always be transferred to a realistic one by learning or just applying an appropriate layer-specific scaling factor λ_l, as also proposed in LT pruning experiments [52]. For homogeneous activation functions like RELUs, even a global parameter scaling is sufficient [12]. For instance, let us assume that our initial parameters in Layer l are distributed as $U([-\sigma_l, \sigma_l])$. A common choice would be a He [19] or Glorot [16] initialization with $\sigma_l \propto 1/\sqrt{n_l}$. In this case, we would need to adapt our proofs by replacing $\{\theta^l\}$ of a LT by $\{\lambda_l \theta^l\}$ with $\lambda_l = 1/\sigma_l$ to construct the same function that we have derived for convenient initializations.

For specific activation functions with $\phi(0) \neq 0$ (e.g. SIGMOIDS), instead of Assumption 2.1, we will assume an initialization that has originally been derived to ensure dynamical isometry for RELUs [2]. Interestingly, this initialization also supports LTs.

Figure 1: LT construction idea. (a) Target network f_t. (b) $L_0 = 2L_t$ construction of f_ϵ. (c) $L_0 = L_t + 1$ construction of f_ϵ. Subset sum blocks are framed (purple corresponding to target neurons, pink to biases). Dashed links only exist if source network biases in layers $l > 1$ are initialized to zero.

Assumption 2.2 (Looks-linear initialization). We assume that the weight matrices of the source network f_s are initialized as $W^{(l)} = \begin{bmatrix} M^{(l)} & -M^{(l)} \\ -M^{(l)} & M^{(l)} \end{bmatrix}$, where $M^{(l)}$ and $b^{(l)}$ are distributed as in Assumptions 2.1.

In general, we measure the approximation error with respect to the supremum norm, which is defined as $\|g\|_\infty := \sup_{\mathbf{x} \in \mathcal{D}} \|g\|_1$ for any function g and the L1-norm $\|x\|_1 := \sum_i |x_i|$. In the formulation of theorems, we also make use of the universal constant C that can attain different values.

Lottery Tickets as Subnetworks [30] were the first to give probabilistic guarantees and provide a lower bound on the required width of the source network that is polynomial in the width of the target network. Their $O(n_t^5 L_t^2/\epsilon^2)$ requirement, or under additional sparsity assumptions $O(n_t^2 L_t^2/\epsilon^2)$, has

been improved to a logarithmic dependency of the form $O(n_t^2 \log(n_t L_t)/\epsilon)$ for weights that follow an unusual hyperbolic distribution [34] and $O(n_t \log(n_t L_t/\epsilon))$ for uniformly distributed weights [35]. While these assume target networks with zero biases, [12] transferred the approach by [35] to nonzero biases. All assume that the source network has exactly twice the depth of the target network ($L_s = 2L_t$). Only [11] prove existence for extremely sparse tickets for $L_s = L_t + 1$ but the width requirements are unrealistic for most target architectures. [3] show how to leverage additional depth $L_s \geq 2L_t$ but still assume excessive depth in general. Furthermore, all of these works focus on RELU activation functions. Both limitations, the focus on RELUs and the $L_s = 2L_t$ requirement rely on the following construction idea that is also visualized in Fig. 1(a-b). Every layer of the target network f_t is represented by two layers in the lottery ticket f_ϵ and equipped with RELU activation functions $\phi_R(x) = \max\{x, 0\}$ with the possible exception of the last output layer. We can obtain two layers by representing the identity as $x = \phi_R(x) - \phi_R(-x)$ and writing each target neuron $x_{t,i}^{(l)}$ as $x_{t,i}^{(l)} = \phi_R\left(\sum_j w_{t,ij}^{(l)} x_{t,j}^{(l-1)} + b_{t,i}^{(l)}\right) = \phi_R\left[\sum_j w_{t,ij}^{(l)} \phi_R\left(x_{t,j}^{(l-1)}\right) - w_{t,ij}^{(l)} \phi_R\left(-x_{t,j}^{(l-1)}\right) + b_{t,i}^{(l)}\right]$. The advantage of this 2-layer representation is that (a) we gain the flexibility to select the neurons in the middle layer among a higher number of available neurons in the source network and (b) these neurons are univariate so that they depend on a single nonzero parameter and are thus simple to approximate with high probability. The question is how many nodes n_0 in the middle layer of the source network are required to guarantee an accurate selection. The answer distinguishes previous work. [35] achieve a factor γ (where $n_s = \gamma n_t$) that is logarithmic in n_s, ϵ, δ, etc. by solving a separate subset sum approximation problem for each parameter utilizing results by [28]. [12] transfers these results to target networks with nonzero biases.

Our first contribution is to extend a similar construction to a wider class of activation functions that is not restricted to RELUs. We need this result to approximate at least the first layer of our target network in our second contribution, an $L + 1$-construction, as shown in Fig. 1(c). For the remaining layers, we propose to construct the subset sum blocks for the next layer directly from the previous layer by sharing nodes in the construction. This has multiple advantages. The obvious one is that we can use the available depth of the source network to start from a potentially sparser target architecture to solve a given problem. Also the LT itself consists usually of less neurons. Furthermore, the subset sum approximation of parameters becomes more efficient.

Subset Sum Approximation In the discussed construction, we generally have multiple random neurons and parameters available to approximate a target parameter z by $\widehat{z}$ up to error ϵ so that $|z - \widehat{z}| \leq \epsilon$. Let us denote the independent random variables that we can use for this approximation as $X_1, ..., X_m$. If they contain uniform distributions, Lueker [28] has shown that $m \geq C \log(1/\min\{\epsilon, \delta\})$ is sufficient for the existence of a subset $I \subset \{1..., m\}$ so that the approximation of z by $\widehat{z} = \sum_{k \in I} X_k$ is successful with probability at least $1 - \delta$. Standard distributions of interest like uniform and normal distributions as well as their products have this property [35]. For convenience, a precise corollary is stated in the appendix as Cor. A.2. Note that C depends on the distributions of the X_k and is usually larger in the two-layers-for-one than in the one-layer-for-one construction, because the X_k are given by products $X_k = w_{0,ik}^{(l+1)} w_{0,kj}^{(l)}$ in the former but $X_k = w_{0,ik}^{(l+1)}$ in the latter case.

2.1 Two Layers for One

Our first contribution is to transfer the two-layers-for-one construction to activation functions that can be different from ReLUs. We will utilize this result also in our one-layer-for-one construction to represent the first layer of the target network. This is necessary as the input neurons are fixed. We need to increase their multiplicity in the first layer of the source network to solve subset sum approximation problems that create target Layer 1 in the LT's Layer 2.

2.1.1 Activation Functions

The main property of ReLUs ϕ_R that is utilized in LT existence proofs is that we can represent the identity as $x = \phi_R(x) - \phi_R(-x)$. This identity is exact and holds for all inputs $x \in \mathbb{R}$. Yet, we can show that, in combination with the right initialization of the source network, it is sufficient if we can approximate the identity on an interval that contains 0. This approximation is feasible with most continuous activation functions that are not constant zero in a neighborhood of 0, as we detail next.

Assumption 2.3 (Activation function (first layer))**.** For any given $\epsilon' > 0$ exists a neighborhood $[-a(\epsilon'), a(\epsilon')]$ of 0 with $a(\epsilon') > 0$ so that the activation function ϕ can be approximated by $\widehat{\phi}(x)$ on that neighborhood such that $\sup_{x \in [-a,a]} |\phi(x) - \widehat{\phi}(x)| \leq \epsilon'$, where $\widehat{\phi}(x) = m_+ x + d$ for $x \geq 0$ and $\widehat{\phi}(x) = m_- x + d$ for $x < 0$ with $m_+, m_-, d \in \mathbb{R}$, and $m_+ + m_- \neq 0$. We further assume that, if $a(x)$ is finite, $g(x) = x/a(x)$ is invertible on an interval $]0, \epsilon'']$ with $\epsilon'' > 0$ and $\lim_{\to 0} g(x) = 0$.

Most continuous functions and thus most popular activation functions fulfill this assumption. For instance, RELUS $\phi_R(x) = \max(x, 0)$ inflict zero error on $\mathbb{R}$ (i.e., $a = \infty$) with $m_+ = 1$, $m_- = 0$, and $d = 0$. Similarly, LRELUS can be represented without error by $m_+ = 1$, $m_- = \alpha$, and $d = 0$ for an $\alpha > 0$. $\phi(x) = \tanh(x)$ is approximately linear so that $|\tanh(x) - x| \leq x^3/3$ for $|x| < \pi/2$, which can be seen by Taylor expansion of $\tanh$. This implies that the choice $m_+ = 1$, $m_- = 1$, and $d = 0$ with $a = \min\{(3\epsilon')^{1/3}, \pi/2\}$ fulfills our assumption. SIGMOIDS $\phi(x) = 1/(1 + \exp(-x))$ can be analyzed in the same way with $m_+ = m_- = 0.25$, $d = 0.5$, and $a = \min\{(48\epsilon')^{1/3}, \pi\}$, since $\phi(x) = (\tanh(x/2) + 1)/2$. We should point out that not all continuous functions fulfill this property. Counterexamples include a shifted ReLU $\phi(x) = \phi_R(x - 1)$ or $\phi(x) = |x|$. However, in our $L + 1$-construction, almost all activation functions can be arbitrary continuous functions. We will only ask the activation functions in the first layer to meet our assumption above. How can we represent the identity with such activation functions?

Lemma 2.4 (Representation of the identity)**.** *For any $\epsilon' > 0$, for a function $\phi(x)$ that fulfills Assumption 2.3 with $a = a(\epsilon') > 0$, and for every $x \in [-a, a]$ we have*

$$\left| x - \frac{1}{m_+ + m_-} \left(\phi(x) - \phi(-x)\right) \right| \leq \frac{2\epsilon'}{m_+ + m_-}. \tag{1}$$

Note that RELUS and LRELUS inflict no approximation error so that the above statement holds also for $\epsilon' = 0$ and $a = \infty$. Some activation functions can have other advantages over RELUS. For instance, functions for which $m_+ = m_- = m$ and $d = 0$ like TANH can also be approximated by $|x - \phi(x)/m| \leq \epsilon'/m$ and do not need separate approximations of the positive and the negative part. Furthermore, SIGMOIDS and general activation functions with $d \neq 0$ do not need nonzero biases in the source network, since we can approximate a bias by random variables of the form $X_k = w_k \phi(0)$.

The challenge in utilizing this lemma is to incorporate the error that is inflicted by the approximation of the identity in addition to the pruning error into the analysis of the total approximation error. The allowed interval size a also influences which variables can enter our subset sum blocks and could affect our width requirement if we would not initialize our parameters in the right way.

2.1.2 Lottery Ticket Existence (Two-for-One)

Our first goal is to identify a LT f_ϵ that approximates a single hidden layer neural network $f_t(x) : \mathcal{D} \subset \mathbb{R}^{n_0} \to \mathbb{R}$ with $f_t(x) = \phi_t \left(\sum_{j=1}^{n_0} w_{t,j} x_j + b_t\right)$. We could easily extend this result to approximate each layer of a multilayer neural network but we will discuss a more promising alternative that uses the following result for approximating the first layer only. f_ϵ can be obtained by pruning a fully-connected source network f_s of depth $L_s = 2$ with $n_{s,1}$ hidden neurons that are equipped with the activation function ϕ_0, which can be different from the outer ϕ_t. The additional layer in f_s has the purpose to create multiple copies of input nodes that can be used in subset sum approximations.

To achieve this despite the potential non-linear activation function ϕ_0 in the hidden layer, we have to approximate the identity with the help of ϕ_0. The precise approximation can pose two additional challenges in comparison with the standard construction for RELUS. (a) If the piece-wise linear approximation of ϕ_0 in Assumption 2.3 holds only on a finite neighborhood of 0 with $a(\epsilon) < \infty$, we can only use parameters that render the approximation valid. Thus, the success of our approach relies on an appropriate parameter initialization in the first layer of the source network f_s. (b) A nonzero intercept ($d \neq 0$) in the approximation of ϕ_0 demands for a different initialization scheme to avoid the need for large bias approximations. For simplicity, let us first assume that ϕ_0 fulfills Assumption 2.3 with zero intercept ($d = 0$).

Theorem 2.5 (LT Existence (Two-for-One))**.** *Assume that $\epsilon', \delta' \in (0, 1)$, a target network $f_t(x) : \mathcal{D} \subset \mathbb{R}^{n_0} \to \mathbb{R}^{n_1}$ with $f_{t,i}(x) = \phi_t \left(\sum_{j=1}^{n_0} w_{t,ij} x_j + b_{t,i}\right)$, and two-layer source network f_s with architecture $[n_0, n_{s,1}, n_1]$ and activation functions ϕ_0 in the first and ϕ_t in the second layer*

are given. Let ϕ_0 fulfill Assumption 2.3 with $a(\epsilon'') > 0$ and $d = 0$, ϕ_t have Lipschitz constant T_t, and $M := \max\{1, \max_{\mathbf{x} \in \mathcal{D}, i} |x_i|\}$. Let the parameters of f_s be conveniently initialized as $w_{ij}^{(1)}, b_i^{(1)} \sim U[-\sigma, \sigma]$ and $w_{ij}^{(2)} \sim U[-1/(|m_+ + m_-|\sigma), 1/(|m_+ + m_-|\sigma)]$, $b_i^{(2)} = 0$, where $\sigma = \min\left\{1, a(\epsilon'')/M\right\}$ with $\epsilon'' = g^{-1}\left(\epsilon'/\left(CT_t n_0 \frac{M}{|m_+ + m_-|} \log\left(\frac{n_0}{\min\left\{\frac{\delta'}{n_{t,1}}, \frac{\epsilon'}{T_t M}\right\}}\right)\right)\right)$. Then, with probability at least $1 - \delta'$, f_s contains a subnetwork $f_{\epsilon'} \subset f_s$ so that each output component i is approximated as $\max_{\boldsymbol{x} \in \mathcal{D}} |f_{t,i}(\boldsymbol{x}) - f_{\epsilon',i}(\boldsymbol{x})| \leq \epsilon'$ if

$$n_{s,1} \geq C n_0 \log\left(\frac{n_0}{\min\{\epsilon'/(T_t M), \delta'/n_{t,1}\}}\right).$$

Proof Outline. The construction of a LT consists of three steps. First, we prune the hidden neurons of f_s to become univariate. Second, we identify neurons in the hidden layer for which we can approximate ϕ_0 for small inputs according to Assumption 2.3. Third, if $n_{s,1}$ is large enough, we can select subsets I_j and I_b of the hidden neurons with small inputs so that we can use Cor. A.2 on subset sum approximation to approximate the parameters of the target. The resulting subnetwork of f_s is of the following form $f_{\epsilon',i}(x) = \phi_t\left(\sum_{k \in I} w_{ik}^{(2)} \phi_0\left(w_{kj}^{(1)} x_j\right) + \sum_{k \in I_b} w_{ik}^{(2)} \phi_0\left(b_k^{(1)}\right)\right)$, where $I = \cup_j I_j$ and $\sum_{k \in I_j} w_{ik}^{(2)} w_{kj}^{(1)}$ can be used to approximate $w_{t,ij}$. $f_{\epsilon,i}$ qualifies as LT if $|f_{t,i}(x) - f_{\epsilon',i}(x)| \leq \epsilon'$. A straight-forward series of bounds shows that we can achieve this if $\Delta_j = \left|w_{t,ij} x_j - \sum_{k \in I_j} w_{ik}^{(2)} \phi_0\left(w_{kj}^{(1)} x_j\right)\right| \leq \epsilon'/(T_t(n_0 + 1))$ for each j. This also applies to the approximation of $b_{t,i}$, respectively. We would like to approximate $\phi_0\left(w_{kj}^{(1)} x_j\right) \approx \mu_\pm(w_{kj}^{(1)} x_j) w_{kj}^{(1)} x_j \pm \epsilon''$, where $\mu_\pm(x) = m_+ x$ if $x \geq 0$ and $\mu_\pm(x) = m_- x$ otherwise. Note that $\mu_\pm(x) + \mu_\pm(-x) = m_+ + m_-$ for all $x \neq 0$. By construction, the activation function approximation is valid, as $|w_{kj}^{(1)} x_j| \leq M a(\epsilon'')/M = a(\epsilon'')$. Hence, we can split the error into two subset sum approximation problems and the activation function approximation error: $\Delta_j \leq M \frac{|\mu_\pm(x_j)|}{|m_+ + m_-|} |w_{t,ij} - |m_+ + m_-| \sum_{k \in I_j^+} w_{ik}^{(2)} w_{kj}^{(1)}| + M\left(1 - \frac{|\mu_\pm(x_j)|}{|m_+ + m_-|}\right)|w_{t,ij} - |m_+ + m_-| \sum_{k \in I_j^-} w_{ik}^{(2)} w_{kj}^{(1)}| + |\sum_{k \in I_j} w_{ik}^{(2)} \left(\phi_0(w_{kj}^{(1)} x_j) - \mu_\pm(w_{kj}^{(1)} x_j) w_{kj}^{(1)} x_j\right)|$, where I_j is split into indices I_j^+ for which $w_{kj}^{(1)} > 0$ and I_j^- all the ones for which $w_{kj}^{(1)} < 0$. The first two terms can be bounded according to Cor. A.2 with probability $1 - \delta''$ if $C \log\left(\frac{1}{\min\{\epsilon'/(2(n_0+1)MT_t), \delta''\}}\right)$ random variables X_k are available to choose from $I_j^\pm$, since the random variables $X_k = |m_+ + m_-| w_{ik}^{(2)} w_{kj}^{(1)}$ are distributed as $X_k \sim U[-1, 1]U[0, 1]$ or $X_k \sim U[-1, 1]U[-1, 0]$ and thus contain a uniform distribution $U[-1, 1]$ as shown by [35]. We can solve $2(n_0 + 1)n_{t,1}$ independent subset sum approximation problems with probability $1 - \delta'$ if each problem is solved with $\delta'' = \delta'/(2(n_0 + 1)n_{t,1})$ and if we have in total $C n_0 \log\left(\frac{n_0}{\min\{\epsilon'/(MT_t), \delta'/n_{t,1}\}}\right)$ random variables available. $\square$

The full proof is given in the appendix. A key result of our construction is that the activation function approximation error does not affect the width requirement. As long as we choose the scaling factor σ small enough, we can achieve a small enough error. Note that for RELUs, the above theorem reduces to known results [12], since $\sigma = 1$, $m_+ + m_- = 1$, $a = \infty$, and $d = 0$. LRELUs have the same advantageous property and are now covered in addition. The only difference is that $m_+ + m_- = 1 + \alpha$. Another new insight is that also activation functions with finite approximation support $a(\epsilon'') < \infty$ support the existence of lottery tickets with the right parameter initialization with $0 < \sigma < 1$. Interestingly, they can still achieve the same realistic width requirement.

Even though the theorem does not provide details on the universal constant, the minimum width requirement in this construction would be achieved by a linear activation function $\phi_0(x) = x$, which does not require a distinction between positive and negative $w_{kj}^{(1)}$, has $a(\epsilon'') = \infty$, does not inflict any approximation error, and is homogeneous, which makes it easy to transfer the above results to realistic parameter initialization schemes.

Remember that only ϕ_0 in the first layer needs to fulfill Ass. 2.3. ϕ_t is an arbitrary continuous function. However, it is relatively uncommon in practice to combine different activation functions in

the same neural network so that $\phi_0 \neq \phi_t$. Regardless, RELU neural networks have been observed to learn the identity in the first layers (close to the input) [40]. For these reasons it could be beneficial in general to equip at least the first layer with linear activation functions.

Also a 'looks-linear' parameter initialization can be of great benefit, in particular, if the intermediary activation function ϕ_0 has a nonzero intercept $d \neq 0$, as shown next.

Theorem 2.6 (LT Existence (Two-for-One) with Nonzero Intercept). *Thm. 2.5 applies also to activation functions ϕ_0 that fulfill Assumption 2.3 with $d \neq 0$ if the parameters are initialized according to Assumption 2.2 with $M_0^{(l)}$ distributed as the weights in Thm. 2.5.*

Proof Outline. We can closely follow the steps of the previous proof. The major difference is that we approximate $\phi_0(x) \approx \mu_{\pm}(x)x + d$ so that the activation function approximation produces an additional error term, i.e., $\left| d \sum_{k \in I_j} w_{ik}^{(2)} \right|$. In principle, we could have modified the bias subset sum approximation by approximating $b_{t,i} + d \sum_j \sum_{k \in I_j} w_{ik}^{(2)}$ instead of $b_{t,i}$. Yet, $\sum_j \sum_{k \in I_j} w_{ik}^{(2)}$ could be a large number, with which we would need to multiply our width requirement, if each $w_{ik}^{(2)}$ is initialized as in Thm. 2.5. In contrast, with the looks-linear initialization we can choose $w_{ik'}^{(2)} = -w_{ik}^{(2)}$ so that $\sum_{k \in I_j} w_{ik}^{(2)} = \sum_{k \in I_j^+} w_{ik}^{(2)} + \sum_{k' \in I_j^-} w_{ik'}^{(2)} = \sum_{k \in I_j^+} w_{ik}^{(2)} - \sum_{k \in I_j^+} w_{ik}^{(2)} = 0.$ $\qquad \square$

As for RELUS [12], we could use these results to approximate every layer of a target multi-layer feed-forward neural network for general activation functions by pruning two layers of a source network with double the depth as the target network, as visualized in Fig. 1 (b). As alternative, next we propose to prune a source network that has almost the same depth as the target network.

2.2 One Layer for One

Our second major contribution is to show how we can approximate intermediate target layers by pruning a single layer of the source network. This is achieved by connecting subset sum approximation blocks directly as visualized in Fig. 1 (c). The main idea is to create, instead of a single target neuron, ρ copies to support subset sum approximations in the next layer.

In comparison with the two-layer-for-one construction, we have to solve a higher number of subset sum approximation problems but this number is only higher by a logarithmic factor and can be integrated in the universal constant C. It is usually negligible. In total, the lottery ticket might also consist of a higher number of parameters, i.e., link weights, but a smaller number of neurons, which is the more critical case to reduce computational costs [32]. The benefits usually outweigh the costs, as we need less random variables to guaranty a successful subset sum approximation and, most importantly, can use almost the full depth of the source network to find a sparser representation of the target network. Furthermore, source networks of lower depth are easier to train and thus also more amenable to pruning algorithms that utilize gradient based algorithms.

Interestingly, we can further relax our requirements on the activation functions, as they only influence the error propagation through the network but are not involved anymore in creating random variables for the subset sum approximation problems. Let us start with the approximation of a single layer.

Theorem 2.7. *Assume that $\epsilon', \delta' \in (0,1)$, a target network layer $f_t(x) : \mathcal{D} \subset \mathbb{R}^{n_{t,l}} \to \mathbb{R}^{n_{t,l+1}}$ with $f_{t,i}(x) = \phi_t\left(\sum_{j=1}^{n_{t,l}} w_{t,ij} x_j + b_{t,i}\right)$, and one source network layer f_s with architecture $[n_{s,l+1}, n_{s,l+2}]$ and the same activation function ϕ_t are given. Let ϕ_t have Lipschitz constant T, and define $M := \max\{1, \max_{\mathbf{x} \in \mathcal{D}, i} |x_i|\}$. Let the parameters of f_s be initialized according to Assumption 2.1. Then, with probability at least $1 - \delta'$, f_s contains a subnetwork $f_{\epsilon'} \subset f_s$ so that ρ copies of each output component i are approximated as $\max_{\mathbf{x} \in \mathcal{D}} |f_{t,i}(\mathbf{x}) - f_{\epsilon',i'}(\mathbf{x})| \leq \epsilon'$ if*

$$n_{s,l+1} \geq C n_{t,l} \log \left(\frac{n_{t,l}}{\min\{\epsilon'/(MT), \delta'/(\rho n_{t,l+1})\}} \right).$$

Proof. For each target input neuron j, we assume that we can create multiple copies (with index set I_j) that we can use then as basis for subset sum approximations of target weights $w_{t,ij}^{(l+1)}$. Similarly, for biases we reserve neurons I_b in the first layer that are pruned so that we have $\phi_t(c) =$

1 or another constant. Particularly parameter efficient would be $\phi_t(0) = d$. Thus, our lottery ticket is of the form $f_{\epsilon',i'}(x) = \phi_t\Big(\sum_{j=1}^{n_{t,l}} x_j \sum_{k \in I_{i'j} \subset I_j} w_{i'k}^{(l+2)} + \sum_{k \in I_{i'b} \subset I_b} w_{i'k}^{(l+2)} \phi_t(c)\Big)$. The subsets $I_{i'j}$ and $I_{i'b}$ are chosen so that $|w_{t,ij}^{(l+1)} - \sum_{k \in I_{i'j} \subset I_j} w_{i'k}^{(l+2)}| \le \epsilon'/(MT(n_{t,l}+1))$ and $|b_{t,i}^{(l+1)} - \sum_{k \in I_{i'b} \subset I_b} w_{i'k}^{(l+2)} \phi_t(b_k^{(l+1)})| \le \epsilon'/T(n_{t,l}+1)$, which can be achieved by subset sum approximation based on the random variables $X_k = w_{i'k}^{(l+2)} \sim U[-1,1]$. In total, we have to solve maximally $\rho n_{t,l+1}(n_{t,l}+1)$ of these problems and can thus spend $\delta'/(\rho n_{t,l+1}(n_{t,l}+1))$ on each of them. Note that we only need a separate subset sum block for each input target neuron and not for its ρ copies, as we can reuse each block in the construction of each output. □

The advantage the construction above is that we can skip the approximation of the identity function. The real challenge, however, lies in the derivation of the required multiplicative factor ρ for approximating a multi-layer target network.

2.3 Multi-layer Lottery Ticket Existence

Our main result is to derive realistically achievable lower bounds on the width of a source network that has depth $L_s = L_t + 1$. To prove the existence of LTs that approximate general multi-layer target networks using the last theorems, we have to overcome two challenges. First, when we consider multiple network layers, we need to understand how much error we can afford to make in each target parameter approximation for general activation functions beyond RELUS to stay below the global error bound, as error can get amplified when signal is sent through multiple layers. Second, we need to identify the required layer-wise width scaling factor ρ in Thm. 2.7.

Lemma 2.8 (Error propagation). *Let two networks f_1 and f_2 of depth L have the same architecture and activation functions with Lipschitz constant T. Define $M_l := \sup_{x \in \mathcal{D}} \left\| \boldsymbol{x}^{(l)} \right\|_1$. Then, for any $\epsilon > 0$ we have $\|f_1 - f_2\|_\infty \le \epsilon$, if every parameter θ_1 of f_1 and corresponding θ_2 of f_2 in layer l fulfils $|\theta_1 - \theta_2| \le \epsilon_l$ for*

$$\epsilon_l := \frac{\epsilon}{n_l L}\Big[T^{L-l+1}\left(1 + M_{l-1}\right)\left(1 + \frac{\epsilon}{L}\right)\prod_{k=l+1}^{L-1}\left(\left\|W_1^{(k)}\right\|_\infty + \frac{\epsilon}{L}\right)\Big]^{-1}.$$

For suitable target networks, this requirement essentially becomes $\epsilon_l = C\epsilon/(n_l L)$. This estimate can be used in two-layers-for-one as well as one-layer-for-one LT constructions. The latter follows as our main result.

Theorem 2.9 (LT existence ($L+1$ construction)). *Assume that $\epsilon, \delta \in (0,1)$, a target network $f_t(x) : \mathcal{D} \subset \mathbb{R}^{n_0} \to \mathbb{R}^{n_L}$ with architecture $\bar{n}_t$ of depth L_t, N_t nonzero parameters, and a source network f_s with architecture $\bar{n}_s$ of depth $L_s = L_t + 1$ are given. Let ϕ_t be the activation function of f_t in the layers $l \ge 2$ of f_s with Lipschitz constant T, ϕ_0 be the activation function of the first layer of f_0 fulfilling Assumption 2.3, and $M := \max\{1, \max_{\mathbf{x} \in \mathcal{D}, l} \left\| \mathbf{x_t}^{(1)} \right\|_1\}$. Let the parameters of f_s be initialized according to Ass. 2.1 for $l > 2$ and Thm. 2.5 or 2.6 for $l \le 2$. Then, with probability at least $1 - \delta$, f_s contains a subnetwork $f_\epsilon \subset f_s$ so that each output component i is approximated as $\max_{\boldsymbol{x} \in \mathcal{D}} |f_{t,i}(\boldsymbol{x}) - f_{\epsilon',i}(\boldsymbol{x})| \le \epsilon$ if*

$$n_{s,l+1} \ge C n_{t,l} \log\left(\frac{1}{\min\{\epsilon_{l+1}, \delta/\rho\}}\right)$$

for $l \ge 1$, where ϵ_{l+1} is defined by Lemma 2.8 and $\rho = C N_t^{1+\gamma} \log(1/\min\{\min_l \epsilon_l, \delta\})$ for any $\gamma > 0$. Furthermore, we require $n_{s,1} \ge C n_{t,1} \log\left(\frac{1}{\min\{\epsilon_{l+1}, \delta/\rho\}}\right)$.

The full proof is presented in the appendix. While the layer-wise constructions are explained by the proofs of Thms. 2.6, 2.5, and 2.7, yet with updated ϵ_l, the main challenge is to determine the increased number of subset sum problems that have to be solved to derive the scaling factor ρ. Note that ρ only enters the logarithm and is negligible. By updating C, we in fact have the same asymptotic dependence $n_{s,l+1} \ge C n_{t,l} \log\left(n_{t,l} L / \min\{\epsilon, \delta\}\right)$ as in the two-layers-for-one construction.

3 Experiments

To demonstrate that our theoretical results make realistic claims, we prune for LTs that approximate a target network by following closely our constructive proofs. Solving the associated subset sum problems is NP-hard in general, as the size of the power set and thus the number of potential solutions scales exponentially in the set size m, i.e., as 2^m. However, as a set size of $m = 15$ and even smaller is sufficient for our purpose, we could solve each problem optimally by exhaustively evaluating all 2^m solutions. To reduce the size of the associated LTs, we instead identify the smallest subset consisting of up to 10 variables out of $m = 20$ to achieve an approximation error that does not exceed 0.01.

As the influential work by [13], we use Iterative Magnitude Pruning (IMP) on LeNet networks with architecture $[784, 300, 100, 10]$ to find LTs that achieve a good performance on the MNIST classification task [7]. Using the Pytorch implementation of the Gihub repository open_lth[1] with MIT license on a machine with Intel(R) Core(TM) i9-10850K CPU @ 3.60GHz processor and GPU NVIDIA GeForce RTX 3080 Ti, we arrive at a target network for each of four considered activation functions after 12 pruning steps: RELU, LRELU, SIGMOID, and TANH. Their performance and number of nonzero parameters are reported in Table 2 alongside our results for the $(L + 1)$-construction and our $2L$ construction, which achieve a similar performance. Note that, while the $L + 1$ construction relies in this case on a higher number of parameters, it uses less neurons and a smaller depth, which are the relevant criteria for fast computations and network training. Additional experiments on tiny-ImageNet and the circle problem of [11] are reported in the appendix and highlight more potential advantages of the $L + 1$-construction. We conclude that our proofs make realistic claims and identify feasible conditions for LT existence.

4 Discussion

We have shown that randomly initialized fully-connected feed forward neural networks contain lottery tickets with high probability for a wide class of activation functions by deriving two types of constructions: (a) The $(2L_t)$-construction assumes that the larger random source network has at least double the depth of the target network and is wider only by a logarithmic factor $O(n_t \log(n_t L_t / \min\{\delta, \epsilon\})$ in the approximation error and the LT existence probability. (b) The $(L_t + 1)$-construction allows for potentially sparser target network representations, as these can utilize almost the full available depth $L_s = L_t + 1$ of the source network. Remarkable about this result is that asymptotically, we can maintain the logarithmic overparametrization. It is important to note that in our MNIST experiments we constructed the same target network based on source networks with different depth. In practice however, the number of neurons and depth of the network are defined by the source network and could lead to a $L_s/2$- or a $L_s - 1$-construction of target networks with different representations. An example is provided in the appendix. The LT for the $L_t = L_s - 1$- will often consist of fewer parameters than the LT corresponding to the $L_s/2$-construction.

We have mainly discussed the case, in which the source network has exactly depth $L_s = L_t + 1$, but not all target network representations become sparser with increasing depth. What if the sparsest target representation has depth $L_t + 1 < L_s$? With the help of Lemma 2.4, we could simply add layers that approximate the identity and thus construct a target with depth $L_t = L_s - 1$. In future, it could be interesting to leverage excessive depth to distribute subset sum blocks on multiple layers instead, as it has been proposed for RELUs [3].

---

[1]https://github.com/facebookresearch/open_lth

Table 1: LT pruning results on MNIST. Averages and 0.95 standard confidence intervals are reported for 5 independent source network initializations. Parameters are counted in packs of 1000.

CONSTR.	TARGET		$L + 1$		$2L$	
	% ACC.	# PARAM.	% ACC.	# PARAM.	% ACC.	# PARAM.
RELU	97.99	18.6	97.78 ± 0.05	1106.5 ± 0.9	97.96 ± 0.02	119.2 ± 0.04
LRELU	97.88	18.6	97.63 ± 0.08	1102.4 ± 0.9	97.84 ± 0.06	119.2 ± 0.1
TANH	98.2	18.6	98.07 ± 0.07	660.3 ± 0.4	98.14 ± 0.03	67.0 ± 0.06
SIGMOID	98.08	18.6	98.08 ± 0.02	669.7 ± 0.4	98.07 ± 0.02	67.4 ± 0.05

References

[1] Rebekka Burkholz. Convolutional and residual networks provably contain lottery tickets. In *arXiv:2205.02343*, 2022.

[2] Rebekka Burkholz and Alina Dubatovka. Initialization of ReLUs for dynamical isometry. In *Advances in Neural Information Processing Systems*.

[3] Rebekka Burkholz, Nilanjana Laha, Rajarshi Mukherjee, and Alkis Gotovos. On the existence of universal lottery tickets. In *International Conference on Learning Representations*, 2022.

[4] Tianlong Chen, Yu Cheng, Zhe Gan, Jingjing Liu, and Zhangyang Wang. Data-efficient GAN training beyond (just) augmentations: A lottery ticket perspective. In *Advances in Neural Information Processing Systems*, 2021.

[5] Tianlong Chen, Yongduo Sui, Xuxi Chen, Aston Zhang, and Zhangyang Wang. A unified lottery ticket hypothesis for graph neural networks. In *International Conference on Machine Learning*, 2021.

[6] Xiaohan Chen, Yu Cheng, Shuohang Wang, Zhe Gan, Jingjing Liu, and Zhangyang Wang. The elastic lottery ticket hypothesis. In *Advances in Neural Information Processing Systems*, 2021.

[7] Li Deng. The mnist database of handwritten digit images for machine learning research. *IEEE Signal Processing Magazine*, 29(6):141–142, 2012.

[8] James Diffenderfer and Bhavya Kailkhura. Multi-prize lottery ticket hypothesis: Finding accurate binary neural networks by pruning a randomly weighted network. In *International Conference on Learning Representations*, 2021.

[9] Xin Dong, Shangyu Chen, and Sinno Jialin Pan. Learning to prune deep neural networks via layer-wise optimal brain surgeon. In *Advances in Neural Information Processing Systems*, 2017.

[10] Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners. In *International Conference on Machine Learning*, 2020.

[11] Jonas Fischer and Rebekka Burkholz. Plant 'n' seek: Can you find the winning ticket? In *International Conference on Learning Representations*, 2022.

[12] Jonas Fischer, Advait Gadhikar, and Rebekka Burkholz. Lottery tickets with nonzero biases, 2021.

[13] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2019.

[14] Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In *International Conference on Machine Learning*, 2020.

[15] Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Pruning neural networks at initialization: Why are we missing the mark? In *International Conference on Learning Representations*, 2021.

[16] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *International Conference on Artificial Intelligence and Statistics*, volume 9, pages 249–256, May 2010.

[17] Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. In *Advances in Neural Information Processing Systems*, 2015.

[18] Babak Hassibi and David G. Stork. Second order derivatives for network pruning: Optimal brain surgeon. In *International Conference on Neural Information Processing Systems*, 1992.

[19] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

[20] Yann LeCun, John Denker, and Sara Solla. Optimal brain damage. In *Advances in Neural Information Processing Systems*, 1990.

[21] Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pages 598–605, 1990.

[22] Namhoon Lee, Thalaiyasingam Ajanthan, Stephen Gould, and Philip H. S. Torr. A signal propagation perspective for pruning neural networks at initialization. In *International Conference on Learning Representations*, 2020.

[23] Namhoon Lee, Thalaiyasingam Ajanthan, and Philip H. S. Torr. Snip: single-shot network pruning based on connection sensitivity. In *International Conference on Learning Representations*, 2019.

[24] Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient convnets. In *International Conference on Learning Representations*, 2017.

[25] Ning Liu, Geng Yuan, Zhengping Che, Xuan Shen, Xiaolong Ma, Qing Jin, Jian Ren, Jian Tang, Sijia Liu, and Yanzhi Wang. Lottery ticket preserves weight correlation: Is it desirable or not? In *International Conference on Machine Learning*.

[26] Ning Liu, Geng Yuan, Zhengping Che, Xuan Shen, Xiaolong Ma, Qing Jin, Jian Ren, Jian Tang, Sijia Liu, and Yanzhi Wang. Lottery ticket preserves weight correlation: Is it desirable or not? In *International Conference on Machine Learning*, 2021.

[27] Shiwei Liu, Tianlong Chen, Xiaohan Chen, Zahra Atashgahi, Lu Yin, Huanyu Kou, Li Shen, Mykola Pechenizkiy, Zhangyang Wang, and Decebal Constantin Mocanu. Sparse training via boosting pruning plasticity with neuroregeneration. In *Advances in Neural Information Processing Systems*, 2021.

[28] George S. Lueker. Exponentially small bounds on the expected optimum of the partition and subset sum problems. *Random Structures & Algorithms*, 12(1):51–62, 1998.

[29] Xiaolong Ma, Geng Yuan, Xuan Shen, Tianlong Chen, Xuxi Chen, Xiaohan Chen, Ning Liu, Minghai Qin, Sijia Liu, Zhangyang Wang, and Yanzhi Wang. Sanity checks for lottery tickets: Does your winning ticket really win the jackpot? In *Advances in Neural Information Processing Systems*, 2021.

[30] Eran Malach, Gilad Yehudai, Shai Shalev-Schwartz, and Ohad Shamir. Proving the lottery ticket hypothesis: Pruning is all you need. In *International Conference on Machine Learning*, 2020.

[31] Hrushikesh Mhaskar, Qianli Liao, and Tomaso Poggio. When and why are deep networks better than shallow ones? In *AAAI Conference on Artificial Intelligence*, page 2343–2349, 2017.

[32] Pavlo Molchanov, Stephen Tyree, Tero Karras, Timo Aila, and Jan Kautz. Pruning convolutional neural networks for resource efficient inference. In *International Conference on Learning Representations*, 2017.

[33] Michael C Mozer and Paul Smolensky. Skeletonization: A technique for trimming the fat from a network via relevance assessment. In *Advances in Neural Information Processing Systems*, 1989.

[34] Laurent Orseau, Marcus Hutter, and Omar Rivasplata. Logarithmic pruning is all you need. *Advances in Neural Information Processing Systems*, 33, 2020.

[35] Ankit Pensia, Shashank Rajput, Alliot Nagle, Harit Vishwakarma, and Dimitris Papailiopoulos. Optimal lottery tickets via subset sum: Logarithmic over-parameterization is sufficient. In *Advances in Neural Information Processing Systems*, volume 33, pages 2599–2610, 2020.

[36] Vivek Ramanujan, Mitchell Wortsman, Aniruddha Kembhavi, Ali Farhadi, and Mohammad Rastegari. What's hidden in a randomly weighted neural network? In *Computer Vision and Pattern Recognition*, pages 11893–11902, 2020.

[37] Alex Renda, Jonathan Frankle, and Michael Carbin. Comparing rewinding and fine-tuning in neural network pruning. In *International Conference on Learning Representations*, 2020.

[38] Pedro Savarese, Hugo Silva, and Michael Maire. Winning the lottery with continuous sparsification. In *Advances in Neural Information Processing Systems*, 2020.

[39] Pedro Savarese, Hugo Silva, and Michael Maire. Winning the lottery with continuous sparsification. In *Advances in Neural Information Processing Systems*, 2020.

[40] Wenling Shang, Kihyuk Sohn, Diogo Almeida, and Honglak Lee. Understanding and improving convolutional neural networks via concatenated rectified linear units. In *International Conference on International Conference on Machine Learning*, 2016.

[41] Suraj Srinivas and R. Venkatesh Babu. Generalized dropout. *CoRR*, abs/1611.06791, 2016.

[42] Jingtong Su, Yihang Chen, Tianle Cai, Tianhao Wu, Ruiqi Gao, Liwei Wang, and Jason D Lee. Sanity-checking pruning methods: Random tickets can win the jackpot. In *Advances in Neural Information Processing Systems*, 2020.

[43] Hidenori Tanaka, Daniel Kunin, Daniel L. Yamins, and Surya Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. In *Advances in Neural Information Processing Systems*, 2020.

[44] Stijn Verdenius, Maarten Stol, and Patrick Forré. Pruning via iterative ranking of sensitivity statistics, 2020.

[45] Chaoqi Wang, Guodong Zhang, and Roger B. Grosse. Picking winning tickets before training by preserving gradient flow. In *International Conference on Learning Representations*, 2020.

[46] Andreas Weigend, David Rumelhart, and Bernardo Huberman. Generalization by weight-elimination with application to forecasting. In *Advances in Neural Information Processing Systems*, 1991.

[47] Dmitry Yarotsky. Optimal approximation of continuous functions by very deep relu networks. In *Conference On Learning Theory*, pages 639–649, 2018.

[48] Haoran You, Chaojian Li, Pengfei Xu, Yonggan Fu, Yue Wang, Xiaohan Chen, Richard G. Baraniuk, Zhangyang Wang, and Yingyan Lin. Drawing early-bird tickets: Toward more efficient training of deep networks. In *International Conference on Learning Representations*, 2020.

[49] Shuai Zhang, Meng Wang, Sijia Liu, Pin-Yu Chen, and Jinjun Xiong. Why lottery ticket wins? a theoretical perspective of sample complexity on sparse neural networks. In *Advances in Neural Information Processing Systems*, 2021.

[50] Zeru Zhang, Jiayin Jin, Zijie Zhang, Yang Zhou, Xin Zhao, Jiaxiang Ren, Ji Liu, Lingfei Wu, Ruoming Jin, and Dejing Dou. Validating the lottery ticket hypothesis with inertial manifold theory. In *Advances in Neural Information Processing Systems*, 2021.

[51] Zhenyu Zhang, Xuxi Chen, Tianlong Chen, and Zhangyang Wang. Efficient lottery ticket finding: Less data is more. In *International Conference on Machine Learning*, 2021.

[52] Hattie Zhou, Janice Lan, Rosanne Liu, and Jason Yosinski. Deconstructing lottery tickets: Zeros, signs, and the supermask. In *Advances in Neural Information Processing Systems*, pages 3597–3607, 2019.