FUND: Density Flow for Sampling Unnormalised Distributions

Abstract

Efficient sampling from Boltzmann distributions is central to modelling complex physical systems. Markov Chain Monte Carlo (MCMC) methods suffer from critical slowing down, high autocorrelation, and poor mode-mixing, limiting their scalability. Recent advances, like Boltzmann Generators, offer a promising alternative but remain constrained by costly MCMC-based training, inefficient sampling, and poor ergodicity. We introduce an algorithm for learning Boltzmann distributions that does not require any true samples for training. Our approach draws inspiration from flow matching but departs fundamentally from sample-trajectory matching to distribution-trajectory matching. The algorithm iteratively reshapes the target distribution, using model generated samples to guide learning and ensure comprehensive mode coverage. We validate our method on standard benchmarks, including a 2D Gaussian mixture, Many-Well distributions, and high-dimensional scalar ϕ^4 theory. Our approach not only outperforms traditional MCMC and flow-based methods in efficiency and accuracy but also establishes a new method for sample-free learning of complex physical distributions.

1 Introduction

Sampling from unnormalized probability distributions plays a crucial role in understanding and characterizing the behavior of physical systems. In many scientific disciplines, including statistical physics (Gibbs, 2010; Goto et al., 2018), quantum mechanics (Temme et al., 2011), computational chemistry (Noe et al., 2019) and biological sciences (Frauenfelder et al., 1991; Bryngelson et al., 1995), these systems are often represented by Boltzmann distributions, which capture the probabilistic structure of states based on their energy levels.

Sampling such distributions defined as $p(\mathbf{x}) \propto e^{-E(\mathbf{x})}$ with complex energy landscapes in high dimensions pose significant challenges. Traditional samplers such as Markov chain Monte Carlo (MCMC) (Hastings, 1970; Andrieu et al., 2003; Neal, 2011) and Molecular dynamics (MD) (Leimkuhler & Matthews, 2012) proceed via local perturbations, often resulting in slow convergence, high computational cost and poor mode mixing due to a high energy barrier between metastable states. Advances in deep generative models (Song & Ermon, 2019; Song et al., 2020; Wang et al., 2021; Papamakarios et al., 2021; Kobyzev et al., 2021; Lipman et al., 2022; Máté & Fleuret, 2023; Cao et al., 2024; Zhang et al., 2025) have enabled efficient sampling from such distributions and improved the fidelity of generated samples, across several applications in statistical mechanics and biological sciences (Noe et al., 2019; Albergo et al., 2019; Nicoli et al., 2021; Hoogeboom et al., 2022; Watson et al., 2023; Midgley et al., 2023; Akhound-Sadegh et al., 2024; Kanaujia et al., 2024; Zheng et al., 2024; Wang et al., 2024; Njirjak et al., 2024; Ünlü et al., 2025). However, these models typically based on likelihood estimation (Kingma & Welling, 2014; Van den Oord et al., 2016; Dinh et al., 2017; Papamakarios et al., 2021), adversarial learning (Goodfellow et al., 2014; Arjovsky & Bottou, 2017; Singh et al., 2021), or stochastic regression (Ho et al., 2020; Song et al., 2020) remain highly data-intensive, requiring large training datasets to achieve reliable performance. This limitation is often mitigated by falling back to MCMC or MD methods to generate the training data.

Among these approaches, Normalizing flows (NFs) (Papamakarios et al., 2021), which support exact likelihood evaluation and efficient sample generation, are particularly well suited for approximating Boltzmann

distributions. Their flexibility allows training either from samples of the target distribution ($p(\mathbf{x})$) or directly from the underlying energy function. When samples are available, NFs are typically optimized via the forward KL divergence ($\mathcal{KL}(p\|q_\theta)$), which encourages coverage of all modes but tends to overweight low-probability configurations, a well-known mode-covering effect (Nicoli et al., 2023; Kanaujia & Arora, 2025). In the absence of samples, NFs can instead be trained by minimizing the reverse KL divergence ($\mathcal{KL}(q_\theta\|p)$), requiring only energy evaluations up to an additive constant. While this energy-based objective allows learning without data, it biases the model toward a few low-energy regions and the samples generated from the model fail to be ergodic. This phenomenon is referred to as mode collapse (Kanaujia et al., 2024; Midgley et al., 2023). Consequently, despite their advantages, conventional NF training objectives often fail to fully capture the complexity of high-dimensional Boltzmann distributions.

These limitations have prompted growing interest in training strategies that bypass the need for target-distribution samples and rely instead on direct evaluations of the underlying energy function. Such methods aim to build more accurate approximations of the target distribution that can then be used as high-quality proposal distribution. Within this research direction, leading approaches include Flow Annealed Importance Sampling Bootstrap (FAB) (Midgley et al., 2023) and Iterated Denoising Energy Matching (iDEM) (Akhound-Sadegh et al., 2024), both of which employ energy-driven objectives to iteratively enhance the accuracy of the model. FAB couples normalizing flows with annealed importance sampling (AIS), using AIS-generated samples to progressively learn the modelled distribution. While effective in moderate-dimensional settings, this reliance on AIS introduces substantial computational overhead and limits scalability to high dimensions. In contrast, iDEM relies on Monte Carlo (MC) sampling to estimate score. For sampling, it requires solving a reverse SDE, which is computationally expensive. Additionally, iDEM does not yield likelihoods directly: it trains a separate optimal-transport conditional flow-matching model (Tong et al., 2023) on its generated samples, and the reverse ODE of this model is then used to compute negative log-likelihoods (Akhound-Sadegh et al., 2024). This two-stage pipeline is computationally expensive. Moreover, the likelihoods are only approximate and do not ensure bias correction when used with importance weighting or Independent Metropolis Hastings (Kanaujia et al., 2024; Noe et al., 2019).

In this work, we draw inspiration from the framework of Flow Matching (FM) (Lipman et al., 2022) which models the path that a point takes through the evolving probability distribution. This point is realized as a sample that can be seen as carrying a portion of the probability mass. In other words, FM models a way of diffusing or transporting the probability mass from one distribution to another through a continuous transformation using *per sample* paths.

Here, we use this idea of continuous transformations and sample paths to train a tractable sampler $q(\mathbf{x})$, without using any true samples. Let $p_t(\mathbf{x})$ be the continuous density transformation, with $p_1(\mathbf{x}) = p(\mathbf{x})$, the given target distribution, and $p_0(\mathbf{x})$ be a unimodal initial distribution which is easy to sample. Instead of modeling the trajectory of samples with respect to t (as in flow matching), we model the density q_t as a function of t so as to obtain accurate and efficient computation of model density during inference.

Our approach proceeds iteratively, gradually advancing from $t \to 0$ to $t = 1$. At any $t + \delta t$, we generate samples from q_t and re-weight them to learn the distribution $p_{t+\delta t}$ in a supervised way, for example, using weighted FKL or score matching. In addition, we also use sample free objective to learn from the target distribution $p_{t+\delta t}$, for example, RKL. The density trajectories p_t are constructed in such a way that the modes separate gradually. We start with a single mode at $t \to 0$. As t increases, these modes sharpen and separate and our proposed method ensures that q_t learns all the modes. The reweighted samples stabilize the learning as t evolves.

Unlike continuous-time flow matching approaches that learn and integrate a time-dependent velocity field through ODE dynamics, the proposed framework instead learns successively annealed intermediate distributions, progressively transporting probability mass toward the target distribution without requiring continuous-time integration.

We evaluate our proposed approach on three families of unnormalized distributions. The results demonstrate that our method achieves competitive performance for deep learning–based sample generation from unnormalized target distributions, enabling training without access to true samples that would otherwise require computationally expensive MCMC or molecular-dynamics (MD) simulations.

2 Proposed Method

In this section, we outline the proposed approach. We build on the NF framework (Papamakarios et al., 2021) to model complex target distributions by continuously transforming samples drawn from a simple prior into those of the desired distribution through a smooth and invertible mapping. Let $\mathbf{z} \sim q_z(\mathbf{z})$ be sampled from the prior distribution, and let its continuous transformation be $f_t(\mathbf{z}; \theta), t \in [0, 1]$ such that $\mathbf{x} = f_t(\mathbf{z}; \theta)$ should follow $p_t(\mathbf{x})$. The modelled density q_t is given by

$$q_t(\mathbf{x}; \theta) = q_z(f_t^{-1}(\mathbf{x}))|\det[\frac{\partial f_t^{-1}(\mathbf{x})}{\partial \mathbf{x}}]| \tag{1}$$

In contrast to traditional flow-matching methods, which learn the time-dependent trajectories of individual samples, we instead model the evolving density q_t directly as a function of t. This formulation enables accurate and computationally efficient evaluation of the model density during inference. To learn the corresponding transformation, we train f_t by minimizing the loss

$$\mathcal{L}(\theta) = \mathbb{E}_{\mathbf{x} \sim p_t}[d(p_t(\mathbf{x}), q_t(\mathbf{x}))] \tag{2}$$

where θ parameterizes f_t, thereby determining q_t, and d denotes a distance measure between the densities p_t and q_t. For d, we can use f-divergence or the Fisher divergence. Since samples from $p_t(\mathbf{x})$ are not directly available, we use importance weighting on the samples from $q_{t'}(\mathbf{x}), t' < t$.

$$\mathcal{L}(\theta) = \mathbb{E}_{\mathbf{x} \sim q_{t'}}[w(\mathbf{x})d((p_t(\mathbf{x}), q_t(\mathbf{x})))] \tag{3}$$

where $w(\mathbf{x}) = \frac{p_t(\mathbf{x})}{q_{t'}(\mathbf{x})}$. $q_{t'}$ is learnt inductively starting from q_0. Keeping t' closer to t ensures that $w(\mathbf{x})$ remains close to unity, thereby improving numerical stability.

Likelihood- and score-driven objectives typically encourage mode-covering behaviour (Lyu, 2009; Midgley et al., 2023; Kanaujia et al., 2024; Kanaujia & Arora, 2025), often diluting the representation of high-probability regions. To counterbalance this tendency, we introduce an additional reverse KL term in the loss, whose intrinsic mode-seeking behaviour encourages concentration around dominant regions of the distribution. By combining these opposing tendencies, the overall objective balances exploration and concentration, ensuring that all modes are effectively captured.

$$\mathcal{L}_{\mathcal{RKL}}(\theta) = \mathbb{E}_{\mathbf{x} \sim q_t} \log \frac{q_t(\mathbf{x})}{p_t(\mathbf{x})} \tag{4}$$

The final objective function is given by:

$$\mathcal{L}_{final}(\theta) = \lambda_1 \mathcal{L}(\theta) + \lambda_2 \mathcal{L}_{\mathcal{RKL}}(\theta) \tag{5}$$

In this expression, the coefficients λ_1 and λ_2 correspond to hyperparameters, the specifics of which are elaborated in Section 2.3. The overall learning procedure proceeds as follows. Starting from a simple unimodal distribution $q_z(\mathbf{z})$, we define a continuous family of densities $\{p_t(\mathbf{x})\}_{t \in (0,1]}$ that transforms smoothly into the target distribution. The target distribution $p_1(\mathbf{x})$ may be highly multi-modal, but the flow is designed so that its modes appear gradually as t increases (see Figure 2). The model then propagates samples through these intermediate distributions and learns progressively, beginning with lower values of t and advancing toward $t = 1$.

At $t = 0$, the distribution q contains only a single mode. As t increases, additional modes gradually emerge, capturing the increasing complexity of the evolving distribution. Samples drawn from q_t carry information from all these modes, ensuring a smooth transition between distributions over time and effectively preventing mode collapse. In the following, we detail the main components of the proposed method, FUND.

2.1 Designing Intermediate Distribution p_t

FUND uses a normalising flow to gradually transform the prior as defined in Eq. (1). Rather than modelling individual sample trajectories as in flow matching, FUND models the trajectory of distributions $q_t(x; \theta)$. It learns q_t iteratively using samples from the learnt distribution $q_{t'}$ (with $t' < t$) weighted by importance weights. t' and t are kept sufficiently close to maintain low-variance estimates. We define target trajectory as $p_t(x) \propto p(x)^t$, where $p(x)$ denotes the target distribution. This construction suppresses the peaks and smoothes out the modes for small t, substantially reducing the complexity of the distribution and making it easier to learn without missing any mode. As t gradually increases, the modes of p_t sharpen and separate. Figure 2 shows the intermediate target distributions p_t for the 1-D Gaussian mixture, demonstrating the progressive sharpening and separation of modes as t grows.

In our experiments, we approximate the continuous time parameter by discretising the interval $(0, 1]$ into N ordered points $0 < t_1 < t_2 < \cdots < t_N = 1$.

2.2 Distance Measure with Importance Weighting

To learn each intermediate distribution, we employ distance measures (refer Eq. (2)) defined with respect to p_t, specifically the forward KL divergence and the Fisher divergence. Since direct samples from p_t are not available, we adopt an importance-weighting strategy based on samples drawn from the previously learned distribution $q_{t'}, t' < t$. For sufficiently small increments in t, the distribution $q_{t'}$ closely approximates p_t, ensuring adequate support overlap and stable importance weights. This enables reliable estimation of both divergence objectives and facilitates the sequential learning of the model across time. Using importance weighting, the forward KL objective can be estimated as

$$\mathcal{L}_{FKL}(\theta) = -\mathbb{E}_{x \sim q_{t'}(x)}[w(x) \log q_t(x)] \tag{6}$$

where $w(x) = \frac{p_t(x)}{q_{t'}(x)}$ denotes the importance weight. Similarly, the Fisher divergence objective (Hyvärinen, 2005) can be written as

$$\mathcal{L}_{\text{score}}(\theta) = \frac{1}{2} \mathbb{E}_{x \sim q_{t'}(x)} \left[w(x) \left\| \nabla_x \log q_t(x; \theta) - \nabla_x \log p_t(x) \right\|^2 \right]. \tag{7}$$

Here, $\nabla_x \log q_t(x; \theta)$ is computed via automatic differentiation of the model likelihood.

2.3 Sequential Modeling Strategy

Several implementation choices exist for FUND. One possible implementation is to construct the model incrementally: A new NF coupling block is appended whenever t is incremented and is trained to minimise the loss in Eq. (5) while the previous blocks are frozen. This design is memory-inefficient and fails to learn all modes of the target distribution as detailed in the Appendix B.

Another implementation is a single-block architecture refined across all time steps. Training proceeds sequentially: the model is first optimised as q_{t_1} with p_{t_1} as the target. At subsequent t, the same model is optimised as q_t with p_t as the target. This strategy enables significant memory savings and facilitates incremental learning (Figure 2.2).

Initial training: Learning begins at $t_1 > 0$, where $\mathcal{L}(\theta)$ is unknown due to the absence of training samples from p_{t_1}. We therefore set $\lambda_1 = 0$ and optimize only $\mathcal{L}_{RKL}$. The choice of a small t_1 results in a unimodular density p_{t_1} with broadened support, and is easy to learn.

Sample Buffer: To ensure efficient reuse of samples during the progression from t_1 to t_N, we implement a persistent buffer of size B maintained throughout training. At t_1, the buffer is populated by transforming prior samples into the intermediate distribution q_{t_1} and saving both the transformed samples and their corresponding log-likelihoods $\log q_{t_1}$. These stored pairs enable the computation of importance weights when training the subsequent distribution q_{t_2}.

Figure 1: (A) Progressive learning of successive intermediate distributions within a unified flow model using iterative sample reuse. Here $t' > t$, and samples generated from q_t are reused to train $q_{t'}$. Latent samples from $q_z(z)$ are used to compute $\mathcal{L}_{\mathcal{RKL}}(\theta)$, while replay-buffer samples together with $\log q_t(x)$ and $\log p_{t'}(x)$ are used to compute $\mathcal{L}(\theta)$ (B) Illustrates sample generation procedure using the trained flow model.

Reusing the samples of $q_{t'}$ to learn $q_t, t > t'$ can be made efficient and effective by using a prioritised replay buffer (Schaul et al., 2016), which tends to retain samples from different modes and reduces computations. Replay buffers in continual learning are widely used to mitigate catastrophic forgetting by reusing samples from previously learned distributions during subsequent optimization steps Lesort (2020); Rolnick et al. (2019). In FUND, the persistent sample buffer continuously reuses samples from earlier intermediate distributions while optimizing later distributions, thereby reinforcing previously learned modes and reducing distributional drift across annealing stages.

Besides, the optimization objective $\mathcal{L}_{final}(\theta)$ integrates $\mathcal{L}_{\mathcal{RKL}}(\theta)$ with $\mathcal{L}(\theta)$ which is either FKL or score-matching supervision. The RKL term uses current transformed samples, whereas the supervision loss leverages samples from previously learned distributions stored in the buffer. As FKL and score-based objectives encourage learning across multiple modes Kanaujia & Arora (2025); Kanaujia et al. (2024), the framework empirically maintains stable mode coverage without requiring explicit prioritised replay and mitigate catastrophic forgetting. Thus, we did not need a prioritised replay buffer. We use a uniform replay buffer to store the samples and log-likelihood of $q_{t'}$. While incrementing $t' \to t$, the buffer is updated with samples from $q_{t'}$.

Hyperparameter annealing: The training objective incorporates a weighted combination of $\mathcal{L}(\theta)$ and $\mathcal{L}_{RKL}(\theta)$. The optimization begins in a sample-driven regime with $\lambda_1 \gg \lambda_2$, enabling propagation of the modal structure encoded by samples from $q_{t'}$. At each t, an annealing schedule gradually reduces λ_1 and increases λ_2 based on $-\mathbb{E}_{q_t} \log p_t(x)$, thereby transitioning toward a mode-sharpening phase in which the RKL term enhances mode separation and corrects residual density discrepancies. For more details, refer Appendix C.

Algorithm 1 outlines the training procedure of FUND, which progressively learns a sequence of intermediate distributions. The method employs buffering to compute importance weights and reuse samples for learning at subsequent time steps. During training, the hyperparameters λ_1 and λ_2, which weight the loss components $\mathcal{L}(\theta)$ and $\mathcal{L}_{RKL}(\theta)$, are annealed to ensure stable and accurate convergence at each time step.

3 Results

We assess the proposed approach using three metrics: Negative Log-Likelihood (NLL), Reverse Negative Log-Likelihood (RNLL), and Effective Sample Size (ESS).

Figure 2: Visualisation of intermediate annealed target distributions $p_t(\mathbf{x}) \propto p(\mathbf{x})^t$ for a 1-D Gaussian mixture model. As t increases, the density gradually transitions from a smoothed, low-contrast form to the fully resolved target distribution. The panel shows 1-D plot for: (A) $t_1 = 0.01$, (B) $t_2 = 0.1$, (C) $t_3 = 0.2$, and (D) $t_N = 1$.

NLL measures how effectively a model fits the observed samples via predicted likelihoods. Lower NLL estimates indicate a model closer to the true distribution.

$$\text{NLL} = -\mathbb{E}_{\mathbf{x} \sim p} \log q(\mathbf{x}) \tag{8}$$

RNLL, in conjunction with NLL, provides insight into the model's behaviour across modes. A high NLL accompanied by a low RNLL suggests mode collapse, whereas low NLL and high RNLL reflects broad mode coverage. When both metrics attain low values, the model is well aligned with the target distribution.

$$\text{RNLL} = -\mathbb{E}_{\mathbf{x} \sim q} \log p(\mathbf{x}) \tag{9}$$

ESS quantifies how much independent information is effectively represented by a weighted sample set and is defined as

$$\text{ESS} = \frac{(\frac{1}{N} \sum_i p(\mathbf{x}_i)/q(\mathbf{x}_i))^2}{\frac{1}{N} \sum_i (p(\mathbf{x}_i)/q(\mathbf{x}_i))^2} \tag{10}$$

Higher values indicate improved sample diversity and independence.

We compare the proposed framework against four established baselines. (A) **FKL**: An NF model trained by minimising the forward KL divergence (FKL), equivalent to maximum-likelihood estimation and therefore requiring direct samples from the target distribution. (B) **RKL**: An NF model trained using the reverse

Figure 3: Sample plots for the MOG-40 distribution generated using different methods alongside the corresponding ground-truth samples. These plots illustrate the mode-coverage behavior discussed in the quantitative results and highlight the ability of different methods to preserve the multimodal structure of the target distribution during sampling. (A) Ground-truth samples. (B) FKL. (C) RKL. (D) IDEM. (E) FAB. (F) Proposed FUND(SCORE) method.

KL divergence (RKL). (C) **FAB** (Midgley et al., 2023) trains the flow by minimising an α-divergence, with expectations approximated using samples generated via AIS. (D) **iDEM** (Akhound-Sadegh et al., 2024) uses stochastic score-matching objective to learn the model. As IDEM does not provide closed-form likelihoods, we approximate its NLL by training an optimal transport conditional flow matching (OT-CFM) model (Tong et al., 2023) on the empirical distribution of iDEM-generated samples.

For the proposed method, we investigate two variants distinguished by the choice of distance measure (d) in Eq. (2): **FUND(FKL)**, which employs the forward KL divergence, and **FUND(SCORE)**, which adopts a score-matching based objective. We evaluate the methods across three benchmark Boltzmann distributions as follows:

3.1 Mixture of Gaussian (MOG-40)

The MOG-40 benchmark comprises a 2-D mixture of 40 Gaussian components with modes scattered over the range $[-50, 50]$ in both dimensions. This produces a complex, widely separated modal structure that can be clearly visualised from the sample plots. Further information, including the analytical definition of the distribution, is provided in Appendix A.1.

We report the results for the MOG-40 benchmark in Table 1. Both FUND variants perform better than competing methods on MOG-40. FUND(SCORE) provides the best likelihood fit—achieving the lowest NLL—and simultaneously delivers the second-best ESS, signifying strong coverage of the multimodal landscape. FUND(FKL) achieves comparable performance, being slightly worse in NLL and exhibiting slightly higher ESS values compared to FUND(SCORE), but still substantially outperforming all baselines. While FKL and FAB obtain moderate NLL values, their ESS scores reveal high correlation among the generated samples. IDEM also achieves the lowest NLL, albeit with a comparatively low ESS value. RKL exhibits severe degradation in NLL, consistent with its strongly mode-seeking behaviour. Although RKL yields the lowest RNLL values, this result is meaningful only when considered alongside the corresponding NLL. The combination of poor NLL and good RNLL reveals mode collapse, where the model generates samples from only a few modes, artificially inflating RNLL performance. FUND variants achieve better RNLL scores as compared to those of FKL, and FAB, reflecting better alignment with the target distribution. Representative

Table 1: Evaluation results for the MOG-40, MW-8, and MW-16 distributions, using the metrics described in Section 3. Best results are highlighted in bold and second best are underlined.

	MOG-40			MW-8			MW-16		
Method	NLL↓	RNLL↓	ESS↑	NLL↓	RNLL↓	ESS↑	NLL↓	RNLL↓	ESS↑
FKL	$7.16_{\pm 0.02}$	$7.87_{\pm 0.06}$	$0.63_{\pm 0.01}$	$7.60_{\pm 0.05}$	$-31.60_{\pm 0.77}$	$0.34_{\pm 0.02}$	$17.14_{\pm 0.07}$	$-48.57_{\pm 5.77}$	$0.001_{\pm 0.004}$
RKL	$3527.06_{\pm 106.44}$	$7.07_{\pm 0.25}$	$0.42_{\pm 0.26}$	$76.72_{\pm 73.84}$	$-35.40_{\pm 0.01}$	$\mathbf{0.97}_{\pm 0.03}$	$604.83_{\pm 85.65}$	$-70.80_{\pm 0.06}$	$\mathbf{0.83}_{\pm 0.06}$
FAB	$7.14_{\pm 0.03}$	$8.30_{\pm 0.29}$	$0.63_{\pm 0.06}$	$7.00_{\pm 0.02}$	$-33.87_{\pm 0.10}$	$0.81_{\pm 0.01}$	$14.28_{\pm 0.01}$	$-66.53_{\pm 0.13}$	$0.31_{\pm 0.02}$
IDEM	$\mathbf{7.09}_{\pm 0.28}$	$7.01_{\pm 0.30}$	$0.42_{\pm 0.03}$	$7.64_{\pm 0.09}$	$-34.86_{\pm 0.02}$	$0.55_{\pm 0.03}$	$15.32_{\pm 0.43}$	$-70.08_{\pm 0.36}$	$0.25_{\pm 0.03}$
FUND(FKL)	$7.11_{\pm 0.03}$	$7.53_{\pm 0.10}$	$\mathbf{0.68}_{\pm 0.03}$	$6.97_{\pm 0.01}$	$-34.25_{\pm 0.04}$	$0.87_{\pm 0.02}$	$14.04_{\pm 0.05}$	$-67.95_{\pm 0.25}$	$0.71_{\pm 0.04}$
FUND(SCORE)	$\mathbf{7.09}_{\pm 0.01}$	$7.53_{\pm 0.01}$	$0.67_{\pm 0.01}$	$\mathbf{6.95}_{\pm 0.01}$	$-34.20_{\pm 0.04}$	$0.90_{\pm 0.01}$	$\mathbf{13.93}_{\pm 0.02}$	$-68.35_{\pm 0.12}$	$0.78_{\pm 0.02}$

Figure 4: Sample plots of intermediate distributions q_t learned for the MOG-40 distribution, illustrating the gradual transformation induced by the flow model over t. Panels show sample plots for distribution : (A) q_{t_1} at $t_1 = 0.01$ (B) q_{t_2} at $t_2 = 0.05$ (C) q_{t_N} at $t_N = 1.0$ and (D) the target distribution p.

sample visualizations for the MOG-40 distribution generated by different methods are shown in Figure 3, further illustrating the mode-coverage behavior discussed in the quantitative results.

In Figure 4, we illustrate the progression of training using sample plots drawn from the intermediate distributions. At an early time step ($t_1 = 0.01$), the distribution exhibits overlapping modes with a broadened support compared to the target. As training proceeds to $t_2 = 0.05$, the samples from q_{t_1} are used to learn the next intermediate distribution. The sample plot of q_{t_2} shows increasingly sharper and more distinct modes, indicating that the flow gradually refines and preserves the underlying structure.

3.2 Many-Well Potential

In sampling tasks, Many-Well Potential (Midgley et al., 2023) represents a benchmark distribution with an energy function characterized by several metastable wells. Sampling from the associated Boltzmann distribution becomes challenging as transitions between wells require overcoming energy barriers, leading to slow mixing and pronounced multimodality. We evaluate our method on 8- and 16-dimensional Many-Well distributions. Appendix A.2 provides the analytical form of the distribution along with other details regarding quantitative evaluation.

Across all baselines, and as demonstrated in Table 1, the proposed method, FUND(SCORE) consistently attains the best well-rounded performance in terms of NLL, RNLL, and ESS. The FUND(FKL) variant performs at par with FUND(SCORE), demonstrating its effectiveness as well.

3.3 Scalar ϕ^4 Theory distribution

Scalar ϕ^4 theory (Albergo et al., 2019; Singha et al., 2023) is a classical benchmark model in statistical physics and quantum field theory, characterized by a quartic term in its potential. The resulting Boltzmann distribution is highly multimodal, making it a challenging testbed for evaluating sampling algorithms. The corresponding energy function is specified in Appendix A.3. For quantitative analysis, we generate a test set comprising 10,000 samples via HMC. The associated hyperparameter settings are described in the appendix.

Table 2: Scalar ϕ^4 distribution results, with metrics described in Section 3. Best results are highlighted in bold and second best are underlined.

Method	8 × 8			10 × 10			12 × 12		
	NLL↓	RNLL↓	ESS↑	NLL↓	RNLL↓	ESS↑	NLL↓	RNLL↓	ESS↑
FKL	13.40$_{\pm\ 0.07}$	-9.48$_{\pm\ 0.59}$	0.06$_{\pm\ 0.01}$	22.01$_{\pm\ 0.08}$	-17.60$_{\pm\ 0.19}$	0.01$_{\pm\ 0.00}$	29.89$_{\pm\ 0.07}$	-32.86$_{\pm\ 0.58}$	0.02$_{\pm\ 0.004}$
RKL	23.18$_{\pm\ 0.19}$	-18.75$_{\pm\ 0.44}$	0.08$_{\pm\ 0.05}$	29.01$_{\pm\ 1.01}$	-29.32$_{\pm\ 0.78}$	**0.70**$_{\pm\ 0.04}$	38.55$_{\pm\ 8.29}$	-41.32$_{\pm\ 0.23}$	0.29$_{\pm\ 0.02}$
FAB	13.19$_{\pm\ 0.21}$	-5.14$_{\pm\ 0.59}$	0.10$_{\pm\ 0.05}$	21.47$_{\pm\ 0.22}$	-1.05$_{\pm\ 0.86}$	0.0001$_{\pm\ 0.00}$	31.44$_{\pm\ 0.60}$	-31.06$_{\pm\ 8.35}$	0.09$_{\pm\ 0.07}$
IDEM	23.76$_{\pm\ 1.05}$	-23.17$_{\pm\ 2.70}$	0.004$_{\pm\ 0.004}$	38.13$_{\pm\ 2.13}$	-25.64$_{\pm\ 7.12}$	0.004$_{\pm\ 0.004}$	65.84$_{\pm\ 4.44}$	-15.82$_{\pm\ 3.63}$	0.003$_{\pm\ 0.005}$
FUND(FKL)	12.48$_{\pm\ 0.21}$	-13.94$_{\pm\ 1.52}$	0.14$_{\pm\ 0.04}$	19.59$_{\pm\ 0.03}$	-17.54$_{\pm\ 0.83}$	0.14$_{\pm\ 0.01}$	28.74$_{\pm\ 0.17}$	-35.49$_{\pm\ 1.29}$	0.33$_{\pm\ 0.14}$
FUND(SCORE)	**12.29**$_{\pm\ 0.06}$	-14.95$_{\pm\ 0.74}$	**0.32**$_{\pm\ 0.02}$	**19.45**$_{\pm\ 0.04}$	-15.06$_{\pm\ 0.62}$	0.15$_{\pm\ 0.01}$	**28.66**$_{\pm\ 0.04}$	-36.88$_{\pm\ 0.75}$	**0.55**$_{\pm\ 0.02}$

Results for the scalar ϕ^4 model across different lattice sizes are summarised in Table 2. Across all settings, the proposed framework consistently outperforms established baselines. On the 8×8 lattice, the FUND(SCORE) variant achieves the lowest NLL and the highest ESS, indicating substantially improved sampling efficiency and mode coverage, while FUND(FKL) also surpasses all baselines on both metrics. At 10×10, the performance gap widens: FUND(SCORE) again attains the best NLL and ESS, with FUND(FKL) closely following. Although RKL yields a moderately high ESS and RNLL, its NLL remains significantly worse, highlighting an imbalance between its mode-seeking behaviour and overall distribution accuracy. In the largest configuration, 12×12 (144 dimensional distribution), the proposed method maintains strong performance, with FUND(SCORE) achieving the best NLL and ESS, and FUND(FKL) also outperforming all baselines. By contrast, the baselines degrade substantially with increasing dimensionality: FKL, FAB, and IDEM exhibit severe reductions in ESS, while RKL exhibits poor likelihood fit despite moderate ESS values and good RNLL values, learning only a few dominant modes. Overall, the proposed approach, particularly FUND(SCORE), exhibits consistent performance across increasing lattice sizes, thereby demonstrating scalability and superior density estimation capability for high-dimensional Boltzmann distributions arising in lattice field theory.

4 Discussion

In this work, we introduce the idea of gradually shaping the target distribution over time rather than evolving sample trajectories. The flow learns a sequence of intermediate distributions, with each providing samples for the next, resulting in a more accurate approximation of the target distribution. Evaluations on a broad suite of Boltzmann distributions—MOG-40, Many-Well, and scalar ϕ^4 theory—demonstrate the effectiveness of the proposed method, with results consistently surpassing existing state-of-the-art approaches.

In general, it is preferable to begin with a small initial value of t_1, but choosing the small value increases the computational cost. Hence, there is a trade-off. However, we find that for high-dimensional distributions with low multimodality, a larger t_1 can be used without affecting performance, offering computational savings. For example, in Tables 1 and 2, we begin with $t_1 = 0.01$ for MOG-40, $t_1 = 0.1$ for Many well and $t_1 = 0.2$ for the ϕ^4 theory. But a larger t_1 may lead to mode collapse in highly multi-modal distributions. For example, in MOG-40, starting with $t_1 = 0.1$ results in missed modes, and this early error propagates to later stages, causing the model to learn only a subset of the modes.

In our setup, t lies in $(0, 1]$, and we discretize this interval into N steps. Larger values of N allow smoother progression between intermediate distributions but at a higher computational cost. Smaller values reduce training time but result in mild performance drops. This trade-off is analysed empirically in Table 5 of the Appendix C.

In the Figure 5, we present the evolution of the test NLL with respect to t for the scalar ϕ^4 and MW-16 benchmarks, thereby visualising the learning progression over intermediate distributions. Both the variants of FUND consistently exhibit monotonic improvement in NLL. In both cases, the most significant NLL gains occur during the early stages of the transition between successive intermediate distributions, with improvements gradually tapering off as the model converges toward the target distribution at $t = 1$.

Our findings indicate that FUND maintains strong efficiency even for high-dimensional probability distributions. In the scalar ϕ^4 theory, where dimensionality grows substantially with lattice size, the method

delivers consistently strong performance across all evaluation metrics. This contrasts with several baseline approaches, many of which exhibit pronounced degradation as dimensionality increases (Table 2). The stability of FUND under rising complexity highlights its robustness and its ability to model high-dimensional, multimodal Boltzmann distributions without loss of fidelity.

FUND introduces additional sequential optimization stages due to progressive annealing across intermediate distributions. However, this staged optimization improves stability and mode coverage by gradually transporting the model from simpler intermediate densities toward the final multimodal target distribution. As observed in Tables 1 and 2, this sequential distributional learning improves NLL and ESS performance while mitigating mode-collapse behavior. Once training is complete, FUND enables efficient parallel sample generation through a single forward pass of the trained flow model.

In comparison, FAB incurs additional computational overhead from repeated Annealed Importance Sampling (AIS) steps used during optimization to generate training samples across intermediate distributions. This overhead becomes increasingly significant in higher-dimensional settings. In contrast, IDEM has comparatively lower training cost but slower inference, since sample generation requires numerically simulating the reverse-time stochastic differential equation (SDE) using the learned diffusion sampler. MCMC-based methods exhibit the opposite trade-off: they require little or no training cost but incur high inference cost because samples must be generated sequentially through Markov chain transitions, with computational cost scaling directly with the number of generated samples.

Overall, the experiments suggest that FUND achieves a favorable cost-accuracy trade-off. Although training is more expensive than single-stage flow optimization, the sequential annealing strategy substantially improves sample quality and mode coverage while still retaining fast parallel inference after training.

The mode-seeking behavior induced by training with the reverse KL divergence is well documented across variational inference, generative modeling, and Bayesian learning (MacKay, 2003; Bishop & Nasrabadi, 2006). Such behavior often leads to biased approximations, underestimates uncertainty, and insufficient exploration of the global structure of complex distributions—limitations that become especially severe in high-dimensional settings (Blei et al., 2017; Yao et al., 2018). The framework proposed in this work provides an alternative mechanism that mitigates these issues: it reduces the risk of mode collapse, preserves broader support coverage, and enables reliable distribution learning even where reverse KL–based methods typically struggle.

This contribution is also relevant to Bayesian inference, where posterior sampling for complex models is still dominated by classical MCMC techniques such as Metropolis–Hastings, Gibbs sampling, and Hamiltonian-based algorithms (Brooks et al., 2011; Neal, 2011). While theoretically principled, these methods often suffer from slow mixing and difficulty in traversing well-separated modes. By supplying a transport-based mechanism capable of capturing the evolving structure of the posterior, FUND offers a pathway toward scalable, amortized, and adaptable sampling.

Finally, the methodology resonates strongly with challenges encountered in lattice field theory, QCD, and gauge-theoretic simulations, where sampling remains highly demanding due to extreme dimensionality, strong correlations, and gauge constraints (Gattringer & Lang, 2009; DeGrand & DeTar, 2006). The corresponding Boltzmann distributions exhibit long autocorrelation times and complex action landscapes, making standard algorithms—such as Hamiltonian Monte Carlo—susceptible to critical slowing down and topological trapping, particularly near the continuum limit (Schaefer et al., 2011). These persistent difficulties underscore the need for more flexible sampling strategies that maintain gauge fidelity while improving exploration efficiency. Our approach directly addresses these requirements and therefore holds significant potential for future applications in lattice and gauge-theoretic contexts.

The primary constraint of the proposed framework lies in its sequential learning procedure, which requires the model to progress through intermediate distributions one stage at a time. While computational cost can be reduced by using fewer intermediates, this must be balanced against the need to maintain smooth structural evolution of the distribution; overly coarse discretization may disrupt the transition dynamics and hinder accurate learning.

Figure 5: Test negative log-likelihood (NLL) trajectories over t for the scalar ϕ^4 and MW-16 benchmarks. The curves compare the performance of FUND(SCORE) and FUND(FKL) across intermediate target densities.

5 Conclusion

This work presents FUND, a novel learning framework for training NFs on unnormalised target distributions without requiring access to true target samples. Unlike existing sample-driven approaches, the proposed method progressively shapes the model distribution through a sequence of intermediate distributions of increasing complexity. By using importance weighted samples from the intermediate distributions, FUND achieves stable learning, comprehensive mode coverage, and tractable likelihood evaluation.

The effectiveness of the proposed approach is demonstrated across several challenging benchmarks, including MOG-40, Many-Well, and scalar ϕ^4 theory. The results show that FUND consistently outperforms state-of-the-art approaches, particularly in high-dimensional and highly multimodal settings. Overall, this work establishes FUND as a robust and scalable framework for learning complex unnormalised distributions without reliance on target samples.

References

Tara Akhound-Sadegh, Jarrid Rector-Brooks, Joey Bose, Sarthak Mittal, Pablo Lemos, Cheng-Hao Liu, Marcin Sendera, Siamak Ravanbakhsh, Gauthier Gidel, Yoshua Bengio, et al. Iterated denoising energy matching for sampling from boltzmann densities. In *International Conference on Machine Learning*, pp. 760–786. PMLR, 2024.

M. S. Albergo, G. Kanwar, and P. E. Shanahan. Flow-based generative models for markov chain monte carlo in lattice field theory. *Physical Review D*, 100:034515, 2019.

Christophe Andrieu, Nando de Freitas, Arnaud Doucet, and Michael I. Jordan. An introduction to mcmc for machine learning. *Machine Learning*, 50:5–43, 2003.

Martin Arjovsky and Leon Bottou. Towards principled methods for training generative adversarial networks. In *International Conference on Learning Representations*, 2017.

Christopher M Bishop and Nasser M Nasrabadi. *Pattern recognition and machine learning*, volume 4. Springer, 2006.

David M Blei, Alp Kucukelbir, and Jon D McAuliffe. Variational inference: A review for statisticians. *Journal of the American statistical Association*, 112:859–877, 2017.

Steve Brooks, Andrew Gelman, Galin Jones, and Xiao-Li Meng. *Handbook of markov chain monte carlo*. CRC press, 2011.

Joseph D. Bryngelson, José Nelson Onuchic, Nicholas D. Socci, and Peter G. Wolynes. Funnels, pathways, and the energy landscape of protein folding: A synthesis. *Proteins: Structure, Function, and Bioinformatics*, 21:167–195, 1995.

Hanqun Cao, Cheng Tan, Zhangyang Gao, Yilun Xu, Guangyong Chen, Pheng-Ann Heng, and Stan Z Li. A survey on generative diffusion models. *IEEE transactions on knowledge and data engineering*, 36: 2814–2830, 2024.

Thomas DeGrand and Carleton DeTar. *Lattice Methods for Quantum Chromodynamics*. World Scientific Publishing Co. Pte. Ltd., 2006.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real NVP. In *International Conference on Learning Representations*, 2017.

Hans Frauenfelder, Stephen G. Sligar, and Peter G. Wolynes. The energy landscapes and motions of proteins. *Science*, 254:1598–1603, 1991.

Christof Gattringer and Christian Lang. *Quantum chromodynamics on the lattice: an introductory presentation*, volume 788. Springer Science & Business Media, 2009.

Josiah Willard Gibbs. *Elementary Principles in Statistical Mechanics: Developed with Especial Reference to the Rational Foundation of Thermodynamics*. Cambridge University Press, 2010.

Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Proceedings of the 28th International Conference on Neural Information Processing Systems-Volume 2*, pp. 2672–2680, 2014.

Hayato Goto, Zhirong Lin, and Yasunobu Nakamura. Boltzmann sampling from the ising model using quantum heating of coupled nonlinear oscillators. *Scientific Reports*, 8:7154, 2018.

W. K. Hastings. Monte carlo sampling methods using markov chains and their applications. *Biometrika*, 57: 97–109, 1970.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851, 2020.

Emiel Hoogeboom, Vıctor Garcia Satorras, Clément Vignac, and Max Welling. Equivariant diffusion for molecule generation in 3d. In *International conference on machine learning*, pp. 8867–8887. PMLR, 2022.

Aapo Hyvärinen. Estimation of non-normalized statistical models by score matching. *Journal of Machine Learning Research*, 6:695–709, 2005.

Vikas Kanaujia and Vipul Arora. Scorenf: Score-based normalizing flows for sampling unnormalized distributions. *arXiv preprint arXiv:2510.21330*, 2025.

Vikas Kanaujia, Mathias S Scheurer, and Vipul Arora. Advnf: Reducing mode collapse in conditional normalising flows using adversarial learning. *SciPost Physics*, 16:132–160, 2024.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014.

Ivan Kobyzev, Simon J.D. Prince, and Marcus A. Brubaker. Normalizing flows: An introduction and review of current methods. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43:3964–3979, 2021.

B. Leimkuhler and C. Matthews. Rational construction of stochastic numerical methods for molecular sampling. *Applied Mathematics Research eXpress*, 2013:34–56, 2012.

Timothée Lesort. Continual learning: Tackling catastrophic forgetting in deep neural networks with replay processes. *arXiv preprint arXiv:2007.00487*, 2020.

Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. Flow matching for generative modeling. In *The Eleventh International Conference on Learning Representations*, 2022.

Siwei Lyu. Interpretation and generalization of score matching. In *Proceedings of the Twenty-Fifth Conference on Uncertainty in Artificial Intelligence*, pp. 359–366, 2009.

David JC MacKay. *Information theory, inference and learning algorithms*. Cambridge university press, 2003.

Bálint Máté and François Fleuret. Learning interpolations between boltzmann densities. *Transactions on Machine Learning Research*, 2023.

Laurence Illing Midgley, Vincent Stimper, Gregor NC Simm, Bernhard Schölkopf, and José Miguel Hernández-Lobato. Flow annealed importance sampling bootstrap. In *International Conference on Learning Representations*, 2023.

Radford M. Neal. *MCMC Using Hamiltonian Dynamics*, pp. 113–162. Chapman and Hall/CRC, 2011.

Kim A Nicoli, Christopher J Anders, Lena Funcke, Tobias Hartung, Karl Jansen, Pan Kessel, Shinichi Nakajima, and Paolo Stornati. Estimation of thermodynamic observables in lattice field theories with deep generative models. *Physical review letters*, 126:032001, 2021.

Kim A Nicoli, Christopher J Anders, Tobias Hartung, Karl Jansen, Pan Kessel, and Shinichi Nakajima. Detecting and mitigating mode-collapse for flow-based sampling of lattice field theories. *Physical Review D*, 108:114501, 2023.

Marko Njirjak, Lucija Žužić, Marko Babić, Patrizia Janković, Erik Otović, Daniela Kalafatovic, and Goran Mauša. Reshaping the discovery of self-assembling peptides with generative ai guided by hybrid deep learning. *Nature Machine Intelligence*, 6:148–1500, 2024.

Frank Noe, Simon Olsson, Jonas Kohler, and Hao Wu. Boltzmann generators: Sampling equilibrium states of many-body systems with deep learning. *Science*, 365:1147, 2019.

George Papamakarios, Eric Nalisnick, Danilo Jimenez Rezende, Shakir Mohamed, and Balaji Lakshminarayanan. Normalizing flows for probabilistic modeling and inference. *Journal of Machine Learning Research*, 22:1–64, 2021.

David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy Lillicrap, and Gregory Wayne. Experience replay for continual learning. *Advances in neural information processing systems*, 32, 2019.

Stefan Schaefer, Rainer Sommer, and Francesco Virotta. Critical slowing down and error analysis in lattice qcd simulations. *Nuclear Physics B*, 845:93–119, 2011.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *International Conference on Learning Representations (ICLR)*, 2016.

Japneet Singh, Mathias S Scheurer, and Vipul Arora. Conditional generative models for sampling and phase transition indication in spin systems. *SciPost Physics*, 11:043–071, 2021.

Ankur Singha, Dipankar Chakrabarti, and Vipul Arora. Conditional normalizing flow for markov chain monte carlo sampling in the critical region of lattice field theory. *Phys. Rev. D*, 107:014512, 2023.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in neural information processing systems*, 32, 2019.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2020.

K. Temme, T. J. Osborne, K. G. Vollbrecht, D. Poulin, and F. Verstraete. Quantum metropolis sampling. *Nature*, 471:87–90, 2011.

Alexander Tong, Nikolay Malkin, Guillaume Huguet, Yanlei Zhang, Jarrid Rector-Brooks, Kilian FATRAS, Guy Wolf, and Yoshua Bengio. Improving and generalizing flow-based generative models with minibatch optimal transport. In *ICML Workshop on New Frontiers in Learning, Control, and Dynamical Systems*. PMLR, 2023.

Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. *Advances in neural information processing systems*, 29, 2016.

Lingxiao Wang, Gert Aarts, and Kai Zhou. Diffusion models as stochastic quantization in lattice field theory. *Journal of High Energy Physics*, 2024(5):1–30, 2024.

Zhengwei Wang, Qi She, and Tomás E. Ward. Generative adversarial networks in computer vision: A survey and taxonomy. *ACM Computing Surveys*, 54:1–38, 2021.

Joseph L. Watson, David Juergens, Nathaniel R. Bennett, Brian L. Trippe, Jason Yim, Helen E. Eisenach, Woody Ahern, Andrew J. Borst, Robert J. Ragotte, Lukas F. Milles, Basile I. M. Wicky, Nikita Hanikel, Samuel J. Pellock, Alexis Courbet, William Sheffler, Jue Wang, Preetham Venkatesh, Isaac Sappington, Susana Vázquez Torres, Anna Lauko, Valentin De Bortoli, Emile Mathieu, Sergey Ovchinnikov, Regina Barzilay, Tommi S. Jaakkola, Frank DiMaio, Minkyung Baek, and David Baker. De novo design of protein structure and function with rfdiffusion. *Nature*, 620:1089–1100, 2023.

Yuling Yao, Aki Vehtari, Daniel Simpson, and Andrew Gelman. Yes, but did it work?: Evaluating variational inference. In *International Conference on Machine Learning*, pp. 5581–5590. PMLR, 2018.

Fengzhe Zhang, Laurence Illing Midgley, and José Miguel Hernández-Lobato. Efficient and unbiased sampling from boltzmann distributions via variance-tuned diffusion models. *Transactions on Machine Learning Research*, 2025.

Shuxin Zheng, Jiyan He, Chang Liu, Yu Shi, Ziheng Lu, Weitao Feng, Fusong Ju, Jiaxi Wang, Jianwei Zhu, Yaosen Min, He Zhang, Shidi Tang, Hongxia Hao, Peiran Jin, Chi Chen, Frank Noé, Haiguang Liu, and Tie-Yan Liu. Predicting equilibrium distributions for molecular systems with deep learning. *Nature Machine Intelligence*, 6:558–567, 2024.

Atabey Ünlü, Elif Çevrim, Melih Gökay Yiğit, Ahmet Sarıgün, Hayriye Çelikbilek, Osman Bayram, Deniz Cansen Kahraman, Abdurrahman Olğaç, Ahmet Sureyya Rifaioglu, Erden Banoğlu, and Tunca Doğan. Target-specific de novo design of drug candidate molecules with graph-transformer-based generative adversarial networks. *Nature Machine Intelligence*, 7:1524–1540, 2025.

A Distributions

In this section, we briefly discuss the distributions that we modelled.

A.1 Mixture of Gaussian (MOG-40)

It is defined as a mixture of 40 Gaussian components in $\mathbb{R}^2$. The density function is given by

$$p(\mathbf{x}) = \sum_{i=1}^{N} a_i \, \mathcal{N}(\mathbf{x}; \boldsymbol{\mu}_i, \Sigma_i), \tag{11}$$

with mixture weights $a_i > 0$, means $\boldsymbol{\mu}_i \in \mathbb{R}^2$, and covariance matrices $\Sigma_i \in \mathbb{R}^{2 \times 2}$. For the MOG-40 specification, we choose $a_i = 1/40$, sample $\boldsymbol{\mu}_i \sim \mathcal{U}(-40, 40)$, and set $\Sigma_i = I$. This produces a structured multimodal distribution suitable for evaluation. We generate a test set of 5,000 samples following Midgley et al. (2023) with a fixed seed of 2000. In addition, the FKL baseline requires data for model training. We therefore also generate 10,000 samples for training, together with 5,000 samples for validation.

A.2 Many-Well Distribution

It is a synthetic distribution constructed as the product of $d/2$ independent copies of the two-dimensional double-well distribution (Noe et al., 2019), where d denotes the dimensionality of the space. This construction produces an exponentially large number of modes ($2^{d/2}$), making the distribution challenging for density estimation and sampling tasks. Its energy function is given by

$$H(\mathbf{x}) = \sum_{i=1}^{d/2} \left(x_{2i-1}^4 - 6x_{2i-1}^2 - 0.5x_{2i-1} + 0.5x_{2i}^2 \right), \quad \mathbf{x} \in \mathbb{R}^d \tag{12}$$

To study performance across increasing multimodality, we experiment with both MW-8 and MW-16. Using rejection sampling, as in Midgley et al. (2023), we generate 10,000 test samples, along with an additional 10,000 training and 10,000 validation samples for the FKL baseline for each distribution.

A.3 Scalar ϕ^4 theory distribution

It is a fundamental lattice field theory model widely used in computational physics to study interacting scalar fields, renormalisation, symmetry breaking, and critical phenomena. A real scalar field $\mathbf{x}$ defined on a two-dimensional square lattice with d sites is characterised by the energy function

$$H(\mathbf{x}) = \sum_{l=1}^{d} \left(\lambda x_l^4 + m^2 x_l^2 + 2 \sum_{l' \in n(l)} (x_l^2 - x_l x_{l'}) \right) \tag{13}$$

The set $n(l)$ identifies the two nearest neighbours of each site l. Here, λ parameterises the quartic self-interaction, while m specifies the mass term. This is commonly used as a benchmark in numerical simulations and sampling studies. To study the proposed method across different system scales, we conduct experiments on three lattice sizes: 8×8, 10×10, and 12×12. Following the setup in Singha et al. (2023), samples are drawn using HMC (Neal, 2011) with parameters $\lambda = 4$ and $m^2 = -4$. The integrator uses a step size of 0.05 and 20 leapfrog steps per trajectory. We discard the first 1,000 samples on account of thermalization. A total of 10,000 samples are generated for testing, and for the FKL baseline, we additionally generate 10,000 training and 10,000 validation samples.

B Model details

In this section, we provide an overview of the model architecture used in our experiments. As discussed under modelling strategy in Section 2, we first explored an incremental modelling strategy. In this setup, with the increment of the time parameter t, we add new coupling blocks atop the previously trained ones, allowing the model to progressively learn the intermediate distributions. During training, the model encounters difficulties at intermediate time instants, leading to missed modes and results in degradation of test NLL. Furthermore, the incremental construction is inherently memory-inefficient. Besides, each added coupling block required

Table 3: Comparison between incremental modelling and single block modelling on MOG-40.

Modelling strategy	NLL($\downarrow$)
Incremental Modelling	7.69
Single Block Modelling	**7.07**

Table 4: Summary of the NF architecture configurations used across different distributions.

Distribution	# Affine Coupling Blocks	F or D
MOG-40	16	320
MW-8	12	512
MW-16	12	512
Scalar $\phi^4(8 \times 8)$	10	256
Scalar $\phi^4(10 \times 10)$	12	256
Scalar $\phi^4(12 \times 12)$	12	256

training from scratch, while previously learned blocks remained frozen, limiting overall training efficiency. Hence, we adopt another efficient implementation that employs a single-block model (see in Figure 2.2) refined across all time steps. Starting with the optimisation of q_{t_1} toward p_{t_1}, the same block is subsequently updated for each later t. This approach greatly reduces memory usage and enables incremental learning. Our experiments on the MOG-40 distribution also support this. The incremental modelling strategy produces a considerably higher NLL, while single block implementation delivers improved performance, as summarised in Table 3. Throughout the paper, we use the single block implementation for FUND.

We implement the model using the RNVP architecture as in Dinh et al. (2017) using Affine coupling blocks. For the MOG-40 and Many-Well distributions defined in $\mathbb{R}^d$ space, the affine coupling block is realized using fully connected (dense) networks. Each coupling block consists of two dense layers, each comprising D hidden units equipped with ReLU activation functions. The network then branches into two output layers corresponding to the scale s and translation t. The scale layer uses a `tanh` activation to output the scaling factors, while the translation layer provides a linear output.

For the scalar ϕ^4 distribution, the field x is defined on a 2D square lattice with $d = N_1 \times N_1$ sites. The affine coupling block is implemented using convolutional layers: two convolutional layers with F filters of size 3×3, periodic padding, and ReLU activation. The output then branches into two layers—one producing the scale s and the other the translation t. Each layer uses a single 3×3 filter, with tanh activation applied to the scale and a linear activation applied to the translation. Table 4 summarizes the affine coupling configurations used across all distributions, including the number of coupling blocks and the corresponding filter count F (for convolutional layers) and neuron count D (for dense layers).

For MOG-40, MW-8, and MW-16, we adopt a batch size of 512, whereas for the scalar ϕ^4 theory distribution we use a batch size of 256. All models are trained with the Adam optimizer and an initial learning rate of 1×10^{-5}. The learning rate is lowered during the final stages, specifically for the last two time instants, t_{N-1} and t_N.

For baseline models FAB and IDEM, we primarily followed the architectures, optimizer settings, and training procedures recommended in the respective original papers and official repositories. In addition, we performed limited hyperparameter tuning to ensure stable convergence and competitive performance on our benchmark distributions.

Since both FAB and FUND are flow-based methods, we kept the normalizing-flow (NF) architectures identical wherever possible to ensure a fair comparison. In particular, the NF configurations for FUND and FAB were matched for the scalar ϕ^4 experiments. Complete architectural details are provided in Table 4 of Appendix B.

For MOG-40, MW-8 and MW-16, we used the recommended settings reported in the original FAB paper and official implementation repository.

For FAB, hyperparameter tuning primarily involved the number of intermediate annealing distributions and the number of MCMC transition steps. In the ϕ^4 experiments, we used HMC as the transition operator with 4 intermediate distributions and 5 MCMC transition steps. The learning rate was fixed at 1×10^{-4}.

Similarly, for IDEM, we largely followed the official implementation and only performed limited tuning for the ϕ^4 experiments, including learning rate, batch size, and model depth/width within reasonable ranges. We used an MLP architecture consisting of 4 hidden layers with 512 neurons per layer and sinusoidal embeddings of dimension 512. The learning rate was fixed at 1×10^{-4}. The remaining hyperparameter settings were adopted from the original repository.

For the remaining baselines, namely FKL and RKL, we used the same RealNVP architecture as employed in FUND to ensure a fair comparison across flow-based models.

We did not perform exhaustive large-scale hyperparameter searches for any method. All methods were trained under comparable computational budgets and hardware settings to ensure a fair empirical comparison. The rest of the hyperparameter details would be subsequently shared on the FUND github repo asap.

C Hyperparameter Selection and Tuning

The proposed approach introduces several hyperparameters that shape its learning dynamics, including the number of intermediate distributions that determine the transition path, the initial timestep that affects early-mode coverage, the buffer size used for storing training samples, and the weights that govern how the two loss terms contribute at different stages of optimization (Eq. (5)).

The selection of N is particularly impactful and plays an important role in shaping of intermediate distributions. It determines how finely the $t \in (0, 1]$ is discretized. Larger N allows for smoother interpolation, albeit at increased computational cost. Smaller values improve efficiency but lead to reduced performance. In Table 5, we report the impact of different values of N on the 8×8 scalar ϕ^4 theory distribution. As N increases, performance consistently improves across metrics, highlighting that smoother transitions between intermediates enhance both fidelity and sampling efficiency.

Table 5: Results for the scalar ϕ^4 model distribution on an 8×8 lattice, illustrating the effect of varying the number of intermediate distributions N on model performance.

N	NLL($\downarrow$)	RNLL($\downarrow$)	ESS($\uparrow$)
4	15.04	3.25	0.02
6	13.13	-9.75	0.02
9	**12.34**	**-15.68**	**0.15**

As discussed in Section 4, the initialization of t is central to ensuring that the model captures all the modes of the target distribution before progressing through the intermediate stages. Although very small starting values are often ideal, our empirical findings demonstrate that in high-dimensional scenarios, starting from a moderately larger t_1 does not degrade performance. This provides a practical advantage by lowering computational requirements while maintaining reliable distributional learning. We tune this parameter via grid search to ensure stable learning across all distributions. Table 6 provides the number of intermediate distributions N selected and the specific discretized t values used for each target distribution during training.

Since training at stage t depends on samples generated at the previous intermediate distribution as detailed in Section 2, the size of the buffer B directly influences the quality of the learned transitions. A sufficiently large buffer helps maintain broad support and prevents the loss of modes, particularly in high-dimensional or strongly multimodal settings. While smaller buffers reduce computational overhead but may compromise stability if mode structure is complex. For the experiments conducted in this work, we set the buffer size to

Table 6: Intermediate distribution parameters N and t-schedules used in training.

Target Distribution	N	t
MOG-40	7	$\{0.01, 0.05, 0.1, 0.25, 0.50, 0.75, 1.0\}$
MW-8	6	$\{0.1, 0.2, 0.4, 0.6, 0.8, 1.0\}$
MW-16	6	$\{0.1, 0.2, 0.4, 0.6, 0.8, 1.00\}$
Scalar $\phi^4(8 \times 8)$	9	$\{0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0\}$
Scalar $\phi^4(10 \times 10)$	9	$\{0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0\}$
Scalar $\phi^4(10 \times 10)$	9	$\{0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0\}$

10,000 for MOG-40, MW-8, and MW-16. For the ϕ^4 model, we used 10,000 samples for the 8×8 lattice and increased the buffer to 25,000 for the 10×10 and 12×12 cases to preserve sample diversity.

Within our framework, training proceeds using a composite loss involving $\mathcal{L}(\theta)$ and $\mathcal{L}_{\mathrm{RKL}}(\theta)$, weighted by the hyperparameters λ_1 and λ_2. At the first intermediate level $t = t_1$, samples are unavailable, necessitating the use of the reverse KL term only by setting $\lambda_1 = 0$ and $\lambda_2 = 1$. For all subsequent t, optimization leverages samples generated at the previous time step, with λ_1 initially assigned a larger value to maintain high fidelity to the previously learned mode structure. This configuration is retained until improvements in the monitored reverse NLL objective begin to plateau. Beyond this point, an annealing schedule gradually lowers λ_1 while increasing λ_2, thereby transitioning the algorithm toward a refinement phase in which the reverse KL term promotes sharper mode resolution and fine-scale correction of residual density mismatches.

D Sensitivity Analysis of the Loss Annealing Schedule

Training in FUND proceeds using the composite objective

$$\mathcal{L}_{\{\}\backslash \dashv \updownarrow}(\theta) = \lambda_1 \mathcal{L}(\theta) + \lambda_2 \mathcal{L}_{\mathcal{RKL}}(\theta), \tag{14}$$

where $\mathcal{L}(\theta)$ denotes either the FKL or score-matching objective, and $\mathcal{L}_{\mathrm{RKL}}(\theta)$ denotes the reverse KL regularization term.

At the first annealing stage $t = t_1$, replay-buffer samples are unavailable. Consequently, optimization initially relies only on the reverse KL objective by setting

$$\lambda_1 = 0, \qquad \lambda_2 = 1. \tag{15}$$

For all subsequent annealing stages, optimization additionally leverages replay-buffer samples generated at the previous timestep. In this phase, λ_1 is initially assigned a relatively larger value to preserve previously learned mode structure and maintain continuity along the annealed trajectory. As training progresses and the reverse NLL objective begins to plateau, the optimization gradually transitions toward stronger reverse-KL-based refinement by decreasing λ_1 and increasing λ_2.

To study the sensitivity of FUND to this annealing strategy, we conducted an ablation study on the MW-8 distribution using the FUND(FKL) variant under four different annealing schedules.

Setting 1

$$(1, 1) \to (0.5, 1) \to (0.25, 1) \to (0.1, 1) \to (0.01, 1) \tag{16}$$

Here, λ_1 is annealed down from 1 to 0.01, while λ_2 remains fixed at 1.

Setting 2

$$(1, 0.1) \to (1, 0.25) \to (1, 0.5) \to (1, 1) \tag{17}$$

Here, λ_1 remains fixed at 1, while λ_2 is annealed upward from 0.1 to 1.

Table 7: Sensitivity analysis of the annealing schedule for (λ_1, λ_2) on the MW-8 distribution using FUND(FKL).

Setting	Annealing Schedule (λ_1, λ_2)	NLL ↓	RNLL ↓	ESS ↑
Setting 1	$(1,1) \to (0.5,1) \to (0.25,1) \to (0.1,1) \to (0.01,1)$	7.07	-33.60	0.79
Setting 2	$(1,0.1) \to (1,0.25) \to (1,0.5) \to (1,1)$	7.05	-33.46	0.77
Setting 3	$(1,0.1) \to (1,0.5) \to (0.5,1) \to (0.1,1)$	7.03	-33.62	0.82
Setting 4	$(1,0.1) \to (1,0.25) \to (1,0.5) \to (1,1) \to (0.5,1) \to (0.25,1) \to (0.1,1) \to (0.01,1)$	**6.96**	**-34.30**	**0.88**

Table 8: Sensitivity analysis of the initial annealing parameter t_1 on the MOG-40 benchmark.

t_1	NLL (↓)	Number of Modes Recovered
0.10	1327.82	12
0.01	7.07	40

Setting 3

$$(1,0.1) \to (1,0.5) \to (0.5,1) \to (0.1,1) \tag{18}$$

In this setting, λ_1 is annealed downward while λ_2 is annealed upward over four stages.

Setting 4

$$(1,0.1) \to (1,0.25) \to (1,0.5) \to (1,1) \to (0.5,1) \to (0.25,1) \to (0.1,1) \to (0.01,1) \tag{19}$$

This schedule is similar to Setting 3 but performs the annealing more gradually over eight stages.

Across all settings, we observed that FUND remains reasonably stable provided that:

- the supervision objective $\mathcal{L}(\theta)$ dominates during the early stages of optimization, and

- the transition between $\mathcal{L}(\theta)$ and $\mathcal{L}_{\mathrm{RKL}}(\theta)$ occurs gradually rather than abruptly.

The overall performance trends remained qualitatively consistent across all schedules. However, keeping either λ_1 or λ_2 effectively fixed throughout training (Settings 1 and 2) generally resulted in inferior performance. Gradual annealing of both coefficients yielded the best empirical performance (Setting 4), suggesting that a smooth transition between mode preservation and reverse-KL-based refinement is beneficial. However, this schedule also incurs higher computational cost due to the increased number of optimization stages.

In contrast, Setting 3 provides a favorable trade-off between computational efficiency and performance, achieving results close to Setting 4 while requiring fewer annealing stages.

E   Sensitivity Analysis of Initial Annealing Parameter t_1

The choice of the initial annealing parameter t_1 plays an important role in the stability of the method and the preservation of mode coverage during the early stages of training.

As discussed in the main manuscript, choosing a sufficiently small t_1 smooths the target landscape and connects otherwise isolated modes, thereby simplifying the initial optimization problem. However, when t_1 is chosen too large, the initial annealed distribution remains highly multimodal, increasing the mode-seeking tendency of reverse-KL optimization and potentially leading to mode collapse.

To better characterize this behavior, we conducted additional sensitivity experiments on the MOG-40 benchmark by varying t_1 and measuring both the number of recovered modes and the corresponding NLL values. The quantitative results are summarized in Table 8.

Figure 6: Sensitivity analysis of the initial annealing parameter t_1 on the MOG-40 dataset. Larger values of t_1 lead to noticeable mode collapse, whereas smaller values preserve the multimodal structure of the target distribution more reliably. (A) Target distribution samples. (B) Generated samples with $t_1 = 0.1$. (C) Generated samples with $t_1 = 0.01$.

Our observations indicate a clear trend: larger values of t_1 lead to severe mode collapse, whereas sufficiently small values of t_1 significantly improve stability and preserve the modal structure of the target distribution. In particular, we observed noticeable mode collapse at $t_1 = 0.1$, while using $t_1 = 0.01$ successfully preserved all major modes of the MOG-40 distribution.

Figure 6 further illustrates the effect of t_1 on sample quality and mode coverage. The results visually demonstrate that smaller initial annealing values improve support coverage and help maintain the multimodal structure of the target distribution throughout optimization.

F Practical Guidelines for Hyperparameter Selection

FUND involves several hyperparameters that influence optimization stability, mode coverage, and computational cost. In this section, we summarize practical guidelines and empirical heuristics for selecting these hyperparameters when applying the method to new target distributions.

F.1 Choice of Initial Annealing Parameter t_1

The most important hyperparameter is the initial annealing parameter t_1, since it controls the smoothness of the first intermediate distribution:

$$p_{t_1}(x) \propto p(x)^{t_1}.$$

In general:

- highly multimodal distributions with sharp energy barriers benefit from smaller values of t_1,

- whereas simpler or weakly multimodal targets with high dimensionality can tolerate relatively larger values.

Intuitively, t_1 should be chosen sufficiently small so that the initial annealed distribution exhibits overlap across modes and can be learned without severe mode collapse. If t_1 is too large, the initial optimization problem may remain highly multimodal, increasing the mode-seeking tendency of reverse-KL optimization.

The sensitivity analysis presented in Appendix E demonstrates this behavior empirically on the MOG-40 benchmark.

F.2 Number of Annealing Stages N

The number of annealing stages N determines how gradually the model transitions from the initial annealed distribution toward the target distribution.

In practice:

- more complex or highly multimodal targets generally require larger values of N,

- whereas simpler distributions can often be modeled with fewer annealing stages.

Using a sufficiently large N helps maintain overlap between successive intermediate distributions, thereby improving stability of importance-weight estimation and reducing optimization difficulty. Additionally, as shown in Table 5 in Appendix C for the 8×8 scalar ϕ^4 distribution, increasing the number of annealing stages N consistently improves performance across all evaluation metrics, indicating that smoother transitions between successive intermediate distributions enhance both distributional fidelity and sampling efficiency.

F.3 Replay Buffer Size

The replay buffer stores samples generated from previously learned intermediate distributions and is used for importance-weighted supervision during later stages of optimization.

Larger buffer sizes generally improve the stability of importance-weight estimation and enhance mode preservation. However, larger buffers also increase memory requirements.

When the approximate number of modes in the target distribution is known analytically, the replay-buffer size should ideally be chosen large enough to ensure adequate sample representation across all modes. Insufficient buffer coverage may bias the importance-weighted supervision toward dominant modes, reduce stability during later annealing stages, and lead to insufficient mode coverage.

F.4 Annealing Schedule for (λ_1, λ_2)

The optimization objective in FUND combines the replay-buffer supervision term and the reverse-KL regularization term:

$$\mathcal{L}_{\text{final}}(\theta) = \lambda_1 \mathcal{L}(\theta) + \lambda_2 \mathcal{L}_{\text{RKL}}(\theta).$$

Based on our empirical observations, gradual annealing of the loss weights (λ_1, λ_2) produces more stable optimization behavior compared to abrupt transitions.

In practice:

- larger initial values of λ_1 help preserve previously learned mode structure during early optimization,

- while progressively increasing λ_2 improves local refinement and density correction at later stages.

To systematically study this behavior, we conducted an additional sensitivity analysis on the MW-8 benchmark using multiple annealing schedules. The corresponding observations and quantitative comparisons are presented in Appendix D.

Overall, we observed that smooth transitions between the two objectives improve optimization stability and mode coverage, whereas abrupt changes can degrade performance.

G Computational Cost and Runtime Analysis

All experiments were conducted on a system equipped with four NVIDIA GeForce RTX 3080 GPUs, each with 10GB memory. Individual experiments were performed using a single GPU card. We report both:

Table 9: Training and inference runtime comparison across methods for ϕ^4 (12×12) and MW-16.

Method	ϕ^4 (12×12)		MW-16	
	Training Time	Inference Time	Training Time	Inference Time
MCMC (HMC)	0 sec	510 sec	–	–
RKL	15.16 hrs	2.2 sec	0.24 hrs	0.56 sec
FAB	51.20 hrs	2.2 sec	2.5 hrs	0.56 sec
IDEM	5.25 hrs	44.0 sec	4.3 hrs	34.0 sec
FUND(FKL)	35.69 hrs	2.2 sec	2.3 hrs	0.56 sec
FUND(SCORE)	123.90 hrs	2.2 sec	13.6 hrs	0.56 sec

- total training time required to learn the model, and

- inference/sample-generation time required to generate 10000 samples after training.

We include timing comparisons for both MW-16 and the high-dimensional ϕ^4 (12×12) benchmark. The runtime comparisons are summarized in Table 9.

We did not include FKL in the discussion since it requires access to true samples from the target distribution during training, whereas the remaining methods learn directly from the unnormalized target density without requiring target samples.

The results highlight several important computational trade-offs across methods.

- MCMC methods require computationally expensive sequential sampling during inference, and the computational cost increases significantly with the number of generated samples.

- IDEM has comparatively lower training cost; however, sample generation is substantially slower because inference requires numerically simulating the reverse-time stochastic differential equation (SDE) using the learned diffusion sampler.

- Methods such as FAB and FUND incur higher training cost. In FUND, the additional overhead arises from progressive annealing and repeated optimization across successive intermediate distributions. In FAB, the overhead additionally arises from repeated Annealed Importance Sampling (AIS) steps used for generating training samples.

- Once trained, flow-based approaches enable extremely fast parallel sample generation through a single forward pass of the learned flow model.

- Although RKL requires comparatively moderate training time, it suffers from severe mode-collapse behavior, as reflected in the quantitative results reported in Tables 1 and 2. Consequently, lower training cost alone does not necessarily translate into better generative performance or mode coverage.

- Compared to FAB, FUND(FKL) achieves lower training cost while maintaining similarly fast inference-time generation. In contrast, the score-based variant of FUND incurs higher training overhead due to the additional score-computation operations required for score-loss optimization, including both target-score and model-score evaluations.

- Although FUND introduces additional sequential optimization stages, this overhead is justified by the corresponding improvements in sampling quality and mode coverage. The progressive learning of successive annealed distributions allows the model to incrementally adapt from simpler intermediate densities toward the final target distribution, rather than attempting to learn a highly multimodal target in a single optimization stage. This sequential distributional learning helps preserve modal

structure across annealing stages, improves support coverage, and reduces mode-collapse behavior, particularly for challenging multimodal targets. As reflected in Tables 1 and 2, FUND consistently achieves stronger NLL and ESS performance compared to competing methods on several benchmarks.

- Furthermore, once training is complete, FUND enables efficient parallel sample generation through a single forward pass of the flow model, resulting in substantially faster inference compared to MCMC-based approaches, whose sequential sampling cost scales directly with the number of generated samples.

Algorithm 1 Training of FUND

1: Initialize flow $q(\mathbf{x}; \theta)$ parameterized by f
2: Discretize t into N steps: $\{t_1, t_2, \ldots, t_N\}$
3: Initialize buffer $B \leftarrow \emptyset$
4: **for** $i = 1$ to N **do**
5:      **if** $i = 1$ **then**   ▷ Initial time step
6:          Set $\lambda_1 \leftarrow 0$, $\lambda_2 \leftarrow 1$
7:          **while** $-\mathbb{E}_{q_{t_1}} \log p_{t_1}(x)$ not converged **do**
8:              Sample minibatch $\{z^{(1:m)}\} \sim q_z(z)$
9:              Compute $\mathcal{L}_{\mathrm{RKL}}(\theta)$
10:             Compute:

$$\mathcal{L}_{\mathrm{final}}(\theta) = \lambda_2 \mathcal{L}_{\mathrm{RKL}}(\theta)$$

11:             Update parameters:

$$\theta \leftarrow \theta - \eta \nabla_\theta \mathcal{L}_{\mathrm{final}}(\theta)$$

12:          **end while**
13:          Sample latent variables $z \sim q_z(z)$
14:          Compute $x = f_{t_1}(z; \theta)$
15:          Store $(x, \log q_{t_1}(x))$ in buffer B
16:      **else**   ▷ Subsequent time steps
17:          Compute importance weights for $x_j \in B$:

$$w(x_j) = \frac{p_{t_i}(x_j)}{q_{t_{i-1}}(x_j)}$$

18:          Normalize weights:

$$w(x_j) \leftarrow \frac{w(x_j)}{\sum_{k=1}^{|B|} w(x_k)}$$

19:          Initialize hyperparameters:

$$\lambda_1^{(1)} \leftarrow 1.0, \qquad \lambda_2^{(1)} \leftarrow 0.1$$

20:          **for** $j = 1$ to K **do**   ▷ Annealing stages
21:             **while** $-\mathbb{E}_{q_{t_i}} \log p_{t_i}(x)$ not converged **do**
22:                 Sample minibatch $\{(x_b, w_b)\}_{b=1}^{m_B} \sim B$
23:                 Sample minibatch $\{z^{(1:m)}\} \sim q_z(z)$
24:                 Compute $\mathcal{L}(\theta)$ using minibatch buffer samples $\{(x_b, w_b)\}_{b=1}^{m_B}$
25:                 Compute $\mathcal{L}_{\mathrm{RKL}}(\theta)$ using latent minibatch $\{z^{(1:m)}\}$
26:                 Compute:

$$\mathcal{L}_{\mathrm{final}}(\theta) = \lambda_1^{(j)} \mathcal{L}(\theta) + \lambda_2^{(j)} \mathcal{L}_{\mathrm{RKL}}(\theta)$$

27:                 Update parameters using minibatch gradient:

$$\theta \leftarrow \theta - \eta \nabla_\theta \mathcal{L}_{\mathrm{final}}(\theta)$$

28:             **end while**
29:             Anneal hyperparameters: decrease $\lambda_1^{(j)}$, increase $\lambda_2^{(j)}$
30:          **end for**
31:          Sample latent variables $z \sim q_z(z)$
32:          Compute:

$$x = f_{t_i}(z; \theta)$$

33:          Update buffer B with $(x, \log q_{t_i}(x))$
34:      **end if**
35: **end for**