Scaling the Depth of Vision Transformers via the Fourier Domain Analysis

Abstract

Vision Transformer (ViT) has recently demonstrated promise in computer vision problems. However, unlike Convolutional Neural Networks (CNN), it is known that the performance of ViT saturates quickly with depth increasing, due to the observed attention collapse or patch uniformity. Despite a couple of empirical solutions, a rigorous framework studying on this scalability issue remains elusive. In this paper, we first establish an analytic framework to investigate ViT from the spectrum domain. We show that the self-attention mechanism inherently amounts to a low-pass filter, which indicates when ViT scales up its depth, excessive low-pass filtering will cause feature maps to only preserve their Direct-Current (DC) component. We then propose two straightforward yet effective techniques to mitigate the undesirable low-pass limitation. The first technique, termed **AttnScale**, decomposes a self-attention block into low-pass and high-pass components, then rescales and combines these two filters to produce an all-pass self-attention matrix. The second technique, termed **FeatScale**, re-weights feature maps on separate frequency bands to amplify the high-frequency signals. Both techniques are efficient, hyperparameter-free, and can effectively avoid attention collapse and patch uniformity caused by low-pass filtering. Our experiments demonstrate our proposed methods consistently help ViT benefit from deeper architectures, bringing $\geq 1.0\%$ performance gain with little parameter overhead. In addition to the baseline model, our techniques are also successfully applied to ViT variants. All our codes and pre-trained models will be publicly released upon acceptance.

1 Introduction

Transformers have achieved a phenomenal success in Natural Language Processing (NLP) (Vaswani et al., 2017; Devlin et al., 2018; Dai et al., 2019; Brown et al., 2020), and recently in a wide range of computer vision applications too (Dosovitskiy et al., 2020; Liu et al., 2021; Arnab et al., 2021; Carion et al., 2020; Jiang et al., 2021a). One representative advance, the Vision Transformer (ViT) (Dosovitskiy et al., 2020), stacks Multi-head Self-Attention (MHA) blocks, by treating each local image patch as semantic tokens and modeling their interactions globally. Unlike Convolutional Neural Networks (CNNs) that hierarchically enlarge the receptive from local to global, even a shallow ViT is able to effectively capture the global contexts, leading to their very competitive performance on image classification and other tasks (Liu et al., 2021; Jiang et al., 2021a).

Going deep has always been a trend in deep learning (LeCun et al., 2015; Krizhevsky et al., 2012), and ViT was expected to make no exception. One might reasonably conjecture that a deeper ViT with more MHA blocks significantly outperform its shallower baseline. Unfortunately, building deeper ViTs face practical challenges. Empirically, Zhou et al. (2021a) shows a vanilla ViT of 32 layers under-performs the 24-layer one. Gong et al. (2021) demonstrates a downgraded patch diversity in deeper layers, and Dong et al. (2021) mathematically reveals the rank collapse phenomenon when Transformer goes deeper. Despite efforts towards deep ViT through patch diversification (Gong et al., 2021; Zhou et al., 2021b), rank collapse alleviation (Zhou et al., 2021a; Zhang et al.), and training stabilization (Touvron et al., 2021b; Zhang et al., 2019), most of them are restricted to empirical studies. Rethinking the problem with deep ViT from a more principled angle pends further efforts.

In this paper, we present the first rigorous analysis of stacking self-attention mechanism in the Fourier space. We mathematically show that cascading self-attention blocks is equivalent to repeatedly

applying a low-pass filter, regardless of the input key or query tokens (Section 2.2). As a consequence, going deeper with vanilla ViT blocks only preserves Direct Component (DC) of the signal at the output layer. This theoretical finding explains the observations of patch uniformity and rank collapse, and is also inherently related to the over-smoothing phenomenon in Graph Convolutional Networks (GCNs) (Kipf & Welling, 2016; Nt & Maehara, 2019; Oono & Suzuki, 2019; Cai & Wang, 2020). Moreover, we also reveal the role of other transformer modules (e.g., MLP and residual connection) in preventing this undesirable low-pass filtering (Section 2.3).

Built on the aforementioned analysis framework in the Fourier domain, we propose two novel techniques, to mitigate the low-pass filtering effect of self-attention and effectively scale up the depth of ViTs. The first technique, termed *Attention Scaling* (**AttnScale**), directly manipulates on the calculated attention map to enforce an all-pass filter (Section 3.1). It decomposes the self-attention matrix into a low-pass filter plus a high-pass filter, then adopts a learnable weight to adaptively amplify the effect of high-pass filter. The second technique, termed *Feature Scaling* (**FeatScale**), hinges on feature maps to re-weight different frequency bands separately (Section 3.2). It employs trainable coefficients to re-mix the DC and high-frequency components, hence selectively enhancing the high-frequency portion of the MHA output. Both AttnScale and FeatScale are extremely memory and computationally friendly. Neither runs Fourier transformation explicitly, bringing little extra complexity to the original ViTs.

Our contributions can be summarized as follows:

- We establish the first rigorous theoretical analysis of ViT from the spectral domain. We characterize the low-pass filtering effect of cascading MHAs, which connects to the recent empirical findings of ViT patch diversity loss or rank collapse.

- We present two theoretically grounded Fourier-domain scaling techniques, named AttnScale and FeatScale. They operating on re-adjusting the low- and high-frequency components of the attention maps and feature maps, respectively. Both are efficient, hyperparameter-free, easy-to-use, and able to generalize across different ViT variants.

- We conduct extensive experiments by integrating AttnScale and FeatScale with different ViT backbones. Both of our approaches substantially boost DeiT and CaiT with 1.0% and 0.3% performance gain without whistles and bells.

2 WHY ViT CANNOT GO DEEPER?

2.1 NOTATION AND PRELIMINARIES

We begin by introducing our notations. Let $\boldsymbol{X} \in \mathbb{R}^{n \times d}$ denote the feature matrix, where n is the number of samples, and d is the feature dimension. Let $\boldsymbol{x}_i \in \mathbb{R}^d, \forall i = 1, \cdots, n$, the i-th row of $\boldsymbol{X}$, denote the feature vector of the i-th sample, and $\boldsymbol{z}_j \in \mathbb{R}^n, \forall j = 1, \cdots, d$, the j-th column of $\boldsymbol{X}$, represent signals of the j-th channel. In the context of ViT, $\boldsymbol{X}$ denotes a set (sequence) of image patches, $\boldsymbol{x}_i$ denotes the flatten version of the i-th patch embedding (d = patch width $\times$ patch height), and $\boldsymbol{z}_j$ denotes a whole image signal of the j-th channel.

Transformer Architecture Vision Transformer (ViT) consists of three main components: a patch embedding and position encoding part, a stack of transformer encoder block with Multi-Head Self-Attention (MHA) and Feed-Forward Network (FFN), and a score readout function for image classification. We depict a transformer block in Fig. 3a. The key ingredient here is the Self-Attention (SA) module, which takes in the token representation of the last layer, and encodes each image token by aggregating information from other patches with respect to the computed attention value, formulated as below (Vaswani et al., 2017):

$$\mathrm{SA}(\boldsymbol{X}) = \mathrm{softmax}\left(\frac{\boldsymbol{X}\boldsymbol{W}_Q(\boldsymbol{X}\boldsymbol{W}_K)^T}{\sqrt{d}}\right)\boldsymbol{X}\boldsymbol{W}_V, \tag{1}$$

where $\boldsymbol{W}_K \in \mathbb{R}^{d \times d_k}, \boldsymbol{W}_Q \in \mathbb{R}^{d \times d_q}, \boldsymbol{W}_V \in \mathbb{R}^{d \times d}$ are the key, query, and value weight matrices, respectively, $\sqrt{d}$ here denotes a scaling factor, and $\mathrm{softmax}(\cdot)$ operates on $\boldsymbol{X}$ row-wisely. Multi-Head Self-Attention (MHA) involves a group of SA heads and combines their outputs through a linear

Figure 1: Visualize the intensity of high-frequency component and their theoretical upper bounds under different transformer blocks. The blue line is defined by $\log(\|\mathcal{HC}\,[\boldsymbol{X}_l]\|_F/\|\mathcal{HC}\,[\boldsymbol{X}_0]\|_F)$, and the red line is estimated using the results in Section 2.2 & 2.3. See details in Appendix F.1.

projection (Vaswani et al., 2017):

$$\text{MHA}(\boldsymbol{X}) = [\text{SA}_1(\boldsymbol{X}) \quad \cdots \quad \text{SA}_H(\boldsymbol{X})]\,\boldsymbol{W}_O, \tag{2}$$

where the subscripts denote the SA head number, H is the total number of SA heads, and $\boldsymbol{W}_O \in \mathbb{R}^{Hd \times d}$ projects multi-head outputs to the hidden dimension. Besides MHA module, each transformer block is equipped with a normalization layer, feed-forward network, and skip connections to cooperate with MHA. Formally, a transformer block can be written as follows:

$$\boldsymbol{X}' = \text{MHA}(\text{LayerNorm}(\boldsymbol{X})) + \boldsymbol{X}, \tag{3}$$

$$\boldsymbol{Y} = \text{FFN}(\text{LayerNorm}(\boldsymbol{X}')) + \boldsymbol{X}'. \tag{4}$$

Fourier Analysis   The main analytic tool in this paper is Fourier transform. Denote $\mathcal{F} : \mathbb{R}^n \to \mathbb{C}^n$ be the Discrete Fourier Transform (DFT) with the Inverse Discrete Fourier Transform (IFT) $\mathcal{F}^{-1} : \mathbb{C}^n \to \mathbb{R}^n$. Applying $\mathcal{F}$ to a flatten image signal $\boldsymbol{x}$ is equivalent to left multiplying a DFT matrix, whose rows are the Fourier basis $\boldsymbol{f}_k = \left[e^{2\pi \mathrm{j}(k-1)\cdot 0} \quad \cdots \quad e^{2\pi \mathrm{j}(k-1)\cdot(n-1)}\right]^T / \sqrt{n} \in \mathbb{R}^n$, where k denotes the k-th row of DFT matrix, and j is the imaginary unit. Let $\tilde{\boldsymbol{z}} = \mathcal{F}\boldsymbol{z}$ be the spectrum of $\boldsymbol{z}$, and $\tilde{\boldsymbol{z}}_{dc} \in \mathbb{C}$, $\tilde{\boldsymbol{z}}_{hc} \in \mathbb{C}^{n-1}$ take the first element and the rest elements of $\tilde{\boldsymbol{z}}$, respectively. Define $\mathcal{DC}\,[\boldsymbol{z}] = \tilde{\boldsymbol{z}}_{dc}\boldsymbol{f}_1 \in \mathbb{C}^n$ as the Direct-Current (DC) component of signal $\boldsymbol{z}$, and $\mathcal{HC}\,[\boldsymbol{z}] = [\boldsymbol{f}_2 \quad \cdots \quad \boldsymbol{f}_n]\,\tilde{\boldsymbol{z}}_{hc} \in \mathbb{C}^n$ the complementary high-frequency component.

In signal processing, a low-pass filter is a system that suppresses the high-frequency component of signals and retain the low-frequency component. In this paper, we refer to low-pass filter as a particular type of filters that only preserve the DC component, while diminishing the remaining high-frequency component. To be more precise, we define low-pass filters in Definition 1.

Definition 1. *Given an endomorphism $f : \mathbb{R}^n \to \mathbb{R}^n$ with f^t denoting applying f for t times, f is a low-pass filter if and only if for all $\boldsymbol{z} \in \mathbb{R}^n$:*

$$\lim_{t \to \infty} \frac{\|\mathcal{HC}\,[f^t(\boldsymbol{z})]\|_2}{\|\mathcal{DC}\,[f^t(\boldsymbol{z})]\|_2} = 0. \tag{5}$$

Definition 1 reveals the nature of low-pass filters: they will produce a dominant response on DC component, while imposing an inhibition effect on the high-frequency band. We refer interested readers to Appendix A for more useful backgrounds.

2.2   SELF-ATTENTION IS LOW-PASS FILTER

In this subsection, we will give theoretical justification on self-attention in terms of its spectral-domain effect. Our main result is that self-attention is constantly a low-pass filter, which continuously erases high-frequency information, thus causing ViT to lose features expressiveness at deep layers.

Formally, we have the following theorem that shows attention matrix produced by a softmax function (e.g, Eqn. 1) is a low-pass filter independent of the input token features or key/query matrices.

Theorem 1. *(SA matrix is a low-pass filter) Let $\boldsymbol{A} = \text{softmax}(\boldsymbol{P})$, where $\boldsymbol{P} \in \mathbb{R}^{n \times n}$. Then $\boldsymbol{A}$ must be a low-pass filter. For all $\boldsymbol{z} \in \mathbb{R}^n$, $\lim_{t \to \infty} \|\mathcal{HC}\,[\boldsymbol{A}^t \boldsymbol{z}]\|_2 / \|\mathcal{DC}\,[\boldsymbol{A}^t \boldsymbol{z}]\|_2 = 0$.*

Theorem 1 is a straightforward result of Perron-Frobenius theorem. See Appendix B.1 for a proof. Theorem 1 also reveals that no matter how attention is computed inside the softmax function, including dot product (Vaswani et al., 2017), linear combination (Veličković et al., 2017), or L2 distance (Kim et al., 2021), the resulting attention matrix is always a low-pass filter. One can see consecutively applying self-attention matrix simulates the process of ViT's forward propagation. As the layer number increases infinitely, the final output will only keep the DC bias, and ViT loses all the feature expressive power.

Figure 2: Visualize the spectral response of an attention map. We randomly pick a sample and depict its first head of 4/8/12-th layer. Refer to Appendix F.2.

Corollary 2. *Let $\boldsymbol{P}_1, \boldsymbol{P}_2, \cdots, \boldsymbol{P}_n$ be a sequence of matrix in $\mathbb{R}^{n \times n}$, and each $\boldsymbol{P}_k, \forall k = 1, \cdots, L$ has $\boldsymbol{A}_k = \text{softmax}(\boldsymbol{P}_k)$. Then $\prod_{k=1}^{L} \boldsymbol{A}_k$ is also a low-pass filter.*

In fact, ViT re-computes self-attention matrices per layer, which seems to avoid the consecutive power of an identical self-attention matrix. However, we also provide Corollary 2, which suggests even the ViT consists of distinctive self-attention matrix at each layer, their composition turns out to act like a low-pass filter as well. We also visualize the spectrum of attention maps (Fig. 2 and more on Appendix F.2) to support our theoretical conclusions.

Knowing that self-attention matrices amount to low-pass filters, we are also interested in to which extent an MHA layer would suppress the high-frequency component. Thereby, we also provide a convergence rate to illustrate this speed that the high-frequency component are being annihilated.

Theorem 3. *(convergence rate of SA) Let $\boldsymbol{A} = \text{softmax}(\boldsymbol{P})$ and $\alpha = \max_{i,j} |\boldsymbol{P}_{ij}|$, where $\boldsymbol{P} \in \mathbb{R}^{n \times n}$. Define $\text{SA}(\boldsymbol{X}) = \boldsymbol{A}\boldsymbol{X}\boldsymbol{W}_V$ as the output of a self-attention module, then*

$$\|\mathcal{HC}\left[\text{SA}(\boldsymbol{X})\right]\|_F \le \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha} + n - 1}} \|\boldsymbol{W}_V\|_2 \|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F. \tag{6}$$

In particular, when $\boldsymbol{P} = \boldsymbol{X}\boldsymbol{W}_Q(\boldsymbol{X}\boldsymbol{W}_K)^T/\sqrt{d}$, and assume tokens are distributed inside a ball with radius $\gamma > 0$, i.e., $\|\boldsymbol{x}_i\|_2 \le \gamma, \forall i = 1, \cdots, n$, then $\alpha \le \gamma^2 \|\boldsymbol{W}_Q\boldsymbol{W}_K^T\|_2/\sqrt{d}$.

The proof of Theorem 3 can be found in Appendix B.3. Theorem 3 says the high-frequency intensity ratio to the pre- and post- attention aggregation is upper bounded by $\|\boldsymbol{W}_V\|_2 \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}$. When $\|\boldsymbol{W}_V\|_2 \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}} < 1$, $\mathcal{HC}\left[\text{SA}(\boldsymbol{X})\right]$ converges to zero exponentially. We note that, no matter how attention is computed or signals are initialized, since $\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}$ is bounded by $\sqrt{n}$, $\|\boldsymbol{W}_V\|_2 < 1/\sqrt{n}$ will definitely cause a monotonically decreasing high-frequency component. When dot-product attention is adopted, a sufficient condition that $\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F$ decreases to zero within logarithmic time is $\gamma^2 \|\boldsymbol{W}_Q\boldsymbol{W}_K^T\|_2/\sqrt{d} + \log\|\boldsymbol{W}_V\|_2 \le \log\frac{n-1}{n}/2$.

2.3 Existing Mechanisms that Counteract Low-Pass Filtering

In this section, we take other building blocks of ViT into consideration. We will justify whether Multi-Head Attention (MHA), Feed-Forward Network (FFN), and residual connections can effectively alleviate the low-pass filtering drawbacks. All the derivations follow from Theorem 3, and some proof ideas are borrowed from Dong et al. (2021). We further present Fig. 1 to justify our results.

Does multi-head help? MHA employs weights to combine the results of multiple self-attention blocks. We can rewrite it as $\text{MHA}(\boldsymbol{X}) = \sum_{h=1}^{H} \text{SA}(\boldsymbol{X})\boldsymbol{W}_O^h$. We show by Proposition 4 in Appendix C.1 that the convergence rate turns to $\sigma_1\sigma_2 H \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}$, where H is the number of heads, $\sigma_1 = \max_{h=1}^{H} \|\boldsymbol{W}_V^h\|_2$ and $\sigma_2 = \max_{h=1}^{H} \|\boldsymbol{W}_O^h\|_2$. One can see MHA can only slow down the convergence up to a constant $\sigma_2 H$, which does not root out the problem.

Does residual connection benefit? In addition to MHA, a transformer block also leverages a skip connection, which can be formulated as $\text{Res}(\boldsymbol{X}) = \text{MHA}(\boldsymbol{X}) + \boldsymbol{X}$. We show that residual

connection can effectively prevent high-frequency component from diminishing to zero by promoting the rate $\sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}$ to $1 + \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}} > 1$. Refer to Proposition 5 in Appendix C.2.

Does FFN make a change? A feed-forward network is appended to MHA module. We characterize its effect in Appendix C.3. Our Proposition 6 suggests that a FFN with Lipschitz constant σ_3 contributes a $\sigma_3\left(1 + \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\right)$ convergence rate, which does not improve the original one. However, if skip connection is adopted over FFN, $\sigma_3 > 1$ can guarantee the magnitude of the high-frequency component is non-contractive.

2.4 Connections to Existing Theoretic Understanding Works

It is known that Graph Convolutional Networks (GCN) are not more than low-pass filters (Nt & Maehara, 2019). In the meanwhile, Oono & Suzuki (2019); Cai & Wang (2020) pointed out GCN's node features will be exponentially trapped into the nullspace of the graph Laplacian matrix. Similarly, our work concludes that self-attention module is yet another low-pass filter. Combining with our theoretical derivation, one can see the root reason is that both graph Laplacian matrices and self-attention matrices consistently own a fixed leading eigenvector, namely the DC basis. This makes aggregating information via such matrices inherently project the token representation onto these invariant eigenspaces. And we note that over-smoothing, rank collapse, and patch uniformity are all the manifestation of excessive low-pass filtering. See Appendix D.1 for more discussion.

In Dong et al. (2021), the authors proved that ViT's feature maps will doubly exponentially collapses to a rank-1 matrix, which reveals ViT loses feature expressiveness at deep layers. Besides, they also gave a systematic study on other building blocks of transformer. While they share the similar insights with us, our work further specifies which rank-1 matrix the feature activation will converge to, namely the subspace spanned by the DC basis. That makes our theory to be better grounded with signal-processing and geometric interpretations, via directly measuring the intensity of the high-frequency residual, instead of examining a composite norm distance to an agnostic rank-1 matrix. Although Dong et al. (2021) presented a faster convergence speed, we respectfully suggest that the current proof of Dong et al. (2021) might be deficient, or at least incomplete in the assumptions (see Appendix D.2). Moreover, our theory can be generalized to other attention mechanisms such as logistic attention (Veličković et al., 2017) and L2 distance (Kim et al., 2021). See Appendix D.3.

3 AttnScale & FeatScale: Scaling from the Fourier-Domain

3.1 AttnScale: Make Attention an All-Pass Filter

As we discussed in Section 2.2, self-attention matrix can only perform low-pass filtering, which narrows the filter space ViT can express. Inspired by this, we propose a scaling techniques directly manipulating the attention map, termed *Attention Scaling* (**AttnScale**), to balance the effects of low- and high-pass filtering and produce all-pass filters. AttnScale decomposes the self-attention matrix to a low-pass filter plus a high-pass filter, and introduces a trainable parameter to rescale the high-pass filter to match the magnitude with the low-pass component.

Formally, let $\boldsymbol{A}$ denote a self-attention matrix. To decompose a low-pass filter from $\boldsymbol{A}$, we find the *largest possible* low-pass filter that can be extracted from $\boldsymbol{A}$. We use Lemma 8 in Appendix E to justify our solution. By Lemma 8, we can simply extract $\boldsymbol{L} = \mathcal{F}^{-1}\operatorname{diag}(1, 0, \cdots, 0)\mathcal{F} = \mathbf{1}\mathbf{1}^T/n$ from $\boldsymbol{A}$ and take the complementary part as the high-pass filter. Afterward, we can rescale the high-pass component of the filter, and combine low-pass and high-pass together to form a new self-attention matrix. We illustrate this scaling trick in Fig. 3b. To be more precise, for the l-th layer and h-th head, we recompute the self-attention map as follows:

$$\boldsymbol{A}_{LP}^{(l,h)} = \frac{1}{n}\mathbf{1}\mathbf{1}^T, \tag{7}$$

$$\boldsymbol{A}_{HP}^{(l,h)} = \boldsymbol{A}^{(l,h)} - \boldsymbol{A}_{LP}^{(l,h)}, \tag{8}$$

$$\hat{\boldsymbol{A}}^{(l,h)} = \boldsymbol{A}_{LP}^{(l,h)} + (\omega_{l,h}+1)\boldsymbol{A}_{HP}^{(l,h)}, \tag{9}$$

Figure 3: Illustration of our proposed techniques. **(a)** recalls the standard ViT block. **(b)** and **(c)** illustrate our proposed AttnScale and FeatScale, which scaling high-pass filter component and high-frequency signals, respectively.

Figure 4: Visualize cosine similarity of attention and feature maps with/without our proposed methods. Refer to Appendix F.3 for details.

where $\omega_{l,h}$ is a trainable parameter, and different layers and heads adopt separate $\omega_{l,h}$. During training time, $\omega_{l,h}$'s are initialized with 0, and jointly tuned with the other network parameters. By adjusting $\omega_{l,h}$, $\hat{\boldsymbol{A}}^{(l,h)}$ can simulate any type of filters: low-pass, high-pass, band-pass, or all-pass. Note that our AttnScale is extremely lightweight, as it only brings $O(HL)$ extra parameters, where H is the number of heads, and L is the number of ViT blocks.

3.2 FEATSCALE: REWEIGHT HIGH-FREQUENCY SIGNALS

According to our analysis in Section 2.2, MHA module will indiscriminately suppress high-frequency signals, which leads to severe information loss. Even though residual connection can retrieve lost information through the skip path, the high-frequency portion will be inevitably diluted (Theorem 1). To this end, we propose another scaling technique that operates on feature maps, named *Feature Scaling* (**FeatScale**). FeatScale processes the output of MHA by mixing the information from varying frequency bands discriminatively. FeatScale first decomposes the resultant signals into their DC and high-frequency components. Then it introduces two groups of parameters to re-weight the two components for each channel, respectively. The pipeline of this scaling technique is depicted in Fig. 3c. To be more precise, we re-weight the output of the l-th MHA by

$$\boldsymbol{X}_{DC}^{(l)} = \mathcal{DC}\left[\text{MHA}(\boldsymbol{X})\right](\text{diag}(\boldsymbol{s}_l) + \boldsymbol{I}), \tag{10}$$

$$\boldsymbol{X}_{HC}^{(l)} = \mathcal{HC}\left[\text{MHA}(\boldsymbol{X})\right](\text{diag}(\boldsymbol{t}_l) + \boldsymbol{I}), \tag{11}$$

$$\boldsymbol{X}^{(l)} = \boldsymbol{X}_{DC}^{(l)} + \boldsymbol{X}_{HC}^{(l)}, \tag{12}$$

where $\boldsymbol{s}_l \in \mathbb{R}^d$ and $\boldsymbol{t}_l \in \mathbb{R}^d$ are learnable parameters to perform channel-wise re-weighting. We initialize $\boldsymbol{s}_l$ and $\boldsymbol{t}_l$ with zeros and tune them with gradient descent. After adjusting the proportion of different frequency signals, FeatScale can prevent the dominance of the DC component. $\mathcal{DC}\left[\cdot\right]$ and $\mathcal{HC}\left[\cdot\right]$ are cheap to compute without explicit Fourier transform. Calculating $\mathcal{DC}\left[\boldsymbol{X}\right]$ is as simple as running the column average of matrix $\boldsymbol{X}$, and $\mathcal{HC}\left[\boldsymbol{X}\right]$ can be efficiently computed by $\boldsymbol{X} - \mathcal{DC}\left[\boldsymbol{X}\right]$.

3.3 DISCUSSION

We have proposed two methods to facilitate the deeper stacking of ViT MHA modules, and discussed their motivations and strengths from our perspective of filtering and signal processing. In this section, we will connect these two techniques with commonly mentioned problems with ViTs.

How does AttnScale prevent attention collapse? Deep ViT suffers from the attention collapse issue (Zhou et al., 2021a). When transformer goes deepr, the attention maps gradually become similar and even much the same after certain layers. Combining with our thoery, one can see collapsed attention maps turn out to be a pure low-pass filter, which wipes off all the high-frequency information

in one shot. Zhou et al. (2021a) proposed the re-attention trick, which blends attention map across different heads. By doing this, modified attention maps aggregate high-pass components from other heads and is endowed with richer filtering property. We note that our AttnScale is akin to a more lightweight re-attention mechanism with better interpretability. We rewrite the attention map as a sum of an already-collapsed attention ($\mathbf{1}\mathbf{1}^T/n$) with the complementary residual map that encodes diverse patterns in a self-attention matrix. By re-weighting the residual map, the diversified patterns can be amplified, which prevents it from degenerating to a rank-1 matrix. We further verify this argument using cosine similarity metric (Zhou et al., 2021a) in the upper sub-figure of Fig. 4.

How does FeatScale conserve patch diversity?   Self-attention blocks tend to map different patches into similar latent representations, yielding information loss and performance degradation (Gong et al., 2021). By our theory, this asymptotic smoothness of feature map is caused by excessive low-pass filtering, and the remaining DC bias signifies uniform patch representations. Conventional approaches to addressing this problem include incorporating convolutional layers (Wu et al., 2021; Jiang et al., 2021b) and enforcing patch diversity regularizations (Gong et al., 2021). As diverse features are often characterized by high-frequency signals, our FeatScale instead elevating the high-frequency component via a learnable scaling factor, can be regarded as a more straightforward way to reconstruct the patch richness. Compared with LayerScale (Touvron et al., 2021b), in which each frequency band is equally scaled, our FeatScale treating DC and high-frequency components differently, not only perform a per-channel normalization, but also perform a spectral-domain calibration with high-frequency details and low-frequency characteristics. The lower sub-plot of Fig. 4 shows ViT with our FeatScale has lower feature similarity at deep layer.

4   RELATED WORK

Transformers in Vision.   Transformer (Vaswani et al., 2017) entirely relies on self-attention mechanism to capture correlation and exchange information globally among the input. It has achieved a remarkable performance in natural language processing (Devlin et al., 2018; Dai et al., 2019; Brown et al., 2020) and many cross-disciplinary applications (Jumper et al., 2021; Ying et al., 2021). Recent advances have also successfully applied Transformer to computer vision tasks. Dosovitskiy et al. (2020) first adopts a pure transformer architecture (ViT) for image classification. The follow-up works extend ViT to various vision tasks, such as object detection (Carion et al., 2020; Zhu et al., 2020; Zheng et al., 2020; Sun et al., 2020), segmentation (Chen et al., 2021; Wang et al., 2021), image generation (Parmar et al., 2018; Jiang et al., 2021a), video processing (Zhou et al., 2018; Arnab et al., 2021), and 3D instance processing (Guo et al., 2021; Lin et al., 2021). To capture multi-scale non-local contexts, Zhang et al. (2020) designs transformers in self-level, top-down, and bottom-up interaction fashion. Liu et al. (2021) presents hierarchical ViTs with shifted window based attention that can efficiently extract multi-scale features. To dismiss ViT from the heavy reliance on large-scale dataset pre-training, Touvron et al. (2021a); Yuan et al. (2021) propose knowledge distillation and progressive tokenization for data-efficient training. Despite impressive effectiveness, most of these model are only based on relatively shallow ViT backbones with a dozen of MHA blocks or so.

Advances in deep ViTs.   Building deeper ViTs has arisen many interests. Zhou et al. (2021a) first investigated the depth scalability of ViT. The authors found that the attention collapse hinders ViT from scaling up, and propose two methods to conquer this problem i) increasing the embedding dimension, and ii) a cross-head re-attention trick to regenerate attention map. A concurrent work Touvron et al. (2021b) came up with a LayerScale layer that performs per-channel multiplication for each residual block. More importantly, they make explicit separation of transformer layers involving self-attention between patches, from class-attention layers that are devoted to extract the global content into a single embedding to be decoded. Gong et al. (2021) further proposed a series of losses that can enforce patch diversity in ViT. Such regularizations include penalty on cosine similarity, patch-wise contrastive loss, and mixing loss. Tang et al. (2021) presented a shortcut augmentation scheme with block-circulant projection to improve feature diversity. Although these existing solutions manage to deepen ViTs, most of them are empirical works and bring no principled theory.

Role of depth in NNs.   Discussing the importance of deep structures in Neural Networks (NNs) is an over broad topic. Here we only focus on a subset of works that scaling up a transformer could relate to. For ordinal deep learning models, such as FFNs and CNNs, deep architecture immediately

Table 1: Experimental evalutation of AttnScale & FeatScale plugged into DeiT and CaiT. The number inside the ($\uparrow \cdot$) represents the performance gain compared with the baseline model, and accuracies within/out of parenthesis are the reported/reproduced performance.

Backbone	Method	# Param	Input size	# Layer	Top-1 Acc (%)
DeiT	DeiT-S	22M	224	12	79.8 (79.9)
	DeiT-S + AttnScale	22M	224	12	80.3 ($\uparrow$ 0.5)
	DeiT-S + FeatScale	22M	224	12	80.9 ($\uparrow$ 1.1)
	DeiT-S	43M	224	24	80.5 (81.0)
	DeiT-S + AttnScale	43M	224	24	81.1 ($\uparrow$ 0.6)
	DeiT-S + FeatScale	43M	224	24	81.3 ($\uparrow$ 0.8)
CaiT	CaiT-XXS	12M	224	24	77.5 (77.6)
	CaiT-XXS + AttnScale	12M	224	24	77.8 ($\uparrow$ 0.3)
	CaiT-XXS + FeatScale	12M	224	24	77.8 ($\uparrow$ 0.3)
	CaiT-S	47M	224	24	82.6 (82.7)
	CaiT-S + AttnScale	47M	224	24	82.8 ($\uparrow$ 0.2)
	CaiT-S + FeatScale	47M	224	24	82.9 ($\uparrow$ 0.3)

benefits from the universal approximation power and expressive capacity (Cybenko, 1989; Hornik, 1991; Telgarsky, 2016; Lu et al., 2017; Petersen & Voigtlaender, 2020; Zhou, 2020). In contrast, several studies in graph learning domain have reported severe performance degradation due to over-smoothing when stacking many layers (Kipf & Welling, 2016; Wu et al., 2019; Li et al., 2018). The subsequent studies (Nt & Maehara, 2019; Oono & Suzuki, 2019; Cai & Wang, 2020) gave theoretical explanations of the over-smoothing phenomena from the views of graph signal filtering and feature dynamics. Likewise, ViT have been witnessed performance saturation when going deeper. However, to our best knowledge, Dong et al. (2021) is the sole work in the literature that systematically and rigorously analyzes this issue with deep ViT. The main idea of this work is showing the self-attention block will downgrade the rank of the feature maps. Our work takes one step forward by studying ViT on spectral domain, and manages to reveal the signals will ultimately fall into the one-dimension DC subspace. We see our theory and techniques are also applicable to NLP transformers. However, we only focus on ViT because empirical observations indicate NLP modeling (including Transformer) does not require a deep structure (Vaswani et al., 2017; Brown et al., 2020), while vision tasks always demand one (LeCun et al., 2015).

5 EXPERIMENTS

In this section, we report experiment results to validate our proposed methods. First, we testify the effectiveness of our AttnScale and FeatScale when integrated with different deep ViT backbones (Section 5.1). Second, we compare our best models with state-of-the-art (SOTA) results (Section 5.2). All of our experiments are conducted on the ImageNet dataset (Russakovsky et al., 2015) with around 1.3M images in the training set and 50k images in the validation set. Our implementations are based on Timm (Wightman, 2019) and DeiT (Touvron et al., 2021a) repositories.

5.1 HOW CAN ATTNSCALE & FEATSCALE BENEFIT DEEP VIT?

Experiment Settings. In this subsection, we intend to testify our models are beneficial to various ViT backbones with different depth settings. We choose DeiT (Touvron et al., 2021a) as our first backbone in order to train from scratch. We only test our models on DeiT-S with at most 24 layers and 512 batch size due to prohibitive computational resources. For other settings, we follow the same training recipe, hyper-parameters, and data augmentation with Touvron et al. (2021a). As suggested by Touvron et al. (2021b), we set dropout rate to 0.2 when training 24-layer DeiT. Our second backbone is CaiT (Touvron et al., 2021b), the current SOTA model for 24-layer ViT. We are aimed to testify whether CaiT can be further boosted by our proposed approaches. We only apply our techniques to the patch embedding layers. Different from DeiT, we fine-tune CaiT with AttnScale and FeatScale parameters from the pre-trained models for 60 epochs following Gong et al. (2021). For a fair comparison, we simultaneously train a plain CaiT for another 60 epochs. During fine-tuning, we reduce learning rate to 5×10^{-5} and weight decay to 5×10^{-4}. We only target on lightweight CaiT-XXS and CaiT-S finetuned with 224 resolution inputs and 256 batch size because of GPU memory bottleneck. All other hyper-parameters and training recipe are kept consistent with the original paper (Touvron et al., 2021b).

Table 2: Compared with state-of-the-art models on ImageNet dataset. Accuracies with superscript (∗) are reported by Gong et al. (2021), with superscript (†) are reported by Yuan et al. (2021), and others are reported by the original papers. Bold accuracies signifies best models among pure transformers.

Category	Method	# Param	Input size	# Layer	Top-1 Acc (%)
CNN	ResNet-152 (He et al., 2016)	230M	224	152	78.1 ∗
	DenseNet-201 (Huang et al., 2017)	77M	224	201	77.6 ∗
	EffNetV2-L (Tan & Le, 2019)	121M	384	42	85.7 ∗
CNN+ Transformer	CVT-21 (Wu et al., 2021)	32M	224	21	82.5 ∗
	LV-ViT-S (Jiang et al., 2021b)	26M	224	16	83.3 ∗
Transformer	ViT-S/16 (Dosovitskiy et al., 2020)	49M	224	12	78.1 †
	ViT-B/16 (Dosovitskiy et al., 2020)	86M	224	12	79.8 †
	DeiT-S (Touvron et al., 2021a)	22M	224	12	79.8
	DeiT-S Distilled (Touvron et al., 2021a)	22M	224	12	81.2
	SWIN-S (Liu et al., 2021)	50M	224	12	**83.0**
	T2T-ViT-24 (Yuan et al., 2021)	64M	224	24	82.3
	DeepViT-24B (Zhou et al., 2021a)	36M	224	24	80.1
	CaiT-S (Touvron et al., 2021b)	47M	224	24	82.7
	DeiT-S + DiversePatch (Gong et al., 2021)	44M	224	24	82.2
Ours	DeiT-S + AttnScale (from scratch)	43M	224	24	81.1
	DeiT-S + FeatScale (from scratch)	43M	224	24	81.3
	CaiT-S + AttnScale (fine-tuning)	47M	224	24	**82.8**
	CaiT-S + FeatScale (fine-tuning)	47M	224	24	**82.9**

Results. All of our experimental evaluations are summarized in Table 1. The results suggest our proposed AttnScale and FeatScale successfully facilitate both DeiT and CaiT under different depth settings. Specifically, AttnScale brings *less than 100/150 extra parameters for 12/24-layer DeiT* while boosting the top-1 accuracy by 0.5% for 12-layer DeiT and 0.6% for 24-layer DeiT. Our FeatScale substantially improves top-1 accuracy by 1% for 12-layer DeiT and 0.8% for 24-layer DeiT. We observe that FeatScale outperforms AttnScale by a large gap on DeiT. We explain this is because FeatScale specifies separate re-weighting factors for each channel and thus can extract richer features. When AttnScale and FeatScale cooperate with 24-layer CaiTs, we find only *tens of epoch's fine-tuning* can further promote their performance by $\geq 0.2\%$ regardless of the model size. However, FeatScale no more takes advantage over AttnScale on CaiT. We defer more model interpretation and visualization to Appendix F.4. Overall, our results demonstrate the promising effectiveness of our methods with only hundreds of parameters overhead.

5.2 COMPARED WITH SOTA MODELS

In this subsection, we compare our best models with state-of-the-art models on ImageNet benchmark. We choose SOTA models from three classes: CNN only, CNN + transformer, and pure transformer. For transformer domain, we only conduct experiments with those lightweight models with comparable number of parameters, such as ViT-S and DeiT-S. All the results are presented in Table 2.

Among all methods, our fine-tuned results (CaiT-S + AttnScale and CaiT-S + FeatScale) on 24-layer CaiT-S approach SOTA SWIN-S, and beat all other pure transformers, while keeping low parameter cost. That our performance surpasses some CNN-based models (e.g., ResNet-152 and CVT) indicates by increasing depth, ViT will be endowed with higher potential to surpass CNNs that have been dominating computer vision domain so far. Our DeiT-S+FeatScale result also outperforms ViT-B/16 and DeiT-S Distilled, which suggests deepening network can bring more considerable accuracy gain than increasing model width or employing a teacher model.

6 CONCLUSION

In this paper, we investigate the scalability issue with ViT and propose two practical solutions via Fourier domain analysis. Our theoretical findings indicate Multi-Head Self-Attention (MHA) inherently performs low-pass filtering on image signals, thus causes rank collapse and patch uniformity problems in deep ViT. To this end, we proposed two techniques, AttnScale and FeatScale, that can effectively break such low-pass filtering bottleneck by adaptively scaling high-pass filter component and high-frequency signals, respectively. Our experiments also validate the effectiveness of our methods. Both techniques can boost various ViT backbones by a significant performance gain. Grounded with our theoretical framework, interesting directions for further work include designing parameter regularizations and spectrum-specific normalization layers.

REPRODUCIBILITY STATEMENT

To ensure reproducibility, we use the Machine Learning Reproducibility Checklist v2.0, Apr. 7 2020 (Pineau et al., 2021). An earlier version of this checklist (v1.2) was used for NeurIPS 2019.

- For all **models** and **algorithms** presented,
  - **A clear description of the mathematical settings, algorithm, and/or model.** We clearly describe all of the settings, formulations, and algorithms in Section 2 and 3.
  - **A clear explanation of any assumptions.** We do not make assumptions.
  - **An analysis of the complexity (time, space, sample size) of any algorithm.** We provide a brief piece of analysis at the end of Section 3.1.
- For any **theoretical claim**,
  - **A clear statement of the claim.** We make clear and rigorous statements in Section 2.2 and Appendix C, E.
  - **A complete proof of the claim.** Complete proofs can be found in Appendix B, C, E.
- For all **datasets** used, check if you include:
  - **The relevant statistics, such as number of examples.** We only use widely adopted dataset ImageNet. All the information can be found at its official website.
  - **The details of train/validation/test splits.** We follow the standard splits.
  - **An explanation of any data that were excluded, and all pre-processing step.** We did not exclude any data. We ported the data loading pipeline from DeiT repository.
  - **A link to a downloadable version of the dataset or simulation environment.** We have attached our code within the supplementary materials.
  - **For new data collected,a complete description of the data collection process, such as instructions to annotators and methods for quality control.** We do not collect or release new datasets.
- For all reported **experimental results**, check if you include:
  - **The range of hyper-parameters considered, method to select the best hyper-parameter configuration, and specification of all hyper-parameters used to generate results.** Most of our hyper-parameters inherit from DeiT repository. We provide hyper-parameter and training recipe differences in Section 5.1.
  - **The exact number of training and evaluation runs.** Same with DeiT, CaiT, etc., we only train and evaluate once with a fixed seed.
  - **A clear definition of the specific measure or statistics used to report results.** We use standard image classification loss and metric, same with DeiT, etc.
  - **A description of results with central tendency (e.g. mean) & variation (e.g. error bars).** We only report the test accuracies run by once.
  - **The average runtime for each result, or estimated energy cost.** We do not report the running time or energy cost.
  - **A description of the computing infrastructure used.** All of our experiments are conducted on NVIDIA RTX A6000.

REFERENCES

Anurag Arnab, Mostafa Dehghani, Georg Heigold, Chen Sun, Mario Lučić, and Cordelia Schmid. Vivit: A video vision transformer. *arXiv preprint arXiv:2103.15691*, 2021.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Chen Cai and Yusu Wang. A note on over-smoothing for graph neural networks. *arXiv preprint arXiv:2006.13318*, 2020.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pp. 213–229. Springer, 2020.

Hanting Chen, Yunhe Wang, Tianyu Guo, Chang Xu, Yiping Deng, Zhenhua Liu, Siwei Ma, Chunjing Xu, Chao Xu, and Wen Gao. Pre-trained image processing transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12299–12310, 2021.

George Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of control, signals and systems*, 2(4):303–314, 1989.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint arXiv:1901.02860*, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: Pure attention loses rank doubly exponentially with depth. *arXiv preprint arXiv:2103.03404*, 2021.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Chengyue Gong, Dilin Wang, Meng Li, Vikas Chandra, and Qiang Liu. Vision transformers with patch diversification, 2021.

Meng-Hao Guo, Jun-Xiong Cai, Zheng-Ning Liu, Tai-Jiang Mu, Ralph R Martin, and Shi-Min Hu. Pct: Point cloud transformer. *Computational Visual Media*, 7(2):187–199, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kurt Hornik. Approximation capabilities of multilayer feedforward networks. *Neural networks*, 4(2): 251–257, 1991.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Yifan Jiang, Shiyu Chang, and Zhangyang Wang. Transgan: Two transformers can make one strong gan. *arXiv preprint arXiv:2102.07074*, 2021a.

Zihang Jiang, Qibin Hou, Li Yuan, Daquan Zhou, Xiaojie Jin, Anran Wang, and Jiashi Feng. Token labeling: Training a 85.5% top-1 accuracy vision transformer with 56m parameters on imagenet. *arXiv preprint arXiv:2104.10858*, 2021b.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, pp. 1–11, 2021.

Hyunjik Kim, George Papamakarios, and Andriy Mnih. The lipschitz constant of self-attention. In *International Conference on Machine Learning*, pp. 5562–5571. PMLR, 2021.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25:1097–1105, 2012.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *Thirty-Second AAAI conference on artificial intelligence*, 2018.

Kevin Lin, Lijuan Wang, and Zicheng Liu. End-to-end human pose and mesh reconstruction with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1954–1963, 2021.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *arXiv preprint arXiv:2103.14030*, 2021.

Zhou Lu, Hongming Pu, Feicheng Wang, Zhiqiang Hu, and Liwei Wang. The expressive power of neural networks: A view from the width. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 6232–6240, 2017.

Carl D Meyer. *Matrix analysis and applied linear algebra*, volume 71. Siam, 2000.

Hoang Nt and Takanori Maehara. Revisiting graph neural networks: All we have is low-pass filters. *arXiv preprint arXiv:1905.09550*, 2019.

Kenta Oono and Taiji Suzuki. Graph neural networks exponentially lose expressive power for node classification. *arXiv preprint arXiv:1905.10947*, 2019.

Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Lukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. Image transformer. In *International Conference on Machine Learning*, pp. 4055–4064. PMLR, 2018.

Philipp Petersen and Felix Voigtlaender. Equivalence of approximation by convolutional neural networks and fully-connected networks. *Proceedings of the American Mathematical Society*, 148 (4):1567–1581, 2020.

Joelle Pineau, Philippe Vincent-Lamarre, Koustuv Sinha, Vincent Larivière, Alina Beygelzimer, Florence d'Alché Buc, Emily Fox, and Hugo Larochelle. Improving reproducibility in machine learning research (a report from the neurips 2019 reproducibility program). *Journal of Machine Learning Research*, 22, 2021.

Dana Randall. Rapidly mixing markov chains with applications in computer science and physics. *Computing in Science & Engineering*, 8(2):30–41, 2006.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115 (3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Zhiqing Sun, Shengcao Cao, Yiming Yang, and Kris Kitani. Rethinking transformer-based set prediction for object detection. *arXiv preprint arXiv:2011.10881*, 2020.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pp. 6105–6114. PMLR, 2019.

Yehui Tang, Kai Han, Chang Xu, An Xiao, Yiping Deng, Chao Xu, and Yunhe Wang. Augmented shortcuts for vision transformers. *arXiv preprint arXiv:2106.15941*, 2021.

Matus Telgarsky. Benefits of depth in neural networks. In *Conference on learning theory*, pp. 1517–1539. PMLR, 2016.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pp. 10347–10357. PMLR, 2021a.

Hugo Touvron, Matthieu Cord, Alexandre Sablayrolles, Gabriel Synnaeve, and Hervé Jégou. Going deeper with image transformers. *arXiv preprint arXiv:2103.17239*, 2021b.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Nitika Verma, Edmond Boyer, and Jakob Verbeek. Feastnet: Feature-steered graph convolutions for 3d shape analysis. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2598–2606, 2018.

Yuqing Wang, Zhaoliang Xu, Xinlong Wang, Chunhua Shen, Baoshan Cheng, Hao Shen, and Huaxia Xia. End-to-end video instance segmentation with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8741–8750, 2021.

Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *International conference on machine learning*, pp. 6861–6871. PMLR, 2019.

Haiping Wu, Bin Xiao, Noel Codella, Mengchen Liu, Xiyang Dai, Lu Yuan, and Lei Zhang. Cvt: Introducing convolutions to vision transformers. *arXiv preprint arXiv:2103.15808*, 2021.

Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. Do transformers really perform bad for graph representation? *arXiv preprint arXiv:2106.05234*, 2021.

Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Zihang Jiang, Francis EH Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-token vit: Training vision transformers from scratch on imagenet. *arXiv preprint arXiv:2101.11986*, 2021.

Aston Zhang, Alvin Chan, Yi Tay, Jie Fu, Shuohang Wang, Shuai Zhang, Huajie Shao, Shuochao Yao, and Roy Ka-Wei Lee. On orthogonality constraints for transformers.

Biao Zhang, Ivan Titov, and Rico Sennrich. Improving deep transformer with depth-scaled initialization and merged attention. *arXiv preprint arXiv:1908.11365*, 2019.

Dong Zhang, Hanwang Zhang, Jinhui Tang, Meng Wang, Xiansheng Hua, and Qianru Sun. Feature pyramid transformer. In *European Conference on Computer Vision*, pp. 323–339. Springer, 2020.

Minghang Zheng, Peng Gao, Xiaogang Wang, Hongsheng Li, and Hao Dong. End-to-end object detection with adaptive clustering transformer. *arXiv preprint arXiv:2011.09315*, 2020.

Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Zihang Jiang, Qibin Hou, and Jiashi Feng. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021a.

Daquan Zhou, Yujun Shi, Bingyi Kang, Weihao Yu, Zihang Jiang, Yuan Li, Xiaojie Jin, Qibin Hou, and Jiashi Feng. Refiner: Refining self-attention for vision transformers. *arXiv preprint arXiv:2106.03714*, 2021b.

Ding-Xuan Zhou. Universality of deep convolutional neural networks. *Applied and computational harmonic analysis*, 48(2):787–794, 2020.

Luowei Zhou, Yingbo Zhou, Jason J Corso, Richard Socher, and Caiming Xiong. End-to-end dense video captioning with masked transformer. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8739–8748, 2018.

Xizhou Zhu, Weijie Su, Lewei Lu, Bin Li, Xiaogang Wang, and Jifeng Dai. Deformable detr: Deformable transformers for end-to-end object detection. *arXiv preprint arXiv:2010.04159*, 2020.

A MORE PRELIMINARIES ON FOURIER ANALYSIS

In this appendix, we provide more preliminary knowledge about Fourier analysis. Here, we only consider discrete Fourier transform on real-value domain $\mathcal{F} : \mathbb{R}^n \to \mathbb{C}^n$. A Discrete Fourier transform (DFT) can be written in a matrix form as below:

$$
\boldsymbol{DFT} = \frac{1}{\sqrt{n}} \begin{bmatrix} 1 & 1 & \cdots & 1 \\ 1 & e^{2\pi\mathrm{j}} & \cdots & e^{2\pi\mathrm{j}(n-1)} \\ \vdots & \vdots & \ddots & \vdots \\ 1 & e^{2\pi\mathrm{j}(k-1)\cdot 1} & \cdots & e^{2\pi\mathrm{j}(k-1)\cdot(n-1)} \\ \vdots & \vdots & \ddots & \vdots \\ 1 & e^{2\pi\mathrm{j}(n-1)} & \cdots & e^{2\pi\mathrm{j}(n-1)^2} \end{bmatrix}, \tag{13}
$$

and its inverse discrete Fourier transform is $\boldsymbol{DFT}^{-1} = \boldsymbol{DFT}$. In this paper, we regard matrices as multi-channel signals. For example, $\boldsymbol{X} \in \mathbb{R}^{n \times d}$ means d-channel n-length signals. When DFT and inverse DFT are applies to multi-channel signals, each channel is transformed independently, i.e., $\mathcal{F}(\boldsymbol{X}) = [\mathcal{F}(\boldsymbol{x}_1) \quad \cdots \quad \mathcal{F}(\boldsymbol{x}_d)] = \boldsymbol{DFT} \cdot \boldsymbol{X}$.

Hereby, we can simply operators $\mathcal{DC}[\cdot]$ and $\mathcal{HC}[\cdot]$ using the matrices in Eqn. 13. By definition, we can write $\mathcal{DC}[\cdot]$ as below:

$$
\mathcal{DC}[\boldsymbol{x}] = \boldsymbol{DFT}^{-1} \operatorname{diag}(1, 0, \cdots, 0) \boldsymbol{DFT} \boldsymbol{x} \tag{14}
$$

$$
= \frac{1}{n} \boldsymbol{1} \boldsymbol{1}^T \boldsymbol{x}, \tag{15}
$$

namely $\mathcal{DC}[\cdot] = \boldsymbol{1}\boldsymbol{1}^T/n$. Conversely, we can write $\mathcal{HC}[\cdot]$ as:

$$
\mathcal{HC}[\boldsymbol{x}] = \boldsymbol{DFT}^{-1} \operatorname{diag}(0, 1, \cdots, 1) \boldsymbol{DFT} \boldsymbol{x} \tag{16}
$$

$$
= \boldsymbol{DFT}^{-1}(\boldsymbol{I} - \operatorname{diag}(1, 0, \cdots, 0)) \boldsymbol{DFT} \boldsymbol{x} \tag{17}
$$

$$
= \boldsymbol{I} - \frac{1}{n} \boldsymbol{1} \boldsymbol{1}^T \boldsymbol{x}, \tag{18}
$$

which indicates $\mathcal{HC}[\cdot] = \boldsymbol{I} - \boldsymbol{1}\boldsymbol{1}^T/n$. We will frequently use these derivations later in the proofs.

B DEFERRED PROOFS

B.1 PROOF OF THEOREM 1

Theorem 1. *(SA matrix is a low-pass filter) Let $\boldsymbol{A} = \operatorname{softmax}(\boldsymbol{P})$, where $\boldsymbol{P} \in \mathbb{R}^{n \times n}$. Then $\boldsymbol{A}$ must be a low-pass filter. For all $\boldsymbol{z} \in \mathbb{R}^n$,*

$$
\lim_{t \to \infty} \frac{\|\mathcal{HC}[\boldsymbol{A}^t \boldsymbol{z}]\|_2}{\|\mathcal{DC}[\boldsymbol{A}^t \boldsymbol{z}]\|_2} = 0.
$$

Proof. Let $\lambda_1, \lambda_2, \cdots, \lambda_s \in \mathbb{C}$ be the eigenvalues of $\boldsymbol{A}$ with ordering $|\lambda_1| \geq |\lambda_2| \geq \cdots \geq |\lambda_s|$. Notice that, $\boldsymbol{A}$ is a positive matrix, each of whose element is strictly greater than zero ($\boldsymbol{A}_{ij} > 0, \forall i, j$). Besides, for all $i = 1, \cdots, n$, $\sum_{j=1}^{n} \boldsymbol{A}_{i,j} = 1$. Therefore, $\boldsymbol{A}\boldsymbol{1} = \boldsymbol{1}$ implies $\boldsymbol{A}$ must have an eigenvalue 1 and its corresponding eigenvector is the all-one vector $\boldsymbol{1}$.

By Perron-Frobenius Theorem (Meyer, 2000), eigenvalue 1 corresponds to a all-positive eigenvector $\boldsymbol{1}$, implies $\lambda_1 = 1$ should be the largest eigenvalue without multiplicity, and the absolute value of other eigenvalues $\lambda_2, \cdots, \lambda_s$ must be less than 1. Let us rewrite $\boldsymbol{A}$ in the Jordan canonical form $\boldsymbol{A} = \boldsymbol{PJP}^{-1}$:

$$
\boldsymbol{A} = \underbrace{\begin{bmatrix} \boldsymbol{v}_1 & \cdots & \boldsymbol{v}_n \end{bmatrix}}_{\boldsymbol{P}} \underbrace{\begin{bmatrix} \lambda_1 & & & \\ & \boldsymbol{J}(\lambda_2) & & \\ & & \ddots & \\ & & & \boldsymbol{J}(\lambda_s) \end{bmatrix}}_{\boldsymbol{J}} \underbrace{\begin{bmatrix} \boldsymbol{u}_1^T \\ \vdots \\ \boldsymbol{u}_n^T \end{bmatrix}}_{\boldsymbol{P}^{-1}}, \tag{19}
$$

where the Jordan block $J(\lambda)$ can be written as

$$
J(\lambda) = \begin{bmatrix} \lambda & 1 & & & \\ & \lambda & 1 & & \\ & & \ddots & \ddots & \\ & & & \lambda & 1 \\ & & & & \lambda \end{bmatrix}.
\tag{20}
$$

Applying A to z for t times can be written as $A^t z$ which is equivalent to:

$$
A^t z = P J^t P^{-1} z = P \begin{bmatrix} \lambda_1 & & & \\ & J(\lambda_2) & & \\ & & \ddots & \\ & & & J(\lambda_s) \end{bmatrix}^t P^{-1} z
\tag{21}
$$

$$
= P \begin{bmatrix} \lambda_1^t & & & \\ & J(\lambda_2)^t & & \\ & & \ddots & \\ & & & J(\lambda_s)^t \end{bmatrix} P^{-1} z
\tag{22}
$$

Let $f(x) = x^t$, then $A^t = P f(J) P^{-1} = P \operatorname{diag}(f(\lambda_1), f(J(\lambda_2)), \cdots, f(J(\lambda_s))) P^{-1}$. Suppose a Jordan block with shape $k \times k$, then

$$
f(J(\lambda)) = \begin{bmatrix} f(\lambda) & f'(\lambda) & \frac{f''(\lambda)}{2!} & \cdots & \frac{f^{(k-1)}(\lambda)}{(k-1)!} \\ & f(\lambda) & f'(\lambda) & \ddots & \vdots \\ & & \ddots & \ddots & \frac{f''(\lambda)}{2!} \\ & & & f(\lambda) & f'(\lambda) \\ & & & & f(\lambda) \end{bmatrix}
\tag{23}
$$

Therefore, on the diagonal number $m \le \min(t, k-1)$ above the main diagonal stands:

$$
\frac{t(t-1)...(t-m+1)}{m!} \lambda^{t-m}
\tag{24}
$$

For arbitrary $m \le k-1$ and $|\lambda| < 1$,

$$
\lim_{t \to \infty} \frac{t(t-1)...(t-m+1)}{m!} \lambda^{t-m} = 0
\tag{25}
$$

Recall that $\lambda_1 = 1$ and according to the definition of Jordan canonical form, $v_1 = \mathbf{1}$. By Eqn. 25:

$$
\lim_{t \to \infty} A^t z = P \lim_{t \to \infty} \operatorname{diag}(f(\lambda_1), f(J(\lambda_2)), \cdots, f(J(\lambda_s))) P^{-1} z
\tag{26}
$$

$$
= P \operatorname{diag}(\lambda_1^t, \mathbf{0}, \cdots, \mathbf{0}) P^{-1} z
\tag{27}
$$

$$
= \lambda_1^t v_1 u_1^T z
\tag{28}
$$

$$
= \mathbf{1} u_1^T z
\tag{29}
$$

Plug the result from Eqn. 29 into the original limit:

$$\lim_{t\to\infty} \frac{\|\mathcal{HC}\,[\boldsymbol{A}^t\boldsymbol{z}]\|_2}{\|\mathcal{DC}\,[\boldsymbol{A}^t\boldsymbol{z}]\|_2} = \lim_{t\to\infty} \sqrt{\frac{\|\mathcal{HC}\,[\boldsymbol{A}^t\boldsymbol{z}]\|_2^2}{\|\boldsymbol{z} - \mathcal{HC}\,[\boldsymbol{A}^t\boldsymbol{z}]\|_2^2}} \tag{30}$$

$$= \lim_{t\to\infty} \sqrt{\frac{\|\mathcal{HC}\,[\boldsymbol{A}^t\boldsymbol{z}]\|_2^2}{\|\boldsymbol{z}\|_2^2 - \|\mathcal{HC}\,[\boldsymbol{A}^t\boldsymbol{z}]\|_2^2}} \tag{31}$$

$$= \lim_{t\to\infty} \sqrt{\frac{\|(\boldsymbol{I} - \frac{1}{n}\boldsymbol{1}\boldsymbol{1}^T)\boldsymbol{A}^t\boldsymbol{z}\|_2^2}{\|\boldsymbol{z}\|_2^2 - \|(\boldsymbol{I} - \frac{1}{n}\boldsymbol{1}\boldsymbol{1}^T)\boldsymbol{A}^t\boldsymbol{z}\|_2^2}} \tag{32}$$

$$= \sqrt{\frac{\|(\boldsymbol{I} - \frac{1}{n}\boldsymbol{1}\boldsymbol{1}^T)\boldsymbol{1}\boldsymbol{u}_1^T\boldsymbol{z}\|_2^2}{\|\boldsymbol{z}\|_2^2 - \|(\boldsymbol{I} - \frac{1}{n}\boldsymbol{1}\boldsymbol{1}^T)\boldsymbol{1}\boldsymbol{u}_1^T\boldsymbol{z}\|_2^2}} \tag{33}$$

$$= \sqrt{\frac{\|(\boldsymbol{I}\boldsymbol{1}\boldsymbol{u}_1^T\boldsymbol{z} - \boldsymbol{1}\boldsymbol{u}_1^T\boldsymbol{z}\|_2^2}{\|\boldsymbol{z}\|_2^2 - \|(\boldsymbol{I}\boldsymbol{1}\boldsymbol{u}_1^T\boldsymbol{z} - \boldsymbol{1}\boldsymbol{u}_1^T\boldsymbol{z}\|_2^2}} \tag{34}$$

$$= 0 \tag{35}$$

where Eqn. 31 is due to the orthogonality of DC and HC terms. $\qquad\square$

B.2 PROOF OF COROLLARY 2

Corollary 2. *Let $\boldsymbol{P}_1, \boldsymbol{P}_2, \cdots, \boldsymbol{P}_n$ be a sequence of matrix in $\mathbb{R}^{n\times n}$, and each $\boldsymbol{P}_k, \forall k = 1, \cdots, L$ has $\boldsymbol{A}_k = \mathrm{softmax}(\boldsymbol{P}_k)$. Then $\prod_{k=1}^{L} \boldsymbol{A}_k$ is also a low-pass filter.*

Proof. Let $\boldsymbol{A} = \prod_{k=1}^{L} \boldsymbol{A}_k$, then we show $\boldsymbol{A}$ satisfies the following conditions, so that $\boldsymbol{A}$ can be regarded as another self-attention matrix. Then we can conclude the proof by Theorem 1.

1) For every $i = 1, \cdots, n$, $\sum_{j=1}^{n} \boldsymbol{A}_{ij} = 1$.

Suppose $\sum_{j=1}^{n} \boldsymbol{B}_{ij} = 1$ for every $i = 1, \cdots, n$, then for every $k = 1, \cdots, L$ and $i = 1, \cdots, n$,

$$\sum_{j=1}^{n}(\boldsymbol{A}_k\boldsymbol{B})_{ij} = \sum_{j=1}^{n}\sum_{m=1}^{n} \boldsymbol{A}_{k,im}\boldsymbol{B}_{mj} \tag{36}$$

$$= \sum_{m=1}^{n}\left(\boldsymbol{A}_{k,im}\left(\sum_{j=1}^{n}\boldsymbol{B}_{mj}\right)\right) \tag{37}$$

$$= \sum_{m=1}^{n} \boldsymbol{A}_{k,im} = 1. \tag{38}$$

By induction, for every i, $\sum_{j=1}^{n} \boldsymbol{A}_{1,ij} = 1 \Rightarrow \sum_{j=1}^{n}(\boldsymbol{A}_2\boldsymbol{A}_1)_{ij} = 1 \Rightarrow \cdots \Rightarrow \sum_{j=1}^{n} \boldsymbol{A}_{ij} = 1$.

2) For every $i, j = 1, \cdots, n$, $\boldsymbol{A}_{ij} > 0$.

Suppose $\boldsymbol{B}_{ij} > 0, \forall i, j$, then for every $k = 1, \cdots, L$, $(\boldsymbol{A}_k\boldsymbol{B})_{ij} = \sum_{k=1}^{n} \boldsymbol{A}_{k,im}\boldsymbol{B}_{mj}$. Since $\boldsymbol{A}_{k,im} > 0, \boldsymbol{B}_{mj} > 0$, then $(\boldsymbol{A}_k\boldsymbol{B})_{ij} > 0$. By induction, for every i, j, $\boldsymbol{A}_{1,ij} > 0 \Rightarrow (\boldsymbol{A}_2\boldsymbol{A}_1)_{ij} > 0 \Rightarrow \cdots \Rightarrow \boldsymbol{A}_{ij} > 0$. $\qquad\square$

B.3 PROOF OF THEOREM 3

Theorem 3. *(convergence rate of SA) Let $\boldsymbol{A} = \mathrm{softmax}(\boldsymbol{P})$ and $\alpha = \max_{i,j}|\boldsymbol{P}_{ij}|$, where $\boldsymbol{P} \in \mathbb{R}^{n\times n}$. Define $\mathrm{SA}(\boldsymbol{X}) = \boldsymbol{A}\boldsymbol{X}\boldsymbol{W}_V$ as the output of a self-attention module, then*

$$\|\mathcal{HC}\,[\mathrm{SA}(\boldsymbol{X})]\|_F \leq \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha} + n - 1}}\|\boldsymbol{W}_V\|_2\|\mathcal{HC}\,[\boldsymbol{X}]\|_F.$$

In particular, when $\boldsymbol{P} = \boldsymbol{X}\boldsymbol{W}_Q(\boldsymbol{X}\boldsymbol{W}_K)^T/\sqrt{d}$, and assume tokens are distributed inside a ball with radius $\gamma > 0$, i.e., $\|\boldsymbol{x}_i\|_2 \leq \gamma, \forall i = 1, \cdots, n$, then $\alpha \leq \gamma^2\|\boldsymbol{W}_Q\boldsymbol{W}_K^T\|_2/\sqrt{d}$.

Proof. First, we write $\boldsymbol{X} = \mathcal{DC}\left[\boldsymbol{X}\right] + \mathcal{HC}\left[\boldsymbol{X}\right] = \mathbf{1}^T \boldsymbol{z} + \boldsymbol{H}$, where $\mathcal{DC}\left[\boldsymbol{X}\right] = \mathbf{1}\boldsymbol{z}^T$ equals to the orthogonal projection of $\boldsymbol{X}$ to subspace $\text{span}(\mathbf{1})$, and $\boldsymbol{H} = \mathcal{HC}\left[\boldsymbol{X}\right]$ represents the remaining part of the original signals.

$$\mathcal{HC}\left[\text{SA}(\boldsymbol{X})\right] = (\boldsymbol{I} - \mathbf{1}\mathbf{1}^T)\boldsymbol{A}\boldsymbol{X}\boldsymbol{W}_V \tag{39}$$

$$= \left(\boldsymbol{I} - \frac{1}{n}\mathbf{1}\mathbf{1}^T\right)\boldsymbol{A}(\mathbf{1}\boldsymbol{z}^T + \boldsymbol{H})\boldsymbol{W}_V \tag{40}$$

$$= \left(\boldsymbol{I} - \frac{1}{n}\mathbf{1}\mathbf{1}^T\right)\boldsymbol{A}\mathbf{1}\boldsymbol{z}^T\boldsymbol{W}_V + \left(\boldsymbol{I} - \frac{1}{n}\mathbf{1}\mathbf{1}^T\right)\boldsymbol{A}\boldsymbol{H}\boldsymbol{W}_V \tag{41}$$

$$= \left(\boldsymbol{I} - \frac{1}{n}\mathbf{1}\mathbf{1}^T\right)\boldsymbol{A}\boldsymbol{H}\boldsymbol{W}_V \tag{42}$$

Therefore,

$$\|\mathcal{HC}\left[\text{SA}(\boldsymbol{X})\right]\|_F = \left\|\left(\boldsymbol{I} - \frac{1}{n}\mathbf{1}\mathbf{1}^T\right)\boldsymbol{A}\boldsymbol{H}\boldsymbol{W}_V\right\|_F \tag{43}$$

$$\leq \left\|\boldsymbol{I} - \frac{1}{n}\mathbf{1}\mathbf{1}^T\right\|_2 \|\text{softmax}(\boldsymbol{P})\|_2\|\boldsymbol{W}_V\|_2\|\boldsymbol{H}\|_F \tag{44}$$

$$\leq \sqrt{\|\text{softmax}(\boldsymbol{P})\|_1\|\text{softmax}(\boldsymbol{P})\|_\infty}\|\boldsymbol{W}_V\|_2\|\boldsymbol{H}\|_F \tag{45}$$

$$= \sqrt{\|\text{softmax}(\boldsymbol{P})\|_1}\|\boldsymbol{W}_V\|_2\|\boldsymbol{H}\|_F \tag{46}$$

The Eqn. 45 leverages a special case of Hölder's inequality, and the Eqn. 46 can be yielded from $\|\text{softmax}(\boldsymbol{P})\|_\infty = 1$. Now we need to upper bound $\|\text{softmax}(\boldsymbol{P})\|_1$. Suppose $\alpha = \max_{i,j}|\boldsymbol{P}_{ij}|$, then for each $i = 1, \cdots, n$, we have the following inequality for the element with the largest value (say the j-th column):

$$\boldsymbol{A}_{ij} = \frac{e^{\boldsymbol{P}_{ij}}}{\sum_{t=1}^n e^{\boldsymbol{P}_{it}}} \leq \frac{e^\alpha}{e^\alpha + \sum_{t\neq j} e^{-\alpha}} = \frac{e^{2\alpha}}{e^{2\alpha} + (n-1)} \tag{47}$$

Hence, we have $\|\text{softmax}(\boldsymbol{P})\|_1 \leq \sum_i \max_j \boldsymbol{A}_{ij} \leq \frac{ne^{2\alpha}}{e^{2\alpha}+(n-1)}$. Insert this result to Eqn. 46, we can conclude the proof. In particular, when $\boldsymbol{P} = \boldsymbol{X}\boldsymbol{W}_Q(\boldsymbol{X}\boldsymbol{W}_K)^T/\sqrt{d}$,

$$\alpha = \max_{i,j}|\boldsymbol{P}_{ij}| = \max_{i,j}\left|\frac{\boldsymbol{x}_i^T\boldsymbol{W}_Q\boldsymbol{W}_K^T\boldsymbol{x}_j}{\sqrt{d}}\right|. \tag{48}$$

Since $\|\boldsymbol{x}_i\|_2, \|\boldsymbol{x}_j\|_2 \leq \gamma, \forall i,j$, $\alpha \leq \max_{i,j}\|\boldsymbol{x}_i\|_2\|\boldsymbol{W}_Q\boldsymbol{W}_K^T\|_2\|\boldsymbol{x}_j\|_2/\sqrt{d} \leq \gamma^2\|\boldsymbol{W}_Q\boldsymbol{W}_K^T\|_2/\sqrt{d}$. □

C EXTENSION OF THEOREM 3

C.1 MULTI-HEAD ATTENTION

Proposition 4. *(convergence rate with MHA) Let $\boldsymbol{A}^h = \text{softmax}(\boldsymbol{P}^h)$, where $\boldsymbol{P}^h \in \mathbb{R}^{n\times n}$ with $h = 1, \cdots, H$. Let $\alpha = \max_{h=1}^H \max_{i,j}|\boldsymbol{P}_{ij}^h|$. Define $\text{MHA}(\boldsymbol{X}) = \sum_{h=1}^H \boldsymbol{A}^h\boldsymbol{X}\boldsymbol{W}_V^h\boldsymbol{W}_O^h$ as the output of a multi-head self-attention module, then*

$$\|\mathcal{HC}\left[\text{MHA}(\boldsymbol{X})\right]\|_F \leq \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F,$$

where H is the number of heads, $\sigma_1 = \max_{h=1}^H\|\boldsymbol{W}_V^h\|_2$ and $\sigma_2 = \max_{h=1}^H\|\boldsymbol{W}_O^h\|_2$.

Proof. For the h-th head, according to Theorem 3:

$$\|\mathcal{HC}\left[\text{SA}_h(\boldsymbol{X})\right]\|_F \leq \sqrt{\frac{ne^{2\alpha_h}}{e^{2\alpha_h}+n-1}}\|\boldsymbol{W}_V^h\|_2\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F, \tag{49}$$

where $\alpha_h = \max_{i,j}|\boldsymbol{P}_{ij}^h|$. Then we have:

$$\|\mathcal{HC}\left[\mathrm{MHA}_h(\boldsymbol{X})\right]\|_F = \left\|\mathcal{HC}\left[\sum_{h=1}^H \mathrm{SA}_h(\boldsymbol{X})\boldsymbol{W}_O^h\right]\right\|_F \tag{50}$$

$$\leq \sum_{h=1}^H \left\|\mathcal{HC}\left[\mathrm{SA}_h(\boldsymbol{X})\boldsymbol{W}_O^h\right]\right\|_F \tag{51}$$

$$\leq \sum_{h=1}^H \sqrt{\frac{ne^{2\alpha_h}}{e^{2\alpha_h}+n-1}}\|\boldsymbol{W}_V^h\|_2\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_2 \tag{52}$$

$$\leq \sum_{h=1}^H \sqrt{\frac{ne^{2\alpha_h}}{e^{2\alpha_h}+n-1}}\|\boldsymbol{W}_V^h\|_2\|\boldsymbol{W}_O^h\|_2\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F \tag{53}$$

$$\leq \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F, \tag{54}$$

where Eqn. 51 follows from the linearity of $\mathcal{HC}\left[\cdot\right]$ and triangle inequality. Eqn. 54 can be obtained by relaxing α_h, $\|\boldsymbol{W}_V^h\|_2$, and $\|\boldsymbol{W}_O^h\|_2$ to α, σ_1 and σ_2 (Note that $\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}$ is monotonically increasing with α). $\qquad\square$

C.2 RESIDUAL CONNECTION

Proposition 5. *(convergence rate with skip connection) Let $\boldsymbol{A}^h = \mathrm{softmax}(\boldsymbol{P}^h)$, where $\boldsymbol{P}^h \in \mathbb{R}^{n\times n}$ with $h = 1,\cdots,H$. Let $\alpha = \max_{h=1}^H \max_{i,j}|\boldsymbol{P}_{ij}^h|$. Define $\boldsymbol{X}' = \mathrm{MHA}(\boldsymbol{X}) + \boldsymbol{X}$ as the output of a multi-head self-attention module with skip connection, then*

$$\|\mathcal{HC}\left[\boldsymbol{X}'\right]\|_F \leq \left(1 + \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\right)\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F$$

where H is the number of heads, $\sigma_1 = \max_{h=1}^H\|\boldsymbol{W}_V^h\|_2$ and $\sigma_2 = \max_{h=1}^H\|\boldsymbol{W}_O^h\|_2$.

Proof. By Proposition 4,

$$\|\mathcal{HC}\left[\boldsymbol{X}'\right]\|_F = \|\mathcal{HC}\left[\mathrm{MHA}(\boldsymbol{X}) + \boldsymbol{X}\right]\|_F \tag{55}$$

$$\leq \|\mathcal{HC}\left[\mathrm{MHA}(\boldsymbol{X})\right]\|_F + \|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F \tag{56}$$

$$\leq \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F + \|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F \tag{57}$$

$$= \left(1 + \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\right)\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F. \tag{58}$$

Again, Eqn. 56 follows from the linearity of $\mathcal{HC}\left[\cdot\right]$ and triangle inequality. $\qquad\square$

C.3 FEED-FORWARD NETWORK

Proposition 6. *(convergence rate with FFN) Let $\boldsymbol{A}^h = \mathrm{softmax}(\boldsymbol{P}^h)$, where $\boldsymbol{P}^h \in \mathbb{R}^{n\times n}$ with $h = 1,\cdots,H$. Let $\alpha = \max_{h=1}^H \max_{i,j}|\boldsymbol{P}_{ij}^h|$. Define $\boldsymbol{Y} = \mathrm{FFN}(\mathrm{MHA}(\boldsymbol{X}) + \boldsymbol{X})$ as the output of a transformer block, then*

$$\|\mathcal{HC}\left[\boldsymbol{Y}\right]\|_F \leq \sigma_3 \left(1 + \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\right)\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F$$

where $FFN : \mathbb{R}^d \to \mathbb{R}^d$ represents a feed-forward network, H is the number of heads, $\sigma_1 = \max_{h=1}^H\|\boldsymbol{W}_V^h\|_2$, $\sigma_2 = \max_{h=1}^H\|\boldsymbol{W}_O^h\|_2$, and $\sigma_3 = \mathrm{Lips}(\mathrm{FFN})$ is the Lipschitz constant of FFN. In particular, $\sigma_3 = 1 + \mathrm{Lips}(\mathrm{FFN})$ when residual connection is considered in FFN.

Proof. Let $\boldsymbol{X}' = \mathrm{MHA}(\boldsymbol{X}) + \boldsymbol{X}$ and $\boldsymbol{z}' = \boldsymbol{1}^T(\boldsymbol{X}'/n) \in \mathbb{R}^d$, then we have

$$\|\mathcal{HC}\left[\mathrm{FFN}(\boldsymbol{X}')\right]\|_F \leq \|\mathrm{FFN}(\boldsymbol{X}') - \boldsymbol{1}\,\mathrm{FFN}(\boldsymbol{z})^T\|_F \tag{59}$$

$$= \|\mathrm{FFN}(\boldsymbol{X}') - \mathrm{FFN}(\boldsymbol{1}\boldsymbol{z}^T)\|_F \tag{60}$$

$$\leq \sigma_3 \|\boldsymbol{X}' - \boldsymbol{1}\boldsymbol{z}^T\|_F \tag{61}$$

$$= \sigma_3 \left\|\left(\boldsymbol{I} - \frac{1}{n}\boldsymbol{1}\boldsymbol{1}^T\right)\boldsymbol{X}'\right\|_F = \sigma_3\|\mathcal{HC}\left[\boldsymbol{X}'\right]\|_F \tag{62}$$

$$\leq \sigma_3 \left(1 + \sigma_1\sigma_2 H\sqrt{\frac{ne^{2\alpha}}{e^{2\alpha} + n - 1}}\right)\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F, \tag{63}$$

where Eqn. 59 follows from Lemma 7, Eqn. 60 holds because FFN operates row-wisely on feature matrix, and Eqn. 61 is due to the definition of Lipschitz constant. Finally, Eqn. 63 is yielded from Proposition 5. $\qquad\square$

Lemma 7. *Given* $\boldsymbol{X} \in \mathbb{R}^{n \times d}$, $\|\mathcal{HC}\left[\boldsymbol{X}\right]\|_F \leq \|\boldsymbol{X} - \boldsymbol{1}\boldsymbol{z}^T\|_F$ *for all* $\boldsymbol{z} \in \mathbb{R}^d$.

Proof. We prove the Lemma by showing that $\boldsymbol{z}^* = \boldsymbol{X}^T\boldsymbol{1}/n$ achieves the minimum of the optimization problem $\arg\min_{\boldsymbol{z}}\|\boldsymbol{X} - \boldsymbol{1}\boldsymbol{z}^T\|_F^2$.

$$\|\boldsymbol{X} - \boldsymbol{1}\boldsymbol{z}^T\|_F^2 = \mathrm{Tr}(\boldsymbol{X}^T - \boldsymbol{z}\boldsymbol{1}^T)(\boldsymbol{X} - \boldsymbol{1}\boldsymbol{z}^T) \tag{64}$$

$$= \mathrm{Tr}(\boldsymbol{X}^T\boldsymbol{X}) - \mathrm{Tr}(\boldsymbol{z}\boldsymbol{1}^T\boldsymbol{X}) - \mathrm{Tr}(\boldsymbol{X}^T\boldsymbol{1}\boldsymbol{z}^T) + \mathrm{Tr}(\boldsymbol{z}^T\boldsymbol{1}^T\boldsymbol{1}\boldsymbol{z}) \tag{65}$$

$$= n\boldsymbol{z}^T\boldsymbol{z} - 2\,\mathrm{Tr}(\boldsymbol{X}^T\boldsymbol{1}\boldsymbol{z}^T) + \mathrm{Tr}(\boldsymbol{X}^T\boldsymbol{X}) \tag{66}$$

It is easy to show the derivative in terms of $\boldsymbol{z}$:

$$\nabla_{\boldsymbol{z}}\|\boldsymbol{X} - \boldsymbol{1}\boldsymbol{z}^T\|_F^2 = 2n\boldsymbol{z} - 2\boldsymbol{X}^T\boldsymbol{1}. \tag{67}$$

Therefore, $\boldsymbol{z}^* = \frac{1}{n}\boldsymbol{X}^T\boldsymbol{1}$ achieves the minimum. $\qquad\square$

D DEFERRED REMARKS ON SECTION 2.4

D.1 CONNECTION WITH RANDOM WALK THEORY

We add that the asymptotic evolution of feature representations can be interpreted through the lens of random walk theory. We can regard self-attention map $\boldsymbol{A}$ as probability transition matrices for a Markov chain. Since each entry is larger than zero, the Markov chain should be irreducible. This implies the Markov chain will converge into a unique stationary distribution $\boldsymbol{\pi}$ (Randall, 2006). Let $\boldsymbol{a}_i$ denote the i-th row of $\boldsymbol{A}$, then for all $i = 1, \cdots, n$ we have $\|(\boldsymbol{a}_i)^T\boldsymbol{A} - \boldsymbol{\pi}^T\| \leq \lambda\|\boldsymbol{a}_i - \boldsymbol{\pi}\|$, where $\lambda \in (0, 1)$ is the mixing rate of the transition matrix $\boldsymbol{A}$. As a consequence, $\lim_{l\to\infty}\boldsymbol{A}^l = \boldsymbol{1}\boldsymbol{\pi}^T$ yields a pure low-pass filter. When repeatedly applying this self-attention matrix to feature maps, $\lim_{l\to\infty}\boldsymbol{A}^l\boldsymbol{X} \to \boldsymbol{1}\boldsymbol{\pi}^T\boldsymbol{X}$ only preserves the rank-1/DC portion of the signals, which is consistent with our Theorem 1. Nevertheless, this interpretation does not bring other transformer components into consideration. And our theory further provides a concrete convergence rate with respect to the network parameters (Theorem 3).

D.2 REMARKS ON DONG ET AL. (2021)

Here we respectfully elaborate on the hidden assumptions in the proof of the current preprint of Dong et al. (2021).

1) In the proof of Lemma A.3, Taylor expansion was used to approximate and upper bound an exponentiation. However, to let the right-hand side upper bound satisfied, we conjectured that the authors implicitly assumed $\boldsymbol{E}_{ij} - \boldsymbol{E}_{ij'}$ is bounded around zero. After directly communicating with the authors, they confirmed that a missed assumption here is $\max_{i,j}(\boldsymbol{E}_{ij} - \boldsymbol{E}_{ij'}) \leq 1$.

2) In the proof of Lemma A.1, to let Eqn. (8)-(9) hold, the authors may have assumed $\boldsymbol{R}, \boldsymbol{W}_V \geq 0$, where $\geq$ denotes entry-wise inequality. As the authors suggested, an entry-wise absolute value can be imposed to $\boldsymbol{R}$ and $\boldsymbol{W}_V$ as a simple fix, without influencing their ℓ_1 and ℓ_∞ norm. However,

even after those changes, we still have difficulty walking through Eqn. (6)-(8), and we are currently communicating with the authors on this matter.

3) In the proof of Lemma A.1, we find Eqn. (12) may not be satisfied in general. We can raise the following counterexample: Since $\boldsymbol{E}, \boldsymbol{r}, \boldsymbol{R}, \boldsymbol{W}_V$ can be any matrices, we simply let $\boldsymbol{D} = \mathrm{diag}(2,3), \mathrm{softmax}(\boldsymbol{r}) = [0.8 \quad 0.2]^T, \boldsymbol{R} = \boldsymbol{W}_V = \boldsymbol{I}$. Then $\|\boldsymbol{D}\boldsymbol{1}\mathrm{softmax}(\boldsymbol{r})^T\boldsymbol{R}\boldsymbol{W}_V\|_1 = 4$ while $\|\boldsymbol{D}\boldsymbol{1}\|_\infty\|\boldsymbol{R}\|_1\|\boldsymbol{W}_V\|_1 = 3$, which disproves the claim. We conjecture that some additional prerequisite constraints on $\boldsymbol{E}, \boldsymbol{r}$ might be needed here to proceed the derivation, and we are currently communicating with the authors on this matter.

D.3 Generalize to Other Attention Mechanism

Our theorizing can be smoothly generalized to other attention mechanisms because our Theorem 1 and 3 do not require any prior knowledge on pre-softmax pairwise correlation $\boldsymbol{P}$.

Logistic Attention. We refer logistic attention to the attention mechanism used in Veličković et al. (2017); Verma et al. (2018), where attention is calculated via a linear combination:

$$\boldsymbol{A}_{ij} = \frac{\exp\left(\boldsymbol{x}_i^T \boldsymbol{u}_Q + \boldsymbol{x}_j^T \boldsymbol{u}_K + b\right)}{\sum_t \exp\left(\boldsymbol{x}_i \boldsymbol{u}_Q + \boldsymbol{x}_t \boldsymbol{u}_K + b\right)} \tag{68}$$

where $\boldsymbol{u}_Q$ and $\boldsymbol{u}_K$ are query/key parameters, b is the bias term. With the same condition in Theorem 3, we can upper bound α by $|(\|\boldsymbol{u}_K\|_2 + \|\boldsymbol{u}_Q\|_2)\gamma + b|$.

L2 Distance Attention. L2 distance based attention (Kim et al., 2021) Lipschitz formulation of self-attention. The pair-wise attention can be written as follows:

$$\boldsymbol{A}_{ij} = \frac{\exp\left(-\|\boldsymbol{x}_i^T \boldsymbol{W}_Q - \boldsymbol{x}_j^T \boldsymbol{W}_K\|_2^2/\tau\right)}{\sum_t \exp\left(-\|\boldsymbol{x}_i^T \boldsymbol{W}_Q - \boldsymbol{x}_t^T \boldsymbol{W}_K\|_2^2/\tau\right)} \tag{69}$$

where $\boldsymbol{W}_Q$ and $\boldsymbol{W}_k$ are query/key weights, and τ is a scaling factor. Similar to Theorem 3, we can upper bound α by $(\|\boldsymbol{W}_K\|_2 + \|\boldsymbol{W}_Q\|_2)^2 \gamma^2/\tau$.

E An Auxiliary Lemma for AttnScale

Lemma 8. *Let $\tilde{\boldsymbol{A}} = \mathcal{F}\boldsymbol{A}\mathcal{F}^{-1}$ be the spectral response of attention matrix $\boldsymbol{A}$, and parameterize a low-filter by $\boldsymbol{L} = \mathcal{F}^{-1}\mathrm{diag}(\beta, 0, \cdots, 0)\mathcal{F}$. Then $\beta^* = 1$ is the optimal solution of the following optimization problem:* $\arg\min_\beta\|\boldsymbol{A} - \boldsymbol{L}\|_F$.

Proof. First we make simplification $\boldsymbol{L} = \mathcal{F}^{-1}\mathrm{diag}(\beta, 0, \cdots, 0)\mathcal{F} = \beta\boldsymbol{1}\boldsymbol{1}^T$ (refer to Appendix A). Then we have:

$$\|\boldsymbol{A} - \boldsymbol{L}\|_F^2 = \|\boldsymbol{A} - \beta\boldsymbol{1}\boldsymbol{1}^T\|_F^2 = \mathrm{Tr}(\boldsymbol{A} - \beta\boldsymbol{1}\boldsymbol{1}^T)^T(\boldsymbol{A} - \beta\boldsymbol{1}\boldsymbol{1}^T) \tag{70}$$

$$= \mathrm{Tr}\left(\boldsymbol{A}^T\boldsymbol{A} - \frac{\beta}{n}\boldsymbol{A}^T\boldsymbol{1}\boldsymbol{1}^T - \frac{\beta}{n}\boldsymbol{1}\boldsymbol{1}^T\boldsymbol{A} + \frac{\beta^2}{n}\boldsymbol{1}\boldsymbol{1}^T\right) \tag{71}$$

$$= \frac{\beta^2}{n}\mathrm{Tr}\,\boldsymbol{1}\boldsymbol{1}^T - \frac{2\beta}{n}\mathrm{Tr}\,\boldsymbol{1}\boldsymbol{1}^T\boldsymbol{A} + \mathrm{Tr}\,\boldsymbol{A}^T\boldsymbol{A} \tag{72}$$

$$= \beta^2 - \frac{2\beta}{n}\sum_{j=1}^{n}\sum_{i=1}^{n}\boldsymbol{A}_{ij} + \mathrm{Tr}\,\boldsymbol{A}^T\boldsymbol{A} \tag{73}$$

$$= \beta^2 - 2\beta + \mathrm{Tr}\,\boldsymbol{A}^T\boldsymbol{A} \tag{74}$$

From Eqn. 74, $\beta^* = 1$ achieves the minimum of the objective function. $\qquad\square$

F More on Visualization

F.1 Details on Figure 1

To verify our Theorem 3, we depict the high-frequency intensity of each layer's output and its theoretical upper bound. Our visualization is based on the official checkpoint of 12-layer DeiT-S. Since

training a ViT without either FFN or residual connection will certainly cause failure, we remove these components directly from the pre-trained model to illustrate the effects of different components. We use logarithmic scale for the purpose of better view. Let X_l denote the output of the l-th layer, and X_0 be the initial inputs. For red line, we directly calculate $\log(\|\mathcal{HC}[X_l]\|_F / \|X_0\|_F)$ at each layer. For blue line, we first obtain the coefficient γ_l in Section 2.2 and 2.3 with respect to network parameters (e.g., we can compute $\gamma_l = \sqrt{\frac{ne^{2\alpha}}{e^{2\alpha}+n-1}}\|W_V\|_2$ for attention only architecture). Then we estimate the upper bound by $\gamma_l\|\mathcal{HC}[X_{l-1}]\|_F$ and apply the logarithm by $\log(\gamma_l\|\mathcal{HC}[X_{l-1}]\|_F / \|X_0\|_F)$. To summarize, one can see without residual connection, the first two sub-figures imply an exponential convergence rate, which is consistent with our Theorem 3.

F.2 MORE VISUALIZATION ON SPECTRUM

In this appendix, we provide more visualization on the spectrum of attention map to validate our Theorem 1. We compute the spectrum of attention map A for both Fig. 2 and Fig. 5 in the following way. By regarding A as a linear filter, its Fourier-domain response is another linear kernel $\Lambda = \mathcal{F}A\mathcal{F}^{-1}$. When Λ is applied to a spectrum $\tilde{x} = \mathcal{F}x$ of signals x, the i-th frequency response will be $\Lambda_i\tilde{x}$, where Λ_i is the i-th row of Λ. Hence, we can use $\|\Lambda_i\|_2$ to evaluate the spectral response intensity of the i-th frequency band. Below we provide a complete spectral visualization of attention maps computed from a random sample in ImageNet validation set.

Figure 5: Visualize the spectrum of attention maps. Each row demonstrates every head at a same layer, and from top to bottom, the 12 rows correspond to 1 ~ 12-th layer, for left to right, the 6 columns correspond to 1 ~ 6-th head, respectively. Best view in a zoomable electronic copy.

F.3 DETAILS ON SIMILARITY CURVES (FIGURE 4)

We follow the definition in Zhou et al. (2021a) to compute the cosine similarity metric for attention maps. Instead of measuring cross-layer similarity, we calculate average cross-patch similarity at the same layer. Given the layer index l and corresponding attention maps $\boldsymbol{A}^{(l,h)} \in \mathbb{R}^{n \times n}$, the cosine similarity can be computed by:

$$M_{\text{attn}}^l = \frac{2}{n(n-1)H} \sum_{h=1}^{H} \sum_{i=1}^{n} \sum_{j=i+1}^{n} \frac{\left| \boldsymbol{A}_{:,i}^{(l,h)T} \boldsymbol{A}_{:,j}^{(l,h)} \right|}{\left\| \boldsymbol{A}_{:,i}^{(l,h)} \right\|_2 \left\| \boldsymbol{A}_{:,j}^{(l,h)} \right\|_2}, \tag{75}$$

where $\boldsymbol{A}_{:,i}^{(l,h)}$ denotes the i-th column of $\boldsymbol{A}^{(l,h)}$, and H is the number of heads. The cosine similarity between i-th and j-th column of $\boldsymbol{A}^{(l,h)}$ measures how the contribution of one token (say the i-th token) varies from the other (say the j-th token). We average the similarity between every pair of tokens' attention map (excluding the self-to-self similarity) and every attention head. We refer interested readers to Zhou et al. (2021a) for more details.

We use the similar metric to compute similarity for feature maps. Following Gong et al. (2021), we compute pair-wise cosine similarity between every two different tokens. Formally, given the layer index l, and its output $\boldsymbol{X}^{(l)} \in \mathbb{R}^{n \times d}$, the cosine similarity is estimated by:

$$M_{\text{feat}}^l = \frac{2}{n(n-1)} \sum_{i=1}^{n} \sum_{j=i+1}^{n} \frac{\left| \boldsymbol{X}_{i,:}^{(l)T} \boldsymbol{X}_{j,:}^{(l)} \right|}{\left\| \boldsymbol{X}_{i,:}^{(l)} \right\|_2 \left\| \boldsymbol{X}_{j,:}^{(l)} \right\|_2}, \tag{76}$$

where $\boldsymbol{X}_{i,:}^{(l)}$ denotes the i-th row of $\boldsymbol{X}^{(l)}$. The cosine similarity between between i-th and j-th row of $\boldsymbol{X}^{(l)}$ measures how similar the feature representations of two tokens are. Likewise, we average the similarity between every pair of tokens' features except for the self-to-self similarity. More details can found in Gong et al. (2021).

F.4 VISUALIZATION AND MODEL INTERPRETATION

In this subsection, we provide visualization to interpret our models and further support our experiments. Below we visualize the learned weights of our AttnScale. From Fig. 6, we can conclude our AttnScale are successfully trained to amplify the high-pass component. We also find when layer index goes larger, the scaling weights turns larger as well. This is because deeper the layer is, more likely the self-attention maps will collapse. AttnScale tends to learn a larger weight at deeper layer to recover the shrinking high-pass portion.

Figure 6: Visualize the learned weights of DeiT-S + AttnScale. Each sub-plot depicts the scaling weights of the same head for different layers. For left to right, top to bottom, six sub-figures correspond to 1 ~ 6-th head, respectively. Best view in color.

We also compare the attention map produced by AttnScale with those produced by original DeiT. We observe from Fig. 7 that our AttnScale can extract sharper and more salient attention than vanilla

DeiT, which indicates our AttnScale possesses higher capability to distinguish tokens from larger variety of attention schemes. Interestingly, we also notice that the attention pattern learned with or without AttnScale are almost the same, while adding AttnScale can enhance the pattern to have a higher contrast.

Figure 7: Visualize the attention map of DeiT-S with/without AttnScale. 4×4 max pooling has been applied. The first row visualizes attention maps without AttnScale, and the second row visualizes attention maps with AttnScale. Each column corresponds to the layer noted by its sub-title. The attention map are computed from a random sample in ImageNet validation set. We only demonstrate the first head of each layer. Best view in a zoomable electronic copy.

We also visualize the scaling weights of FeatScale in Fig. 8. We observe that the re-weighting factors learned for high-frequency components t is consistently larger than the weights for the DC term s, which indicates our FeatScale is successfully trained to elevate high-frequency features against the dominance of DC component to conquer low-pass bottleneck. Similarly, the gap between s and t becomes huger when going deeper. For the same reason, feature maps are more likely to be over-smoothened at larger layer index. FeatScale retains high-frequency signals by strongly scaling them via a huge factor.

Figure 8: Visualize the learned weights of DeiT-S + FeatScale. Each sub-plot depicts two groups of scaling weights of the same head for different layers. For left to right, top to bottom, six sub-figures correspond to 1 ~ 6-th head, respectively. Best view in color.