SMART: Sentences as Basic Units for Text Evaluation

Abstract

Widely used evaluation metrics for text generation either do not work well with longer texts or fail to evaluate all aspects of text quality. In this paper, we introduce a new metric called SMART to mitigate such limitations. Specifically, we treat sentences as basic units of matching instead of tokens, and use a sentence matching function to *soft*-match candidate and reference sentences. Candidate sentences are also compared to sentences in the source documents to allow grounding (e.g., factuality) evaluation. Our results show that system-level correlations of our proposed metric with a model-based matching function outperforms all competing metrics on the SummEval summarization meta-evaluation dataset, while the same metric with a string-based matching function is competitive with current model-based metrics. The latter does not use any neural model, which is useful during model development phases where resources can be limited and fast evaluation is required. SMART also outperforms all factuality evaluation metrics on the TRUE benchmark. Finally, we also conducted extensive analyses showing that our proposed metrics work well with longer summaries and are less biased towards specific models.

1 Introduction

One major obstacle in the progress of text generation tasks (e.g., document summarization, long-form question answering, data-to-text generation, etc.) is automatic evaluation. Traditionally, automatic metrics that rely on discrete token-level matching such as ROUGE (Lin, 2004) and BLEU (Papineni et al., 2002) have been utilized to check whether system outputs are of high quality across four dimensions (Kryscinski et al., 2019; Fabbri et al., 2021): coherence, factuality, fluency, and informativeness. These metrics do not correlate well with human judgments on all four dimensions of text quality (Fabbri et al., 2021). Because of this, the evaluation is usually coupled with human elicitation studies that ask humans to rate texts. These studies can be expensive and nearly impossible to reproduce.

More recently, pretrained language models are leveraged for automatically evaluating system-generated texts (Zhang* et al., 2020; Sellam et al., 2020; Yuan et al., 2021), which have shown improvements on correlation with human judgments. Nevertheless, both ROUGE and LM-based metrics have three major drawbacks. Firstly, these metrics are not good at evaluating long and multi-sentence texts. Figure 1 illustrates system-level rank correlations of ROUGE in different text lengths, which shows that after a certain length, ROUGE drastically decreases its evaluative power. By design, ROUGE is also not robust to evaluating possibly shuffled information in long outputs, hurting its performance on evaluating coherence. On the other hand, LM-based metrics such as the state-of-the-art BARTScore (Yuan et al., 2021), are constrained to the length limitation of the pretrained LM used, thus they are not able to evaluate outputs longer than this limit. Secondly, most of these metrics only use reference texts during evaluation. This restricts the capability of the metrics from evaluating dimensions of text quality that requires grounding to the source. Yuan et al. (2021) suggested to use the source document during evaluation, however their evaluation is still limited to short documents because of length limitations in LMs. Finally, LM-based metrics can be very slow, which hinders usage in the model development stages, where quick evaluation is necessary. As such, most practitioners use ROUGE in these stages, which can lead to suboptimal modeling.

Figure 1: Kendall tau system-level correlations of ROUGE and SMART averaged over four dimensions of summary quality as the number of tokens increases. Summaries are from CNN/DM (Hermann et al., 2015) and human annotations are from SummEval (Fabbri et al., 2021). Each bucket in the x-axis contains equal number of data points. More details in Section A.2.

In this paper, we propose an automatic metric called SMART (**S**entence **MA**tching for **R**ating **T**ext). To support long and multi-sentence texts, we treat sentences as basic units of matching instead of tokens. Since sentences most likely do not have exact matches, we use a soft-matching function that returns a matching score between 0 and 1, given a pair of sentences. Moreover, to allow grounded evaluation, we also include the source in the calculation of the metric. Similar to ROUGE, we introduce multiple SMART versions using sentence n-gram overlap and longest common subsequence. We show that SMART with BLEURT (Sellam et al., 2020) as a soft-matching function outperforms all the competing approaches on all four dimensions of quality in the SummEval dataset (Fabbri et al., 2019). We also show that SMART with T5-ANLI (Honovich et al., 2022) outperforms all competing factuality-based evaluation metrics on the TRUE benchmark (Honovich et al., 2022). Moreover, a faster variant of SMART, which does not use any neural model for text matching, shows competitive correlations with human judgments. Finally, our extensive analyses show that SMART works better with longer summaries and is less biased towards specific models. We will release and maintain a toolkit containing scripts to easily run evaluation using SMART.

2 RELATED WORK

Evaluation in conditional generation tasks such as machine translation and document summarization is a long-standing problem. Traditionally, evaluation involves human elicitation studies that score texts based on different metrics of quality, such as adequacy, fidelity, and fluency in machine translation (Hovy, 1999), and coherence, conciseness, fluency, readability, and content relevance in summarization (Mani, 2001). Automatic metrics based on token n-gram matching have been developed to replace these expensive and time-consuming studies, in which ROUGE (Lin, 2004) and BLEU (Papineni et al., 2002) are most widely used in summarization and translation, respectively. Several extensions to token n-gram matching have been proposed, such as using paraphrases, synonyms (Lavie & Agarwal, 2007), and word embeddings (Ng & Abrecht, 2015) to handle cases that are semantically equivalent, and downweighting common n-grams to focus more on salient ones (Vedantam et al., 2015). Popović (2015) instead use character-level n-gram matching to also match words that are conjugated differently and support morphologically rich languages.

With the introduction and success of pretrained language models such as BERT (Devlin et al., 2019) and BART (Lewis et al., 2020), evaluation metrics that leverage them have been proposed. BERTScore (Zhang* et al., 2020) leverages contextualized token embeddings from BERT and obtains pairwise matching of tokens from reference and system summaries. MoverScore (Zhao et al., 2019) extends BERTScore by instead having many-to-one soft alignments using Word Mover's Distance (WMD; Kusner et al., 2015). BLEURT (Sellam et al., 2020) fine-tunes BERT to predict human scores with large-scale synthetic training data. BARTScore (Yuan et al., 2021) uses BART and treats evaluation as a text generation problem, using likelihood of predicting the system summary given the source document or the reference summary. Clark et al. (2019) and Zhao et al. (2019) also explored sentence-level matching with WMD using (contextualized) sentence embeddings, however they show

no concrete improvements over other model-based metrics (Fabbri et al., 2021). In contrast, we show that our metric which uses sentence-level matching correlates better with human judgments than all competing models.

Factuality in summarization (Falke et al., 2019; Maynez et al., 2020) is usually evaluated separately since most automatic metrics are focused on informativeness and do not include the source document in the metric calculation. Factuality-specific metrics can be divided into three approaches: natural language inference (NLI) based approaches (Falke et al., 2019; Maynez et al., 2020; Laban et al., 2022), where a summary is considered factual if all its facts are entailed by the source document, model-based approaches (Kryscinski et al., 2020; Deng et al., 2021), where a model is trained to detect factual errors in the summary, and question answering (QA) based approaches (Durmus et al., 2020; Wang et al., 2020; Honovich et al., 2021), where questions generated in a factual summary should be answerable using the source. While we also compare correlations of automatic metrics with human judgments on factuality, the goal of our work is to find holistic metrics for evaluation that can also effectively evaluate other dimensions of text quality. Our results show that other dimensions such as coherence, fluency, and informativeness also benefit in the use of the source documents in the metric. Finally, we also show that our metric improves the state-of-the-art of factual consistency evaluation based on the TRUE benchmark Honovich et al. (2022).

3 PROBLEM DEFINITION

We primarily use document summarization – the task of generating concise and accurate summaries of input documents (Mani, 2001) – to explain our metric, but the proposed metric can be easily adapted to other tasks, as shown in Section 5.2.

Let $\mathcal{S}$ be a list of source documents, $\mathcal{C}$ be a list of summaries generated for $\mathcal{S}$ by a candidate system, and $\mathcal{R}$ be a list of reference summaries produced by human annotators for $\mathcal{S}$. Note that $\mathcal{R}$ can be a nested list, i.e., for each example, there can be multiple references. Moreover, let $\mathcal{Q}$ be a list of dimensions of summary quality, and let $\mathcal{H}_q$ be a list of human-annotated scores for $\mathcal{C}$ in terms of a certain summary quality q. For each summary quality $q \in \mathcal{Q}$, the problem is to devise an evaluation metric $f_q(\mathcal{S}, \mathcal{R}, \mathcal{C})$ that outputs a list of scores that correlates well with $\mathcal{H}_q$. Note that, unlike most of previous work on summarization evaluation (Lin, 2004; Clark et al., 2019; Bhandari et al., 2020; Fabbri et al., 2021), we also take into account source documents $\mathcal{S}$ when calculating metric $f_q(\cdot)$. This ensures that the metric can evaluate quality dimensions that require looking at the source.

We define the list of summary quality $\mathcal{Q}$ as the following four dimensions of summary quality, defined as follows (based on definitions in Fabbri et al., 2021 and Yuan et al., 2021):

- **Coherence**: The summary should be well-structured and well-organized. The summary should not just be a heap of related information, but should build from sentence to sentence to a coherent body of information about a topic.

- **Factuality**: The summary should only contain statements that are entailed by the source document. The summary should not contain hallucinated facts that either do not exist in the source or contradict facts from the source.

- **Fluency**: The summary should have no formatting problems, capitalization errors or obviously ungrammatical sentences (e.g., fragments, missing components) that make the text difficult to read.

- **Informativeness**: The summary should include only important information from the source document. The summary should not include redundant information and information that are considered excessive and non-salient.

4 SENTENCE MATCHING FOR RATING TEXT

We now describe our proposed metric, SMART (**S**entence **MA**tching for **R**ating **T**ext), which has two key ideas. Firstly, we treat sentences as basic units of matching between system and reference summaries, instead of tokens. At sentence-level, exactly matching sentences are most likely non-existent (in datasets with abstractive reference summaries), thus we instead utilize soft-matching functions to compare sentences. Similar to ROUGE, we present two types of SMART: n-gram overlap

(SMART-N) and longest common subsequence (SMART-L). Secondly, SMART allows to compare the candidate system summary with *both* the reference summary and the source document. This is particularly important when evaluating dimensions of summary quality that rely on the source document such as factuality.

SMART-N In order for SMART to work, summaries should be split into sentences. Let $R = [r_i]$ and $C = [c_j]$ be the sequence of sentences of the reference and the candidate system summary. SMART-N finds pairs of sentence n-grams in R and C that have the highest matching scores given by a sentence matching function that returns a score between 0 and 1 (detailed description in Section A.1).

Formally, given N as the number of sentences in the sentence n-gram, SMART-N can be calculated as follows:

$$prec' = \sum_{j=1}^{|C|-N+1} \max_{r_i \in R; i \leq |R|-N+1} \left[\sum_{n=0}^{N-1} \texttt{match}(c_{j+n}, r_{i+n})/N \right] \tag{1}$$

$$prec = prec'/(|C| - N + 1) \tag{2}$$

$$rec' = \sum_{i=1}^{|\mathcal{R}|-N+1} \max_{c_j \in C; j \leq |C|-N+1} \left[\sum_{n=0}^{N-1} \texttt{match}(r_{i+n}, c_{j+n})/N \right] \tag{3}$$

$$rec = rec'/(|R| - N + 1) \tag{4}$$

$$f = 2 * prec * rec/(prec + rec) \tag{5}$$

where $\texttt{match}(\cdot, \cdot)$ is the sentence matching function, $prec$, rec, and f are precision, recall, and f-measure, respectively. Note that unlike ROUGE, the numerators of precision and recall are different due to the use of a soft-matching function, thus they are calculated separately. In our experiments, we used SMART-1 and SMART-2[1], but SMART-N can be easily extended to work with larger Ns.

SMART-L SMART-L is essentially the Longest Common Subsequence (LCS) of sentences in the reference and the candidate system summary. However, the original LCS algorithm requires an exact match to work. We instead use a *soft* version of LCS, where the task is defined as: Given two sequences $X = [x_i]$ and $Y = [y_j]$ and a matching function $\texttt{match}(x_i, y_j)$, find two *soft-*subsequences $x_{i_1}, ..., x_{i_l}$ and $y_{j_1}, ..., y_{j_l}$ of length l with $i_{k-1} \leq i_k \leq i_{k+1}$ and $j_{k-1} \leq j_k \leq j_{k+1}$, maximizing the sum $\sum_{k=1}^{l} \texttt{match}(x_{i_k}, y_{j_k})$.

Unlike normal subsequences, soft-subsequences allow repetition of sentences as long as they do not go back to previous sentences (hence the use of $\leq$ operator). This relaxation helps in cases where the meaning of a sentence on one side spans over multiple sentences on the other side. Furthermore, Soft-LCS is similar but different from a simple sequence alignment problem since the weight of the match depends on *both* the positions of the items in the sequence and the items themselves. It is a less-restricted version of the Heaviest Common Subsequence (HCS; Jacobson & Vo, 1992) since the matching function is relaxed to allow the use of a soft match (which is essentially an exact mismatch) in the subsequence.

It turns out that Soft-LCS can be solved using a dynamic programming algorithm similar to that of LCS, which is illustrated as a pseudocode in Figure 2. The main difference is that since we do not require an exact match, we always take the maximum among three cases: (1) choosing to soft-match x_i and y_j, (2) choosing to soft-match x_i and y_{j-1}, and (3) choosing to skip x_i.

---

[1]In special cases where either the candidate or the reference is a single-sentence summary, a normal implementation of SMART-2 would return zero since one of the summaries would have zero sentence bigrams. To mitigate this issue, we pad summaries with a blank sentence on both sides when calculating SMART-2. This ensures that we get a non-zero score for single-sentence summaries. In fact, SMART-2 reduces to SMART-1 in this case.

```python
def soft_lcs(X, Y):
  lcs = [[0] * (len(Y)+1)] * (len(X)+1)
  for i in range(len(X)+1):
    for j in range(len(Y)+1):
      if i != 0 and j != 0:
        m = match(X[i], Y[j])
        lcs[i][j] = max(lcs[i-1][j-1]+m, lcs[i-1][j]+m, lcs[i][j-1])
  return lcs[-1][-1]
```

Figure 2: Python pseudocode of the soft version of Longest Common Subsequence (Soft-LCS) given two sets of summary sentences X and Y.

Given the Soft-LCS function, we can then calculate SMART-L as follows:

$$prec' = \texttt{soft-lcs}(C, R) \tag{6}$$

$$prec = prec'/|C| \tag{7}$$

$$rec' = \texttt{soft-lcs}(R, C) \tag{8}$$

$$rec = rec'/|R| \tag{9}$$

$$f = 2 * prec * rec/(prec + rec) \tag{10}$$

Comparing with Source Some dimensions of summary quality require access to source to be effectively evaluated. To cover those dimensions, SMART also compares the candidate system summary with the source, in addition to comparison with the reference summary. Let $S = [s_k]$ be the sequence of sentences of the source document. SMART that uses both source and reference is calculated as follows. We first calculate two SMART scores that (1) compares candidate system summary C with reference summary R, and (2) compares C with source document S. Then, we aggregate the scores by taking their maximum. For example, $\texttt{SMART-N}(S, R, C)$ is calculated as:

$$\texttt{SMART-N}(S, R, C) = \max(\\ \texttt{SMART-N}(S, C), \texttt{SMART-N}(R, C)) \tag{11}$$

Multiple References Finally, when there are multiple reference summaries, we calculate SMART for each reference, and aggregate them by taking their maximum, as also commonly done in previous work (Fabbri et al., 2021). This is intuitive since the candidate system summary only needs to match with at least one of the reference.

Shorter Acronym We use the following template to describe SMART variants in a space-efficient manner: `S[1|2|L]-m`, where `m` is the sentence matching function of choice. For example, SMART-1 with a BLEURT (Sellam et al., 2020) matching function can be shortened into S1-BLEURT.

5 EXPERIMENTS AND RESULTS

Sentence Matching Functions One advantage of SMART is that it is easily extensible by changing the matching functions depending on the task. We investigated and compared six different matching functions, three model-based and three string-based, in Sections A.1 and A.5 of the Appendix and use the ones that perform the best for each task. Specifically, for document summarization, we use BLEURT (Sellam et al., 2020) as the best model-based function and CHRF (Popović, 2015) as the best string-based function. For factual consistency, we use ANLI (Honovich et al., 2022) as the matching function.

Implementation Details The sentence matching functions are implemented as follows. For BLEURT (Sellam et al., 2020), we used the `BLEURT-20` checkpoint[2] suggested by the authors which also supports non-English languages. For ANLI, we used the same implementation as in Honovich et al. (2022), where T5-11B is fine-tuned with 25K training steps on ANLI (Nie et al.,

---

[2] https://github.com/google-research/bleurt

2020), treating both contradiction and neutral pairs as not entailed. Sentences are split using `nltk`[3]. For the document summarization experiments, we report f-measure scores whenever available, such as in ROUGE, BERTScore, and SMART. For the factual consistency experiments, we report precision scores. We also report the version of SMART that considers both source and reference as in Eq 11.

We tested our metric in two different tasks: document summarization and factual consistency. We discuss them in detail in the next sections.

5.1 DOCUMENT SUMMARIZATION

Dataset and Evaluation We conducted experiments on the SummEval dataset (Fabbri et al., 2021), a document summarization meta-evaluation suite consisting of summaries from the CNN/DM dataset (Hermann et al., 2015). Annotation is done in two stages and using experts to ensure high quality and high agreement across annotators. There are 1600 data points (16 systems × 100 examples) in total, each of which includes a score between 1 to 5 for each of the four dimensions of summary quality, which represents the average score given by three experts. Each data point also includes 11 reference summaries: the original summary from the CNN/DM dataset and 10 human-written abstractive summaries from Kryscinski et al. (2020). For evaluation, we use system-level correlation using Kendall tau, where we first take the average score for each system and take the correlation.[4]

Comparison Metrics We compared SMART with three types of metrics: string-based metrics, source-free and source-dependent model-based metrics.

String-based metrics include: (1-3) ROUGE-1/2/L (Lin, 2004) measures token-level overlap between reference and output summaries; (4) BLEU (Papineni et al., 2002) measures token-level overlap between reference and output summaries with a focus on precision; (5) CHRF (Popović, 2015) measures character-based n-gram overlap between reference and output summaries; and (6-8) S1/2/L-CHRF, our best SMART metric using a string-based matching function, as shown in §A.1 of the Appendix.

Source-free model-based metrics include: (9) BERTScore (Zhang* et al., 2020): A metric that relies on BERT(-like) models (Devlin et al., 2019) and computes an aggregation of the token-level similarity scores; (10) MoverScore (Zhao et al., 2019): measures the semantic distance between BERT n-gram embeddings of reference and candidate summaries using Word Mover's Distance (WMD; Kusner et al., 2015); (11) BLEURT (Sellam et al., 2020): finetunes BERT using a combination of real and synthetic training data with gold-/silver-standard human judgment scores; and (12) Sentence Mover's Similarity (SMS; Clark et al., 2019): uses an extension of WMD that works with sentences instead of tokens.

Source-dependent model-based metrics include: (13) PRISM (Thompson & Post, 2020): leverages a zero-shot paraphrasing model and uses probabilities from force-decoding the candidate summary given the source as input; (14) Q^2 (Honovich et al., 2021): employs question generation and question answering models and checks whether answers from the summary are entailed by answers from source; (15) ANLI (Honovich et al., 2022): fine-tunes T5 (Raffel et al., 2020) using the ANLI dataset (Nie et al., 2020) to produce an entailment score given the source as premise and the summary as hypothesis; (16-17) BARTScore(+CNN) (Yuan et al., 2021): evaluates text using probabilities from force-decoding the candidate summary given the source as input using BART (Lewis et al., 2020) without (with) finetuning with CNN/DM summarization dataset (Hermann et al., 2015); and (18-20) S1/2/L-BLEURT: Our best SMART metric using a model-based matching function, as shown in §A.1 of the Appendix.

Results Table 1 reports the system-level correlations of different metrics for each quality dimension. For all quality dimensions, SMART with BLEURT matching function has the highest correlation, where SL-BLEURT evaluates coherence and informativeness better, and S1-BLEURT and S2-BLEURT evaluate factuality and fluency better, respectively. On average, SL-BLEURT performs best,

---

[3] https://pypi.org/project/nltk/

[4] While they claimed to report system-level correlation, the BARTScore paper (Yuan et al., 2021) actually calculated *summary*-level correlation (Louis & Nenkova, 2013), where they first get correlation for each system and then take the average. Since we use evaluation metrics to rank *systems*, we report system-level correlation following Fabbri et al. (2021).

Metric	Coherence	Factuality	Fluency	Informativeness	μ
String-based Metrics					
ROUGE-1	.350	.550	.527	.583	.503
ROUGE-2	.233	.600	.494	.433	.440
ROUGE-L	.117	.117	.259	.350	.211
BLEU	.217	.050	.326	.383	.244
CHRF	.350	.617	.561	.550	.519
S1-CHRF	.300	**.733**	.494	.500	.507
S2-CHRF	.300	.700	.460	.433	.473
SL-CHRF	.367	**.733**	.494	.500	.523
Source-free Model-based Metrics					
BERTScore	.333	-.030	.142	.200	.161
MoverScore	.217	-.050	.259	.350	.194
BLEURT	**.533**	.200	.410	.467	.403
SMS	.267	.600	.360	.400	.407
Source-dependent Model-based Metrics					
PRISM	.233	.600	.360	.367	.390
Q^2	.250	**.750**	.577	.450	.507
ANLI	.250	.583	.544	.517	.473
BARTScore	.350	.617	.494	.450	.478
BARTScore+CNN[†]	**.550**	.317	.594	.583	.511
S1-BLEURT	.433	.667	**.644**	.667	.603
S2-BLEURT	.417	**.750**	**.628**	.583	.594
SL-BLEURT	**.567**	.567	.611	**.733**	.619

Table 1: Kendall tau system-level correlation of different metrics on the SummEval dataset. Correlations of metrics not significantly outperformed by any other metric (using William's Test; Graham & Baldwin, 2014) for that specific dimension are **boldfaced**. We also show the average scores in the μ column, where the best values for each block are underlined. Note that BARTScore+CNN uses BART that is fine-tuned on CNN/DM, the same data source as SummEval, thus direct comparison with the other metrics is not possible.

followed by S1-BLEURT and S2-BLEURT, all three of which outperforming BARTScore+CNN, which is finetuned on the same summarization dataset as SummEval. S2-BLEURT also performs comparably with Q^2 in factuality evaluation. Given that each of the SMART metrics are better at evaluating different quality dimensions, it is therefore recommended to use them as a set, similar to how ROUGE metrics are used. We can also see in the table that source-dependent metrics are better than source-free ones, signifying the importance of the use of source documents during summary evaluation. Among source-free metrics, SMS performs the best, showing the superiority of sentence-level matching metrics against the token-level ones. Among string-based metrics, SL-CHRF performs the best, with a competitive system-level correlation when compared with BARTScore+CNN on average. This shows that SMART achieves comparable evaluation power with previous LM-based metrics even without using any pretrained language models.

Ablation Studies We present various ablation studies on the different components of SMART in Table 2. For simplicity, we report on SMART-X, an average of SMART-l, SMART-2 and SMART-L.[5] The first block contains SMART-X that uses only either precision or recall, both of which have substantially lower system-level correlation than f-measure. The recall variant performs better, which follows results from traditionally recall-oriented evaluation metrics in summarization (Lin, 2004).

The second block contains different ways to aggregate SMART scores that compare candidate summaries (1) to the source documents and (2) to the reference summaries. When using only one of the two scores (i.e., reference- or source-only), SMART scores significantly perform worse, which implies that using both source and reference is necessary for SMART to work. We also tried

---

[5]From here on, we use X to correspond to the average of the three `[1|2|L]` variants of ROUGE or SMART.

Component	Coherence	Factuality	Fluency	Informativeness	μ
SX-BLEURT	.450	.750	.661	.650	.628
using precision or recall					
precision	.083	.017	.259	.350	.177
recall	.283	.683	.410	.383	.440
using a different source/reference aggregation					
ref-only	-.100	-.300	-.092	-.033	-.131
src-only	.267	.700	.460	.433	.465
average	.400	.750	.577	.600	.582
minimum	.267	.700	.427	.467	.465
using a different reference summary					
ref-only (CNN/DM)	-.100	-.300	-.059	-.033	-.123
ref-only (best system)	.367	.100	.410	.500	.344
max (CNN/DM)	.500	.767	.711	.667	.661
max (best system)	.667	.467	.745	.867	.686

Table 2: Ablation study. Kendall tau system-level correlation of SX-BLEURT when one component is set to a different configuration.

aggregation through taking the average or the minimum, both of which perform worse than taking the maximum as in Eq 11.

One interesting finding is that using only the reference summaries to calculate SMART gives negative correlation scores on all dimensions. Given the findings from Fabbri et al. (2021) that CNN/DM summaries are worse than system summaries in terms of human ratings, we further investigated using different reference summaries for SMART. Specifically, we tried (1) replacing the set of reference summaries from SummEval into the original summary from CNN/DM, and (2) treating the best system summary according to the average human score as the reference. As can be seen in the third block of Table 2, CNN/DM reference summaries correlate negatively on all dimensions. When using the best system summary as the reference, SMART now obtains positive correlations across all dimensions. The correlation further improves when SMART uses both the source and the new reference.

Further Analyses   We provide several analyses in the Appendix to further understand our metrics. In §A.2, we show that SMART works better with longer summaries, and in §A.3, we also show that it is less biased towards specific models compared to other competing metrics. Finally, in §A.4, we show that source-only SMART works well as a reference-free metric and correctly ranks systems that popular metrics such as ROUGE (Lin, 2004), BERTScore (Zhang* et al., 2020), and QAEval (Deutsch et al., 2021) cannot, according to Goyal et al. (2022).

5.2   FACTUAL CONSISTENCY

Dataset and Evaluation   We conducted experiments on the TRUE benchmark (Honovich et al., 2022), a meta-evaluation suite for factuality, consisting of source and candidate texts from different kinds of text generation tasks: abstractive summarization, dialogue generation, and paraphrase detection. We note that there is no reference text given and the candidate text is compared only to the source. In this benchmark, factuality scores are binary (positive/negative, in contrast to the five-scale scoring in SummEval), and the generated text needs to be fully factual to get a positive score. Given this, the metrics are evaluated using the Received Operating Characteristic Area Under the Curve (ROC AUC) to remove the necessity of setting a specific decision threshold.

Comparison Metrics   The best matching function for factual consistency is ANLI, as shown in §A.5 of the Appendix. Since there is no reference text, we used the version of SMART that compares only with the source. Moreover, we aggregated S1/2/L-ANLI into SX-ANLI by taking their mean for brevity (results of individual metrics are reported in §A.5). We compared (1) SX-ANLI with three factuality-specific evaluation metrics: (2) Q^2 (Honovich et al., 2021); (3) ANLI (Honovich et al.,

Task	3-Ensemble	2-Ensemble		Single Metrics			
	$ANLI + Q^2 + SC_{ZS}$	$ANLI + SX\text{-}ANLI$	$ANLI + Q^2$	$SX\text{-}ANLI$	$ANLI$	SC_{ZS}	Q^2
FRANK	91.2	91.1	89.6	89.4	89.4	89.1	87.8
SummEval	82.9	82.2	80.7	80.6	80.5	81.7	78.8
MNBM	76.6	77.0	75.6	73.0	77.9	71.3	68.7
QAGS-C	87.7	85.3	86.0	81.7	82.1	80.9	83.5
QAGS-X	84.8	84.0	81.8	77.2	83.8	78.1	70.9
BEGIN	86.2	84.9	85.7	85.0	82.6	82.0	79.7
$Q^2_{dataset}$	82.8	81.5	83.0	82.4	72.7	77.4	80.9
DialFact	90.4	90.3	89.4	90.4	77.7	84.1	86.1
PAWS	91.2	95.7	90.5	98.3	86.4	88.2	89.7
Average	**86.0**	**85.8**	84.7	**84.2**	81.5	81.4	80.7

Table 3: ROC AUC results for the different metrics on the development set of the TRUE benchmark. Results can be from ensembles of multiple metrics, and are grouped by the number of metrics used in the ensemble. The highest average score for each group is **boldfaced**.

2022); and (4) SC_{ZS} (Summary Consistency; Laban et al., 2022) that splits the source and candidate texts into sentences, computes entailment probabilities on all sentence pairs, and aggregates them into a single score. The last metric is similar to S1-ANLI, but with two key differences: (a) The aggregation is different; and (b) Training is done using both NLI and fact verification datasets.

Finally, following Honovich et al. (2022) we also compared three ensembles of multiple metrics by averaging their scores: (5) $ANLI + Q^2$, (6) $ANLI + SX\text{-}ANLI$, and (7) $ANLI + Q^2 + SZ_{ZS}$.

Results Table 3 shows the ROC AUC scores of different metrics. Among single metrics, $SX\text{-}ANLI$ performs the best, substantially improving over the second best metric. Moreover, ensembling $SX\text{-}ANLI$ with ANLI provides another boost, performing superiorly compared to the $ANLI + Q^2$ ensemble metric and comparably with the $ANLI + Q^2 + SZ_{ZS}$ ensemble metric. Our ensemble metric is also more cost-effective since it only requires a single model, while the other ensemble metric requires at least two more (e.g., question answering and generation models for Q^2).

6 CONCLUSIONS

In this paper, we proposed SMART (Sentence Matching for Rating Text), a new metric for evaluating generated text given both a source document and a reference text. SMART makes use of a sentence-level soft-matching function to match sentences, which can either be string-based or model-based depending on the available resources. This function can easily be replaced with new and better ones, which allows us to create a better SMART metric. We provided two types of SMART based on n-gram overlap and longest common subsequence, and our extensive experiments showed that SMART evaluates document summaries better in terms of all four dimensions of summary quality: coherence, factuality, fluency, and informativeness. Our analyses also showed that SMART is better as summary length increases and is less biased than other competing metrics.

6.1 LIMITATIONS AND FUTURE WORK

We acknowledge several limitations of our work. Firstly, SMART currently assumes single-source inputs, which makes it non-trivial to use for evaluating texts in tasks with multi-source inputs. While this can be mitigated by concatenating documents in chronological order, there may be cases where such ordering is not possible. Ultimately, finding an efficient way to extend the (soft version of) longest common subsequence algorithm into multiple sources is necessary, which we plan to explore in the future.

Moreover, we plan to maintain an open-source toolkit which includes scripts to easily run evaluation using SMART, and is updated accordingly when new features, such as better matching functions or support for multi-source inputs.

REFERENCES

Manik Bhandari, Pranav Narayan Gour, Atabak Ashfaq, Pengfei Liu, and Graham Neubig. Re-evaluating evaluation in text summarization. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9347–9359, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.751. URL https://aclanthology.org/2020.emnlp-main.751.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.

Elizabeth Clark, Asli Celikyilmaz, and Noah A. Smith. Sentence mover's similarity: Automatic evaluation for multi-sentence texts. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2748–2760, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1264. URL https://aclanthology.org/P19-1264.

Mingkai Deng, Bowen Tan, Zhengzhong Liu, Eric Xing, and Zhiting Hu. Compression, transduction, and creation: A unified framework for evaluating natural language generation. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7580–7605, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.599. URL https://aclanthology.org/2021.emnlp-main.599.

Daniel Deutsch, Tania Bedrax-Weiss, and Dan Roth. Towards question-answering as an automatic metric for evaluating the content quality of a summary. *Transactions of the Association for Computational Linguistics*, 9:774–789, 2021. doi: 10.1162/tacl_a_00397. URL https://aclanthology.org/2021.tacl-1.47.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://aclanthology.org/N19-1423.

Esin Durmus, He He, and Mona Diab. FEQA: A question answering evaluation framework for faithfulness assessment in abstractive summarization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5055–5070, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.454. URL https://aclanthology.org/2020.acl-main.454.

Alexander Fabbri, Irene Li, Tianwei She, Suyi Li, and Dragomir Radev. Multi-news: A large-scale multi-document summarization dataset and abstractive hierarchical model. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1074–1084, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1102. URL https://aclanthology.org/P19-1102.

Alexander R. Fabbri, Wojciech Kryściński, Bryan McCann, Caiming Xiong, Richard Socher, and Dragomir Radev. SummEval: Re-evaluating summarization evaluation. *Transactions of the Association for Computational Linguistics*, 9:391–409, 2021. doi: 10.1162/tacl_a_00373. URL https://aclanthology.org/2021.tacl-1.24.

Tobias Falke, Leonardo F. R. Ribeiro, Prasetya Ajie Utama, Ido Dagan, and Iryna Gurevych. Ranking generated summaries by correctness: An interesting but challenging application for natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational*

Linguistics, pp. 2214–2220, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1213. URL https://aclanthology.org/P19-1213.

Tanya Goyal, Junyi Jessy Li, and Greg Durrett. News summarization and evaluation in the era of gpt-3. 2022.

Yvette Graham and Timothy Baldwin. Testing for significance of increased correlation with human judgment. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 172–176, Doha, Qatar, October 2014. Association for Computational Linguistics. doi: 10.3115/v1/D14-1020. URL https://aclanthology.org/D14-1020.

Karl Moritz Hermann, Tomáš Kočiský, Edward Grefenstette, Lasse Espeholt, Will Kay, Mustafa Suleyman, and Phil Blunsom. Teaching machines to read and comprehend. In *Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 1*, NIPS'15, pp. 1693–1701, Cambridge, MA, USA, 2015. MIT Press.

Or Honovich, Leshem Choshen, Roee Aharoni, Ella Neeman, Idan Szpektor, and Omri Abend. q^2: Evaluating factual consistency in knowledge-grounded dialogues via question generation and question answering. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7856–7870, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.619. URL https://aclanthology.org/2021.emnlp-main.619.

Or Honovich, Roee Aharoni, Jonathan Herzig, Hagai Taitelbaum, Doron Kukliansy, Vered Cohen, Thomas Scialom, Idan Szpektor, Avinatan Hassidim, and Yossi Matias. TRUE: Re-evaluating factual consistency evaluation. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 3905–3920, Seattle, United States, July 2022. Association for Computational Linguistics. URL https://aclanthology.org/2022.naacl-main.287.

Eduard H Hovy. Toward finely differentiated evaluation metrics for machine translation. In *Proceedings of the EAGLES Workshop on Standards and Evaluation Pisa, Italy, 1999*, 1999.

Guy Jacobson and Kiem-Phong Vo. Heaviest increasing/common subsequence problems. In *Annual Symposium on Combinatorial Pattern Matching*, pp. 52–66. Springer, 1992.

Tom Kocmi, Christian Federmann, Roman Grundkiewicz, Marcin Junczys-Dowmunt, Hitokazu Matsushita, and Arul Menezes. To ship or not to ship: An extensive evaluation of automatic metrics for machine translation. In *Proceedings of the Sixth Conference on Machine Translation*, pp. 478–494, Online, November 2021. Association for Computational Linguistics. URL https://aclanthology.org/2021.wmt-1.57.

Wojciech Kryscinski, Nitish Shirish Keskar, Bryan McCann, Caiming Xiong, and Richard Socher. Neural text summarization: A critical evaluation. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 540–551, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1051. URL https://aclanthology.org/D19-1051.

Wojciech Kryscinski, Bryan McCann, Caiming Xiong, and Richard Socher. Evaluating the factual consistency of abstractive text summarization. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9332–9346, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.750. URL https://aclanthology.org/2020.emnlp-main.750.

Matt J. Kusner, Yu Sun, Nicholas I. Kolkin, and Kilian Q. Weinberger. From word embeddings to document distances. In *Proceedings of the 32nd International Conference on International Conference on Machine Learning - Volume 37*, ICML'15, pp. 957–966. JMLR.org, 2015.

Philippe Laban, Tobias Schnabel, Paul N. Bennett, and Marti A. Hearst. SummaC: Re-visiting NLI-based models for inconsistency detection in summarization. *Transactions of the Association for Computational Linguistics*, 10:163–177, 2022. doi: 10.1162/tacl_a_00453. URL https://aclanthology.org/2022.tacl-1.10.

Alon Lavie and Abhaya Agarwal. METEOR: An automatic metric for MT evaluation with high levels of correlation with human judgments. In *Proceedings of the Second Workshop on Statistical Machine Translation*, pp. 228–231, Prague, Czech Republic, June 2007. Association for Computational Linguistics. URL `https://aclanthology.org/W07-0734`.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7871–7880, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.703. URL `https://aclanthology.org/2020.acl-main.703`.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL `https://aclanthology.org/W04-1013`.

Yixin Liu, Pengfei Liu, Dragomir Radev, and Graham Neubig. BRIO: Bringing order to abstractive summarization. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2890–2903, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.207. URL `https://aclanthology.org/2022.acl-long.207`.

Annie Louis and Ani Nenkova. Automatically assessing machine summary content without a gold standard. *Computational Linguistics*, 39(2):267–300, 2013.

Inderjeet Mani. *Automatic summarization*, volume 3. John Benjamins Publishing, 2001.

Nitika Mathur, Johnny Wei, Markus Freitag, Qingsong Ma, and Ondřej Bojar. Results of the WMT20 metrics shared task. In *Proceedings of the Fifth Conference on Machine Translation*, pp. 688–725, Online, November 2020. Association for Computational Linguistics. URL `https://aclanthology.org/2020.wmt-1.77`.

Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. On faithfulness and factuality in abstractive summarization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 1906–1919, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.173. URL `https://aclanthology.org/2020.acl-main.173`.

Shashi Narayan, Shay B. Cohen, and Mirella Lapata. Don't give me the details, just the summary! topic-aware convolutional neural networks for extreme summarization. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 1797–1807, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1206. URL `https://aclanthology.org/D18-1206`.

Jun-Ping Ng and Viktoria Abrecht. Better summarization evaluation with word embeddings for ROUGE. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 1925–1930, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1222. URL `https://aclanthology.org/D15-1222`.

Yixin Nie, Adina Williams, Emily Dinan, Mohit Bansal, Jason Weston, and Douwe Kiela. Adversarial NLI: A new benchmark for natural language understanding. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4885–4901, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.441. URL `https://aclanthology.org/2020.acl-main.441`.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *arXiv preprint arXiv:2203.02155*, 2022.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL `https://aclanthology.org/P02-1040`.

Maja Popović. chrF: character n-gram F-score for automatic MT evaluation. In *Proceedings of the Tenth Workshop on Statistical Machine Translation*, pp. 392–395, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/W15-3049. URL https://aclanthology.org/W15-3049.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

Victor Sanh, Albert Webson, Colin Raffel, Stephen Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Arun Raja, Manan Dey, M Saiful Bari, Canwen Xu, Urmish Thakker, Shanya Sharma Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Fevry, Jason Alan Fries, Ryan Teehan, Teven Le Scao, Stella Biderman, Leo Gao, Thomas Wolf, and Alexander M Rush. Multitask prompted training enables zero-shot task generalization. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=9Vrb9D0WI4.

Thibault Sellam, Dipanjan Das, and Ankur Parikh. BLEURT: Learning robust metrics for text generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7881–7892, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.704. URL https://aclanthology.org/2020.acl-main.704.

Brian Thompson and Matt Post. Automatic machine translation evaluation in many languages via zero-shot paraphrasing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 90–121, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.8. URL https://www.aclweb.org/anthology/2020.emnlp-main.8.

R. Vedantam, C. Zitnick, and D. Parikh. Cider: Consensus-based image description evaluation. In *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4566–4575, Los Alamitos, CA, USA, jun 2015. IEEE Computer Society. doi: 10.1109/CVPR.2015.7299087. URL https://doi.ieeecomputersociety.org/10.1109/CVPR.2015.7299087.

Alex Wang, Kyunghyun Cho, and Mike Lewis. Asking and answering questions to evaluate the factual consistency of summaries. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5008–5020, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.450. URL https://aclanthology.org/2020.acl-main.450.

Weizhe Yuan, Graham Neubig, and Pengfei Liu. BARTScore: Evaluating generated text as text generation. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=5Ya8PbvpZ9.

Tianyi Zhang*, Varsha Kishore*, Felix Wu*, Kilian Q. Weinberger, and Yoav Artzi. Bertscore: Evaluating text generation with bert. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SkeHuCVFDr.

Wei Zhao, Maxime Peyrard, Fei Liu, Yang Gao, Christian M. Meyer, and Steffen Eger. MoverScore: Text generation evaluating with contextualized embeddings and earth mover distance. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 563–578, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1053. URL https://aclanthology.org/D19-1053.

A   APPENDIX

A.1   SENTENCE MATCHING FUNCTIONS

The scores we get from SMART depend on the sentence matching function `match`. We investigate six different sentence matching functions widely used in both machine translation and document summarization. Specifically, we compare three string-based and three model-based matching functions. The former do not rely on accelerators (GPUs/TPUs) while the latter leverage pretrained neural models. Thus, we expect string-based matching functions to be inferior, but they are good alternatives for faster evaluation or when accelerators are not available.

ROUGE (Lin, 2004)   A popular document summarization evaluation metric, it measures the number of overlapping textual units. As with most summarization work, we explored three types of textual units: unigrams (ROUGE-1), bigrams (ROUGE-2), and longest common subsequence (ROUGE-L).

BLEU (Papineni et al., 2002)   A popular machine translation evaluation metric, it is a precision-focused metric that calculates n-gram overlap between two texts and also includes a brevity penalty.

CHRF (Popović, 2015)   Another machine translation evaluation metric, it calculates character-based n-gram overlap between system and reference sentences. Unlike ROUGE and BLEU which operate at the token level, CHRF is more effective especially in morphologically-rich languages as it does not require any tokenization, lemmatization, and stemming (Mathur et al., 2020; Kocmi et al., 2021).

BERTScore (Zhang* et al., 2020)   A model-based metric that leverages contextualized token embeddings from BERT(-like models). It computes similarity scores by aligning tokens from reference and candidate summaries, and token alignments are computed greedily to maximize cosine similarity.

ANLI (Honovich et al., 2022)   Another model-based metric mainly used to evaluate factuality, which uses T5 (Raffel et al., 2020) fine-tuned on the ANLI dataset (Nie et al., 2020) to produce a score between 0 (not entailed) and 1 (entailed) given a premise and a hypothesis. We use the source/reference as premise and the candidate summary as hypothesis.

BLEURT (Sellam et al., 2020)   A supervised model-based metric that uses BERT that is trained to predict human judgment scores using a small-scale dataset. To make it more robust, the model is first pretrained with a large-scale synthetic dataset. Moreover, it is optimized using several objectives including ROUGE, BLEU, BERTScore, and entailment. BLEURT has been shown to be effective in evaluating sentence match in machine translation, thus we expect it to be the better matching function among all matching functions.

One advantage of SMART is that it is easily extensible by changing the matching functions to better ones. This means that a more domain-specific matching function can be used for evaluation towards specific domains, or a better-performing sentence matching metric can be used to improve overall evaluation.

SMART with Different Matching Functions   We compare different variants of SMART using the six matching functions described in Section A.1. Table 4 shows their system-level correlations, where Coh, Fac, Flu, and Inf stand for coherence, factuality, fluency, and informativeness, respectively. Among string-based matching functions, CHRF performs the best in terms of average correlation, followed by BLEU. This shows that machine translation metrics are better sentence matchers. Among model-based matching functions, BLEURT performs the best by a large margin; SMART with BLEURT significantly outperforms all the other model-based variants on all dimensions of summary quality. We believe that this is because BLEURT is optimized to match sentences, as well as to predict ROUGE, BLEU, BERTScore, and entailment scores. Interestingly, ANLI as a matching function underperforms even in the factuality dimension. We posit that this is because sentences are passed to the matching function without their neighboring context.

Matching Function	SMART Type	Coherence	Factuality	Fluency	Informativeness	μ
SMART with String-based Matching Functions						
ROUGE-1	S1	.233	**.733***	.494	.500*	.490
	S2	.217	.683	.477	.417	.448
	SL	.267	.700	.460	.467	.473
ROUGE-2	S1	.183	.650	.477	.417	.432
	S2	.183	.650	.477	.417	.432
	SL	.217	.650	.444	.383	.423
ROUGE-L	S1	.233	**.733***	.527*	.500*	.498
	S2	.217	.683	.477	.417	.448
	SL	.267	.700	.460	.467	.473
BLEU	S1	.300	**.733***	.527*	.467	.507
	S2	.283	.717	.510	.450	.490
	SL	.317	.717	.460	.483	.494
CHRF	S1	.300	**.733***	.494	.500*	.507
	S2	.300	.700	.460	.433	.473
	SL	.367*	**.733***	.494	.500*	.523
SMART with Model-based Matching Functions						
BERTScore	S1	.317	.683	.561	.517	.519
	S2	-.017	.383	.276	.183	.207
	SL	.383	.683	.527	.583	.544
ANLI	S1	.117	.550	.444	.350	.365
	S2	.133	.533	.360	.333	.340
	SL	.117	.483	.343	.350	323
BLEURT	S1	.433	.667	**.644***	.667	.603
	S2	.417	**.750***	**.628***	.528	.594
	SL	**.567***	.567	.611	**.733***	.619

Table 4: Kendall tau system-level correlation of variants of SMART using different matching functions. For each block, correlations of metrics not significantly outperformed by any other metric (using William's Test; Graham & Baldwin, 2014) for that specific dimension are marked with an asterisk (*). Those that are not significantly outperformed by all metrics are **boldfaced**. We also show the average scores in the μ column, where the top three values for each block are underlined.

Figure 3: Length Analysis. Relative increase in Kendall tau system-level correlation with respect to ROUGE-X of four evaluation metrics for each length bucket (leftmost bucket has the shortest lengths).

A.2 SMART WORKS WELL WITH LONGER SUMMARIES

We divided the datasets into four buckets based on the average number of tokens in the reference summary, where the first bucket contains the shortest reference summaries. For each bucket, we then calculated system-level correlation for all competing metrics. For each quality dimension, we report the relative increase in correlation with respect to ROUGE-X, which is illustrated in Figure 3. As can be seen in the figure, in general, all metrics perform better relative to ROUGE as the number of tokens increases from 43 tokens, which shows that ROUGE is not suitable for long summary evaluation. Interestingly, ROUGE also underperforms in the first bucket, which means that it is also not good at

Figure 4: Bias Analysis. Difference in ranking between human scores and metric scores for each competing metric, averaged over all quality dimensions. A negative value means that the metric ranks the system higher. M0 to M23 in the x-axis correspond to the summarization models, where M0 to M5 are extractive and the rest are abstractive. See Fabbri et al. (2021) for detailed model descriptions.

	Metric	σ(Rank Diff) $\downarrow$	Pairwise Acc. $\uparrow$
Coh	ROUGE-X	5.012	63.33
	SMS	5.500	63.33
	BARTScore	4.717	67.50
	SX-CHRF	5.232	65.00
	SX-BLEURT	**4.228**	**72.50**
Fac	ROUGE-X	4.228	70.00
	SMS	2.915	80.83
	BARTScore	2.915	80.83
	SX-CHRF	**2.062**	86.67
	SX-BLEURT	2.151	**87.50**
Flu	ROUGE-X	3.969	72.50
	SMS	4.650	67.50
	BARTScore	4.031	75.00
	SX-CHRF	3.824	74.17
	SX-BLEURT	**2.646**	**83.33**
Inf	ROUGE-X	3.841	75.00
	SMS	4.783	70.00
	BARTScore	4.500	72.50
	SX-CHRF	4.198	75.00
	SX-BLEURT	**2.739**	**82.50**

Table 5: The standard deviation of the difference in ranking between human and metric scores σ(Rank Diff) and the pairwise ranking accuracy of different metrics for different summary quality. Best scores are **boldfaced**.

evaluating short summaries. Among the competing metrics, SX-BLEURT (and SX-CHRF) correlate the best (and second best) when the there are more tokens in the source/reference.

A.3   SMART IS LESS BIASED TOWARDS SPECIFIC MODELS

While we acknowledge that all automatic metrics are not perfect as shown in Table 1, their rankings should not be hugely different from human rankings. Moreover, they should not be biased towards a single summarization model. To this end, we get the difference in rankings given by humans and by the automatic metrics for each summarization model for each quality dimension. Figure 4 illustrates the resulting differences averaged over all dimensions of summary quality, in which we have two interesting observations. Firstly, all automatic metrics are in general biased towards

Model	Human Ranking	ROUGE-1	ROUGE-2	ROUGE-L	BLEURT	Sx-BLEURT
		BBC Dataset				
GPT3-D2	1st	15.812	10.847	12.774	41.871	49.275
T0	2nd	10.617	4.831	8.185	39.952	42.747
BRIO	3rd	10.964	5.741	8.556	39.200	41.852
		CNN Dataset				
GPT3-D2	1st	24.357	17.974	20.215	42.946	48.911
BRIO	2nd	22.128	16.552	17.299	42.950	43.436
T0	3rd	15.182	10.445	12.492	40.641	41.486

Table 6: Scores of three systems on two different datasets based on five different reference-free metrics. Human rankings are also shown for comparison. Values that are colored red are those that do not correspond to the human rankings.

ranking extractive systems higher. This suggests that a separate extractive and abstractive model evaluation is necessary using current automatic metrics. We leave exploration of metrics that are equally unbiased towards both extractive and abstractive for future work. Secondly, we found that BARTScore scores BART (M22 in Figure 4; Lewis et al., 2020) significantly higher than all the other models (BARTScore of BART is -1.398 vs. -2.303 ± 0.313 on average without BART). This problem is amplified when BARTScore is finetuned using the CNN/DM dataset (-0.488 vs. -1.702 ± 0.248). This shows that using pretrained encoder-decoder models for summary evaluation induces bias towards summarization models finetuned on the same model.

In Figure 4, we can see that Sx-BLEURT is the least biased since its rank differences with human scores are closer to zero. To quantitatively measure if the above statement is true, we use two measures. The first one is the standard deviation of the rank difference, where the score closest to zero can be considered the least biased. The second measure is the pairwise ranking accuracy, where for all pairs of system, we check whether human and metric rankings are equivalent. Table 5 shows these numbers, which show that Sx-BLEURT has the lowest standard deviation of the rank difference and the highest pairwise rank accuracy across all quality dimensions. This entails that the metric is the least biased among the competing metrics.

A.4 SMART IS EFFECTIVE EVEN WITHOUT REFERENCE SUMMARIES

In this section, we show that SMART does not require reference summaries to effectively evaluate system summaries. We make use of two sets of newswire data from BBC and CNN from Goyal et al. (2022). Each dataset consists of a source news article and three candidate summaries generated by (1) GPT3-D2: a GPT-3 model (Brown et al., 2020) which is trained to follow user instructions (Ouyang et al., 2022); (2) BRIO (Liu et al., 2022): a summarization model fine-tuned on both CNN/DM (Hermann et al., 2015) and XSum (Narayan et al., 2018) which currently achieves state-of-the-art results; and (3) T0 (Sanh et al., 2022): a prompt-based model fine-tuned on multiple tasks which include summarization datasets.

Goyal et al. (2022) showed that reference-dependent metrics such as ROUGE (Lin, 2004), BERTScore (Zhang* et al., 2020), and QAEval (Deutsch et al., 2021) do not correlate well with human judgments. We therefore compared *reference-free* versions of five metrics: ROUGE 1/2/L, BLEURT, and Sx-BLEURT, where we calculate the scores by instead comparing the candidate summary with the source. Table 6 reports the scores of these metrics on the BBC and CNN datasets. As can be seen in the table, only Sx-BLEURT is able to rank the systems correctly on both datasets, according to the given human rankings. Both ROUGE and BLEURT scores produce incorrect rankings on one dataset, however GPT3-D2 is ranked the highest in most cases for all metrics. This entails that using reference summaries may not be necessary (and can be detrimental) to evaluate system summaries, and our results demonstrate that SMART is better equipped than other metrics.

Task	S1-ANLI	S2-ANLI	SL-ANLI	S1-BLEURT	S2-BLEURT	SL-BLEURT	S1-CHRF	S2-CHRF	SL-CHRF
FRANK	90.5	89.9	90.4	83.8	84.8	82.9	83.3	84.0	83.2
SummEval	80.8	77.4	81.0	75.3	74.8	75.8	75.2	75.5	75.9
MNBM	73.0	73.0	73.0	67.9	68.0	67.9	68.0	68.0	68.0
QAGS-C	83.0	79.7	79.1	80.9	79.2	79.4	75.5	75.2	74.9
QAGS-X	77.2	77.2	77.2	61.6	61.6	61.6	59.0	59.0	59.0
BEGIN	85.0	84.8	85.0	86.7	86.8	86.7	83.6	83.5	83.6
$Q^2_{dataset}$	82.3	82.5	82.2	69.6	70.5	69.6	60.7	62.0	60.7
DialFact	90.4	90.2	90.4	65.8	69.9	66.7	65.8	68.6	65.7
PAWS	98.3	98.3	98.3	66.4	66.3	66.4	66.3	66.2	66.3
Average	84.5	83.7	84.1	73.1	73.5	73.0	70.8	71.3	70.8

Table 7: ROC AUC results for the different metrics on the development set of the TRUE benchmark. The highest average score is **boldfaced**.

A.5 SMART FOR ASSESSING FACTUAL CONSISTENCY

Table 7 reports the ROC AUC scores of different individual SMART metrics using three different kinds of matching functions: ANLI, BLEURT, and CHRF. Overall, SMART with ANLI performs significantly better than the other matching functions. This is expected since ANLI produces scores that are extremely polarized (i.e., close to 0 or 1) even for slightly nonfactual pairs, which is more appropriate for this task. BLEURT and CHRF, on the other hand, produce partial scores for such pairs, which make them more appropriate in ranking systems, such as in SummEval.