Disentanglement of Correlated Factors via Hausdorff Factorized Support

Abstract

A grand goal in deep learning research is to learn representations capable of generalizing across distribution shifts. Disentanglement is one promising direction aimed at aligning a model's representations with the underlying factors generating the data (e.g. color or background). Existing disentanglement methods, however, rely on an often unrealistic assumption: that factors are statistically independent. In reality, factors (like object color and shape) are correlated. To address this limitation, we propose a relaxed disentanglement criterion – the Hausdorff Factorized Support (HFS) criterion – that encourages a factorized *support*, rather than a factorial distribution, by minimizing a Hausdorff distance. This allows for arbitrary distributions of the factors over their support, including correlations between them. We show that the use of HFS consistently facilitates disentanglement and recovery of ground-truth factors across a variety of correlation settings and benchmarks, even under severe training correlations and correlation shifts, with in parts over $+60\%$ in relative improvement over existing disentanglement methods. In addition, we find that leveraging HFS for representation learning can even facilitate transfer to downstream tasks such as classification under distribution shifts. We hope our original approach and positive empirical results inspire further progress on the open problem of robust generalization.

1 Introduction

Disentangled representation learning (Bengio et al., 2013; Higgins et al., 2018) is a promising path to facilitate reliable generalization to in- and out-of-distribution downstream tasks (Bengio et al., 2013; Higgins et al., 2018; Milbich et al., 2020; Dittadi et al., 2021; Horan et al., 2021), on top of being more interpretable and fair (Locatello et al., 2019a; Träuble et al., 2021). While Higgins et al. (2018) propose a formal definition based on group equivariance, and various metrics have been proposed to measure disentanglement (Higgins et al., 2017; Chen et al., 2018; Eastwood & Williams, 2018) the most commonly understood definition is as follows:

Definition 1.1 (Disentanglement) *Assuming the data has been generated by a set of unknown, ground-truth latent factors, a representation is said to be disentangled if each factor is recovered in one and only one dimension of the representation.*

Figure 1: *Real data exhibits correlations* between generative factors: cows are likely on grass, camels on sand. This contradicts disentanglement methods assuming statistically independent factors. Instead, we show that merely assuming and aiming for a factorized support can yield robust disentanglement even under correlated factors.

Consequently, the *goal* of disentangled representation is clear: a one-to-one correspondence between latent dimensions and ground-truth factors. The *method* by which to achieve this goal however, remains an open research question. Weak and semi-supervised settings, e.g. using paired data samples or auxiliary variables, can provably offer disentanglement and recovery of ground truth factors (Bouchacourt et al., 2018; Locatello et al., 2020b; Khemakhem et al., 2020; Klindt et al.,

2021). But fully unsupervised disentanglement – our focus in this study – is in theory impossible to achieve in the general unconstrained nonlinear case (Hyvärinen & Pajunen, 1999; Locatello et al., 2019b). In practice however the inductive biases embodied in common autoencoder architectures allow for effective practical disentanglement (Rolinek et al., 2019). Perhaps more problematic, standard unsupervised disentanglement methods (s.a. Higgins et al. (2017); Kim & Mnih (2018); Chen et al. (2018)) rely on an unrealistic assumption of statistical independence of ground truth factors. Real data however contains correlations (Träuble et al., 2021). Even with well defined factors, such as object shape, color or background, correlations are pervasive—yellow bananas are more frequent than red ones; cows are much more often on pasture than sand dunes. In more realistic settings where factors are correlated, prior work (e.g. Träuble et al. (2021); Dittadi et al. (2021)) has shown existing disentanglement methods fail.

To address this limitation, we propose to *relax* the unrealistic assumption of statistical independence of factors (i.e. that they have a factorial distribution), and only assume the *support* of the factors' distribution factorizes – a much weaker but more realistic constraint. For example, in a dataset of animal images (Fig. 1), background and animal are heavily correlated (camels most likely on sand, cows on grass). Under the original assumption of factor independence, a model likely learns a short-cut solution where animal and landscape share the same latent correspondence (Beery et al., 2018). On the other hand with a factorized support, learned factors should be such that any combination of their values has some grounding in reality: a cow on sand is an unlikely, yet not impossible combination. We still rely, just as standard unsupervised disentanglement methods, on the inductive bias of encoder-decoder architectures to recover factors (Rolinek et al., 2019). However, we expect our method to facilitate *robustness to any distribution shifts within the support* (Träuble et al., 2021; Dittadi et al., 2021), as it makes no assumptions on the distribution beyond its factorized support.

On this basis, we propose a concrete Hausdorff Factorized Support (HFS) training criterion to disentangle correlated factors by aiming for latents to have a factorized support. Specifically we enforce a factorized support by minimizing a Hausdorff set-distance between the finite sample approximation of the actual support and its factorization (Huttenlocher et al., 1993; Rockafellar & Wets, 1998). Across large-scale experiments on standard disentanglement benchmarks and novel extensions with correlated factors, HFS consistently facilitates disentanglement. We also show that HFS can be implemented as a regularizer alongside other disentanglement methods to reliably improve disentanglement. In particular, we observe significant improvements of in parts over $+60\%$ in disentanglement performance over baselines as measured by DCI-D (Eastwood & Williams, 2018) (§4.1, Tab. 1). On downstream classification tasks, we show improved generalization to more severe distribution shifts as well as improved sample efficiency (§4.2, Fig. 2). To summarize our contributions:

1. A novel principle for learning disentangled representations under correlated factors: relaxing the assumption of statistically independent factors into a factorized support only (§2.2).

2. A concrete training criterion through a Hausdorff distance term, which can also be combined with existing disentanglement methods (§2.3).

3. Extensive experiments on three main benchmarks under up to 14 increasingly difficult correlations settings, over in total more than 20k models, show that our criterion/regularizer systematically improves disentanglement (as measured by DCI-D) by up to $+61\%$ over standard baselines (β-VAE, β-TCVAE, FactorVAE and AnnealedVAE, c.f. §4.1). Upon acceptance, we will release our complete code base for the research community to further study disentanglement under a variety of correlation settings.

4. We show that our method improves robustness in the context of factor distribution shifts between train and test, with consistent improvements over disentanglement baselines on classification tasks of up to $+28\%$, as well as increased sample efficiency.

2 PROPOSED APPROACH

2.1 DISENTANGLEMENT VERSUS INDEPENDENCE

We are given a dataset $\mathcal{D} = \{\mathbf{x}^i\}_{i=1}^N$ (e.g. images), where each $\mathbf{x}^i$ is a realization of a random variable, e.g., an image. We consider that each $\mathbf{x}^i$ is generated by an unknown generative process, involving a ground truth latent random vector $\mathbf{z}$ whose components correspond to the dataset's underlying factors of variations (s.a. object shape, color, background, . . .). This process generates an

observation $\mathbf{x}$, by first drawing a realization $\mathbf{z} = (z_1, \ldots, z_k)$ from a distribution $p(\mathbf{z})$, i.e. $\mathbf{z} \sim p(\mathbf{z})$. Observation $\mathbf{x}$ is then obtained by drawing $\mathbf{x} \sim p(\mathbf{x}|\mathbf{z})$. Given $\mathcal{D}$, the *goal* of disentangled representation learning can be stated as learning a mapping f_ϕ that for any $\mathbf{x}$ recovers as best as possible the associated $\mathbf{z}$ i.e. $f_\phi(\mathbf{x}) \approx \mathbb{E}[\mathbf{z}|\mathbf{x}]$ up to a permutation of elements and elementwise bijective transformation. In unsupervised disentanglement, the $\mathbf{z}$ are unobserved, and both $p(\mathbf{z})$ and $p(\mathbf{x}|\mathbf{z})$ are *a priori unknown to us*, though we might assume specific properties and functional forms. Most unsupervised disentanglement methods follow the formalization of VAEs and employ parameterized *probabilistic generative models* of the form $p_\theta(\mathbf{x}, \mathbf{z}) = p_\theta(\mathbf{z})p_\theta(\mathbf{x}|\mathbf{z})$ to estimate the ground truth generative model over $\mathbf{z}, \mathbf{x}$. As in VAEs, these methods make the strong assumption that ground truth factors are statistically independent:

$$p(\mathbf{z}) = p(z_1)p(z_2)\ldots p(z_k). \tag{1}$$

and conflate the goal of learning a disentangled representation with that of learning a representation with statically independent components. This assumption naturally translates to a factorial model prior $p_\theta(\mathbf{z})$. Successful variants of VAE for disentanglement (Higgins et al., 2017; Kim & Mnih, 2018; Chen et al., 2018) further modify the original VAE objective to even more strongly enforce elementwise independence of the aggregate posterior (i.e. the *encoder* outputs) than afforded by the VAE's optimized evidence lower bound. However, as explained in the introduction, the assumption of factor independence clearly doesn't hold for realistic data distributions. Consequently, methods that enforce this unrealistic assumption suffer from that discrepancy, as shown in Träuble et al. (2021); Dittadi et al. (2021) and confirmed in our own experiments. To address this shortcoming, we develop a novel method to *relax* the unrealistic assumption of factor independence.

2.2 Relaxing the independence assumption into that of factorized support

Instead of assuming independent factors (i.e. a factorial distribution on $\mathbf{z}$ as in Eq. 1) we will only assume that the *support* of the distribution factorizes. Let us denote by $\mathcal{S}(p(\mathbf{z}))$ the *support* of $p(\mathbf{z})$, i.e. the set $\{\mathbf{z} \in \mathcal{Z} \,|\, p(\mathbf{z}) > 0\}$. We say that $\mathcal{S}(p(\mathbf{z}))$ is factorized if it equals to the Cartesian product of supports over individual dimensions' marginals, i.e. if:

$$\mathcal{S}(p(\mathbf{z})) = \mathcal{S}(p(z_1)) \times \mathcal{S}(p(z_2)) \times \ldots \times \mathcal{S}(p(z_k)) \stackrel{\text{def}}{=} \mathcal{S}^\times(p(\mathbf{z})) \tag{2}$$

where $\times$ denotes the Cartesian product. Of course, 1 (independence) $\Rightarrow$ 2 (factorized-support) but 2 (factorized-support) $\not\Rightarrow$ 1 (independence). Assuming a factorized support is thus a *relaxation* of the (unrealistic) assumption of factorial distribution, (i.e. of statistical independence) of disentangled factors. Refer to the cartoon example in Fig. 1, where the distribution of the two disentangled factors would not satisfy an independence assumption, but does have a factorized support. Informally the factorized support assumption is merely stating that whatever values z_1 and z_2, etc... may take individually, any combination of these is *possible* (even when not very likely). In the next section we will develop a concrete training criterion that encourages the obtained latent representation to have a factorized support rather than a factorial distribution.

2.3 A practical criterion for factorized support

Based on our relaxed hypothesis, we now define a concrete *training criterion* that encourages a factorized support. Let us consider deterministic *representations* obtained by the encoder $\mathbf{z} = f_\phi(\mathbf{x})$. We enforce the factorial support criterion on the aggregate distribution $\bar{q}_\phi(\mathbf{z}) = \mathbb{E}_\mathbf{x}[f_\phi(\mathbf{x})]$, where $\bar{q}_\phi(\mathbf{z})$ is conceptually similar to the *aggregate posterior* $q_\phi(\mathbf{z})$ in e.g. TCVAE, though we consider points produced by a deterministic mapping f_ϕ rather than a stochastic one. To match our factorized support assumption on the ground truth we want to encourage the support of $\bar{q}_\phi(\mathbf{z})$ to factorize, i.e. that $\mathcal{S}(\bar{q}_\phi(\mathbf{z}))$ and the Cartesian product of each dimension support, $\mathcal{S}^\times(\bar{q}_\phi(\mathbf{z}))$, are equal. For clarity we use shorthand notations $\mathcal{S}$ and $\mathcal{S}^\times$ to denote $\mathcal{S}^\times(\bar{q}_\phi(\mathbf{z}))$ and $\mathcal{S}(\bar{q}_\phi(\mathbf{z}))$ respectively when it is clear from context. To guide the learning, we thus need a divergence or metric to tell us how far $\mathcal{S}$ is from $\mathcal{S}^\times$. Supports are sets, so it is natural to use a set distance such as the Hausdorff distance.

Hausdorff distance between sets Given a base distance metric $d(\mathbf{z}, \mathbf{z}')$ between any two points in $\mathcal{Z}$ (e.g. the Euclidean metric in $\mathcal{Z} = \mathbb{R}^k$), the Hausdorff Distance between sets (here, $\mathcal{S}^\times$ and $\mathcal{S}$), is then defined as

$$d_H(\mathcal{S}, \mathcal{S}^\times) = \max \left(\sup_{\mathbf{z} \in \mathcal{S}^\times} \left[\inf_{\mathbf{z}' \in \mathcal{S}} d(\mathbf{z}, \mathbf{z}') \right], \sup_{\mathbf{z} \in \mathcal{S}} \left[\inf_{\mathbf{z}' \in \mathcal{S}^\times} d(\mathbf{z}, \mathbf{z}') \right] \right) = \sup_{\mathbf{z} \in \mathcal{S}^\times} \left[\inf_{\mathbf{z}' \in \mathcal{S}} d(\mathbf{z}, \mathbf{z}') \right] \tag{3}$$

with the second part of the Hausdorff distance equating to zero since $\mathcal{S} \subset \mathcal{S}^{\times}$.

Monte-Carlo Hausdorff Distance Estimation   In practice we only have a finite sample of observations $\{\mathbf{x}\}_i^N$, and can only estimate the support and Hausdorff distances from the finite number of representations $\{f_\phi(\mathbf{x})\}_i^N$. We thus introduce a practical Monte-Carlo batch-approximation : with access to a batch of b inputs $\mathbf{X}$ yielding b k-dimensional latent representations $\mathbf{Z} = f_\phi(\mathbf{X}) \in \mathbb{R}^{b \times k}$, we estimate Hausdorff distances using sample-based approximations to the support: $\mathcal{S} \approx \mathbf{Z}$ and $\mathcal{S}^{\times} \approx \mathbf{Z}_{:,1} \times \mathbf{Z}_{:,2} \times ... \times \mathbf{Z}_{:,k} = \{(z_1, \ldots, z_k), \; z_1 \in \mathbf{Z}_{:,1}, \ldots, z_k \in \mathbf{Z}_{:,k}\}$. Here $\mathbf{Z}_{:,j}$ must be understood as the *set* (not vector) of all elements in the j^{th} column of $\mathbf{Z}$. Plugging into Eq. 3 yields:

$$\hat{d}_H(\mathbf{Z}) = \max_{\mathbf{z} \in \mathbf{Z}_{:,1} \times \mathbf{Z}_{:,2} \times ... \times \mathbf{Z}_{:,k}} \left[\min_{\mathbf{z}' \in \mathbf{Z}} d(\mathbf{z}, \mathbf{z}')\right] \tag{4}$$

where by noting $\mathbf{z}' \in \mathbf{Z}$ we consider the matrix $\mathbf{Z}$ as a *set* of rows, over which we find the min[1].

Further relaxing the assumption to pairwise factorization   In high dimension, with many factors, the assumption that *every combination of all latent values is possible* might still be too strong an assumption. And even if we assumed all to be in principle possible, we can never hope to observe all in a finite dataset of realistic size due to the combinatorial explosion of conceivable combinations. However, it is statistically reasonable to expect evidence of a factorized support for all pairs of elements[2]. To encourage such a pairwise factorized support, we can minimize a sliced/pairwise Hausdorff estimate with the additional benefit of keeping computation tractable when k is large

$$\hat{d}_H^{(2)}(\mathbf{Z}) = \sum_{i=1}^{k-1} \sum_{j=i+1}^{k} \max_{\mathbf{z} \in \mathbf{Z}_{:,i} \times \mathbf{Z}_{:,j}} \left[\min_{\mathbf{z}' \in \mathbf{Z}_{:,(i,j)}} d(\mathbf{z}, \mathbf{z}')\right] \tag{5}$$

where $\mathbf{Z}_{:,(i,j)}$ denotes the concatenation of column i and column j, yielding a *set of rows*.

Avoiding collapse and retaining input information   We will be learning representations $\mathbf{z} = f_\phi(\mathbf{x})$ by learning parameters ϕ that optimize a training objective. Because the Hausdorff distance builds on a base distance $d(\mathbf{z}, \mathbf{z}')$, if we were to minimize only this, it could be trivially minimized to 0 by collapsing all representations to a single point. Avoiding this can be achieved in several ways, s.a. by including a term that encourages the variance of $\mathbf{z}_{:,i}$ to be above 1 (a technique used e.g. in self-supervised learning method VICReg (Bardes et al., 2022)) or – more in line with traditional VAE variants for disentanglement – by using a stochastic autoencoder (SAE) reconstruction error:

$$\ell_{\text{SAE}}(\mathbf{x}; \phi, \theta) = -\mathbb{E}_{q_\phi(\mathbf{z}|\mathbf{x})} \left[\log p_\theta(\mathbf{x}|\mathbf{z})\right] \tag{6}$$

where typically $q_\phi(\mathbf{z}|\mathbf{x}) = \mathcal{N}(f_\phi(\mathbf{x}), \Sigma_\phi(\mathbf{x}))$ with mean given by our deterministic mapping f_ϕ, $\Sigma_\phi(\mathbf{x})$ producing a diagonal covariance parameter, and e.g. $\log p_\theta(\mathbf{x}|\mathbf{z}) = \|r_\theta(z) - x\|^2$ with r_θ a parameterized decoder. The autoencoder term ensures representations $f_\phi(\mathbf{x})$ retaining as much information as possible about $\mathbf{x}$ for reconstruction, preventing collapse of representations to a single point. A minimum scale can also be ensured by imposing $\Sigma_\phi(\mathbf{x})$ to be above a minimal threshold.

2.4   PUTTING IT ALL TOGETHER

Our basic training objective for Hausdorff-based Factored Support (HFS) can thus be formed by simply combining the stochastic auto-encoder loss of Eq. 6 and our Hausdorff estimate of Eq. 5:

$$\mathcal{L}_{\text{HFS}}(\mathcal{D}; \phi, \theta) = \mathbb{E}_{\mathbf{X} \overset{b}{\sim} \mathcal{D}} \left[\gamma \hat{d}_H^{(2)}(f_\phi(\mathbf{X})) + \frac{1}{b} \sum_{\mathbf{x} \in \mathbf{X}} \ell_{\text{SAE}}(\mathbf{x}; \phi, \theta)\right] \tag{7}$$

where $\mathbf{X} \overset{b}{\sim} \mathcal{D}$ denotes a batch of b training inputs, $f_\phi(\mathbf{X})$ the corresponding batch of representations $\mathbf{Z}$, $\sum_{\mathbf{x} \in \mathbf{X}}$ the sum over batch samples, and γ the hyperparameter controlling the tradeoff between the Hausdorff and SAE terms. To compare with existing VAE-based disentanglement methods s.a. the β-VAE (Higgins et al., 2017), we can also add our Hausdorff regularizer of Eq. 5 on top:

$$\begin{aligned}
\mathcal{L}_{\beta\text{VAE}+\text{HFS}}(\mathcal{D}; \phi, \theta) = \mathbb{E}_{\mathbf{X} \overset{b}{\sim} \mathcal{D}} \big[&\gamma \hat{d}_H^{(2)}(f_\phi(\mathbf{X})) \\
&+ \frac{1}{b} \sum_{\mathbf{x} \in \mathbf{X}} \left(\ell_{\text{SAE}}(\mathbf{x}; \phi, \theta) + \beta D_{\text{KL}}(q_\phi(\mathbf{z}|\mathbf{x}) || p_\theta(\mathbf{z})))\right) \big]
\end{aligned} \tag{8}$$

---

[1]One can alternatively use softened max and min operations, as defined in Appendix A.4. In practice, we saw no robustness benefit to this, likely because we compute $\hat{d}_H$ over batches, not the entire dataset.

[2]Straightforward to generalize to larger tuples, but computational and statistical benefits shrink accordingly.

where D_{KL} is the Kullback-Leibler divergence, and $p_\theta(\mathbf{z})$ the usual VAE factorial unit Gaussian prior. This is a hybrid objective, which recovers the original β-VAE with $\gamma = 0$, and our HFS objective of Eq. 7 with $\beta = 0$. One can thus see that the plain HFS objective *replaces* the β-VAE KL term by our factorized-support-encouraging Hausdorff term, which precisely gets rid of the factorial prior $p(\mathbf{z})$. We can similarly extended other VAE-based variants (Chen et al., 2018; Kim & Mnih, 2018; Burgess et al., 2018) by adding our Hausdorff term as regularizer, to deemphasize getting a precise factorial distribution and focus more on its support.

3 RELATED WORK

Disentangled Representation Learning. Disentangled representation learning aims to recover representation spaces where each ground-truth generative factor is encoded in a unique entry or subspace (Bengio et al., 2013; Higgins et al., 2018) to benefit subsequent downstream transfer (Bengio et al., 2013; Peters et al., 2017; Tschannen et al., 2018; Locatello et al., 2019b; Montero et al., 2021; Mancini et al., 2021; Funke et al., 2022), interpretability (Chen et al., 2016; Esser et al., 2018; Niemeyer & Geiger, 2021) and fairness (Locatello et al., 2019a; Träuble et al., 2021) via compositionality of representations and properties. To tackle this, methods often rely on variants of Variational AutoEncoders (VAEs) (Kingma & Welling, 2014; Rezende et al., 2014), trying to constrain the (aggregate) posterior of the encoder, e.g. via penalties on the bottleneck capacity of the VAE (β-VAE (Higgins et al., 2017)) with progressive constraints or network growing (Annealed-VAE (Burgess et al., 2018), ProVAE (Li et al., 2020)), the total correlation (β-TCVAE (Chen et al., 2018), FactorVAE (Kim & Mnih, 2018)) or the mismatch to some factorized prior (DIP-VAE (Kumar et al., 2018), DoubleVAE (Mita et al., 2020)). In practice these approaches assume *statistically independent* ground-truth factors, an invalid assumption for realistic data (as motivated in §1).

Disentanglement under correlated factors. Consequently, while most methods have been shown to perform well on toy datasets and ones with known independent factors such as Shapes3D (Kim & Mnih, 2018), MPI3D (Gondal et al., 2019), DSprites (Higgins et al., 2017), SmallNorb (LeCun et al., 2004) or Cars3D Reed et al. (2015), recent research (Montero et al., 2021; Träuble et al., 2021; Montero et al., 2022; Funke et al., 2022; Dittadi et al., 2021) has started to connect these setups to more realistic scenarios where factor correlations are existent: Träuble et al. (2021) introduce artificial correlations between two factors, and Montero et al. (2021) exclude specific value combinations for recombination studies. In such settings, Montero et al. (2021); Träuble et al. (2021); Montero et al. (2022); Dittadi et al. (2021) show that unsupervised disentanglement methods that assume independent factors fail to disentangle, with potentially negative impact to out-of-distribution generalization. The analysis of Suter et al. (2019) assumes confounders between the ground-truth factors, and only propose a causal metric to evaluate disentanglement in that setting. Choi et al. (2020) only introduce a Gaussian mixture model to model dependencies between continuous and discrete variables in a very structured setup, and assume the number of mixtures to be known. Thus, to the best of our knowledge we are the first to propose a generic remedy by relaxing the independence assumption without explicit auxiliary variables or specific prior models. We also significantly extend the experimental suite done in Träuble et al. (2021) to investigate harder and more complex correlation settings and shifts. To evaluate disentanglement, we utilize DCI-D (part of DCI – **D**isentanglement, **C**ompleteness, **I**nformativeness, see Eastwood & Williams (2018)) as our leading metric. As opposed to other metrics s.a. Beta-/FactorVAE scores (Higgins et al., 2017; Kim & Mnih, 2018), MI Gap Chen et al. (2018), Modularity (Ridgeway & Mozer, 2018) or SAP (Kumar et al., 2018), Locatello et al. (2020a); Dittadi et al. (2021) have indicated DCI-D as the potentially most suitable metric to evaluate disentanglement (and as also done e.g. in Locatello et al. (2019b; 2020b); Träuble et al. (2021)), with generally strong correlations between most metrics (Locatello et al., 2019b).

4 EXPERIMENTS

We start with experimental details listed below, before studying HFS on benchmarks with and without training correlations (§4.1). These results are extended in §4.2 to evaluate the transfer and downstream adaptability (§4.3) of learned representations across different correlation shifts and link HFS during training to various downstream metrics (§4.4). We include variant, qualitative and hyperparameter robustness studies in appendix §B, §E and §D - all favouring our HFS objective.

Table 1: *Disentanglement by explicitly factorizing the support* using HFS, on 3 benchmark problems, across various numbers of correlated factors (columns) with correlation increasing from left (no correlation) to right (every factor correlated to one confounder). Reported numbers are the DCI-D metric computed on uncorrelated test data. (**Bold**) **boldblue** denotes (second) best performance per benchmark/correlation. [a, b] indicate 25th/75th percentiles around the median. The results show that relaxing the goal of a factorial latent distribution to a **factorized support** with standalone HFS already **offers competitive disentanglement**. Moreover adding HFS as regularizer over standard methods (β-VAE/TCVAE) to steer them towards a more factorized support yields even higher improvements, beating other standard approaches (with optimally tuned hyperparameters s.a. β). Remarkably on MPI3D, optimal tuning turned β and other TCVAE terms to 0, leaving only HFS which consistently worked best. For DSprites, three pairs are not possible - see main text.

METHOD	NO CORR.	PAIRS: 1 $\sigma = 0.1$	PAIRS: 2 $\sigma = 0.1$	PAIRS: 3 $\sigma = 0.1$	SHARED CONF. $\sigma = 0.2$
Shapes3D (Kim & Mnih, 2018)					
β-VAE	70.7 [65.2, 75.4]	71.6 [60.9, 72.5]	55.6 [45.8, 57.2]	37.1 [32.3, 38.9]	38.0 [35.0, 38.6]
HFS	78.3 [75.1, 83.6]	77.8 [74.4, 78.8]	56.0 [41.0, 57.4]	47.5 [38.0, 49.1]	46.2 [36.3, 47.5]
β-VAE + HFS	**91.2 [75.8, 100.0]**	**80.9 [76.4, 81.4]**	**67.6 [62.4, 69.3]**	**47.9 [44.0, 50.8]**	**63.5 [61.2, 65.5]**
β-TCVAE	77.1 [76.6, 78.3]	71.1 [65.5, 72.5]	63.8 [59.1, 65.1]	47.3 [36.7, 50.0]	49.9 [45.8, 55.9]
β-TCVAE + HFS	**85.7 [82.5, 97.3]**	**75.2 [63.1, 76.6]**	**68.3 [61.0, 71.8]**	**51.6 [47.7, 52.8]**	61.5 [53.8, 64.2]
FactorVAE	66.1 [51.2, 69.1]	70.8 [70.5, 71.2]	57.2 [55.9, 62.0]	46.8 [40.8, 49.0]	31.6 [27.9, 35.1]
AnnealedVAE	62.2 [60.7, 63.2]	57.2 [49.5, 59.3]	31.6 [26.9, 34.1]	33.6 [31.0, 38.0]	23.0 [20.1, 25.9]
DSprites (Higgins et al., 2017)					
β-VAE	32.2 [25.3, 37.9]	9.5 [7.9, 10.3]	7.5 [6.7, 8.3]	N/A	11.4 [9.9, 13.9]
HFS	34.9 [27.4, 36.0]	13.6 [7.6, 16.7]	11.9 [9.7, 13.8]	N/A	15.1 [11.0, 16.0]
β-VAE + HFS	**49.9 [30.0, 50.4]**	19.7 [17.0, 21.1]	**17.3 [6.0, 19.6]**	N/A	15.8 [12.3, 16.7]
β-TCVAE	30.9 [28.9, 35.2]	**24.0 [23.6, 24.4]**	11.4 [7.6, 13.6]	N/A	**20.9 [17.5, 23.6]**
β-TCVAE + HFS	**53.1 [41.8, 53.2]**	**26.5 [25.6, 27.2]**	**27.8 [16.1, 31.6]**	N/A	**24.8 [23.8, 26.3]**
FactorVAE	25.7 [20.9, 30.9]	15.1 [11.9, 16.3]	13.4 [12.4, 15.0]	N/A	14.7 [13.5, 15.3]
AnnealedVAE	39.4 [38.7, 40.0]	14.8 [14.3, 15.9]	8.5 [6.9, 10.3]	N/A	14.3 [14.1, 14.5]
MPI3D (Gondal et al., 2019)					
β-VAE	25.6 [24.7, 26.1]	20.5 [17.7, 20.9]	23.6 [22.6, 24.3]	11.6 [11.1, 11.7]	11.8 [10.0, 12.7]
HFS	**32.8 [30.0, 34.3]**	**28.4 [26.5, 29.5]**	**28.0 [27.4, 28.2]**	**14.3 [13.1, 14.8]**	**16.1 [15.0, 16.6]**
β-VAE + HFS	**32.8 [30.0, 34.3]**	**28.4 [26.5, 29.5]**	**28.0 [27.4, 28.2]**	**14.3 [13.1, 14.8]**	**16.1 [15.0, 16.6]**
β-TCVAE	26.6 [26.0, 27.4]	20.7 [20.4, 21.3]	23.3 [21.9, 23.8]	11.4 [10.3, 12.6]	14.2 [13.4, 15.4]
β-TCVAE + HFS	**32.8 [30.0, 34.3]**	**28.4 [26.5, 29.5]**	**28.0 [27.4, 28.2]**	**14.3 [13.1, 14.8]**	**16.1 [15.0, 16.6]**
FactorVAE	26.0 [24.8, 27.5]	21.9 [20.1, 23.9]	27.8 [27.2, 29.2]	10.9 [10.7, 11.9]	13.6 [12.8, 13.9]
AnnealedVAE	11.8 [10.8, 12.4]	11.7 [10.4, 12.9]	11.8 [11.6, 12.1]	11.6 [10.6, 12.2]	13.4 [12.8, 13.9]

Design Details Across experiments, we re-implemented baselines (β-VAE (Higgins et al., 2017), FactorVAE (Kim & Mnih, 2018), AnnealedVAE (Burgess et al., 2018), β-TCVAE (Chen et al., 2018)) as done e.g., in Locatello et al. (2019b; 2020b); Träuble et al. (2021). To investigate methods under correlated ground truth factors, we use and extend the correlation framework introduced in Träuble et al. (2021) who introduce correlation between pairs of factors as $p(z_1, z_2) \propto \exp\left(-(z_1 - f(z_2))^2/(2\sigma^2)\right)$, where higher σ notes weaker correlation between normalized factors z_1 and z_2, and $f(z) = z$ or $f(z) = 1 - z$ for inverted correlations when necessary . We extend this framework to include correlations between *multiple* factor pairs (either 1, 2 or 3 pairs) and shared confounders (one factor correlated to all others). All reported numbers are computed on at least 6 seeds (with ≥ 10 seeds used for key experiments s.a. Tab. 1 or Fig. 2). Similar to existing literature (Locatello et al., 2019b; 2020b; Träuble et al., 2021; Dittadi et al., 2021) we cover at least 7 hyperparameter settings for each baseline. Further experimental details are provided in §G.

4.1 FACTORIZATION OF SUPPORTS FOR DISENTANGLEMENT ON STANDARD BENCHMARK

We study the behaviour of HFS and baselines on standard disentanglement learning benchmarks and correlated variants thereof (see §4) - Shapes3D (Kim & Mnih, 2018), MPI3D Gondal et al. (2019) and DSprites (Higgins et al., 2017). For each setting, we report results averaged over ≥ 10 seeds in Tab. 1. Each column denotes the test performance on uncorrelated data for all methods trained on a particular correlation setting. As DSprites only has five effective factors of variation, no three-pair setting is possible. Values reported denote median DCI-D with 25th and 75th percentiles in grey.

Figure 2: *Out-of-Distribution Disentanglement and Generalization across large ranges of correlation shifts* between train and test data on Shapes3D. We evaluate the impact of encouraging factorized support on disentanglement (DCI-D) and classification performance of test ground truth factors (DCI-I) via HFS. Y-axis denotes source correlations increasing from top to bottom, x-axis target correlations (left to right). Darker blue and green mean higher scores and absolute improvements, respectively. **[Leftmost]:** DCI-D β-VAE for all shifts, dropping with higher training correlations. **[Left]:** Consistent and in parts very high absolute improvements in DCI-D when explicitly encouraging factorized support via β-VAE + HFS across shifts. **[Right]:** DCI-I using a Gradient Boosted Tree over embeddings generated by a β-VAE model trained on respective source correlations. Drop in performance with higher training correlation or test data variation (bottom left corner). **[Rightmost]:** Absolute changes in DCI-I when instead using a β-VAE + HFS model, revealing particularly high benefits to generalization when shifts are severe (c.f. bottom and bottom left corner). These results showcase that explicitly encouraging factorized support benefits disentanglement across correlation shifts and facilitates downstream generalization as these become more severe.

Our results indicate that a factorization of the support via HFS encourages disentanglement (as measured via DCI-D) without relying on a factorial distribution objective (s.a. β-VAE and its variants), consistently matching or outperforming the comparable β-VAE setting - both when no correlation is encountered during training (*"No Corr."*) as well as for much more severe correlations (*"Conf."*). Even more, we find that extending existing disentanglement objectives s.a. β-VAE (or stronger extensions like β-TCVAE) with explicit factorization of the support (+HFS) can provide even further, **significant** improvements. For example, without correlations we find relative improvements of nearly **+30**%, while for some correlated settings, e.g. with a shared confounder, these go over **+60**%! In addition, relative increases of up to **+140**% on β-TCVAE further highlight both the general importance of an explicit factorization of the support for disentanglement even under training correlations, as well as it being a property generally neglected until now.

4.2 OUT-OF-DISTRIBUTION GENERALIZATION UNDER CORRELATION SHIFTS

As β-VAE and β-VAE + HFS models in §4.1 were trained on correlated and evaluated on uncorrelated data, the performance differences provide a first indication that benefits of explicitly encouraging a factorized support transfer under correlation shifts. Such changes in correlation from train to test data is commonly referred to as "distributional shift" (Quinonero-Candela et al., 2009), which are a practical problem as the test data becomes out-of-distribution for the model, and mark a key issue interfering with generalization in realistic settings (Arjovsky et al., 2019; Koh et al., 2021; Milbich et al., 2021; Funke et al., 2022). While some works point to initial benefits of disentangled representations for out-of-distribution (OOD) generalization (e.g. Träuble et al. (2021); Dittadi et al. (2021)), some have raised concerns about the gains from disentanglement e.g. on OOD recombination (Montero et al., 2022). Conceptually, one way a disentangled representation can benefit a downstream prediction task is when the true predictor is a function of only a *subset* of the true factors. Successful recovery of all factors, disentangled, enables effective subsequent feature selection (e.g. by L1-regularized logistic regression or shallow decision trees). **A downstream predictor can thus be far more sample efficient (Ng, 2004) in learning to ignore irrelevant factors**, that may be spuriously correlated with the target, than if they were entangled in the representation. As we showed that explicit support factorization reliably provides stronger disentanglement, we leverage this to offer further insights into its benefits on OOD tasks. Given the strong performance of HFS to disentangle Shapes3D, we extend our experiments from §4.1 on this dataset with more training correlations and the same set of correlations on the test data. This gives a large transfer grid (Fig. 2)

Figure 3: *Increased accuracy and sample efficiency on downstream classification.* We plot relative improvement (%) in average ground truth factor classification accuracy by using our factorized support regularization (HFS) on top of a β-VAE, as a function of the amount of labeled training data. Classifier is a gradient boosted tree (for linear probe see §F.2) receiving either the entire latent vector (black) or only the most expressive latent entry (blue). The increased disentanglement through HFS gives consistent improvements in all cases, and gets even more pronounced in the low data regime for full latents, **indicating higher sample efficiency, as expected from better disentanglement**. Finally, relative improvements up to nearly $+80\%$ in the single latent entry case across correlation shifts highlight the better reflection of ground truth factors across correlation shifts.

across all kinds of (increasingly severe) correlation shifts. For each grid, the y- and x-axis indicate training and test correlations increasing from top to bottom and left to right, respectively. Darker colors refer to a score increase. We use these grids to see **(1)** how different correlation shifts impact disentanglement, and **(2)** if improvements in disentanglement via explicitly aiming for a factorized support impact downstream transferability of the learned representations.

(1) We first evaluate the disentanglement of a standard β-VAE (**leftmost** grid; each square uses optimal parameters for a given correlation and seed), and find an expected drop where β-VAE struggles to separate ground truth factors at test time with increased correlation on the training data. The subsequent grid shows changes when adding our proposed HFS to β-VAE. Note that all number are positive, showing consistent improvements in disentanglement of test data over β-VAE across **all** correlation shifts, and extend our insights from Tab. 1.

(2) To understand the usefulness of our learned representations for practical transfer tasks under correlation shifts, we train a Gradient Boosted Tree (using sklearn (Pedregosa et al., 2011), c.f. Locatello et al. (2019b; 2020b)) to take representations of the test data and predict the exact values for each ground truth factor; reflected in the third grid for the β-VAE baseline and measured by the DCI-I metric introduced in Eastwood & Williams (2018). We see that the downstream classification performance, while saturated for small shifts, drops notably both with increased training correlation or more variation in the test data (performance drop towards bottom left corner). If we now measure the absolute change in downstream classification performance when **adding** HFS (last grid), we see that while for small shifts the benefits of better disentanglement through a factorized support are small, they noticeably increase for larger ones (increase towards same bottom left corner). This indicates that changes in disentanglement through our support factorization become increasingly important as distributional shifts increase, and highlight that benefits for OOD generalization drawn from improvements in disentanglement may be particularly evident for harder shifts.

4.3 BENEFITS UNDER VARYING DOWNSTREAM ADAPTATION METHODS

This section augments §4.2 to investigate how generalization improvements hold when the amount of downstream test data changes, and revisits the recovery of ground truth factors under correlation shifts by looking at the classification performance when only the single most important latent entry (instead of the full latent) is given, to highlight how the increased disentanglement is reflected in the informativeness of each latent entry. Again, we train Gradient Boosted Trees (as we only care about relative changes, we utilize the xgboost (Chen & Guestrin, 2016) for much faster training) on embeddings extracted either from an optimal β-VAE or a β-VAE extended with HFS. For the single-latent-entry training, we first train a GBT to select the most important entry to predict each respective ground truth factor, and then only use said entry to train a second ground truth factor predictor. See Appendix §F.2 for the same experiments using a linear probe with L1-regularization.

All results are shown in Fig. 3, showing relative improvements when applying $\mathcal{L}_{\text{HFS}}$ on a β-VAE. In all cases, explicit support factorization facilitates downstream adaptation with particular

Figure 4: **[Left, orange]**: Increased support factorization on train data, as measured and encouraged by lower Hausdorff estimate $\hat{d}_H^{(2)}$ by increasing the HFS weighting γ (Eq. 7), improves downstream disentanglement (DCI-D) with and without factor correlations on Shapes3D (more correlation settings in App. Fig. 9). **[Center, black]**: Minimizing the β-VAE KL-Divergence by increasing β implicitly encourages a factorized support, via pushing towards full independence (which hurts disentanglement and generalization because an incorrect assumption). **[Right]**: We find strong correlation between HFS on train data and 6 standard disentanglement metrics evaluated on test data ([%], darker → higher), even under higher training correlations (top to bottom). Detailed figure in §F.5.

benefits when only little data is provided at test time. For example in the standard uncorrelated setting, relative improvements can increase from 4% up to 45%, with similar trends holding up across correlation shifts. Finally, our experiments reveal that increased disentanglement expectedly results in a better reflection of ground truth factors in single latent entries, shown in the nearly $+80\%$ relative improvement when training and predicting on the most expressive entry. All these insights both reinforce that an explicit factorization of support through HFS encourages improved disentanglement also under correlation shits, as well as showcasing potentially notable benefits in downstream generalisation performance especially in the low data regime.

4.4 FACTORIZATION AS A PERFORMANCE METRIC

We now explore the relationship of HFS w.r.t. existing metrics across correlations. In particular, we utilize Eq. 5 as a separate evaluation metric for the factorization of the support across the whole training data, facilitated through increased HFS weighting γ, and see how this relates to disentanglement and metrics evaluated on uncorrelated test data. Indeed, when the factorization of the support across the training data goes down (Fig. 4 *(left, orange)*), the disentanglement on the test data consistently goes up, verifying again the connection between support factorization and disentanglement. Fig. 4 *(center, black)* shows that the standard β-VAE implicitly encourages a factorized support, via pushing towards independence (which hurts disentanglement and generalization, as shown in our experiments). Finally, we find (Fig. 4 *(right)*) that a factorized support on the training data exhibits notable correlation with various disentanglement metrics, mostly consistent across also stronger training correlations, albeit lower than the uncorrelated setting. This is particularly useful, as the computation of HFS neither requires access to ground truth factor information nor specifying a prior distributions over the support, and can thus serve as a useful proxy for the development and training evaluation of future works.

5 CONCLUSION

To avoid the unrealistic assumption of factors independence (i.e. factorial distribution) as in traditional disentanglement, which stands in contrast to realistic data being correlated, we proposed an approach that only aims at recovering a factorized *support*. Doing so achieves disentanglement by requiring the model to encode any possible combination of generative factors in the learned latent space, while allowing for arbitrary distributions over the support – in particular those with correlations. Indeed, through a practical criterion using Hausdorff set-distances – HFS – we show that encouraging a factorized support is already sufficient to match traditional disentanglement methods. Even more so, our experiments show that HFS can steer existing disentanglement methods towards a more factorized support, giving large relative improvements of up to over $+60\%$ on common benchmarks across a large variety of increasingly harder correlation shifts. We find this improvement in disentanglement across correlation shifts to be also reflected in improved out-of-distribution generalization especially as these shifts become more severe; tackling a key promise for disentangled representation learning. We thus hope that our results encourage further research into the application of disentanglement to the open problem of robust generalization in more realistic settings.

6 REPRODUCIBILITY STATEMENT

To reproduce the results from this paper and avoid implementational and library-related differences, we will release our codebase upon acceptance, as noted in §1.

To reproduce Tab. 1, we first refer to Tab. 5, which contains all Tab. 1 results with additional details on the exact correlations used (as well as other correlation settings). For each of the correlation settings, the associated factor correlation pairs are provided in §G.1, with the training, model as well as grid-search details all noted in §G. The correlation formula to introduce artificial correlations between respective factors follows the setup described in the experimental details noted at the beginning of §4.

For the correlation shift transfer experiments used in §4.2, the same training and correlation settings are used. For our downstream adaptability results, we provide all relevant details in §4.3 and §G.

REFERENCES

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization, 2019. URL https://arxiv.org/abs/1907.02893.

Adrien Bardes, Jean Ponce, and Yann LeCun. VICReg: Variance-invariance-covariance regularization for self-supervised learning. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=xm6YD62D1Ub.

Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 35(8):1798–1828, 2013. doi: 10.1109/TPAMI.2013.50.

Diane Bouchacourt, Ryota Tomioka, and Sebastian Nowozin. Multi-level variational autoencoder: Learning disentangled representations from grouped observations. *Proceedings of the AAAI Conference on Artificial Intelligence*, 32(1), Apr. 2018. doi: 10.1609/aaai.v32i1.11867. URL https://ojs.aaai.org/index.php/AAAI/article/view/11867.

Christopher P. Burgess, Irina Higgins, Arka Pal, Loïc Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in beta-vae. *CoRR*, abs/1804.03599, 2018. URL http://arxiv.org/abs/1804.03599.

Ricky T. Q. Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/1ee3dfcd8a0645a25a35977997223d22-Paper.pdf.

Tianqi Chen and Carlos Guestrin. XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, pp. 785–794, New York, NY, USA, 2016. ACM. ISBN 978-1-4503-4232-2. doi: 10.1145/2939672.2939785. URL http://doi.acm.org/10.1145/2939672.2939785.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/7c9d0b1f96aebd7b5eca8c3edaa19ebb-Paper.pdf.

Jaewoong Choi, Geonho Hwang, and Myungjoo Kang. Discond-vae: Disentangling continuous factors from the discrete. *CoRR*, abs/2009.08039, 2020. URL https://arxiv.org/abs/2009.08039.

Andrea Dittadi, Frederik Träuble, Francesco Locatello, Manuel Wuthrich, Vaibhav Agrawal, Ole Winther, Stefan Bauer, and Bernhard Schölkopf. On the transfer of disentangled representations in realistic settings. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=8VXvj1QNRl1.

Cian Eastwood and Christopher K. I. Williams. A framework for the quantitative evaluation of disentangled representations. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=By-7dz-AZ.

Patrick Esser, Ekaterina Sutter, and Björn Ommer. A variational u-net for conditional appearance and shape generation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Christina M Funke, Paul Vicol, Kuan-Chieh Wang, Matthias Kuemmerer, Richard Zemel, and Matthias Bethge. Disentanglement and generalization under correlation shifts. In *ICLR2022 Workshop on the Elements of Reasoning: Objects, Structure and Causality*, 2022. URL https://openreview.net/forum?id=H8QVUSuIqgq.

Muhammad Waleed Gondal, Manuel Wuthrich, Djordje Miladinovic, Francesco Locatello, Martin Breidt, Valentin Volchkov, Joel Akpo, Olivier Bachem, Bernhard Schölkopf, and Stefan Bauer. On the transfer of inductive bias from simulation to the real world: a new disentanglement dataset. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/d97d404b6119214e4a7018391195240a-Paper.pdf.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-VAE: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Sy2fzU9gl.

Irina Higgins, David Amos, David Pfau, Sébastien Racanière, Loïc Matthey, Danilo J. Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *CoRR*, abs/1812.02230, 2018. URL http://arxiv.org/abs/1812.02230.

Daniella Horan, Eitan Richardson, and Yair Weiss. When is unsupervised disentanglement possible? In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 5150–5161. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/file/29586cb449c90e249f1f09a0a4ee245a-Paper.pdf.

D.P. Huttenlocher, G.A. Klanderman, and W.J. Rucklidge. Comparing images using the hausdorff distance. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 15(9):850–863, 1993. doi: 10.1109/34.232073.

Aapo Hyvärinen and Petteri Pajunen. Nonlinear independent component analysis: Existence and uniqueness results. *Neural Netw.*, 12(3):429–439, apr 1999. ISSN 0893-6080. doi: 10.1016/S0893-6080(98)00140-3. URL https://doi.org/10.1016/S0893-6080(98)00140-3.

Ilyes Khemakhem, Diederik Kingma, Ricardo Monti, and Aapo Hyvarinen. Variational autoencoders and nonlinear ica: A unifying framework. In Silvia Chiappa and Roberto Calandra (eds.), *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pp. 2207–2217. PMLR, 26–28 Aug 2020. URL https://proceedings.mlr.press/v108/khemakhem20a.html.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 2649–2658. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/kim18b.html.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In Yoshua Bengio and Yann LeCun (eds.), *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL http://arxiv.org/abs/1312.6114.

David A. Klindt, Lukas Schott, Yash Sharma, Ivan Ustyuzhaninov, Wieland Brendel, Matthias Bethge, and Dylan Paiton. Towards nonlinear disentanglement in natural data with temporal sparse coding. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=EbIDjBynYJ8.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, Tony Lee, Etienne David, Ian Stavness, Wei Guo, Berton Earnshaw, Imran Haque, Sara M Beery, Jure Leskovec, Anshul Kundaje, Emma Pierson, Sergey Levine, Chelsea Finn, and Percy Liang. Wilds: A benchmark of in-the-wild distribution shifts. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5637–5664. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/koh21a.html.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. VARIATIONAL INFERENCE OF DISENTANGLED LATENT CONCEPTS FROM UNLABELED OBSERVATIONS. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=H1kG7GZAW.

Yann LeCun, Fu Jie Huang, and Léon Bottou. Learning methods for generic object recognition with invariance to pose and lighting. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 2:II97–II104, 2004. ISSN 1063-6919. Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, CVPR 2004 ; Conference date: 27-06-2004 Through 02-07-2004.

Zhiyuan Li, Jaideep Vitthal Murkute, Prashnna Kumar Gyawali, and Linwei Wang. Progressive learning and disentanglement of hierarchical representations. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SJxpsxrYPS.

Francesco Locatello, Gabriele Abbati, Thomas Rainforth, Stefan Bauer, Bernhard Schölkopf, and Olivier Bachem. On the fairness of disentangled representations. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019a. URL https://proceedings.neurips.cc/paper/2019/file/1b486d7a5189ebe8d8c46afc64b0d1b4-Paper.pdf.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 4114–4124. PMLR, 09–15 Jun 2019b. URL https://proceedings.mlr.press/v97/locatello19a.html.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Rätsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. A sober look at the unsupervised learning of disentangled representations and their evaluation. *J. Mach. Learn. Res.*, 21(1), jan 2020a. ISSN 1532-4435.

Francesco Locatello, Ben Poole, Gunnar Raetsch, Bernhard Schölkopf, Olivier Bachem, and Michael Tschannen. Weakly-supervised disentanglement without compromises. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6348–6359. PMLR, 13–18 Jul 2020b. URL https://proceedings.mlr.press/v119/locatello20a.html.

Massimiliano Mancini, Muhammad Ferjad Naeem, Yongqin Xian, and Zeynep Akata. Open world compositional zero-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5222–5230, June 2021.

Timo Milbich, Karsten Roth, Homanga Bharadhwaj, Samarth Sinha, Yoshua Bengio, Björn Ommer, and Joseph Paul Cohen. Diva: Diverse visual feature aggregation for deep metric learning. In *Computer Vision – ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part VIII*, pp. 590–607, Berlin, Heidelberg, 2020. Springer-Verlag. ISBN 978-3-030-58597-6. doi: 10.1007/978-3-030-58598-3_35. URL https://doi.org/10.1007/978-3-030-58598-3_35.

Timo Milbich, Karsten Roth, Samarth Sinha, Ludwig Schmidt, Marzyeh Ghassemi, and Bjorn Ommer. Characterizing generalization under out-of-distribution shifts in deep metric learning. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 25006–25018. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/file/d1f255a373a3cef72e03aa9d980c7eca-Paper.pdf.

Graziano Mita, Maurizio Filippone, and Pietro Michiardi. An identifiable double vae for disentangled representations, 2020. URL https://arxiv.org/abs/2010.09360.

Milton L. Montero, Jeffrey S. Bowers, Rui Ponte Costa, Casimir J. H. Ludwig, and Gaurav Malhotra. Lost in latent space: Disentangled models and the challenge of combinatorial generalisation, 2022. URL https://arxiv.org/abs/2204.02283.

Milton Llera Montero, Casimir JH Ludwig, Rui Ponte Costa, Gaurav Malhotra, and Jeffrey Bowers. The role of disentanglement in generalisation. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=qbH974jKUVy.

Andrew.Y. Ng. Feature selection, l1 vs. l2 regularization, and rotational invariance. In *Proceedings of the twenty-first international conference on Machine learning*, 2004.

Michael Niemeyer and Andreas Geiger. Giraffe: Representing scenes as compositional generative neural feature fields. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 11453–11464, June 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of Causal Inference: Foundations and Learning Algorithms*. Adaptive Computation and Machine Learning. MIT Press, Cambridge, MA, 2017. ISBN 978-0-262-03731-0. URL https://mitpress.mit.edu/books/elements-causal-inference.

Joaquin Quinonero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D. Lawrence. *Dataset shift in machine learning*. 2009. ISBN 9780262170055. URL http://dl.acm.org/citation.cfm?id=1462129.

Scott E Reed, Yi Zhang, Yuting Zhang, and Honglak Lee. Deep visual analogy-making. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015. URL https://proceedings.neurips.cc/paper/2015/file/e07413354875be01a996dc560274708e-Paper.pdf.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *Proceedings of The 30th International Conference on Machine Learning (ICML)*, 2014.

Karl Ridgeway and Michael C Mozer. Learning deep disentangled embeddings with the f-statistic loss. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/2b24d495052a8ce66358eb576b8912c8-Paper.pdf.

R. Tyrrell Rockafellar and Roger J.-B. Wets. *Variational Analysis*, volume 317 of *Grundlehren der mathematischen Wissenschaften*. Springer, 1998. ISBN 978-3-540-62772-2. doi: 10.1007/978-3-642-02431-3. URL https://doi.org/10.1007/978-3-642-02431-3.

Michal Rolinek, Dominik Zietlow, and Georg Martius. Variational autoencoders pursue pca directions (by accident). In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Raphael Suter, Djordje Miladinovic, Bernhard Schölkopf, and Stefan Bauer. Robustly disentangled causal mechanisms: Validating deep representations for interventional robustness. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6056–6065. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/suter19a.html.

Frederik Träuble, Elliot Creager, Niki Kilbertus, Francesco Locatello, Andrea Dittadi, Anirudh Goyal, Bernhard Schölkopf, and Stefan Bauer. On disentangled representations learned from correlated data. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 10401–10412. PMLR, 18–24 Jul 2021. URL https://proceedings.mlr.press/v139/trauble21a.html.

Michael Tschannen, Olivier Bachem, and Mario Lucic. Recent advances in autoencoder-based representation learning. *ArXiv*, abs/1812.05069, 2018.

A   ALTERNATE HAUSDORFF VARIANTS

In this section, we introduce various variants to our Hausdorff distance approximation introduced in §2.3 and particularly Eq. 5, which we then experimentally evaluate in §B.

A.1   AVERAGED HAUSDORFF

First, due to the sensitivity to outliers, one can also utilize the average Hausdorff distance, which simply gives:

$$\hat{d}_{H,avg}^{(2)}(\mathbf{Z}) = \sum_{i=1}^{k} \sum_{j=i+1}^{k} \frac{1}{|\mathbf{Z}_{:,i} \times \mathbf{Z}_{:,j}|} \sum_{\mathbf{z} \in \mathbf{Z}_{:,i} \times \mathbf{Z}_{:,j}} \left[\min_{\mathbf{z}' \in \mathbf{Z}_{:,(i,j)}} d(\mathbf{z}, \mathbf{z}') \right] \tag{9}$$

using the same pair-based approximation introduced in Eq. 5.

A.2   SUBSAMPLING

One can also operate on the full approximated $\hat{\mathcal{S}}^{\times}$ with $\mathcal{S}^{\times} \approx \hat{\mathcal{S}}^{\times} = \mathbf{Z}_{:,1} \times \mathbf{Z}_{:,2} \times ... \times \mathbf{Z}_{:,k}$ instead of a collection of $\hat{\mathcal{S}}_{i,j}^{\times} = \mathbf{Z}_{:,i} \times \mathbf{Z}_{:,j}$, by simply utilising a randomly subsampled version of $\hat{\mathcal{S}}^{\times}$, denoted $\hat{\mathcal{S}}_{\text{sub}}^{\times}$ (through i.i.d. stitching of latent entries sampled from each dimension support):

$$\hat{d}_{H,\text{sub}} = \max_{\mathbf{z} \in \hat{\mathcal{S}}_{\text{sub}}^{\times}} \left[\min_{\mathbf{z}' \in \mathbf{Z}} d(\mathbf{z}, \mathbf{z}') \right] \tag{10}$$

However, in practice (as shown in §B), we found $\hat{d}_{H}^{(2)}$ to work better, as the max-operation over a collection of 2D subspaces provides a less sparse training signal than a single backpropagated distance pair in $\hat{d}_{H,\text{sub}}$.

A.3   SAMPLING-BASED SOFTMIN

In addition, as the latent representations and the corresponding support change during training, one can also encourage some degree of exploration during training instead of relying on the use of hard max and min operations, for example through a probabilistic selection of the final distance to minimize for, allowing for a controllable degree of exploration during training:

$$\hat{d}_{H,\text{prob}}^{(2)} = \sum_{i=1}^{k} \sum_{j=i+1}^{k} \max_{\mathbf{z} \in \hat{\mathcal{S}}^{\times}(Z)} \left[\mathbb{E}_{\mathbf{z}' \sim p_{\text{softmin}}(\cdot | \mathbf{z}, \mathbf{Z}_{:,(i,j)}, \tau)} \left[d(\mathbf{z}, \mathbf{z}') \right] \right] \tag{11}$$

with the SoftMin-distribution

$$p_{\text{softmin}}(\mathbf{z}' | \mathbf{z}, \mathbf{Z}, \tau) = \frac{\exp(-d(\mathbf{z}, \mathbf{z}')/\tau)}{\sum_{\mathbf{z}^* \in \mathbf{Z}} \exp(-d(\mathbf{z}, \mathbf{z}^*)/\tau)} \tag{12}$$

though as shown in the following experimental section, we found minimal benefits in doing so.

A.4   SOFTENED HAUSDORFF DISTANCE

To potentially better align the Hausdorff distance objective with the differentiable optimization process, it may make be beneficial to look into soft variants to relax the hard minimization and maximization, respectively (note the $\tilde{d}$ instead of $\hat{d}$):

$$
\begin{aligned}
\sigma_{\min}(\mathbf{z}, \mathbf{z}', \mathbf{Z}) &= \frac{\exp(-d(\mathbf{z}, \mathbf{z}')/\tau_1)}{\sum_{\mathbf{z}^* \in \mathbf{Z}} \exp(-d(\mathbf{z}, \mathbf{z}^*)/\tau_1)} \\
d_{\min}^{\text{soft}}(\mathbf{z}, \mathbf{Z}) &= \sum_{\mathbf{z}' \in \mathbf{Z}} \sigma_{\min}(\mathbf{z}, \mathbf{z}', \mathbf{Z}) \, d(\mathbf{z}, \mathbf{z}') \\
\tilde{d}_{H}^{(2)}(\mathbf{Z}) &= \sum_{i=1}^{k} \sum_{j=i+1}^{k} \sum_{\mathbf{z} \in \mathbf{Z}_{:,(i,j)}} \frac{\exp(d_{\min}^{\text{soft}}(\mathbf{z}, \mathbf{Z}_{:,(i,j)})/\tau_2)}{\sum_{\mathbf{z}^* \in \mathbf{Z}_{:,(i,j)}} \exp(d_{\min}^{\text{soft}}(\mathbf{z}^*, \mathbf{Z}_{:,(i,j)})/\tau_2)} d_{\min}^{\text{soft}}(\mathbf{z}, \mathbf{Z}_{:,(i,j)})
\end{aligned}
\tag{13}
$$

Table 2: Method ablations to $\hat{d}_H^{(2)}$. We compare our default pairwise Hausdorff approximation against a variant using averaging instead of $\max$ ($\hat{d}_{H,avg}^{(2)}$), a probabilistic approximation to $\min$ ($\hat{d}_{H,prob}^{(2)}$) as well as subsampling of the full-dimensional factorized support without any pairwise approximations. In all cases, entries are selected with at least 5 seeds and optimal values chosen from a gridsearch over $\gamma \in \{1, 3, 10, 30, 100, 300, 1000, 3000, 10000\}$.

Setup ↓	No Correlation	Correlated Pairs: 1	Correlated Pairs: 3
$\hat{d}_H^{(2)}$	76.9 [74.3, 81.4]	55.9 [47.6, 59.9]	48.0 [39.1, 48.9]
$\hat{d}_{H,avg}^{(2)}$ (Eq. 9)	61.1 [55.6, 65.5]	33.5 [26.9, 36.0]	42.4 [38.9, 46.3]
$\hat{d}_{H,prob}^{(2)}$ (Eq. 11)	74.7 [69.5, 77.4]	56.2 [46.0, 60.4]	46.9 [37.7, 48.0]
$\hat{d}_H^{sub}$ (Eq. 10), Subs. 80	56.4 [52.6, 61.7]	38.1 [21.2, 42.9]	29.7 [19.7, 32.0]
$\hat{d}_H^{sub}$ (Eq. 10), Subs. 800	60.0 [55.0, 62.8]	44.5 [25.7, 48.0]	31.6 [24.4, 34.1]
$\hat{d}_H^{sub}$ (Eq. 10), Subs. $8 \cdot 10^3$	62.2 [59.5, 69.3]	52.1 [48.8, 54.7]	32.1 [27.0, 33.1]
$\hat{d}_H^{sub}$ (Eq. 10), Subs. $8 \cdot 10^4$	66.9 [61.3, 71.2]	54.5 [49.3, 59.7]	39.2 [31.9, 43.8]
$\hat{d}_H^{sub}$ (Eq. 10), Subs. $8 \cdot 10^5$	66.6 [62.2, 72.4]	56.8 [50.1, 59.4]	40.9 [37.3, 45.2]

Figure 5: Results for our soft approximation to Eq. 5. Blue horizontal line denotes the default Eq. 5 objective, while orange denotes a replaced of the $\max$-operation with a mean. We find that generally, a convergence of the soft approach to our default hard variant performs best, with large choices in the outer temperature converging towards our mean approximation.

Here, the temperature τ_1 controls the translation between putting more weight on the minimal distance (smaller τ_1) versus a more uniform distribution (larger τ_1), moving further away from the corresponding $\min$ operation.

A secondary τ_2 then controls the transition between the $\max$-operation over our soft distances and a more uniform weighting over all (non-zero) soft distances, with the limit case $\tau_2 \to \infty$ approximating the simple mean over soft distances.

B   EVALUATION OF HAUSDORFF DISTANCE APPROXIMATION VARIANTS

As our utilized distance function $\hat{d}_H^{(2)}$ only approximates the Hausdorff distance to the factorized support, we now move to a variant study of other alternative distance measures as described above.

In particular, we investigate **(1)** a replacement of the $\max$-operation with a corresponding mean over support samples to address potential outliers better, **(2)** a probabilistic approximation to our $\min$-operation over $d(\mathbf{z}, \mathbf{z}')$ (see Eq. 11), **(3)** and a fully soft approximation to both $\max$ and $\min$ using a respective *Softmax* and *Softmin* formulation (A.4). **(4)** Finally, we also revisit the impact of exlicit scale regularization as introduced in §2.3.

Method ablation.   Ablation studies across the default as well as two different training correlation settings can be found in Tab. 2, with each entry computed over at least 6 seeds, and a gridsearch over $\gamma \in \{1, 3, 10, 30, 100, 300, 1000, 3000, 10000\}$. Our results show that for optimization purposes, approximating the Hausdorff distances in a "sliced", pairwise fashion as suggested in Eq. 5 is noticeably better than subsampling from the incredibly high-dimensional factorized support, as instead of a single distance entry that is optimized for (after the $\max$-$\min$ selection), we have vari-

Table 3: Impact of the number of 2D approximations in $\hat{d}_H^{(2)}$. Our experiments reveal that the use of multiple 2D approximations to the full Hausdorff distances has notable merits up to a certain degree (change in disentanglement performance from e.g. 64% to 75% in the uncorrelated transfer setting). Each entry was chosen as the highest value in a gridsearch over $\gamma \in \{0.01, 0.1, 1, 10, 100\}$.

Correlation ↓	Num. Pairs: 1	Num. Pairs: 2	Num. Pairs: 5	Num. Pairs: 15	Num. Pairs: 25	Num. Pairs: 35	Num. Pairs: 45
No Correlation	64.0 [58.5, 68.7]	66.3 [63.8, 72.6]	67.9 [66.2, 69.5]	76.6 [63.7, 79.5]	74.1 [73.8, 77.6]	75.5 [72.4, 79.9]	74.5 [71.0, 76.0]
Correlated Pairs: 1	26.3 [21.0, 29.6]	25.0 [23.9, 35.4]	28.7 [24.5, 45.6]	54.2 [44.2, 67.0]	51.4 [42.5, 58.3]	53.6 [48.3, 57.9]	53.5 [51.0, 59.1]
Correlated Pairs: 3	40.9 [38.5, 44.3]	44.3 [41.3, 48.0]	46.8 [44.9, 48.9]	46.5 [45.7, 47.3]	48.7 [47.8, 50.2]	48.8 [46.8, 52.0]	49.2 [45.6, 51.8]

Table 4: Impact of scale regularization (as detailed in §C) using VAE + $\hat{d}_H^{(2)}$ with $\gamma = 100$. For each setting, we perform a gridsearch over either the weight scale $\delta \in \{0, 1, 3, 10, 30, 100, 300, 1000, 3000, 10000\}$ or the L2 Regularization weight $\in \{10^{-6}, 10^{-5}, 10^{-4}, 10^{-3}, 10^{-2}, 10^{-1}\}$. Results show that scale regularization, while not necessarily detrimental, does not provide any consistent benefits.

Setup ↓ Correlation →	No Correlation	Correlated Pairs: 1	Correlated Pairs: 3
Baseline	74.1 [73.8, 77.6]	51.4 [42.5, 58.3]	48.7 [47.8, 50.2]
Variance	72.4 [65.4, 76.1]	54.4 [53.0, 55.6]	50.1 [49.2, 53.3]
Min. Range	75.0 [67.5, 78.5]	50.6 [38.7, 55.2]	51.5 [44.2, 53.3]
L2 Decoder	73.4 [70.1, 78.2]	56.3 [51.4, 60.0]	52.9 [44.3, 52.2]

ous latent subsets that incur a training gradient, and in two dimensions can cheaply compute the full factorized support.

Similarly, we also find that replacing the min-selection over latent entries with a probabilistic variant, as well as the max-selection over factorized support elements, offer no notable benefits. In particular the replacement of the outer max-operation can severely impact the disentanglement performance.

These insights are additionally supported when utilizing a soft variant (see Eq. A.4 in the appendix), which replaces both max and min operations with a respective Softmax and Softmin operation, each with respective temperatures τ_1 and τ_2. When utilizing this objective, we see that small temperature choices on both soft approximations are beneficial, and approximate the hard variant. Similarly, we find a consistent drop in performance when either one of these temperatures is reduced, with the soft performance converging towards the Mean variant when increasing the outer temperature τ_2. Overall, we don't see any major benefits in a soft approximation, while also introducing two additional hyperparameters that would need to be optimized.

Finally, we ablate the key parameter for our Hausdorff distance approximation of choice, $\hat{d}_H^{(2)}$ (Eq. 5 - the number of pairs over which we compute a sliced 2D variant. Given a total latent dimensionality k, we are given $\binom{k}{2}$ usable combinations, which we can choose to subsample all the way down to a single pair of latent entries, which is what we do in Tab. 3. The results showcase that while a minimal number of latent pairs is crucial, not all combinations are needed, with diminishing returns for more pairs included. For practical purposes, we therefore choose 25 pairs as our default setting to strike a balance between performance and compute cost, which however can be easily increased if needed. On the latter note, we also highlight that while the addition of $\mathcal{L}_{\mathrm{HFS}}$ does incur a higher epoch training time (60s for a standard VAE as used in Locatello et al. (2020b) on a NVIDIA Quadro GV100) than β-VAE (52s), it still compares favourably when compared to e.g. β-TCVAE (70s) or FactorVAE (96s). In addition, the impact on the training time diminishes when larger backbone networks are utilized.

C REGULARIZING SCALE TO AVOID COLLAPSE

In the limit case, the standard Hausdorff matching problem is solved by collapsing all representations into a singular point. In addition to that, the actual scale of the latent entries directly impacts the distance scale. One can therefore provide additional regularization on top to ensure both a scale-invariant measure as well as work against a potential collapse, for example by enforcing a minimal

standard deviation ρ on each factor[3]

$$\mathcal{L}_{\text{scale}} = \sum_{i=1}^{d} \max\left[0, 1 - \sqrt{\text{Var}\left[\mathbf{z}_{:,i}\right]}\right] \tag{14}$$

or simply enforcing a minimal range $[a, b]$ of the support:

$$\mathcal{L}_{\text{scale}} = \sum_{i=1}^{d} \max\left[0, b - \max(\mathbf{z}_{:,i})\right] + \max\left[0, \min(\mathbf{z}_{:,i}) - a\right] \tag{15}$$

In real setups however, we have found regularization of scale to not be necessary in the majority of cases, as the use of the additional autoencoding term alongside the Hausdorff Support Factorization is sufficient to avoid collapse (see part in §2.3 on collapse), as shown in Tab. 4. For Tab. 4, we also investigate what happens if we apply L2 regularization on the decoder.

In all cases, we perform a grid-search over an additional scale regularization weight parameter δ (with $\delta \in \{0, 1, 3, 10, 30, 100, 300, 1000, 3000, 10000\}$) or the L2 Regularization weight ($\in \{10^{-6}, 10^{-5}, 10^{-4}, 10^{-3}, 10^{-2}, 10^{-1}\}$). Our results show no improvements that are both significant and consistent across correlation settings. And while these regularization may become relevant for future variants and extensions, in this work we choose to forego a scale regularizer with the benefits of having one less hyperparameter to tune for.

Figure 6: Robustness to factorized support weighting γ - much less detrimental to overall training dynamics.

D   HYPERPARAMETER EVALUATION

To understand to what extent the factorization of support parameter γ impacts the learning and performance of the model, we also compare grid searches over γ and the standard β-VAE prior matching weight β. The results in Fig. 6 indicate that a factorization of support is much less dependent on the exact choice of weighting γ as opposed to the standard KL-Divergence to the normal prior used in β-VAE frameworks (notice the logarithmic value grid). This stands to reason, as a factorization of the support instead of distributions is both a more realistic property as well as a much weaker constraint on the overall training dynamics.

E   SAMPLE RECONSTRUCTIONS AND QUALITATIVE EVALUATION

We also provide some qualitative impression of the impact an explicit factorization has on the overall disentanglement across different correlations. In particular, Figure 7 visuals latent traversals both for the β-VAE baseline (top)as well as the HFS-augmented variant (bottom) for the latent entry most expressive for the first mentioned latent entry in ("Correlations addressed"). To generate these figures, we select the best performing seed for each setup, and report the respective DCI-D score within each subplot. As can be seen, beyond the increase in maximally achievable DCI-D, an explicit factorization of the support helps the disentangling method separate factors it initially struggled with - both when correlations exists in the training data as well as for generally failure modes when the β-VAE fails to fully disentangle in the uncorrelated setting.

---

[3]Though this enforces an implicit assumption on the density within each latent factor.

Figure 7: Sample traversals for the Shapes3D benchmark Kim & Mnih (2018) in latent space for latent entry most closely associated with various ground truth factors of variations across different correlation shifts. In all cases, the best seed (out of 10) was selected to perform these qualitative studies. Each image also reports the associated overall DCI-D score of each respective best seed for β-VAE and β-VAE + HFS.

Method	No Corr.	Pair: 1 [V1, σ = 0.1]	Pair: 1 [V3, σ = 0.1]	Pair: 1 [V4, σ = 0.1]	Pair: 1 [V4-inv, σ = 0.1]	Pair: 1 [V1, σ = 0.4]	Pairs: 2 [V2, σ = 0.4]	Pairs: 2 [V1, σ = 0.1]	Pairs: 2 [V2, σ = 0.1]	Pairs: 2 [V3, σ = 0.1]	Pairs: 2 [V3-inv, σ = 0.1]	Pairs: 3 [V1, σ = 0.1]	Pairs: 3 [V2, σ = 0.1]	Pairs: 3 [V3-inv, σ = 0.1]	Conf. [V1, σ = 0.2]	Conf. [V2, σ = 0.2]
β-VAE	70.7 [65.2, 75.4]	55.9 [53.8, 59.0]	71.6 [60.9, 72.5]	66.1 [62.8, 67.0]	64.8 [62.0, 66.4]	64.5 [62.6, 66.1]	68.5 [56.8, 76.9]	71.5 [68.1, 75.1]	58.7 [57.1, 62.9]	55.6 [45.8, 57.2]	60.2 [54.8, 61.6]	55.5 [52.8, 56.2]	37.1 [32.3, 38.9]	40.0 [33.8, 47.5]	46.8 [42.0, 50.7]	38.0 [35.0, 38.6]
HFS	78.3 [75.3, 83.6]	56.4 [46.6, 60.2]	77.8 [74.4, 78.8]	68.1 [61.2, 69.4]	71.0 [65.8, 73.6]	69.6 [68.2, 71.0]	73.9 [65.5, 80.0]	76.7 [69.7, 81.2]	62.6 [61.2, 64.3]	56.0 [41.0, 57.4]	64.4 [62.3, 65.3]	61.5 [55.8, 62.6]	47.5 [38.0, 49.1]	41.1 [31.7, 42.7]	51.3 [46.2, 52.5]	46.2 [36.7, 47.5]
β-VAE + HFS	91.2 [75.8, 100.0]	67.3 [39.5, 72.3]	80.9 [76.4, 81.4]	76.1 [72.2, 79.5]	75.8 [67.1, 78.9]	74.0 [71.8, 78.9]	89.1 [78.2, 98.5]	83.3 [79.0, 86.5]	65.5 [62.0, 66.6]	67.6 [62.4, 69.3]	65.8 [63.2, 68.4]	63.8 [57.7, 65.4]	47.9 [44.0, 59.8]	52.0 [48.7, 54.5]	59.7 [58.6, 62.1]	63.5 [61.2, 65.5]
β-TCVAE	77.1 [76.6, 78.3]	62.0 [56.6, 64.5]	71.1 [65.5, 72.5]	69.8 [67.3, 70.8]	63.2 [61.7, 66.6]	66.4 [65.1, 66.7]	75.8 [73.0, 79.1]	75.2 [69.0, 75.9]	65.7 [62.9, 70.0]	63.8 [59.1, 65.1]	60.1 [53.6, 62.7]	54.3 [50.8, 54.8]	47.3 [36.7, 50.0]	58.1 [56.2, 61.1]	55.9 [52.7, 59.9]	49.9 [45.8, 55.9]
FactorVAE	66.1 [51.2, 69.1]	52.2 [44.7, 54.8]	70.8 [70.5, 71.2]	65.9 [64.2, 67.8]	64.6 [63.7, 64.8]	63.5 [61.9, 64.4]	70.2 [64.8, 75.0]	71.2 [63.0, 77.7]	62.0 [60.7, 64.5]	57.2 [55.9, 62.0]	60.3 [52.9, 60.9]	56.8 [53.3, 57.6]	46.8 [40.8, 49.0]	40.2 [35.2, 44.6]	39.2 [34.2, 47.8]	31.6 [27.9, 35.1]
AnnealedVAE	62.2 [60.7, 63.2]	39.6 [29.6, 41.6]	57.2 [49.5, 59.3]	56.3 [53.0, 57.2]	58.0 [49.9, 60.7]	58.9 [37.6, 61.2]	60.4 [59.3, 64.9]	48.5 [39.7, 49.1]	50.9 [46.0, 52.9]	31.6 [26.9, 34.1]	50.7 [48.5, 53.4]	51.3 [49.5, 52.3]	33.6 [31.0, 38.0]	30.2 [27.1, 30.8]	26.2 [22.0, 26.8]	23.0 [20.1, 25.9]

(a) Shapes3D

Method	No Corr.	Pair: 1 [V1, σ = 0.1]	Pair: 1 [V2, σ = 0.1]	Pair: 1 [V3, σ = 0.1]	Pairs: 2 [V1, σ = 0.4]	Pairs: 2 [V2, σ = 0.4]	Pairs: 2 [V1, σ = 0.1]	Pairs: 2 [V2, σ = 0.1]	Pairs: 3 [V1, σ = 0.1]	Pairs: 3 [V2, σ = 0.1]	Conf. [V1, σ = 0.2]	Conf. [V2, σ = 0.2]
β-VAE	25.6 [24.7, 26.1]	15.7 [13.9, 17.0]	20.5 [17.7, 20.9]	23.5 [22.5, 24.4]	23.6 [21.3, 24.7]	24.8 [24.5, 25.9]	21.2 [19.5, 21.7]	23.6 [22.6, 24.3]	11.6 [11.1, 11.7]	11.1 [10.9, 11.3]	15.1 [14.5, 15.8]	11.8 [10.0, 12.7]
HFS	32.8 [30.0, 34.3]	20.7 [19.5, 21.2]	28.4 [26.5, 29.5]	26.9 [24.7, 28.0]	30.1 [29.7, 31.0]	30.2 [29.5, 30.5]	25.6 [24.0, 26.2]	28.0 [27.4, 28.2]	14.3 [13.1, 14.8]	19.0 [17.8, 19.3]	18.9 [14.4, 19.2]	16.1 [15.0, 16.6]
β-VAE + HFS	32.8 [30.0, 34.3]	20.7 [19.5, 21.2]	28.4 [26.5, 29.5]	26.9 [24.7, 28.0]	30.1 [29.7, 31.0]	30.2 [29.5, 30.5]	25.6 [24.0, 26.2]	28.0 [27.4, 28.2]	14.3 [13.1, 14.8]	19.0 [17.8, 19.3]	18.9 [14.4, 19.2]	16.1 [15.0, 16.6]
β-TCVAE	26.6 [26.0, 27.4]	21.6 [20.4, 23.8]	20.7 [20.4, 21.3]	23.7 [23.5, 24.2]	25.6 [25.1, 25.9]	25.6 [25.4, 26.2]	21.6 [19.9, 23.2]	23.3 [21.9, 23.8]	11.4 [10.3, 12.6]	16.5 [15.4, 18.2]	16.7 [16.0, 17.1]	14.2 [13.4, 15.4]
FactorVAE	26.0 [24.8, 27.5]	20.1 [15.5, 22.7]	21.9 [20.1, 23.9]	24.6 [23.8, 26.2]	25.0 [24.0, 25.9]	27.8 [27.2, 29.2]	21.9 [18.6, 24.0]	21.6 [17.6, 24.4]	10.9 [10.7, 11.9]	15.4 [14.8, 16.4]	15.5 [15.0, 16.5]	13.6 [12.8, 13.9]
AnnealedVAE	11.8 [10.8, 12.4]	10.8 [9.6, 11.9]	11.7 [10.4, 12.9]	10.6 [10.3, 11.9]	12.9 [11.0, 14.8]	11.8 [11.6, 12.1]	10.8 [9.8, 11.6]	12.5 [10.1, 13.5]	11.6 [10.6, 12.2]	10.1 [9.8, 11.0]	13.3 [11.4, 13.8]	13.4 [12.8, 13.9]

(b) MPI3D

Method	No Corr.	Pair: 1 [V1, σ = 0.1]	Pair: 1 [V2, σ = 0.1]	Pair: 1 [V3, σ = 0.1]	Pairs: 2 [V1, σ = 0.4]	Pairs: 2 [V1, σ = 0.1]	Pairs: 2 [V2, σ = 0.1]	Pairs: 2 [V2, σ = 0.4]	Conf. [V1, σ = 0.2]	Conf. [V2, σ = 0.2]
β-VAE	32.2 [25.3, 37.9]	17.9 [10.4, 23.0]	9.5 [7.9, 10.3]	13.5 [9.8, 16.1]	20.5 [18.7, 27.6]	7.5 [6.7, 8.3]	24.8 [11.0, 27.6]	10.0 [6.8, 12.3]	14.0 [10.4, 18.5]	11.4 [9.9, 13.9]
HFS	34.9 [27.4, 36.0]	22.7 [14.4, 25.6]	13.6 [7.6, 16.7]	23.3 [13.8, 28.4]	24.1 [13.3, 30.3]	11.9 [9.7, 13.8]	24.3 [21.7, 25.6]	11.1 [9.8, 11.3]	15.8 [5.4, 18.9]	15.1 [11.0, 16.0]
β-VAE + HFS	49.9 [30.0, 50.4]	32.9 [21.3, 39.0]	19.7 [17.0, 21.1]	37.5 [25.9, 39.1]	38.2 [21.9, 41.7]	17.3 [6.0, 19.6]	32.7 [23.1, 33.0]	14.6 [14.3, 14.9]	22.1 [17.7, 24.4]	15.8 [12.3, 16.7]
β-TCVAE	35.3 [29.5, 38.8]	35.1 [32.3, 38.4]	24.0 [23.6, 24.4]	25.0 [19.0, 30.9]	30.2 [27.9, 42.2]	11.4 [7.6, 13.6]	33.0 [24.3, 37.8]	20.7 [16.5, 21.9]	29.4 [28.7, 30.9]	20.9 [17.5, 23.6]
FactorVAE	25.7 [20.9, 30.9]	22.6 [20.8, 25.4]	15.1 [11.9, 16.3]	21.2 [19.2, 24.6]	21.2 [13.5, 22.9]	13.4 [12.4, 15.0]	23.4 [22.3, 26.1]	13.0 [6.5, 14.4]	18.3 [17.5, 19.2]	14.7 [13.5, 15.3]
AnnealedVAE	39.4 [38.7, 40.0]	40.8 [39.4, 41.3]	14.8 [14.3, 15.9]	29.0 [26.6, 29.9]	30.3 [28.3, 31.4]	8.5 [6.9, 10.3]	28.3 [27.6, 28.5]	10.1 [9.3, 10.6]	19.1 [18.2, 19.2]	14.3 [14.1, 14.5]

(c) DSprites

Table 5: Full table for Tab. 1 with detailed and extended correlation settings. To understand the exact factors correlated, please check the associated pairings from §G.

Figure 8: This figure shows adaptation behaviour across different amounts of test data for a L1-optimal linear probe (i.e. for each seed and entry, we selected the optimal L1-regularization values). Reported values show relative improvement in average ground truth factor classification performance of β-VAE + **HFS** versus standard β-VAE. As can be seen, the increased disentanglement through an explicitly factorized support gives expected improvements increasing with the severity of training correlations encountered.

F DETAILED FIGURES AND TABLES

In this section, we provide detailed variants of figures and tables utilised in the main paper.

F.1 ADDITIONAL DISENTANGLEMENT RESULTS

For Tab. 1 studying the impact of HFS both as a standalone objective and as a regularizer on disentanglement of test data across varying degrees of training correlations, we include a more detailed variant highlighting the exact splits utilised in Tab. 5, as well as additional correlation settings.

F.2 FURTHER ADAPTATIONS

Extending our adaptation experiments done in §4.3, we also investigate the average classification performance of ground truth factors of a weaker, L1-regularized linear probe in Fig. 8. Similar to

Figure 9: This is the full figure for Fig. 4, showcasing that a factorization of the support on the training data is consistently linked to improved downstream disentanglement (*top*), and that a minimization of the standard β-VAE KLD-objective for a factorial distribution implicitly minimizes for a factorized support across settings.

Figure 10: This is the detailed correlation shift transfer grid utilized in Fig. 2, indicating the exact correlation settings used for training and test data.

our transfer results, we again find that the increased disentanglement through an explicitly factorized support gives expected improvements which increasing with the severity of training correlations.

F.3 FURTHER PROGRESSIONS

Fig. 9 provides visualization of the relations between training support factorization and disentanglement performance on test data (top), as well the KL-Divergence loss in the standard β-VAE for more training correlation settings as shown in the main paper figure 4(orange and black graphs), with insights transferring from the main paper.

F.4 DETAILED CORRELATION SHIFT TRANSFER GRID

For replicability, we provide a copy of Fig. 2 with the exact utilised correlation settings in Fig. 10.

F.5 DETAILED METRIC GRID

Finally, we also provide a more detailed copy of the metric transfer grid in Fig. 4(right, blue) with the exact correlation settings investigated.

Figure 11: Correlation of Hausdorff distance to factorized support on the training data to various disentanglement metrics (in particular DCI and MIG) across correlation shifts. We find factorization of supports on the training data to strongly relate to downstream disentanglement even when experiencing strong correlation during training.

G FURTHER EXPERIMENTAL DETAILS

Study design. We implement all our experiments using the PyTorch framework Paszke et al. (2019). For exact and fair comparability, we re-implement all baseline methods based on Tensorflow implementation provided through Locatello et al. (2019b) (https://github.com/google-research/disentanglement_lib), as well as the following public repositories: https://github.com/YannDubs/disentangling-vae, https://github.com/nmichlo/disent/blob/main, https://github.com/ubisoft/ubisoft-laforge-disentanglement-metrics/blob/main/src/metrics/dci.py and https://github.com/AntixK/PyTorch-VAE.

For the implementation of the disentanglement metrics, we follow the implementation used in Locatello et al. (2019b), which for the computation of the DCI metrics leverages a gradient boosted tree from the scikit-learn package. The VAE architecture used throughout our experiments follows the one utilized in Locatello et al. (2020b), which leverages the following architecture, assuming input image sizes of $64 \times 64 \times n_c$ with n_c the number of input channels, usually 3, and a latent dimensionality of 10:

- **Encoder**: [conv(32, 4×4, stride 2) + ReLU] $\times$ 2, [conv(64, 4×4, stride 2) + ReLU] $\times$ 2, MLP(256), MLP(2 $\times$ 10)
- **Decoder**: MLP(256), [upconv(64, 4×4, stride 2) + ReLU] $\times$ 2, [upconv(32, 4×4, stride 2) + ReLU], [upconv(n_c, 4×4, stride 2) + ReLU]

The training details are as follows:

- Optimization: Batchsize = 64, Optimizer = Adam ($\beta_1 = 0.9, \beta_2 = 0.999, \epsilon = 10^{-8}$), Learning rate = 10^{-4}.
- Training: Decoder distribution = Bernoulli, Training steps = 300000

Note that FactorVAE Kim & Mnih (2018) introduces a separately trained discriminator, we we again utilize the setting described in Locatello et al. (2020b):

- Architecture: [MLP(1000), leakyReLU] x 6, MLP(2)
- Optimization: Batchsize = 64, Optimizer = Adam ($\beta_1 = 0.5, \beta_2 = 0.9, \epsilon = 10^{-8}$)

Method	Parameter	Values
β-VAE	β	[1, 2, 3, 4, 6, 8, 10, 12, 16]
β-TCVAE	β	[1, 2, 3, 4, 6, 8, 10, 12, 16]
AnnealedVAE	$c_{\max}$	[2, 5, 10, 25, 50, 75, 100, 150]
FactorVAE	β	[2, 5, 10, 25, 50, 75, 100, 150]
HFS	γ	[20, 40, 80, 100, 200, 400, 800, 1000, 2000, 4000]
β-VAE + HFS	γ	[30, 60, 100, 300, 600, 1000, 3000, 6000]

Table 6: Hyperparameter grid searches for different baseline methods as well as our factorized support objective.

Finally, we provide the hyperparameter gridsearches performed for every baseline method which mostly follow Locatello et al. (2020b), as well as for HFS (though for some ablation studies more coarse-grained grids very utilised) and β-VAE + HFS: Note that for AnnealedVAE, we also leverage an iteration threshold of 10^5 and $\gamma = 10^3$.

G.1 CORRELATION SETTINGS

We now provide more detailed information regarding the specific abbrevations used throughout the main text and for the following appendix to denote various correlation setups during training. We note that to introduce multiple correlated factors pairs, we simply multiply respective $p(c_i, c_j)$ entries.

For Shapes3D (Kim & Mnih, 2018), we introduce the following correlations:

- `No Corr.`: No Correlation during training. This constitutes the default evaluation setting.
- `Pair: 1 [V1]`: `floorCol` and `wallCol`.
- `Pair: 1 [V2]`: `objType` and `objSize`.
- `Pair: 1 [V3]`: `objType` and `wallCol`.
- `Pair: 1 [V4]`: `objType` and `objCol`.
- `Pair: 1 [inv, V4]`: `objType` and `objCol`, but inverse correlation.
- `Pairs: 2 [V1]`: `objSize` and `floorCol` as well as `objType` and `wallCol`.
- `Pairs: 2 [V2]`: `objSize` and `objType` as well as `floorCol` and `wallCol`.
- `Pairs: 2 [V3]`: `objType` and `objCol` as well as `objType` and `objSize`.
- `Pairs: 2 [inv, V3]`: `objType` and `objCol` as well as `objType` and `objSize`, but with inverse correlation.
- `Pairs: 3 [V1]`: `objSize` and `objAzimuth` as well as `objType` and `wallCol`, and `objCol` and `floorCol`.
- `Pairs: 3 [V2]`: `objCol` and `objAzimuth` as well as `objType` and `objSize`, and `wallCol` and `floorCol`.
- `Shared Conf. [V1]`: We correlate (confound) `objType` against all other factors.
- `Shared Conf. [V2]`: We correlate (confound) `wallCol` against all other factors.

For MPI3D (Gondal et al., 2019), we introduce the following correlations:

- `No Corr.`: No Correlation during training. This constitutes the default evaluation setting.
- `Pair: 1 [V1]`: `cameraHeight` and `backgroundCol`.
- `Pair: 1 [V2]`: `objCol` and `objSize`.
- `Pair: 1 [V3]`: `posX` and `posY`.
- `Pairs: 2 [V1]`: `objCol` and `objShape` as well as `posX` and `posY`.
- `Pairs: 2 [V2]`: `objCol` and `posX` as well as `objShape` and `posY`.

- `Pairs: 3 [V1]:` `objCol` and `backgroundCol` as well as `cameraHeight` and `posX`, and `objShape` and `posY`.
- `Pairs: 3 [V2]:` `objCol` and `posX` as well as `objShape` and `posY`, and `backgroundCol` and `cameraHeight`.
- `Shared Conf. [V1]:` We correlate (confound) `objShape` against all other factors.
- `Shared Conf. [V2]:` We correlate (confound) `posX` against all other factors.

For DSprites (Higgins et al., 2017), we introduce the following correlations:

- `No Corr.:` No Correlation during training. This constitutes the default evaluation setting.
- `Pair: 1 [V1]:` `shape` and `scale`.
- `Pair: 1 [V2]:` `posX` and `posY`.
- `Pair: 1 [V3]:` `shape` and `posY`.
- `Pairs: 2 [V1]:` `shape` and `scale` as well as `posX` and `posY`.
- `Pairs: 2 [V2]:` `shape` and `posX` as well as `scale` and `posY`.
- `Shared Conf. [V1]:` We correlate (confound) `shape` against all other factors.
- `Shared Conf. [V2]:` We correlate (confound) `posX` against all other factors.

H PSEUDOCODE

Finally, we provide a PyTorch-style pseudocode to quickly re-implement and apply the factorization objective following Eq. 5.

```python
1  # Inputs:
2  # * Batch of latents <z> [bs x dim]
3  # * Number of latent pairs to use for approximation <n_pairs_to_use>.
4
5  import itertools as it
6  import numpy as np
7  import torch
8
9  # Get available latent pairs.
10 pairs = np.array(list(it.combinations(range(dim), 2)))
11 n_pairs = len(pairs)
12 pairs = pairs[np.random.choice(n_pairs, n_pairs_to_use, replace=False)]
13
14 # Subsample batch <z> [bs x latent_dim] into <s_z> [bs x num_latent_pairs
       x 2]
15 s_z = z[..., pairs]
16
17 # ixs_a = [0, ..., bs-1, 0, 1, ...., bs-1]
18 ref_range = torch.arange(len(z), device=z.device)
19 ixs_a = torch.tile(ref_range, dims=(len(z),))
20 # ixs_b = [0, 0, 0, ..., 1, 1, ..., bs-1]
21 ixs_b = torch.repeat_interleave(ref_range, len(z))
22
23 # Aggregate factorized support:
24 #    For every latent pair, we select all possible batch pairwise
25 #    combinations, giving our factorized support <fact_z>:
26 #    dim(fact_z) = bs **2 x num_latent_pairs x 2
27 fact_z = torch.cat([s_z[ixs_a, :, 0:1], s_z[ixs_b, :, 1:2]], dim=-1)
28
29 # Compute distance between factorized support and 2D batch embeddings:
30 # dim(dists) = bs ** 2 x bs x num_pairs
31 dists = ((fact_z.unsqueeze(1) - s_z.unsqueeze(0)) ** 2).sum(-1)
32
33 # Compute Hausdorff distance for each pair, then sum up each pair
       contribution.
34 hfs_distance = dists.min(1)[0].max(0)[0].sum()
```

Listing 1: Sample PyTorch Implementation of $\hat{d}_H^{(2)}$ (Eq. 5)