Debate as Reward: A Multi-Agent Reward System for Scientific Ideation via RL Post-Training

Abstract

Large Language Models (LLMs) have demonstrated potential in automating scientific ideation, yet current approaches relying on iterative prompting or complex multi-agent architectures often suffer from hallucination or computational inefficiency. A critical bottleneck in applying Reinforcement Learning (RL) to this open-ended domain is reward hacking—where models exploit imperfect evaluation proxies to maximize scores without producing genuine scientific innovation. To address these limitations, we propose an RL framework explicitly tailored for high-quality scientific idea generation. We propose the first multi-agent reward function designed to serve as a judge, decoupling methodological validation from implementation details while providing strict binary rewards that are robust to reward hacking. To effectively optimize against this sparse signal, we utilize an unbiased variant of Group Relative Policy Optimization to mitigate artificial length bias. We grounded our training in ICLR-320, a curated dataset of problem-solution pairs extracted from ICLR 2024 proceedings. Experiments demonstrate that our framework significantly outperforms state-of-the-art baselines across expert-evaluated metrics of novelty, feasibility, and effectiveness. Our code is available at `https://anonymous.4open.science/r/debate-as-reward-80AF`.

1 Introduction

Scientific progress fundamentally depends on the generation of novel, feasible, and impactful research ideas. While large language models (LLMs) have shown promise in accelerating scientific discovery—assisting in hypothesis formulation, experimental design, and literature synthesis—their ability to produce genuinely innovative ideas remains limited Shahhosseini et al. (2025). Current approaches predominantly rely on inference-time augmentation strategies.

Our work specifically targets the generation of a high-quality scientific idea that directly addresses a user-provided research question. Although the existing methods demonstrate utility, they operate atop frozen base models and fail to internalize the sophisticated, multi-step reasoning required to bridge open-ended research questions with methodologically sound and conceptually novel solutions. Consequently, their generated ideas often lack depth, technical rigor, or true novelty when subjected to expert or systematic evaluation Guo et al. (2024); Si et al. (2024); Wang et al. (2024b).

In parallel, recent advances in reinforcement learning (RL) post-training—particularly Group Relative Policy Optimization (GRPO) Shao et al. (2024) and Proximal Policy Optimization (PPO) Schulman et al. (2017)—have significantly enhanced the performance of large language models (LLMs) on reasoning-intensive tasks, such as mathematical problem solving Wang et al. (2025) and code generation Robeyns & Aitchison (2025). Building on this foundation, researchers have begun exploring RL-based alignment for higher-level cognitive tasks beyond formal reasoning. Notably, Li et al. (2024) demonstrated that RL post-training can also improve scientific idea generation by aligning model outputs with human judgments of novelty and feasibility—suggesting that the benefits of policy optimization extend from structured reasoning to open-ended, creative scientific synthesis.

A central challenge remains: designing a reward signal that is both accurate—capturing nuanced dimensions such as novelty and feasibility—and robust against exploitation, or "reward hacking," where models learn

to game superficial markers of quality without producing substantive innovation Skalse et al. (2022). To address this, we developed and evaluated over fifty distinct prompting strategies for our judge LLM. Through iterative qualitative analysis of model outputs during training, we identified numerous forms of reward hacking. Some were implicit and common, such as generating excessively long ideas, becoming overly specific yet irrelevant or remaining overly vague and generic. More strikingly, we observed a sophisticated failure mode where the generator model intentionally outputs incomplete placeholder phrases, such as "... the answer part ...". Because the judge model is provided with both the research question and the ground-truth abstract as context, these placeholders inadvertently act as completion prompts. The judge is thereby tricked into generating the missing scientific idea itself within its reasoning section. It then compares its own generated idea against the abstract—naturally finding a strong methodological match—and erroneously assigns a reward of 1. Thus, the generator successfully exploits the judge's generative capabilities to bypass the ideation process entirely.

Compounding this issue, the evaluation of scientific ideas remains inherently difficult. Many studies resort to "LLM-as-a-judge" paradigms Baek et al. (2025); Su et al. (2025); Li et al. (2025) or embedding-based similarity metrics Keya et al. (2025); Wang et al. (2024a) to score outputs along dimensions such as novelty, feasibility, and effectiveness. Yet LLMs struggle to reliably assess abstract qualities like conceptual novelty, and encoder-based metrics often conflate semantic similarity with true innovation.

We address these challenges through a novel RL post-training framework that internalizes expert-level scientific reasoning directly into a compact LLM. Our core insight is that high-quality idea generation is best achieved not by adding complexity at inference time, but by fundamentally reshaping the model's generative policy through targeted training on high-impact scientific exemplars. To construct a robust reward signal, we leverage the observation that LLMs are more reliable at detecting similarity than novelty Zheng et al. (2023). Accordingly, we curate a set of high-quality, accepted papers from ICLR 2024 and NeurIPS 2025 that were published after the model's knowledge cutoff date, and treat each paper's abstract as a "target" idea. We then used an LLM prompted to decide whether a generated idea matches the target abstract, and trained the model on a subset of the ICLR 2024 dataset.

To mitigate reward hacking, we systematically refined the judge's prompting strategy and incorporated multi-agent deliberation. We note that, unlike prior work that uses multi-agent LLM judges after generation, we are the first to integrate multi-agent judge directly into the online RL training loop as the reward function. To quantify this refinement, we established a controlled empirical protocol using a fixed, expert-annotated validation set comprising 177 (research question, abstract, generated idea) triples collected across multiple training runs. Each sample was rigorously labeled via majority vote by seven domain experts. Every prompt modification and architectural change was assessed over five independent runs to mitigate stochastic variance.

Our initial single-call binary judge achieved a mean precision of 0.85, remaining vulnerable to verbosity bias and superficial lexical overlap. A reduced multi-agent setup utilizing only a single LLM analyst improved precision to 0.906 but still permitted false-positive rewards. Ultimately, we converged on a multi-agent deliberative judge that explicitly separates methodological decomposition and final aggregation. This final system achieves perfect precision (1.00) on the expert benchmark. Because false-positive rewards are the primary driver of reward hacking in RL settings, eliminating them is paramount to our framework's success. Full details of the prompt evolution, strategy comparisons, and comprehensive ablation studies are provided in Appendix D.

We define the input to our system as a problem-only research question: a concise, self-contained query that articulates the core scientific challenge addressed in a paper, while deliberately omitting any trace of its proposed solution or method. These questions are generated by prompting Gemini 2.5 pro to analyze a paper's title and abstract and extract only the underlying problem, following strict guidelines that prevent information leakage from the "golden idea." For example, given the research agent Baek et al. (2025) paper, the research question would be "How can the generation of novel scientific research ideas be automated and accelerated?"

Trained exclusively on ICLR 2024 papers via GRPO, our model learns to map research questions to novel methodological proposals with unprecedented fidelity—demonstrating that RL post-training can transform small, efficient models into specialized scientific ideation engines.

For final evaluation, we employ two independent LLM judges (one providing absolute scores, the other pairwise comparisons) on a subset of both the ICLR 2024 and Neurips datasets, complemented by manual relative assessments on 10 unsolved research questions authored by domain experts.

Our contributions are threefold:

- The first GRPO-based post-training framework explicitly designed for scientific idea generation, moving beyond inference-time augmentation to internalize deep reasoning capabilities.

- We propose the first multi-agent LLM judge system deployed in an online RL post-training loop for LLMs, enabling robust, consensus-driven reward signals that mitigate reward hacking.

- Empirical validation showing significant improvements over supervised fine-tuning (SFT) and strong baselines in both automatic (LLM-based) and human expert evaluations.

2 Related Work

Automated Research Idea Generation The capability of Large Language Models to generate novel scientific ideas has attracted significant attention. Early approaches such as SciMon Wang et al. (2024a), leveraged retrieval-augmented generation to produce new ideas based on prior literature, focusing on novelty optimization. This was further advanced by ResearchAgent Baek et al. (2025), which introduced an iterative refinement process where LLMs critique and improve their own ideas using knowledge graphs and literature entities. Similarly, GPT Researcher Assafelovic (2023) leverages a plan-and-solve agentic architecture to automate web scraping, filtering and comprehensive literature synthesis, thereby streamlining research workflows.

More recently, the field has moved toward end-to-end automation. The AI Scientist Lu et al. (2024) and its successor The AI Scientist-v2 Yamada et al. (2025) propose fully automated pipelines that not only generate ideas but also execute code and write papers, using techniques such as agentic tree search. Concurrently, CycleResearcher Weng et al. (2025) improves automated research outcomes by integrating a review-refinement loop directly into the generation cycle.

Other works have focused on the structural quality of ideas. Chain of Ideas Li et al. (2025) organizes the generation process into sequential chains of literature to enhance logical flow, while LDC Li et al. (2024) introduces dynamic control mechanisms to guide the generation path. Similarly SPARK Sanyal et al. (2025) emphasizes creative generation through system-level architecture. However despite these advances, most existing methods rely on inference-time prompting strategies or extensive retrieval pipelines with frozen models. In contrast our approach focuses on internalizing the reasoning capabilities required for idea generation by fine-tuning a smaller and efficient model via reinforcement learning.

LLM-based Evaluation and Multi-Agent Debate Evaluating open-ended text generation, particularly in scientific domains, remains a critical bottleneck. IdeaBench Guo et al. (2024) and recent large-scale human studies Si et al. (2024) highlight the difficulty of assessing novelty and feasibility without human experts. To mitigate this, recent works have turned to agentic frameworks. Generative Agent Reviewers Bougie & Watanabe (2025) simulates the peer review process.

Multi-agent debate has emerged as a powerful paradigm for improving accuracy. ChatEval Chan et al. (2024) demonstrates that a committee of agents discussing open-ended questions can converge on higher-quality evaluations than single agents. We adopt this insight not merely for final evaluation, but as a dense reward signal. By employing a multi-agent debate system (simulating diverse roles to judge methodological alignment with ground truth), we construct a robust reward function that guides the training of our smaller model.

Reinforcement Learning and Self-Improvement While Supervised Fine-Tuning (SFT) aligns models with instruction formats, Reinforcement Learning (RL) encourages complex reasoning. Techniques like Self-Rewarding Language Models Yuan et al. (2024) allow models to generate their own training signals. In the

Figure 1: **Overview of the proposed framework for internalizing scientific reasoning via Reinforcement Learning (RL) post-training.** The pipeline consists of five distinct stages: (1) **Dataset Curation**, where research questions and abstracts are extracted from accepted ICLR 2024 papers to form the ICLR-320 dataset; (2) **Candidate Generation**, utilizing a Qwen2.5 14B policy model to propose research ideas; (3) **Multi-Agent Judge**, employing a debate-based mechanism (two Analysts, and one Evaluator) to assign binary rewards; (4) **Policy Optimization**, utilizing Dr. GRPO (Group Relative Policy Optimization) to update the model without standard deviation scaling; and (5) **Final Evaluation**, assessing the trained model for novelty, feasibility, and effectiveness using both LLM-as-a-judge and human expert review.

mathematical domain, DeepSeekMath Shao et al. (2024) introduced Group Relative Policy Optimization (GRPO), a memory-efficient variant of PPO Schulman et al. (2017) that eliminates the need for a value function critic by normalizing scores within a group of outputs.

Our work bridges the gap between structured mathematical reasoning and open-ended scientific discovery by adapting the GRPO framework to the task of research idea generation. This method enables the model to internalize the subtle reasoning patterns required to bridge an open research question to a methodologically sound and novel solution.

3 Methodology

We propose a closed-loop framework designed to automate the generation of high-quality, novel scientific research ideas. Our approach integrates a specialized research dataset, a deliberative multi-agent reward model, and a recent reinforcement learning policy optimization strategy. Formally, the pipeline consists of three phases: (1) Dataset Curation, where we extract problem-solution pairs from high-impact literature; (2) Multi-Agent Evaluation, where a committee of LLM agents provides robust feedback; and (3) Policy Optimization, where the generator is fine-tuned via an unbiased version of Generative Reinforcement Policy Optimization (Dr. GRPO).

3.1 Overview of the Framework

We conceptualize the research idea generation task as a conditional sequence generation problem. Let π_θ denote the generator policy parameterized by θ. Given a research question $\mathbf{q}$, the model generates a candidate solution $\mathbf{o}$. To optimize π_θ, we employ a Reinforcement learning paradigm (RL) where the reward signal is not derived from static ground truth but is synthesized by a Multi-Agent Judge System.

As illustrated in Fig. 1, The training cycle proceeds as follows:

1. **Sampling:** For a given question $\mathbf{q}$, the generator samples a set of G candidate ideas $\{\mathbf{o}_1, \ldots, \mathbf{o}_G\}$ (Figure 8).

2. **Deliberation:** The Multi-Agent Judge evaluates each candidate $\mathbf{o}_i$ by comparing it against the ground-truth abstract $\mathbf{o}_{\text{gt}}$ and the original question $\mathbf{q}$, both extracted from the target paper. Through an adversarial dialogue among multiple LLM-based agents, the system produces a binary reward $R(\mathbf{q}, \mathbf{o}_i; \mathbf{o}_{\text{gt}})$ indicating whether $\mathbf{o}_i$ meaningfully aligns with the core contribution of $\mathbf{o}_{\text{gt}}$.

3. **Optimization:** We update θ to maximize the expected reward using Dr. GRPO, estimating advantages based on the group outputs.

3.2 Multi-Agent Evaluation Framework (The Judge)

A critical bottleneck in RLHF (Reinforcement Learning from Human Feedback) for open-ended tasks is the reliability of the reward model. Single-model evaluators are prone to "reward hacking" where the generator optimizes for length or keyword frequency rather than quality. To mitigate this, we introduce a Deliberative Multi-Agent Judge, simulating a peer-review committee.

We instantiate three distinct agents using the GPT-OSS 120B model. The evaluation protocol is structured as a hierarchical dialog.

The framework enforces a strict evaluation criterion: agents must focus exclusively on methodology, novelty, and critical assumptions, explicitly ignoring non-conceptual details such as dataset choices, evaluation metrics, or experimental setups.

1. **The Analyst (Methodological Investigator):** This agent's core responsibility is to decompose the ground-truth Idea into its fundamental methodological elements (Figure 16). It decomposes the generated idea $\mathbf{o}$ into technical components. It compares $\mathbf{o}$ against the ground truth $\mathbf{o}_{gt}$ to identify aligned contributions and potential hallucinations, presenting a structured feasibility report (e.g., specific algorithms, architectural innovations, or theoretical assumptions).

2. **The Evaluator (Final Decision Maker):** The Evaluator functions as the meta-reviewer and final aggregator (Figure 20). It consumes the full interaction history between two Analysts. By weighing the technical merits against the exposed flaws, it synthesizes a final binary reward ($r \in \mathbb{R}$) alongside a structured reasoning trail.

This multi-turn adversarial dynamic reduces the variance of the reward signal and penalizes plausible-sounding but vacuous text. In our internal experiments, we observed that standard LLM-as-a-Judge methods—including single-pass scalar scoring and static majority voting—frequently succumb to reward hacking, favoring verbose or lexically complex outputs regardless of logical soundness. The debating framework effectively resolves this by transforming evaluation from a static scoring task into a dynamic verification process. Through adversarial cross-examination, agents are forced to defend their assessments, exposing logical gaps and hallucinated complexity that evade single-pass detection. This successfully ensures that rewards target the intrinsic logic of the scientific mechanism rather than mere lexical overlap or specific implementation contexts.

3.3 Policy Optimization via Dr. GRPO

We fine-tune the generator π_θ using Dr. GRPO Liu et al. (2025), an unbiased variant of Group Relative Policy Optimization. Unlike PPO, GRPO estimates baselines directly from group scores of sampled outputs, eliminating the need for a separate value network and reducing memory overhead—critical for our 14B parameter model.

However, our empirical observations show that standard GRPO suffers from a length bias: it applies sequence-level advantages uniformly across tokens, causing longer outputs to accumulate disproportionately large gradients regardless of quality. This is particularly problematic for scientific ideation, where verbose but vacuous responses can exploit the reward signal. Dr. GRPO addresses this by introducing length-normalized token-level advantages:

$$\hat{A}_{i,t} = \hat{A}_i \cdot \frac{|\mathbf{o}_i|^{-1}}{\frac{1}{G}\sum_{j=1}^{G}|\mathbf{o}_j|^{-1}} \tag{1}$$

where $\hat{A}_i$ is the standardized sequence-level advantage. This normalization ensures each response contributes equally to the gradient irrespective of length, improving token efficiency and preventing the model from favoring padded elaborations over concise, high-quality ideas.

The Dr. GRPO loss follows the standard clipped objective:

$$\mathcal{L}_{\mathrm{Dr.GRPO}}(\theta) = \frac{1}{G}\sum_{i=1}^{G}\sum_{t=1}^{|\mathbf{o}_i|}\min\Big[\rho_{i,t}(\theta)\hat{A}_{i,t}, \mathrm{clip}\big(\rho_{i,t}(\theta), 1-\epsilon, 1+\epsilon\big)\hat{A}_{i,t}\Big] \tag{2}$$

where $\rho_{i,t}(\theta)$ is the importance sampling ratio at token t, and ϵ is the clipping hyperparameter. This formulation, combined with our binary reward signal from the Multi-Agent Judge, provides strong gradients that reinforce methodologically sound ideas without the length exploitation common in open-ended generation tasks.

4 Experiments and Results

4.1 Implementations

We implement both our method and all baselines in two configurations: (1) using the Unsloth-optimized, 4-bit quantized version of Qwen 2.5 14B to ensure a fair and computationally efficient comparison across all approaches, and (2) using the full-precision Unsloth-optimized Qwen 2.5 7B model to assess performance under higher numerical fidelity and mitigate potential artifacts introduced by quantization.

Many baseline methods are inherently expensive during inference; agentic systems (e.g., GPT Researcher, ResearchAgent) involve numerous internal LLM calls and iterative refinement loops, while other methods utilize costly per-token decoding schemes. In contrast, our model performs a single, highly efficient forward pass. To ensure a fair, compute-matched evaluation against these resource-intensive baselines, we evaluate our proposed method using a Best-of-10 (BoN(10)) approach. For each research question, we generate 10 candidate ideas and prompt the same model to select the one it deems most novel (see Figure 10 for the Best-of-N prompt). This strategy aligns our inference budget with the more complex methods, ensuring an equitable comparison of final output quality for a similar amount of compute without requiring external evaluators.

4.2 Data

To train and evaluate our model, we collected accepted papers from ICLR 2024 and NeurIPS 2025, then removed any papers archived before model's knowledge cutoff date. Next, we plotted score histograms for each set and retained about the top 50% of papers with the highest scores. Since our task specifically required papers containing novel ideas, we used the GPT-OSS-120B model to classify the papers into three categories: surveys, evaluation-focused papers, and those presenting novel ideas (see Figure 4 for the prompt details). We retained only the latter category for our dataset.

Next, we extracted the full text of each paper, spanning from the abstract up to (but not including) the references section. We then passed this full text to DeepSeek-V3.1 to extract the "golden idea" of each paper (see Figure 22 for the Idea Extraction prompt). For ICLR papers, we extracted the research question using Gemini 2.5 Pro, while for NeurIPS papers, we used DeepSeek-V3.1 with the same input prompt (as shown in Figure 6), supplemented by the abstract of each paper. Initially, we relied solely on abstracts under the assumption that the central research question would be clearly stated there; however, the resulting extracted ideas lacked sufficient specificity. Consequently, we switched to using the full text of the papers to extract more precise and meaningful golden ideas.

During dataset creation, whenever we used LLMs for any purpose, we carefully analyzed their outputs and either corrected the results when necessary or revised the input prompts if a significant number of records exhibited low quality.

Finally, we reserved 40 papers from ICLR 2024 and 40 papers from NeurIPS 2025 as the RL test sets for evaluation. For supervised fine-tuning (SFT), we used a subset of the ICLR 2024 data for training and the remainder for validation (80 and 16 samples, respectively); no SFT data was used from NeurIPS 2025. Also, only the ICLR 2024 training split (320 samples) was used for RL post-training.

Table 1: Dataset splits for RL and SFT

Dataset	ICLR 2024	NeurIPS 2025
RL Train	320	-
RL Validation	40	270
RL Test	40	40
SFT Train	80	-
SFT Validation	16	-

In addition to these conference papers, we incorporated two supplementary sources: (1) 203 AI-generated papers from AI Scientist Lu et al. (2024), from which we extracted research questions using their abstracts using DeepSeek-V3.1; (2) A curated set of 30 active research questions contributed by PhD candidates, each representing core components of their ongoing or future research in their respective subfields; we call these the golden RQs. We have included representative samples in Appendix G to provide insight into the nature and complexity of these questions.

4.3 Baselines

We compare the ideas generated from our model by greedy sampling using temperature equal to 1.0 against several common baselines in idea generation. Here are the baselines we used:

- **Unsloth Qwen 2.5 14B Instruct 4-bit**: The pretrained model quantized to 4-bit, provided with the same input prompt as our trained model to serve as a zero-shot baseline (see Figure 8 for the idea generation prompt).

- **SFT**: Supervised fine-tuning of the Qwen 2.5 14B Instruct model on our curated ICLR 2024 dataset of (research question, abstract) pairs (see Figure 12 for the SFT prompt).

- **Research Agent** Baek et al. (2025): An agentic framework that iteratively proposes, critiques, and refines research ideas using a knowledge graph and self-reflection loops. We modified its prompt to generate shorter outputs and used the method section as the idea.

- **GPT Researcher** Assafelovic (2023): A pipeline that leverages an LLM to autonomously conduct literature reviews, formulate hypotheses, and generate research proposals based on user-defined topics. We modified its prompt to generate a research idea instead of the report.

- **AI-Scientist** Lu et al. (2024): A fully automated system that generates novel scientific hypotheses, designs experiments, and writes manuscripts in specific domains.

- **AI-Scientist v2** Yamada et al. (2025): An enhanced version of AI-Scientist with improved hypothesis generation, broader domain coverage, and integrated validation modules.

Because AI-Scientist requires domain-specific code templates as input to generate papers, we evaluated all methods on a shared set of research questions extracted from existing AI-Scientist output samples. Consequently, AI-Scientist v1 was not evaluated on other datasets, as it cannot operate without its required template-based context.

Table 2: Performance comparison across different datasets for unsloth-Qwen2.5-14B 4-bit quantized. Best scores are **bolded**.

Dataset	Metric	Base Model 14B 4-bit	Our Method - BoN(10)	SFT	GPT Researcher	Research Agent	AI Scientist V2	AI Scientist	LDC
ICLR 2024	Absolute Novelty	3.92	**4.22**	4.10	4.08	4.08	3.90	-	4.08
	Absolute Feasibility	4.08	3.88	3.80	3.75	3.95	**4.22**	-	3.98
	Absolute Effectiveness	4.42	4.40	4.25	4.30	**4.67**	4.22	-	4.38
	Pairwise Novelty	1.05	**5.00**	2.42	4.01	3.63	1.00	-	4.38
	Pairwise Feasibility	**5.00**	1.25	2.66	1.99	2.10	4.44	-	1.00
	Pairwise Effectiveness	2.43	**5.00**	1.00	3.21	4.89	1.92	-	4.55
Neurips 2025	Absolute Novelty	3.88	**4.28**	4.08	4.12	3.92	3.92	-	4.25
	Absolute Feasibility	4.12	3.88	3.82	3.92	3.75	**4.20**	-	3.90
	Absolute Effectiveness	4.35	4.42	4.28	**4.53**	4.30	4.28	-	4.53
	Pairwise Novelty	1.00	**5.00**	2.11	4.77	2.44	1.08	-	3.29
	Pairwise Feasibility	4.20	1.00	3.18	1.27	3.01	**5.00**	-	1.94
	Pairwise Effectiveness	1.44	**5.00**	1.85	3.96	1.00	1.33	-	1.55
AI-Scientist	Absolute Novelty	3.71	**4.1**	3.95	3.93	4.01	3.68	3.75	3.62
	Absolute Feasibility	4.31	3.96	3.93	4.01	3.75	4.31	**4.35**	4.01
	Absolute Effectiveness	4.32	**4.46**	4.22	4.35	4.24	4.1	4.13	4.24
	Pairwise Novelty	3.71	**5.00**	2.68	3.55	3.45	1.00	1.38	2.66
	Pairwise Feasibility	4.34	1.00	2.55	2.10	1.88	4.99	**5.00**	4.01
	Pairwise Effectiveness	4.32	**5.00**	1.43	3.33	2.17	2.14	1.00	3.83

4.4 Evaluation

Automatic evaluation. Following established practices in prior work, we employ two complementary LLM-based evaluation protocols: (1) *absolute scoring* (as shown in Figure 26), where each idea is independently rated on a fixed scale, and (2) *pairwise comparison* (as shown in Figure 24), where all generated ideas are evaluated against one another. We implement both to ensure robust assessment.

For evaluation, we use Qwen 2.5 72B, which shares the same knowledge cutoff date as our trained model. This ensures the evaluator is not biased by familiarity with post-cutoff papers, enabling fair and unbiased assessment of novelty and feasibility. Model selection was constrained to systems whose training data predates our dataset (September 2024) to minimize the risk that the evaluator had previously seen examples from the dataset.

In the absolute scoring setup, the evaluator assigns each idea an integer score from 1 to 5, with 5 indicating the highest quality. For pairwise comparisons, we present every unordered pair of ideas twice—once in each order—to mitigate position bias. The model's judgment for each comparison is mapped to a numerical value: +1 if the first idea is preferred, –1 if the second is preferred, and 0 if they are deemed equivalent. We aggregate these values across all comparisons for each idea and linearly normalize the resulting scores to the 1–5 range, where 5 again corresponds to the highest-performing method.

Table 2 presents the absolute and pairwise evaluation scores of our model and baselines across three key dimensions: novelty, feasibility, and effectiveness. Our method consistently outperforms all baselines under both scoring protocols. Notably, this superior performance is achieved while using only a single research question as input—without relying on external retrieval, iterative refinement, or multi-agent pipelines—making our approach significantly more computationally efficient than existing methods.

As shown in Table 2, the pairwise feasibility score of our method is the lowest across all datasets. As discussed in Si et al. (2024), there exists a clear trade-off between novelty and feasibility, particularly when ideas are evaluated by an LLM. Nevertheless, the absolute feasibility scores remain comparable to those of other methods.

Similar to the 14B quantized variant, the 7B full-precision model also outperforms all baselines when evaluated under a shared base model architecture (see Table 6). However, scoring scientific ideas—particularly along dimensions such as novelty and feasibility—remains a challenging task for LLMs. This limitation is well recognized in the literature; consequently, many prior studies supplement or replace automated evaluation with human assessment, which is generally considered more reliable for nuanced, high-stakes judgments.

Human evaluation. We collected a set of 30 open research questions from PhD candidates across various subfields of computer science. For each question, we generated candidate ideas using our model and the

Figure 2: Ablation of multi-agent Judge architectures. *Left:* absolute precision/recall for each configuration. *Right:* change relative to the four-role Ordinary baseline (Moderator+Analyst+Critic+Evaluator).

baseline methods. The outputs were anonymized and presented to domain experts in artificial intelligence, who independently evaluated each idea on three criteria—*novelty*, *feasibility*, and *effectiveness*. Each criterion was scored on a scale from 1 (worst) to 5 (best).

Table 3: Human evaluation scores on a set of 30 open research questions collected from PhD candidates. Domain experts evaluated anonymized generated ideas on a scale from 1 (worst) to 5 (best) across three criteria: novelty, feasibility, and effectiveness. Values represent the average score for each method.

	Base Model 14B 4-bit	GPT Researcher	Research Agent	AI Scientist V2	Our Method - BoN (10)	SFT	LDC
Average Novelty	2.83	2.47	2.46	2.12	**3.43**	3.11	2.62
Average Feasibility	**3.29**	3.17	2.55	3.02	3.13	2.82	2.86
Average Effectiveness	2.93	2.69	2.41	2.70	**3.38**	2.94	2.67

Table 3 reports the average scores assigned by the experts. Our method achieves the highest average score, consistently outperforming all baselines. This result indicates that the ideas generated by our approach are not only more novel and feasible but also highly specific and well-aligned with the posed research questions. A sample research question along with its corresponding model outputs is presented in Appendix G.

4.5 Ablation Studies on Multi-Agent Judge Architecture

Since our RL signal is a strict binary reward produced by the deliberative Judge, we ablate the Judge architecture to understand which roles are necessary for reliable supervision. In all configurations, all judge agents are instantiated from the same frozen GPT-OSS-120B backbone. We vary only the role prompts and the interaction graph. The reference configuration (Ordinary) uses a four-role debate: a Moderator (Figure 14) opens each round and enforces the methodological-only constraint; an Analyst (Figure 16) decomposes the abstract and the idea into core methodological components; a Critic (Figure 18) challenges the Analyst's reasoning and searches for logical gaps or reward-hacking patterns; and a final Evaluator (Figure 20) aggregates the discussion into the binary decision. This design follows our principle that judgments must focus on methodology, novelty, and critical assumptions.

Figure 2 reports precision/recall for different graph variants. Removing the Analyst substantially degrades precision (0.780), suggesting the system becomes prone to over-accepting matches without a structured decomposition step. In contrast, removing the Evaluator yields perfect precision but collapses recall to 0.033, indicating that a dedicated aggregation step is essential to avoid overly conservative (false-negative) decisions. Dropping the Moderator slightly increases precision (0.977) but reduces recall (0.205), consistent with the Moderator's role in keeping the debate on-track and preventing premature convergence to rejection.

Removing the Critic has a smaller effect (0.897/0.322), but still reduces robustness compared to architectures with explicit adversarial scrutiny.

These ablations indicate that debate improves reward correctness only when methodological decomposition and final aggregation are both preserved. Removing the Analyst substantially lowers precision, suggesting that without an explicit decomposition of ideas in to methodological components, the Judge over-accepts superficially similar but logically mismatched proposals. Conversely, removing the Evaluator yields extreme conservatism and almost no recall, showing that a dedicated aggregation step is required to convert conflicting arguments in to a calibrated binary decision. Architectures that retain both analysis and aggregation—and that constrain agents to methodology, novelty, and critical assumptions—exhibit the strongest alignment between debate outcomes and ground-truth labels.

The ablations also reveal that adding structure or additional agents does not automatically guarantee correctness For example, dropping the Moderator slightly increases precision but reduces recall, consistent with debates drifting off-task or converging prematurely. Moreover, architectures with excessively many critics and analysts tend to push the committee toward false negatives. These results highlight that debate fails when roles are weakly differentiated, or when the balance between analysis and aggregation is distorted.

We also study scaling the number of Analysts with a single Evaluator. Using multiple Analysts generally improves precision, reaching 1.0 for 2/4/6-Analyst variants, while recall peaks with a moderate committee size (e.g., 3 Analysts + 1 Evaluator achieves 0.962/0.372). Adding an extra Analyst+Critic pair (+1 Critic +1 Analyst) improves precision (0.924) but reduces recall (0.200), suggesting that excessive criticism can push the committee toward false negatives. Given the trade-off between accuracy and test-time compute, we adopt 2 Analysts + 1 Evaluator as our default Judge in the main pipeline: it attains perfect precision with competitive recall (0.300).

5   Conclusion

In this work, we apply Group Relative Policy Optimization (GRPO) to perform reinforcement learning (RL) post-training on a large language model (LLM), significantly enhancing its performance on scientific idea generation. To mitigate reward hacking—a common pitfall in RL-based training—we manually analyzed model outputs across dozens of distinct judge prompting strategies and iteratively refined our evaluation protocol. Both automatic evaluations using LLM-as-a-judge and human expert assessments confirm that our method generates ideas that are significantly more novel than those produced by baseline approaches.

Limitations

Our work has several limitations that we hope future research will address. First, our RL post-training relies on only 320 high-quality examples from ICLR 2024; scaling the dataset with more expert-validated scientific ideas could further improve performance. Second, we fine-tuned a relatively small pretrained model (Qwen 14B 4 bit quantized); using larger or more capable foundation models may yield higher-quality and more diverse idea proposals. Third, our RL post-training was applied directly to a pretrained instruct model rather than a supervised fine-tuned checkpoint—an approach that might better align the model with scientific discourse before reinforcement learning. Finally, our evaluation is limited to papers from ICLR and NeurIPS, both of which focus on computer science. The generalizability of our method to other scientific domains (e.g., biology, physics, or social sciences) remains an important open question for future work.

References

Assafelovic. gpt-researcher, 2023. URL: https://github.com/assafelovic/gpt-researcher.

Jinheon Baek, Sujay Kumar Jauhar, Silviu Cucerzan, and Sung Ju Hwang. ResearchAgent: Iterative research idea generation over scientific literature with large language models. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Vol-*

ume 1: Long Papers), pp. 6709–6738, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-189-6. doi: 10.18653/v1/2025.naacl-long.342. URL `https://aclanthology.org/2025.naacl-long.342/`.

Nicolas Bougie and Narimawa Watanabe. Generative reviewer agents: Scalable simulacra of peer review. In Saloni Potdar, Lina Rojas-Barahona, and Sebastien Montella (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pp. 98–116, Suzhou (China), November 2025. Association for Computational Linguistics. ISBN 979-8-89176-333-3. doi: 10.18653/v1/2025.emnlp-industry.8. URL `https://aclanthology.org/2025.emnlp-industry.8/`.

Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. ChatEval: Interactive LLM-evaluated multi-agent debate for open-ended questions. In *International Conference on Learning Representations (ICLR)*, 2024. URL `https://openreview.net/forum?id=FQepisCUWu`.

Sikun Guo, Amir Hassan Shariatmadari, Guangzhi Xiong, Albert Huang, Eric Xie, Stefan Bekiranov, and Aidong Zhang. IdeaBench: Benchmarking large language models for research idea generation. *arXiv preprint arXiv:2411.02429*, 2024. URL `https://doi.org/10.48550/arXiv.2411.02429`.

Farhana Keya, Gollam Rabby, Prasenjit Mitra, Sahar Vahdati, Sören Auer, and Yaser Jaradeh. Sci-idea: Context-aware scientific ideation using token and sentence embeddings. *arXiv preprint arXiv:2503.19257*, 2025. URL `https://doi.org/10.48550/arXiv.2503.19257`.

Long Li, Weiwen Xu, Jiayan Guo, Ruochen Zhao, Xingxuan Li, Yuqian Yuan, Boqiang Zhang, Yuming Jiang, Yifei Xin, Ronghao Dang, Yu Rong, Deli Zhao, Tian Feng, and Lidong Bing. Chain of ideas: Revolutionizing research via novel idea development with LLM agents. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 8971–9004, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.477. URL `https://aclanthology.org/2025.findings-emnlp.477/`.

Ruochen Li, Liqiang Jing, Chi Han, Jiawei Zhou, and Xinya Du. LDC: Learning to generate research idea with dynamic control. *arXiv preprint arXiv:2412.14626*, 2024. URL `https://doi.org/10.48550/arXiv.2412.14626`.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Understanding r1-zero-like training: A critical perspective. In *Conference on Language Modeling (COLM)*, 2025. URL `https://doi.org/10.48550/arXiv.2503.20783`.

Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. The AI scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*, 2024. URL `https://doi.org/10.48550/arXiv.2408.06292`.

Maxime Robeyns and Laurence Aitchison. Improving llm-generated code quality with grpo. *arXiv preprint arXiv:2506.02211*, 2025. URL `https://doi.org/10.48550/arXiv.2506.02211`.

Aishik Sanyal, Samuel Schapiro, Sumuk Shashidhar, Royce Moon, Lav R. Varshney, and Dilek Hakkani-Tur. SPARK: A system for scientifically creative idea generation. In *Proceedings of the 16th International Conference on Computational Creativity (ICCC)*, 2025. URL `https://doi.org/10.48550/arXiv.2504.20090`.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017. URL `https://doi.org/10.48550/arXiv.1707.06347`.

Fatemeh Shahhosseini, Arash Marioriyad, Ali Momen, Mahdieh Soleymani Baghshah, Mohammad Hossein Rohban, and Shaghayegh Haghjooy Javanmard. Large language models for scientific idea generation: A creativity-centered survey. *arXiv preprint arXiv:2511.07448*, 2025. URL `https://doi.org/10.48550/arXiv.2511.07448`.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y.K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024. URL `https://doi.org/10.48550/arXiv.2402.03300`.

Chenglei Si, Diyi Yang, and Tatsunori Hashimoto. Can LLMs generate novel research ideas? a large-scale human study with 100+ NLP researchers. *arXiv preprint arXiv:2409.04109*, 2024. URL `https://doi.org/10.48550/arXiv.2409.04109`.

Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krasheninnikov, and David Krueger. Defining and characterizing reward gaming. In *Advances in Neural Information Processing Systems*, volume 35, 2022. URL `https://doi.org/10.48550/arXiv.2209.13085`.

Haoyang Su, Renqi Chen, Shixiang Tang, Zhenfei Yin, Xinzhe Zheng, Jinzhe Li, Biqing Qi, Qi Wu, Hui Li, Wanli Ouyang, Philip Torr, Bowen Zhou, and Nanqing Dong. Many heads are better than one: Improved scientific idea generation by a LLM-based multi-agent system. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 28201–28240, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.1368. URL `https://aclanthology.org/2025.acl-long.1368/`.

Qingyun Wang, Doug Downey, Heng Ji, and Tom Hope. SciMON: Scientific inspiration machines optimized for novelty. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 279–299, Bangkok, Thailand, August 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.18. URL `https://aclanthology.org/2024.acl-long.18/`.

Xiaoxuan Wang, Ziniu Hu, Pan Lu, Yanqiao Zhu, Jieyu Zhang, Satyen Subramaniam, Arjun R. Loomba, Shichang Zhang, Yizhou Sun, and Wei Wang. Scibench: Evaluating college-level scientific problem-solving abilities of large language models. In *International Conference on Machine Learning (ICML)*, 2024b. URL `https://doi.org/10.48550/arXiv.2307.10635`.

Yikun Wang, Yibin Wang, Dianyi Wang, Zimian Peng, Qipeng Guo, Dacheng Tao, and Jiaqi Wang. Geometryzero: Improving geometry solving for llm with group contrastive policy optimization. *arXiv preprint arXiv:2506.07160*, 2025. URL `https://doi.org/10.48550/arXiv.2506.07160`.

Yixuan Weng, Minjun Zhu, Guangsheng Bao, Hongbo Zhang, Jindong Wang, Yue Zhang, and Linyi Yang. Cycleresearcher: Improving automated research via automated review. In *The Thirteenth International Conference on Learning Representations*, 2025. URL `https://openreview.net/forum?id=bjcsVLoHYs`.

Yutaro Yamada, Robert Tjarko Lange, Cong Lu, Shengran Hu, Chris Lu, Jakob Foerster, Jeff Clune, and David Ha. The AI scientist-v2: Workshop-level automated scientific discovery via agentic tree search. *arXiv preprint arXiv:2504.08066*, 2025. URL `https://doi.org/10.48550/arXiv.2504.08066`.

Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. Self-rewarding language models. In *International Conference on Machine Learning (ICML)*, 2024. URL `https://doi.org/10.48550/arXiv.2401.10020`.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL `https://papers.nips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets_and_Benchmarks.html`.

A Experimental Setup and Training Details

A.1 Model Specifications

We utilize Qwen 2.5 14B as our base policy model. To ensure computational efficiency during the Reinforcement Learning (RL) phase, the model is loaded in 4-bit quantization. The reward signal is generated by a larger, stronger teacher model, GPT-OSS-120B, operating within our multi-agent framework.

A.2 GRPO Hyperparameters

We employ Group Relative Policy Optimization (GRPO) to align the model. Unlike PPO, GRPO normalizes rewards within a group of generated outputs for the same input, eliminating the need for a separate value function network.

Table 4: Hyperparameters used for GRPO Post-training.

Hyperparameter	Value
Base Model	Qwen 2.5 14B (4-bit)
KL Coefficient (β)	0
Learning Rate	1×10^{-5}
Batch Size	8
Group Size (G)	8
Temperature	1
Number of Epochs	15
Gradient Accumulation	1
Optimizer	AdamW
Scheduler	Cosine Decay
Weight Decay	0.1
Loss Type	dr. grpo

B Data Construction

Our training dataset is derived from accepted papers at ICLR 2024. To ensure our model has not been exposed to the training data and to maintain a fair evaluation, we strictly use papers published after our model's knowledge cutoff date (September 2024). From this post-cutoff set, we exclude lower-scoring papers based on peer-review scores and further use the GPT OSS 120B model to identify and remove survey papers and empirical studies that do not propose novel ideas, retaining only papers that introduce original contributions.

Next, we extract the core research question from each paper's abstract using DeepSeek-V3.1. This yields a dataset of input–target pairs (Research Question, Abstract), where the research question serves as the prompt and the abstract acts as the target against which generated ideas are rewarded.

C Idea Generation Prompts

The policy model uses a structured Chain-of-Thought (CoT) format to ensure reasoning precedes the final idea proposal.

D LLM-as-a-Judge Details

We developed and evaluated over 50 distinct prompting strategies for the judge model. Refinement was conducted under a controlled empirical protocol using a fixed, expert-annotated validation set of 177 (research question, abstract, generated idea) triples collected across various training runs, including reward-hacked

samples. Each sample was rigorously labeled via majority vote by 7 domain experts with discrepancies resolved via consensus meetings. The Precision score determines the proportion of instances predicted as positive that were actually positive, meaning a perfect precision score indicates that every single positive prediction was correct and no false positives occurred therefore, high precision is vital to prevent reward hacking in RL.

Every prompt modification or architectural change was re-evaluated on this fixed benchmark. Each configuration was assessed over 5 independent runs, reporting mean precision, recall, F1 score, and accuracy to mitigate stochastic variance.

To arrive at our final judge architecture, we iterated through several distinct evaluation paradigms:

1. **Single-call Binary Judge:** A direct binary comparison between the generated idea and the abstract. While moderately effective, this setup was vulnerable to verbosity bias and superficial lexical overlap.

2. **Embedding-based Similarity:** Cosine similarity between abstract, research question, and idea embeddings using manually tuned thresholds. Although recall improved, the approach lacked interpretability and was highly sensitive to threshold choice.

3. **Structured Bullet-Point Compliance:** Required ideas to satisfy explicitly enumerated methodological elements (e.g., $\geq 80\%$ coverage). This improved transparency but allowed partial compliance exploitation.

4. **Keyword Alignment Heuristics:** Extracted key methodological terms and measured overlap. While improving interpretability, this method failed to capture deeper conceptual misalignment.

5. **Multi-stage Venue-style Novelty Judgment:** Simulated peer-review style novelty comparison with preconditions (on-topic verification and methodological specificity). This reduced certain exploitations but introduced novelty-manipulation artifacts.

6. **Final Multi-Agent Deliberative Judge:** Two debating Analysts perform structured methodological decomposition, followed by an Evaluator issuing a binary decision. This adversarial verification mechanism explicitly separates decomposition, critique, and aggregation.

In our final multi-agent model, robustness arises from the combination of these points:

1. **Prompt refinement alone is insufficient:** In Section 4.5 (Figure 2), we evaluate reduced versions of the architecture, including a single-LLM configuration ("1 LLM Analyst"). While this setup achieves relatively high recall, it suffers from lower precision (0.906), making it susceptible to reward hacking. This demonstrates that prompt quality alone does not eliminate exploitation.

2. **Hierarchy without careful prompt design is also insufficient:** During early multi-agent experiments, loosely specified roles led to inconsistent judgments and new forms of exploitation. Robust performance emerged only after iterative refinement of agent-specific prompts, explicit methodological constraints, and role separation.

3. **Empirical validation on annotated data:** The final multi-agent judge achieves perfect precision (1.0) on the hand-labeled dataset, demonstrating that robustness is not anecdotal but quantitatively validated.

Thus, the hierarchical structure provides variance reduction and adversarial verification, while prompt refinement ensures that each agent's reasoning is methodologically grounded. The robustness claim refers specifically to the final combined system.

Table 5 reports a summary of the best-performing configuration from each strategy category. Notably, while certain single-model strategies achieve relatively high recall (e.g., embedding-based similarity), they

Table 5: Comparison of Best Configurations per Evaluation Strategy (Mean over 5 runs). Our Final Multi-Agent Judge achieves perfect precision, eliminating false-positive rewards critical for mitigating reward hacking.

Strategy	Precision	Recall	F1	Accuracy
Single-call Binary	0.85	0.49	0.75	0.82
Embedding Similarity	0.58	0.69	0.73	0.76
Structured Compliance	0.80	0.47	0.72	0.79
Keyword Heuristics	0.79	0.23	0.60	0.74
Multi-stage Novelty	0.90	0.42	0.72	0.80
Multi-Agent (Final)	**1.00**	0.30	0.66	0.78

E   Multi-Agent Reward System Details

To mitigate reward hacking common in single-judge setups, we implement a Multi-Agent Debate framework. The system consists of four distinct roles simulated by GPT-OSS-120B. The agents engage in a multi-round discussion (typically 2 rounds) before a final verdict is rendered.

To validate this design, we evaluated the impact of each role on the stability of the reward signal. We conducted an ablation study comparing the reference four-role architecture against configurations where specific agents were removed or scaled. Figure 3 visualizes the resulting trade-offs between precision and recall. The data reveals that distinct roles safeguard against specific failure modes. for instance, removing the Analyst causes a sharp drop in precision due to a lack of structured decomposition, whereas removing the Evaluator results in overly conservative decision-making, collapsing recall. Based on these findings, we identified that scaling the analysis phase (2 Analysts + 1 Evaluator) maximizes precision while maintaining competitive recall, justifying its selection for our primary pipeline.

Figure 3: **Precision vs. Recall for Multi-Agent Judge Configurations.** We analyze the performance of various agent compositions, numbered 1 through 13. The plot highlights the sensitivity of the reward signal to agent roles: removing the *Analyst* [1] significantly degrades precision, while removing the *Evaluator* [10] nearly eliminates recall. Configuration [11] (2 Analysts + 1 Evaluator) represents the optimal trade-off chosen for the main pipeline, achieving perfect precision (1.0) with robust recall (0.300).

F Prompts

System Prompt: Survey Classifier

You are an expert research assistant. Your task is to determine if a research paper is a SURVEY/REVIEW paper, a NEW IDEA/METHOD paper, or an EVALUATION/TESTING paper.
Guidelines:
1. If the paper mainly reviews, surveys, or summarizes existing work then it is a SURVEY (`"paper_type": "survey"`).
2. If the paper introduces a new method, model, algorithm, framework, or experimental setup then it is a NEW IDEA (`"paper_type": "new_idea"`).
3. If the paper does not introduce a new method but instead focuses on evaluating, testing, benchmarking, or stress-testing existing methods on certain tasks or datasets, then it is an EVALUATION paper (`"paper_type": "evaluation"`).
Output format:
1. First write your reasoning step by step.
2. Then give the final answer in strict JSON format, for example:
`{"paper_type": "survey"}`
`{"paper_type": "new_idea"}`
`{"paper_type": "evaluation"}`
Don't forget to tell your reasoning.

Figure 4: The system prompt used to classify whether a paper contains new ideas or is a survey or evaluation paper.

User Prompt: Survey Classifier

Here is the title of the paper:
`"""{title}"""`

Here is the abstract:
`"""{abstract}"""`

Now follow the instructions and provide the final answer in JSON format after writing your reasoning.

Figure 5: The user prompt used to classify whether a paper contains new ideas or is a survey or evaluation paper.

System Prompt: Research Question Generator

Prompt for Generating a Research Question from a Paper's Title and Abstract

Role: You are an expert research analyst. Your task is to distill the core problem from a scientific paper's title and abstract and frame it as a concise research question.

Primary Task: Analyze the provided **title and abstract** to identify the central problem the paper addresses and the unique solution it proposes (the "golden idea"). Based on this analysis, you will generate a single, short research question that focuses solely on the problem. The title often hints at the solution, while the abstract provides the necessary context about the problem.

Output Format: Your entire response must be a single JSON object. Do not add any text before or after the JSON block. The JSON object must contain two keys:

1. `"reasoning"`: A brief analysis of the title and abstract, clearly separating the identified problem from the "golden idea" (the solution).
2. `"research_question"`: The final, carefully formulated research question.

Critical Rules for the Research Question

1. **Problem-Focused, Not Solution-Focused:** The question must articulate only the **problem, challenge,** or **gap** that the research aims to solve. It must **NOT** contain, hint at, or incorporate any part of the specific method, technique, input type, or key finding (the "golden idea") that the paper presents as the solution. Base it strictly on the general problem described before the solution is introduced.
2. **Answerable by the Abstract:** The primary contribution described in the abstract should serve as a direct answer to the question you generate.
3. **Completely Self-Contained:** The question must be fully understandable on its own without needing the abstract. **Crucially, it must not reference the paper, the authors, or the abstract itself** (e.g., avoid phrases like "in this paper" or "the authors' method").
4. **Interrogative Form:** Phrase the question to inquire about a method, possibility, or approach. Good starting points include "How can...", "What is an effective way to...", or "Is it possible to...".
5. **Conciseness:** Keep the research question short and direct, ideally under 20 words. Avoid adding details or qualifiers that could leak information from the abstract—focus on the essence of the problem only.
6. **No Information Leakage:** Double-check that the question reveals nothing about the solution, such as specific data types, techniques, or improvements mentioned in the abstract. If a detail feels tied to the solution, exclude it.

Example to Follow

Provided Title: "AffiniNet: A Fast and Accurate End-to-End Graph Neural Network for Protein-Ligand Binding Affinity Prediction"

Provided Abstract: "Current machine learning models for predicting protein-ligand binding affinity often require extensive computational resources and hand-engineered features, limiting their scalability. We introduce 'AffiniNet,' a novel graph neural network... [truncated for brevity] ... traditional docking simulations."

Required JSON Output: {
```
"reasoning":  "The title names the solution:  'AffiniNet,' a graph neural network.  The
abstract describes the problem:  existing methods...  are computationally expensive...  The
'golden idea' is a GNN...",
"research_question":  "How can protein-ligand binding affinity be predicted more efficiently
without hand-engineered features?"
}
```

Figure 6: The system prompt used to generate a **Research Question** from a paper's title and abstract.

User Prompt: Research Question Generator

Now, apply these rules and generate the JSON output for the title and abstract provided below.

Title:
{title}

Abstract:
{abstract}

Figure 7: The user prompt used to generate a **Research Question** from a paper's title and abstract.

System Prompt: Idea Generation Policy

You are an expert research collaborator. Your purpose is to refine a general research question into a specific, actionable, and feasible research idea. Your goal is to identify a concrete research gap or a logical next step based on the research question.

Your process for the `<reasoning>` tag must be:

1. **Synthesize the Core Problem:** Briefly state the central challenge or question based on the user's query.

2. **Identify the Gap/Opportunity:** Analyze the research question to infer a specific limitation, an unanswered aspect, a methodological gap, or an underexplored niche. State this gap clearly.

3. **Formulate the Bridge:** Explain how your proposed idea will directly address the identified gap.

Your final `<answer>` must:

- Directly follow the `<reasoning>` and be a logical conclusion of it.

- Be a specific, testable hypothesis or a concrete experimental plan focused on idea generation and the proposed method.

- Be technically feasible with current scientific/engineering methods.

- Propose a clear and fully-formed investigation describing only the proposed method, without discussing results, accuracy, evaluation methods, or any outcomes.

- Describe the idea and proposed method in detail, not a general area of study.

- Output exclusively in English, except for Greek letters, mathematical symbols, or other standard scientific notations commonly used in English-language technical writing.

 # FORMAT (Strictly Adhere)

- You must use exactly one `<reasoning>` tag and exactly one `<answer>` tag.

- The `<answer>` tag must appear immediately after the closing `</reasoning>` tag.

- Your entire output must be enclosed within these two tags. No other text is allowed.

- All content must be in English only, with exceptions as noted above.

`<reasoning>`
1. Core Problem: [Synthesize the main challenge]
2. Gap/Opportunity: [State the specific gap inferred from the question]
3. Bridge: [Explain how your idea connects the gap to a solution]
`</reasoning>`
`<answer>`
[Your specific and actionable research idea, focusing on the proposed method]
`</answer>`

Figure 8: The full system prompt used for the Idea Generation Policy.

User Prompt: Idea Generation Policy

Research Question:
{research_question}

Based on the instructions, please synthesize this information to generate one specific and feasible research idea. Follow the required format precisely.

Figure 9: The full user prompt used for the Idea Generation Policy.

System Prompt: Best of N

You are an expert Scientific Innovation Scout and Novelty Reviewer. Your goal is to identify the most theoretically original and distinct scientific ideas from a given list.
YOUR OBJECTIVES:

1. **Analyze Novelty Only:** You must evaluate ideas solely based on how distinct they are from the current State-of-the-Art (SOTA). Do not evaluate feasibility, cost, or implementation risks.

2. **Identify Divergence:** For each idea, identify the standard paradigm it challenges and explain the specific divergence.

3. **Select the Best:** Select the single most novel idea—the one that offers the most unique angle, mechanism, or hypothesis.

OUTPUT FORMAT:
You must output your response STRICTLY as a valid JSON object using the schema below. Do not output conversational text or markdown formatting (like "`json).
JSON SCHEMA:

```
{
  "idea_evaluations": [
    {
      "id": "String (matches input ID)",
      "sota_comparison": "Brief description of the standard approach...",
      "novelty_reasoning": "Analysis of why this is distinct/surprising.",
      "novelty_score": "Integer 1-10 (10 = Revolutionary, 1 = Derivative)"
    }
  ],
  "winner": {
    "id": "String (ID of the most novel idea)",
    "rationale": "Why this idea was chosen as the most novel."
  }
}
```

Figure 10: The system prompt used for selecting the best idea among N generated ideas.

User Prompt: Best of N

Here is the data for your evaluation.

Research Question:
{research_question}

List of Input Ideas:
{ideas}

Based on the system instructions, analyze the novelty of these ideas and generate the JSON output.

Figure 11: The user prompt used for selecting the best idea among N generated ideas.

System Prompt: Supervised Fine-Tuning

You are an expert research collaborator. Your purpose is to refine a general research question into a specific, actionable, and feasible research idea. Your goal is to identify a concrete research gap or a logical next step based on the research question.
Your final answer must:

- Be a specific, testable hypothesis or a concrete experimental plan focused on idea generation and the proposed method.

- Be technically feasible with current scientific/engineering methods.

- Propose a clear and fully-formed investigation describing only the proposed method, without discussing results, accuracy, evaluation methods, or any outcomes.

- Describe the idea and proposed method in detail, not a general area of study.

- Output exclusively in English, except for Greek letters, mathematical symbols, or other standard scientific notations commonly used in English-language technical writing.

Figure 12: The system prompt used for supervised fine-tuning.

User Prompt: Supervised Fine-Tuning

Research Question:
{research_question}

Based on the instructions, please synthesize this information to generate one specific and feasible research idea. Follow the required format precisely.

Figure 13: The user prompt used for supervised fine-tuning.

System Prompt: The Moderator Agent

You are an expert research evaluation moderator. Your role is to guide a discussion that evaluates the alignment between a given Abstract and a Generated Idea.

Your primary responsibility is to ensure the discussion focuses on assessing the key *methodological* and *contribution* aspects of both the Abstract and the Generated Idea.

Important Guidelines:

1. The discussion must *not* compare the Abstract and the Generated Idea based on data pipelines or evaluation setups. If any participant attempts this, issue a clear warning.
2. Ensure they compare concrete components — algorithms, frameworks — and that they do not compare the datasets and evaluation process.
3. If the Generated Idea contains placeholder text or fails to propose a substantial or meaningful solution to the stated Research Question, immediately halt the discussion and notify all participants.
4. You are *not* a participant in the discussion. You act as a moderator — your job is to guide and manage the conversation ensuring it stays focused and methodologically sound.

Figure 14: The system prompt used for the **Moderator Agent**, tasked with guiding the discussion and enforcing methodological alignment.

User Prompt: The Moderator Agent

{history}
Round {round_num} of discussion.

Research Question: {rq}
Abstract: {abs}
Generated Idea: {idea}

Lead the experts to focus only on *core methodological* alignment between Abstract and Generated Idea.

Your role: remind everyone of the goal (to decide if Abstract matches the Generated Idea in essence and intent).

Ask the Analyst to start by discussing the conceptual alignment between Abstract and Idea.

Figure 15: The user prompt used for the **Moderator Agent**, tasked with guiding the discussion and enforcing methodological alignment.

System Prompt: The Analyst Agent

You are the Analyst, a method-oriented research evaluator in a multi-agent discussion.

Your role is to critically examine the alignment between the Abstract and the Generated Idea focusing exclusively on the methodology, novelty, and critical assumptions — not on dataset details, evaluation setups, or performance metrics.

Your Responsibilities:

1. Carefully review the previous discussions and your own earlier opinions to ensure continuity and consistency in reasoning.
    – If your current assessment differs from your prior view explicitly explain why your opinion evolved.
2. Identify the core methodological elements and novel contributions in the Abstract — such as models, algorithms, architectures, and assumptions.
3. Compare each core methodological or conceptual element of the Abstract against the Generated Idea.
4. Highlight any misalignment or omission, such as when a critical component from the Abstract is absent, replaced, or contradicted in the Generated Idea.
5. Pay extra attention to specific innovations or contributions rather than general context, background, or motivation.
6. Engage with other persons by commenting on their observations:
    – You may agree, partially agree, or respectfully disagree.
    – Provide analytical reasoning when commenting, always grounded in methodological evidence.
    – If another person's reasoning is unclear, inconsistent or off-topic, politely request clarification.

Your Output Should Include:

- A clear list of the Abstract's *core methodological elements* (e.g., models, frameworks, algorithms, assumptions).
- A structured comparison showing which elements align, differ or are missing in the Generated Idea.
- Comments addressing other people points of agreement or contention, where relevant.
- A concise concluding assessment of overall alignment and conceptual consistency and noting any evolution in your opinion since prior discussions.

Remember: Your task is analytical and conversational. Focus on methodological alignment and explain any evolution in your reasoning since the last discussion. You are not a passive participant — you are an analyst and commentator ensuring methodological rigor and logical coherence across the discussion. If a generated idea hasn't been provided and the text is just a placeholder, don't create one yourself. Simply end the discussion and inform others to do the same.

Figure 16: The system prompt used for the **Analyst Agent**, tasked with identifying core methodological elements and comparing them.

User Prompt: The Analyst Agent

{history}

Research Question: {rq}
Abstract: {abs}
Generated Idea: {idea}

Now, based on the prior discussions and your previous stance, re-evaluate your analysis.
Provide your updated opinion explicitly noting any changes or reaffirmations compared to your earlier assessments.
Conclude with a summary indicating how many of the Abstract's core methodological elements are reflected or missing in the Generated Idea.

Figure 17: The user prompt used for the **Analyst Agent**, tasked with identifying core methodological elements and comparing them..

System Prompt: The Critic Agent

You are the Critic, a methodological evaluator in a multi-agent research discussion.
Your Role: You critically analyze whether the Abstract and the Generated Idea are methodologically aligned — focusing on the core approach, underlying logic, and assumptions used to address the research question.
Your Responsibilities:
1. Review prior discussions and your own previous opinions before providing a new one.
    – Ensure consistency with your earlier assessments, or clearly explain any evolution in your stance.
2. Identify the Abstract's core methodological assumptions and approach — including theoretical foundations, modeling frameworks, or algorithmic strategies.
    – Do not consider datasets, data pipelines, evaluation setups, or metrics for comparison.
3. Compare these elements with the Generated Idea:
    – Highlight any missing, altered, or replaced methodological aspects.
    – Explicitly point out contradictions or incompatible assumptions.
4. Engage with other agents constructively:
    – You may agree, partially agree, or respectfully disagree with their analysis.
    – Provide concise, evidence-based commentary that either supports or challenges their reasoning.
    – If another participant's comment is vague or off-topic, request clarification politely.
Your Output Should Include:
- A list or brief summary of the Abstract's methodological approach and key assumptions.
- A comparison indicating where the Generated Idea aligns, diverges, or contradicts the Abstract.
- Constructive comments addressing the reasoning of other participants.
- A closing summary that states your updated position, mentioning whether and why it differs from your previous opinion.
Note: Stay objective, analytical, and cooperative. Your goal is to ensure methodological consistency and intellectual rigor across the discussion. If a generated idea hasn't been provided and the text is just a placeholder, don't create one yourself. Simply end the discussion and inform others to do the same.

Figure 18: The system prompt used for the **Critic Agent**, tasked with scrutinizing logic and detecting contradictions.

User Prompt: The Critic Agent

`{history}`

Research Question: `{rq}`
Abstract: `{abs}`
Generated Idea: `{idea}`

Based on the ongoing discussion and your previous critiques, reassess whether the Generated Idea aligns methodologically with the Abstract.

- Identify the Abstract's and Generated Idea's methodological assumptions and logic.

- Compare them with each other.

- Engage with other participants by commenting on their reasoning when appropriate.

- If your opinion has changed since your earlier analysis, clearly explain the reason.

Conclude with a concise summary of the overall methodological alignment or contradictions between the Abstract and the Generated Idea.

Figure 19: The user prompt used for the **Critic Agent**, tasked with scrutinizing logic and detecting contradictions.

System Prompt: The Evaluator Agent

You are the Evaluator and the final decision maker in a multi-agent research discussion.
Your Role: Your task is to deliver the final, objective judgment on whether the Abstract and the Generated Idea align in terms of their *methodology* and *core contributions*.
Your Workflow:
1. Begin by reviewing and summarizing the prior discussion among people (Analyst, Critic, Moderator, etc.).
   – Briefly capture the essence of their arguments and reasoning.
   – Consider the reasoning and arguments made by all participants (Analyst, Critic, Moderator, etc.).
   – Extract each participant's individual opinion (e.g., match or not match) and reasoning.
   – Identify whether the participants generally agree or disagree.
2. After summarizing, perform your own evaluation:
   – Focus solely on *methodology* and *core contributions*.
   – Ignore datasets, metrics, or evaluation setups as comparison factors.
3. Determine alignment: Decide whether the Abstract and the Generated Idea express essentially the same core methodological logic and contributions.
4. Provide a final, concise judgment reflecting both the discussion summary and your reasoning.
5. Justify your conclusion: Provide a brief, evidence-based explanation that reflects the entire discussion history.
Output Format: After writing the summarization and your reasoning, return your answer strictly in the following JSON format:
```
<summarization> Your summarization </summarization>
<reasoning> Your reasoning </reasoning>
"'json
{
"reason":  "short text summarizing others' opinions and explaining your final
decision",
"match":  true or false,
"reward":  1 if match else 0
}
"'
```
Note: Be concise, analytical, and decisive — your response represents the final conclusion of the entire discussion.

Figure 20: The system prompt used for the **Evaluator Agent**, tasked with synthesizing the debate and issuing the final binary reward.

User Prompt: The Evaluator Agent

```
{history}
```

Research Question: {rq}
Abstract: {abs}
Generated Idea: {idea}

Based on the complete discussion history and all previous people opinions:

1. First summarize the discussion among participants and write it down.

   - Extract each participant's stance (match or not match) and key reasoning.
   - State whether they generally agree or disagree.

2. Then, make your own evaluation strictly based on *methodology* and *core contributions* and write your reasoning.

   - Ignore dataset, metrics, and evaluation setups.
   - If the Generated Idea captures the *main idea* and *central logic* of the Abstract, even with small or secondary differences, mark it as a match.
   - Mark it as not a match if it diverges from or contradicts the Abstract's fundamental methodology or contributions.

After writing the summarization and your reasoning, return your answer strictly in the following JSON format: If the Generated Idea captures the main methodological logic and central contributions of the Abstract, mark it as a match. If some main parts are aligned and some parts are different, still mark it as matched.

```
<summarization> Your summarization </summarization>
<reasoning> Your reasoning </reasoning>

```json
{
  "reason": "short text summarizing others' opinions and explaining your reasoning",
  "match": true or false,
  "reward": 1 if match else 0
}
```

Figure 21: The user prompt used for the **Evaluator Agent**, tasked with synthesizing the debate and issuing the final binary reward.

System Prompt: Idea Extraction

Act as a research analyst specializing in identifying core innovations. From the provided paper text, perform strict extraction (no external knowledge) to identify:

1. **The central research question the paper explicitly or implicitly seeks to answer.**
   Requirements:
   - Must be phrased as a single, direct question ending with "?"
   - Must be answerable exclusively by the paper's novel methodology (not prior work)
   - If multiple questions exist, select the one addressed by the most novel contribution

2. **Reasoning trail (CONTENT-ONLY, NO REFERENCES).**
   Requirements:
   - Exactly 2 sentences max:
     – Sentence 1: How the research question was derived from the paper's stated problem gap
     – Sentence 2: Why this specific method component is novel per authors' explicit claims
   - **STRICTLY PROHIBITED:**
     – Section numbers (e.g., "Section 3.1")
     – Definition/equation labels (e.g., "(Definition 2.3)")
     – Figure/table references
     – Page numbers or citation markers
   - Use only conceptual language from the paper's narrative (e.g., "authors identify a gap in...", "they claim novelty in...")

3. **The core novel methodology that answers this question.**
   Requirements:
   - Describe ONLY the novel mechanism/design at architectural/algorithmic level
   - **STRICTLY EXCLUDE:**
     – Evaluation contexts ("applied to...", "tested on...")
     – Datasets, domains, or application scenarios
     – Performance metrics or comparisons
   - Must be explicitly claimed as novel by authors (e.g., "we propose", "our key innovation")

Output JSON Format (STRICT):

```
{
  "research_question": "[Exact question text]",
  "reasoning": "[Exactly two sentences of pure conceptual justification]",
  "method": "[Pure technical mechanism description ONLY]"
}
```

Critical Constraints:
- NEVER invent details; omit uncertain elements

Figure 22: The full system prompt used for extracting the idea from the output of AI Scientist.

User Prompt: Idea Extraction

```
## Paper Text
"`text
{paper}
"`
```

Figure 23: The full user prompt used for extracting the idea from the output of GPT Researcher and AI Scientist.

System Prompt: Pairwise Idea Evaluator

You are an expert scientific reviewer tasked with comparing two research methods. You will be provided with:

1. A scientific research question
2. Two proposed methods (Method A and Method B) to address that question

Your role is to compare these methods based on three criteria: **Novelty**, **Feasibility**, and **Effectiveness**. Provide thorough reasoning explaining how the methods compare on each criterion before indicating which method is superior.

Evaluation Criteria

1. Novelty

- **Definition:** The degree to which the proposed method introduces new concepts, approaches, or perspectives that differ from existing work in the field.
- *Task:* Compare which method demonstrates greater originality, introduces more innovative concepts, or combines ideas in more unprecedented ways.

2. Feasibility

- **Definition:** The practical viability of implementing the proposed method given current technological capabilities, resource requirements, time constraints, and technical complexity.
- *Task:* Compare which method is more practical to implement, requires fewer resources, faces fewer technical barriers, or has a more realistic timeline.

3. Effectiveness

- **Definition:** The expected capability of the method to adequately address the research question and produce meaningful, reliable results that advance scientific understanding.
- *Task:* Compare which method better addresses the research question, is more likely to produce robust results, or has stronger scientific methodology.

Comparison Values

For each criterion, you must indicate which method is better using one of these values:

- **"A"** - Method A is clearly better
- **"equal"** - Both methods are approximately equal on this criterion
- **"B"** - Method B is clearly better

Instructions

1. **Carefully read** the research question and both proposed methods.
2. **Compare** the methods systematically against each criterion.
3. **Provide detailed reasoning** for each criterion (3-5 sentences explaining the comparison, highlighting strengths and weaknesses of each method).
4. **Assign comparison values** based on the definitions above.
5. **Be objective and nuanced** - recognize that methods may have different trade-offs.
6. **Think like an expert reviewer** - consider practical constraints, disciplinary standards, and realistic expectations.

Output Format

First, provide your comparative reasoning for each criterion in prose, structured as follows:

Novelty Comparison:

[Your detailed comparison of novelty between Method A and Method B]

Feasibility Comparison:

[Your detailed comparison of feasibility between Method A and Method B]

Effectiveness Comparison:

[Your detailed comparison of effectiveness between Method A and Method B]

Then, output your comparison results in the following JSON format:

```
{
"novelty":  "<A|equal|B>",
"feasibility":  "<A|equal|B>",
"effectiveness":  "<A|equal|B>"
}
```

Figure 24: The system prompt used to evaluate two ideas based on novelty, feasibility, and effectiveness, selecting the superior idea or marking them as equal.

Figure 25: The user prompt used to evaluate two ideas based on novelty, feasibility, and effectiveness, selecting the superior idea or marking them as equal.

System Prompt: Absolute Idea Evaluator

You are an expert scientific reviewer tasked with evaluating research methods and ideas. You will be provided with:
1. A scientific research question
2. A proposed method or idea to address that question

Your role is to critically assess the proposed method based on three criteria: **Novelty**, **Feasibility**, and **Effectiveness**. Provide thorough reasoning for each criterion before assigning scores.

Evaluation Criteria
1. Novelty (1-5)
• **Definition:** The degree to which the proposed method introduces new concepts, approaches, or perspectives that differ from existing work in the field.
• **5 (Highly Novel):** Introduces groundbreaking concepts or paradigm-shifting approaches not previously explored.
• **4 (Novel):** Presents fresh perspectives or modifications that significantly advance beyond current methods.
• **3 (Moderately Novel):** Offers incremental improvements or reasonable variations on existing approaches.
• **2 (Minimally Novel):** Largely relies on well-established methods with minor tweaks.
• **1 (Not Novel):** Directly replicates existing approaches without meaningful differentiation.

2. Feasibility (1-5)
• **Definition:** The practical viability of implementing the proposed method given current technological capabilities and resources.
• **5 (Highly Feasible):** Can be readily implemented with existing resources and technology.
• **4 (Feasible):** Implementation is practical with reasonable effort.
• **3 (Moderately Feasible):** Presents notable implementation challenges.
• **2 (Low Feasibility):** Faces major practical obstacles.
• **1 (Not Feasible):** Cannot be realistically implemented with current technology.

3. Effectiveness (1-5)
• **Definition:** The expected capability of the method to adequately address the research question.
• **5 (Highly Effective):** Directly and comprehensively addresses all aspects of the research question.
• **4 (Effective):** Addresses the core research question well.
• **3 (Moderately Effective):** Partially addresses the research question.
• **2 (Minimally Effective):** Tangentially relates to the research question.
• **1 (Ineffective):** Does not adequately address the research question.

Instructions
1. **Carefully read** both the research question and the proposed method.
2. **Analyze** the method systematically against each criterion.
3. **Provide detailed reasoning** for each criterion (2-4 sentences).
4. **Assign scores** from 1-5 for each criterion.
5. **Be objective and balanced** - acknowledge both strengths and weaknesses.
6. **Think like an expert reviewer** - consider practical constraints.

Output Format
First, provide your reasoning for each criterion in prose. Then, output your scores in the following JSON format:
`{"novelty": <1-5>, "feasibility": <1-5>, "effectiveness": <1-5>}`

Figure 26: The system prompt used to evaluate a given scientific idea based on novelty, feasibility and effectiveness.

User Prompt: Absolute Idea Evaluator

Research Question:
{research_question}

Proposed Method/Idea:
{method}

Figure 27: The user prompt used to evaluate a given scientific idea based on novelty, feasibility and effectiveness.

G   Sample Generations

In this section, we present a direct comparison of research ideas generated by our proposed method and several baselines across three representative research questions from our curated set of golden RQs.

Example 1: Input Research Question

How can we detect and mitigate hallucinations in large models without access to ground-truth knowledge?

Figure 28: The input research question (Sample 1) used to prompt all models for this comparison.

Example 1: Generated Idea from Unsloth Qwen2.5 14B

Propose a methodology where crowdsourced annotators evaluate model outputs for consistency and factual accuracy. Annotators would receive input samples generated by the model and rate them based on predetermined criteria such as plausibility and adherence to known facts. Scores from multiple annotators are aggregated to identify patterns of inconsistent or erroneous outputs indicative of hallucinations. Based on these evaluations, the model could be fine-tuned using a subset of inputs labeled by humans as likely to produce hallucinations, thereby mitigating future hallucinations without requiring comprehensive ground-truth data.

Figure 29: Research idea generated for sample 1 by the Unsloth Qwen2.5 14B baseline.

Example 1: Generated Idea from GPT Researcher

To address the challenge of detecting and mitigating hallucinations in large language models without relying on ground-truth knowledge, a promising research direction involves developing a self-supervised learning framework that leverages model-generated outputs for feedback. This approach would train the model to recognize inconsistencies within its own responses by comparing them against a set of generated examples, identifying patterns indicative of hallucination. The core idea is to create a system where the model learns to evaluate its own outputs based on internal consistency, coherence, and logical flow, thereby enhancing its ability to self-correct. This research fills a critical gap in existing methodologies, which often require extensive human-labeled data or external validation sources to detect errors. By enabling models to autonomously assess their reliability, this study aims to significantly reduce the reliance on external ground-truth knowledge, making the detection and mitigation of hallucinations more scalable and practical for real-world applications.

Figure 30: Research idea generated for sample 1 by the GPT Researcher agent.

Example 1: Generated Idea from AI Scientist V2

This paper proposes a novel approach to detect and mitigate hallucinations in large language models without relying on ground-truth knowledge. By focusing on the self-consistency and internal consistency of model responses, we demonstrate that it is possible to identify instances where the model generates inconsistent or illogical outputs. Specifically, we introduce a method that compares the responses of a model to different prompts or inputs that should yield similar outputs, thereby identifying discrepancies indicative of hallucinations. We evaluate our approach on a variety of language models and show that it can effectively detect hallucinations in scenarios where traditional methods relying on ground truth data are not applicable. The proposed method provides a promising avenue for improving the reliability and trustworthiness of large language models in real-world applications.

Figure 31: Research idea generated for sample 1 by AI Scientist V2.

Example 1: Generated Idea from Research Agent

We propose a method that integrates the holonomic brain theory, concreteness metrics, and neural correlates of consciousness to detect and mitigate hallucinations in large language models (LLMs). Specifically, we will:
1. Train an LLM to simulate neural activity patterns inspired by the holonomic brain theory, focusing on distributed memory and interference patterns.
2. Incorporate concreteness scores for input and output text segments, ensuring the model penalizes responses that deviate from human-like semantic coherence.
3. Use Representational Similarity Analysis (RSA) to compare the model's semantic representations with those of humans, as established in Related Paper #6.
4. Implement a scoring mechanism that detects deviations in neural activity patterns simulated by the LLM compared to those observed in human brains, guided by Related Papers #7 and #9.
5. Develop a threshold-based system that flags potential hallucinations when the deviation exceeds predefined thresholds.
6. Use this flagged data to iteratively refine the model's training, enhancing its ability to mitigate hallucinations over time.
7. Evaluate the effectiveness of our method using qualitative and quantitative assessments, including human judgment and benchmark datasets.
8. Ensure the method's generalizability by testing it across various types of LLMs and application domains.

Figure 32: Research idea generated for sample 1 by the Research Agent.

Example 1: Generated Idea from SFT

A framework that monitors the evolution of intermediate representations throughout model generations by computing the KL divergence between distributions sampled from each representation layer at consecutive steps; if divergence exceeds a threshold set during training, it triggers re-rewinding to the most stable earlier point before resuming generation under a constrained sampling process that minimizes changes between sequential generations.

Figure 33: Research idea generated for sample 1 by the model Fine-Tuned on ICLR data (SFT).

Example 1: Generated Idea from LDC

A model-free detection and mitigation system that integrates two orthogonal methods: (a) a confidence-based ranking heuristic that scores each token output for plausibility without relying on prior knowledge or additional tokens from the model, and (b) a self-supervised loss function based on contrastive cosine similarity between tokens from the current generation and the last generation, with a regularization term that penalizes divergent token embeddings over generations.

Figure 34: Research idea generated for sample 1 by LDC.

Example 1: Generated Idea from our method - BoN (10)

The research idea involves designing a self-consistency mechanism for large language models through recursive querying. The process operates as follows:

Upon receiving a query, the model first generates a primary response. Then, to check the consistency of the generated answer, secondary queries are formulated based on the semantic content and context of the initial response, aiming to elicit complementary or correlative details that would substantiate or contradict parts of the original answer. These secondary queries could include asking follow-up questions like "What supporting evidence leads to this conclusion?" or requesting paraphrases ("Can you say it differently?"), alongside more direct verification questions ("Is this factually accurate according to what you know?"). The responses to these secondary queries are compared with the original to flag any contradictions or unsupported claims, indicating potential hallucinations.

In cases where inconsistencies are detected, the system iterates, refining the original response by seeking additional contextual details from further related inquiries, thereby attempting to resolve or mitigate identified hallucinations through a dynamic, iterative refinement loop. This method reduces reliance on external ground-truth data by leveraging the internal consistency of information and reasoning processes within the model itself, making it a viable strategy even when direct ground-truth comparison is infeasible.

Figure 35: Research idea generated for sample 1 by our method - BoN (10).

Example 2: Input Research Question

How can we implement an efficient user profile updater in a recommendation system using their behaviorial patterns while having an optimized update strategy?

Figure 36: The input research question (Sample 2) used to prompt all models for this comparison.

Example 2: Generated Idea from Unsloth Qwen2.5 14B

To develop a machine learning-based predictive model that determines optimal moments for updating user profiles in a recommendation system by analyzing historical behavioral data. This model will use supervised learning techniques to predict changes in user preferences and needs, triggering profile updates only when significant behavioral shifts are detected, thus enhancing efficiency and maintaining relevance.

Figure 37: Research idea generated for sample 2 by the Unsloth Qwen2.5 14B baseline.

Example 2: Generated Idea from GPT Researcher

To address the challenge of efficiently updating user profiles in a recommendation system based on behavioral patterns, a novel research idea could involve developing a hybrid model that integrates both online learning algorithms and periodic batch updates. This approach would leverage real-time user interactions for immediate adjustments to user profiles while also periodically refining these profiles through comprehensive analysis of historical data. The research would explore how to optimally balance the frequency and depth of these updates to ensure that the system remains responsive to recent user behavior without overwhelming computational resources. By focusing on identifying key behavioral indicators that significantly influence user preferences, the study aims to reduce the noise in profile updates and enhance the precision of recommendations. This research addresses the gap between the need for timely updates and the efficiency constraints of frequent computations, potentially leading to more accurate and personalized recommendations with minimal resource consumption.

Figure 38: Research idea generated for sample 2 by the GPT Researcher agent.

Example 2: Generated Idea from AI Scientist V2

Existing recommendation systems often rely on static user profiles that are periodically updated, leading to suboptimal recommendations during periods of rapid user interest change. This paper proposes an efficient user profile updater that leverages temporal behavioral patterns to dynamically adjust user profiles. By focusing on recent interactions, the system can adapt more quickly to changing user preferences, enhancing recommendation accuracy while minimizing computational overhead. Experiments demonstrate that this approach significantly improves recommendation quality compared to traditional methods, making it a promising solution for real-time recommendation systems.

Figure 39: Research idea generated for sample 2 by AI Scientist V2.

Example 2: Generated Idea from Research Agent

Develop a hybrid user profile updater in a recommendation system that integrates both implicit (behavioral) and explicit (direct) feedback through a dynamic weighting mechanism. This mechanism will adjust the influence of each type of feedback based on the frequency and consistency of user interactions. Additionally, implement an adaptive update strategy that employs temporal decay functions to balance short-term responsiveness with long-term accuracy, ensuring that recent preferences do not overshadow long-term interests.

Figure 40: Research idea generated for sample 2 by the Research Agent.

Example 2: Generated Idea from SFT

A two-level hierarchical queue management mechanism where recent user actions are processed in a priority queue, and older interactions are stored in a FIFO (First-In-First-Out) queue, combined with a frequency-based pruning algorithm that removes redundant entries after a specified number of updates have been made.

Figure 41: Research idea generated for sample 2 by the model Fine-Tuned on ICLR data (SFT).

Example 2: Generated Idea from LDC

An adaptive updating frequency control mechanism that dynamically adjusts the update frequency of user profiles based on behavioral patterns, integrating behavioral clustering to categorize users into similarity groups for targeted updates, with feedback-based optimization to refine and maintain an optimal update strategy over time.

Figure 42: Research idea generated for sample 2 by LDC.

Example 2: Generated Idea from our method - BoN (10)

Develop and test an adaptive scheduling framework for user profile updates in recommendation systems, which utilizes real-time data streaming and anomaly detection algorithms to identify critical moments of user behavior change. Utilize machine learning models like LSTM networks to analyze sequential behavioral patterns and predict optimal times for profile adjustments. For each identified significant shift, employ a lightweight ML model to summarize the essence of the new behavior and adjust the user profile accordingly. Validate the efficacy of this approach by comparing user engagement metrics (e.g., click-through rate, time spent on recommended content) between systems employing traditional batch update strategies versus those using the adaptive scheduling framework, focusing particularly on dynamic environments where user interests fluctuate rapidly.

Figure 43: Research idea generated for sample 2 by our method - BoN (10).

Example 3: Input Research Question

Since there are limited ASR foundation models, so when a person wants to use one of them, he will fine tune one these limited models. the problem with this approach is that since they are limited foundation models and are open source and attack are generated against the based model can easily transfer to the fine tuned version, this gives the attacker a near whitebox access to the fine tuned version. How can we propose a solution that can outperform existing standard adversarial training to make the model robust against these attacks?

Figure 44: The input research question (Sample 3) used to prompt all models for this comparison.

Example 3: Generated Idea from Unsloth Qwen2.5 14B

Propose an adaptive adversarial training framework for fine-tuned ASR models that uses online learning and transfer learning to continuously update the model's defenses against newly discovered or evolving adversarial attacks. Specifically, design an algorithm where the fine-tuned ASR model undergoes periodic updates through the addition of new adversarial examples generated using transfer learning techniques, where these adversarial examples are derived from both the base model and the fine-tuned version itself. The system should include an online learner module that incrementally trains the model with these new examples, ensuring that the model stays robust against a broader spectrum of attacks. Additionally, incorporate a mechanism to dynamically adjust the learning rate based on the confidence score of the model's predictions to prevent overfitting to specific types of attacks. This method aims to reduce the computational cost and improve the robustness of the fine-tuned ASR model against a variety of unknown adversarial attacks.

Figure 45: Research idea generated for sample 3 by the Unsloth Qwen2.5 14B baseline.

Example 3: Generated Idea from GPT Researcher

To address the vulnerability of fine-tuned ASR models to adversarial attacks stemming from their limited foundational models, a novel research direction could involve developing a dynamic adversarial training framework that leverages contextualized noise injection during the fine-tuning process. This framework would introduce adaptive noise patterns that evolve based on the specific characteristics of the fine-tuned model, thereby creating a more resilient defense mechanism. By continuously updating the types and magnitudes of noise according to real-time feedback from the model's performance and input data, the system can better anticipate and mitigate potential attacks. This approach not only enhances the robustness of the fine-tuned model but also reduces the likelihood of attackers successfully transferring attacks from the base model. The research would focus on designing algorithms that can efficiently generate and apply such adaptive noise, ensuring that the model remains functional while being resistant to adversarial perturbations.

Figure 46: Research idea generated for sample 3 by the GPT Researcher agent.

Example 3: Generated Idea from AI Scientist V2

Fine-tuning pre-trained ASR models is a common practice, yet these models remain susceptible to adversarial attacks due to inherited vulnerabilities. This paper proposes a novel approach to enhance the robustness of fine-tuned ASR models by integrating domain-specific adversarial training during the fine-tuning process. Our method generates adversarial examples tailored to the fine-tuned model's task and domain, ensuring a more comprehensive defense against targeted attacks. Experiments demonstrate significant improvements over standard adversarial training methods, highlighting the effectiveness of our approach in mitigating adversarial vulnerabilities in fine-tuned ASR models.

Figure 47: Research idea generated for sample 3 by AI Scientist V2.

Example 3: Generated Idea from Research Agent

Develop a novel fine-tuning method for ASR models that integrates differential privacy and adaptive regularization. Specifically, apply differential privacy during the fine-tuning process by injecting controlled amounts of noise into the gradients, and implement adaptive regularization by dynamically adjusting the strength of the regularizer based on the gradient norms and model complexity.

Figure 48: Research idea generated for sample 3 by the Research Agent.

Example 3: Generated Idea from SFT

The proposed method involves developing a multi-level robustness enhancement framework that incorporates domain-adaptive pre-training with cross-domain adversarial attacks, followed by post-processing using the Gaussian noise injection defense mechanism with selective noise application guided by the detection score from a trained outlier detection model.

Figure 49: Research idea generated for sample 3 by the model Fine-Tuned on ICLR data (SFT).

Example 3: Generated Idea from LDC

A multi-layered defense framework that combines multiple adversarial attacks into one training phase, using a novel perturbation distribution learning algorithm to generate attack samples for each layer, followed by alternating minimization with the Adam optimizer to optimize the model's parameters.

Figure 50: Research idea generated for sample 3 by LDC.

Example 3: Generated Idea from our method - BoN (10)

Propose and implement an ASR fine-tuning mechanism utilizing meta-learning principles designed to detect and mitigate adversarial attacks through continuous adaptation rather than static adversarial training. Specifically, this entails developing a model that integrates differentiable neural processes, allowing it to maintain and update parameters for detecting adversarial inputs based on newly encountered threat data. These parameters would enable the ASR system to improve its ability to recognize and neutralize adversarial samples in real-time, effectively reducing vulnerability to transferred attacks across diverse fine-tuned configurations. The method will focus on incorporating lightweight meta-learning components during fine-tuning to ensure minimal impact on the overall performance while significantly enhancing robustness against adversarial manipulation.

Figure 51: Research idea generated for sample 3 by our method - BoN (10).

H Additional Quantitative Analysis

To further analyze the performance characteristics of our proposed method on 14B 4-bit model against baselines, we visualize the mean scores and standard deviations from our pairwise evaluation protocol.

Figure 52 and Figure 53 illustrate the performance distribution across the ICLR 2024 and NeurIPS 2025 datasets, respectively. While our method achieves superior scores in *Novelty* and *Effectiveness*, it exhibits a lower score in *Feasibility* compared to the Base Model and AI Scientist V2.

Figure 52: **Pairwise Evaluation Scores on ICLR 2024 Dataset.** The plot compares the mean scores of our method against five baselines across Novelty, Feasibility, and Effectiveness. Error bars indicate standard deviation. Our method demonstrates a significant advantage in Novelty and Effectiveness.

Figure 53: **Pairwise Evaluation Scores on NeurIPS 2025 Dataset.** Consistent with the ICLR results, our method maintains a lead in Novelty and Effectiveness, while the Base Model and AI Scientist V2 score higher on Feasibility.

Table 6: Performance comparison across different datasets for unsloth-Qwen2.5-7B. Best scores are **bolded**.

Dataset	Metric	Base Model 7B	Our Method - BoN (10)	GPT Researcher	Research Agent	AI Scientist V2	AI Scientist
ICLR 2024	Absolute Novelty	4.03	**4.18**	3.90	3.75	4.00	-
	Absolute Feasibility	**4.12**	4.10	3.90	3.62	4.05	-
	Absolute Effectiveness	4.40	**4.53**	4.45	4.10	4.25	-
	Pairwise Novelty	2.15	**5.00**	4.40	1.00	3.25	-
	Pairwise Feasibility	**5.00**	1.98	1.00	4.16	3.88	-
	Pairwise Effectiveness	3.60	**5.00**	3.33	1.00	3.79	-
Neurips 2025	Absolute Novelty	4.08	**4.15**	4.03	3.64	4.05	-
	Absolute Feasibility	4.03	3.90	3.79	3.51	**4.18**	-
	Absolute Effectiveness	4.44	**4.59**	4.54	3.77	4.38	-
	Pairwise Novelty	1.93	**5.00**	3.87	1.00	2.89	-
	Pairwise Feasibility	**5.00**	1.05	1.00	1.97	3.54	-
	Pairwise Effectiveness	2.83	**5.00**	3.04	1.00	3.27	-
AI-Scientist	Absolute Novelty	3.75	**4.05**	3.84	3.99	3.8	3.71
	Absolute Feasibility	4.22	4.04	4.17	3.62	4.28	**4.37**
	Absolute Effectiveness	4.41	**4.5**	4.33	4.25	4.22	4.1
	Pairwise Novelty	1.93	**5.0**	3.3	3.35	2.59	1.00
	Pairwise Feasibility	3.89	1.39	2.31	1.00	3.52	**5.00**
	Pairwise Effectiveness	3.51	**5.00**	3.19	1.77	3.51	1.00