SeqMatchNet: Contrastive Learning with Sequence Matching for Place Recognition & Relocalization

Abstract: Visual Place Recognition (VPR) for mobile robot global relocalization is a well-studied problem, where contrastive learning based representation training methods have led to state-of-the-art performance. However, these methods are mainly designed for single image based VPR, where sequential information, which is ubiquitous in robotics, is only used as a post-processing step for filtering single image match scores, but is never used to guide the representation learning process itself. In this work, for the first time, we bridge the gap between single image representation learning and sequence matching through *SeqMatchNet* which transforms the single image descriptors such that they become more responsive to the sequence matching metric. First, we propose a novel triplet loss formulation where the distance metric is based on *sequence matching*, that is, the aggregation of temporal order-based single-image Euclidean distances. We use the same metric for mining negatives online during the training which helps the optimization process by selecting appropriate positives and harder negatives. To overcome the computational overhead of sequence matching for negative mining, we propose a 2D convolution based formulation of sequence matching for efficiently aggregating distances within a distance matrix computed using single images. We show that our proposed method achieves consistent gains in performance as demonstrated on four benchmark datasets. Source code will be made publicly available.

Keywords: Relocalization, Place Recognition, Sequences, Contrastive Learning

1 Introduction

In the context of mobile robotics, Visual Place Recognition (VPR) is defined as the task of recognizing previously seen places by matching currently observed images with those stored in the reference map [1, 2, 3]. It is one of the key capabilities of a mobile robot and is required for the task of visual localization, either in the form of coarse location estimation [4, 5] given a prior map or for loop closures and mapping in visual SLAM [6, 7]. These VPR-driven tasks are relevant for many practical robotic applications, including driverless cars, last mile delivery and exploratory rovers.

One of the main challenges in VPR is scene appearance variations as a place can be revisited during a different time of day, season or weather conditions, for example, nighttime [8] or snowy conditions [9]. Under such difficult scenarios, classical feature encoding techniques often fail [10, 11, 12, 13]. Hence, learning-based techniques have been developed for both local [14, 15] and global feature representations [4, 16, 17]. In VPR, learning a single image descriptor has been accomplished by both classification [17, 18] and contrastive representation learning [4, 19] type approaches. While these single image based methods address the appearance challenges to some extent, dealing with significant perceptual aliasing typically requires the use of additional information in the form of image sequences [20, 21, 22, 23, 24].

In the VPR literature, several sequence-based models have been explored including the use of DTW [25], linear diagonal search [21], graphs [23] and particle filters [26]. Most of these methods follow an underlying common principle of aggregating match scores obtained by comparing single image representations. The community has thus focused on both the aspects, that

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

is, learning more robust single image global descriptors through a variety of deep learning techniques [4, 16, 19, 17, 27, 28] and developing robust sequence matching techniques [29, 30, 31, 32] – *but in isolation*. That is, single image representations are learnt without ever considering the subsequent task of sequence score aggregation (or sequence matching). Thus, there remains a disconnect between the two, as the latter never guides the learning process of the former. In this paper, we address this issue through triplet-loss based contrastive learning with the following key contributions:

- for the first time, we integrate sequence matching in the VPR training pipeline, bridging the gap between learning single image descriptors and sequence matching;
- we propose a sequence matching metric based on temporal order-preserved average of Euclidean distances for both computing triplet loss and mining negatives; and
- finally, to overcome the computational overhead of sequence matching for negative mining, we propose a novel, GPU-friendly 2D convolutions based distance matrix computation method.

We show that transforming an existing single image descriptor by directly optimizing it for sequence matching using the latter both as a loss function and for negative mining leads to superior performance, as compared to traditional formulations based on single image based distance metrics.

2 Related Work

A detailed literature review on VPR is provided in [1, 3, 33, 2]. Here, we cover the recent VPR literature involving learning-based and sequence-based techniques, and related literature that employs triplets-based contrastive learning techniques.

2.1 Learning for VPR

Recent advances in deep learning using CNNs have led to significant progress in the VPR literature, where superior performance was first achieved by simply using off-the-shelf deep-learnt image encoders [34, 35] for image retrieval [36] and place recognition [37], followed by analyses of different CNN layers and training data suitability [38, 39]. Several works exist that employ off-the-shelf CNNs in unique ways to improve VPR [40, 41, 42, 31, 43, 44, 45]. Learning directly for VPR, one of the most notable works, NetVLAD [4], re-established the well-known local feature aggregation technique: VLAD (Vector of Locally Aggregated Descriptor) [13] by employing a deep-learnt image encoder, a learnable VLAD layer and triplets-based contrastive learning. The follow-up literature has explored learning methods both in the context of feature aggregation and learning method types.

Chen et al. [17] trained AMOSNet and HybridNet on a place classification task to later use the learnt features as place representations. DeLF [46] and its recent global descriptor adaptation with DeLG [18] learnt features through a landmark recognition task. Sarlin et al. [27] proposed HF-Net employing knowledge distillation for simultaneously learning local and global features. Different pooling techniques such as GeM [16, 19], NetBoW [47, 48], NetFV [47], pyramid pooling [49, 50], max pooling [7], and graph attention pooling [51] have also been explored to learn robust image representations. Other learning based methods include descriptor standardization [52, 39], autoencoders [53], CapsuleNet [54] based feature segregation [55], and omnidirectional CNNs [56]. However, all these methods are specifically designed for single image based representation learning and are agnostic to any subsequent sequential processing.

2.2 Sequences for VPR

Use of sequential information in VPR is known to improve robustness against perceptual aliasing as more visual evidence becomes available to disambiguate false matches, which are otherwise hard to prevent through limited information or occasional transient noise within single images. Ho and Newman [20] proposed dynamic programming based sub-sequence searching to detect loop closures given a matrix of single image based distances. Milford and Wyeth [21] proposed SeqSLAM, a sequence searching VPR method based on local velocity search within a column-normalized score matrix. SMART [57] adapted SeqSLAM with the use of odometry information to deal with the velocity-sensitivity problem. Along the same lines, Lynen et al. [29] transformed the distance matrix to obtain "placial indices" and computed vote density using odometry information to form

Figure 1: SeqMatchNet: (a) Images are encoded using an existing single image representation method and then a fully connected layer with bias is used as the learnable linear transform. The resultant *single* image descriptors are then processed as a sequence for computing triplet loss. Euclidean distance is only computed between *temporally corresponding* descriptors, say for the anchor and positive sequence, which is then averaged to obtain sequence matching distance d_{ap}. (b) For online negative mining, the distance matrix $\mathbb{M}_{single}$ (obtained from single image descriptor comparisons) is convolved with an Identity matrix $\mathbb{I}_L$ to efficiently compute sequence matching distances.

a "placeless" place recognition system. A number of follow-up works [22, 58, 23, 59, 60] have proposed novel sequence searching techniques to robustly estimate place match hypotheses, for example, by using models based on Network Flow [22], HMM [61], Directed Acyclic Graph [23], kNN-DTW [25], and Particle Filter [26, 62, 32]. However, all of these methods are agnostic to the underlying feature representation techniques and do not use any learning-based mechanisms.

2.3 Triplet Loss and Contrastive Learning

Contrastive learning is used to learn a representation of the given signal by pulling closer the associated signals in contrast to other signals in the dataset [63, 64]. It has been employed for face verification [65], dimension reduction [66], object detection [67], video alignment [68], action recognition [69, 70], and several other tasks in scene understanding [71, 72, 73, 63, 74, 75]. Loss formulations typically differ among these methods; examples include noise-contrastive loss [76], normalized temperature based cross entropy loss [63], and max margin-based triplet loss [77] which is also used in this work. In the context of sequential imagery or videos, self-supervised triplet generation is quite common, as the positives can be sampled using either temporal proximity [78], 'clips' from within the same video [79, 80], another view of the same scene [81], or a different video from the same known cluster [82]. All of these methods aggregate frame-wise information explicitly by channel-wise concatenation of individual frames with 2D CNNs [70] or implicitly by encoding clips through a 3D CNN [79, 69, 80]. The supervisory signal in most of these methods is either based on strict timestamps [78] or nearby frames/clips [79, 82]. Contrary to that, *frame-level correspondences* are available for place recognition datasets through GPS or other sensors. This aids in defining supervised loss functions for accurate sequence alignment where order information can be explicitly enforced, unlike unordered set-based matching methods [83, 84, 85].

2.4 Learning with sequences for VPR

Recent work in VPR has started to explore learning based techniques for sequence-based methods but have mainly focused on generating sequential descriptors as a *single summary vector* representation of a sequence of images. This includes online discriminative learning of memory cells [86], end-to-end multi-view learning via feature grouping, fusion and recurrence [87, 88], learning descriptor grouping for sequence matching optimization [89], unsupervised coresets based summarization [90], topological map learning via recurrence [91], unsupervised change-based descriptor adaptation [92], and supervised 1D temporal convolution based hierarchical VPR [93]. Although [87, 93] use sequential information with triplet loss, the learnt representation is a weighted combination of a sequence of images that results in a single summary vector, thus doing away with the need for sequence matching within the triplet loss. In this work, single image representations are adapted independent of the sequential information, and sequential information is only introduced as the matching metric when defining the loss function.

3 SeqMatchNet

Here, we present all the components of *SeqMatchNet* (see Figure 1). We first explain how the existing single image representations are transformed; then we present our training framework which includes the triplet loss, sequence matching metric and convolutions-based distance matrix computation for negative mining; and finally, we describe the test time sequential query retrieval process.

3.1 Image Representation

Given an image I, its corresponding descriptor $X \in \mathbb{R}^D$ is assumed to be pre-computed using an existing single image representation method. This descriptor is linearly transformed to $X' \in \mathbb{R}^D$ using a learnable fully-connected layer with weight matrix $W \in \mathbb{R}^{D \times D}$ and bias $B \in \mathbb{R}^D$.

$$X' = WX + B \tag{1}$$

X' is l2-normalized before computing distances. W and B are shared across all the descriptors and also when computing triplets, as explained next.

3.2 Training

Here, we present the training pipeline including contrastive triplet loss and the use of sequence matching as a distance metric both for computing loss and mining negatives.

Contrastive Triplet Loss: Our objective is to learn X' such that for any given *anchor* image descriptor X'_a, its distance from a *positive* image descriptor X'_p (belonging to a nearby physical location) is smaller than its distance from a *negative* image descriptor X'_n (belonging to a far-off physical location) by a certain margin (m). That is, the contrastive max-margin triplet loss $\mathcal{L}$ is defined as:

$$\mathcal{L} = max(d_{ap} - d_{an} + m, 0) \tag{2}$$

Sequence-based Distance Metric: In most existing works, the distance computation in the aforementioned triplet loss formulation is based on single summary vector metrics [4, 87]. In this work, we instead use a sequence of image descriptors of length L centered at any given single image descriptor to define a distance metric, inspired by well-established sequence matching methods [21, 57, 23, 94, 93]. Thus, for a temporally-ordered list of images within a sequence, order-corresponding pairwise Euclidean distances are computed between any two sequences centered at X'_i and X'_j, and then averaged to obtain the sequence matching distance[1] (see Figure 1):

$$d_{ij} = 1/L \sum_{t=-L/2}^{L/2} \|X'_{i+t} - X'_{j+t}\|_2 \tag{3}$$

The above sequential order-preserving distance measure is practical for many robotic applications, for example, autonomous driving, where an agent navigates repeatedly through the same route, especially when a shorter metric span (short sequence) is considered. Unlike several existing video-based learning methods [78, 79, 70, 69, 82], the availability of motion and position information (odometry/GPS) from robot's sensor data allows sub-sampling of image sequences using a fixed metric separation while also providing frame-to-frame correspondence across reference and query databases [6, 21, 4]. This enables simplified supervision with the help of the proposed distance metric and loss formulation for the task of visual place recognition, unlike unordered set-based matching metrics used in other domains [83, 84, 85].

Using sequence-based matching during training as proposed has a threefold effect. *1)* It *simultaneously* optimizes for L consecutive descriptors – this prevents the system from over-focusing on any one single descriptor within a sequence which is too hard (a positive or a negative) to optimize standalone (as in traditional approaches) but might only have a minimal impact on the aggregated sequence distance. *2)* Since the individual descriptors within a sequence are matched in a temporal-order preserving manner, the anchor-positive distance so achieved is ideally the lowest – this prevents the system from unnecessarily optimizing for all possible combinations of anchors

---

[1]$\mathbf{d}_{ij}$ follows all the distance metric properties since it is an average of an ordered list of Euclidean distances.

and positives within a certain localization radius, e.g. trying to minimize a full $L \times L$ distance matrix between an anchor and a positive sequence as opposed to ideally minimizing only the diagonal elements of that matrix. *3)* As an aggregated distance is computed between an anchor and a negative through sequence matching, the negatives selected online during training are harder than those which would have been selected when using single image based training – this gives priority to those regions of the environment where several consecutively-occurring negatives make it difficult to avoid perceptual aliasing. While all the aforementioned effects highlight the benefits of using sequence matching over single matching, other alternative strategies can also be defined for temporal order-preserved contrastive learning.

Distance Matrix Computation for Negative Mining: Matching sequences of image descriptors naturally comes at an additional cost of computation. This becomes a bottleneck during training when searching for hard negatives in a large reference database. Since most of the sequence-based VPR datasets are long vehicular trajectories of the environment, it is typical to first compute a distance matrix through single image descriptor comparisons. This distance matrix is then further processed to obtain sequence matching scores [20, 21, 5]. Leveraging GPUs' high computational compatibility with convolution operations, we propose an efficient 2D convolution based approach to compute sequence-based distance matrix $\mathbb{M}_{seq}$ by convolving an identity matrix $\mathbb{I}_L$ with the single descriptor-based distance matrix $\mathbb{M}_{single}$:

$$\mathbb{M}_{seq}(i,j) = \mathbb{I}_L * \mathbb{M}_{single}(i,j)/L \tag{4}$$

The above formulation computes the mean of the diagonal elements of $\mathbb{M}_{single}$ as $\mathbb{I}_L$ strides along its rows (reference database) and columns (query database), thus the outcome is the same as that of Equation 3.

3.3   Testing

Sequential Query Retrieval: During the test time, query images are retrieved using sequences of length L centered at each query image. In the batch approach of sequence matching (Equation 4) for mining negatives during training, all the queries of the train set were available beforehand. For the test time, similar to an online operation, we assume query images to be accrued incrementally. Thus, we re-use Equation 4 for computing sequence matching distances but perform convolutions only along the rows of the matrix $\mathbb{M}_{single}$. Using the resultant distance matrix $\mathbb{M}_{seq}$, a reference image with the lowest sequence matching distance is retrieved as a match for any given query sequence.

4   Experimental Settings

4.1   Datasets

We use four datasets to present results in a few different settings, as explained below. The dataset splits details and visualizations are provided in the supplementary material.

Nordland [9]:   This dataset is comprised of 728 km rail journey repeated under four seasons. We use its Summer traverse as the reference database and Winter traverse as the query, and for both of them train/val/test splits are defined with geographical separation. We remove the image frames where the vehicle was stationary or passing through tunnels [38, 95] Since this dataset is vastly different from the road/street imagery datasets described next, we only use it for an ablation study of loss and negative mining method types (see Section 5.1).

Oxford Robotcar [8]:   This dataset comprises several 10 km traverses of Oxford captured over an year under substantially different appearance conditions. We use the left stereo images from the traverse ids: 2015-03-17-11-08-44 and 2014-12-16-18-44-24 which respectively form our daytime reference database and nighttime query.

Brisbane City Loop [96]:   This dataset comprises two 38 km traverses of Brisbane: City Loop Day and City Loop Night, which are used as reference and query respectively. We use Oxford Robotcar and Brisbane City Loop datasets for cross-testing generalization capabilities of models trained on each city, following the protocol of [93] from where the datasets were sourced. Since the

Oxford traverse is much smaller than the Brisbane one, a common validation set is defined for both the methods using the Brisbane dataset, and train/test splits are defined for each city individually.

Mapillary Street Level Sequences (MSLS) [88]: This dataset comprises short image sequences of street-view imagery captured from a variety of camera configurations, several different cities and under a range of appearance conditions. For all the cities, reference and query databases are pre-defined [88]. We used Melbourne for training, Austin for validation and Amman for testing.

4.2 Pre-processing and Evaluation

We used NetVLAD with PCA+Whitening [4] as our image descriptor of size $D = 4096$, computed by downsampling images to a resolution of 640×320. The linearly transformed learnt descriptors are retained to be of the same size D to enable fair comparison against vanilla NetVLAD baselines. For the sequence matching distance, $L = 5$ is used for both training and testing. For testing, localization radius of 10 meters, 20 meters and 10 frames is used respectively for Oxford, Brisbane/MSLS and Nordland[2] dataset. We use Recall@K [97] as the evaluation metric as also used by previous works [4, 93, 87, 95]. It is defined as the ratio of queries that are correctly matched within its top-K retrieved images to the total number of queries. Please refer to the supplementary material for training parameters details.

5 Results and Discussion

In this section, we first present the key results of improving VPR using sequence matching within the training pipeline both as a loss function and for mining negatives, which is compared against the vanilla method of using single image based distance metrics. We then visualize the distance margins to observe the effect of learning descriptor transformation. Then, we present results for cross-city testing of models trained on different cities to observe generalization trends. Finally, we present results for state-of-the-art VPR comparisons considering a variety of sequence-based approaches.

5.1 Sequence Matching based Loss and Negative Mining

Table 1 shows how the choice of matching metric affects the recall performance when defining the loss and mining negatives. For this, we consider Equation 3 for computing loss and negatives during training using a sequence length of 1 or 5, referred to as *Single* and *SeqMatch* respectively in Table 1. Results reported on the train/test splits of each of the three datasets are based on the use of sequence matching for test-time query retrieval. It can be observed that given the retrieval task of sequence matching, using SeqMatch as a metric during training for *both* loss and mining leads to superior performance for all the datasets (last row: SeqMatch-SeqMatch) as compared to when not using it at all (first row: Single-Single). Furthermore, when using a cross-combination (second and third row), use of SeqMatch either retains or improves performance. In particular, it can be observed that the Oxford dataset necessarily requires SeqMatch-based loss to improve performance, leading to an absolute increase in Recall@1 by 3%. On the other hand, the Nordland dataset benefits more from SeqMatch-based mining, leading to a 7% absolute performance improvement. This study shows the importance of optimizing single image descriptors for sequence matching-based VPR using SeqMatch as the metric (Equation 3) during training.

Table 1: Ablation study of different loss types and mining types for sequence-based VPR using Recall@K (1/5/20).

	Loss Type	Mining Type	Oxford	Nordland	Brisbane
Existing:	Single	Single	0.76/0.89/0.97	0.59/0.75/0.86	0.50/0.62/**0.75**
Proposed:	SeqMatch	Single	**0.79/0.90**/0.97	0.61/0.76/0.87	**0.51**/0.62/0.74
	Single	SeqMatch	0.76/0.89/0.97	**0.66/0.81/0.91**	**0.51/0.63/0.75**
	SeqMatch	SeqMatch	*0.78*/0.89/0.97	**0.66/0.81/0.91**	**0.51/0.63/0.75**

---

[2]In the Nordland dataset, consecutive frames are approximately 20 meters apart and it is common to use this dataset with units of localization radius as frames instead of meters [9, 97, 87, 93]

| (a) Nordland | (b) Oxford |

Figure 2: Latent space distance vs relative frame separation between a query and its nearby reference images. Distance margin, that is, the difference between the trough and the peak values of a curve is relatively higher when using SeqMatchNet-based NetVLAD transformation (blue) than using Vanilla SeqMatch+NetVLAD (orange).

5.2 Visualizing Distance Margins

In Figure 2, we show how the latent space distance margins are affected by the proposed transformation of NetVLAD descriptors via SeqMatchNet (in orange) as compared to when no transformation is performed and vanilla NetVLAD descriptors are used (Vanilla SeqMatch in blue). Both the single image distances (thin opaque lines) and sequence matching distances (semi-transparent thick lines) are plotted against the physical distance (frame-wise or metric) between a query and reference images, selected relative to the ground truth reference image in either direction of the trajectory. The distance values are averaged over 20 uniformly sampled query images. The latent space distance margin can be observed as the difference between the trough and the peak values of a curve. For both the datasets, distance margins are relatively higher when using SeqMatchNet as compared to the vanilla system. Here, we use the Brisbane-trained model on the Oxford test set and the Nordland's train set model on the Nordland's test set. The increase in margin is apparent for both the single image distances and the sequence matching distances.

5.3 Cross-City VPR Performance

In Table 2, we present sequence matching results for training on one city and testing on the other. Even though the environmental conditions vary across different cities, cross-city generalization trends look promising. For example, SeqMatchNet-based Recall@1 for Oxford (0.70) and Brisbane (0.29) during cross-testing is significantly better than the use of sequence matching on top of vanilla NetVLAD which respectively achieves 0.67 and 0.21 (in the first row, referred to as *No Transformation*). A similar trend in relative performance improvements can be observed for MSLS-Amman, where trained models from all three cities lead to higher recall.

Table 2: Cross-City VPR Performance: Recall@K (1/5/20) when training on one city and testing on the other. Best is boldfaced and second best italicized per column.

Train City\Test City	Oxford	Brisbane	MSLS-Amman
No Transformation	0.67/0.79/0.90	0.21/0.27/0.37	0.25/0.34/*0.40*
Oxford	**0.78/0.89/0.97**	*0.29/0.38/0.50*	*0.26*/**0.36/0.41**
Brisbane	*0.70/0.84/0.94*	**0.51/0.63/0.75**	*0.26/0.35*/**0.41**
MSLS-Melbourne	0.58/0.72/0.86	0.22/0.27/0.36	**0.27**/*0.35/0.40*

5.4 Benchmarking against State-of-the-Art Sequence-based Methods

Sequence-based information can be leveraged in different ways to improve single image based VPR performance. In Table 3, we compare against a variety of methods as following. 1) *Sequential descriptors* refer to single summary vector representation constructed through a sequence of images, which includes Smoothing/Averaging [92], Delta Descriptors [92] and SeqNet [93]. 2) *Sequence matching* refers to aggregation of single image based distances which can either be based on the diagonal of the matrix or graph-based path search within the matrix [58, 5]. For the former, we consider SeqNet's single frame version S_1 which is the same as using SeqMatchNet but with $L = 1$ in Equation 3, that is, without guiding single image descriptors with sequence matching metric. For the latter, we consider Graph-based Image Sequence Matcher [58], referred to as GISM, and

Table 3: Comparison against other approaches: Recall@1/5/20 with train/test across cities.

	Methods	Oxford	Brisbane
No Sequence:	NetVLAD [4]	0.47/0.70/0.85	0.20/0.28/0.41
Sequential Descriptor:	Smoothing [92]	0.59/0.72/0.85	0.20/0.25/0.32
	Delta [92]	0.37/0.55/0.74	0.20/0.33/0.50
	SeqNet (S_5) [93]	**0.62/0.76/0.88**	***0.32/0.40/0.55***
Sequence Matching:	NetVLAD [4]	0.67/0.79/0.90	0.21/0.27/0.37
	S_1 [93]	***0.71***/0.83/0.93	0.28/0.36/0.48
	S_1 [93] + GISM [58]	0.65/-/-	0.26/-/-
	S_1 [93] + GRH [5]	0.34/-/-	0.18/-/-
	Ours: SeqMatchNet	0.70/***0.84/0.94***	**0.29/0.38/0.50**
Hierarchical:	HVPR (S_5, S_1) [93]	***0.71***/0.82/0.88	0.29/***0.40/0.55***
	Ours: HVPR (S_5, SeqMatchNet)	***0.71***/0.82/0.88	**0.30/*0.40/0.55***

Graph-based Relocalization using LSH [5], referred to as GRH. 3) *Hierarchical* sequence matching is considered as per [93] where sequential descriptors shortlist candidates for sequence matching. The first row in Table 3 does not use any sequential information and corresponds to single image based VPR baseline. For all other methods, we use a sequence length of $L = 5$. For all methods that use training, results are presented using models trained on the other city. The best results within any block are boldfaced and the overall best are additionally italicized. The underlying single image descriptor for all the methods is either NetVLAD [4] or an adaptation of NetVLAD as cited.

It can be observed that in most cases, use of sequential information improves performance over single image descriptors as expected. SeqMatchNet establishes a new state-of-the-art on the Oxford dataset considering Recall@K(5,20) and achieves the best results on the Brisbane dataset within the sequence matching block. Among the sequential descriptors, SeqNet [93] achieves state-of-the-art results on the Brisbane dataset but these results deteriorate when using S_5 within HVPR due to inferior sequence matching of S_1. However, this is not the case with the HVPR combination of S_5 and SeqMatchNet, where Recall@1 improves over the baseline HVPR while maintaining the overall state-of-the-art Recall@K(5,20). This shows the relevance of improved sequence matching with SeqMatchNet which benefits from the inclusion of sequence matching in its training pipeline.

6 Conclusion

Recent advances in visual place recognition have been accelerated by learning based techniques, which are predominantly governed by single image based distance metrics. The use of sequential information, although well established in the literature, has never been explored in the context of biasing single image representations to suit the subsequent task of sequence matching. In this paper, we bridge this gap for the first time through *SeqMatchNet* and show that overall VPR performance can be improved by including sequence matching in the training pipeline by adapting an existing single image descriptor. For this, we proposed temporal order-preserved average of Euclidean distances as the sequence matching metric which is used to both compute the loss and mine negatives online. To reduce the overhead of sequence matching for the latter, we proposed a novel 2D convolution-based processing of the distance matrix. We established that the single image descriptors learnt through SeqMatchNet are more robust and lead to superior performance with the help of sequence matching metric as opposed to the use of single image matching metrics.

In mobile robotics, localization pipelines are typically comprised of several steps of robustness inducing processes. The same is true of VPR where single image global representation matching is followed by performance enhancement techniques like sequential processing [20, 21], local feature matching [98, 42], feature filtering [99, 100], query expansion [101], and even dimensionality reduction [4]. One can expect that including these subsequent processes in the representation learning process can improve the overall robustness. This work takes a step in that direction by the inclusion of sequence matching in the training itself which leads to consistent performance gains. This study will hopefully encourage the researchers to reconsider the existing VPR and localization pipelines which can benefit from end-to-end task-relevant learning.

References

[1] S. Lowry, N. Sünderhauf, P. Newman, J. J. Leonard, D. Cox, P. Corke, and M. J. Milford. Visual place recognition: A survey. *IEEE Transactions on Robotics*, 32(1):1–19, 2016.

[2] C. Masone and B. Caputo. A survey on deep visual place recognition. *IEEE Access*, 9: 19516–19547, 2021.

[3] S. Garg, T. Fischer, and M. Milford. Where is your place, visual place recognition? In *IJCAI*, 2021.

[4] R. Arandjelovic, P. Gronat, A. Torii, T. Pajdla, and J. Sivic. Netvlad: Cnn architecture for weakly supervised place recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

[5] O. Vysotska and C. Stachniss. Relocalization under substantial appearance changes using hashing. In *Proceedings of the IROS Workshop on Planning, Perception and Navigation for Intelligent Vehicles, Vancouver, BC, Canada*, volume 24, 2017.

[6] M. Cummins and P. Newman. Fab-map: Probabilistic localization and mapping in the space of appearance. *The International Journal of Robotics Research*, 27(6):647–665, 2008.

[7] M. Lopez-Antequera, R. Gomez-Ojeda, N. Petkov, and J. Gonzalez-Jimenez. Appearance-invariant place recognition by discriminatively training a convolutional neural network. *Pattern Recognition Letters*, 92:89–95, 2017.

[8] W. Maddern, G. Pascoe, C. Linegar, and P. Newman. 1 year, 1000 km: The oxford robotcar dataset. *IJ Robotics Res.*, 36(1):3–15, 2017.

[9] N. Sünderhauf, P. Neubert, and P. Protzel. Are we there yet? challenging seqslam on a 3000 km journey across all four seasons. In *Proc. of Workshop on Long-Term Autonomy, IEEE International Conference on Robotics and Automation (ICRA)*, page 2013, 2013.

[10] D. G. Lowe. Distinctive image features from scale-invariant keypoints. *International journal of computer vision*, 60(2):91–110, 2004.

[11] H. Bay, T. Tuytelaars, and L. Van Gool. Surf: Speeded up robust features. In *Eur. Conf. Comput. Vis.*, pages 404–417, 2006.

[12] E. Rublee, V. Rabaud, K. Konolige, and G. Bradski. Orb: An efficient alternative to sift or surf. In *Int. Conf. Comput. Vis.*, pages 2564–2571, 2011.

[13] H. Jégou, M. Douze, C. Schmid, and P. Pérez. Aggregating local descriptors into a compact image representation. In *IEEE Conf. Comput. Vis. Pattern Recog.*, pages 3304–3311, 2010.

[14] D. DeTone, T. Malisiewicz, and A. Rabinovich. Superpoint: Self-supervised interest point detection and description. In *IEEE Conf. Comput. Vis. Pattern Recog. Worksh.*, pages 224–236, 2018.

[15] P.-E. Sarlin, D. DeTone, T. Malisiewicz, and A. Rabinovich. SuperGlue: Learning feature matching with graph neural networks. In *IEEE Conf. Comput. Vis. Pattern Recog.*, pages 4938–4947, 2020.

[16] F. Radenović, G. Tolias, and O. Chum. Fine-tuning cnn image retrieval with no human annotation. *IEEE Trans. Pattern Anal. Mach. Intell.*, 41(7):1655–1668, 2018.

[17] Z. Chen, A. Jacobson, N. Sünderhauf, B. Upcroft, L. Liu, C. Shen, I. Reid, and M. Milford. Deep learning features at scale for visual place recognition. In *Robotics and Automation (ICRA), 2017 IEEE International Conference on*, pages 3223–3230. IEEE, 2017.

[18] B. Cao, A. Araujo, and J. Sim. Unifying deep local and global features for image search. In *European Conference on Computer Vision*, pages 726–743. Springer, 2020.

[19] J. Revaud, J. Almazán, R. S. Rezende, and C. R. d. Souza. Learning with average precision: Training image retrieval with a listwise loss. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 5107–5116, 2019.

[20] K. L. Ho and P. Newman. Detecting loop closure with scene sequences. *International Journal of Computer Vision*, 74(3):261–286, 2007.

[21] M. J. Milford and G. F. Wyeth. Seqslam: Visual route-based navigation for sunny summer days and stormy winter nights. In *Robotics and Automation (ICRA), 2012 IEEE International Conference on*, pages 1643–1649. IEEE, 2012.

[22] T. Naseer, L. Spinello, W. Burgard, and C. Stachniss. Robust visual robot localization across seasons using network flows. In *Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014.

[23] O. Vysotska and C. Stachniss. Lazy data association for image sequences matching under substantial appearance changes. *IEEE Robotics and Automation Letters*, 1(1):213–220, 2016.

[24] S. Garg, N. Sünderhauf, and M. Milford. Semantic-geometric visual place recognition: A new perspective for reconciling opposing views. *The International Journal of Robotics Research*, 2019.

[25] A. Forechi, A. F. De Souza, C. Badue, and T. Oliveira-Santos. Sequential appearance-based global localization using an ensemble of knn-dtw classifiers. In *Neural Networks (IJCNN), 2016 International Joint Conference on*, pages 2782–2789. IEEE, 2016.

[26] E. Pepperell, P. Corke, and M. Milford. Routed roads: Probabilistic vision-based place recognition for changing conditions, split streets and varied viewpoints. *The International Journal of Robotics Research*, 35(9):1057–1179, 2016.

[27] P.-E. Sarlin, C. Cadena, R. Siegwart, and M. Dymczyk. From coarse to fine: Robust hierarchical localization at large scale. *arXiv preprint arXiv:1812.03506*, 2018.

[28] H. Porav, W. Maddern, and P. Newman. Adversarial training for adverse conditions: Robust metric localisation using appearance transfer. In *IEEE Int. Conf. Robot. Autom.*, pages 1011–1018, 2018.

[29] S. Lynen, M. Bosse, P. T. Furgale, and R. Siegwart. Placeless place-recognition. In *3DV*, pages 303–310, 2014.

[30] T. Naseer, W. Burgard, and C. Stachniss. Robust visual localization across seasons. *IEEE Transactions on Robotics*, 2018.

[31] O. Vysotska and C. Stachniss. Effective visual place recognition using multi-sequence maps. *IEEE Robotics and Automation Letters*, 2019.

[32] A.-D. Doan, T.-T. Do, Y. Latif, T.-J. Chin, and I. Reid. Practical visual localization for autonomous driving: Why not filter? *arXiv preprint arXiv:1811.08063*, 2018.

[33] X. Zhang, L. Wang, and Y. Su. Visual place recognition: A survey from deep learning perspective. *Pattern Recognition*, 2020.

[34] A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.

[35] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[36] A. S. Razavian, H. Azizpour, J. Sullivan, and S. Carlsson. Cnn features off-the-shelf: an astounding baseline for recognition. In *Computer Vision and Pattern Recognition Workshops (CVPRW), 2014 IEEE Conference on*, pages 512–519. IEEE, 2014.

[37] Z. Chen, O. Lam, A. Jacobson, and M. Milford. Convolutional neural network-based place recognition. In *Australasian Conference on Robotics and Automation*, volume 2, page 4, 2014.

[38] N. Sünderhauf, S. Shirazi, F. Dayoub, B. Upcroft, and M. Milford. On the performance of convnet features for place recognition. In *Intelligent Robots and Systems (IROS), 2015 IEEE/RSJ International Conference on*, pages 4297–4304. IEEE, 2015.

[39] S. Garg, N. Suenderhauf, and M. Milford. Don't look back: Robustifying place categorization for viewpoint- and condition-invariant place recognition. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2018.

[40] N. Sünderhauf, S. Shirazi, A. Jacobson, F. Dayoub, E. Pepperell, B. Upcroft, and M. Milford. Place recognition with convnet landmarks: Viewpoint-robust, condition-robust, training-free. *Proceedings of Robotics: Science and Systems XII*, 2015.

[41] Z. Chen, F. Maffra, I. Sa, and M. Chli. Only look once, mining distinctive landmarks from convnet for visual place recognition. In *Intelligent Robots and Systems (IROS), 2017 IEEE/RSJ International Conference on*, pages 9–16. IEEE, 2017.

[42] S. Garg, N. Suenderhauf, and M. Milford. Lost? appearance-invariant place recognition for opposite viewpoints using visual semantics. In *Proceedings of Robotics: Science and Systems XIV*, 2018.

[43] Y. Hou, H. Zhang, and S. Zhou. Evaluation of object proposals and convnet features for landmark-based visual place recognition. *Journal of Intelligent & Robotic Systems*, 92(3-4): 505–520, 2018.

[44] Y. Hou, H. Zhang, and S. Zhou. Bocnf: Efficient image matching with bag of convnet features for scalable and robust visual place recognition. *Autonomous Robots*, 42(6):1169–1185, 2018.

[45] M. Zaffar, A. Khaliq, S. Ehsan, M. Milford, and K. McDonald-Maier. Levelling the playing field: A comprehensive comparison of visual place recognition approaches under changing conditions. *arXiv preprint arXiv:1903.09107*, 2019.

[46] H. Noh, A. Araujo, J. Sim, T. Weyand, and B. Han. Large-scale image retrieval with attentive deep local features. In *Int. Conf. Comput. Vis.*, pages 3456–3465, 2017.

[47] A. Miech, I. Laptev, and J. Sivic. Learnable pooling with context gating for video classification. In *IEEE Conf. Comput. Vis. Pattern Recog. Worksh.*, 2017.

[48] E.-J. Ong, S. S. Husain, M. Bober-Irizar, and M. Bober. Deep architectures and ensembles for semantic video classification. *IEEE Trans. Circuits Syst. Video Technol.*, 29(12):3568–3582, 2018.

[49] J. Yu, C. Zhu, J. Zhang, Q. Huang, and D. Tao. Spatial pyramid-enhanced netvlad with weighted triplet loss for place recognition. *IEEE Trans. Neural Netw. Learn. Syst.*, 31(2): 661–674, 2019.

[50] Y. Zhu, J. Wang, L. Xie, and L. Zheng. Attention-based pyramid aggregation network for visual place recognition. In *2018 ACM Multimedia Conference on Multimedia Conference*, pages 99–107. ACM, 2018.

[51] Y. Yang, B. Ma, X. Liu, L. Zhao, and S. Huang. Gsap: A global structure attention pooling method for graph-based visual place recognition. *Remote Sensing*, 13(8):1467, 2021.

[52] S. Schubert, P. Neubert, and P. Protzel. Unsupervised learning methods for visual place recognition in discretely and continuously changing environments. *arXiv preprint arXiv:2001.08960*, 2020.

[53] A. Maldonado-Ramírez and L. A. Torres-Mendez. Learning ad-hoc compact representations from salient landmarks for visual place recognition in underwater environments. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 5739–5745. IEEE, 2019.

[54] S. Sabour, N. Frosst, and G. E. Hinton. Dynamic routing between capsules. *arXiv preprint arXiv:1710.09829*, 2017.

[55] P. Yin, L. Xu, X. Li, C. Yin, Y. Li, R. A. Srivatsan, L. Li, J. Ji, and Y. He. A multi-domain feature learning method for visual place recognition. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 319–324. IEEE, 2019.

[56] T.-H. Wang, H.-J. Huang, J.-T. Lin, C.-W. Hu, K.-H. Zeng, and M. Sun. Omnidirectional cnn for visual place recognition and navigation. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2341–2348. IEEE, 2018.

[57] E. Pepperell, P. Corke, and M. Milford. Towards persistent visual navigation using smart. In *Proceedings of Australasian Conference on Robotics and Automation*. ARAA, 2013.

[58] O. Vysotska, T. Naseer, L. Spinello, W. Burgard, and C. Stachniss. Efficient and effective matching of image sequences under substantial appearance changes exploiting gps priors. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2774–2779. IEEE, 2015.

[59] D. Bai, C. Wang, B. Zhang, X. Yi, and X. Yang. Sequence searching with cnn features for robust and fast visual place recognition. *Computers & Graphics*, 70:270–280, 2018.

[60] R. Arroyo, P. F. Alcantarilla, L. M. Bergasa, and E. Romera. Towards life-long visual localization using an efficient matching of binary sequences from images. In *2015 IEEE international conference on robotics and automation (ICRA)*, pages 6328–6335. IEEE, 2015.

[61] P. Hansen and B. Browning. Visual place recognition using hmm sequence matching. In *Intelligent Robots and Systems (IROS 2014), 2014 IEEE/RSJ International Conference on*, pages 4549–4555. IEEE, 2014.

[62] Y. Liu and H. Zhang. Towards improving the efficiency of sequence-based slam. In *Mechatronics and Automation (ICMA), 2013 IEEE International Conference on*, pages 1261–1266. IEEE, 2013.

[63] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[64] P. Khosla, P. Teterwak, C. Wang, A. Sarna, Y. Tian, P. Isola, A. Maschinot, C. Liu, and D. Krishnan. Supervised contrastive learning. *arXiv preprint arXiv:2004.11362*, 2020.

[65] S. Chopra, R. Hadsell, and Y. LeCun. Learning a similarity metric discriminatively, with application to face verification. In *2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05)*, volume 1, pages 539–546. IEEE, 2005.

[66] R. Hadsell, S. Chopra, and Y. LeCun. Dimensionality reduction by learning an invariant mapping. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, volume 2, pages 1735–1742. IEEE, 2006.

[67] S. Pirk, M. Khansari, Y. Bai, C. Lynch, and P. Sermanet. Online object representations with contrastive learning. *arXiv preprint arXiv:1906.04312*, 2019.

[68] S. Haresh, S. Kumar, H. Coskun, S. N. Syed, A. Konin, M. Z. Zia, and Q.-H. Tran. Learning by aligning videos in time. *arXiv preprint arXiv:2103.17260*, 2021.

[69] A. Singh, O. Chakraborty, A. Varshney, R. Panda, R. Feris, K. Saenko, and A. Das. Semi-supervised action recognition with temporal contrastive learning. *arXiv preprint arXiv:2102.02751*, 2021.

[70] G. Lorre, J. Rabarisoa, A. Orcesi, S. Ainouz, and S. Canu. Temporal contrastive pretraining for video action recognition. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 662–670, 2020.

[71] A. Shrivastava, T. Malisiewicz, A. Gupta, and A. A. Efros. Data-driven visual similarity for cross-domain image matching. In *Proceedings of the 2011 SIGGRAPH Asia Conference*, pages 1–10, 2011.

[72] A. Dosovitskiy, P. Fischer, J. T. Springenberg, M. Riedmiller, and T. Brox. Discriminative unsupervised feature learning with exemplar convolutional neural networks. *IEEE transactions on pattern analysis and machine intelligence*, 38(9):1734–1747, 2015.

[73] T. Park, A. A. Efros, R. Zhang, and J.-Y. Zhu. Contrastive learning for unpaired image-to-image translation. In *European Conference on Computer Vision*, pages 319–345. Springer, 2020.

[74] I. Misra and L. v. d. Maaten. Self-supervised learning of pretext-invariant representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6707–6717, 2020.

[75] J. Spencer, R. Bowden, and S. Hadfield. Defeat-net: General monocular depth via simultaneous unsupervised representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14402–14413, 2020.

[76] M. Gutmann and A. Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In Y. W. Teh and M. Titterington, editors, *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pages 297–304, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR. URL http://proceedings.mlr.press/v9/gutmann10a.html.

[77] F. Schroff, D. Kalenichenko, and J. Philbin. Facenet: A unified embedding for face recognition and clustering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 815–823, 2015.

[78] P. Sermanet, C. Lynch, Y. Chebotar, J. Hsu, E. Jang, S. Schaal, S. Levine, and G. Brain. Time-contrastive networks: Self-supervised learning from video. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 1134–1141. IEEE, 2018.

[79] I. Dave, R. Gupta, M. N. Rizve, and M. Shah. Tclr: Temporal contrastive learning for video representation. *arXiv preprint arXiv:2101.07974*, 2021.

[80] L. Tao, X. Wang, and T. Yamasaki. Self-supervised video representation learning using inter-intra contrastive framework. In *Proceedings of the 28th ACM International Conference on Multimedia*, pages 2193–2201, 2020.

[81] N. Rai, E. Adeli, K.-H. Lee, A. Gaidon, and J. C. Niebles. Cocon: Cooperative-contrastive learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3384–3393, 2021.

[82] R. Qian, T. Meng, B. Gong, M.-H. Yang, H. Wang, S. Belongie, and Y. Cui. Spatiotemporal contrastive video representation learning. *arXiv preprint arXiv:2008.03800*, 2020.

[83] J. Ribera, D. Guera, Y. Chen, and E. J. Delp. Locating objects without bounding boxes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6479–6489, 2019.

[84] H. Fan, H. Su, and L. J. Guibas. A point set generation network for 3d object reconstruction from a single image. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 605–613, 2017.

[85] P. Fang, P. Ji, L. Petersson, and M. Harandi. Set augmented triplet loss for video person re-identification. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 464–473, 2021.

[86] V. A. Nguyen, J. A. Starzyk, and W.-B. Goh. A spatio-temporal long-term memory approach for visual place recognition in mobile robotic navigation. *Robotics and Autonomous Systems*, 61(12):1744–1758, 2013.

[87] J. M. Facil, D. Olid, L. Montesano, and J. Civera. Condition-invariant multi-view place recognition. *arXiv preprint arXiv:1902.09516*, 2019.

[88] F. Warburg, S. Hauberg, M. López-Antequera, P. Gargallo, Y. Kuang, and J. Civera. Mapillary street-level sequences: A dataset for lifelong place recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2626–2635, 2020.

[89] H. Zhang, F. Han, and H. Wang. Robust multimodal sequence-based loop closure detection via structured sparsity. In *Robotics: Science and systems*, 2016.

[90] M. Volkov, G. Rosman, D. Feldman, J. W. Fisher, and D. Rus. Coresets for visual summarization with applications to loop closure. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3638–3645. IEEE, 2015.

[91] P. Neubert, S. Schubert, and P. Protzel. A neurologically inspired sequence processing model for mobile robot place recognition. *IEEE Robotics and Automation Letters*, 4(4):3200–3207, 2019.

[92] S. Garg, B. Harwood, G. Anand, and M. Milford. Delta descriptors: Change-based place representation for robust visual localization. *IEEE Robotics and Automation Letters*, 5(4): 5120–5127, 2020.

[93] S. Garg and M. J. Milford. Seqnet: Learning descriptors for sequence-based hierarchical place recognition. *IEEE Robotics and Automation Letters*, 2021.

[94] S. Garg and M. Milford. Fast, compact and highly scalable visual place recognition through sequence-based matching of overloaded representations. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, 2020.

[95] S. Hausler, S. Garg, M. Xu, M. Milford, and T. Fischer. Patch-netvlad: Multi-scale fusion of locally-global descriptors for place recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14141–14152, 2021.

[96] M. Milford, S. Garg, and J. Mount. P1-007: How automated vehicles will interact with road infrastructure now and in the future. Technical report, iMove, QUT and Queensland Government, January 2020. URL https://imoveaustralia.com/wp-content/uploads/2020/02/P1-007-Milestone-6-Final-Report-Second-Revision.pdf.

[97] M. Zaffar, S. Garg, M. Milford, J. Kooij, D. Flynn, K. McDonald-Maier, and S. Ehsan. Vprbench: An open-source visual place recognition evaluation framework with quantifiable viewpoint and appearance change. *International Journal of Computer Vision*, pages 1–39, 2021.

[98] M. Cummins and P. Newman. Appearance-only slam at large scale with fab-map 2.0. *The International Journal of Robotics Research*, 30(9):1100–1123, 2011.

[99] J. Knopp, J. Sivic, and T. Pajdla. Avoiding confusing features in place recognition. In *European Conference on Computer Vision*, pages 748–761. Springer, 2010.

[100] S. Garg, V. Babu, T. Dharmasiri, S. Hausler, N. Suenderhauf, S. Kumar, T. Drummond, and M. Milford. Look no deeper: Recognizing places from opposing viewpoints under varying scene appearance using single-view depth estimation. In *IEEE Int. Conf. Robot. Autom.*, pages 4916–4923, 2019.

[101] O. Chum, A. Mikulik, M. Perdoch, and J. Matas. Total recall II: Query expansion revisited. In *IEEE Conf. Comput. Vis. Pattern Recog.*, pages 889–896, 2011.