LMA: Latent Motion Adjuster for Physics-based Multi-agent Interaction

Abstract

Learning interactive multi-agent behaviors from scratch is often sample-inefficient and fails to exploit reusable skills learned in simpler settings. While latent skill representations enable efficient single-agent reinforcement learning, their extension to multi-agent interaction requires conditioning behaviors on other agents without destroying pretrained structure. We formulate multi-agent interaction as a latent adaptation problem and propose the Latent Motion Adjuster (LMA), a lightweight conditional module that modifies latent actions produced by a pretrained single-agent policy based on other agents' states. Rather than relearning policies from scratch, our method performs structured residual adaptation in latent space, enabling efficient skill reuse under both cooperative and competitive scenarios. Experiments on physics-based control benchmarks demonstrate that latent-space adaptation improves sample efficiency and interaction performance over fine-tuning and strategic baselines. These results suggest that conditional latent modulation provides a principled mechanism for transferring single-agent skills to multi-agent reinforcement learning.

1 Introduction

Learning physically consistent control policies for embodied agents remains a central challenge in reinforcement learning. Early approaches to character and robot control relied on carefully designed dynamic controllers (Ijspeert, 2008; Raibert & Hodgins, 1991), imitation learning from human demonstrations (Schmidts et al., 2011; Schaal, 1999), or end-to-end reinforcement learning (Levine et al., 2016; Johannink et al., 2019). Although effective in specific tasks, these methods typically require task-specific training and often struggle to maintain natural, physically plausible behaviors under distributional shift.

Recent advances in hierarchical reinforcement learning address this limitation by introducing motion priors, i.e., pretrained latent skill representations that capture diverse and physically valid behaviors. Such representations have demonstrated strong transferability across downstream tasks in character animation (Peng et al., 2022; Tessler et al., 2023), VR avatar control (Luo et al., 2023; 2024a), and real robot control (Serifi et al., 2024). By learning compact latent spaces aligned with physical constraints, high-level policies can efficiently adapt to new objectives while preserving motion realism. Extensions of these ideas to multi-agent settings have also been explored; however, most prior approaches learn interaction policies from scratch in the multi-agent phase (Zhu et al., 2023; Liu et al., 2022; Won et al., 2022), which limits sample efficiency and reduces the benefit of previously acquired single-agent skills.

In this work, we reformulate multi-agent interaction as a latent adaptation problem. Rather than relearning high-level policies for interactive settings, we propose to reuse single-agent skills and condition them on other agents through structured modulation in latent space. Concretely, we introduce the Latent Motion Adjuster (LMA), a lightweight conditional module that refines latent actions produced by a pretrained single-agent policy based on the observed state of other agents. This design enables efficient skill reuse while allowing policies to dynamically respond to cooperative or adversarial behavior.

We instantiate the proposed framework on physics-based control benchmarks involving whole-body humanoid agents in cooperative and competitive scenarios. Empirical results demonstrate that latent-space adaptation achieves stronger interaction performance and improved learning efficiency compared to fine-tuning

Figure 1: Overview of Latent Motion Adjuster (LMA): By adjusting motions represented in the latent space based on the observed behaviors of other agents, this approach leverages skills learned in the single-agent setting while enabling advanced cooperation and competition in multi-agent interactions.

or learning-from-scratch baselines. These findings suggest that conditional latent modulation provides a principled mechanism for transferring single-agent skills to multi-agent reinforcement learning.

The main contributions of this work are summarized as follows:

- We formulate multi-agent interaction as a latent skill adaptation problem and propose a multi-agent learning framework that reuses pretrained single-agent policies instead of learning interaction policies from scratch.

- We introduce the Latent Motion Adjuster (LMA), a lightweight conditional module that performs structured residual modulation in latent space, enabling policies to adapt to other agents while preserving pretrained skill structure.

- We empirically demonstrate that conditional latent adaptation improves interaction performance and sample efficiency compared to fine-tuning and learning-from-scratch baselines in physics-based multi-agent control benchmarks.

2 Related Work

2.1 Motion Prior

With the advancement of motion capture technology and human motion estimation from videos, numerous large-scale datasets covering diverse human motions have been proposed (Mahmood et al., 2019; Sigal et al., 2010). The motion prior is a motion generator that learns compact latent motion representations capable of reproducing such diverse human motions in a simulation. The pretrained motion prior is subsequently reused as a controller to generate motions for downstream tasks. By learning high-level policies to control the latent motions, it can quickly acquire effective actions for target tasks such as sword slashing (Peng et al., 2022; Tessler et al., 2023), javelin throwing (Luo et al., 2024b), or waltz dancing (Cui et al., 2024).

Several prior studies have proposed the use of the motion prior not only for single-agent control but also for multi-agent interactions (Zhu et al., 2023; Liu et al., 2022; Won et al., 2022; Han et al., 2024). However, these studies typically learn multi-agent interactions from scratch and do not leverage high-level policies acquired by a single agent, as our research does. The study by (Han et al., 2024) is similar to our method in that it reuses single-agent policies for multi-agent interactions. However, it learns a strategic-level policy that outputs sub-goals for single-agent policies, whereas our method directly adjusts the latent motions generated by single-agent policies.

Figure 2: Structure and training flow of the proposed method. 1: Pre-training stage where the latent motion representation of the motion prior is acquired by imitating the motion clip dataset. 2: Task stage where the high-level policy is learned to control the latent motion of the motion prior according to the given task. 3: Multi-agent interaction stage where the latent motion adjuster is trained to adjust the latent motion output by the high-level policy according to the opponent's state.

2.2 Multi-agent Reinforcement Learning Utilizing Skill Transfer

The acquisition of cooperative and adversarial policies among multiple agents has been a long-standing challenge within the framework of multi-agent reinforcement learning (MARL) (Zhang et al., 2021; Yu et al., 2022). Generally, MARL involves learning policies for multiple agents simultaneously. On the other hand, many methods have also been proposed to leverage past experiences for immediate responses to multi-agent interactions. (Won et al., 2021) developed a mixture-of-experts learning framework that adapts to tasks requiring multi-agent interactions by combining skills acquired through prior imitation learning. (Haarnoja et al., 2024) achieved dynamic skill switching in soccer using actual humanoid robots through a two-stage learning process involving single-agent skill acquisition and multi-agent interactions via self-play. However, these methods require the preparation of multiple skills in advance, making it challenging to respond to multi-agent interactions by adjusting only a single skill, such as a motion prior.

3 Methods

The training process of the proposed method consists of three stages: 1) Pre-training stage: A motion prior is trained to acquire a latent motion representation by imitating a diverse set of motion clips. 2) Task stage: A high-level policy is learned to control the latent motion of the motion prior in order to solve specific downstream tasks. 3) Multi-agent interaction stage: A latent motion adjuster is trained to modulate the latent motions generated by the high-level policy based on the state of an opponent (Fig. 2).

The overall policies are trained using a VAE-based model architecture (Kingma & Welling, 2014), with each stage contributing to the progressive construction of the final controller. Details of each stage are described in the following sections.

3.1 Learning Latent Motion Representation of Motion Prior

In the pre-training stage, the motion encoder and the motion prior are trained to imitate various character's motions (left of Fig. 2). The motion encoder $\pi_e(\mathbf{z}_t|\mathbf{s}_t, \bar{\mathbf{s}}_{1:T})$ generates latent motions $\mathbf{z}_t \in \mathbb{R}^{d_z}$ from the agent's proprioceptive state $\mathbf{s}_t \in \mathbb{R}^{d_s}$ and the reference motion clip $\bar{\mathbf{s}}_{1:T}$ sampled from the motion clip dataset $\mathcal{M}$. Then, the motion prior $\pi_l(\mathbf{a}_t|\mathbf{s}_t, \mathbf{z}_t)$ outputs actions $\mathbf{a}_t \in \mathbb{R}^{d_a}$ from the agent's state $\mathbf{s}_t$ and the

---

Algorithm 1 Pre-training stage

Input: Motion clip dataset $\mathcal{M}$, pretrained PHC+ π_{PHC+}, encoder π_e, motion prior π_l, and prior distribution $\mathcal{R}$

1: **while** not converged **do**
2:     $\mathcal{D} \leftarrow \emptyset$
3:     **while** $\mathcal{D}$ not full **do**
4:         $\bar{\mathbf{s}}_{1:T} \sim \mathcal{M}$
5:         **for** $t \leftarrow 1 \ldots T$ **do**
6:             $\mathbf{z}_t \sim \pi_e(\mathbf{z}_t|\mathbf{s}_t, \bar{\mathbf{s}}_{1:T})$
7:             $\mathbf{a}_t \sim \pi_l(\mathbf{a}_t|\mathbf{s}_t, \mathbf{z}_t)$
8:             $\mathbf{a}_t^{\text{PHC+}} \sim \pi_{\text{PHC+}}(\mathbf{a}_t^{\text{PHC+}}|\mathbf{s}_t, \bar{\mathbf{s}}_{1:T})$
9:             store $(\mathbf{s}_t, \mathbf{z}_t, \mathbf{a}_t, \mathbf{a}_t^{\text{PHC+}})$ into $\mathcal{D}$
10:             $\mathbf{s}_{t+1} \sim p(\mathbf{s}_{t+1}|\mathbf{s}_t, \mathbf{a}_t)$
11:         **end for**
12:     **end while**
13:     Update $\pi_e, \pi_l, \mathcal{R}$ using pairs of $(\mathbf{s}_t, \mathbf{z}_t, \mathbf{a}_t, \mathbf{a}_t^{\text{PHC+}})$ and Equation 1
14: **end while**
15: **return** $\pi_e, \pi_l, \mathcal{R}$

---

latent variable $\mathbf{z}_t$. Here, $\mathbf{s}_t$ and $\bar{\mathbf{s}}_{1:T}$ typically represent ego-centric states that include the positions and velocities of the character's body parts. The environment transitions to the next state $\mathbf{s}_{t+1}$ based on the transition probability $p(\mathbf{s}_{t+1}|\mathbf{s}_t, \mathbf{a}_t)$.

This study specifically follows the PULSE training flow (Luo et al., 2024a). In PULSE, a controller called PHC+ is separately prepared and trained to imitate the motions in the motion clip dataset. PHC+ achieves high performance, but directly outputs actions $\mathbf{a}_t^{\text{PHC+}}$ from $\pi_{\text{PHC+}}(\mathbf{a}_t^{\text{PHC+}}|\mathbf{s}_t, \bar{\mathbf{s}}_{1:T})$ without utilizing latent motion representations. To address this, PULSE treats the actions output by PHC+ as teacher data and trains a motion encoder and decoder to mimic the actions of PHC+ minimizing the following reconstruction error $\mathcal{L}$,

$$
\begin{aligned}
\mathcal{L} = &||\mathbf{a}_t^{\text{PHC+}} - \mathbf{a}_t||^2 + \alpha\mathcal{L}_{reg} + \\
&\beta D_{KL}[\pi_e(\mathbf{z}_t|\mathbf{s}_t, \bar{\mathbf{s}}_{1:T})||\mathcal{R}(\mathbf{z}_t|\mathbf{s}_t)],
\end{aligned}
\tag{1}
$$

where $\mathcal{L}_{reg}$ is an additional regularization term for consecutive latent motions, $\mathcal{R}(\mathbf{z}_t|\mathbf{s}_t)$ is the prior distributions of the latent motions, and α and β are hyperparameters. When the encoder distribution is modeled as a normal distribution $\mathcal{N}(\mathbf{z}_t|\boldsymbol{\mu}_t, \boldsymbol{\sigma}_t)$, $\mathcal{L}_{reg}$ constrains the distance between the centers $||\boldsymbol{\mu}_t - \boldsymbol{\mu}_{t-1}||^2$. PULSE also uses a learned conditional prior distribution $\mathcal{R}(\mathbf{z}_t|\mathbf{s}_t)$ in the KL constraint instead of a zero-mean Gaussian prior. By pretraining the motion prior through these interactions, the policy capable of generating diverse actions included in the motion clip dataset $\mathcal{M}$, and a latent space that represents these motions can be acquired. Algorithm 1 outlines the pre-training stage.

3.2 Learning Latent Motion Control for Downstream Task

In the task stage, we learn a high-level policy $\pi_h(\mathbf{z}_t|\mathbf{s}_t, \mathbf{s}_t^g)$ that outputs the latent variable $\mathbf{z}_t$ of the motion prior on the basis of the agent's state $\mathbf{s}_t$ and task-dependent state $\mathbf{s}_t^g$ (middle of Fig. 2). The motion prior is fixed, and the high-level policy is trained to maximize the following cumulative rewards,

$$
\mathcal{J}_g = \mathbb{E}_{p(\boldsymbol{\tau})}^{\pi_h}\left[\sum_{t=1}^{T} \gamma^{t-1} r_t^g\right],
\tag{2}
$$

where r_t^g is the task-dependent reward $r_t^g = r_g(\mathbf{s}_t, \mathbf{s}_t^g, \mathbf{a}_t)$, $\mathbb{E}_{p(\boldsymbol{\tau})}^{\pi_h}[\cdot]$ is the expected value over the trajectory $\boldsymbol{\tau} = [\mathbf{s}_1, \mathbf{s}_1^g, \mathbf{a}_1, r_1^g, \cdots, \mathbf{s}_{T-1}, \mathbf{s}_{T-1}^g, \mathbf{a}_{T-1}, r_{T-1}^g, \mathbf{s}_T, \mathbf{s}_T^g]$ by following π_h, and γ is the discount factor. By training the high-level policy in the task stage, it becomes possible to leverage the natural motion generation of the motion prior while acquiring actions suitable for the target task. Algorithm 2 outlines the task stage.

Algorithm 2 Task stage

Input: pretrained motion prior π_l, and high-level policy π_h

1: **while** not converged **do**
2:      $\mathcal{D} \leftarrow \emptyset$
3:      **while** $\mathcal{D}$ not full **do**
4:          **for** $t \leftarrow 1 \ldots T$ **do**
5:              $\mathbf{z}_t \sim \pi_h(\mathbf{z}_t | \mathbf{s}_t, \mathbf{s}_t^g)$
6:              $\mathbf{a}_t \sim \pi_l(\mathbf{a}_t | \mathbf{s}_t, \mathbf{z}_t)$
7:              $\mathbf{s}_{t+1}, \mathbf{s}_{t+1}^g \sim p(\mathbf{s}_{t+1}, \mathbf{s}_{t+1}^g | \mathbf{s}_t, \mathbf{s}_t^g, \mathbf{a}_t)$
8:              $r_t^g \leftarrow r_g(\mathbf{s}_t, \mathbf{s}_t^g, \mathbf{a}_t)$
9:              store $(\mathbf{s}_t, \mathbf{s}_t^g, \mathbf{z}_t, \mathbf{a}_t, r_t^g, \mathbf{s}_{t+1}, \mathbf{s}_{t+1}^g)$ into $\mathcal{D}$
10:          **end for**
11:      **end while**
12:      Update π_h using Equation 2 and experiences collected in $\mathcal{D}$
13: **end while**
14: **return** π_h

3.3 Latent Motion Adjustment for Multi-agent Interaction

Similar to the task stages discussed in the previous section, the goal of the agents in the multi-agent interaction stage is to maximize the following cumulative rewards,

$$\mathcal{J}_{mi} = \mathbb{E}_{p(\boldsymbol{\tau})}^{\pi_h} \left[\sum_{t=1}^{T} \gamma^{t-1} r_t^{mi} \right], \tag{3}$$

where $r_t^{mi} = r_{mi}(\mathbf{s}_t, \mathbf{s}_t^g, \mathbf{s}_t^{mi}, \mathbf{a}_t)$ is the reward that reflect the quality of interactions among multiple agents. However, unlike when learning single-agent tasks, agents are required to output appropriate actions $\mathbf{a}_t$ based on the observed opponent's states $\mathbf{s}_t^{mi}$.

While prior researches generally involve learning high-level policies from scratch for multi-agent interactions, the proposed method aims to efficiently acquire policies for multi-agent interactions by leveraging skills obtained from single-agent tasks (Right of Fig. 2). The challenge of reusing single-agent skills in this manner lies in addressing the differences in observations received between single-agent tasks and multi-agent interaction tasks. As previously mentioned, in multi-agent interactions, it is necessary to consider the opponent's states $\mathbf{s}_t^{mi}$ in addition to the states received from the environment in single-agent tasks $(\mathbf{s}_t, \mathbf{s}_t^g)$. High-level policies acquired from single-agent tasks cannot directly input $\mathbf{s}_t^{mi}$ as they are. However, deciding actions without using $\mathbf{s}_t^{mi}$ makes it difficult to appropriately adjust actions based on the current states of the opponent, thereby hindering advanced cooperation and adversarial motions.

To address the challenge of reusing single-agent skills, we add a small model called a latent motion adjuster π_{LMA} that can fine-tune the output of the high-level policy based on the opponent's states (Right side of Fig. 2). As shown in the following equation, π_{LMA} outputs an increment $\Delta\mathbf{z}_t$ to adjust the latent motion based on the latent motion $\mathbf{z}_t$ output by the high-level policy π_h and the current state of the opponent $\mathbf{s}_t^{mi}$,

$$\Delta\mathbf{z}_t \sim \pi_{LMA}(\Delta\mathbf{z}_t | \mathbf{s}_t^{mi}, \mathbf{z}_t). \tag{4}$$

The latent motion is adjusted to $\mathbf{z}'_t = \mathbf{z}_t + \eta\Delta\mathbf{z}_t$, where η is a hyperparameter that determines the degree of adjustment for latent motion. Then, by inputting the adjusted latent motion $\mathbf{z}'_t$ into the motion prior π_l, the agent generates action $\mathbf{a}_t$ that consider the opponent's state. By learning the adjustment method of π_{LMA} according to Equation 4, the proposed method can effectively utilize skills acquired from single-agent tasks while generating advanced cooperative and adversarial motions for multi-agent interactions. Algorithm 3 outlines the multi-agent interaction stage.

Algorithm 3 Multi-agent interaction stage

Input: pretrained motion prior π_l and high-level policy π_h, latent motion adjuster π_{LMA}, and hyperparameter η

1: **while** not converged **do**
2:     $\mathcal{D} \leftarrow \emptyset$
3:     **while** $\mathcal{D}$ not full **do**
4:        **for** $t \leftarrow 1 \ldots T$ **do**
5:           $\mathbf{z}_t \sim \pi_h(\mathbf{z}_t | \mathbf{s}_t, \mathbf{s}_t^g)$
6:           $\Delta\mathbf{z}_t \sim \pi_{LMA}(\Delta\mathbf{z}_t | \mathbf{s}_t^{mi}, \mathbf{z}_t)$
7:           $\mathbf{z}'_t \leftarrow \mathbf{z}_t + \eta\Delta\mathbf{z}_t$
8:           $\mathbf{a}_t \sim \pi_l(\mathbf{a}_t | \mathbf{s}_t, \mathbf{z}'_t)$
9:           $\mathbf{s}_{t+1}, \mathbf{s}_{t+1}^g, \mathbf{s}_{t+1}^{mi} \sim$
    $p(\mathbf{s}_{t+1}, \mathbf{s}_{t+1}^g, \mathbf{s}_{t+1}^{mi} | \mathbf{s}_t, \mathbf{s}_t^g, \mathbf{s}_t^{mi}, \mathbf{a}_t)$
10:          $r_t^{mi} \leftarrow r_{mi}(\mathbf{s}_t, \mathbf{s}_t^g, \mathbf{s}_t^{mi}, \mathbf{a}_t)$
11:          store $(\mathbf{s}_t, \mathbf{s}_t^g, \mathbf{s}_t^{mi}, \mathbf{z}_t, \Delta\mathbf{z}_t, \mathbf{a}_t, r_t^{mi},$
    $\mathbf{s}_{t+1}, \mathbf{s}_{t+1}^g, \mathbf{s}_{t+1}^{mi})$ into $\mathcal{D}$
12:        **end for**
13:     **end while**
14:     Update π_h using Equation 3 and experiences collected in $\mathcal{D}$
15: **end while**
16: **return** π_{LMA}

---

4 Experiments

4.1 Environments

We used simulated table tennis and tennis environments in SMPLOlympics (Luo et al., 2024b), in which a physics simulator IsaacGym (Makoviychuk et al., 2021) is used to control agents (Fig. 1). The proprioceptive state $\mathbf{s}_t = [h_{root}, \mathbf{p}_{body}, \mathbf{v}_{body}, \boldsymbol{\theta}_{body}, \boldsymbol{\omega}_{body}] \in \mathbb{R}^{358}$ consisted of the height of the agent's pelvis $h_{root} \in \mathbb{R}^1$ and the position $\mathbf{p}_{body} \in \mathbb{R}^{3\times(24-1)}$, velocity $\mathbf{v}_{body} \in \mathbb{R}^{3\times24}$, 6DoF rotation representation $\boldsymbol{\theta}_{body} \in \mathbb{R}^{6\times24}$, and rotational velocity $\boldsymbol{\omega}_{body} \in \mathbb{R}^{3\times24}$ of 24 body parts as seen from the pelvis. The rotation representation uses (Zhou et al., 2019). Action $\mathbf{a}_t \in \mathbb{R}^{3\times23}$ is target joint angles for 23 joints, which are converted into torques using PD control.

In the task stage, $\mathbf{s}_t^g = [\mathbf{p}_{ball}, \mathbf{v}_{ball}, \mathbf{p}_{racket}, \mathbf{p}_{self}^*, \mathbf{p}_{ball}^*] \in \mathbb{R}^{15}$ consisted of the ball position $\mathbf{p}_{ball} \in \mathbb{R}^3$, ball velocity $\mathbf{v}_{ball} \in \mathbb{R}^3$, racket position $\mathbf{p}_{racket} \in \mathbb{R}^3$, the agent's target positions at the time of ball impact $\mathbf{p}_{self}^* \in \mathbb{R}^3$, and the target position for the ball's landing $\mathbf{p}_{ball}^* \in \mathbb{R}^3$. We used the reward r_t^g designed in SMPLOlympics, which is intended to encourage hitting the ball back to the target position on the opponent's court. The experimental details, including the specific reward design, are provided in the supplementary material.

In the multi-agent interaction stage, we conducted experiments with two types of tasks: rallies for cooperation and competitive matches. In both tasks, $\mathbf{s}_t^{mi} = [\mathbf{p}_{op}, \mathbf{p}_{racket\_op}] \in \mathbb{R}^6$ consisted of the positions of the opponent $\mathbf{p}_{op} \in \mathbb{R}^3$ and opponent's racket $\mathbf{p}_{racket\_op} \in \mathbb{R}^3$ as seen from the agent. In the rally task, we used r_t^g as the reward r_t^{mi}. The cumulative reward of r_t^g increases the longer the rally with the opponent continues, thus encouraging the acquisition of cooperative motions that return the ball in a way that is easy for the opponent to hit. On the other hand, in the match task, the reward r_t^{mi} was a combination of r_t^g and the match reward r_{match}, which is designed to encourage the acquisition of adversarial motions to defeat the opponent by giving a significantly larger reward compared to r_t^g when winning the match and a penalty when losing the match. In this experiment, we assigned a reward r_{match} of 100 for a win and a penalty of -100 for a loss.

While the observations and rewards for table tennis and tennis are similar, the skills required for learning differ significantly. In table tennis, minimal lower-body movement is required, and the primary skill involves

returning the ball using only arm control. In contrast, tennis requires moving to the ball's landing position and returning it using the entire body. By evaluating the proposed method across these qualitatively distinct tasks, we validated its versatility and applicability as a general-purpose approach. Moreover, the proposed method is not restricted to the presented tasks and can be broadly applied. The motion prior used in our approach is trained on diverse human motion datasets, making it applicable not only to the racket movements shown in this paper but also to a wide range of downstream tasks. Furthermore, the inputs to both the task policy and the LMA consist of ego-centric representations of positions and velocities for each body part of the agent, the manipulated object, and the opponent. We consider this input representation to be generic and applicable to a wide range of tasks.

4.2 Training Procedure

To implement the proposed method, we pre-trained the motion prior π_l and high-level policy π_h. As mentioned earlier, We used PULSE (Luo et al., 2024a) for training of the motion prior and high-level policy. In the pre-training stage, we utilized an off-the-shelf motion prior learned from the AMASS dataset (Mahmood et al., 2019). In the task stage, sufficient training time was allocated for both table tennis and tennis until the cumulative rewards converged, allowing the agents to acquire the skill to return the ball to specified positions. In the multi-agent interaction stage, we adopted self-play and trained both agent and opponent using alternating optimal strategies from (Won et al., 2021).

Unlike the task stage, in the multi-agent interaction stage, the decision of where to return the ball is arbitrary. In this study, we interpret the target position of the ball included in $\mathbf{s}_t^g$ in the multi-agent interaction stage as a self-determined target position and evaluated the proposed method in two scenarios: one where this value is set randomly and another where it is determined using the strategic-level network described later.

We executed 512 Isaac Gym environments in parallel on a Geforce RTX A6000, and both π_h and π_{LMA} were trained according to the rollouts collected using PPO (Schulman et al., 2017). We constructed both policies with a standard MLP, and the dimension of the latent motion d_z was set to 32. π_h had three hidden layers with dimensions of 2048, 1024, and 512, respectively. On the other hand, π_{LMA} had two hidden layers with dimensions of 1024 and 512, respectively. As hyperparameters during training, we set $\alpha = 0.005$, $\gamma = 0.99$ and $\eta = 0.0001$. We annealed β from 0.01 to 0.001. Additionally, the learning rate was set to 2×10^{-5}, and the frequency of agent swapping in self-play was set to once every 500 steps.

4.3 Baselines

To verify the performance of the proposed method, we compared the following four baselines: (i) learning the high-level policy from scratch (PULSE (from scratch)), (ii) fine tuning of the high-level policy (PULSE (fine tuning)), (iii) strategic-level learning (PULSE + SEPMC (Han et al., 2024)), and (iv) learning the high-level policy with KL prior (PULSE + KL (simplified (Liu et al., 2022))). Method (i) learns the high-level policy from scratch as prior studies. Method (ii) perform additional learning on the high-level policy acquired in single-agent tasks without $\mathbf{s}_t^{mi}$. Method (iii) applies PULSE to (Han et al., 2024) and learns a strategic-level policy that outputs sub-goals, such as the ball target position, which the high-level policy takes as input. Method (iv) is a simplified version of (Liu et al., 2022). It adds a penalty based on KL divergence between the latent motion distributions output by the newly learned high-level policy and the pre-trained high-level policy. In (Liu et al., 2022), population-based training (Jaderberg et al., 2017) is also employed to simultaneously learn multiple hyper-parameters. However, this approach is computationally expensive and deviates from the rapid adaptation to multi-agent interactions. Therefore, it was not adopted in our experiments.

We evaluated the proposed method in four configurations: (v) fixing the parameters of the high-level policy and training only the latent motion adjuster (PULSE + LMA (ours w/ freeze)), (vi) simultaneously training both the high-level policy and the latent motion adjuster (PULSE + LMA (ours w/o freeze)), (vii) method (v) further enhanced with the strategic-level network from (Han et al., 2024) (PULSE + LMA + SEPMC (ours w/ freeze)) , and (viii) method (vi) further enhanced with the strategic-level network from (Han et al., 2024) (PULSE + LMA + SEPMC(ours w/o freeze)).

Figure 3: Comparison of learning performance with baseline methods in multi-agent cooperative tasks.

Figure 4: Example movements generated during cooperative multi-agent tasks (Green: Agent, Orange: Opponent). Top: Table tennis, Bottom: Tennis.

As previously mentioned, the ball's target positions in methods (iii), (vii) and (viii) were determined using the strategic-level network, while random target positions were assigned for the other methods.

5 Results

5.1 Cooperation in Multi-agent Interaction

Figure 3 shows the learning curve of each method for cooperative behavior learning in table tennis and tennis, indicating the average and standard deviation of the cumulative reward $\mathcal{J}$ over three trials. Additionally, Figure 4 illustrates examples of the motions for each method at a specific moment during multi-agent cooperation.

Method (i) and (iv) start by learning the basic motions required to hit the ball from scratch, which necessitates a significant amount of time for multi-agent interaction training. Consequently, within the range of 10,000 learning steps, they were unable to acquire adequate ball-hitting behaviors. Method (ii) resulted in low cumulative rewards because it returns the ball without considering the opponent's state. Although Method (iii) considers the opponent's state, it similarly achieves low cumulative rewards. This is likely because learning only ball's target position makes it challenging to fine-tune behaviors according to the opponent's state. The proposed method (v) shows high cumulative rewards in the very early stages of learning, demonstrating its ability to quickly adapt to the opponent's state. However, similar to method (iii), merely fine-tuning the latent motions is insufficient for acquiring advanced cooperative behaviors, leading

Figure 5: The average number of rallies for each method (*: $p < 0.05$, **: $p < 0.01$).

to rapid convergence. On the other hand, the proposed methods (vi) and (viii), which simultaneously learn the high-level policy, shows slower initial performance but achieves significantly high cumulative rewards in table tennis and tennis compared to other methods, enabling longer rallies. This is likely due to its ability to perform flexible motion adjustments that cannot be addressed through fine-tuning alone.

Figure 5 shows the mean and standard deviation of the rally counts based on 10000 rally trial using the models of each method after 20,000 learning steps. We extracted 100 mean values of rally counts obtained from 100 rally trials each, thereby transforming them to follow a normal distribution under the central limit theorem. We assessed group differences using Welch's ANOVA (Welch, 1951). As the result was significant ($p < 0.01$), post hoc comparisons were conducted using the Games–Howell test (Games & Howell, 1976). * and ** indicate statistical significance at $p < 0.05$ and $p < 0.01$, respectively. For both table tennis and tennis rally counts, the proposed methods (vi) and (viii) achieve significantly higher rally counts compared to the other methods.

Sensitivity of LMA to Observations   To verify whether the LMA can adjust the latent motion according to the observed opponent state, we conducted a Sobol sensitivity analysis (Sobolı, 2001; Saltelli, 2002), a method that quantifies how each input dimension contributes to the variability of a model's output by decomposing the output variance into components attributable to each input. Using 10,000 observation samples obtained from the proposed methods (v) and (vi), we computed the range of possible values for each input dimension of the LMA. Within these ranges, we generated $1000 \times (2 \times 38 + 2) = 78,000$ samples using the Saltelli sampler. We then applied PCA to Δz, the output of LMA, and measured the contribution of each input dimension to the variance of each principal component.

Figure 6 presents the results of the Sobol sensitivity analysis for LMA in both table tennis and tennis. The left column corresponds to method (v), and the right column corresponds to method (vi). S1 denotes the first-order indices, and ST represents the total-order indices. From top to bottom, bar charts show the sensitivity indices for the first to third principal components of Δz. The horizontal axis of each bar chart represents the input dimensions of LMA, ordered as follows: the dimensions of the latent motion z output by the high-level policy, the x, y, and z components of the opponent's position $\mathbf{p}_{op}$, and the x, y, and z components of the opponent's racket position $\mathbf{p}_{racket\_op}$. Here, the x-axis is aligned with the sideline, while the y-axis is parallel to the endline or baseline. Method (v), which uses a fixed high-level policy, allows many input dimensions to influence the output of the LMA, whereas method (vi), which jointly trains the high-level policy, results in the LMA being affected only by the opponent's state.

From the results of method (vi) in Figure 6, we can also observe that the LMA adjusts the latent motion by selectively focusing on different opponent-related input dimensions depending on the environment. In table

Figure 6: Sobol sensitivity analysis results for LMA (top: table tennis, bottom: tennis. left: method (v), right: method (vi)).

Figure 7: Ball return position visualization for method (vi) in the table tennis rally task

tennis, the opponent's racket position in the x-direction is the most influential factor, whereas in tennis, the agent's behavior varies according to the opponent's z-coordinate. Figure 7 visualizes the locations on the table where the agent returned the ball under method (vi), conditioned on the opponent's racket x-coordinate. The figure provides a top-down view of the opponent's side of the table, where the opponent's racket x-coordinate at the moment the agent hits the ball is grouped into three categories (near: 2.5 m, medium: 3.0 m, and far: 3.5 m). The colors represent the return probability for each region, with brighter

Figure 8: Ball return position visualization for method (vi) in the tennis rally Task

Figure 9: Elo score of each method in multi-agent competitive tasks.

areas indicating higher frequencies of ball bounces under that condition. It shows that the agent appropriately adjusts its behavior to ensure that the ball bounces at a suitable height near the opponent's hitting point: when the opponent's racket is close, the ball is returned to bounce near the center of the table, whereas when the racket is farther away, the ball is returned to bounce closer to the table's edge. Similar to Figure 7, Figure 8 visualizes how the ball's landing position on the opponent's court changes under method (vi) when the opponent's z-coordinate is grouped into three categories (low: -0.3 m, medium: 0.0 m, and high: 0.3 m). In the single-agent setting, the learned behaviors primarily consist of low-center-of-gravity backhand shots and high-center-of-gravity forehand shots. Figure 8 suggests that the agent exploits this tendency: when the opponent's center of gravity is low, the agent returns the ball toward the left side of the court, where backhand shots are easier to execute, whereas when the opponent's center of gravity is high, the agent directs the ball toward the right side, facilitating forehand shots.

5.2 Competition in Multi-agent Tennis Matches

Figure 9 shows the transitions of Elo scores (Elo, 1967) for each method in the competitive tasks for table tennis and tennis. The Elo score is an indicator of an agent's strength and is commonly used for evaluating competitive outcomes. We dumped the weights of each method every 2000 learning steps during the training process of the competitive tasks in table and tennis across three trials. The results of methods (i) and (iv) were excluded as they did not sufficiently acquire ball-hitting motions. Consequently, a total of 108 models were prepared by dumping weights six times during training for each of the six remaining methods across three trials. We conducted a round-robin tournament using these models, where each pair of models played 100 matches. Elo scores were calculated based on the win-loss results for each model combination. In the

Figure 10: Ball landing positions on the opponent's court when using method (vi) for multi-agent interactions in tennis.

table tennis task, it can be observed that the proposed methods (vi) and (viii) become significantly stronger as training progresses. This indicates that the proposed method successfully acquires advanced competitive behaviors. Unlike the table tennis task, in the tennis tasks, the transitions of Elo scores do not improve across all methods, including the proposed methods (vi) and (viii). This is due to the insufficient performance of the policies acquired in the single-agent stage, resulting in certain strategies that the agents are unable to adapt to. In the single-agent task, the motion of returning the ball from in front of the endline is rarely learned. Therefore, the proposed method acquires an adversarial policy that returns the ball to a position closer to the net, which is more difficult for the opponent.

Figure 10 shows the landing positions of the ball on the opponent's court when returned using the proposed method (vi) in both the tennis rally task and the tennis match task. The first ball's landing point is indicated by a circle, and the second ball's landing point is indicated by a triangle. In the cooperative task of the tennis rally, the ball is returned to bounce once near the back of the opponent's court so that it rebounds towards the opponent's racket. However, in the competitive task, many trajectories are aimed to bounce once near the net. As a result, the ball often lands twice within the court before the opponent can return it. To acquire more advanced competitive motions, it is desirable to perform additional training in situations where the agent was unable to respond effectively. We plan to develop a continuous skill improvement framework that relearns the weaknesses of agents identified in multi-agent interactions. Additionally, while the proposed method can adapt its actions based on the opponent's immediate state, it does not infer the opponent's strategy. Consequently, it is difficult for the method to acquire globally optimal behaviors, such as anticipating a drop shot and moving forward preemptively. Developing advanced strategic interactions based on opponent strategy inference remains a challenge for future work.

6 Conclusion and Future Works

In this paper, we propose a new method that utilize both motion prior and single-agent task policy for multi-agent interaction. By learning a latent motion adjuster that adjusts the latent motion output by the single-agent task policy based on the opponent's state, it becomes possible to utilize the skills acquired in the single-agent setting while outputting appropriate actions according to the opponent's state. Through simulated sport tasks, we verified that the proposed method achieved higher cooperative and competitive motions at a comparable or faster learning speed than conventional methods. Applying this method to diverse multi-agent interaction tasks that require advanced strategies, including making significant changes to action selection based on the opponent's intentions, remains a challenge for future work.

References

Jieming Cui, Tengyu Liu, Nian Liu, Yaodong Yang, Yixin Zhu, and Siyuan Huang. AnySkill: Learning Open-Vocabulary Physical Skill for Interactive Agents. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 852–862, 2024.

Arpad E Elo. The proposed uscf rating system, its development, theory, and applications. *Chess life*, 22(8): 242–247, 1967.

Paul A. Games and John F. Howell. Pairwise Multiple Comparison Procedures with Unequal N's and/or Variances: A Monte Carlo Study. *Journal of Educational Statistics*, 1(2):113–125, June 1976. ISSN 0362-9791. doi: 10.3102/10769986001002113.

Tuomas Haarnoja, Ben Moran, Guy Lever, Sandy H. Huang, Dhruva Tirumala, Jan Humplik, Markus Wulfmeier, Saran Tunyasuvunakool, Noah Y. Siegel, Roland Hafner, Michael Bloesch, Kristian Hartikainen, Arunkumar Byravan, Leonard Hasenclever, Yuval Tassa, Fereshteh Sadeghi, Nathan Batchelor, Federico Casarini, Stefano Saliceti, Charles Game, Neil Sreendra, Kushal Patel, Marlon Gwira, Andrea Huber, Nicole Hurley, Francesco Nori, Raia Hadsell, and Nicolas Heess. Learning agile soccer skills for a bipedal robot with deep reinforcement learning. *Science Robotics*, 9(89):eadi8022, April 2024. doi: 10.1126/scirobotics.adi8022.

Lei Han, Qingxu Zhu, Jiapeng Sheng, Chong Zhang, Tingguang Li, Yizheng Zhang, He Zhang, Yuzhen Liu, Cheng Zhou, Rui Zhao, Jie Li, Yufeng Zhang, Rui Wang, Wanchao Chi, Xiong Li, Yonghui Zhu, Lingzhu Xiang, Xiao Teng, and Zhengyou Zhang. Lifelike agility and play in quadrupedal robots using reinforcement learning and generative pre-trained models. *Nature Machine Intelligence*, 6(7):787–798, July 2024. ISSN 2522-5839. doi: 10.1038/s42256-024-00861-3.

Auke Jan Ijspeert. Central pattern generators for locomotion control in animals and robots: A review. *Neural Networks*, 21(4):642–653, 2008. ISSN 0893-6080. doi: 10.1016/j.neunet.2008.03.014.

Max Jaderberg, Valentin Dalibard, Simon Osindero, Wojciech M. Czarnecki, Jeff Donahue, Ali Razavi, Oriol Vinyals, Tim Green, Iain Dunning, Karen Simonyan, Chrisantha Fernando, and Koray Kavukcuoglu. Population Based Training of Neural Networks. *arXiv preprint arXiv:1711.09846*, November 2017. doi: 10.48550/arXiv.1711.09846.

Tobias Johannink, Shikhar Bahl, Ashvin Nair, Jianlan Luo, Avinash Kumar, Matthias Loskyll, Juan Aparicio Ojea, Eugen Solowjow, and Sergey Levine. Residual Reinforcement Learning for Robot Control. In *International Conference on Robotics and Automation (ICRA)*, pp. 6023–6029, 2019. doi: 10.1109/ICRA. 2019.8794127.

Diederik P. Kingma and Max Welling. Auto-Encoding Variational Bayes. In *International Conference on Learning Representations (ICLR)*, 2014. doi: 10.48550/arXiv.1312.6114.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-End Training of Deep Visuomotor Policies. *Journal of Machine Learning Research*, 17(39):1–40, 2016. ISSN 1533-7928.

Siqi Liu, Guy Lever, Zhe Wang, Josh Merel, S. M. Ali Eslami, Daniel Hennes, Wojciech M. Czarnecki, Yuval Tassa, Shayegan Omidshafiei, Abbas Abdolmaleki, Noah Y. Siegel, Leonard Hasenclever, Luke Marris, Saran Tunyasuvunakool, H. Francis Song, Markus Wulfmeier, Paul Muller, Tuomas Haarnoja, Brendan Tracey, Karl Tuyls, Thore Graepel, and Nicolas Heess. From motor control to team play in simulated humanoid football. *Science Robotics*, 7(69):eabo0235, 2022. ISSN 2470-9476. doi: 10.1126/scirobotics. abo0235.

Matthew Loper, Naureen Mahmood, Javier Romero, Gerard Pons-Moll, and Michael J. Black. SMPL: A skinned multi-person linear model. *ACM Transactions on Graphics*, 34(6):248:1–248:16, October 2015. ISSN 0730-0301. doi: 10.1145/2816795.2818013.

Zhengyi Luo, Jinkun Cao, Alexander Winkler, Kris Kitani, and Weipeng Xu. Perpetual Humanoid Control for Real-time Simulated Avatars. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 10861–10870, 2023. doi: 10.1109/ICCV51070.2023.01000.

Zhengyi Luo, Jinkun Cao, Josh Merel, Alexander Winkler, Jing Huang, Kris Kitani, and Weipeng Xu. Universal Humanoid Motion Representations for Physics-Based Control. In *International Conference on Learning Representations (ICLR)*, 2024a. doi: 10.48550/arXiv.2310.04582.

Zhengyi Luo, Jiashun Wang, Kangni Liu, Haotian Zhang, Chen Tessler, Jingbo Wang, Ye Yuan, Jinkun Cao, Zihui Lin, Fengyi Wang, Jessica Hodgins, and Kris Kitani. SMPLOlympics: Sports Environments for Physically Simulated Humanoids. *arXiv preprint arXiv:2407.00187*, 2024b. doi: 10.48550/arXiv.2407.00187.

Naureen Mahmood, Nima Ghorbani, Nikolaus F. Troje, Gerard Pons-Moll, and Michael Black. AMASS: Archive of Motion Capture As Surface Shapes. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 5441–5450, 2019. doi: 10.1109/ICCV.2019.00554.

Viktor Makoviychuk, Lukasz Wawrzyniak, Yunrong Guo, Michelle Lu, Kier Storey, Miles Macklin, David Hoeller, Nikita Rudin, Arthur Allshire, Ankur Handa, and Gavriel State. Isaac Gym: High Performance GPU Based Physics Simulation For Robot Learning. In *Neural Information Processing Systems Datasets and Benchmarks Track*, 2021.

Xue Bin Peng, Ze Ma, Pieter Abbeel, Sergey Levine, and Angjoo Kanazawa. AMP: Adversarial motion priors for stylized physics-based character control. *ACM Transactions on Graphics*, 40(4):144:1–144:20, July 2021. ISSN 0730-0301. doi: 10.1145/3450626.3459670.

Xue Bin Peng, Yunrong Guo, Lina Halper, Sergey Levine, and Sanja Fidler. ASE: Large-Scale Reusable Adversarial Skill Embeddings for Physically Simulated Characters. *ACM Transactions on Graphics*, 41(4):1–17, 2022. ISSN 0730-0301, 1557-7368. doi: 10.1145/3528223.3530110.

Marc H. Raibert and Jessica K. Hodgins. Animation of dynamic legged locomotion. *ACM SIGGRAPH Computer Graphics*, 25(4):349–358, 1991. ISSN 0097-8930. doi: 10.1145/127719.122755.

Andrea Saltelli. Making best use of model evaluations to compute sensitivity indices. *Computer Physics Communications*, 145(2):280–297, May 2002. ISSN 0010-4655. doi: 10.1016/S0010-4655(02)00280-1.

Stefan Schaal. Is imitation learning the route to humanoid robots? *Trends in Cognitive Sciences*, 3(6):233–242, 1999. ISSN 1364-6613, 1879-307X. doi: 10.1016/S1364-6613(99)01327-3.

Alexander M. Schmidts, Dongheui Lee, and Angelika Peer. Imitation learning of human grasping skills from motion and force data. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1002–1007, 2011. doi: 10.1109/IROS.2011.6094951.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal Policy Optimization Algorithms. *arXiv preprint arXiv:1707.06347*, 2017. doi: 10.48550/arXiv.1707.06347.

Agon Serifi, Ruben Grandia, Espen Knoop, Markus Gross, and Moritz Bächer. VMP: Versatile Motion Priors for Robustly Tracking Motion on Physical Characters. *Computer Graphics Forum*, 43(8):e15175, 2024. doi: 10.1111/cgf.15175.

Leonid Sigal, Alexandru O. Balan, and Michael J. Black. HumanEva: Synchronized Video and Motion Capture Dataset and Baseline Algorithm for Evaluation of Articulated Human Motion. *International Journal of Computer Vision*, 87(1):4–27, 2010. ISSN 1573-1405. doi: 10.1007/s11263-009-0273-6.

I. M Sobolʹ. Global sensitivity indices for nonlinear mathematical models and their Monte Carlo estimates. *Mathematics and Computers in Simulation*, 55(1):271–280, February 2001. ISSN 0378-4754. doi: 10.1016/S0378-4754(00)00270-6.

Chen Tessler, Yoni Kasten, Yunrong Guo, Shie Mannor, Gal Chechik, and Xue Bin Peng. CALM: Conditional Adversarial Latent Models for Directable Virtual Characters. In *ACM SIGGRAPH 2023 Conference Proceedings*, pp. 1–9, 2023. ISBN 9798400701597. doi: 10.1145/3588432.3591541.

Bernard Lewis Welch. On the comparison of several mean values: an alternative approach. *Biometrika*, 38(3-4):330–336, December 1951. ISSN 0006-3444. doi: 10.1093/biomet/38.3-4.330.

Jungdam Won, Deepak Gopinath, and Jessica Hodgins. Control strategies for physically simulated characters performing two-player competitive sports. *ACM Transactions on Graphics*, 40(4):146:1–146:11, 2021. ISSN 0730-0301. doi: 10.1145/3450626.3459761.

Jungdam Won, Deepak Gopinath, and Jessica Hodgins. Physics-based character controllers using conditional VAEs. *ACM Transactions on Graphics*, 41(4):96:1–96:12, 2022. ISSN 0730-0301. doi: 10.1145/3528223. 3530067.

Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, Alexandre Bayen, and Yi Wu. The Surprising Effectiveness of PPO in Cooperative Multi-Agent Games. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Kaiqing Zhang, Zhuoran Yang, and Tamer Başar. Multi-Agent Reinforcement Learning: A Selective Overview of Theories and Algorithms. In Kyriakos G. Vamvoudakis, Yan Wan, Frank L. Lewis, and Derya Cansever (eds.), *Handbook of Reinforcement Learning and Control*, pp. 321–384. Springer International Publishing, Cham, 2021. ISBN 978-3-030-60990-0. doi: 10.1007/978-3-030-60990-0_12.

Yi Zhou, Connelly Barnes, Jingwan Lu, Jimei Yang, and Hao Li. On the Continuity of Rotation Representations in Neural Networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5745–5753, 2019.

Qingxu Zhu, He Zhang, Mengting Lan, and Lei Han. Neural Categorical Priors for Physics-Based Character Control. *ACM Transactions on Graphics*, 42(6):178:1–178:16, 2023. ISSN 0730-0301. doi: 10.1145/3618397.

A   Appendix

A.1   Experimental Details

We used simulated table tennis and tennis environments in SMPLOlympics (Luo et al., 2024b). These environments utilize a humanoid with the kinematic structure of SMPL (Loper et al., 2015), which has 24 joints, 23 of which are controllable. The control cycle for the humanoid output by the proposed method and baseline methods was set to 30 Hz.

In the table tennis environment, a circular racket with an 8 cm radius is attached 12 cm away from the humanoid's right wrist (Left of Fig. 11). The dimensions of the table and ball conform to standard sizes. The table is 1.525 m wide, 2.74 m long, and 0.76 m tall, with a net height of 15.25 cm, and thw ball has a radius of 2cm.

In the tennis environment, a circular racket with a radius of 15 cm is attached 35 cm away from the humanoid's right wrist (Right of Fig. 11). The dimensions of the court are the same as actual tennis courts, with a width of 8.23 m, a length of 23.77 m. Additionally, the net height is 1 m, ant the ball has a radius of 3.2 cm.

In both environments, at the start of each episode, a ball is launched into the player's court with a random speed and direction. The target position for the ball's landing point $\mathbf{p}^*_{ball}$ is randomly assigned within the opponent's court at the start of each episode or when the opponent returns the ball. In methods that use the strategic-level network described in the main text, this target position is replaced by its output. Additionally, at each time step, the predicted arrival point of the ball at the end line of the agent's court is calculated based on the current ball position and velocity. The agent's target position $\mathbf{p}^*_{self}$ is then set such that the racket aligns with this predicted arrival point. Each episode ends when the ball is missed or goes out of bounds and the outcome of each episode is also determined based on these results in competitive tasks.

A.2   Reward Design and Training Details

In the task stage for both table tennis and tennis, we used task-dependent reward r^g_t designed in SMPLOlympics (Luo et al., 2024b).

Figure 11: Components and sizes of table tennis and tennis.

In table tennis task, we used the following reward,

$$
\begin{aligned}
r_t^g =& \mathbb{I}(N_c = 0) \times e^{-4d_{br}^2 - 4d_{st}^2 - n_z} + \\
& \mathbb{I}(N_c > 0) \times e^{-4d_{st}^2}(e^{-4d_{lt}^2} + 2 + N_o) + \\
& \mathbb{I}((N_c > 0) \wedge (d_{lt} < 0.01)) \times e^{-4d_{st}^2},
\end{aligned}
\tag{5}
$$

where d_{br}, d_{st}, and d_{lt} is the distance between the ball and the racket, the current agent position and the agent's target position $\mathbf{p}_{self}^*$, and the ball's landing position and the target ball position $\mathbf{p}_{ball}^*$, respectively. n_z denotes the z-direction value of the racket's normal. N_c, N_l represent the number of times the ball makes contact with the racket and lands on the court, respectively. N_c and N_l are reset to 0 each time the opponent returns the ball in the multi-agent interaction stage. The first term on the right-hand side of Eq. 5 rewards the agent for adopting a position and posture that makes it easier to return the ball. The second and third term encourage the agent to maintain its position while returning the ball to the target location.

In the tennis task, we used the following reward

$$
\begin{aligned}
r_t^g =& \mathbb{I}(N_c = 0) \times e^{-d_{br}^2 - 2d_{st}^2} + \\
& \mathbb{I}((N_c > 0) \wedge (z_b < 3)) \times e^{-d_{lt}^2}(e^{-2d_{st}^2} + 0.1) + \\
& \mathbb{I}((N_l > 0) \wedge (z_b < 3)) \times (e^{-2d_{st}^2} + 0.1) + \\
& \mathbb{I}((N_l > 0) \wedge (d_{lt} < 0.1)) \times (e^{-2d_{st}^2} + 0.1),
\end{aligned}
\tag{6}
$$

where z_b is the height of the ball.

In the task stage for tennis, we utilized r^{AMP}, the reward from AMP (Peng et al., 2021), in addition to the task-dependent rewards. r^{AMP} reflects the difficulty of distinguishing between motions sampled from the motion dataset and those actually obtained in the simulation, thereby promoting the acquisition of natural motions. We calculated r^{AMP} based on the tennis motion data provided by SMPLOlympics and set the overall reward given during the task stage as $0.5r_t^g + 0.5r_t^{AMP}$. On the other hand, we observed that using r^{AMP} in table tennis significantly reduced performance. This is likely because the provided data consists of motion extracted from videos, and for table tennis, the extraction quality leads to the inclusion of physically inappropriate movements. Therefore, in the task stage for table tennis, we trained the high-level policy using only r_t^g.

As mentioned in the main text, the performance of the high-level policy significantly influences the subsequent performance in multi-agent interactions. Therefore, in the task-stage, training was continued for sufficient time even after the learning curve had approximately converged, and the final weights were used for multi-agent interactions. Specifically, 70,000 steps of training were conducted for table tennis and 180,000 steps

Figure 12: Results of the computation time required for a single action output across each method (*: $p <$ 0.05, **: $p < 0.01$).

for tennis. When running 2,048 Isaac Gym environments in parallel on a Geforce RTX A6000, the training took approximately one to two days.

A.3 Computational costs

Figure 12 shows the results of comparing the computation time required for a single action output across each method. We extracted 100 mean values of computation times obtained from 10000 samples, thereby transforming them to follow a normal distribution under the central limit theorem. We assessed group differences using Welch's ANOVA (Welch, 1951). As the result was significant ($p < 0.01$), post hoc comparisons were conducted using the Games–Howell test (Games & Howell, 1976). * and ** indicate statistical significance at $p < 0.05$ and $p < 0.01$, respectively. Compared with the conventional method that uses only the task policy, the proposed methods—particularly those combined with SEPMC ((vii) and (viii))—require longer computation times. However, both the task policy and the LMA are lightweight two-layer MLPs, which are faster to compute than the simulation update steps. Therefore, the total computational cost required for training remains largely unchanged regardless of whether the LMA is incorporated or the task policy is trained jointly.

A.4 Effect of the Adjustment Scale in LMA

To assess the influence of η, which determines the adjustment scale in LMA, we conducted three training runs for each η value ($[1e{-}8, 1e{-}6, 1e{-}4, 1e{-}2, 1e0]$) in the proposed methods (v) and (vi), and evaluated the resulting learning curves.

Figure 13 shows the results of the learning curves obtained for each value of η. In method (v), $\eta = 1$ yields higher learning performance than the other values, whereas in method (vi), $\eta = 1$ results in lower performance. This suggests that the role of LMA differs depending on whether the high-level policy is trained simultaneously. Under the experimental setting of this study, it is difficult to achieve efficient cooperative behavior using only the high-level policy trained in a single-agent task. In method (v), which uses a fixed high-level policy, LMA functions as a residual reinforcement learning module that compensates for the high-level policy; therefore, setting an adjustment scale comparable to that of the high-level policy is important for effective learning. In contrast, in method (vi), where the high-level policy is trained jointly, LMA serves as an auxiliary component that provides fine-grained adjustments based on the opponent's state. Consequently,

Figure 13: Results of the learning curves obtained for each value of η (left: method (v), right: method (vi)).

assigning an adjustment scale comparable to that of the high-level policy can lead to interference, ultimately degrading performance.