SummEQuAL: Summarization Evaluation via Question Answering using Large Language Models

Abstract

Summarization is hard to evaluate due to its diverse and abstract nature. Although N-gram-based metrics like BLEU and ROUGE are prevalent, they often do not align well with human evaluations. While model-based alternatives such as BERTScore improve, they typically require extensive labelled data. The advent of Large Language Models (LLMs) presents a promising avenue for evaluation. To this end, we introduce SummEQuAL, a novel content-based framework using LLMs for unified, reproducible summarization evaluation. SummEQuAL evaluates summaries by comparing their content with the source document, employing a question-answering approach to gauge both recall and precision. To validate SummEQuAL's effectiveness, we develop a dataset based on MultiWOZ. We conduct experiments on SummEval and our MultiWOZ-based dataset, showing that SummEQuAL largely improves the quality of summarization evaluation. Notably, SummEQuAL demonstrates a 19.7% improvement over QuestEval in terms of sample-level Pearson correlation with human assessments of consistency on the SummEval dataset. Furthermore, it exceeds the performance of the BERTScore baseline by achieving a 17.3% increase in Spearman correlation on our MultiWOZ-based dataset. Our study illuminates the potential of LLMs for a unified evaluation framework, setting a new paradigm for future summarization evaluation.

1 Introduction

Summary evaluation remains a complex task, and to this day, it cannot be adequately accomplished by automatic metrics (Chen et al., 2022; Goyal et al., 2022). While N-gram-based metrics like BLEU (Papineni et al., 2002) and ROUGE (Lin, 2004) are widely used, yet they often show a poor correlation with human judgment, particularly in content assessment (Kasai et al., 2022a; Reiter and Belz, 2009). In addition, these methods rely on references as a "gold standard", which diminishes their effectiveness especially when assessing varied and abstract summaries due to the limited availability of reference texts. Summary evaluation has higher requirements for diversity and accuracy.

The rise of Large Language Models (LLMs) offers a promising way to evaluate generative texts more effectively, due to their understanding and reasoning abilities. While previous studies have been conducted in various contexts, such as machine translation Kocmi and Federmann (2023) and summarization (Chen et al., 2023; Fu et al., 2023; Liu et al., 2023) (without relying on reference summarization), the use of LLMs for evaluation has its limitations. Specifically, it typically has a large variation across different prompts and LLMs, which complicates the use of a unified evaluation framework. While the question-answering (QA) approach offers a structured method for evaluation to mitigate this issue, existing QA approaches still have several limitations (Durmus et al., 2020; Manakul et al., 2023; Scialom et al., 2021; Wang et al., 2020): (1) previous works are more confined to direct answers, and answers based on reasoning or hidden information are often tricky; (2) models in generating questions lack focus so they may introduce irrelevant information; and (3) models always need expensive pre-training and the performance will be influenced by the coverage and quality of training data.

To address these issues, we propose a novel unified framework for summarization evaluation *SummEQuAL*, which can effectively identify abstract information across a wide range of topics and perform complex inference. Specifically, SummEQuAL simplifies the evaluation process by breaking it down into two separate tasks with five steps and conducts QA per human instruction to approximate human-like evaluation. It guides LLMs with a structured schema to identify key information and

A: Abstract the text's key points from a given schema. The key points are up to 30 words. Avoid any minor details or examples unless they are crucial for understanding the topic. If the text does not mention a schema element, ignore that element and do not include this key point in your output. Out put a JSON, where ......
<Schema>Schema</Schema><Text>Text</Text>

B: Generate up to 20 binary questionanswer pairs derived from all specific details in the provided summary. Ensure that the answers are either 'Yes' or 'No,' and the questions should be binary queries like 'Did xxx ...?' or 'Is it true that ...?'. Keep generating questions until all details from the summary have been covered, and avoid irrelevant questions. Out put a JSON, where ......
<Summary>Summary</Summary>

C: Evaluate the presence of key points within a given summary. If a key point is mentioned in the summary, provide the relevant sentence as a citation. If the key point is completely absent, output 'Not found' as the citation. Assign a score of 1 for mentioned, 0.5 for partially mentioned, and 0 for completely absence. Ensure your evaluation is derived from your understanding of the text and not based on simple matching. Output a JSON, where...... <Summary>Summary</Summary> <Key Points>Key Points</Key Points>

D: Answer the following questions using the provided text. Responses should be 'Yes' or 'No.' If you cannot find any relevant content in the text to answer a question, respond with 'Not found'. Before presenting your conclusion, explain your thought process. Ensure that your answers are derived from your understanding of the text and not based on simple text matching. Output a JSON, where ...... <Question>Question</Question> <Text>Text</Text>

Figure 1: Illustration of the SummEQuAL framework. The blue and red area represents the recall-oriented and the precision-oriented framework respectively. Solid colored lines and letters represent subtasks of LLMs. Other lines are simple comparison and calculation. The right side is an example of prompts for the subtasks.

employs a QA mechanism to complete the content evaluation, producing more reliable results. Our experimental results on the SummEval dataset and MultiWOZ-based dataset demonstrate that the QA process benefits from LLMs. Particularly remarkable is that SummEQuAL improves the Spearman correlation with human evaluation by 19.7% on SummEval consistency, compared with our baseline QuestEval.

In summary, the main contributions of this paper are as follows:

1. We propose a unified summarization evaluation framework, SummEQuAL, for content correctness via QA using LLMs, minimising human works (§3).

2. We introduce a new dataset on MultiWOZ to assess the quality of summarization content evaluation (§4.2).

3. Through experiments, our proposed framework, SummEQuAL, improves the baseline by 19.7% on the SummEval benchmark (§5.1.2) and 17.3% on the MultiWOZ-based dataset (§5.2.2).

4. Our further analysis reveals that LLMs can

evaluate uniformly and robustly through designing a fixed workflow with objective subtasks (§6).

2 Related Works

2.1 N-gram-based Evaluation Metrics

N-gram-based metrics measure the overlap between the generated summary and a reference summary. BLEU (Papineni et al., 2002) quantifies the concurrence of n-grams in a precision-oriented manner. ROUGE (Lin, 2004) assesses summarization from recall orientation. Since the above methods mainly focus on n-gram matching, they may fail to capture higher-level issues such as sentence structure, syntax, and semantics. Also, it can be affected by the repeated use of common phrases. As a result, they cannot accurately measure the content quality of a generated text (Reiter and Belz, 2009). Although many new metrics have appeared, nearly 70% of research works are still based on the old BLUE and ROUGE matrics (Kasai et al., 2022b).

2.2 Pre-trained Model-based Evaluation

Pre-trained model metrics are a category of methods that utilize pre-trained language models to evaluate. The language models can better cap-

ture semantic information and consequently assess the quality of generated text more accurately. BERTScore (Zhang et al., 2020) compares the text embeddings, calculating similarity scores through the alignment of generated and reference summaries at a token level. MoverScore (Zhao et al., 2019) based on BERT considers the movement between words to evaluate the similarity between the generated text and the reference text. BARTScore (Yuan et al., 2021) regards evaluation as a text generation problem, which calculates the probability of a text generating or generated from other texts to evaluate.

2.3 QA-based Evaluation

A direct approach to compare the information of summaries and source documents is through the QA process. Previous research has explored this in fine-tuned language models. SummaQA (Scialom et al., 2019) generates questions from the source document and compares the QA model's confidence in answering based on the summary, but fake answers are not considered. FEQA (Durmus et al., 2020) and QAGS (Wang et al., 2020), from another angle, generate questions from summarizations, using the original text for answering, to evaluate factual consistency. QuestEval (Scialom et al., 2021) subsequently applied QA in both directions, and MQAG (Manakul et al., 2023) introduced a Multiple-choice QA model for dealing with highly abstractive summarizations or multiple-answer spans.

2.4 LLM-based Evaluation

LLMs have been pre-trained on vast text data, enabling them to address a variety of domains without specific training. They can identify complex logical content. GPTscore (Fu et al., 2023) utilizes LLMs for zero-shot instruction and in-context learning, suggesting that texts of higher quality are generated with a higher likelihood. Incorporating CoT (Wei et al., 2022), G-EVAL (Liu et al., 2023) yields superior outcomes, allowing LLMs to autonomously generate evaluation methods. There's a bias observed favouring LLM-created content. Additionally, Chen et al. (Chen et al., 2023) determined that explicit LLM evaluations are more effective than implicit ones. In conclusion, while LLMs offer promising capabilities in text evaluation, challenges such as sensitivity, model bias, and score distribution bias remain.

3 SummEQuAL Framework

We propose a QA-based framework with LLMs to evaluate summarization systems, which considers *completeness*, *informativeness*, and *consistency*, without the requirement of human reference for each summary. SummEQuAL consists of two approaches and five LLM sub-tasks, as shown in Figure 1. Below we delve into details for each criterion of our framework.

3.1 Completeness

Summarization aims to extract core information from texts to present the main content of the original text in a shorter form. A good summary should include as much important information from the original text as possible. Based on this concept, we first consider how much important information from the original text is included in the summary.

Rather than generating questions from the entire source document, we utilize LLMs to generate a concise list of information key points. To ensure that the LLMs can better understand the text and perform the evaluation task more effectively, we introduce a schema that can be defined by experts. This schema can include important information such as the main character of a story, the purpose of a product, or the time required to reserve a restaurant table, depending on the purpose and content of the summarization. Also, if a schema is not provided, the LLMs can generate key points based on their general understanding of the article. An example of a schema is:

```
{
    "Time": "When does the event happen?",
    "Location": "Where does the event happen?",
    "Figure": "Who are the participants involved?",
    "Description": "What is the main event?",
    "Cause": "Why does the main event happen?",
    "Result": "What are the results of the event?"
}
```

After generating the list of key points, LLMs assess whether these key points are included in the summary. Leveraging LLMs' reasoning abilities across a wide range of topics, the QA process can be simplified into a straightforward boolean question, allowing LLMs to determine whether key points are present in the summary to be evaluated. Given a key point list K including n key points k_1 ... k_n, and a summary S, We define the *completeness* of a summary as:

$$\text{Comp.} = \frac{1}{n}\sum_{i=1}^{n} M(S, k_i), \qquad (1)$$

where M is a match function performed on LLMs, indicating whether a key point is included in a summary. The value of $M(S, k)$ is between 0 and 1, when S completely includes k the value is 1 and when S does not intersect with k at all, the value is 0.

3.2 Informativeness

A good summary should also avoid incorporating irrelevant information, and ideally all the information within summaries should be of significance. In evaluation, we employ LLMs to generate question-answer pairs pertaining to the details of summaries. Subsequently, we prompt LLMs to answer questions using a key point list and then assess whether the answers to the two sets of questions match. To streamline the comparison process, we also generate boolean questions. Denote the question list generated from summary S by LLMs as $Q(S)$, and q are questions in it. Given a text T and a question q, the answer generated by LLMs is $A(T, q)$. We define *informativeness* as:

$$\texttt{Inf.} = \frac{1}{|Q(S)|} \sum_{q \in Q(S)} \delta(A(S, q), A(K, q)), \quad (2)$$

where $|\cdot|$ represents the size of the set and $\delta(a, b)$ is equal to 1 when $a = b$ otherwise 0.

3.3 Consistency

Generative models could mistakenly create information that seems plausible but is not actually right, which is known as hallucinations. In the summarization task, this property introduces information outside the source document, thus damaging the consistency of the summary with the source document. To measure consistency, we use the summary to generate question-answer pairs, then answer the question by the source text with LLMs. After these, we compare the two sets of answers. For a given source document D, *consistency* is defined as:

$$\texttt{Cons.} = \frac{1}{|Q(S)|} \sum_{q \in Q(S)} \delta(A(S, q), A(D, q)) \quad (3)$$

3.4 SummEQuAL Score

SummEQuAL score is a comprehensive index combining *completeness*, *informativeness*, and *consistency*. The summary takes into account the quantity of important information, the amount of redundant information, and the extent to which false information is included. Multiplying the harmonic mean of *completeness* and *informativeness* with *consistency*, SummEQuAL score is computed as follows:

$$\texttt{SummEQuAL} = 2 \cdot \frac{\texttt{Comp} \cdot \texttt{Inf}}{\texttt{Comp} + \texttt{Inf}} \cdot \texttt{Cons} \quad (4)$$

4 Datasets

4.1 SummEval

SummEval (Fabbri et al., 2021) is one of the largest human annotated datasets for summarization evaluation tasks, built on the foundation of the CNN/Daily Mail (Hermann et al., 2015) dataset. SummEval collects and releases both expert and crowd-sourced human evaluation for 16 model outputs on 100 articles across 4 dimensions to advance research into human-correlated evaluation metrics. For each summary, there are 3 expert and 5 crowd-sourced evaluations, totalling 12,800 human annotations. We will compare the correlation between LLMs' evaluations within the SummEQuAL framework and human evaluations in this dataset.

4.2 MultiWOZ

MultiWOZ (Budzianowski et al., 2018) is an open dataset released by the University of Cambridge, serving as a widely-used multi-domain task-oriented dialogue dataset with detailed human annotations for tracking dialogue information. As a task-oriented dataset, MultiWOZ offers objective schemas for specific tasks and annotated slot values for all dialogues. The dataset presents complex logic and multiple topics within individual dialogue texts, making it suitable for evaluating the framework's proficiency in working with a designed schema. We choose the newest version MultiWOZ 2.4 (Ye et al., 2022) for the experiment.

Dataset Construction Task-oriented summarization focuses on specific results. For booking tickets, we expect the summaries to fully contain information on user demands and the booking result. With this in mind, we created summaries on the MultiWOZ dataset and manually evaluated the completeness of the summaries. We randomly sample 50 dialogues from the test set of the MultiWOZ 2.4 dataset, and generate both short summaries and detailed summaries for each dialogue using the text-curie-001 model, GPT-3.5-turbo-0613 model, and GPT-4 model(OpenAI, 2023), totaling 300 summaries. The statistics of the dialogues and the summaries are shown in Table 2. Then, we annotated the summaries' completeness by checking

Table 1: Sample-level Spearman correlation (Spear.), Pearson correlation (Pear.), and Kendall's Tau correlation (Kend.) of relevance and consistency on SummEval. #Ref. is the number of reference summaries in evaluation. The mean columns represent the average of relevance and consistency. Results of QA metrics are from Scialom's work (Scialom et al., 2021).

Metrics	#Ref.	Relevance			Consistency			Mean		
		Spear.	Pear.	Kend.	Spear.	Pear.	Kend.	Spear.	Pear.	Kend.
ROUGE-1	1	0.199	0.220	0.152	0.157	0.200	0.132	0.178	0.210	0.142
ROUGE-2	1	0.145	0.174	0.105	0.137	0.162	0.116	0.141	0.168	0.110
ROUGE-L	1	0.203	0.221	0.156	0.149	0.198	0.125	0.176	0.210	0.141
ROUGE-1	11	**0.311**	0.347	0.237	0.153	0.216	0.125	0.232	0.282	0.181
ROUGE-2	11	0.248	0.298	0.189	0.122	0.181	0.101	0.185	0.240	0.145
ROUGE-L	11	0.293	0.329	0.224	0.103	0.180	0.082	0.198	0.255	0.153
BERTScore	11	0.269	0.304	0.203	0.168	0.242	0.140	0.219	0.273	0.172
BARTScore	11	0.264	0.290	0.197	0.311	0.321	0.256	0.288	0.306	0.227
MoverScore	11	0.282	0.313	0.215	0.166	0.221	0.137	0.224	0.267	0.176
SummaQA	0	–	0.262	–	–	0.083	–	–	0.173	–
QAGS	0	–	0.204	–	–	0.091	–	–	0.148	–
QuestEval	0	–	**0.392**	–	–	0.420	–	–	**0.406**	–
SummEQuAL	0	**0.311**	0.337	**0.241**	0.274	0.324	0.227	0.292	0.331	0.234
-Completeness	0	0.252	0.274	0.204	0.151	0.182	0.131	0.201	0.228	0.167
-Informativeness	0	0.181	0.187	0.143	0.161	0.188	0.136	0.171	0.188	0.139
-Consistency	0	0.228	0.265	0.193	**0.432**	**0.503**	**0.403**	**0.330**	0.384	**0.298**

how much proportion of the schema information was contained to provide a score. We used three annotators for marking. If the annotations by the first two annotators were inconsistent, the third annotator adjudicated to determine the final annotation.

Table 2: Statistics for dialogue and summary. The lengths are described by the number of words.

Dialogue		Average Summary Lengths	
Metric	Value	Summarization	Length
Dialogue Turn	6.98	gpt-3.5 simple	109.7
Mean Length	205.8	gpt-3.5 detailed	126.5
Min. Length	70	gpt-4 simple	69.0
Max. Length	470	gpt-4 detailed	89.9
Median Length	210	text-curie-001 simple	68.7
Std. Deviation	81.2	text-curie-001 detailed	72.7

5 Experiments and Results

Evaluation Strategy. We evaluate automatic metrics by comparing their alignment with reference evaluations. Three prevalent correlations, the Spearman correlation, the Person correlation and the Kendall's Tau correlation are employed. Given n source texts and m summary models, the i-th text's summary generated by the j-th model is denoted as $s_{i,j}$. The formula of correlation at a sample level is as follows:

$$\text{Corr} = \frac{1}{n}\sum_{i=1}^{n}\rho\left([e_{\text{auto}}(s_{i,1}),\dots,e_{\text{auto}}(s_{i,M})],\right.$$
$$\left.[e_{\text{ref}}(s_{i,1}),\dots,e_{\text{ref}}(s_{i,M})]\right) \quad (5)$$

where ρ denotes the function of correlation met-

rics. e_{auto} and e_{ref} denote the automatic evaluation and reference evaluation functions, respectively.

5.1 Evaluation on SummEval

5.1.1 Experimental Setup

We evaluate the SummEval dataset with our SummEQuAL framework and compare the evaluation results with human evaluations. Considering other LLMs do not always follow the instructions strictly to work with the SummEQuAL framework currently. In this paper, if not specified, we use the GPT-3.5-turbo-0613 model with a temperature of 0 as the LLM of our framework. To avoid confusion across texts, each step of our framework separately inputs data into the LLM and is linked by processing output JSON. The human evaluation is set using the average scores from three experts. The determined input schema is the same as the example schema shown in Section 3.1. To make the evaluation for our framework convincing, we also use a rephrased version of the prompts besides the example prompts in Figure 1 and calculate the average correlation.

5.1.2 Results

LLMs have demonstrated competitive results within the SummEQuAL framework in Table 1. On the aspect of consistency, SummEQuAL has shown a clear superiority over traditional automatic metrics, improving by 19.7% compared to the best-performing QA models. This improvement bene-

fits from the potential of LLMs-based inferencing in QA. LLMs generate more accurate responses to questions, effectively verifying whether the information in the summary is consistent with the original text.

In terms of relevance, the correlations are high on ROUGE-1 with 11 references and QuestEval, yet SummEQuAL also achieved competitive results. The primary reason for not outstanding results lies in the differences in the definitions of relevance. The SummEval dataset emphasizes selecting important content from the source without stressing correctness but SummEQuAL does consider it. In contrast, ROUGE-1, which precisely matches identical words, emphasizes relevance but not accuracy. QuestEval, when utilizing summaries to answer questions generated from the original text, relies on the answerability confidence instead of an answer, thus aligning more closely with the definition of relevance in SummEval.

5.2 Task-oriented Summarization Evaluation

Task-oriented summarization requires a focus on specific information within the text. For instance, in ticket booking dialogues, details about the ticket such as time and location are crucial, while in a doctor's diagnostic interview notes, the patient's symptoms and feelings are of importance. To accurately evaluate the effectiveness of task-oriented summarization, a well-defined schema that lists all the relevant information is helpful. SummEQuAL can then be used to provide a desirable evaluation for the tasks, ensuring that the summarization meets the specific requirements. To test the ability of the SummEQuAL framework on task-oriented summarization evaluation, we build a MultiWOZ-based dataset, which contains dialogues interactions between users and conversational systems, involving a range of tasks, such as restaurant reservations, travel bookings, information queries, and so forth, and then we conduct experiments with the SummEQuAL framework.

5.2.1 Experimental Setup

A dictionary with the 35 types of slots tracked in the dialogue dataset is set as the schema for generating key points. Within the SummEQuAL framework, we input schemas into both the GPT-3.5 and GPT-4 models, generating two lists of key points. To evaluate the LLMs' capability to generate key points based on the schema, we manually compared these generated lists against the slot values

annotated in MultiWOZ. Considering the target of this ticket-booking summarization, only slot values in the final turn of user-system dialogues are extracted as the ground truth. After this, we use a simple match, ROUGE-L, BERTscore and LLMs to compare the key point list with the source document (C in Figure 1) and generate a completeness score. We compared these completeness scores with human scores to demonstrate whether this framework benefits from LLMs. Last but not least, we compare the performance of different evaluation metrics like ROUGE, BERTScore and BARTScore on the 300 summaries consisting of simple and detailed summaries generated by the text-curie-001, the GPT-3.5-turbo-0613 and GPT-4 models. Based on our observation, the GPT-4 model is better than the GPT-3.5 model, and both outperform the text-curie-001 model; the detailed version is better than the simple version of the same model. So we assigned them scores from high to low as ground truth. Finally, we calculated the correlation coefficients of metrics and assigned scores accordingly.

Table 3: Comparison of Key Point Generation Abilities: Scores are derived by comparing model predictions with the last dialogue turn's state value manually.

Model	Recall	Precision	F1
GPT-3.5	0.919	0.758	0.830
GPT-4	0.958	0.875	0.915

5.2.2 Results

As shown in Table 3, both models can extract key points according to the schema with relatively good results, highlighting the flexibility and adaptability of the SummEQuAL framework. If the schema is given, GPT-3.5 with relatively weak reasoning ability can obtain high recall. Compared with GPT-4, the precision of GPT-3.5 is lower. We checked the output and found this is because some unimportant information outside the schema is introduced, which is often repeated information or redundant content as a result of not correctly following the schema.

Table 4 shows that the evaluation of the SummEQuAL framework benefits from the reasoning ability of LLMs. The comparison based on LLMs is the most consistent with human evaluations, surpassing other methods significantly. Upon careful observation of the results, we discovered that GPT-3.5 tends to make errors and give lower scores, which suggests that in complex scenarios, GPT-3.5's rea-

Table 4: Comparison of Key Point Comparison Abilities: Model correlation with human on comparison of key point and summary.

Model	Spearman	Pearson	Kendall Tau
Simple match	0.298	0.229	0.211
ROUGE-L	0.328	0.282	0.232
BERTScore	0.644	0.634	0.476
GPT-3.5	0.742	0.756	0.599
GPT-4	**0.929**	**0.828**	**0.946**

soning ability may not be sufficient to capture all the details of the summaries. We will discuss this in the analysis section (§6) in detail.

Table 5: Sample-level Correlations of Summarization Evaluation on Our MultiWOZ-based Dataset.

Metrics	Spear.	Pear.	Kend.
ROUGE-1	-0.010	0.077	-0.007
ROUGE-L	0.003	0.079	0.001
BERTScore	0.589	0.657	0.489
BARTScore	0.423	0.519	0.317
SummEQuAL	0.240	0.283	0.192
-Completeness	**0.691**	**0.764**	**0.573**
-Informativeness	0.212	0.257	0.161
-Consistency	-0.028	-0.058	-0.031

By the comparison in Table 5, the completeness of SummEQuAL has achieved the best correlation, but the correlations of other parts are not high. Metrics based on pre-trained language models perform well, but ROUGE performs poorly. This result is from the generation of summarization, the GPT models tend to cover more content when summarizing on MultiWOZ, so the summarization contains comprehensive important information but is not concise. Moreover, since both GPT-3.5 and GPT-4 have good summary capabilities for the MultiWOZ data set, the actual summarization quality of GPT-3.5 is not lower than GPT-4 in some cases, especially considering the consistency. As a result, the assigned scores are not completely accurate, which affects the overall correlation coefficient.

6 Further Analysis

6.1 Discrepancy of Summarization Tasks

The evaluation result is affected by the dataset's features, the evaluation criteria and the evaluation target. Articles in SummEval are longer and contain more detailed descriptions, making it easier for summarizations to introduce non-essential information and produce inconsistent information, while the dialogues are shorter. Moreover, we need to

consider the practical meaning of the comparison scores. The dialogues in MultiWOZ are based on specific tasks, and their themes and key information are more clearly defined. In the case of providing a schema reflecting the content of the task as a reference, the completeness score is more consistent with the target of evaluation. When using SummEQuAL for evaluation tasks, we can clarify the purpose of the task and use a more appropriate schema and metric or combination of metrics for a better evaluation.

6.2 Error Analysis

Inferencing capability. As illustrated in Table 6, the dialogue contains implicit shifts of needed information. GPT-3.5 only capture the user's initial request for a restaurant serving canapes and did not correctly comprehend the system's rejection of the user's proposed dining time of 16:15. This comparison underscores the importance of inferencing abilities of the model's reasoning capabilities. Similar errors could also occur in the evaluation of informativeness and consistency.

Subjectivity. Evaluation on the SummEval dataset is influenced significantly by subjectivity. The evaluation results can vary depending on the chosen schema. Our schema may focus on different information from the human annotation in SummEval. Consequently, the generated key points do not align with information in the reference summaries used by human experts during evaluation, resulting in a potential distortion of the summarization evaluation.

Stability. When generating key points, GPT-3.5 could generate duplicate information or possible schema values that do not appear in the summary, causing the SummEQuAL framework to fail. During the entire evaluation process, GPT-3.5 is occasionally affected by the text content, so that it is unable to correctly execute the framework tasks according to the instructions, and outputs wrong or incomplete content.

6.3 Reproducibility

An inherent characteristic of LLMs, especially when interfaced through APIs, is the potential variability in their outputs upon repeated experiments. We evaluate the potential difference level of this issue by repeating the experiment. Here we use the GPT-3.5-turbo as the base model of the SummEQuAL framework, and we experimented on the

Table 6: Case Study: Comparison of GPT-3.5 and GPT-4 for Key Points Generation. Table (top) provides a brief overview of the dialogue and Table (bottom) summarizes both the actual key points and the predictions. Key points highlighted in green indicate correct summarization, while those in red represent incorrect predictions by the model.

Role	Dialogue
User:	I am looking for a restaurant that serves canapes in the east.
Sys:	Unfortunately there are no restaurants serving canapes in the east.
User:	Ah, well, too bad. In that case, I think that'll be everything that I needed. Thanks and have a good day!
Sys:	Are you sure? I can find other options in other parts of town?
User:	How about Italian food?
Sys:	There is the Pizza Hut Fen Ditton in the east serving Italian food.
User:	Great! Please book a table for 6 at 16:15 on Saturday.
Sys:	Sorry, but no tables are available for that time slot. Would you like to change the time?
User:	How about 15:15 then?
Sys:	Your table is booked. Your reference number is qw8jzwzk. Can I help you with anything else?
User:	Great. Thank you for your help today. That is all.

Key Points (Name)	Slot Values (Truth)	GPT-3.5 (Prediction)	GPT-4 (Prediction)
restaurant-food	italian	canapes	italian
restaurant-area	east	east	east
restaurant-book day	saturday	saturday	saturday
restaurant-book people	6	6	6
restaurant-book time	15:15	16:15	15:15
restaurant-name	pizza hut fenditton	pizza hut fen ditton	pizza hut fen ditton

Table 7: Comparison of Repeated Experiment Results

Metrics	Abs Mean	Variance	Abs Difference Percentage				
			0-0.1	0.1-0.2	0.2-0.3	0.3-0.4	>0.4
S.E.	0.050	0.010	81.31%	11.75%	4.31%	1.69%	0.94%
Comp.	0.052	0.012	78.94%	11.69%	5.69%	2.38%	1.31%
Inf.	0.056	0.016	78.75%	10.19%	5.62%	3.81%	1.62%
Cons.	0.018	0.004	92.31%	4.56%	2.06%	0.75%	0.31%

Figure 2: Standardized SummEQuAL and Human Scores by Summary Length Interval

SummEval benchmark. Table 7 shows that the majority of the results across various metrics fell within the minimal absolute difference percentage range (0-0.1), indicating a high degree of reproducibility. Among all the metrics, the consistency score shows the smallest discrepancy.

6.4 Comparison of Text Lenth

We conduct a comparative analysis with human scores to evaluate the possible bias of our Sum-

mEQuAL score across various text lengths. First, we scale the SummEQuAL and human scores using z-score normalization to ensure comparability. We then grouped the summaries into four equal-sized intervals based on length and computed the mean standardized score for both SummEQuAL and human evaluations within each group. Figure 2 indicates a general trend where both SummEQuAL and human scores increased with the length of the text. The apparent preference in the SummEQuAL model for longer texts could result from the fact that longer summaries are better in the SummEval benchmark. The overall parallel trends in SummEQuAL and human scoring across different text lengths demonstrate a degree of consistency.

7 Conclusion

This work proposes a novel summarization evaluation framework, SummEQuAL, based on LLMs. The SummEQuAL framework provides a novel and effective approach for the evaluation of summarization, opening up a new direction for future work on unified and reproducible summarization evaluation using LLMs. SummEQuAL sheds new light on developing reliable and consistent summarization evaluation methods, expected to help researchers more precisely understand and evaluate the performance of summarization models, thereby improving the quality of summarization content.

Limitation

SummEQuAL's performance depends on the capabilities of LLMs. Any limitations these LLMs have, especially in parsing complex logic or discerning implicit information, will directly influence SummEQuAL's assessments. The framework's reliance on multi-step reasoning, involving numerous LLM interactions, means it can be time-intensive and resource-heavy compared to simpler one-step evaluations. Moreover, although SummEQuAL has shown promise in initial tests, its effectiveness across different models, languages, and text domains still needs further evaluation.

References

Paweł Budzianowski, Tsung-Hsien Wen, Bo-Hsiang Tseng, Iñigo Casanueva, Stefan Ultes, Osman Ramadan, and Milica Gašić. 2018. MultiWOZ - a large-scale multi-domain Wizard-of-Oz dataset for task-oriented dialogue modelling. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 5016–5026, Brussels, Belgium. Association for Computational Linguistics.

Yi Chen, Rui Wang, Haiyun Jiang, Shuming Shi, and Ruifeng Xu. 2023. Exploring the use of large language models for reference-free text quality evaluation: A preliminary empirical study. *ArXiv preprint*, abs/2304.00723.

Yulong Chen, Naihao Deng, Yang Liu, and Yue Zhang. 2022. DialogSum challenge: Results of the dialogue summarization shared task. In *Proceedings of the 15th International Conference on Natural Language Generation: Generation Challenges*, pages 94–103, Waterville, Maine, USA and virtual meeting. Association for Computational Linguistics.

Esin Durmus, He He, and Mona Diab. 2020. FEQA: A question answering evaluation framework for faithfulness assessment in abstractive summarization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5055–5070, Online. Association for Computational Linguistics.

Alexander R. Fabbri, Wojciech Kryściński, Bryan McCann, Caiming Xiong, Richard Socher, and Dragomir Radev. 2021. SummEval: Re-evaluating summarization evaluation. *Transactions of the Association for Computational Linguistics*, 9:391–409.

Jinlan Fu, See-Kiong Ng, Zhengbao Jiang, and Pengfei Liu. 2023. Gptscore: Evaluate as you desire. *ArXiv preprint*, abs/2302.04166.

Tanya Goyal, Junyi Jessy Li, and Greg Durrett. 2022. News summarization and evaluation in the era of gpt-3. *ArXiv preprint*, abs/2209.12356.

Karl Moritz Hermann, Tomás Kociský, Edward Grefenstette, Lasse Espeholt, Will Kay, Mustafa Suleyman, and Phil Blunsom. 2015. Teaching machines to read and comprehend. In *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pages 1693–1701.

Jungo Kasai, Keisuke Sakaguchi, Ronan Le Bras, Lavinia Dunagan, Jacob Morrison, Alexander Fabbri, Yejin Choi, and Noah A. Smith. 2022a. Bidimensional leaderboards: Generate and evaluate language hand in hand. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3540–3557, Seattle, United States. Association for Computational Linguistics.

Jungo Kasai, Keisuke Sakaguchi, Ronan Le Bras, Lavinia Dunagan, Jacob Morrison, Alexander Fabbri, Yejin Choi, and Noah A. Smith. 2022b. Bidimensional leaderboards: Generate and evaluate language hand in hand. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3540–3557, Seattle, United States. Association for Computational Linguistics.

Tom Kocmi and Christian Federmann. 2023. Large language models are state-of-the-art evaluators of translation quality. *ArXiv preprint*, abs/2302.14520.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: NLG evaluation using gpt-4 with better human alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2511–2522, Singapore. Association for Computational Linguistics.

Potsawee Manakul, Adian Liusie, and Mark JF Gales. 2023. Mqag: Multiple-choice question answering and generation for assessing information consistency in summarization. *ArXiv preprint*, abs/2301.12307.

OpenAI. 2023. Openai platform models documentation. Accessed: 2023-10-02.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318, Philadelphia, Pennsylvania, USA. Association for Computational Linguistics.

Ehud Reiter and Anja Belz. 2009. An investigation into the validity of some metrics for automatically evaluating natural language generation systems. *Computational Linguistics*, 35(4):529–558.

Thomas Scialom, Paul-Alexis Dray, Sylvain Lamprier, Benjamin Piwowarski, Jacopo Staiano, Alex Wang, and Patrick Gallinari. 2021. QuestEval: Summarization asks for fact-based evaluation. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6594–6604, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Thomas Scialom, Sylvain Lamprier, Benjamin Piwowarski, and Jacopo Staiano. 2019. Answers unite! unsupervised metrics for reinforced summarization models. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3246–3256, Hong Kong, China. Association for Computational Linguistics.

Alex Wang, Kyunghyun Cho, and Mike Lewis. 2020. Asking and answering questions to evaluate the factual consistency of summaries. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5008–5020, Online. Association for Computational Linguistics.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed H Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*.

Fanghua Ye, Jarana Manotumruksa, and Emine Yilmaz. 2022. MultiWOZ 2.4: A multi-domain task-oriented dialogue dataset with essential annotation corrections to improve state tracking evaluation. In *Proceedings of the 23rd Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 351–360, Edinburgh, UK. Association for Computational Linguistics.

Weizhe Yuan, Graham Neubig, and Pengfei Liu. 2021. Bartscore: Evaluating generated text as text generation. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 27263–27277.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. Bertscore: Evaluating text generation with BERT. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.

Wei Zhao, Maxime Peyrard, Fei Liu, Yang Gao, Christian M. Meyer, and Steffen Eger. 2019. MoverScore: Text generation evaluating with contextualized embeddings and earth mover distance. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 563–578, Hong Kong, China. Association for Computational Linguistics.