Rubric-Grounded Reinforcement Learning:
Structured Judge Rewards for Generalizable Reasoning in Language Models

Manish Bhattarai [1] Ismael Boureima [1] Nishath Rajiv Ranasinghe [1] Scott Pakin [1] Dan O'Malley [1]

Abstract

We argue that decomposing reward into weighted, verifiable criteria and using an LLM judge to score them provides a partial-credit optimization signal: instead of a binary outcome or a single holistic score, each response is graded along multiple task-specific criteria. We formalize *rubric-grounded reinforcement learning (RL)*: a framework in which the policy is optimized against a structured, multi-criterion reward produced by a frozen LLM judge that conditions on auxiliary grounding the policy never sees. We instantiate the framework by deriving rubrics from an Office of Scientific and Technical Information (OSTI)-derived corpus of roughly 100,000 scientific and technical documents and training Llama-3.1-8B-Instruct with Group Relative Policy Optimization (GRPO). With GRPO-based training, the model achieves 71.7% normalized reward on held-out rubric evaluation under the training judge, an improvement that is qualitatively reproduced by an independent judge family. The GRPO-tuned policy also improves over the base model on reasoning benchmarks not derived from the training corpus, with statistically significant gains on GPQA Main and MATH and a comparable gain on GPQA Diamond, while GSM8K is unchanged. These results provide evidence that structured, document-grounded rewards can improve held-out rubric performance and induce reasoning behaviors that transfer beyond the corpus used to construct the training environment.

[1]Los Alamos National Laboratory, Los Alamos, NM, USA. Correspondence to: Manish Bhattarai <ceodspspectrum@lanl.gov>.

Proceedings of the 43^{rd} International Conference on Machine Learning, Seoul, South Korea. PMLR 306, 2026. Copyright 2026 by the author(s).

1. Introduction

Reward design is the binding constraint in reinforcement learning of large language models (LLMs). Standard alignment objectives often compress multi-faceted quality into one scalar signal—a learned preference reward, a pairwise comparison, or a binary verifier, and optimize the policy against that signal. This works when the target behavior can be summarized by one latent utility, but it under-specifies the optimization target whenever quality is naturally decomposable: a strong technical answer must state the right conclusion, use precise terminology, respect methodological caveats, and connect evidence; a strong code review must catch correctness bugs, flag style issues, and surface design concerns. This discarded structure could otherwise provide partial-credit learning signals.

We study a general principle: *decompose reward into weighted, verifiable criteria, use an LLM judge to score them, and optimize the policy with Group Relative Policy Optimization (GRPO) (Shao et al., 2024)*. We call this *rubric-grounded reinforcement learning*. The framework is domain-agnostic: any task whose quality is plausibly written as a checklist of weighted criteria (technical Q&A, clinical summarization, legal drafting, pedagogical assessment, structured code review) admits a rubric-grounded reward.

To validate the principle, we instantiate it on a concrete and scalable data source: an OSTI-derived collection of roughly 100,000 scientific and technical documents [1]. Each document is converted offline into question–rubric pairs, where the rubric decomposes evaluation into weighted criteria with required elements, scoring guides, and verification cues. During training the policy answers each question *without* the source passage; a frozen judge scores each response *with* the passage and rubric. This information asymmetry encourages the policy to learn response patterns that satisfy grounded criteria, rather than relying on access to the source passage at rollout time.

Central claim. The empirical claim is that rubric-grounded GRPO can improve a Llama-3.1-8B-Instruct model on held-out rubric tasks and yield gains on exter-

---

[1]https://www.osti.gov/

nal reasoning benchmarks. We support this with held-out rubric evaluation, cross-judge validation with an independent judge family, in-domain comparison to the supervised warm-start, paired significance tests on four reasoning benchmarks against the base model, and training/held-out reward dynamics.

Contributions.

1. A **general framework**, rubric-grounded RL, that uses weighted criterion-level judge scores as a partial-credit reinforcement learning signal (§3).

2. A **reward-to-RL mechanism** that converts passage-grounded criterion scores into group-relative GRPO advantages while preserving partial-credit structure (§3.1–§3.3).

3. A **scalable instantiation**, document-derived rubrics, that produces RL training data without per-criterion human annotation (§3.4).

4. An **empirical evaluation** showing that a rubric-grounded GRPO policy improves held-out rubric reward and yields gains on reasoning benchmarks not derived from the training corpus relative to the base instruction model (§4–§5.6).

Figure 1 summarizes the framework end to end.

2. Background and Related Work

Reward modeling for LLM alignment. Reinforcement Learning from Human Feedback (RLHF) (Christiano et al., 2017; Ouyang et al., 2022; Stiennon et al., 2020) trains a scalar reward model on human pairwise preferences and optimizes the policy with PPO (Schulman et al., 2017). DPO (Rafailov et al., 2023) and related preference-optimization methods sidestep explicit reward modeling but still operate on pairwise comparisons. Reinforcement Learning from AI Feedback (RLAIF) (Bai et al., 2022; Lee et al., 2023) replaces human preferences with model-generated ones, retaining the scalar form. Our framework departs from this scalar lineage: the reward is an explicitly weighted vector of criterion scores, not a single learned utility, and is tied to evaluation criteria specified at task-construction time rather than inferred from preferences.

LLM-as-judge and rubric-based evaluation. LLM-as-judge methods have become a standard evaluation device (Zheng et al., 2023), with recent work emphasizing structured or rubric-based grading (Kim et al., 2024a;b; Ye et al., 2024; Lee et al., 2024). Most of this literature uses judges *for evaluation only*. We use a rubric-conditioned judge inside the optimization loop, which makes the judge reliability and rubric design first-class methodological concerns rather than evaluation details.

Rubrics as reinforcement-learning rewards. Recent work is closest to ours in using rubrics as RL reward signals: Rubrics as Rewards extends Reinforcement Learning with Verifiable Rewards (RLVR) beyond automatically verifiable domains with rubric-based feedback (Gunjal et al., 2025), Rubric Anchors studies large-scale rubric construction and rubric-based RL for open-ended tasks (Huang et al., 2025), and Rubric-Scaffolded RL uses checklist rubrics both as rollout scaffolds and reward references (Zhou et al., 2025). Our setting differs in three ways: rubrics are synthesized from scientific documents, the policy never sees the source passage during rollout, and rubric synthesis is decoupled from the cheaper judge used repeatedly during RL. The contribution is accordingly not rubric rewards per se, but this information-asymmetric, document-grounded instantiation at scale, together with cross-judge validation of the resulting reward signal.

Process and step-level rewards. Process reward models (PRMs) provide dense per-step supervision (Lightman et al., 2023; Wang et al., 2024; Uesato et al., 2022) and have produced strong reasoning gains, but they typically require human-annotated step labels or oracle verifiers and are usually scoped to math. Rubric-grounded rewards generalize the dense-supervision idea beyond per-step labels: criteria can be at any granularity (an entire limitation discussion, a specific terminological requirement, a verification cue) and require only a written rubric, not labeled trajectories.

Group-relative policy optimization. GRPO (Shao et al., 2024) replaces the learned value baseline with a group-relative one computed from multiple rollouts per prompt, which is a natural fit for judge-scored responses. Decoupled Clip and Dynamic sAmpling Policy Optimization (DAPO) (Yu et al., 2025) and Group Sequence Policy Optimization (GSPO) (Zheng et al., 2025) refine the sampling and importance-sampling machinery. We use GRPO as the optimizer; the contribution lies in the structure of the reward, not the optimizer.

3. Method

We present rubric-grounded RL in domain-agnostic terms; then instantiate it with OSTI-derived documents. A task instance is a tuple $(\mathbf{x}, g, \mathcal{R})$ where $\mathbf{x}$ is the input shown to the policy, g is auxiliary *grounding* (a passage, a reference solution, a code repository, a clinical chart) shown only to the judge, and $\mathcal{R}$ is a structured rubric. The policy $\pi_\theta(\mathbf{y} \mid \mathbf{x})$ produces a response $\mathbf{y}$ without access to g, while a frozen judge $\mathcal{J}$ scores $\mathbf{y}$ against $\mathcal{R}$ using g as grounding.

Definition 1 (Rubric). *A rubric $\mathcal{R} = \{c_1, \ldots, c_M\}$ is a collection of criteria, each $c_j = (w_j, \eta_j, \mathcal{E}_j, \kappa_j, \nu_j)$ with non-negative weight $w_j \in \mathbb{R}_{\geq 0}$, natural-language description η_j, required elements $\mathcal{E}_j$, expected keywords κ_j, and*

Figure 1. **Rubric-Grounded Reinforcement Learning pipeline.** Offline, a corpus of scientific and technical documents is used to synthesize training tuples consisting of a question, grounding passage, and weighted rubric. Online, the policy model receives only the question and generates multiple candidate responses. A frozen LLM judge evaluates each response using the hidden grounding passage and rubric, producing criterion-level scores that are aggregated into normalized rewards. These structured rewards provide the GRPO training signal, enabling the policy to learn from passage-grounded verification without accessing the passage at inference time.

verification method ν_j. The total weight is $W = \sum_j w_j$.

The policy and judge deliberately see different information: the policy answers from $\mathbf{x}$ alone, while the judge sees $(\mathbf{x}, g, \mathbf{y}, \mathcal{R})$. This separates what the policy must learn to produce from what the judge may verify. The same template applies whenever quality can be written as weighted, locally checkable criteria: technical question answering grounded in source documents, clinical reasoning grounded in patient charts, code review grounded in a diff and tests, legal drafting grounded in statutes and precedent, or pedagogical feedback grounded in a marking scheme. The following subsections define the reward, show how it enters GRPO, explain why the resulting scalar is more informative than a flat holistic score, and describe the OSTI-derived document instantiation.

3.1. Reward Construction

Multi-Criterion Judge Reward Given $(\mathbf{x}, g, \mathcal{R})$ and a sampled response $\mathbf{y} \sim \pi_\theta(\cdot \mid \mathbf{x})$, the judge produces a vector of per-criterion scores

$$\{s_j\}_{j=1}^M = \mathcal{J}(\mathbf{x}, g, \mathbf{y}, \mathcal{R}), \quad s_j \in [0, w_j], \qquad (1)$$

where s_j is the awarded weight on criterion c_j. The aggregate raw reward is $r_{\text{raw}} = \sum_j s_j$.

Normalization To compare rubrics with different total weights, we normalize:

$$r(\mathbf{x}, \mathbf{y}) = \frac{1}{W} \sum_{j=1}^M s_j \in [0, 1]. \qquad (2)$$

Parsed rewards are clipped to $[0, 1]$ in implementation to handle schema or numerical edge cases.

Judge Prompt Architecture The judge prompt contains a strict-evaluator system instruction, the grounding g (truncated to fit context), the policy input $\mathbf{x}$, the response $\mathbf{y}$, the rubric serialized as a numbered list with each criterion's weight, description, required elements, scoring guide, keywords, and verification method, and a structured-output specification requiring JSON with per-criterion scores, total, max, and a brief justification. The judge is decoded at low temperature ($\tau_{\mathcal{J}} = 0.1$) to reduce reward variance. Full prompt templates are in Appendix D.

Rubric synthesis and reward judging are decoupled. The rubrics can be created offline with a stronger or more expensive model, while online RL uses a cheaper judge repeatedly for reward computation. This separation is important because rubric construction is paid once, whereas judging is paid at every GRPO step.

Each GRPO step requires $B \times G$ judge calls, which dominate wall-clock time. We deploy N_{workers} parallel judge

actors, each holding an independent client to a vLLM-style inference endpoint; workers process micro-batches of size B_{judge} in parallel. This separates policy training (GPU-bound, autoregressive) from judge evaluation (latency-bound, remote).

3.2. Rubric-Grounded Policy Optimization

The optimizer receives only a scalar reward, but that scalar is produced by a structured measurement process: the judge scores each sampled answer against the same passage-grounded rubric and then aggregates criterion scores. This section describes how that structured reward is converted into GRPO updates in the reported experiments. Implementation variants that were supported but not used in the main run are deferred to Appendix C.

Training Objective For policy π_θ and frozen reference π_{ref},

$$\max_\theta \; \mathbb{E}_{\mathbf{x}\sim\mathcal{D},\, \mathbf{y}\sim\pi_\theta(\cdot|\mathbf{x})}[r(\mathbf{x},\mathbf{y})] - \beta\, \mathbb{E}_{\mathbf{x}}[\text{KL}(\pi_\theta \,\|\, \pi_{\text{ref}})], \quad (3)$$

with r from (2).

Group-relative rubric credit. For each prompt $\mathbf{x}_i$, we sample G responses $\{\mathbf{y}_i^{(g)}\}_{g=1}^G \sim \pi_{\text{gen}}(\cdot \mid \mathbf{x}_i)$. Each response is judged against the same grounding g_i and rubric $\mathcal{R}_i$, producing rewards $\{R_i^{(g)}\}$. Thus, the update compares answer strategies under a fixed assessment context rather than comparing raw scores across unrelated questions. The leave-one-out (LOO) baseline and group standard deviation are

$$b_i^{(g)} = \frac{1}{G-1} \sum_{g'\neq g} R_i^{(g')}, \quad (4)$$

$$\sigma_i = \text{std}\big(\{R_i^{(g')}\}_{g'=1}^G\big), \quad (5)$$

yielding the normalized advantage

$$A_i^{(g)} = \begin{cases} \dfrac{R_i^{(g)} - b_i^{(g)}}{\sigma_i + \delta} & \sigma_i > 0, \\ 0 & \text{otherwise.} \end{cases} \quad (6)$$

The advantage is broadcast to every response token.

Information-asymmetric update. The asymmetry from §3 enters the update through $R_i^{(g)}$: rewards are computed by a judge that sees $(\mathbf{x}_i, g_i, \mathbf{y}_i^{(g)}, \mathcal{R}_i)$, but gradients update a policy that generated $\mathbf{y}_i^{(g)}$ from $\mathbf{x}_i$ alone. The policy cannot retrieve the passage at inference time, but it is trained toward responses that satisfy passage-grounded criteria during learning. The result is a training-time supervision signal closer to an examiner with an answer key than to a retrieval-augmented generator.

Clipped surrogate, KL, and stabilizers. With per-token ratio $r_t = \exp(\log \pi_\theta - \log \pi_{\text{gen}})$, the clipped surrogate is

$$\ell_t^{\text{clip}} = -\min\big(r_t\, A_t,\, \text{clip}(r_t, 1-\epsilon_{\text{clip}}, 1+\epsilon_{\text{clip}})\, A_t\big), \quad (7)$$

and the per-token KL uses the k_3 approximation (Schulman, 2020):

$$\widehat{\text{KL}}_t = e^{u_t} - 1 - u_t, \quad u_t = \log \pi_{\text{ref}} - \log \pi_\theta. \quad (8)$$

Inputs are clamped to $[-20, 20]$ for numerical stability.

Total loss. Combining the clipped policy term and KL penalty gives the token-averaged training loss

$$\boxed{\mathcal{L}(\theta) = \frac{1}{\sum_{i,g} T_{ig}} \sum_{i,g,t} m_t^{(ig)} \Big[\ell_t^{\text{clip}} + \beta\, \widehat{\text{KL}}_t\Big],} \quad (9)$$

where $m_t^{(ig)}$ masks padding and prompt tokens. The complete algorithm is given in Algorithm 1 (Appendix A). In addition to KL regularization, the implementation uses low-temperature judging, schema-constrained parsing, reward clipping, and conservative zero reward on parse failures. These choices are not separate contributions; they are safeguards that make the structured reward usable inside an online RL loop.

3.3. Mechanism: Structured Credit Assignment

The central object is not the final scalar reward but the structured measurement that produces it. For a rubric with positive-weight criteria $w_1, \ldots, w_M$ and total weight $W = \sum_j w_j$, define normalized criterion scores

$$z_j(\mathbf{x}, g, \mathbf{y}) = \frac{s_j(\mathbf{x}, g, \mathbf{y}, \mathcal{R})}{w_j} \in [0,1], \qquad \alpha_j = \frac{w_j}{W}. \quad (10)$$

The reward used by GRPO is the projection

$$r(\mathbf{x}, \mathbf{y}) = \sum_{j=1}^M \alpha_j z_j(\mathbf{x}, g, \mathbf{y}) = \alpha^\top z(\mathbf{x}, g, \mathbf{y}). \quad (11)$$

Thus rubric-grounded RL is scalar RL over a reward that is first factorized into interpretable criterion coordinates. The mechanism below spells out what this factorization buys.

Resolution: more ways to be partly right. Let each criterion score z_j take values on a finite grid $\mathcal{Z}_j$. A binary verifier exposes at most two reward levels. A holistic judge exposes one scalar axis. A rubric exposes the product space

$$\mathcal{Z}_{\mathcal{R}} = \mathcal{Z}_1 \times \cdots \times \mathcal{Z}_M \quad (12)$$

before projection by (11). Even when different criterion vectors collide after weighting, the judge has evaluated the

response through a higher-resolution measurement. When weighted sums do not collide, this yields up to $\prod_j |\mathcal{Z}_j|$ attainable scalar reward levels rather than two.

This is the mathematical version of partial credit: an answer can move from $z = (0, 0, 0)$ to $(1, 0, 0)$ without satisfying all criteria. Early in RL, when most generations are imperfect, such intermediate rewards produce useful ordering among bad, partial, and nearly complete answers.

Localization: criterion failures affect the scalar advantage. The optimizer does not receive separate per-criterion gradients; it receives the scalar $\alpha^\top z$. However, the scalar advantage changes in proportion to the weighted criterion differences between sampled responses:

$$r(\mathbf{y}_a) - r(\mathbf{y}_b) = \sum_{j=1}^{M} \alpha_j \big[z_j(\mathbf{y}_a) - z_j(\mathbf{y}_b) \big]. \qquad (13)$$

A missing required element in criterion j changes the scalar reward by exactly its weighted contribution $\alpha_j \Delta z_j$. The localization therefore lives in the measurement, not in a new optimizer: GRPO still updates on a scalar advantage, but that advantage is assembled from explicit axes of quality rather than from a single free-form preference judgment.

Privileged grounding: a training-time verifier The reward in (11) depends on g, but the policy does not condition on g:

$$\mathbf{y} \sim \pi_\theta(\cdot \mid \mathbf{x}), \qquad r = \mathcal{J}(\mathbf{x}, g, \mathbf{y}, \mathcal{R}). \qquad (14)$$

This is a learning-with-privileged-information setup: grounding is available to the verifier at training time, not to the policy at rollout or evaluation time. Consequently, the reward can penalize unsupported claims and missing facts without converting the policy into a retrieval-augmented system. Successful behavior must therefore come from the policy's learned parameters rather than from copying the hidden passage.

Noise attenuation by effective criteria. Suppose criterion scores are observed with independent zero-mean judge noise: $\tilde{z}_j = z_j + \xi_j$, $\mathbb{E}[\xi_j] = 0$, $\mathrm{Var}(\xi_j) = \tau^2$. The aggregate reward noise is

$$\mathrm{Var}(\alpha^\top \xi) = \tau^2 \sum_j \alpha_j^2 = \frac{\tau^2}{M_{\mathrm{eff}}},$$
$$M_{\mathrm{eff}} = \frac{1}{\sum_j \alpha_j^2} = \frac{W^2}{\sum_j w_j^2}. \qquad (15)$$

For equally weighted criteria, $M_{\mathrm{eff}} = M$: independent criterion noise is averaged across the rubric. This is not a guarantee of judge correctness, systematic or correlated

judge errors do not average away, but it explains why decomposed scoring is preferable to a single holistic call when criterion errors are at least partly independent.

Behavioral transfer hypothesis. The expected transfer is behavioral rather than factual: criteria such as precision, constraint satisfaction, stepwise justification, grounded terminology, and calibrated uncertainty may benefit external tasks that reward similar behaviors. This motivates evaluating on disjoint reasoning benchmarks (§5).

3.4. Instantiation: Document-Derived Rubrics

We instantiate the framework with rubrics derived from an OSTI-derived corpus of roughly 100,000 scientific and technical documents. This corpus is a convenient source because the documents are abundant, naturally grounded (each rubric points to a specific passage), and require no per-criterion human annotation.

Document-to-rubric pipeline. The pipeline operates in three LLM-prompted stages:

Stage 1: Semantic analysis. For each document d, an LLM produces a structured representation $\mathbf{s}(d)$ capturing genre, primary contribution, central concepts, technical depth, and dominant reasoning mode. This representation conditions downstream synthesis.

Stage 2: Joint question–rubric synthesis. Conditioned on $(\mathbf{s}(d), d)$, the LLM produces K_d tuples $\{(q_k, p_k, \mathcal{R}_k)\}$ subject to four constraints: questions and rubrics must be self-contained without the source; questions must target deep understanding rather than surface recall; rubrics must include all five components from Definition 1; and weights must reflect the criterion's contribution to overall quality.

Stage 3: Rubric enrichment. A post-processing step augments criteria with structured cues, expected terminology, core concepts, and verification patterns to improve inter-rater consistency.

Quality assurance. Generated tuples pass structural checks before inclusion: minimum criteria per rubric, minimum total weight, non-empty question, all criterion fields present, non-negative weights. Examples failing any check are discarded. Corpus-level statistics (criteria-per-example, weight distributions, length histograms) are tracked for reporting.

Scalable generation. Documents are dispatched with bounded asynchronous concurrency; outputs are written incrementally and a content-hash index supports idempotent resume. Full data-pipeline configuration is in Appendix E.

4. Experimental Setup

4.1. Dataset

We construct a rubric-grounded dataset of document-grounded questions from OSTI scientific and technical documents; after the structural validation checks of §3.4, the dataset contains 72,755 question–rubric records. Each question is paired with a grounding passage and a structured rubric containing 5–10 weighted criteria. We partition the dataset into 70% training, 15% validation, and 15% test splits. The training split is used for RL reward computation, the validation split for model selection and hyperparameter tuning, and the test split for held-out evaluation.

4.2. Model and Infrastructure

The policy is Llama-3.1-8B-Instruct (Dubey et al., 2024) with π_{ref} initialized from the same checkpoint. Question-rubric dataset generation uses GPT-OSS-120B. Judge inference is served by a GPT-OSS-20B endpoint. Training is distributed with separate generation and judge-evaluation workers; the implementation is built on NeMo-RL [2].

4.3. Hyperparameters

For the main GRPO run, each optimization step uses $B = 64$ prompts and samples $G = 32$ generations per prompt, yielding an effective batch size of 2048. We restrict rollouts to a single turn, and enable both the leave-one-out baseline and reward normalization. The loss uses clipping parameter $\epsilon_{\mathrm{clip}} = 0.2$, advantage stabilizer $\delta = 10^{-8}$, KL coefficient $\beta = 0.01$, and the k_3 KL approximation. We optimize with AdamW at learning rate $\eta = 3 \times 10^{-7}$, weight decay 0.01, and maximum gradient norm 1.0, using 13 warmup steps followed by a constant learning-rate schedule. The judge is run with $N_{\mathrm{workers}} = 32$, temperature $\tau_{\mathcal{J}} = 0.1$, a token budget of 16,000, a maximum passage length of 50,000 characters, and worker batch size 4. Variants not enabled in the main configuration are reported in Appendix C.

4.4. Comparison Models

We compare the trained policy against its initialization and, for in-domain rubric evaluation only, the supervised warm-start:

- **Base:** Llama-3.1-8B-Instruct, no further training.

- **SFT:** supervised warm-start on question–answer data from the same document-derived corpus.

- **Ours:** the same model after one rubric-grounded GRPO run.

---

[2] https://github.com/NVIDIA/NeMo-RL

4.5. Evaluation Benchmarks

We report (i) held-out rubric reward on a random split of the synthesized tuples (in-domain), and (ii) standard accuracy on four reasoning benchmarks not derived from the training corpus: GSM8K (Cobbe et al., 2021), MATH (Hendrycks et al., 2021), GPQA Main, and GPQA Diamond (Rein et al., 2023). Using benchmarks not derived from the corpus is what makes them a transfer test rather than a recall test. Base and Ours are evaluated with the same prompt template, decoding parameters, and scoring script. We report single-sample accuracy. GSM8K and MATH use exact-match final-answer scoring after answer extraction; GPQA Main and GPQA Diamond use the standard multiple-choice accuracy protocol. In-domain rubric results use the GRPO checkpoint selected by held-out rubric reward; benchmark results are reported across the final three checkpoints of the run (Appendix H).

5. Results and Analysis

5.1. In-Domain Judge Measurements

Table 1. **In-domain held-out evaluation.** Base and GRPO are scored on the same held-out question–rubric split by the training judge under the passage-grounded rubric protocol. The SFT warm-start, whose fine-tuning format yields short direct answers rather than rubric-style responses, is scored under the complementary holistic Q&A protocol on a held-out OSTI Q&A test set (Appendix G); its row is marked † and is indicative rather than protocol-identical.

Method	Held-out Judge Score
Base	26.1%
SFT tuned†	41.8%
Ours (GRPO)	**71.7%**

Table 1 reports the in-domain held-out evaluation. For the base and GRPO models, we generate responses to the same held-out questions and score them with the training judge, GPT-OSS-20B, using the corresponding held-out rubrics and grounding passages; GRPO improves held-out rubric reward from 26.1% to 71.7%. The SFT model is instruction-tuned on question–answer pairs derived from the same corpus and produces short direct answers in that format rather than rubric-style responses; it is therefore scored under the holistic Q&A judge protocol on a held-out OSTI Q&A test set (Appendix G), where it improves substantially over the base model (41.8% vs. 24.5%). Supervised warm-starting thus helps in-domain, but the rubric-grounded GRPO policy is what closes most of the remaining gap on held-out rubric tasks.

Figure 2 provides a complementary in-domain comparison under the same passage-grounded rubric-judge protocol. The GRPO-tuned Llama-3.1-8B policy improves from

Table 2. **Transfer to reasoning benchmarks.** Numbers are accuracy; the GRPO row reports mean ± s.d. across the final three checkpoints of the single GRPO run, as a checkpoint-level variance proxy. Per-checkpoint accuracies, paired significance tests, and bootstrap confidence intervals are in Appendix H. None of these benchmarks is derived from the training corpus.

Method	GSM8K	MATH	GPQA Main	GPQA Diamond	Avg. Δ
Base	84.53	50.06	25.22	24.24	–
Ours	**84.99 ± 0.45**	**52.26 ± 0.44**	**31.47 ± 1.74**	**30.30 ± 1.49**	**+3.74**

Figure 2. **Rubric-judge benchmark comparison.** In a passage-grounded rubric-judged evaluation, the RL-tuned 8B policy substantially improves over the base 8B instruction model and approaches the displayed GPT-OSS-120B score under the same rubric-judge protocol. Because the RL policy was optimized against this judge protocol, its absolute score partly reflects judge-specific optimization pressure; §5.5 calibrates this effect with an independent judge family.

the base model's roughly 2.6/10 judge score to roughly 7.1/10, approaching the displayed GPT-OSS-120B score and surpassing several larger comparison models under the same evaluation protocol.

5.2. Out-of-Distribution Transfer

Table 2 shows transfer to disjoint benchmarks. The GPQA gains (+6.3 Main, +6.1 Diamond, averaged across checkpoints) are the largest and are statistically significant under paired item-level tests (McNemar $p < 0.001$ for GPQA Main; Appendix H), suggesting that rubric-grounded training may be especially helpful for scientific reasoning tasks where answers must coordinate facts, assumptions, and evidence. MATH improves by a smaller but significant margin (+2.2, $p < 0.001$), while GSM8K is statistically unchanged. Since none of these benchmarks is derived from the training corpus, the GPQA result is more consistent with transferable reasoning improvement than direct document recall. The flat GSM8K and modest MATH results are also informative: our generated questions are

mostly technical question-answering tasks, not deliberately constructed quantitative-problem or code-generation tasks. This likely makes the learned reward geometry better aligned with GPQA than with benchmarks that require explicit calculation routines.

5.3. Training Dynamics

Validation reward tracks training reward throughout the run (Figure 3); zero-reward judge outcomes decrease monotonically. The validation–training gap stays bounded, which argues against improvements being confined to sampled training prompts.

5.4. Judge Interface Safeguards

The reward signal comes from an LLM, so a reasonable first question is whether the policy learned to answer well or to game the judge. Cross-judge measurements addressing this question are reported in §5.5; independent human-agreement measurements remain future work, so we avoid

Figure 3. **Reward dynamics.** Training and validation rewards increase over the GRPO run while zero-reward judge outcomes decrease. The held-out trajectory supports checkpoint selection by held-out reward and argues against improvements being confined to sampled training prompts.

treating judge reliability as a fully settled empirical result. In addition, the implementation uses four interface safeguards.

Low-temperature judging. The judge is queried at $\tau_{\mathcal{J}} = 0.1$ to reduce stochastic variation in reward assignments.

Structured parsing. The judge must return schema-conforming criterion scores, a total score, and a maximum possible score. Invalid outputs are assigned conservative zero reward rather than repaired optimistically.

Document-grounded scoring. The judge sees the source passage and rubric, while the policy sees only the question. This makes the judge a document-grounded verifier and prevents the policy from using retrieval context at evaluation time.

Held-out validation. The same judge interface is applied to held-out rubric examples during training. The validation trajectory in Figure 3 therefore serves as the main check that reward increases are not confined to the sampled training prompts.

5.5. Cross-Judge Evaluation

Because the same judge family is used for both training reward and held-out evaluation, the headline rubric reward could in principle reflect the policy learning the scoring preferences of that judge rather than genuine answer quality. To measure this directly, we re-score *identical held-out responses* with a judge from a different model family, Gemma-4-31B, changing only the judge model: the same questions, grounding passages, rubrics, and prompt template.

Table 3 reports the result. The independent judge preserves the ordering and a large margin: the GRPO policy

improves from 26.1% to 49.4% under Gemma, compared with 26.1% to 71.7% under the training-family judge. Roughly half of the nominal gain is therefore judge-family-specific score inflation, while the remainder—nearly a doubling over the base model—transfers intact to a judge that never appeared during training. Under the independent judge, reward is essentially uncorrelated with response length, which argues against a verbosity-driven explanation of the gain. We accordingly treat the absolute 71.7% figure as specific to the training judge, but the qualitative conclusion, a large improvement of the GRPO policy on held-out rubric tasks, is reproduced by an independent judge family. A complementary cross-judge comparison under a holistic evaluation protocol, together with detailed agreement and verbosity measurements, is given in Appendix G.

Table 3. **Cross-judge held-out rubric evaluation.** Identical held-out responses scored under the same passage-grounded rubric protocol; only the judge model changes. The independent judge preserves the ordering and a large margin while assigning a smaller absolute gain.

| Method | Held-out Rubric Reward | |
	GPT-OSS-20B (training family)	Gemma-4-31B (independent)
Base	26.1%	26.1%
Ours (GRPO)	**71.7**%	**49.4**%

5.6. Analysis: What Generalizes?

The largest external gains are on GPQA Main and GPQA Diamond. This is the most natural transfer target for the training signal: the reward asks the policy to satisfy document-grounded scientific rubrics, and GPQA also requires careful use of scientific concepts under uncertainty.

MATH improves by a small but statistically significant margin, while GSM8K is unchanged. This suggests that the rubric reward is not merely teaching benchmark-specific shortcuts; rather, it appears to improve general problem-solving behaviors that are most visible when the downstream task resembles technical assessment. A direct test of the reward-design hypothesis would generate document-grounded quantitative tasks and include rubric criteria for equation setup, calculation, units, numerical consistency, and final-answer verification. The analogous code setting would synthesize implementation or debugging tasks from technical documents and score criteria such as API use, algorithmic correctness, edge cases, and test behavior.

6. Discussion

Rubric-grounded RL is not specific to documents or to scientific question answering. The framework requires only a checkable rubric and an instance-level grounding the judge

can use; many practical alignment problems already have these (clinical guidelines, code-style guides, legal frameworks, marking schemes). The key methodological move is exposing the structure of evaluation to the optimizer rather than collapsing it to a scalar.

The framework moves the alignment problem partly into the judge. Noisy or inconsistent criterion scores become noisy advantages, especially when the sampled responses for a prompt have nearly identical rewards. Low-temperature decoding, structured output, parser conservatism, reward clipping, and held-out evaluation are therefore part of the method rather than incidental implementation details. Rubric grounding is most useful when (i) quality decomposes naturally into checkable criteria, (ii) per-instance grounding is cheap to provide, and (iii) scalar preference data is hard or expensive to collect. It is *not* the right tool when the target behavior is genuinely holistic, when criteria are difficult to specify without domain experts, or when the cost of grouped judge calls dominates other training cost considerations.

The present data-generation pipeline mostly produces general document-grounded technical questions. A natural next step is to sample documents selectively for latent math, data-analysis, or programming content and instruct the rubric generator to create tasks whose scoring criteria explicitly reward quantitative setup, symbolic or numerical calculation, unit checks, code correctness, and executable tests. This would test whether the same rubric-grounded RL recipe can move beyond general scientific reasoning gains and produce larger improvements on math and code benchmarks.

7. Limitations

The empirical study is at one model scale (8B), one corpus family (OSTI-derived scientific and technical documents), one judge family during training, and one GRPO training run. The rubric pipeline can inherit biases of the synthesizer LLM and of the OSTI-derived source corpus, and rubric quality is enforced only by structural validity checks (§3.4) rather than human raters. Single-turn answering is the only setting evaluated; extending to multi-turn interactive tasks is straightforward in the framework but not validated here. We report paired significance tests, bootstrap confidence intervals, and checkpoint-level spread (Appendix H), but not variance across random seeds; the external benchmark improvements should therefore be interpreted as single-run evidence rather than a stable estimate of expected gain. Because the same judge family is used during training and validation, held-out rubric reward does not by itself rule out judge-specific reward hacking; the cross-judge evaluation in §5.5 bounds this effect, showing that roughly half of the nominal gain is judge-family-

specific while a large improvement persists under an independent judge. A human-agreement study on a rated subset, and comparisons against GRPO with holistic or binary rewards on the same data, remain important directions for isolating the specific contribution of rubric decomposition.

8. Conclusion

We formalized rubric-grounded RL: reinforcement learning from weighted, judge-scored criteria grounded in instance-specific evidence unavailable to the policy at rollout time. Instantiated on rubrics derived from roughly 100,000 OSTI-derived scientific and technical documents, the framework produced an 8B policy that improves held-out rubric reward—an improvement reproduced by an independent judge family—and yields statistically significant gains on external reasoning benchmarks, most prominently GPQA. The current evidence is narrower than a full ablation study: it shows that one reported rubric-grounded GRPO run improves over the base model under our evaluation protocol, not that every component (in particular, rubric decomposition versus holistic or binary judge rewards) has been causally isolated. Even with that caveat, the result suggests a promising post-training recipe for domains where quality is naturally rubric-shaped.

References

Bai, Y., Kadavath, S., Kundu, S., Askell, A., Kernion, J., Jones, A., Chen, A., Goldie, A., Mirhoseini, A., McKinnon, C., et al. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Christiano, P. F., Leike, J., Brown, T. B., Martic, M., Legg, S., and Amodei, D. Deep reinforcement learning from human preferences. *Advances in Neural Information Processing Systems*, 30, 2017.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., Hesse, C., and Schulman, J. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Dubey, A., Jauhri, A., Pandey, A., Kadian, A., Al-Dahle, A., Letman, A., Mathur, A., Schelten, A., Yang, A., Fan, A., et al. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Gunjal, A., Wang, A., Lau, E., Nath, V., He, Y., Liu, B., and Hendryx, S. Rubrics as rewards: Reinforcement learning beyond verifiable domains. *arXiv preprint arXiv:2507.17746*, 2025.

Hendrycks, D., Burns, C., Kadavath, S., Arora, A., Basart, S., Tang, E., Song, D., and Steinhardt, J. Measuring

mathematical problem solving with the MATH dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Huang, Z., Zhuang, Y., Lu, G., Qin, Z., Xu, H., Zhao, T., Peng, R., Hu, J., Shen, Z., Hu, X., et al. Reinforcement learning with rubric anchors. *arXiv preprint arXiv:2508.12790*, 2025.

Kim, S., Shin, J., Cho, Y., Jang, J., Longpre, S., Lee, H., Yun, S., Shin, S., Kim, S., Thorne, J., and Seo, M. Prometheus: Inducing fine-grained evaluation capability in language models. In *International Conference on Learning Representations*, 2024a.

Kim, S., Suk, J., Longpre, S., Lin, B. Y., Shin, J., Welleck, S., Neubig, G., Lee, M., Lee, K., and Seo, M. Prometheus 2: An open source language model specialized in evaluating other language models. *arXiv preprint arXiv:2405.01535*, 2024b.

Lee, H., Phatale, S., Mansoor, H., Lu, K., Mesnard, T., Bishop, C., Carbune, V., and Rastogi, A. RLAIF: Scaling reinforcement learning from human feedback with AI feedback. *arXiv preprint arXiv:2309.00267*, 2023.

Lee, Y., Kim, J., Kim, J., Cho, H., and Kang, P. CheckEval: Robust evaluation framework using large language model via checklist. In *HEAL Workshop at CHI*, 2024.

Lightman, H., Kosaraju, V., Burda, Y., Edwards, H., Baker, B., Lee, T., Leike, J., Schulman, J., Sutskever, I., and Cobbe, K. Let's verify step by step. *arXiv preprint arXiv:2305.20050*, 2023.

Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C. L., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744, 2022.

Rafailov, R., Sharma, A., Mitchell, E., Ermon, S., Manning, C. D., and Finn, C. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36, 2023.

Rein, D., Hou, B. L., Stickland, A. C., Petty, J., Pang, R. Y., Dirani, J., Michael, J., and Bowman, S. R. GPQA: A graduate-level google-proof Q&A benchmark. *arXiv preprint arXiv:2311.12022*, 2023.

Schulman, J. Approximating KL divergence. *Blog post*, 2020.

Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Zhang, M., Li, Y. K., Wu, Y., and Guo, D. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Stiennon, N., Ouyang, L., Wu, J., Ziegler, D. M., Lowe, R., Voss, C., Radford, A., Amodei, D., and Christiano, P. F. Learning to summarize with human feedback. *Advances in Neural Information Processing Systems*, 33: 3008–3021, 2020.

Uesato, J., Kushman, N., Kumar, R., Song, H. F., Siegel, N. Y., Wang, L., Creswell, A., Irving, G., and Higgins, I. Solving math word problems with process- and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Wang, P., Li, L., Shao, Z., Xu, R., Dai, D., Li, Y., Chen, D., Wu, Y., and Sui, Z. Math-Shepherd: Verify and reinforce LLMs step-by-step without human annotations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, pp. 9426–9439, 2024.

Ye, S., Kim, D., Kim, S., Hwang, H., Kim, S., Jo, Y., Thorne, J., Kim, J., and Seo, M. FLASK: Fine-grained language model evaluation based on alignment skill sets. In *International Conference on Learning Representations*, 2024.

Yu, Q., Zhang, Z., Zhu, R., Yuan, Y., Zuo, X., Yue, Y., Dai, W., Fan, T., Liu, G., Liu, L., et al. DAPO: An open-source LLM reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*, 2025.

Zheng, C., Liu, S., Li, M., Chen, X.-H., Yu, B., Gao, C., Dang, K., Liu, Y., Men, R., Yang, A., Zhou, J., and Lin, J. Group sequence policy optimization. *arXiv preprint arXiv:2507.18071*, 2025.

Zheng, L., Chiang, W.-L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E. P., et al. Judging LLM-as-a-judge with MT-Bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36, 2023.

Zhou, Y., Li, S., Liu, S., Fang, W., Zhang, K., Zhao, J., Yang, J., Zhou, Y., Lv, J., Zheng, T., et al. Breaking the exploration bottleneck: Rubric-scaffolded reinforcement learning for general LLM reasoning. *arXiv preprint arXiv:2508.16949*, 2025.

Algorithm 1 Rubric-Grounded GRPO

Require: Policy π_θ, reference π_{ref}, judge $\mathcal{J}$, dataset $\mathcal{D}$, group size G, clip ϵ_{clip}, stabilizer δ, KL coefficient β, learning rate η, max gradient norm γ

1: Initialize $\pi_{\text{gen}} \leftarrow \pi_\theta$
2: **for** epoch $= 1, \ldots, E$ **do**
3:    **for** batch $\{(\mathbf{x}_i, p_i, \mathcal{R}_i)\}_{i=1}^B \sim \mathcal{D}$ **do**
4:       Synchronize $\pi_{\text{gen}} \leftarrow \pi_\theta$
5:       **for** $i = 1, \ldots, B$ **do**
6:          Sample $\{\mathbf{y}_i^{(g)}\}_{g=1}^G \sim \pi_{\text{gen}}(\cdot \mid \mathbf{x}_i)$; record $\log \pi_{\text{gen}}$.
7:       **end for**
8:       **for** $i = 1, \ldots, B$; $g = 1, \ldots, G$ **(parallel) do**
9:          $R_i^{(g)} \leftarrow \mathcal{J}(\mathbf{x}_i, p_i, \mathbf{y}_i^{(g)}, \mathcal{R}_i)/W_i$
10:      **end for**
11:      **for** $i = 1, \ldots, B$; $g = 1, \ldots, G$ **do**
12:         $b_i^{(g)} \leftarrow \frac{1}{G-1} \sum_{g' \neq g} R_i^{(g')}$; $\sigma_i \leftarrow \text{std}(R_i)$
13:         $A_i^{(g)} \leftarrow (R_i^{(g)} - b_i^{(g)})/(\sigma_i + \delta)$ if $\sigma_i > 0$, else 0
14:      **end for**
15:      Compute $\log \pi_\theta, \log \pi_{\text{ref}}$ via forward passes
16:      **for** each response token (i, g, t) **do**
17:         $r_t \leftarrow \exp(\log \pi_\theta - \log \pi_{\text{gen}})$
18:         $\ell_t \leftarrow -\min(r_t A_t, \text{clip}(r_t, 1-\epsilon_{\text{clip}}, 1+\epsilon_{\text{clip}})A_t)$
19:         $\widehat{\text{KL}}_t \leftarrow \exp(\log \pi_{\text{ref}} - \log \pi_\theta) - 1 - (\log \pi_{\text{ref}} - \log \pi_\theta)$
20:      **end for**
21:      $\mathcal{L} \leftarrow \text{mean}(\ell_t + \beta \widehat{\text{KL}}_t)$
22:      $\theta \leftarrow \theta - \eta \, \text{clip\_grad}(\nabla_\theta \mathcal{L}, \gamma)$
23:    **end for**
24: **end for**

A. Full Algorithm

B. Estimator Notes

LOO baseline. For i.i.d. rewards $R_1, \ldots, R_G$ with mean μ and variance σ^2, the leave-one-out baseline $b^{(g)} = \frac{1}{G-1} \sum_{g' \neq g} R_{g'}$ satisfies $\mathbb{E}[b^{(g)}] = \mu$, $\text{Cov}(R_g, b^{(g)}) = 0$, and $\text{Var}(b^{(g)}) = \sigma^2/(G-1)$.

k_3 **KL approximation.** The approximation $\widehat{\text{KL}} = e^u - 1 - u$ is nonnegative by convexity ($e^u \geq 1+u$), equals zero iff $u = 0$, and has Taylor expansion $\widehat{\text{KL}} = u^2/2 + O(u^3)$.

Judge-noise heuristic. Let the normalized reward be $r = \sum_j w_j s_j / W$, where $W = \sum_j w_j$. If criterion score noise is zero-mean, independent, and has common variance τ^2, then the aggregate noise variance is

$$\text{Var}(r) = \tau^2 \frac{\sum_j w_j^2}{W^2} = \frac{\tau^2}{M_{\text{eff}}}, \quad M_{\text{eff}} = \frac{W^2}{\sum_j w_j^2}. \quad (16)$$

Thus equally weighted criteria reduce independent criterion noise by a factor of M, and uneven weights reduce it by the effective number of criteria M_{eff}. This motivates multi-criterion rubrics but is not used as a formal reliability guarantee in the main paper.

C. Variants Supported but Not Used in the Main Run

Importance sampling. For multi-step updates per rollout, token-level IS uses $w_t = \exp(\log \pi_\theta - \log \pi_{\text{gen}})$. Sequence-level IS (GSPO) uses the geometric mean of pertoken ratios. Truncated variants (TIS, ICEPOP, Seq-Mask-TIS) cap or mask weights outside a configured band.

Dual clipping. For $A_t < 0$, $\ell_t \leftarrow \max(\ell_t^{\text{clip}}, -cA_t)$ with $c > 1$ (typically 3).

Dynamic sampling (DAPO). Filter prompts with $\sigma_i = 0$ and re-sample until the batch contains the required number of informative prompts.

Reward shaping. A length penalty discourages neartruncation responses; a truncation penalty multiplies reward by $\alpha_{\text{stop}} \in [0, 1)$ when the response lacks a stop token. Both are disabled in main runs.

D. Judge Prompt Template

```
SYSTEM: You are a strict, objective
academic evaluator. Score the RESPONSE
against each evaluation criterion using
the provided scoring guide, required
elements, and expected keywords. Return
ONLY a valid JSON object.

USER:
SOURCE PASSAGE: [g, truncated]
QUESTION: [x]
RESPONSE: [y]
CRITERIA (total weight W):
  1. name, w_1, eta_1,
     required E_1, guide, kappa_1, nu_1
  ...
Return:
{ "scores": {"c_1": s_1, ...},
  "total": <sum>, "max_total": <W>,
  "reasoning": "<brief>" }
```

E. Data Schema and Pipeline Configuration

```
{
  "question": <string>,
  "passage":  <string>,
```

```
"criteria": [
  { "id": <string>, "weight": <float>,
    "name": <string>,
    "description": <string>,
    "required_elements": [<string>],
    "scoring_guide": <string>,
    "verification_method": <string>,
    "expected_keywords": [<string>],
    "expected_concepts": [<string>] },
  ...
],
"question_rationale": <string>,
"document_analysis": {
  "genre": <string>,
  "contribution": <string>,
  "concepts": [<string>],
  "depth": <string>,
  "reasoning_mode": <string>
},
"doc_hash": <string>
}
```

F. Held-out Length and Reward Analysis

To test whether the in-domain held-out reward is explained primarily by verbosity, we reconstruct the exact validation split of the OSTI-derived question–rubric dataset used for the reported GRPO validation run. The split contains 10,914 validation examples, produced from 72,755 question–rubric records using a 15% validation split and seed 42. We then join the validation records to the logged GRPO rollout file by validation index, preserving each question, grounding passage, rubric, generated response, scalar judge reward, and response length.

Table 4. **Held-out response length and reward.** Columns: mean response length in tokens, held-out rubric reward, reward per 1,000 response tokens, and per-example correlation between length and reward under the training judge. The GRPO row is computed on the exact held-out validation split of the OSTI-derived question–rubric dataset used for the reported result; the base row uses responses regenerated on the identical validation indices. The SFT warm-start is omitted because its short direct-answer format is evaluated under a different protocol (Appendix G). Length–reward correlations under the independent judge are reported in Appendix G.

Method	Tokens	Reward	Reward/1K	Corr
Base	2172.4	26.1%	0.120	–
GRPO	3702.5	71.7%	0.194	0.178

The positive correlation between response length and reward for the GRPO validation set is modest ($r = 0.178$). This does not rule out judge preference effects, but it argues against a purely length-driven explanation for the held-out reward. The frozen GRPO validation responses

are preserved as a fixed artifact released with the paper (Appendix J). For cross-judge robustness, we re-score this same frozen artifact with an independent judge family, changing only the judge model and not the policy responses; results are reported in §5.5 and Appendix G.

G. Cross-Judge Evaluation Details

This appendix expands on the cross-judge evaluation of §5.5.

Rubric-protocol setup. The GRPO responses are the frozen validation artifact from the reported run, covering all 10,914 held-out examples; base-model responses are regenerated on the identical validation indices with the same prompt template. Both response sets are scored by Gemma-4-31B using the same judge prompt, rubric serialization, and low-temperature decoding as the training judge. The Gemma judge returns parseable scores for more than 99.5% of examples in each response set; unparseable outputs are excluded from the reported means. Per-example rewards from the two judges correlate at $r = 0.59$ on the GRPO responses.

Holistic-protocol cross-judging. As a complementary check under a different evaluation protocol, we re-score the base and SFT model predictions on the held-out OSTI Q&A test set with both judge families under a holistic correctness/completeness/groundedness rubric (Table 5). The ordering is again preserved under both judges; the independent judge in fact scores the SFT model *higher* than the GPT-OSS judge does, indicating that the measured improvements are not an artifact of idiosyncratic GPT-OSS scoring preferences.

Table 5. **Cross-judge holistic Q&A evaluation.** Identical model predictions on the held-out OSTI Q&A test set scored by two judge families under a holistic correctness/completeness/groundedness protocol (overall score in $[0, 1]$). Model ordering is preserved under both judges.

Method	Holistic Judge Score	
	GPT-OSS-120B	Gemma-4-31B
Base	24.5%	21.4%
SFT tuned	41.8%	49.8%

Verbosity under the independent judge. LLM judges often prefer longer responses, so a natural concern is that the GRPO policy's longer answers (Appendix F) drive its scores. Under the independent Gemma judge, the correlation between response length and reward on GRPO responses is $r = -0.05$ (and $r = -0.40$ on base responses), compared with a modest $r = 0.18$ under the training judge. The independent judge therefore assigns the GRPO pol-

icy nearly double the base reward while being essentially indifferent to its response length, which argues against a verbosity-driven explanation of the cross-judge gain.

H. Statistical Robustness of Transfer Results

The transfer results come from a single GRPO training run; we do not have multiple random seeds. To characterize variability and significance without additional training, we use two complementary item-level analyses on the per-example benchmark outputs (Table 6): (i) accuracy for each of the final three GRPO checkpoints, whose spread serves as a cheap checkpoint-level variance proxy (it does not substitute for seed-level variance), and (ii) paired tests against the base model on the strongest late checkpoint—an exact McNemar test on discordant answer pairs and a paired bootstrap 95% confidence interval on the accuracy difference (10,000 resamples).

The GPQA Main and MATH improvements are statistically significant ($p \leq 0.001$), GPQA Diamond is borderline ($p = 0.052$) with a confidence interval excluding zero, and GSM8K is statistically indistinguishable from the base model. We therefore describe the transfer effect as concentrated on scientific reasoning (GPQA) with a small significant MATH gain, rather than as a uniform improvement across benchmarks.

I. Qualitative Examples

For qualitative inspection, we pair frozen GRPO validation responses with base-model responses regenerated on the identical held-out validation indices, so that before/after comparisons never mix non-identical evaluation artifacts. Table 7 shows a representative example in which the base model fails the rubric and the GRPO policy satisfies it, under *both* judge families of §5.5. Table 8 complements this with full-credit and partial-credit GRPO responses, reporting per-criterion awarded weights: the partial-credit structure of the reward is directly visible (an example can earn full marks on formulation criteria while missing a numerical-accuracy criterion), and on these examples the two judge families agree closely on the aggregate score.

J. Reproducibility Details

We intend to release, subject to institutional review, the rubric-generation pipeline, training and evaluation configurations, frozen evaluation responses, and cached judge verdicts sufficient to reproduce the reported tables without access to internal inference endpoints.

The experiments use the OSTI-derived question–rubric dataset described in §3.4, containing 72,755 validated question–rubric records. The reported GRPO validation run uses the deterministic validation split produced by `split_validation_size=0.15` and seed 42, yielding 10,914 validation examples. Each record contains a question, grounding passage, structured weighted rubric, document analysis metadata, and a document hash.

For reproducibility, the following items should be released or cached with the paper artifact:

- the number of source documents sampled and the document-hash split used to prevent document-level leakage;

- filtering criteria for document quality, passage length, non-empty question text, rubric completeness, positive criterion weights, and parseable schema fields;

- passage length distribution and truncation policy used by the judge;

- the question/rubric generation prompt and any post-generation validation checks;

- train/validation/test split method, random seed, and exact validation indices used for reported results;

- deduplication method across documents, questions, passages, and rubrics;

- the judge prompt schema shown in Appendix D;

- parsing failure rate for judge outputs and the fallback reward assigned when parsing fails;

- frozen responses and cached judge verdicts sufficient to reproduce the reported tables without querying an internal endpoint.

Table 6. **Statistical robustness of benchmark transfer.** Accuracy of the base model and the final three GRPO checkpoints (single training run). McNemar p and the paired bootstrap 95% confidence interval on the accuracy difference (in points) compare the strongest late checkpoint (step 1330) against base on identical items.

Benchmark	Base	Step 1320	Step 1330	Step 1340	Mean $\pm$ s.d.	McNemar p	95% CI on Δ
GSM8K	84.53	85.44	84.38	85.14	84.99 ± 0.45	0.94	$[-1.90, +1.67]$
MATH	50.06	51.90	52.88	52.00	52.26 ± 0.44	< 0.001	$[+1.50, +4.12]$
GPQA Main	25.22	30.13	33.93	30.36	31.47 ± 1.74	0.001	$[+4.02, +13.39]$
GPQA Diamond	24.24	29.80	32.32	28.79	30.30 ± 1.49	0.052	$[+0.51, +15.66]$

Table 7. **Qualitative before/after example** (held-out validation example; excerpts abbreviated for space). The base model conflates kinetic and total energy and never produces a defensible evaluation of the design inequality; the GRPO policy executes the full calculation chain required by the rubric. Rewards are normalized rubric scores.

Field	Content
Question	A booster design uses focusing period $S = 2\,\text{m}$. Using $S \leq 12.22\sqrt{\beta\gamma}\sqrt{E[\text{MV/m}] \cdot \sin\varphi_s}$, compute $S_{\max}$ at proton kinetic energy 800 MeV, gradient $E = 25\,\text{MV/m}$, $\varphi_s = -30°$, showing all intermediate steps, and state whether $S = 2\,\text{m}$ satisfies the inequality.
Rubric criteria	Correct total energy and relativistic γ (w=20); accurate β and $\beta\gamma$ (w=20); proper use of $\sin\varphi_s$ (w=15).
Base answer	"Total energy $= 800\,\text{MeV} -938.27\,\text{MeV} +1$ (to account for rest mass energy) ... $\gamma = 800/938.27$ ... $\gamma = 8.526$" — conflates kinetic and total energy, reports an incorrect γ, and drifts without completing a defensible evaluation of the inequality.
GRPO answer	Computes $E_{\text{tot}} = 800 + 938.27 = 1738.27\,\text{MeV}$, $\gamma \approx 1.85$, $\beta\gamma \approx 1.56$, $\sin 30° = 0.5$, $S_{\max} \approx 54.2\,\text{m}$, and concludes that $S = 2\,\text{m}$ satisfies the inequality.
Judge rewards	Base: 0.0 (independent judge). GRPO: 1.0 (training judge) and 1.0 (independent judge).

Table 8. **Full- and partial-credit GRPO responses with per-criterion scores** (held-out validation examples; questions abbreviated). Awarded/maximum weights per criterion are from the independent judge; the normalized rewards from both judges are shown for comparison. The middle example illustrates partial credit: the response sets up the correct posterior parameters and system-reliability formulation but misses the numerical criterion, and both judge families assign it the same aggregate score.

Question (abbreviated)	Per-criterion awarded / max	Training	Independent
Autoresonant accelerator: derive the scaling constant C from the γ=100 case, predict the radial modulation for γ=70, and evaluate the $\leq 30\%$ design requirement.	Derivation of scaling constant C: 20/20; modulation for γ=70: 20/20; evaluation against requirement: 20/20	1.00	1.00
Bayesian reliability of a four-component series system: update beta priors with test data, form the posterior of system reliability, and compute its posterior mean.	Posterior beta parameters: 25/25; system-reliability formulation: 25/25; numerical posterior mean: 0/20	0.71	0.71
Reversed-field-pinch alpha-particle confinement: compute the velocity ratio η, evaluate $J_1(\sigma)$ and the enclosed current, and compare with the confinement threshold.	η computation: 10/20; Bessel/current evaluation: 10/20; threshold comparison: 20/20	0.50	0.67