Spherization Layer: Representation Using Only Angles

Abstract

In neural network literature, angular similarity between feature vectors is frequently used for interpreting or re-using learned representations. However, the inner product in neural networks partially disperses information over the scales and angles of the involved input vectors and weight vectors. Therefore, when using only angular similarity on representations trained with the inner product, information loss occurs in downstream methods, which limits their performance. In this study, we proposed *spherization layer* to represent all information on angular similarity. The layer 1) maps the pre-activations of input vectors into the specific range of angles, 2) converts the angular coordinates of the vectors to Cartesian coordinates with an additional dimension, and 3) trains decision boundaries from hyperplanes, without bias parameters, passing through the origin. This approach guarantees that representation learning always occurs on the hyperspherical surface without the loss of any information unlike other projection-based methods. Furthermore, this method can be applied to any network by replacing an existing layer. We validate the functional correctness of the proposed method in a toy task, retention ability in well-known image classification tasks, and effectiveness in few-shot learning, word analogy test, and hyperspherical learning.

1 Introduction

The inner product is a key element constituting layers in deep neural networks with the nonlinear activation function. The inner product with the Euclidean norms and the angle, that is, $\|\mathbf{w}_i\|\|\mathbf{x}_j\| \cos \boldsymbol{\theta}_{ij}$, has been analyzed in terms of the norms $\|\mathbf{w}_i\|\|\mathbf{x}_j\|$ and the angle $\cos \boldsymbol{\theta}_{ij}$, independently [14, 15, 37]. All factors of the inner products learn distinct information. Therefore, using only one factor results in information loss when re-using or understanding the information in downstream tasks. This problem is termed as *dispersion problem*. The angular similarity between features is frequently used. However, this technique causes a dispersion problem in advanced methods in neural network literature such as decoupled network [15], representation learning [6, 7, 23, 24, 34], metric learning [35], zero-shot learning [26], and generative model [3, 27]. To mitigate the dispersion problem, numerous angle-based learning approaches [1, 12, 13, 16, 18, 17, 35, 36, 38] have been proposed. However, these studies are based on projection onto the hyperspherical surface. In this projection method, distinction by the scale of features is ignored. Therefore, information loss occurs.

We proposed the *spherization layer* as an explicit solution for the dispersion to completely eliminate the interference of the norms in training without drawbacks. This layer is used to locate all represen-

Figure 1: Overview of *spherization layer*. The red box indicates the existing fully connected layer to be replaced with the spherization layer in the blue box. The relations of the input and output of the stage (1), (2), and (3) are illustrated as graphs, which are clearly defined in Eq. 4, Eq. 8, and Eq. 10, respectively. The right side displays how to generate angular coordinates and convert them to Cartesian coordinates in a 3-dimensional space on MNIST

tations onto a constrained region on the hyperspherical surface and train hyperplanes passing through the origin to learn representations with only the angles.

The spherization layer consists of three main components: (1) Angularization function that converts the pre-activations from the previous hidden layer to angles; (2) Conversion from spherical coordinates to Cartesian coordinates located on the hyperspherical surface; (3) *No-bias* layer, a hidden layer without bias parameter, that determines decision boundaries by using only the angles. Figure 1 illustrates the design of the spherization layer. Through *spherization*, representations are located on the hyperspherical surface and the effect of the norms in representation learning is completely eliminated. Therefore, neural networks are enforced to express all representations differently by using only the angles.

We experimentally verified the functional correctness of the spherization layer in a toy task and its applicability to feedforward and convolutional neural networks by evaluating performance on image classification tasks. The results reveal that the training ability of original networks is preserved after applying the spherization layer. Furthermore, we analyzed the sensitivity to width and depth. Finally, we investigated the effect of the methods in downstream tasks through visualization, word analogy test, and few-shot learning. We compared our methods to an angle-based approach using direct projection [15, 19, 21].

The contributions of this paper are as follows:

- To address the dispersion problem, we propose the *Spherization layer* to represent all feature vectors on the hyperspherical surface and learn the representations with only the angles.

- We validate the wide-applicability and scalability of the spherization layer without any loss of performance through experiments on various well-known networks.

- We empirically show that the spherization layer can be used in many applications in which angular similarity is an critical metric in the task.

2 Background

Conversion Spherical to the Cartesian Coordinate System   In most neural networks, all input samples on the n-dimensional space are represented as Cartesian coordinates, in which i-th column value denotes the distance from the origin along the i-th axis, and neural networks trains them by using neurons in which the inner product between the input and weight vector occurred. The pre-activations from neurons are used to determine whether neurons should be activated by using the following activation function. In this process, the pre-activations are calculated by using weight and bias parameters, represented as Cartesian coordinates, which can be converted to spherical coordinates. Given a vector $\mathbf{s}$ represented as Cartesian coordinates on the n-dimensional space, $\mathbf{s}$ can be defined as spherical coordinates $\boldsymbol{\theta} = [r, \boldsymbol{\varphi}]$, composed of a radial coordinate r and n-1 angular coordinates $\boldsymbol{\varphi} = [\varphi_1, \varphi_2, ..., \varphi_{n-1}]$. In this case, the k-th axis of $\mathbf{s}$ can be computed from $\boldsymbol{\theta}$ with Eq. 1

$$\mathbf{s} = [r \cos \varphi_1, \cdots, r \cos \varphi_k \prod_{i=1}^{k-1} \sin \varphi_i, \cdots, r \prod_{i=1}^{n-1} \sin \varphi_i] \tag{1}$$

, where $s_{1<k<n} = r \cos \varphi_k \prod_{i=1}^{k-1} \sin \varphi_i$.

Generally, the spherical coordinate system is a 3-dimensional version of the polar coordinate system. However, the spherical coordinate system in the followings indicates all n-dimensional version of the polar coordinate system, where n is greater than or equals 2.

3 Spherization Layer

We proposed *spherization layer* as displayed in Figure 1 to locate feature vectors on the hyperspherical surface without any loss of information and learn hyperplanes by using only the angles. In this method, a layer of an original network is selected to learn representations by angular similarity. Next, the layer is replaced to a *spherization layer* through three sequential stages: (1) *Angularization*, (2) *Conversion to Cartesian*, and (3) *No-bias training* notated as f, g, and h functions, respectively. The final form of spherization layer f_{sph} is expressed as Eq. 2.

$$f_{sph} = (h \circ g \circ f), \quad f_{sph} : \mathbb{R}^n \to \mathbb{R}^m \tag{2}$$

After training with the layer, we can obtain the representations on the $(n + 1)$-spherical surface, namely spherized representations, as the outputs of $(g \circ f)$ operations.

The common goal of all stages is to preserve the training ability of the original network while the spherization layer trains all information on the $(n + 1)$-spherical surface. The angularization locates all pre-activations on the safe spherical surface. The conversion to Cartesian results in the generation of compatible representations to the ordinary layer. No-bias training enforces training by only the angles. In the followings, we elaborate each stages more detail and only annotate the $(l - 2)$th and (l)th layer as $[l - 2]$ and $[l]$, respectively, for the simplicity.

3.1 Angularization

$$\boldsymbol{\varphi} = f(\mathbf{z}), \quad f : \mathbb{R}^n \to \mathbb{R}^n \tag{3}$$

Angularization is the stage to map a pre-activation vector $\mathbf{z}$, passed from $(l - 1)$th layer, to angular coordinates $\boldsymbol{\varphi}$. The n indicates the dimension of the pre-activation vector. The role of this stage is to configure the shape of the mapped region on the $(n + 1)$-spherical surface for resolving training and computational difficulty.

Angularization f is implemented by applying the following element-wise function to all coordinates of $\mathbf{z}$ as an activation function, and f is illustrated as Eq.4.

$$f(\mathbf{z}) = \left(\frac{\pi}{2} - \varphi_L\right) \cdot \sigma(\alpha \cdot \mathbf{z}) + \varphi_L \tag{4}$$

, where the terms and form are used by three following motivations.

Converting Pre-Activation to the Angular Coordinate   The first step is to convert the input vector into angular coordinates. To ensure conversion as bijective mapping, we restricts the range of the function as $[0, \frac{\pi}{2}]$. To allow a unrestricted input representation on the real-valued domain, the sigmoid function $\sigma(\cdot)$ is used with weight $\frac{\pi}{2}$ for the range setting. As the sigmoid function used, the input vector should be pre-activations, not activations because when activations from ReLU or sigmoid are passed to the angularization, inefficient use of the spherical surface or gradient amplification, respectively, may occur. After converting pre-activations to angular coordinates, the representations on the hyperspherical surface in the same range were located by setting a consistent radius over all inputs. This radius scale is controlled in the conversion-to-Cartesian stage.

Tailoring Angular Representation Space   In the conversion from angular to Cartesian coordinates, the last coordinate can be an extremely small value because trigonometric values in $[0, 1]$ are multiplied many times. This scale descent can map all values in the axis to only a single value by the limit of the floating point data type. To reduce this effect in the angularization, we introduce a lower bound φ_L of angles to guarantee distinguishable values in its corresponding converted Cartesian coordinates as follows:

$$\varphi_L = \sin^{-1}\left(\delta^{1/n}\right) \tag{5}$$

, where δ is a minimal trigonometric value to guarantee the distinguishable representations. The details are presented in Appendix A. We set δ to the empirically obtained proper value 10^{-6}, for all experiments.

Scaling Pre-Activations   In angularization, the activations are concentrated onto the small region because of the lower bound. This concentration renders training difficult with the decrease in the variance. To reduce the effect, we set a learnable parameter α as a weight of $\mathbf{z}$, which controls the variance of $\mathbf{z}$. Using this scale factor, the generated angular representations become abundant.

3.2   Conversion-to-Cartesian

$$\mathbf{s} = g(\boldsymbol{\varphi}), \quad g : \mathbb{R}^n \to \mathbb{R}^{n+1} \tag{6}$$

In the *Conversion-to-Cartesian* stage, the angular coordinates of the previous stage are converted to Cartesian coordinates on the $(n + 1)$-spherical surface. This conversion ensures consistency of the coordinate system with other ordinary layers. This implementation is based on Eq. 1 with the modified range of angles as the following equation.

$$g(\boldsymbol{\varphi}) = [r \cos \varphi_1, \cdots, r \cos \varphi_k \textstyle\prod_{i=1}^{k-1} \sin \varphi_i, \cdots, r \prod_{i=1}^{n} \sin \varphi_i], \quad \varphi_i \in \left[\varphi_L, \frac{\pi}{2}\right] \tag{7}$$

Calculation Trick   Implementation of Eq. 7 as a tensor operation requires the trick defined in the following equation:

$$
\begin{aligned}
\boldsymbol{\phi} &= \mathbf{W}_\varphi^\top \boldsymbol{\varphi} \\
\mathbf{s} &= r \cdot \exp\left(\mathbf{W}_\phi^\top \ln\left(\sin \boldsymbol{\phi}\right) + \ln\left(\cos\left(\boldsymbol{\phi} + \mathbf{b}_\phi\right)\right)\right)
\end{aligned}
\tag{8}
$$

, where $\boldsymbol{\phi}$ is a dimension-expended vector in $\mathbb{R}^{n+1}$ and $\phi_{n+1} = \phi_n$, and r is a constant to control radius. Here, $\mathbf{W}_\varphi$, $\mathbf{W}_\phi$, and $\mathbf{b}_\phi$ are constant matrices and vector in $\mathbb{R}^{n \times (n+1)}$, $\mathbb{R}^{(n+1) \times (n+1)}$, and $\mathbb{R}^{(n+1)}$, respectively. $\mathbf{W}_\varphi = [\mathbf{I}_n; \mathbf{v}]$, where $\mathbf{v} = [\mathbf{0}; 1]^\top \in \mathbb{R}^n$, is used for matching the dimension between $\boldsymbol{\varphi}$ and $\mathbf{s}$. The other constants are used for calculating logarithm trigonometric values from expanded angular coordinates in the way of matrix multiplication, where $\mathbf{W}_\phi$ is an upper triangular matrix in which all diagonals are zero and $(\mathbf{W}_\phi)_{n,n+1}$ is also zero, and $\mathbf{b}_\phi = [\mathbf{0}; -\frac{\pi}{2}]^\top$. See Appendix B for detail hyperparameters and process.

3.3   No-bias Training

$$\mathbf{z}^{[l]} = h(\mathbf{s}), \quad h : \mathbb{R}^{n+1} \to \mathbb{R}^m \tag{9}$$

Through angularization and conversion-to-Cartesian, all representations are located on the $(n + 1)$-spherical surface. In this case, any update to the representations is determined by the change of angular

Figure 2: Visualization of Hyperplanes, Decision Boundary, and Representations in the Toy Task. (w: hyperplanes, boundary: decision boundary, red or green point: representations for label 0 or 1)

similarity. However, hyperplanes determined by the next layer on the $(n + 1)$-dimensional space may not use only the angular similarity, which may assign semantic information to the Euclidean norm of the spherized representation. To synchronize these parameters, we used no-bias training using only the weight parameters $\mathbf{W}^{[l]}$ as illustrated in Eq. 10.

$$\mathbf{z}^{[l]} = \mathbf{W}^{[l]\top} \mathbf{s} \tag{10}$$

Effect of Bias Elimination to Training   In the ordinary layer, the problem of bias elimination is that hyperplanes passing through the origin cannot be shifted to another parallel hyperplanes. However, the problem disappears when all feature vectors are located on the $(n + 1)$-spherical surface because the decision boundary can be shifted by only the angle changes of $(n + 1)$-dimensional hyperplanes even though they pass through the origin.

3.4   Optimization with Overall Process

A training loss L is calculated in the same manner as the original network. The gradient of L for the spherization layer is calculated by multiplying the following partial derivative $\frac{\partial L}{\partial \mathbf{W}}$ to the original backpropagation step from the $(l - 2)$th to (l)th layer. The first term $\frac{\partial L}{\partial \mathbf{z}^{[l]}}$ is calculated by the subsequent layers in the same way of the original network.

$$
\begin{aligned}
\frac{\partial L}{\partial \mathbf{W}} &= \frac{\partial L}{\partial \mathbf{z}^{[l]}} \cdot \frac{\partial \mathbf{z}^{[l]}}{\partial \mathbf{s}} \cdot \frac{\partial \mathbf{s}}{\partial \boldsymbol{\varphi}} \cdot \frac{\partial \boldsymbol{\varphi}}{\partial \mathbf{z}} \cdot \frac{\partial \mathbf{z}}{\partial \mathbf{W}} \\
\frac{\partial \mathbf{z}}{\partial \mathbf{W}} &= \mathbf{a}^{[l-2]} \\
\frac{\partial \boldsymbol{\varphi}}{\partial \mathbf{z}} &= \left(\frac{\pi}{2} - \varphi_L\right) \cdot \alpha \cdot \sigma'(\alpha \cdot \mathbf{z}) \\
\frac{\partial \mathbf{s}}{\partial \boldsymbol{\varphi}} &= [-r \sin \varphi_1, \cdots, -r \prod_{i=1}^{k} \sin \varphi_i, \cdots, r \cos \varphi_n \prod_{i=1}^{n-1} \sin \varphi_i] \\
\frac{\partial \mathbf{z}^{[l]}}{\partial \mathbf{s}} &= \mathbf{W}^{[l]}
\end{aligned}
\tag{11}
$$

4   Experiments

First, we define two terms for simplicity on indicating two networks: one is the network before applying the spherization layer, called *original network*, and the other is the network after substituting an ordinary layer with the spherization layer, called *spherized network*. In the followings, we used these two terms consistently. All experiments were performed five times with random seeds and their training and test accuracy were evaluated except word analogy test and few-shot learning. The mean μ and standard deviation σ of accuracy are represented as $\mu \pm \sigma$ in each table.

4.1   Functional Correctness Test on a Toy Task

Experimental Settings   We verified the spherization layer for learning decision boundaries on a simple binary classification task. We set up the simple binary classification task: given $(\mathbf{x}_i, y_i)$ pairs, where $\mathbf{x}_i$ is the i-th input sample in $\mathbb{R}^2$ and $y_i \in \{0, 1\}$ is the label of $\mathbf{x}_i$. We randomly generated 100 input samples located around $(0, 0)$ for the label 0, and the

Figure 3: Input samples for the toy task

Table 1: Retention of the Training Ability on Image Classification with Various Datasets and Models (Accuarcy(%): $\mu \pm \sigma$)

Network	Dataset	Reference		Reproduced		Spherized	
		train	test	train	test	train	test
SimpleFNN [8]	MNIST	–	98.47	99.99±0.01	98.58±0.03	99.99±0.01	**98.65±0.04**
LeNet-5 [11]		–	99.05	99.55±0.09	99.10±0.05	99.79±0.09	**99.14±0.04**
	F-MNIST	–	94.70	99.19±0.14	**94.32±0.05**	99.12±0.02	94.26±0.07
VGG-11 [33]	CIFAR10	–	90.90	97.03±0.08	91.08±0.15	97.46±0.03	**91.14±0.12**
	CIFAR100	–	66.80	99.69±0.03	68.14±0.34	99.81±0.03	**68.83±0.26**

Table 2: Robustness on Network Width and Depth on Image Classification with CIFAR100 (Accuarcy(%): $\mu \pm \sigma$)

Depth	Width	Reference[1]		Reproduced		Spherized	
		train	test	train	test	train	test
	16/32/64/128	–	–	74.32±4.52	**60.16±0.26**	83.84±0.93	60.06±0.37
	32/64/128/256	–	–	98.27±0.28	64.86±0.15	98.78±0.29	**65.25±0.20**
VGG-11	64/128/256/512	–	–	99.69±0.03	68.14±0.34	99.81±0.03	**68.83±0.26**
	128/256/512/1024	–	–	99.90±0.02	70.43±0.08	99.93±0.01	**70.69±0.27**
	256/512/1024/1024	–	–	99.90±0.01	71.45±0.23	99.93±0.00	**72.05±0.25**
VGG-11		–	68.64	99.69±0.03	68.14±0.34	99.81±0.03	**68.83±0.26**
VGG-16	64/128/256/512	–	72.93	99.43±0.05	72.51±0.25	99.52±0.09	**72.56±0.22**
VGG-19		–	72.23	98.24±0.25	71.66±0.25	99.12±0.18	**72.46±0.24**

other 100 samples for the label 1 around (1, 1), as displayed in Figure 3. We set a 2-layer neural network as the original network, and trained it with the softmax function, cross-entropy, and SGD at a learning rate of 0.01. We applied the proposed method to the original network by replacing the last fully connected layer with the spherization layer. For comparison of representations in the same dimensional space, we set the dimension of the spherization layer to 1, where it is 2 in the original network. The other settings are identical to the original network. We trained both networks on the input samples for 100 epochs with 16 mini-batches, where the networks converged and achieved 100% training accuracy.

Distribution of Representations Initially, all representations are randomly distributed into two groups on a 2-dimensional space. After convergence, the feature vectors are divided into two disjointed groups, as displayed in Figure 3. This means spherized network locates all representations on the 2-spherical surface in both the initial and final epoch, whereas the original network spreads them out.

Hyperplanes Hyperplanes and decision boundary on the hidden vector space are defined as follows with the parameters of the output layer.

$$
\begin{aligned}
&\mathcal{W}_1 : \mathbf{w}_1 \cdot \mathbf{x} + \mathbf{b}_1 = 0 \\
&\mathcal{W}_2 : \mathbf{w}_2 \cdot \mathbf{x} + \mathbf{b}_2 = 0 \\
&\mathcal{D}_{12} : (\mathbf{w}_1 - \mathbf{w}_2) \cdot \mathbf{x} + (\mathbf{b}_1 - \mathbf{b}_2) = 0
\end{aligned}
\tag{12}
$$

, where $\mathcal{W}_i$ is the hyperplane determined by weight parameter $\mathbf{w}_i$ and bias $\mathbf{b}_i$, and $\mathcal{D}_{ij}$ is a linear decision boundary whose points satisfy 0.5 confidence for both labels. In the spherized network, all bias terms are eliminated. In Figure 2, the hyperplanes are illustrated as yellow lines and the decision boundary as a gray line. In the spherization layer, hyperplanes and decision boundary pass through the origin from the initial to the last epoch, unlike the original network. The results imply that the spherization layer can learn the correct decision boundary by changing only angles of hyperplanes passing through the origin.

---

[1]https://github.com/weiaicunzai/pytorch-cifar100

| ● 0 | ● 1 | ● 2 | ● 3 | ● 4 | ● 5 | ● 6 | ● 7 | ● 8 | ● 9 |

| (a) Original 2D | (b) Original 3D | (c) Spherization 3D |

Figure 4: Visualization of Feature Representations on MNIST. (a) and (b) are the visualization results of 2D and 3D feature vectors in the original networks, and (c) is the result in the spherized network

4.2 Retention of Training Ability on Image Classification Benchmarks

Environmental Settings   In this task, we empirically verified that replacing an existing layer to a spherization layer still maintains the training ability of the original networks on well-known image classification tasks. See Appendix C for the detail about networks and datasets.

Results and Analysis   The accuracy results of original and spherized networks are compared in Table 1. The reference and reproduced results of each setting are similar. The accuracy results of the spherized network implemented on the reproduced code are similar or slightly higher on both training and test data than that of the original network. These results imply that the spherization layer maintains the training ability of the original network. In Table 2, the accuracy results of original and spherized networks are displayed in various width and depth settings. The spherized network consistently exhibits similar or higher test accuracy over all width and depth settings. The results reveal that the spherization layer again preserves the training ability of the original networks.

4.3 Downstream Tasks: Visualization

Environmental Settings   To investigate the spherization layer locates feature vectors on the $(n+1)$-spherical surface, we implemented a simple CNN to learn 3-dimensional features for visualization. This technique is called CNN-Vis3D, which generates 3-dimensional feature vectors and shows those representations as a graph. Detailed configurations are presented in Appendix C.

Results and Analysis   The results of visualization are depicted in Figure 4. In the 2D and 3D feature visualization results of the original network, the representations are distributed over wide ranges of both scale and angles. As displayed in decoupled network [15], the angle accounts for semantic difference and the feature norm accounts for intra-class variation. In the spherized network, all the roles are expressed by the angle change on the hyperspherical surface. Thus, in the spherization layer, all trained information can be used in angular similarity-based interpretation.

4.4 Downstream Tasks: Word Analogy Test

Environmental Settings   We used BERT [5] and RoBERTa [20] to conduct the word analogy test, in which angular similarity is used to predict a relation type between words. The settings were identical with [31]. We applied a spherizaton layer to the last hidden layer of the encoder in each model. Next, we trained them on WikiText [22] for 3 epochs with 8 mini-batchs, the softmax function following cross-entropy, SGD at a learning rate 10^{-4} on masked-language modeling.

Table 3: Performance on the Word Analogy Test ($S_{ppl}/S_{pmi}/S_{mppl}$ ↑)

Model	SAT	U2	U4	Google	BATS	Avg.
BERT	**29.4**/28.5/**28.8**	36.0/36.0/**36.8**	**38.7**/34.7/34.3	**33.0**/33.8/**33.0**	32.3/**35.0**/33.2	**33.9**/33.6/**33.2**
BERT + *sph*	29.1/**29.4**/27.9	**37.3**/**39.0**/36.0	36.8/**35.9**/**35.4**	32.4/32.6/32.2	**34.0**/34.2/**33.8**	**33.9**/**34.2**/33.1
RoBERTa	**29.4**/**31.2**/29.7	35.5/**35.5**/**36.4**	33.6/**34.3**/**34.5**	32.8/33.2/30.8	30.9/31.6/30.9	32.4/33.1/32.5
RoBERTa + *sph*	29.1/29.4/**30.0**	**36.4**/35.5/34.2	**34.0**/34.3/33.3	**34.2**/33.6/32.8	**35.0**/33.9/34.8	**33.7**/33.3/33.0

Table 4: Performance of Few-shot Learning on Mini-ImageNet (Accuarcy(%): $\mu \pm \sigma$)

Model	Test Acc.		Model	Test Acc.	
	Euclidean	Cosine		Euclidean	Cosine
ConvNet	50.29±0.18	52.87±0.18	ResNet	37.63±0.15	33.41±0.15
ConvNet + *sph*	43.41±0.16	**53.74±0.16**	ResNet + *sph*	31.77±0.13	**38.71±0.16**

Table 5: Performance of Angle-Based Operators Applied to Penultimate Layer on CIFAR10 (Accuarcy(%): $\mu \pm \sigma$)

Role	Operator	FC-10		FC-256	
		train	test	train	test
base	Original Conv.	99.42±0.73	**92.69±0.14**	99.42±0.73	92.69±0.14
direct projection	Sigmoid	80.25±4.53	77.49±3.14	99.69±0.18	92.52±0.24
	Linear	77.88±5.22	76.44±4.51	99.66±0.21	92.52±0.19
	Cosine	79.25±3.13	75.98±2.57	99.75±0.03	92.72±0.09
indirect projection	Sigmoid W-Softmax	96.33±1.16	90.39±0.94	–	–
	Linear W-Softmax	89.03±1.19	86.34±0.78	–	–
	Cosine W-Softmax	99.67±0.36	92.60±0.16	–	–
proposed	Spherization Layer	99.34±0.68	92.41±0.18	99.57±0.58	**92.80±0.08**

Results and Analysis Table 3 presents the performance evaluated with three metrics [31]. Applying the spherization layer to BERT and RoBERTa improves most average scores. The improvement implies that the spherized representations provide accurate information for angle-based distinction of word relations.

4.5 Downstream Tasks: Few-shot Learning

Environmental Settings We used ProtoNet [29] with ConvNet and ResNet for fewshot learning on Mini-ImageNet [32], in which several feature vectors are compared with the feature vector of an input image by using distance metric. This task was performed according to the guidelines in [2].

Results and Analysis Table 4 details the performance results in few-shot learning [2]. Generally, the Euclidean distance is used to discriminate feature vectors. However, the Eucliean distance also has the dispersion problem. To focus on only the angles, we trained the models with cosine similarity and compared the performances. As shown in Table 4, all spherized models with cosine similarity outperform the baseline models. This improvement indicates the spherized representations are useful for the angle-based metric such as cosine similarity.

4.6 Downstream Tasks: Comparison with Angle-based Approaches

Environmental Settings We compared the method with another angle-based approach to analyze the effect of reducing information loss by projection. For comparison, we used 9-layer CNN, namely CNN-9, with the same experimental settings [19] but reproduced in PyTorch. To apply a spherization layer, we changed the last hidden layer FC-10 or the second hidden layer FC-256, which is located at the previous of the last hidden layer, in each model.

Results and Analysis Table 5 presents the comparison of the performance of the spherization layer with SphereConv operators [19]. In FC-10 and FC-256, the base operators consistently reduce performance, which project input vectors onto the hyperspherical surface for angle-based learning.

In indirect projection as W-Softmax variants omitting feature normalization only used for FC-10, the decreased performance of the base operators recovers to the score similar to the spherization layer. The best test accuracy is obtained by the spherization layer in FC-256. These results imply that guaranteeing spherized representations improves performance by resolving the information loss of projection. Compared with the results of the spherization layer in FC-10 and FC-256, any angle-based operators and the spherization layer can be applied to FC-256 for superior performance. This phenomenon proves the training difficulty of a classifier from the spherized representations, but the spherization layer is robust to this phenomenon than other operators.

5 Related Works

Semantic Analysis on the Inner Product   The inner product is a crucial operator in current neural networks, in which the distance between input vector $\mathbf{x}$ and weight vector $\mathbf{w}$ is encoded. At the decoupled networks [15], the inner product is reparametrized with the norms and the angle, and the intra-class variation and the semantic difference are modeled in neural networks by decoupling them. Furthermore, the substitutes of the inner product have been proposed, where the direction of gradient or the similarity between kernels are used as the key factor instead of the inner product [14, 37]. The spherization layer can be considered to be the substitute of the inner product, which normalizes the input vectors by locating them on the hyperspherical surface. However, the spherization layer is a direct and specific method to convert feature vectors focused on the angles without information loss.

Angle-based Approach   The semantic analysis on the inner product has revealed that the streams focuses on the information in the angles. The angle is a crucial factor, in which the most abundant and discriminative information is preserved [1, 12, 13, 18]. In SphereFace variants [13, 16, 17, 38], the angular softmax that enables CNNs to learn discriminative features on angular separability was used. Furthermore, some of this angular information have been used for regularization [35, 36]. In most angle-based studies, the angular information was used indirectly by the objective function or regularization, whereas the spherization layer ensures the model directly learns the angular information on the hyperspherical surface.

Hyperspherical Representation Learning   In some angle-based approaches, input vectors were directly projected onto the hyperphserical surface [15, 19, 21]. These hyperspherical representation learning methods normalized the input vectors to ensure models are dependent only on the angle. However, this normalization is the projection onto the hyperspherical surface, and it can be less discriminative when some points overlap after the projection. The spherization layer locates the input vectors on the hyperspherical surface without the overlap problem through the spherization.

6 Conclusion

We addressed the dispersion problem of trained information to the Euclidean norm and angle on representations. To address the dispersion problem, we proposed *spherization layer* to learn representations by using only the angles without information loss. We used the angularization for using pre-activations as angular coordinates, conversion-to-Cartesian for locating them on the $(n + 1)$-spherical surface, and no-bias training to learn representations by using only the angles. In the experiments on toy, image classification benchmarks, few-shot learning, and word analogy test, the method achieved accurate learning of the decision boundary, retention of the original training ability, and improved performance in downstream tasks using angle-based information re-used or interpreted. Compared with the other projection-based approach, the method achieved accurate and robust performance. This method can be applied to numerous network layers and downstream applications. A limit of this approach is that the spherization layer should be inserted to a network in a training step to fully utilize its advantage, which restricts the use of pre-trained models trained without it. Recovering trained information on representations with sampling should be investigated in the future.

References

[1] Beidi Chen, Weiyang Liu, Zhiding Yu, Jan Kautz, Anshumali Shrivastava, Animesh Garg, and Animashree Anandkumar. Angular visual hardness. In *International Conference on Machine Learning*, pages 1637–1648. PMLR, 2020.

[2] Da Chen, Yuefeng Chen, Yuhong Li, Feng Mao, Yuan He, and Hui Xue. Self-supervised learning for few-shot image classification. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1745–1749. IEEE, 2021.

[3] Tim R Davidson, Luca Falorsi, Nicola De Cao, Thomas Kipf, and Jakub M Tomczak. Hyperspherical variational auto-encoders. *arXiv preprint arXiv:1804.00891*, 2018.

[4] Li Deng. The mnist database of handwritten digit images for machine learning research [best of the web]. *IEEE signal processing magazine*, 29(6):141–142, 2012.

[5] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[6] Aiden Durrant and Georgios Leontidis. Hyperspherically regularized networks for byol improves feature uniformity and separability. *arXiv preprint arXiv:2105.00925*, 2021.

[7] Yi Hao, Nannan Wang, Jie Li, and Xinbo Gao. Hsme: Hypersphere manifold embedding for visible thermal person re-identification. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pages 8385–8392, 2019.

[8] Geoffrey E Hinton, Simon Osindero, and Yee-Whye Teh. A fast learning algorithm for deep belief nets. *Neural computation*, 18(7):1527–1554, 2006.

[9] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pages 448–456. PMLR, 2015.

[10] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[11] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[12] Rongmei Lin, Weiyang Liu, Zhen Liu, Chen Feng, Zhiding Yu, James M Rehg, Li Xiong, and Le Song. Regularizing neural networks via minimizing hyperspherical energy. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6917–6927, 2020.

[13] Weiyang Liu, Rongmei Lin, Zhen Liu, Lixin Liu, Zhiding Yu, Bo Dai, and Le Song. Learning towards minimum hyperspherical energy. *Advances in neural information processing systems*, 31, 2018.

[14] Weiyang Liu, Zhen Liu, James M Rehg, and Le Song. Neural similarity learning. *Advances in Neural Information Processing Systems*, 32, 2019.

[15] Weiyang Liu, Zhen Liu, Zhiding Yu, Bo Dai, Rongmei Lin, Yisen Wang, James M Rehg, and Le Song. Decoupled networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2771–2779, 2018.

[16] Weiyang Liu, Yandong Wen, Bhiksha Raj, Rita Singh, and Adrian Weller. Sphereface revived: Unifying hyperspherical face recognition. *arXiv preprint arXiv:2109.05565*, 2021.

[17] Weiyang Liu, Yandong Wen, Zhiding Yu, Ming Li, Bhiksha Raj, and Le Song. Sphereface: Deep hypersphere embedding for face recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 212–220, 2017.

[18] Weiyang Liu, Yandong Wen, Zhiding Yu, and Meng Yang. Large-margin softmax loss for convolutional neural networks. In *ICML*, volume 2, page 7, 2016.

[19] Weiyang Liu, Yan-Ming Zhang, Xingguo Li, Zhiding Yu, Bo Dai, Tuo Zhao, and Le Song. Deep hyperspherical learning. *Advances in neural information processing systems*, 30, 2017.

[20] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[21] Chunjie Luo, Jianfeng Zhan, Xiaohe Xue, Lei Wang, Rui Ren, and Qiang Yang. Cosine normalization: Using cosine similarity instead of dot product in neural networks. In *International Conference on Artificial Neural Networks*, pages 382–391. Springer, 2018.

[22] Stephen Merity. The wikitext long term dependency language modeling dataset. *Salesforce Metamind*, 9, 2016.

[23] Pascal Mettes, Elise van der Pol, and Cees Snoek. Hyperspherical prototype networks. *Advances in neural information processing systems*, 32, 2019.

[24] Rafael S Pereira, Alexis Joly, Patrick Valduriez, and Fabio Porto. Hyperspherical embedding for novel class classification. *arXiv preprint arXiv:2102.03243*, 2021.

[25] Xipeng Qiu, Tianxiang Sun, Yige Xu, Yunfan Shao, Ning Dai, and Xuanjing Huang. Pre-trained models for natural language processing: A survey. *Science China Technological Sciences*, 63(10):1872–1897, 2020.

[26] Jiayi Shen, Zehao Xiao, Xiantong Zhen, and Lei Zhang. Spherical zero-shot learning. *IEEE Transactions on Circuits and Systems for Video Technology*, 2021.

[27] Woohyeon Shim and Minsu Cho. Circlegan: Generative adversarial learning across spherical circles. *Advances in Neural Information Processing Systems*, 33:21081–21091, 2020.

[28] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[29] Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, 30, 2017.

[30] Lisa Torrey and Jude Shavlik. Transfer learning. In *Handbook of research on machine learning applications and trends: algorithms, methods, and techniques*, pages 242–264. IGI global, 2010.

[31] Asahi Ushio, Luis Espinosa-Anke, Steven Schockaert, and Jose Camacho-Collados. Bert is to nlp what alexnet is to cv: can pre-trained language models identify analogies? *arXiv preprint arXiv:2105.04949*, 2021.

[32] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. *Advances in neural information processing systems*, 29, 2016.

[33] Shengjie Wang, Tianyi Zhou, and Jeff Bilmes. Bias also matters: Bias attribution for deep neural network explanation. In *International Conference on Machine Learning*, pages 6659–6667. PMLR, 2019.

[34] Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pages 9929–9939. PMLR, 2020.

[35] Zhennan Wang, Canqun Xiang, Wenbin Zou, and Chen Xu. Dma regularization: Enhancing discriminability of neural networks by decreasing the minimal angle. *IEEE Signal Processing Letters*, 27:2089–2093, 2020.

[36] Zhennan Wang, Canqun Xiang, Wenbin Zou, and Chen Xu. Mma regularization: Decorrelating weights of neural networks by maximizing the minimal angles. *Advances in Neural Information Processing Systems*, 33:19099–19110, 2020.

[37] Zhennan Wang, Wenbin Zou, and Chen Xu. Pr product: A substitute for inner product in neural networks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6013–6022, 2019.

[38] Yandong Wen, Weiyang Liu, Adrian Weller, Bhiksha Raj, and Rita Singh. Sphereface2: Binary classification is all you need for deep face recognition. *arXiv preprint arXiv:2108.01513*, 2021.

[39] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

[40] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

[41] Fuzhen Zhuang, Zhiyuan Qi, Keyu Duan, Dongbo Xi, Yongchun Zhu, Hengshu Zhu, Hui Xiong, and Qing He. A comprehensive survey on transfer learning. *Proceedings of the IEEE*, 109(1):43–76, 2020.

A Lower bound ϕ_L

To prevent the last coordinate from an extremely small value, we set a lower bound φ_L of angles. When we assume that the trigonometric value of all angular coordinates is α, $\sin\phi = \alpha$. Based on this assumption, the lower bound φ_L can be obtained as illustrated in Eq. 13.

$$
\begin{aligned}
when \ \sin\phi = \alpha, \ \alpha^n \geq \delta \ &\Leftrightarrow \ \alpha = \delta^{1/n} \\
\phi = \ \sin^{-1}\alpha \geq \ &\sin^{-1}\left(\delta^{1/n}\right) \\
\therefore \ \ \phi_L = &\sin^{-1}\left(\delta^{1/n}\right)
\end{aligned}
\tag{13}
$$

B Calculation Trick

To convert the angular coordinates $\boldsymbol{\varphi} \in \mathbb{R}^n$ to Cartesian coordinates $\mathbf{s} \in \mathbb{R}^{n+1}$, first, expand the dimension of $\boldsymbol{\varphi}$ by using the constant matrix $\mathbf{W}_\varphi = [\mathbf{I}_n; \mathbf{v}] \in \mathbb{R}^{n\times(n+1)}$, where $\mathbf{v} = [\mathbf{0}; 1]^\top \in \mathbb{R}^n$. Then, we can get the expanded angular vector $\boldsymbol{\phi}$ as illustrated in Eq. 8.

When we define $\mathbf{s}'$ as illustrated in Eq. 14 from Eq. 8, we calculate the i-th coordinate s_i as shown in Eq. 15 , where $\mathbf{W}_\phi \in \mathbb{R}^{(n+1)\times(n+1)}$ is an upper triangular matrix in which all diagonals are zero and $(\mathbf{W}_\phi)_{n,n+1}$ is also zero, and $\mathbf{b}_\phi = [\mathbf{0}; -\frac{\pi}{2}]^\top \in \mathbb{R}^{n+1}$.

$$
\mathbf{s}' = \mathbf{W}_\phi^\top \ln(\sin\boldsymbol{\phi}) + \ln\left(\cos\left(\boldsymbol{\phi} + \mathbf{b}_\phi\right)\right)
\tag{14}
$$

$$
\begin{aligned}
s'_{1<k<n+1} &= \ \textstyle\sum_{i=1}^{k-1} \ln(\sin\varphi_i) + \ln(\cos\varphi_k) \\
&= \ \ln\left(\cos\varphi_k \prod_{i=1}^{k-1}\sin\varphi_i\right) \\
s'_1 &= \ \ln(\cos\varphi_1) \\
s'_{n+1} &= \ \ln\left(\prod_{i=1}^{n}\sin\varphi_i\right)
\end{aligned}
\tag{15}
$$

Finally, we get the Cartesian coordinates $\mathbf{s}$ from this calculation trick as illustrated in Eq. 16.

$$
\begin{aligned}
\mathbf{s} \ &= r \cdot \exp(\mathbf{s}') \\
&= [r\cos\varphi_1, \cdots, r\cos\varphi_k \textstyle\prod_{i=1}^{k-1}\sin\varphi_i, \cdots, r\prod_{i=1}^{n}\sin\varphi_i]
\end{aligned}
\tag{16}
$$

C Experimental Details

Image Classification   We conducted image classification experiments on MNIST [4], Fashion-MNIST [40], CIFAR10 and CIFAR100 [10]. For MNIST, we used a 3-layer neural network [8] and LeNet-5 [11]. We followed the settings in [8] and in [11], and the architectures of them are illustrated in Table 6 SimpleFNN and LeNet-5, respectively. Unlike [8], we used 256 mini-batches, the Adam at a learning rate of 0.001 and weight decay of 5e-5 at the 3-layer neural network. At LeNet-5, we set 128 mini-batches, Adam at a learning rate of 0.001, and the other settings are same with [11]. For Fashion-MNIST, CIFAR10, and CIFAR100, we used VGG variants [28] with batch normalization [9] denoted as VGG-*N*. Batch normalization, ReLU, 128 mini-batches, and SGD with momentum of 0.9 and with weight decay of 5e-4 were used as default in three datasets. The number of epochs was set to 100, 300, and 200, respectively. For Fashion-MNIST, the learning rate was initially 0.01 and it was divided by 2 at every 20 epochs. For CIFAR10, we set the initial learning rate as 0.05 and reduced it to half at every 30 epochs. For CIFAR100, the learning rate was initially 0.1 and divided by 5 at 60th, 120th, and 160th epochs. A spherization layer replaced the last fully connected layer of the backbone network for each task. As pre-activations used for generating angular coordinates, the range of angles was reduced when dropout. To resolve this problem, we removed the dropout in front of the spherization layer. For analysis of robustness of the spherization layer to width and depth configurations, we used the VGG backbone again and changed the convolutional configuration of it on CIFAR100. To generate variations on width, we set the number of channels at Conv1.x, Conv2.x, Conv3.x, and Conv4.x to 16/32/64/128, 32/64/128/256, 64/128/256/512, 128/256/512/1024 and 256/512/1024/1024, respectively. The filter in Conv5.x has same number with the filter in Conv4.x (see Table 6). To give variations on depth, we used VGG-11, VGG-16, and VGG-19.

Table 6: Network configurations. The convolutional layer parameters are denoted as "conv(receptive field size)-(number of channels)", and the ReLU activation function is not shown for brevity [28]. The fully connected layer parameters are denoted as "FC-(number of neurons)". In CNN-Vis3D, N is set as 2 or 3 to get the feature vectors for visualization. In VGG-11 (C), $C = [C_1, C_2, C_3, C_4]$ means the number of channels at each convolutional block. N_{out} is set as the number of classes in each image classification task. The highlighted layer means where it is replaced by the spherization layer in the spherized network.

SimpleFNN	LeNet-5	CNN-Vis3D	CNN-9	VGG-11 (C)	VGG-16	VGG-19
FC-500	conv5-6	conv3-32	conv3-128	conv3-C_1	conv3-64	conv3-64
FC-300	conv5-16	conv3-32	conv3-128		conv3-64	conv3-64
FC-10	FC-120	maxpool	conv3-128	maxpool		
soft-max	FC-84	conv3-64	maxpool	conv3-C_2	conv3-128	conv3-128
	FC-10	conv3-64	conv3-192		conv3-128	conv3-128
	soft-max	maxpool	conv3-192	maxpool		
		conv3-128	conv3-192	conv3-C_3	conv3-256	conv3-256
		conv3-128	maxpool	conv3-C_3	conv3-256	conv3-256
		FC-256	conv3-256		conv3-256	conv3-256
		FC-N	conv3-256			conv3-256
		FC-10	conv3-256	maxpool		
		soft-max	maxpool	conv3-C_4	conv3-512	conv3-512
			FC-256	conv3-C_4	conv3-512	conv3-512
			FC-10		conv3-512	conv3-512
			soft-max			conv3-512
				maxpool		
				conv3-C_4	conv3-512	conv3-512
				conv3-C_4	conv3-512	conv3-512
					conv3-512	conv3-512
						conv3-512
				maxpool		
				FC-4096		
				FC-4096		
				FC-N_{out}		
				soft-max		

Visualization   CNN-Vis3D is composed of three convolution layer blocks whose kernel size are 32, 64, and 128, as shown in Table 6. To obtain 3-dimensional feature vectors, we set the number of neurons at the second fully connected layer, which locates before the last fully connected layer, as 3 in the original network. For a fair comparison, we replaced this layer with the spherization layer and changed the number of neurons to 2, and visualized 2-dimensional feature vectors from the original network, in which the number of neurons at the second fully connected layer is 2. In the CNN-Vis3D for 2D and 3D, named Original 2D and Original 3D respectively, batch normalization, ReLU, 64 mini-batches, cross-entropy, and Adam at a learning rate 0.001 were used as default. Unlike the original network, we set 32 mini-batches in the spherized CNN-Vis3D, called Spherization 3D. We trained original 2D, original 3D, and Spherization 3D for 20 epochs, and they converged and achieved the training accuracies(%) 98.87, 99.48, and 99.13, respectively.

D   Effect of Fine-tuning

In neural networks, the fine-tuning technique is used in natural language processing [25, 39] and computer vision [30, 41]. In this method, the pre-trained model is used and re-trained on a new target domain. Fine-tuning can achieve excellent performance. However, for spherization, a layer in the architecture should be replaced with the spherization layer, and this spherized network should be trained from scratch. If not, a mismatch between the learned representations and spherization unexpectedly affect the performance of the fine-tuned model. To verify this phenomenon, we investigated fine-tuning on few-shot learning and the word analogy test. We used the pre-trained weight from [2] for ConvNet and ResNet, and from [39] for BERT and RoBERTa. For synchronizing with spherized features, we loaded the pre-trained models and fine-tuned them on Mini-ImageNet [32] and WikiText dataset [22], respectively. See the experimental details and results on following subsections.

Table 7: Performance on Word Analogy Test (fine-tuning) ($S_{ppl}/S_{pmi}/S_{mppl}$ ↑)

Model	SAT	U2	U4	Google	BATS	Avg.
BERT	**29.7/32.3**/29.4	**37.3/36.0/34.2**	**39.1/34.7/34.6**	**44.8**/44.4/44.2	**44.1/41.3/40.7**	**39.0/37.7/36.6**
BERT + *sph*	29.1/29.1/**30.0**	36.8/35.1/33.3	38.2/32.6/33.3	44.6/**45.8/44.4**	40.8/38.8/39.3	37.9/36.3/36.1
RoBERTa	40.7/38.0/40.1	43.4/47.8/45.6	41.2/43.3/42.1	83.0/84.0/83.2	68.1/68.5/69.3	55.3/56.3/56.0
RoBERTa + *sph*	**41.5/42.1/42.7**	**49.6/50.4/47.8**	**46.3/46.8/46.5**	**88.0/87.0/88.4**	**71.0/70.7/70.9**	**59.3/59.4/59.3**

Table 8: Performance of Few-shot Learning on Mini-ImageNet (fine-tuning) (Accuarcy(%): $\mu \pm \sigma$)

Model	Test Acc.		Model	Test Acc.	
	Euclidean	Cosine		Euclidean	Cosine
ConvNet	**67.80±0.17**	66.60±0.17	ResNet	77.73±0.15	**78.86±0.15**
ConvNet + *sph*	51.56±0.17	61.77±0.17	ResNet + *sph*	72.18±0.15	74.57±0.15

D.1 Word Analogy Test

Experimental Settings   Unlike the few-shot learning, there are no data to re-train the pre-trained weights in word analogy test because they use language models to evaluate the performance on word analogy test. To resolve this problem, we used WikiText [22] to make fine-tuned language models. We loaded pre-trained weights BERT and RoBERTa, respectively, and trained them on WikiText for 3 epochs, 8 mini-batches, softmax function following cross-entropy, SGD at a learning rate 10^{-4}. For spherization, we replaced the last output layer of encoder in each network with spherization layer.

Result and Analysis   The results of fine-tuning on word analogy test are illustrated in Table 7. In the original networks, the performances of both are obviously increased. The spherized BERT also have improvements but not much as the original network, while the spherized RoBERTa shows greater improvement. This result means that the angular information in the pre-trained representations might be more helpful enough to overcome the information collapse.

D.2 Few-shot Learning

Experimental Settings   The experimental settings were used according to the method presented in Downstream Task: Few-shot Learning in Experiments Section. For fine-tuning, we obtained the pre-trained weights [2] for ConvNet and ResNet, respectively. When loading these weights, the part of last fully connected layer was substituted with the spherization layer. Thus, the pre-trained weights of this layer were not necessary anymore.

Result and Analysis   The results of fine-tuning on few-shot learning are displayed in Table 8. In the original networks, the performances increase considerably. The spherized networks exhibit improvements but not as much as the original network. This result indicates that there are some information collapse when training the spherization layer on pre-trained representations but it is not that fine-tuning is not helpful at all. To the best of our knowledge, the angular information in the pre-trained representations might be helpful to train spherized representations.