Exploring Architectural Ingredients of Adversarially Robust Deep Neural Networks

Abstract

Deep neural networks (DNNs) are known to be vulnerable to adversarial examples/attacks. A wide range of defense methods have been proposed to train adversarially robust DNNs, among which adversarial training has demonstrated promising results. However, despite preliminary understandings developed for adversarial training, it is still not clear, from the architectural perspective, what configurations can lead to more robust DNNs. In this paper, we address this gap via a comprehensive investigation on the impact of network width and depth on the robustness of adversarially trained DNNs. Specifically, we make the following key observations: 1) more parameters (higher model capacity) does not necessarily help adversarial robustness; 2) reducing capacity at the last stage (the last group of residual blocks) of the network can actually improve adversarial robustness; and 3) under the same parameter budget, there exists an optimal architectural configuration for adversarial robustness. We also provide a theoretical analysis explaining why such network configuration can help robustness. These architectural insights can help design adversarially robust DNNs.

1 Introduction

Deep neural networks (DNNs) are becoming standard models for many real-world applications such as image classification [1], object detection [2] and natural language processing [3]. However, a line of adversarial research has shown that DNNs are vulnerable to adversarial examples (attacks), which can be easily crafted by slightly perturbing the input instance to maximize the model's classification error [4, 5]. This vulnerability of DNNs has become a major concern for their deployment in security-critical applications such as autonomous driving [6, 7] and medical diagnosis [8, 9].

A number of defense methods have been proposed to train adversarially robust DNNs [5, 10–13], some may cause obfuscated gradients [14] and can be circumvented by an adaptive attack [15], but adversarial training has demonstrated the most promising results [16, 17]. Adversarial training can be viewed as a type of data augmentation that trains DNNs on adversarial (instead of natural) examples [16–19]. Based on adversarial training, a number of works have been proposed to understand the learning and convergence behaviors, and the key factors for training more adversarially robust DNNs. For example, it has been found that adversarial training encourages the network to learn more robust features [20], and it requires more data [21–24] or higher capacity models to gain more robustness [16, 25]. While these understandings have motivated a number of improved defense methods, it is still not clear, from an architectural perspective, *what makes an adversarially robust DNN*.

In this paper, we present the first comprehensive investigation on the architectural ingredients of adversarially robust DNNs. Our investigation is based on adversarial training and WideResNet-34-10 (WRN-34-10) [26], one extensively tested architecture in the adversarial defense literature. Based on the base architectural configuration of WRN-34-10, we apply a finely-controlled grid search to

explore the impact of network width and depth configurations on the robustness of adversarial trained DNNs.

The standard WRN-34-10 consists of 3 stages with each stage being a group of 5 (i.e. depth) residual blocks and each residual block having 2 convolutional layers. We denote the three stages as Stage-1, Stage-2 and Stage-3 following the direction from the input to the output. Each stage is configured by a depth (number of residual blocks) and a width (number of filters) factor. The hyper-parameters for width and depth of each stage control the scale of learnable parameters (capacity). In this paper, we explore different configurations of width and depth for each of the three stages. Based on our explorations, we make the following key observations:

- Simply increasing the number of parameters (model capacity) by upscaling width or depth does not necessarily lead to improved robustness. This contrasts with current beliefs that, under the same type of architecture, more parameters (higher model capacity) can improve adversarial robustness [16, 25, 27]. Adversarial training does require larger capacity models, but there exists a trade-off. We provide both theoretical and empirical evidences that wider/deeper models increase Lipschitzness (larger Lipschitz constant).
- For a larger model used in adversarial training, reducing capacity at the last stage (Stage-3) of WRNs can achieve a better trade-off between capacity and Lipschitzness, thus improving adversarial robustness. This can be achieved by reducing either depth or width, with width reduction being slightly more effective. This highlights that smaller DNNs can also have better robustness if the parameter reduction is applied at the right place (i.e. the last stage).
- Under the same type of architectures (i.e. WRNs) and parameter budget, there may exist an optimal architectural configuration that can produce the most robust DNN. We show that the same configuration rule can also be applied to improve the robustness of VGGs, DenseNets (DNs), as well as networks found by Differentiable Architecture Search (DARTS).

Furthermore, we provide a series of understandings for the above findings, which can not only provide useful insights for training more robust models with adversarial training, but also shed new light on the architectural ingredients of adversarially robust DNNs.

2 Related Work

2.1 Adversarial Training

Adversarial training has been demonstrated to be the most reliable training method for obtaining adversarially robust DNNs [14, 28]. The standard adversarial training (SAT) can be formulated as a min-max optimization framework as follows:

$$\arg\min_{\boldsymbol{\theta}} \mathbb{E}_{(\boldsymbol{x},y)\sim\mathbb{D}}\left[\max_{\boldsymbol{x}'} \mathcal{L}(f_{\boldsymbol{\theta}}, \boldsymbol{x}', y)\right], \tag{1}$$

where the inner maximization generates adversarial examples $\boldsymbol{x}'$, the outer minimization trains the model on $\boldsymbol{x}'$, $f_{\boldsymbol{\theta}}$ denote the neural network and $\mathcal{L}(\cdot)$ is the cross entropy (CE) loss. During the inner maximization process, SAT uses PGD to generate adversarial examples [16]:

$$\boldsymbol{x}'_k = \Pi_\epsilon(\boldsymbol{x}'_{k-1} + \alpha \cdot \text{sign}(\nabla_{\boldsymbol{x}}\mathcal{L}(f_{\boldsymbol{\theta}}, \boldsymbol{x}'_{k-1}, y))), \tag{2}$$

where $\text{sign}(\cdot)$ is the sign function, $\boldsymbol{x}'_k$ is the adversarial example obtained at the k-th (for overall K steps) perturbation step, α is the step size, and Π_ϵ is a projection (clipping) operation that projects the perturbation back onto the ϵ-ball centered around $\boldsymbol{x}$ if it goes beyond.

A number of variants of the SAT based defense have also been proposed to further improve the robustness, such as the trade-off between adversarial robustness and natural accuracy (TRADES) [17], Dynamic AdveRsarial Training (DART) [18], Friendly Adversarial Training (FAT) [29], Misclassification Aware adversarial Training (MART) [19], Robust Self-Training (RST) [22], Unsupervised Adversarial Training (UAT) [30], Guided Adversarial Training (GAT) [31], Max-Margin AT [32], using Max-Mahalanobis center (MMC) loss [33], accelerated AT [34–36], using pre-training [37], incorporating the hypersphere embedding [38], self-progressing robust training [39], Adversarial Weight Perturbation (AWP) [40], Adversarial Distributional Training (ADT) [41], Channel-wise Activation Suppressing (CAS) [42] and Geometry-Aware Instance-Reweighted Adversarial Training (GAIRAT) [43]. Adversarial Training has also been found to cause robust overfitting [44], but this can be mitigated by smoothing techniques [45].

2.2 Understanding Adversarially Trained DNNs

Understanding the underlying contribution of adversarial training to adversarial robustness has been a key research question. For example, it has been found that adversarial training encourages the model to learn more robust features [20], improve the model's transferability to downstream tasks [46] and improve performance on clean data [47]. It has also been found that using auxiliary training data with adversarial training can further improve adversarial robustness [21, 22], and that weight decay plays an important role in adversarial training [48]. Another important finding is that using WRNs instead of ResNets (RNs) can bring $\sim 3\%$-5% more robustness [17–19]. Other works also suggest that adversarial training requires deeper and wider models [16, 25]. Also, the skip-connection operation used in WRN has been found can improve robustness for deeper architectures [49]. On the other hand, there are also works showing that increasing the number of parameters for the same type of DNN architectures can only lead to limited robustness improvement [27, 50]; and wider networks may cause more perturbation instability [51].

Several recent works have applied neural architecture search (NAS) to search for more robust DNN architectures [52]. They found that, 1) densely connected cells result in improved robustness; and 2) under certain computational budget, adding convolution operations to direct connection edge is effective. Other works improve the NAS search strategy by searching on targeted capacity [53], maximizing certified lower bound [54], using the log-normal distribution to approximate the Lipschitz constant [55], using lower and upper confidence bounds in Bandit [56], or using perturbation-based regularization [57]. Another study on hand-crafted versus NAS-based architectures shows that, without adversarial training, NAS-based architectures are more robust for small-scale datasets and simple tasks than hand-crafted architectures, however, hand-crafted architectures are more robust than NAS-based architectures as the dataset size or the task complexity increases [58]. Note that NAS is extremely time-consuming, especially when applied with adversarial training. Previous works using NAS find optimal topological connections within the cell structure [52], but did not investigate depth/width configurations, which arguably has more impact on robustness (e.g. RNs vs. WRNs). In this work, we focus on fine-grained configuration exploration rather than blind search, which can produce more precise understandings of how depth and width affect robustness.

3 Wider and Deeper Models Increase Lipschitz Upper Bound

It has been theoretically shown that high Lipschitzness (larger Lipschitz constant) corresponds to low stability of the model's output to input perturbations [51]. However, adversarial training does require a larger capacity model (e.g. RN vs. WRN), an empirical finding that goes against the theoretical expectation. In this section, we first theoretically show a trade-off between network capacity (width/depth) and the Lipschitz upper bound. In Section 4, we will empirically examine this trade-off and its relation to the improved adversarial robustness for larger capacity models.

The Lipschitz constant L of a DNN measures the maximum rate of change in the output with the change in the input, and is closely related to adversarial robustness [4]. Formally, it is $\|f_{\boldsymbol{\theta}}(\boldsymbol{x}) - f_{\boldsymbol{\theta}}(\boldsymbol{x}')\| \le L \|\boldsymbol{x} - \boldsymbol{x}'\|$.

Theorem 1 (Lipschitz Constant Upper Bound of a Neural Network with Gaussian Distributed Weights). *Consider an n layer DNN f, where the weight parameters $\boldsymbol{\theta}$ are independent Gaussian random variables distributed as $\mathcal{N}(0, \sigma_{\boldsymbol{\theta}}^2)$ with $\sigma_{\boldsymbol{\theta}}^2$ denoting the variance of the Gaussian distribution, and where the activation functions are 1-Lipschitz. The expected Lipschitz constant of a DNN with hidden layer size h is upper bounded by:*

$$L(f_{\boldsymbol{\theta}}) \le \prod_{j=1}^{n} \left(\sqrt{h_{j-1}} + \sqrt{h_j} \right) \cdot \sigma_{\boldsymbol{\theta}_j}$$

Theorem 2. *For a convolutional neural network f, each layer's convolution operation with feature map size $W \times m \times m$ and kernel size $k \times k$, where the weight parameters $\boldsymbol{\theta}$ are independent Gaussian random variables distributed as $\mathcal{N}(0, \sigma_{\boldsymbol{\theta}}^2)$, the expected Lipschitz constant is upper bounded by:*

$$L(f_{\boldsymbol{\theta}}) \le \prod_{j=1}^{n} (m_j \sqrt{W_{j-1}} + (k_j - m_j + 1)\sqrt{W_j}) \cdot \sigma_{\boldsymbol{\theta}_j}$$

The proof for Theorem 1 and 2 is inspired by [59–61] and can be found in Appendix A.1. This establishes a connection between the upper bound on the Lipschitz constant of a feed-forward DNN

with n layers and width of h_j for each layer. For the j-th layer of convolution operations, the Lipschitz constant upper bound increases with its input dimension ($W_{j-1} \times m_j \times m_j$) and the number of output channels W_j. More simply, it is upper-bounded by the variance of the weight matrix and the input representation's dimension plus the output representation's dimension. For the entire network, the Lipschitz constant upper bound grows exponentially with the depth. This suggests that wider and deeper models have a relatively larger change of the output due to the changes in the input, i.e., lower adversarial robustness.

Several works attempt to regularize the network's Lipschitz constant by using Parseval tight frames on the weight matrixes [62], enforcing constraints on the singular values of the weight matrixes [63], or via a Lipschitz-margin training [64]. However, a follow-up work points out that there exist both experimental and theoretical limitations for the above approaches [65]. Whilst the Lipschitz constant may not be used as a regularization, it has been widely adopted for analyzing the stability and adversarially robustness of DNNs [4, 51, 66].

4 Exploring Adversarially Robust Architectures

Our exploration of the relationship between DNN architectural configuration, Lipschitzness (size of the Lipschitz constant) and adversarial robustnessare starts with a fine-controlled grid search on the width/depth of the WideResNet (WRN) [26]. In Sections 4.1 and 4.2, we show our exploration results with depth and width, respectively. Based on these results, a pattern of robust depth/width configuration is discovered. In Section 4.3, we examine a linear scaling effect with the discovered robust configuration. In Section 4.4, we provide an analysis on the trade-off between model capacity and Lipschitzness, and the key factors contributing to improved adversarial robustness.

(a) WRN-34-10 architecture.   (b) Grid search results on Depth.

Figure 1: (a): Illustration of WRN-34-10 denoted as ^{d}5-5-5. (b): Grid search results on different depth configurations. The three-digit numbers highlight the depth configurations of only those networks that have either a low ($<= 50.0\%$) or a high ($>= 52.5\%$) adversarial robustness (against PGD^{20}).

Base architecture. We take the standard WRN-34-10 designed for CIFAR-10 as our base architecture. Figure 1a provides an overview of the architecture and the detailed configurations are summarized in Appendix Table 3. The standard WRN architecture consists of 3 stages (groups) of residual blocks and 4 fixed convolutional layers. Here, we focus on the configuration of the 3 stages, which are the key components of the network. We denote the depth and width configuration for the i-th ($i \in \{1, 2, 3\}$) stage as D_i and W_i, respectively. For standard WRN-34-10, $D_{1/2/3} = 5$ (denoted as ^{d}5-5-5) and $W_{1/2/3} = 10$ (denoted as ^{w}10-10-10). For the rest of this paper, we use $^dD_1$-D_2-D_3 and $^wW_1$-W_2-W_3 to represent the exact width and depth configurations. We explore the stage-wise depth and width configurations while keeping other configurations unchanged: each residual block has 2 convolution layers with 3×3 kernels following the order of BN-ReLU-Conv (BN: batch normalization [67]; ReLU: ReLU activation; Conv: convolution).

Experimental settings. We train all explored networks on CIFAR-10 dataset [1] using the standard adversarial training (SAT) with Projected Gradient Descent (PGD) [16] (see definition in equation (2)). Following the typical adversarial training setting, we constrain the L_∞-norm of the maximum adversarial perturbation to $\epsilon = 8/255$, and use 10-step PGD (PGD^{10}) with step size $\alpha = 2/255$.

After training, we test the robustness of the network on PGD adversarial examples crafted on the entire test set of CIFAR-10, under the same perturbation constraint $\epsilon = 8/255$. For evaluation, we use the 20-step PGD (PGD^{20}) with step size $\alpha = \epsilon/10$. The robustness is measured by the network's accuracy on the PGD^{20} test adversarial examples. More details can be found in Appendix B.

4.1 Exploring Different Depths

We first explore different depth configurations based on the base WRN-34-10 architecture introduced above. For each of the three stages (e.g. Stage-1, Stage-2, Stage-3), we explore different depth $D_i \in \{1, 3, 5, 7, 9\}$. Since each stage has 5 possible depth configurations, the total number of all possible depth configuration for all 3 stages are 125 (5x5x5, permutation with replacement). We first perform a grid search on all the 125 depth configurations, then take a closer look at the impact at each individual stage. The adversarial robustness of the 125 networks (adversarially trained using SAT) against PGD^{20} test adversarial examples is plotted in Figure 1b. Note that the depth configuration of standard WRN-34-10 is [d]5-5-5. By investigating the robustness scores along the x-axis (number of parameters), we find that more parameters does not necessarily lead to improved robustness. For example, the networks with more than 80M (million) parameters are even less robust than some of those with only 20M parameters. Given the same level of parameters, for example ~20M, different depth configurations can lead to ~ 6% difference in robustness. This implies that, *under the same parameter budget, there may exist an optimal depth configuration for adversarial robustness*.

Next, we take a closer look at the above grid search result and investigate the common characteristics of the top-5 most robust networks, the details of which are reported in Figure 2d. Interestingly, we find that the top-5 networks all have a significantly reduced depth of 1 or 3 at the last stage (i.e. Stage-3). This trend indicates that reducing model capacity at the last (deepest) stage can actually improve robustness. The other observation is that, having more residual blocks (higher depth) at the two shallow stages (i.e. Stage-1/2) can also improve robustness. For example, the top-2 networks have 9 residual blocks at Stage-1, and all top-4 networks have 9 or at least 7 residual blocks at Stage-2. This suggests that capacity is more important for the shallow layers. We conjecture this is because the network still needs sufficient capacity to learn the augmented examples by adversarial training. Note that the best performing model [d]9-7-1 only uses half of the parameters of the standard WRN-34-10 ([d]5-5-5), which is only ranked the 45-th out of all 125 models.

| | (a) Stage-1. | (b) Stage-2. | (c) Stage-3. | (d) Top-5 Models. |

Model	Params (M)	Clean (%)	PGD^{20} (%)
[d]9-7-1	22.19	86.84	**54.03**
[d]9-9-1	25.88	86.90	53.65
[d]7-9-3	39.71	86.91	53.16
[d]7-7-1	21.27	87.01	52.97
[d]7-5-1	17.58	86.82	52.93
[d]5-5-5	46.16	87.06	51.43

Figure 2: (a-c) The impact of depth on adversarial robustness at different stages. When studying one stage, the depths of other two stages are fixed to 5. (d) Clean accuracy and adversarial robustness of the top-5 most robust depth configurations discovered in the grid search. All networks are trained using SAT [16] on CIFAR-10. Robustness evaluated using PGD^{20}. [d]5-5-5 is the depth configuration of the baseline WRN-34-10 model.

We further explore the distinctive impacts of depth on adversarial robustness at different stages via a control study. Specifically, we add or remove residual blocks from each individual stage of WRN-34-10 ([d]5-5-5) while keeping the other two stages fixed to depth 5. The robustness results are shown in Figure 2a-2c. As can be observed, reducing depth at the first two stages constantly degrades the robustness, however, it is the other way around at the last stage (i.e. Stage-3). In relation to previous understanding that higher model capacity can lead to more robust models [27, 50], our finding indicates that it is true for the shallow layers but quite the opposite for the deeper layers. In other words, *more parameters can improve adversarial robustness only when added to the shallow layers* (e.g., layers in Stage-1 and Stage-2).

4.2 Exploring Different Widths

We further explore whether width also has a similar effect as depth. The standard WRN-34-10 has a width upscaling factor 10 applied to each stage, that is, [w]10-10-10. Based on our above findings with

211 the depth in Section 4.1, here we skip the grid search and directly investigate the impact of width at
212 different stages. At each stage, we investigate different width configurations $W_i \in \{2, 4, 6, 8, 10\}$ for
213 $i = 1, 2, 3$.

Model	Params (M)	Clean (%)	PGD^{20} (%)
^{w}10-10-2	12.66	86.79	53.95
^{w}10-10-4	17.05	87.03	**54.28**
^{w}10-10-6	24.10	86.80	53.57
^{w}10-10-8	33.80	87.17	52.62
^{w}10-10-10	46.16	87.13	52.04

(a) Stage-1.   (b) Stage-2.   (c) Stage-3.   (d) Stage-3.

Figure 3: (a-c): The impact of width on adversarial robustness at different stages. When studying one stage, the widths of other two stages are fixed to 10. (d): Clean accuracy and adversarial robustness of the networks obtained by reducing width in the last stage (i.e. Stage-3). All networks are trained using SAT [16] on CIFAR-10. Robustness is evaluated using PGD^{20}. ^{w}10-10-10 is the depth configuration of the baseline WRN-34-10 model.

214 The robustness results are illustrated in Figure 3. We find that width reduction generally has a similar
215 effect as depth reduction: reducing width at the first two stages harms robustness until $W_{1/2} = 4$,
216 however, the same operation can improve robustness when applied to the last stage. This confirms the
217 importance of high capacity at the shallow layers and low capacity at the deeper layers. Compared
218 to depth reduction, we find that, with the same amount of robustness improvement, width reduction
219 (at the last stage) can lead to smaller models. For example, ^{w}10-10-4 (the second row in Figure 3d)
220 achieves a similar robustness ($\sim$54%) as ^{d}9-7-1 (the first row in Figure 2d). However, the number of
221 parameters of the ^{w}10-10-4 configuration is only 17.05M, which is much less than the 22.19M of the
222 ^{d}9-7-1 configuration.

223 Another interesting observation is that adversarial robustness does not change much if we reduce the
224 width from $W_{1/2} = 4$ to $W_{1/2} = 2$ at Stage-1 or Stage-2, whereas the same reduction at Stage-3 hurts
225 robustness. This is somewhat expected since, on one hand, the robustness might not be affected much
226 unless a sufficient number of filters (channels) are removed, which is different to depth that configures
227 the entire residual block. On the other hand, if too many filters are removed at the last stage, the
228 network may lose the capacity required for proper learning, while in our depth exploration, there
229 exists at least one residual block ($D_3 \geq 1$) at the last stage. We also experimented with combinations
230 of the best depth configuration in Figure 2d and the top-5 width configurations in Figure 3d, however,
231 none of these models can achieve better adversarial robustness than a simple width reduction to
232 ^{w}10-10-4 (see Appendix C for more detail). Although a more fine-grained (with decimals) exploration
233 of the width configuration may lead to even more robust models, here we simply take the ^{w}10-10-4
234 configuration as our choice of the optimally-reduced WRN.

4.3 Scaling with the Discovered Configuration

236 Previous works [16, 17] have shown that a wider net-
237 work like WRN-34-10 can be trained to be more robust
238 than a standard ResNet like RN-34. Here, we investi-
239 gate if we can obtain more robust models by scaling
240 the discovered width configuration ^{w}10-10-4. We test
241 different scaling ratios $\gamma \in [0.25, 2.0]$, and show the
242 robustness results in Table 1. Compared to ^{w}10-10-4
243 ($\gamma = 1.0$), scaling down γ to 0.5 or 0.25 decreases the
244 robustness while scaling up γ can further improve the
245 robustness, although the improvement become less sig-
246 nificant when γ goes above 1.5. Note that the network
247 with $\gamma = 0.5$ has 10 times fewer parameters than the

Table 1: Clean accuracy and adversarial robustness for scaled ^{w}10-10-4 configurations. All networks are trained using SAT [16] on CIFAR-10. Robustness evaluated using PGD^{20}.

Scaling Ratio	Params (M)	Clean (%)	PGD^{20} (%)
$\gamma = 0.25$	1.07	80.61	50.90
$\gamma = 0.5$	4.27	84.31	54.07
$\gamma = 1.0$	17.05	87.00	54.99
$\gamma = 1.5$	38.33	87.68	55.33
$\gamma = 2.0$	68.12	88.12	**55.35**

248 baseline WRN-34-10, but can already achieve a better robustness against PGD^{20}. The best robustness
249 is achieved at $\gamma = 2.0$, i.e., ^{w}20-20-8. We denote the corresponding WRN-34 network as WRN-34-R,
250 more details can be found in Appendix Table 3. In Section 5, we will apply the ^{w}10-10-4 configuration
251 rule to more network architectures and evaluate their (along with WRN-34-R) adversarial robustness
252 more systematically.

4.4 Empirical Understanding

We apply two closely related metrics, including Perturbation Stability [51] and Empirical Lipschitz [66] to explore the distinctive impact of the deeper layers to adversarial robustness. They measure the output stability of the neural network.

Perturbation Stability. Adversarial robustness is typically measured by the percentage of correctly classified adversarial examples, which can be further decomposed into the set of *correct clean* examples intersect with *stable* examples [51]. *Correct clean* examples refer to clean examples that can be correctly classified by the model $\{(\boldsymbol{x}, y) \sim \mathbb{D}, f_{\boldsymbol{\theta}}(\boldsymbol{x}) = y\}$. *Stable* examples are defined as, $\{\boldsymbol{x} : \forall \boldsymbol{x}' \in \mathcal{X}, f_{\boldsymbol{\theta}}(\boldsymbol{x}) = f_{\boldsymbol{\theta}}(\boldsymbol{x}')\}$, where $\mathcal{X}$ is the domain of the ϵ-ball around $\boldsymbol{x}$. This perturbation stability measures the fraction of examples whose outputs cannot be adversarially perturbed. While many factors can affect the model's performance on the *correct clean* examples such as the generalization capability of the model, the perturbation stability only measures if adversarial perturbations can change the prediction of the output. We apply this metric to understand the role of neural network architecture in adversarial robustness. More specifically we are interested to find out whether the improved robustness is a result of improved generalization, stability or both.

Empirical Lipschitz constant. The empirical Lipschitz constant is defined as [66]:

$$\frac{1}{n} \sum_{i=1}^{n} \max_{\boldsymbol{x}' \in \mathcal{X}} \frac{\|f_{\boldsymbol{\theta}}(\boldsymbol{x}_i) - f_{\boldsymbol{\theta}}(\boldsymbol{x}'_i)\|_1}{\|\boldsymbol{x}_i - \boldsymbol{x}'_i\|_\infty}, \tag{3}$$

where $\mathcal{X}$ is the domain of the ϵ-ball around $\boldsymbol{x}$ and $\boldsymbol{x}'$ can be generated by an adversarial attack (i.e. PGD[20]). A lower value of the empirical Lipschitz constant implies a smoother and more adversarially robust classifier. For our analysis, we measure the empirical Lipschitz constant of the functions represented by the output layers of different residual blocks or the entire network (logits output). E.g., for block-5, we measure the maximum rate of change in its representation output between clean ($\boldsymbol{x}$) and adversarial ($\boldsymbol{x}'$) inputs.

(a) Reducing depth. (b) Reducing width. (c) Scaling configurations γ.

Figure 4: The change of perturbation stability and empirical Lipschitz constant when (a) depth of Stage-3 is reduced, (b) width of Stage-3 is reduced, or (c) linear scaling with γ and ^{w}10-10-4.

The Trade-off Between Capacity and Lipschitzness. We compute the above two metrics on the test set of CIFAR-10 for models with different depth and width configurations explored in Section 4.1 and 4.2. The results are illustrated in Figure 4, where the empirical Lipschitz constant is computed for the entire network. We can observe that, when depth or width for the given network is reduced, the empirical Lipschitz constant is also reduced, and the perturbation stability improves. This is consistent with our theoretical analysis in the Lipschitz constant upper bound. As shown in Figure 4b and 4c, this observation is more obvious for the width reduction. There exists a trade-off between the network capacity and Lipschitzness. For example, with $\gamma = 0.25$ scaling, the network achieves a much lower Lipschitzness and better stability, however, it also significantly reduces the clean accuracy. This indicates that adversarial training does require larger capacity models and a better trade-off can be achieved by balancing model capacity and Lipschitzness using proper architectural reduction.

(a) Reducing width at Stage-1. (b) Reducing width at Stage-2. (c) WRN-34-12 and WRN-34-R

Figure 5: Empirical Lipschitz constant of the output layers of different residual blocks (bins 1-15) or the entire network (bin 16). All experiments are run on CIFAR-10.

In Figure 5, we plotted the empirical Lipschitz constant of the output layer of each residual block or the entire network. The $f_{\boldsymbol{\theta}}(\boldsymbol{x})$ in equation (3) is replaced with the output of each residual block $f_{\boldsymbol{\theta}_j}(\boldsymbol{x})$ (from input to block output), and the last (16-th) bin is the empirical Lipschitz constant of the entire network (from input to logits). From Figure 5, we find that: 1) within each stage, the empirical Lipschitz increases with depth; 2) when transitioning from one stage to the next, the spatial dimension decreases while the empirical Lipschitz decreases; 3) comparing WRN-34-12 with WRN-34-R (Figure 5c), the empirical Lipschitz increase/decrease with the network width. This provides empirical results for our theoretical analysis in Section 3.

Reducing Parameters at Deeper Layers Improves both Perturbation Stability and Lipschitzness. Based on our theoretical analysis, reducing the width at Stage-1 and Stage-2 should improve the Lipschitzness of the corresponding stage as well as the entire network. However, empirically, it is true for the corresponding stage but not necessarily for the entire network. This is because the theoretical analysis in Section 3 only considers the interplay between two adjacent layers (or blocks), not including that of the non-adjacent layers. The empirical results in Figure 5 can fill this gap.

Specifically, Stage-1 width reduction (Figure 5a) lowers the Lipschitzness of Stage-1 blocks but not the overall Lipschitzness. Stage-2 width reduction (Figure 5b) can improve both Stage-2 and the overall Lipschitzness but fails to improve clean accuracy, perturbation stability nor adversarial robustness. WRN-34-R in Figure 5c marks our discovered reduction and scaling rule. Compared with standard WRNs, WRN-34-R not only reduces the width of Stage-3 (decreasing Lipschitzness) but also increases the widths of Stage-1 and Stage-2 (increasing Lipschitzness). Figure 5c shows that the increased Lipschitzness at Stage-1 and Stage-2 of WRN-34-R can be effectively mitigated at Stage-3, leading to decreased overall Lipschitzness and improved robustness (see Table 4.3). This also results in higher clean accuracy and perturbation stability (Figure 4c). We conjecture this is because Stage-3 (the last stage) is closer to the final output, thus has a more direct impact on the overall Lipschitzness. These empirical results provide a more in-depth understanding of the impact of width and depth configurations to the overall Lipschitzness, perturbation stability and adversarial robustness.

5   Adversarial Robustness Evaluation

In this section, we apply the discovered $^{\text{w}}$10-10-4 width configuration rule to VGG, DenseNet (DN), as well as DNNs discovered by NAS, and evaluate their robustness with various adversarial attacks and defence methods on CIFAR-10 [1] in the white-box setting. Additional results for CIFAR-10 black-box and ImageNet [68] using FastAT [35] can be found in Appendix D.

Experimental Settings. We consider VGG-11 [69], DenseNet-121 (DN-121) [70] and a network found by DARTS [71] with 11 cells. We denote the optimized VGG-11, DN-121 and DARTS networks as VGG-11-R, DN-121-R and DARTS-R (see Appendix B.2 for details), respectively. For a fair comparison between the discovered WRN-34-R (scaled by $\gamma = 2.0$) and the standard WRN, we upscale WRN-34-10 to WRN-34-12 to make sure the two models have a similar amount of parameters. We train all networks using 4 adversarial training methods: Standard Adversarial Training (SAT) [16], TRADES [17], Misclassification Aware adveRsarial Training (MART) [19] and Robust Self-Training (RST) with 500K additional data [22]. More details can be found in Appendix B.1.

White-box Robustness. We evaluate the robustness of the networks to 5 adversarial attacks including Fast Gradient Sign Method (FGSM) [5], Projected Gradient Descent (PGD) [16], Carlini and Wagner (CW) [72], Guided Adversarial Margin Attack (GAMA) [31] and AutoAttack (AA) [28]. We apply these attacks on the test sets of CIFAR-10 and CIFAR-100 with the same maximum adversarial perturbation $\epsilon = 8/255$ as adopted for model training. For PGD, we use the 20-step PGD (PGD^{20}) with step size $\alpha = \epsilon/10$. For GAMA attack, we set its perturbation steps to 100 following the original paper. We report the model's accuracy on the test adversarial examples crafted by these evaluation attacks for models obtained at both the best and the last checkpoints, following [17, 44, 19].

The white-box evaluation results including both clean accuracy and adversarial robustness are reported in Table 2. As can be inferred, a robustness gain of $1 \sim 3\%$ can be consistently achieved when the networks are reconfigured following our discovered configuration rule. And the improvements are not restricted to a particular architecture nor adversarial training method, except there is slight decrease for CW$_\infty$ on CIFAR-100 for SAT and MART. This wide range of robustness improvements by a simple architectural reconfiguration confirms that our findings are very general and can be

Table 2: White-box robustness results on CIFAR-10 and CIFAR-100. **500K:** Additional data used as in [22]. **Params:** number of parameters. SAT: Adversarial Training [16]; TRADES [17]; MART [19]; GAMA^{100}: 100-step GAMA attack [31]; AA: AutoAttack [28]; CW$_\infty$: L_∞ version CW attack [72] optimized by PGD; **-R**: reconfigured networks following our discovered robust architectural configuration; **Last:** Results evaluated at the last checkpoint. **Best:** Results evaluated at the best checkpoint according to PGD^{20}. The best results are in **bold**.

Dataset	Model	Method	Params (M)	Clean (%)		FGSM (%)		PGD^{20} (%)		GAMA^{100} (%)		CW$_\infty$ (%)		AA (%)	
				Last	Best	Last	Best	Last	Best	Last	Best	Last	Best	Last	Best
CIFAR-10	VGG-11	SAT	9.23	79.24	77.84	55.98	56.68	42.62	45.46	38.59	40.65	45.45	46.29	37.21	39.84
	VGG-11-R	SAT	5.83	79.63	77.34	**57.35**	**57.11**	43.93	45.97	39.71	41.31	46.49	47.23	**38.44**	**40.65**
	DN-121	SAT	6.96	86.87	86.07	65.56	66.58	51.67	54.79	48.60	51.00	52.03	54.00	47.16	50.34
	DN-121-R	SAT	6.00	87.22	86.01	**67.12**	**67.20**	52.52	55.16	49.37	51.44	53.07	54.67	47.75	50.54
	DARTS	SAT	6.58	86.76	86.55	64.48	**67.10**	49.44	54.23	46.52	50.74	52.03	54.00	45.16	49.98
	DARTS-R	SAT	2.53	87.20	85.79	**66.74**	66.61	52.36	55.01	48.71	50.94	53.07	54.67	47.75	50.54
	WRN-34-12	SAT	66.46	86.71	87.20	64.06	66.26	49.92	53.09	47.45	50.40	52.23	53.58	46.06	49.18
	WRN-34-R	SAT	68.12	87.62	87.85	66.23	**68.15**	51.08	55.35	48.45	51.36	52.42	54.57	46.75	50.03
	WRN-34-12	TRADES	66.46	85.84	84.59	65.70	66.85	53.02	56.01	49.60	52.35	53.35	54.72	48.48	51.83
	WRN-34-R	TRADES	68.12	86.77	86.02	**67.99**	**68.49**	55.15	57.66	51.92	53.86	55.41	56.30	50.90	53.46
	WRN-34-12	MART	66.46	85.98	82.62	66.85	67.00	54.30	57.95	49.58	52.20	52.29	54.61	47.68	51.21
	WRN-34-R	MART	68.12	86.09	83.69	**68.79**	**68.18**	56.31	59.13	51.40	53.22	54.20	55.44	49.90	52.48
CIFAR-10 +500K	WRN-34-12	RST	66.46	90.52	90.36	76.01	76.02	65.52	65.56	61.67	61.70	64.30	64.26	60.90	60.96
	WRN-34-R	RST	68.12	90.73	90.56	**76.51**	**76.44**	66.46	66.51	62.38	62.49	65.12	65.10	61.49	61.56
CIFAR-100	WRN-34-12	SAT	66.53	59.63	60.64	33.67	37.28	24.50	27.61	23.38	24.95	**43.78**	**42.02**	22.27	24.42
	WRN-34-R	SAT	68.16	61.17	61.33	**35.00**	**38.72**	25.03	29.02	23.38	25.70	43.52	41.46	**22.72**	**25.20**
	WRN-34-12	TRADES	66.53	55.62	56.47	35.35	36.90	27.52	29.48	24.94	25.21	44.75	46.19	24.58	24.85
	WRN-34-R	TRADES	68.16	56.83	56.75	**36.95**	**37.68**	29.17	29.92	25.48	25.48	45.04	45.52	25.13	25.23
	WRN-34-12	MART	66.53	58.51	57.29	36.06	39.48	26.50	32.43	23.85	27.64	41.53	38.73	23.33	26.92
	WRN-34-R	MART	68.16	61.72	58.27	**39.68**	**41.24**	29.94	34.12	26.27	29.33	39.20	38.45	**25.60**	**28.63**

immediately applied to commonly used DNNs to obtain more adversarial robustness. For VGG-11, DN-121 and DARTS, our robust reconfiguration can reduce the parameters by a considerable amount.

6 Relation to Existing Understandings

One recent work [51] shows that wider networks tend to increase the Lipschitzness, a finding that is consistent with ours. In [51], the theoretical analysis is based on Neural Tangent Kernel (NTK) under the assumption that all layers share the same width. By contrast, our analysis provides a more in-depth understanding related to the width and depth of each individual layer. Whilst in [51], the wider network utilizes a stronger regularization to mitigate the vulnerability (instability) caused by increased Lipschitzness, our work shows that this can be achieved alternatively by a simple reconfiguration of the architecture.

It has also been found that weight decay plays an important role in adversarial training [48, 73]. This can be explained by our theoretical analysis in Theorem 1 and 2. Considering the weight matrix is normally distributed $\mathcal{N}(0, \sigma_{\boldsymbol{\theta}}^2)$, weight decay encourages the model to learn weights of smaller magnitudes, thus reducing the variance $\sigma_{\boldsymbol{\theta}}^2$ of the weight matrix. This will lead to reduced upper bound of the Lipschitz constant and improved robustness. See Appendix E for more discussions.

7 Conclusion

In this paper, we explored the architectural ingredients of adversarially robust DNNs via extensive fine-controlled experiments and theoretical analysis. Our findings are: 1) more parameters does not necessarily lead to more adversarially robust models; 2) reducing capacity (up to a limit) via either depth or width at the deeper layers improves adversarial robustness; and 3) under the same type of architectures and parameter budget, there may exist an architectural configuration that can exploit the full robustness potential of the network. We also showed that depth and width offer different levels of flexibility for capacity reduction and robustness improvement. Following a width reduction and scaling rule, we showed that our findings are generic, not restricted to a particular adversarial training method, and can be immediately applied to improve both manually-designed or NAS-discovered DNNs. We also provide a series of empirical understandings on the distinctive impacts of the deeper layers on adversarial robustness. Our work can provide useful insights into the architectural perspective of adversarial robustness, and help design more adversarially robust DNNs. The sociatal impacts of our work are discussed in Appendix E.2.

References

[1] Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009.

[2] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *ECCV*, 2014.

[3] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *EMNLP*, 2016.

[4] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian J. Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *ICLR*, 2014.

[5] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *ICLR*, 2015.

[6] Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *CVPR*, 2018.

[7] Ranjie Duan, Xingjun Ma, Yisen Wang, James Bailey, A. Kai Qin, and Yun Yang. Adversarial camouflage: Hiding physical-world attacks with natural styles. In *CVPR*, 2020.

[8] Samuel G Finlayson, John D Bowers, Joichi Ito, Jonathan L Zittrain, Andrew L Beam, and Isaac S Kohane. Adversarial attacks on medical machine learning. *Science*, 363(6433):1287–1289, 2019.

[9] Xingjun Ma, Yuhao Niu, Lin Gu, Yisen Wang, Yitian Zhao, James Bailey, and Feng Lu. Understanding adversarial attacks on deep learning based medical image analysis systems. *Pattern Recognition*, 2020.

[10] Guneet S. Dhillon, Kamyar Azizzadenesheli, Zachary C. Lipton, Jeremy Bernstein, Jean Kossaifi, Aran Khanna, and Animashree Anandkumar. Stochastic activation pruning for robust adversarial defense. In *ICLR*, 2018.

[11] Cihang Xie, Jianyu Wang, Zhishuai Zhang, Zhou Ren, and Alan L. Yuille. Mitigating adversarial effects through randomization. In *ICLR*, 2018.

[12] Jacob Buckman, Aurko Roy, Colin Raffel, and Ian J. Goodfellow. Thermometer encoding: One hot way to resist adversarial examples. In *ICLR*, 2018.

[13] Chuan Guo, Mayank Rana, Moustapha Cissé, and Laurens van der Maaten. Countering adversarial images using input transformations. In *ICLR*, 2018.

[14] Anish Athalye, Nicholas Carlini, and David A. Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *ICML*, 2018.

[15] Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *arXiv preprint arXiv:2002.08347*, 2020.

[16] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *ICLR*, 2018.

[17] Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P. Xing, Laurent El Ghaoui, and Michael I. Jordan. Theoretically principled trade-off between robustness and accuracy. In *ICML*, 2019.

[18] Yisen Wang, Xingjun Ma, James Bailey, Jinfeng Yi, Bowen Zhou, and Quanquan Gu. On the convergence and robustness of adversarial training. In *ICML*, 2019.

[19] Yisen Wang, Difan Zou, Jinfeng Yi, James Bailey, Xingjun Ma, and Quanquan Gu. Improving adversarial robustness requires revisiting misclassified examples. In *ICLR*, 2020.

[20] Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. In *NeurIPS*, 2019.

[21] Ludwig Schmidt, Shibani Santurkar, Dimitris Tsipras, Kunal Talwar, and Aleksander Madry. Adversarially robust generalization requires more data. In *NeurIPS*, 2018.

[22] Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C. Duchi, and Percy Liang. Unlabeled data improves adversarial robustness. In *NeurIPS*, 2019.

[23] Aditi Raghunathan, Sang Michael Xie, Fanny Yang, John Duchi, and Percy Liang. Understanding and mitigating the tradeoff between robustness and accuracy. In *ICML*, 2020.

[24] Runtian Zhai, Tianle Cai, Di He, Chen Dan, Kun He, John Hopcroft, and Liwei Wang. Adversarially robust generalization just requires more unlabeled data. *arXiv preprint arXiv:1906.00555*, 2019.

[25] Cihang Xie and Alan L. Yuille. Intriguing properties of adversarial training at scale. In *ICLR*, 2020.

[26] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *BMVC*, 2016.

[27] Dong Su, Huan Zhang, Hongge Chen, Jinfeng Yi, Pin-Yu Chen, and Yupeng Gao. Is robustness the cost of accuracy?–a comprehensive study on the robustness of 18 deep image classification models. In *ECCV*, 2018.

[28] Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *ICML*, 2020.

[29] Jingfeng Zhang, Xilie Xu, Bo Han, Gang Niu, Lizhen Cui, Masashi Sugiyama, and Mohan Kankanhalli. Attacks which do not kill training make adversarial learning stronger. In *ICML*, 2020.

[30] Jean-Baptiste Alayrac, Jonathan Uesato, Po-Sen Huang, Alhussein Fawzi, Robert Stanforth, and Pushmeet Kohli. Are labels required for improving adversarial robustness? In *NeurIPS*, 2019.

[31] Gaurang Sriramanan, Sravanti Addepalli, Arya Baburaj, and R Venkatesh Babu. Guided adversarial attack for evaluating and enhancing adversarial defenses. *arXiv preprint arXiv:2011.14969*, 2020.

[32] Gavin Weiguang Ding, Yash Sharma, Kry Yik Chau Lui, and Ruitong Huang. Mma training: Direct input space margin maximization through adversarial training. In *ICLR*, 2020.

[33] Tianyu Pang, Kun Xu, Yinpeng Dong, Chao Du, Ning Chen, and Jun Zhu. Rethinking softmax cross-entropy loss for adversarial robustness. In *ICLR*, 2020.

[34] Ali Shafahi, Mahyar Najibi, Amin Ghiasi, Zheng Xu, John P. Dickerson, Christoph Studer, Larry S. Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *NeurIPS*, 2019.

[35] Eric Wong, Leslie Rice, and J. Zico Kolter. Fast is better than free: Revisiting adversarial training. In *ICLR*, 2020.

[36] Dinghuai Zhang, Tianyuan Zhang, Yiping Lu, Zhanxing Zhu, and Bin Dong. You only propagate once: Accelerating adversarial training via maximal principle. In *NeurIPS*, 2020.

[37] Tianlong Chen, Sijia Liu, Shiyu Chang, Yu Cheng, Lisa Amini, and Zhangyang Wang. Adversarial robustness: From self-supervised pre-training to fine-tuning. In *CVPR*, 2020.

[38] Tianyu Pang, Xiao Yang, Yinpeng Dong, Taufik Xu, Jun Zhu, and Hang Su. Boosting adversarial training with hypersphere embedding. In *NeurIPS*, 2020.

[39] Minhao Cheng, Pin-Yu Chen, Sijia Liu, Shiyu Chang, Cho-Jui Hsieh, and Payel Das. Self-progressing robust training. *arXiv preprint arXiv:2012.11769*, 2020.

[40] Dongxian Wu, Shu-Tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization. *NeurIPS*, 2020.

[41] Yinpeng Dong, Zhijie Deng, Tianyu Pang, Jun Zhu, and Hang Su. Adversarial distributional training for robust deep learning. In *NeurIPS*, 2020.

[42] Yang Bai, Yuyuan Zeng, Yong Jiang, Shu-Tao Xia, Xingjun Ma, and Yisen Wang. Improving adversarial robustness via channel-wise activation suppressing. In *ICLR*, 2021.

[43] Jingfeng Zhang, Jianing Zhu, Gang Niu, Bo Han, Masashi Sugiyama, and Mohan Kankanhalli. Geometry-aware instance-reweighted adversarial training. In *ICLR*, 2021.

[44] Leslie Rice, Eric Wong, and J. Zico Kolter. Overfitting in adversarially robust deep learning. In *ICML*, 2020.

[45] Tianlong Chen, Zhenyu Zhang, Sijia Liu, Shiyu Chang, and Zhangyang Wang. Robust overfitting may be mitigated by properly learned smoothening. In *ICLR*, 2021.

[46] Hadi Salman, Andrew Ilyas, Logan Engstrom, Ashish Kapoor, and Aleksander Madry. Do adversarially robust imagenet models transfer better? In *NeurIPS*, 2020.

[47] Cihang Xie, Mingxing Tan, Boqing Gong, Jiang Wang, Alan L Yuille, and Quoc V Le. Adversarial examples improve image recognition. In *CVPR*, 2020.

[48] Tianyu Pang, Xiao Yang, Yinpeng Dong, Hang Su, and Jun Zhu. Bag of tricks for adversarial training. In *ICLR*, 2021.

[49] George Cazenavette, Calvin Murdock, and Simon Lucey. Architectural adversarial robustness: The case for deep pursuit. *arXiv preprint arXiv:2011.14427*, 2020.

[50] Preetum Nakkiran. Adversarial robustness may be at odds with simplicity. *arXiv preprint arXiv:1901.00532*, 2019.

[51] Boxi Wu, Jinghui Chen, Deng Cai, Xiaofei He, and Quanquan Gu. Do wider neural networks really help adversarial robustness? *arXiv preprint arXiv:2010.01279*, 2020.

[52] Minghao Guo, Yuzhe Yang, Rui Xu, Ziwei Liu, and Dahua Lin. When NAS meets robustness: In search of robust architectures against adversarial attacks. In *CVPR*, 2020.

[53] Xuefei Ning, Junbo Zhao, Wenshuo Li, Tianchen Zhao, Huazhong Yang, and Yu Wang. Multi-shot nas for discovering adversarially robust convolutional neural architectures at targeted capacities. *arXiv preprint arXiv:2012.11835*, 2020.

[54] Ramtin Hosseini, Xingyi Yang, and Pengtao Xie. Dsrna: Differentiable search of robust neural architectures. *arXiv preprint arXiv:2012.06122*, 2020.

[55] Minjing Dong, Yanxi Li, Yunhe Wang, and Chang Xu. Adversarially robust neural architectures. *arXiv preprint arXiv:2009.00902*, 2020.

[56] Hanlin Chen, Baochang Zhang, Song Xue, Xuan Gong, Hong Liu, Rongrong Ji, and David Doermann. Anti-bandit neural architecture search for model defense. In *ECCV*, 2020.

[57] Xiangning Chen and Cho-Jui Hsieh. Stabilizing differentiable architecture search via perturbation-based regularization. In *ICML*, 2020.

[58] Chaitanya Devaguptapu, Devansh Agarwal, Gaurav Mittal, and Vineeth N Balasubramanian. An empirical study on the robustness of nas based architectures. *arXiv preprint arXiv:2007.08428*, 2020.

[59] Mark Rudelson and Roman Vershynin. Non-asymptotic theory of random matrices: extreme singular values. In *International Congress of Mathematicians (ICM)*, 2010.

[60] Henry Gouk, Eibe Frank, Bernhard Pfahringer, and Michael J Cree. Regularisation of neural networks by enforcing lipschitz continuity. *Machine Learning*, 2021.

[61] SiQi Zhou and Angela P Schoellig. An analysis of the expressiveness of deep neural network architectures based on their lipschitz constants. *arXiv preprint arXiv:1912.11511*, 2019.

[62] Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. In *ICML*, 2017.

[63] Haifeng Qian and Mark N Wegman. L2-nonexpansive neural networks. *arXiv preprint arXiv:1802.07896*, 2018.

[64] Yusuke Tsuzuku, Issei Sato, and Masashi Sugiyama. Lipschitz-margin training: Scalable certification of perturbation invariance for deep neural networks. In *NeurIPS*, 2018.

[65] Todd Huster, Cho-Yu Jason Chiang, and Ritu Chadha. Limitations of the lipschitz constant as a defense against adversarial examples. In *ECML PKDD*, 2018.

[66] Yao-Yuan Yang, Cyrus Rashtchian, Hongyang Zhang, Ruslan Salakhutdinov, and Kamalika Chaudhuri. A closer look at accuracy vs. robustness. *NeurIPS*, 2020.

[67] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015.

[68] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Fei-Fei Li. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

[69] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *ICLR*, 2015.

[70] Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks. In *CVPR*, 2017.

[71] Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: differentiable architecture search. In *ICLR*, 2019.

[72] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *S&P*, 2017.

[73] Sven Gowal, Chongli Qin, Jonathan Uesato, Timothy Mann, and Pushmeet Kohli. Uncovering the limits of adversarial training against norm-bounded adversarial examples. *arXiv preprint arXiv:2010.03593*, 2020.

[74] Ilya Loshchilov and Frank Hutter. SGDR: stochastic gradient descent with warm restarts. In *ICLR*, 2017.

[75] Vikash Sehwag, Shiqi Wang, Prateek Mittal, and Suman Jana. Hydra: Pruning adversarially robust neural networks. *NeurIPS*, 2020.