META-LEARNING BAYESIAN NEURAL NETWORK PRIORS BASED ON PAC-BAYESIAN THEORY

ABSTRACT

Bayesian deep learning is a promising approach towards improved uncertainty quantification and sample efficiency. Due to their complex parameter space, choosing informative priors for Bayesian Neural Networks (BNNs) is challenging. Thus, often a naive, zero-centered Gaussian is used, resulting both in bad generalization and poor uncertainty estimates when training data is scare. In contrast, *meta-learning* aims to extract such prior knowledge from a set of related learning tasks. We propose a principled and scalable algorithm for meta-learning BNN priors based on PAC-Bayesian bounds. Whereas previous approaches require optimizing the prior and multiple variational posteriors in an interdependent manner, our method does not rely on difficult nested optimization problems and is agnostic to the variational inference method in use. Our experiments show that the proposed method is not only computationally more efficient but also yields better predictions and uncertainty estimates when compared to previous meta-learning methods and BNNs with standard priors.

1 INTRODUCTION

Bayesian Neural Networks (BNNs) offer a probabilistic interpretation of deep learning by inferring distributions over the model's weights (Neal, 1996). With the potential of combining the scalability and performance of neural networks (NNs) with a framework for uncertainty quantification, BNNs have lately received increased attention (Blundell et al., 2015; Gal & Ghahramani, 2016). In particular, their ability to express epistemic uncertainty makes them highly relevant for applications such as active learning (Hernández-Lobato & Adams, 2015) and reinforcement learning (Riquelme et al., 2018).

However, BNNs face two major issues: 1) the intractability of posterior inference and 2) the difficulty of choosing good Bayesian priors. While the former has been addressed in an extensive body of literature on variation inference (e.g. Blundell et al., 2015; Blei et al., 2016; Mishkin et al., 2018; Liu & Wang, 2016), the latter has only received limited attention (Vladimirova et al., 2019; Ghosh & Doshi-Velez, 2017). Choosing an informative prior for BNNs is particularly difficult due to the high-dimensional and hardly interpretable parameter space of NNs. Due to the lack of good alternatives, often a zero-centered, isotropic Gaussian is used, reflecting (almost) no a priori knowledge about the problem at hand. This does not only lead to poor generalization when data is scarce, but also renders the Bayesian uncertainty estimates poorly calibrated (Kuleshov et al., 2018).

Meta-learning (Schmidhuber, 1987; Thrun & Pratt, 1998) acquires inductive bias in a data-driven way, thus, constituting an alternative route for addressing this issue. In particular, meta-learners attempt to extract shared (prior) knowledge from a set of related learning tasks (i.e., datasets), aiming to learn in face of a new, related task. Our work develops a principled and scalable algorithm for meta-learning BNN priors. We build on the PAC-Bayesian framework (McAllester, 1999), a methodology from statistical learning theory for deriving generalization bounds. Previous PAC-Bayesian bounds for meta-learners (Pentina & Lampert, 2014; Amit & Meir, 2018) require solving a difficult optimization problem, involving the optimization of the prior as well as multiple variational posteriors in a nested manner. Aiming to overcome this issue, we present a *PAC-Bayesian bound that does not rely on nested optimization* and, unlike (Rothfuss et al., 2020), can be *tractably optimized for BNNs*. This makes the resulting meta-learner, referred to as *PACOH-NN*, not only much more *computationally efficient and scalable* than previous approaches for meta-learning BNN priors (Amit & Meir, 2018), but also *agnostic to the choice of approximate posterior inference method.*

Our experiments demonstrate that the computational advantages of *PACOH-NN* do result in degraded predictive performance. In fact, across several regression and classification environments, *PACOH-NN* achieves a *comparable or better predictive accuracy* than several popular meta-learning approaches, while *improving the quality of the uncertainty estimates*. Moreover, we showcase how meta-learned *PACOH-NN* priors can be used in a real-world bandit task concerning the development of vaccines, suggesting that many other challenging real-world problems may benefit from the proposed approach.

2 RELATED WORK

Bayesian Neural Networks. The majority of research on BNNs focuses on approximating the intractable posterior distribution (Graves, 2011; Blundell et al., 2015; Liu & Wang, 2016; Wang et al., 2019). In particular, we employ the approximate inference method of Liu & Wang (2016). Another crucial question is how to select a good BNN prior (Vladimirova et al., 2019). While the majority of work (e.g. Louizos & Welling, 2016; Huang et al., 2020) employs a simple zero-centered, isotropic Gaussian, Ghosh & Doshi-Velez (2017) and Pearce et al. (2020) have proposed other prior distributions for BNNs. In contrast, we go the alternative route of choosing priors in a data-driven way.

Meta-learning. A range of popular methods in meta-learning attempt to learn the "learning program" in form of a recurrent model (Hochreiter et al., 2001; Andrychowicz et al., 2016; Chen et al., 2017), learn an embedding space shared across tasks (Snell et al., 2017; Vinyals et al., 2016) or the initialization of a NN such that it can be quickly adapted to new tasks (Finn et al., 2017; Nichol et al., 2018; Rothfuss et al., 2019). A group of recent methods also uses probabilistic modeling to also allow for uncertainty quantification (Kim et al., 2018; Finn et al., 2018; Garnelo et al., 2018). Although the mentioned approaches are able to learn complex inference patterns, they rely on settings where meta-training tasks are abundant and fall short of performance guarantees. In contrast, we provide a formal assessment of the generalization properties of our algorithm. Moreover, *PACOH-NN* allows for principled uncertainty quantification, including separate treatment of epistemic and alleatoric uncertainty. This makes it particularly useful for sequential decision algorithms (Lattimore & Szepesvari, 2020).

PAC-Bayesian theory. Previous work presents generalization bounds for randomized predictors, assuming a prior to be given exogenously (McAllester, 1999; Catoni, 2007; Germain et al., 2016; Alquier et al., 2016). More recent work explores data-dependent priors (Parrado-Hernandez et al., 2012; Dziugaite & Roy, 2016) or extends previous bounds to the scenario where priors are meta-learned (Pentina & Lampert, 2014; Amit & Meir, 2018). However, these meta-generalization bounds are hard to minimize as they leave both the hyper-posterior and posterior unspecified, which leads to nested optimization problems. Our work builds on the results of Rothfuss et al. (2020) who introduce the methodology to derive the closed-form solution of the PAC-Bayesian meta-learning problem. However, unlike ours, their approach suffers from (asymptotically) non-vanishing terms in the bounds and relies on a closed-form solution of the marginal log-likelihood. By contributing a numerically stable score estimator for the generalized marginal log-likelihood, we are able to overcome such limitations, making PAC-Bayesian meta-learning both tractable and scalable for a much larger pool of models, including BNNs.

3 BACKGROUND: THE PAC-BAYESIAN FRAMEWORK

Bayesian Neural Networks. Consider a supervised learning task with data $S = \{(x_j, y_j)\}_{j=1}^m$ drawn the distribution $\mathcal{D}$. In that, $\mathbf{X} = \{x_j\}_{j=1}^m \in \mathcal{X}^m$ denotes training inputs and $\mathbf{Y} = \{y_j\}_{j=1}^m \in \mathcal{Y}^m$ the corresponding targets. For brevity, we also write $z_j := (x_j, y_j) \in \mathcal{Z}$. Let $h_\theta : \mathcal{X} \to \mathcal{Y}$ be a function parametrized by a NN with weights $\theta \in \Theta$. Using the NN mapping, we define a conditional distribution $p(y|x, \theta)$. For regression, we set $p(y|x, \theta) = \mathcal{N}(y|h_\theta(x), \sigma^2)$, where σ^2 is the observation noise variance. For classification, we choose $p(y|x, \theta) = \text{Multinomial}(\text{softmax}(h_\theta(x)))$. For Bayesian inference, one presumes a prior distribution $p(\theta)$ over the model parameters θ which is combined with the training data S into a posterior distribution $p(\theta|\mathbf{X}, \mathbf{Y}) \propto p(\theta)p(\mathbf{Y}|\mathbf{X}, \theta)$. For unseen test data points x^*, we form the predictive distribution as $p(y^*|x^*, \mathbf{X}, \mathbf{Y}) = \int p(y^*|x^*, \theta)p(\theta|\mathbf{X}, \mathbf{Y})d\theta$.

The Bayesian framework presumes partial knowledge of the data-generating process in form of a prior distribution. However, due to the practical difficulties in choosing an appropriate BNN prior, the prior is typically strongly misspecified (Syring & Martin, 2018). As a result, modulating the influence of the prior relative to the likelihood during inference typically improves the empirical performance of BNNs and is thus a common practice (Wenzel et al., 2020). Using such a "tempered" posterior $p_\tau(\theta|\mathbf{X}, \mathbf{Y}) \propto p(\theta)p(\mathbf{Y}|\mathbf{X}, \theta)^\tau$ with $\tau > 0$ is also referred to as *generalized Bayesian learning* (Guedj, 2019).

The PAC-Bayesian Framework. For readers that are unfamiliar with the PAC-Bayesian framework, we introduce the most relevant concepts in the following. For a more details, we refer to Guedj (2019). Given a loss function $l : \theta \times \mathcal{Z} \to \mathbb{R}$, we typically want to minimize the *generalization error* $\mathcal{L}(\theta, \mathcal{D}) = \mathbb{E}_{z^* \sim \mathcal{D}} \; l(\theta, z^*)$. Since $\mathcal{D}$ is unknown, we typically use the *empirical error* $\hat{\mathcal{L}}(\theta, S) = \frac{1}{m} \sum_{i=1}^{m} l(\theta, z_i)$ instead. In the PAC-Bayesian framework, we are concerned with *randomized predictors*, i.e., probability measures on the parameter space Θ, allowing us to reason about *epistemic uncertainty*. In particular, we consider two such probability measures, the *prior* $P \in \mathcal{M}(\mathcal{H})$ and the *posterior* $Q \in \mathcal{M}(\Theta)$. Here, $\mathcal{M}(\Theta)$ denotes the set of all probability measures on Θ. Note that in Bayesian inference, the prior and posterior are tightly connected through Bayes' theorem, whereas the PAC-Bayesian framework only requires the prior to be independent of the data S. Based on the error definitions above, we can define the so-called *Gibbs error* for a randomized predictor Q as $\mathcal{L}(Q, \mathcal{D}) = \mathbb{E}_{h \sim Q} \; \mathcal{L}(h, \mathcal{D})$ and its empirical counterpart as $\hat{\mathcal{L}}(Q, S) = \mathbb{E}_{h \sim Q} \; \hat{\mathcal{L}}(h, S)$. The PAC-Bayesian framework provides upper bounds for the unknown *Gibbs error* in the following form:

Theorem 1. *(Alquier et al., 2016) Given a data distribution $\mathcal{D}$, a prior $P \in \mathcal{M}(\Theta)$, a confidence level $\delta \in (0, 1]$, with probability at least $1 - \delta$ over samples $S \sim \mathcal{D}^m$, we have:*

$$\forall Q \in \mathcal{M}(\Theta) : \quad \mathcal{L}(Q, \mathcal{D}) \leq \hat{\mathcal{L}}(Q, S) + \frac{1}{\sqrt{m}} \left[D_{KL}(Q||P) + \ln \frac{1}{\delta} + \Psi(\sqrt{m}) \right] \tag{1}$$

where $\Psi(\sqrt{m}) = \ln \mathbb{E}_{\theta \sim P} \mathbb{E}_{S \in \mathcal{D}^m} \exp \left[\sqrt{m} \left(\mathcal{L}(\theta, \mathcal{D}) - \hat{\mathcal{L}}(\theta, S) \right) \right].$

If we make additional assumptions about the loss function l, we can bound $\Psi(\sqrt{m})$ and thereby obtain useful PAC-Bayesian bounds. When $l(\theta, z)$ is *bounded* in $[a, b]$, we can use Hoeffding's lemma to obtain $\Psi(\sqrt{m}) \leq ((b-a)^2)/8$. For unbounded loss functions, it is common to assume bounded moments. In particular, a loss function l is considered *sub-gamma* with variance factor s^2 and scale parameter c, under a prior P and data distribution $\mathcal{D}$, if it can be described by random variable $V := \mathcal{L}(h, \mathcal{D}) - l(h, z)$ whose moment generating function is upper bounded by that of a Gamma distribution $\Gamma(s, c)$. For details see Boucheron et al. (2013). In this case, we obtain $\Psi(\sqrt{m}) \leq s^2/(2 - \frac{2c}{\sqrt{m}}))$.

Connecting the PAC-Bayesian framework and generalized Bayesian learning. Typically, we are interested in a posterior distribution Q that promises us the lowest generalization error. Thus, it seems natural to use the posterior that minimizes the bound in (1). The following lemma gives us the closed form solution to such a minimization problem over the space of probability measures $\mathcal{M}(\Theta)$.

Lemma 1. *(Catoni, 2007) Let $g : \Theta \to \mathbb{R}$ be (loss) function and $Q, P \in \mathcal{M}(\Theta)$. Then,*

$$\forall \beta > 0 : \quad Q^*(\theta) := P(\theta) e^{-\beta g(\theta)} / Z(S, P) , \text{ with } \quad Z(S, P) = \mathbb{E}_{\theta \sim P} \left[e^{-\beta g(\theta)} \right] \tag{2}$$

is the minimizing probability density of $\; \arg\min_{Q \in \mathcal{M}(\Theta)} \; \beta \mathbb{E}_{\theta \sim Q} [g(\theta)] + D_{KL}(Q||P) .$

The respective minimizing distribution is known as *Gibbs posterior* Q^* (Catoni, 2007; Lever et al., 2013). As a consequence of Lemma 1, for fixed P, S, m and δ we can write the minimizer of (1) as

$$Q^*(\theta) = \arg\min_Q \sqrt{m} \hat{\mathcal{L}}(Q, S) + D_{KL}(Q||P) = P(\theta) e^{-\sqrt{m} \hat{\mathcal{L}}(\theta, S)} / Z(S, P) \tag{3}$$

where $Z(S, P)$ is a normalization constant. In a probabilistic setting, we would define the loss function as the negative log-likelihood, i.e. $l(\theta, z_i) := -\log p(z_i | \theta)$. In this case, the optimal Gibbs posterior coincides with the *generalized Bayesian posterior* $Q^*(\theta; P, S) \propto P(\theta) p(S|\theta)^{1/\sqrt{m}} / Z(S, P)$ where $Z(S, P) = \int_{\Theta} P(\theta) p(S|\theta)^{1/\sqrt{m}} \, d\theta$ is the *generalized marginal likelihood* of the data sample S.

4 PAC-BAYESIAN BOUNDS FOR META-LEARNING

In the standard supervised learning setup (see Sec. 3), the learner has prior knowledge in the form of a prior distribution P which is given exogeneously. When the learner faces a new task, it uses the evidence, provided in form of the dataset S, to update the prior into a posterior distribution Q. We formalize such a *base learner* $Q(S, P)$ as a mapping $Q : \mathcal{Z}^m \times \mathcal{M}(\mathcal{H}) \to \mathcal{M}(\mathcal{H})$ that takes in a dataset and prior and outputs a posterior.

In contrast, in meta-learning we aim to acquire such such prior P in a data-driven manner, that is, by consulting a set of n statistically related learning tasks $\{\tau_1, ..., \tau_n\}$. We follow the setup of Baxter (2000) in which all tasks $\tau_i := (\mathcal{D}_i, S_i)$ share the same data domain $\mathcal{Z} := \mathcal{X} \times \mathcal{Y}$, parameter space

Θ and loss function $l(\theta, z)$, but may differ in their (unknown) data distribution $\mathcal{D}_i$ and the number of points m_i in the corresponding dataset $S_i \sim \mathcal{D}_i^{m_i}$. Further, we assume that each task $\tau_i \sim \mathcal{T}$ is drawn i.i.d. from an *environment* $\mathcal{T}$, which is a probability distribution over data distributions and corresponding datasets. The goal is to extract knowledge from the observed tasks which can then be used as prior knowledge for learning on new (yet unobserved) target tasks $\tau \sim \mathcal{T}$ (Amit & Meir, 2018).

In order to be able to extend the PAC-Bayesian analysis to the meta-learning setting, we again consider the notion of probability distributions over hypotheses/parameters. However, while the object of learning has previously been the NN parameters θ, it is now the prior distribution $P \in \mathcal{M}(\Theta)$. In particular, the meta-learner presumes a *hyper-prior* $\mathcal{P} \in \mathcal{M}(\mathcal{M}(\mathcal{H}))$, i.e., a distribution over priors P. Observing data sets $S_1, ..., S_n$ from multiple tasks, the meta-learner then updates the hyper-prior into a *hyper-posterior* $\mathcal{Q}$. The performance of this hyper-posterior is measured as the expected Gibbs error when sampling priors P from $\mathcal{Q}$ and applying the base learner, the so-called *transfer-error*:

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) := \mathbb{E}_{P \sim \mathcal{Q}} \left[\mathbb{E}_{(\mathcal{D}, m) \sim \mathcal{T}} \left[\mathbb{E}_{S \sim \mathcal{D}^m} \left[\mathcal{L}(Q(S, P), \mathcal{D}) \right] \right] \right]$$

While $\mathcal{L}(\mathcal{Q}, \mathcal{T})$ is unknown in practice, we can estimate it using the *empirical multi-task error*

$$\hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n) := \mathbb{E}_{P \sim \mathcal{Q}} \left[\frac{1}{n} \sum_{i=1}^{n} \hat{\mathcal{L}} \left(Q(S_i, P), S_i \right) \right] .$$

Similar to the PAC-Bayesian guarantees for single task learning, we can bound the transfer error by its empirical counterpart $\hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n)$ plus several tractable complexity terms:

Theorem 2. *Let $Q : \mathcal{Z}^m \times \mathcal{M}(\mathcal{H}) \rightarrow \mathcal{M}(\mathcal{H})$ be a base learner, $\mathcal{P} \in \mathcal{M}(\mathcal{M}(\mathcal{H}))$ some fixed hyper-prior and $m = m_i \; \forall i = 1, .., n$. For all hyper-posteriors $\mathcal{Q} \in \mathcal{M}(\mathcal{M}(\mathcal{H}))$ and $\delta \in (0, 1]$,*

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq \hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n) + \left(\frac{1}{n\sqrt{m}} + \frac{1}{\sqrt{n}} \right) D_{KL}(\mathcal{Q} || \mathcal{P})$$

$$+ \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{m}} \mathbb{E}_{P \sim \mathcal{Q}} \left[D_{KL}(Q(S_i, P) || P) \right] + C(\delta, n, \tilde{m}) \tag{4}$$

holds with probability $1 - \delta$. If the loss function is bounded, that is $l : \mathcal{H} \times \mathcal{Z} \rightarrow [a, b]$, the above inequality holds with $C(\delta, n, \tilde{m}) = \frac{(b_k - a_k)^2}{8\sqrt{\tilde{m}}} + \frac{(b_k - a_k)^2}{8\sqrt{n}} - \frac{1}{\sqrt{n}} \ln \delta$. If the loss function is sub-gamma with variance factor s_I^2 and scale parameter c_I for data distributions $\mathcal{D}_i$ and s_{II}^2, c_{II} for the task distribution $\mathcal{T}$, the inequality holds with $C(\delta, n, \tilde{m}) = \frac{s_I^2}{2(\sqrt{\tilde{m}} - c_I)} + \frac{s_{II}^2}{2(\sqrt{n} - c_{II})} - \frac{1}{\sqrt{n}} \ln \delta$.

Under bounded loss assumption, Theorem 2 provides a structurally similar, but tighter bound than Pentina & Lampert (2014) and Rothfuss et al. (2020). Beyond that, the theorem also provides guarantees for *unbounded* loss functions under moment constraints (see Appendix A.1 for details). This makes Theorem 2 particularly relevant for probabilistic models such as BNNs in which the loss function coincides with the inherently unbounded negative log-likelihood.

Amit & Meir (2018) propose to meta-learn NN priors by directly minimizing a bound similar to (4). However, the posterior inference for BNNs, i.e. obtaining $Q_i = Q(S_i, P)$, is a stochastic optimization problem in itself whose solution in turn depends on P. Hence, minimizing such meta-level bound w.r.t. P constitutes a computatinally infeasible two-level optimization problem. To circumvent this issue, they jointly optimize P and n approximate posteriors Q_i that correspond to the different datasets S_i, leading to an unstable and poorly scalable meta-learning algorithm.

Aiming to overcome these issues, we employ the methodology of Rothfuss et al. (2020) and assume the Gibbs posterior $Q^*(S_i, P)$ as a base learner. As discussed in Section 3, $Q^*(S_i, P)$ does not only constitute a generalized Bayesian posterior but also minimizes PAC-Bayesian error bound. Thus, the resulting bound in Corollary 1 is tighter than (4). More importantly, the bound can be stated in terms of the partition function $Z(S_i, P)$ which allows us to forgo the explicit reliance on the task posteriors Q_i. This makes the bound much easier to optimize as a meta-learning objective than previous bounds (e.g. Pentina & Lampert, 2014; Amit & Meir, 2018), since it no longer constitutes a two-level optimization problem. Moreover, it renders the corresponding meta-learner agnostic to the choice variational inference method that is used to approximate the Gibbs/Bayes posterior $Q^*(S, P)$ at meta-test time.

Corollary 1. *When choosing the Gibbs posterior $Q^*(S_i, P) := P(\theta) \exp(-\sqrt{\tilde{m}} \hat{\mathcal{L}}(S_i, \theta))/Z(S_i, P)$ as a base learner, under the same assumptions as in Theorem 2, it holds with probability $1 - \delta$ that*

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq -\frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \mathbb{E}_{P \sim \mathcal{Q}} [\ln Z(S_i, P)] + \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q}||\mathcal{P}) + C(\delta, n, \tilde{m}) \quad (5)$$

wherein $Z(S_i, P) = \mathbb{E}_{\theta \sim P} \left[\exp(-\sqrt{m}\hat{\mathcal{L}}(S_i, \theta)) \right]$.

A natural way to obtain a PAC-Bayesian meta-learning algorithm could be to minimize (5) w.r.t. $\mathcal{Q}$. Though, in general, this is a hard problem since it would require a minimization over $\mathcal{M}(\mathcal{M}(\mathcal{H}))$, the space of all probability measures over priors. By employing Lemma 1 on the PAC-Bayes bound in (5), we are able to derive such minimizing distribution $\mathcal{Q}^*$, i.e. the PACOH, in closed form.

Proposition 1. *(PAC-Optimal Hyper-Posterior) Given a hyper-prior $\mathcal{P}$ and data sets $S_1, ..., S_n$, the hyper-posterior $\mathcal{Q}$ that minimizes the PAC-Bayesian meta-learning bound in (5) is given by*

$$\mathcal{Q}^*(P) = \frac{\mathcal{P}(P) \exp \left(\frac{1}{\sqrt{n\tilde{m}}+1} \sum_{i=1}^{n} \ln Z(S_i, P) \right)}{Z^{II}(S_1, ..., S_n, \mathcal{P})} \quad (6)$$

with the partition function defined as $Z^{II} = \mathbb{E}_{P \sim \mathcal{P}} \left[\exp \left(\frac{1}{\sqrt{n\tilde{m}}+1} \sum_{i=1}^{n} \ln Z(S_i, P) \right) \right]$.

We refer to $\mathcal{Q}^*(P)$ as *PAC-optimal* since, among all meta-learners, it gives us the best possible PAC-Bayesian guarantees in the sense of Theorem 2.

5 PACOH-NN: A SCALABLE ALGORITHM FOR LEARNING BNN PRIORS

In this section, we discuss how to translate the PACOH (Proposition 1) into a practical algorithm for meta-learning BNN priors. To this end, we first specify various components of the generic meta-learning setup presented in Section 4 and then discuss how to obtain a tractable approximation of $\mathcal{Q}^*$.

First, we define a family of priors $\{P_\phi : \phi \in \Phi\}$ over the NN parameters θ. For computational convenience, we employ Gaussian priors with diagonal covariance matrix, i.e. $P_\phi = \mathcal{N}(\mu_P, \text{diag}(\sigma_P^2))$ with $\phi := (\mu_P, \log \sigma_P)$. Note that we represent σ_P in the log-space to avoid additional positivity constraints. In fact, any parametric distribution such as normalizing flows (Rezende & Mohamed, 2015) that allows for re-parametrized sampling and has a tractable log-density could be used. As typical in the Bayesian framework, our loss function is the negative log-likelihood, i.e. $l(\theta, z) = -\ln p(y|x, \theta)$ for which we assume an additive Gaussian noise model $p(y|x, \theta) = \mathcal{N}(y; h_\theta(x), \sigma_y^2)$ in regression and a categorigal softmax distribution in case of classification. Moreover, we use a zero-centered, spherical Gaussian $\mathcal{P} := \mathcal{N}(0, \sigma_\mathcal{P}^2 I)$ as a hyper-prior over the parameters ϕ that specify the prior. In our setup, the hyper-prior acts a form of meta-level regularization that penalizes complex priors.

Given the hyper-prior and (level-I) log-partition function $\ln Z(S_i, P)$, we can compute the PACOH $\mathcal{Q}^*$ up to the normalization constant Z^{II}. Such a setup lends itself to approximate inference methods (Blei et al., 2016). In particular, we employ Stein Variational Gradient Descent (SVGD) (Liu & Wang, 2016) which approximates $\mathcal{Q}^*$ as a set of particles $\hat{\mathcal{Q}} = \{\phi_1, ..., \phi_K\}$. Initially, the particles $\phi_K \sim \mathcal{P}$ (i.e. the priors' parameters) are sampled randomly. Subsequently, the method iteratively transports the set of particles to match $\mathcal{Q}^*$, by applying a form of functional gradient descent that minimizes $D_{KL}(\hat{\mathcal{Q}}|\mathcal{Q}^*)$ in the reproducing kernel Hilbert space induced by a kernel function $k(\cdot, \cdot)$. In each iteration, the particles are updated by $\phi_k \leftarrow \phi_k + \eta \psi^*(\phi_k)$ with

$$\psi^*(\phi) = \frac{1}{K} \sum_{k'=1}^{K} \left[k(\phi_{k'}, \phi) \nabla_{\phi_{k'}} \ln \mathcal{Q}^*(\phi_{k'}) + \nabla_{\phi_{k'}} k(\phi_{k'}, \phi) \right] \quad (7)$$

where η is the step size and $\nabla_{\phi_k} \ln \mathcal{Q}^*(\phi_k) = \nabla_{\phi_k} \ln \mathcal{P}(\phi_k) + \frac{1}{\sqrt{n\tilde{m}}+1} \sum_{i=1}^{n} \nabla_{\phi_k} \ln Z(S_i, P_{\phi_k})$ the score of $\mathcal{Q}^*$. The last remaining issue towards a viable meta-learning algorithm is the intractable generalized marginal likelihood in $\ln Z(S_i, P_\phi) = \ln \mathbb{E}_{\theta \sim P_\phi} e^{-\sqrt{m}\hat{\mathcal{L}}(\theta, S)}$. We compute numerically stable Monte Carlo estimates of $\nabla_\phi \ln Z(S_i, P_{\phi_k})$ by using the LogSumExp together with the re-parametrization trick (Kingma & Welling, 2014). In particular, we draw L samples $\theta_l := f(\phi, \epsilon_l) = \mu_P + \sigma_P \odot \epsilon_l$, $\epsilon_l j \sim N(0, I)$ and compute the forward pass as follows:

$$\ln \tilde{Z}(S_i, P_\phi) := \ln \frac{1}{L} \sum_{l=1}^{L} e^{-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S_i)} = \text{LSE}_{l=1}^{L} \left(-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S_i) \right) - \ln L, \quad \theta_l \sim P_\phi \quad (8)$$

The corresponding gradients follow as softmax-weighted average of score gradients:

(a) BNN with isotropic, zero-centered Gaussian prior   (b) BNN with meta-learned *PACOH-NN* prior

Figure 1: BNN posterior predictions with (a) standard Gaussian prior vs. (b) meta-learned prior. Meta-learning with *PACOH-NN-SVGD* was conducted on the *Sinusoids* environment.

$$\nabla_\phi \ln \tilde{Z}(S_i, P_\phi) = -\sqrt{m} \sum_{l=1}^{L} \underbrace{\frac{e^{-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S_i)}}{\sum_{l=1}^{L} e^{-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S_i)}}}_{\text{softmax}} \underbrace{\nabla_\phi f(\phi, \epsilon_l)^\top}_{\text{Jacobian}} \underbrace{\nabla_{\theta_l} \hat{\mathcal{L}}(\theta_l, S_i)}_{\text{score}} \tag{9}$$

Note that $\ln \tilde{Z}(S_i, P_\phi)$ is not an unbiased estimate of $\ln Z(S_i, P_\phi)$. However, in expectation, the optimization procedure that uses the Monte Carlo estimate $\ln \tilde{Z}(S_i, P_\phi)$ still corresponds to minimization of a valid upper bound on the transfer error (see Appendix B). Algorithm 1 in Appendix B summarizes the proposed meta-learning method which we henceforth refer to as *PACOH-NN*.

6 EXPERIMENTS

We empirically evaluate the method introduced in Section 5, in particular, two variants of the algorithm: *PACOH-NN-SVGD* with $K = 5$ priors as particles and the edge case $K = 1$ which coincides with a maximum-a-posteriori (MAP) approximation of $\mathcal{Q}^*$, thus referred to as *PACOH-NN-MAP*. In order to evaluate the quality of the meta-learned prior, i.e. *meta-testing*, we need to do approximate the BNN posterior $Q^*(S, P)$ for which we use SVGD with 5 particles, too.

Comparing it to various NN-based meta-learning approaches on various regression and classification environments, we demonstrate that *PACOH-NN* (i) outperforms previous meta-learning algorithms in terms of predictive accuracy, (ii) improves the quality of uncertainty estimates and (iii) is much more scalable than previous PAC-Bayesian meta-learners. Finally, we showcase how meta-learned *PACOH-NN* priors can be harnessed in a real-world bandit task concerning peptide-based vaccine development.

6.1 META-LEARNING BNN PRIORS FOR REGRESSION AND CLASSIFICATION

Figure 1 illustrates *BNN* predictions on a sinusoidal regression task with a standard Gaussian prior as well as a *PACOH-NN* prior meta-learned on sinusoidal functions of varying amplitude, phase and slope. In Figure 1a we can see that the standard Gaussian prior provides poor inductive bias, not only leading to bad mean predictions away from the training points but also to grossly wrong confidence intervals (blue shaded areas). In contrast, the meta-learned *PACOH-NN* prior encodes useful inductive bias towards sinusoidal function shapes, leading to good predictions and uncertainty estimates, even in face of minimal training data (i.e. 1 training point).

Meta-learning benchmark. In the following, we present a comprehensive benchmark study. First, we use a *BNN* with a zero-centered, spherical Gaussian prior and SVGD posterior inference (Liu & Wang, 2016) as a baseline. Second, we compare our proposed approach against various popular meta-learning algorithms, including neural processes (*NPs*) (Garnelo et al., 2018), model-agnostic meta-learning (*MAML*) (Finn et al., 2017), its first-order version (*FOMAML*) (Nichol et al., 2018), and two variants of the PAC-Bayesian approach by Amit & Meir (2018) (*MLAP*). In that, *MLAP* is the most similar to our approach as it also minimizes PAC-Bayesian bounds of the transfer error. However, unlike *PACOH-NN*, it relies on nested optimization of the task posteriors Q_i and the hyper-posterior $\mathcal{Q}$.

Regression environments. In our experiments, we consider one synthetic and four real-world meta-learning environments for *regression*. As a synthetic environment we follow Rothfuss et al. (2020), employing a 2-dimensional mixture of *Cauchy* distributions plus random GP functions. As real-world environments, we use datasets corresponding to different calibration sessions of the Swiss Free Electron Laser (*SwissFEL*) (Milne et al., 2017; Kirschner et al., 2019b) as well as data from the *PhysioNet* 2012 challenge, which consists of time series of electronic health measurements from intensive care patients (Silva et al., 2012), in particular the Glasgow Coma Scale (*GCS*) and the hematocrit value (*HCT*). In here, the different tasks correspond to different patients. Moreover, we employ the Intel Berkeley Research lab temperature sensor dataset (*Berkeley-Sensor*) (Madden, 2004) where the tasks require auto-regressive prediction of temperatures measurements corresponding to sensors installed in different locations of the building. Further details can be found in Appendix C.1.

	Cauchy	SwissFel	Physionet-GCS	Physionet-HCT	Berkeley-Sensor
BNN (Liu & Wang, 2016)	0.327 ± 0.008	0.529 ± 0.022	2.664 ± 0.274	3.938 ± 0.869	0.109 ± 0.004
PACOH-NN-SVGD (ours)	$\mathbf{0.195 \pm 0.001}$	$\mathbf{0.372 \pm 0.002}$	$\mathbf{1.561 \pm 0.061}$	$\mathbf{2.405 \pm 0.017}$	$\mathbf{0.043 \pm 0.001}$
PACOH-NN-MAP (ours)	0.202 ± 0.003	$\mathbf{0.375 \pm 0.004}$	$\mathbf{1.564 \pm 0.200}$	2.480 ± 0.042	0.047 ± 0.001
MLAP-M (Amit & Meir, 2018)	0.219 ± 0.002	0.492 ± 0.009	2.232 ± 0.261	2.541 ± 0.140	0.052 ± 0.003
MLAP-S (Amit & Meir, 2018)	0.219 ± 0.004	0.486 ± 0.026	2.009 ± 0.248	2.470 ± 0.039	0.050 ± 0.005
FOMAML (Nichol et al., 2018)	0.260 ± 0.007	0.897 ± 0.071	2.545 ± 0.615	$\mathbf{2.408 \pm 0.064}$	0.059 ± 0.005
MAML (Finn et al., 2017)	0.219 ± 0.004	0.730 ± 0.057	1.895 ± 0.141	2.413 ± 0.113	$\mathbf{0.045 \pm 0.003}$
NPs (Garnelo et al., 2018)	0.224 ± 0.008	0.471 ± 0.053	2.056 ± 0.209	2.594 ± 0.107	0.079 ± 0.007

Table 1: Comparison of standard and meta-learning algorithms in terms of test RMSE across 5 meta-learning environments for regression. The mean and the standard deviation are reported.

	Cauchy	SwissFel	Physionet-GCS	Physionet-HCT	Berkeley-Sensor
BNN (Liu & Wang, 2016)	0.055 ± 0.006	0.085 ± 0.008	$\mathbf{0.277 \pm 0.013}$	0.307 ± 0.009	0.179 ± 0.002
PACOH-NN-SVGD (ours)	$\mathbf{0.046 \pm 0.001}$	$\mathbf{0.027 \pm 0.003}$	$\mathbf{0.267 \pm 0.005}$	$\mathbf{0.302 \pm 0.003}$	$\mathbf{0.067 \pm 0.005}$
PACOH-NN-MAP (ours)	0.051 ± 0.002	0.031 ± 0.003	0.268 ± 0.015	0.306 ± 0.003	0.063 ± 0.016
MLAP-M (Amit & Meir, 2018)	0.088 ± 0.004	0.104 ± 0.015	0.339 ± 0.012	$\mathbf{0.297 \pm 0.007}$	0.077 ± 0.010
MLAP-S (Amit & Meir, 2018)	0.086 ± 0.015	0.090 ± 0.021	0.343 ± 0.017	0.344 ± 0.016	0.108 ± 0.024
NPs (Garnelo et al., 2018)	0.057 ± 0.009	0.131 ± 0.056	0.299 ± 0.012	0.319 ± 0.004	0.210 ± 0.007

Table 2: Comparison of standard and meta-learning algorithms in terms of test calibration error (cf. C.3.1) across 5 meta-learning environments for regression.

Table 1 reports the results of our benchmark study in terms of the root mean squared error (RMSE) on unseen test tasks. *PACOH-NN* consistently outperforms the other meta-learning approaches and the standard BNN, demonstrating that the introduced meta-learning framework is not only sound, but also endows us with an algorithm that works well in practice.

Further, we hypothesize that by acquiring the prior in a principled data-driven manner (e.g., with *PACOH-NN*), we can improve the quality of the BNN's uncertainty estimates. To investigate the effect of meta-learned priors on the uncertainty estimates of the BNN, we compute the probabilistic predictors' calibration error, reported in Table 2. The *calibration error* measures the discrepancy between predicted confidence regions and actual frequencies of test data in the respective areas (Kuleshov et al., 2018). Note that, since *MAML* only produces point predictions, the concept of calibration does not apply to it. First, we observe that meta-learning priors with *PACOH-NN* consistently improves the standard BNN's uncertainty estimates. For meta-learning environments where the task similarity is high, i.e. *SwissFel* and *Berkeley-Sensor*, the improvement is substantial. Surprisingly, while improving upon the standard BNN in terms of the RMSE, we find that *NPs* consistently yields worse-calibrated predictive distributions than the BNN without meta-learning. This may be due to meta-level overfitting as NPs lack any form of meta-level regularization (cf. Qin et al., 2018; Rothfuss et al., 2020).

Classification environments. We conduct experiments with the multi-task *classification* environment *Omniglot* (Lake et al., 2015), consisting of handwritten letters across 50 alphabets. Unlike previous work (e.g. Finn et al., 2017) we do not perform data-augmentation and do not re-combine letters of different alphabets, preserving the data's original structure. In particular, one task corresponds to 5-way classification of letters within an alphabet. This leaves us which much fewer tasks (i.e. 30 train and 20 test tasks), thus, making environment more challenging and more interesting for uncertainty quantification. This also allows us to include *MLAP* in the experiment which hardly scales to more than 50 tasks.

In Table 3 we report both the accuracy and calibration error for 2-shot and 5-shot classification on withheld test tasks. Again, *PACOH-NN* yields the most accurate classification results and the lowest calibration error. Note that *MAML* fails to improve upon the standard BNN, i.e. demonstrating negative transfer. This is consistent with previous work (Qin et al., 2018; Rothfuss et al., 2020) raising concerns about overfitting to the meta-training tasks and observing that *MAML* requires a large number of tasks to generalize well. In contrast, by it's very construction on meta-generalization bounds, *PACOH-NN* is able to achieve positive transfer even when the meta-training tasks are diverse and small in number.

Figure 2: Scalability comparison of *PACOH-NN* and MLAP-S in memory footprint and compute time, as the number of meta-training task grows.

Scalability. Unlike the *MLAP* (Amit & Meir, 2018), *PACOH-NN* does not need to maintain posteriors Q_i for the meta-training tasks. To estimate the score of $\mathcal{Q}^*$ in (7), we can even use mini-batching on the task level. As a result, *PACOH-NN* is computationally much faster and more salable than previous PAC-Bayesian meta-learners. Figure 2 showcases this computational advantage during meta-training

	Accuracy		Calibration error	
	Omniglot 2-shot	Omniglot 5-shot	Omniglot 2-shot	Omniglot 5-shot
BNN (Liu & Wang, 2016)	0.6709 ± 0.006	0.795 ± 0.006	0.173 ± 0.009	0.135 ± 0.009
PACOH-NN-SVGD (ours)	0.733 ± 0.009	$\mathbf{0.885 \pm 0.090}$	$\mathbf{0.094 \pm 0.004}$	0.091 ± 0.010
PACOH-NN-MAP (ours)	$\mathbf{0.735 \pm 0.010}$	0.866 ± 0.005	0.099 ± 0.009	$\mathbf{0.075 \pm 0.006}$
MLAP-M (Amit & Meir, 2018)	0.635 ± 0.015	0.804 ± 0.0168	0.108 ± 0.008	0.1185 ± 0.0193
MLAP-S (Amit & Meir, 2018)	0.615 ± 0.037	0.700 ± 0.0135	0.129 ± 0.018	0.108 ± 0.010
FO-MAML (Nichol et al., 2018)	0.429 ± 0.047	0.590 ± 0.010	N/A	N/A
MAML (Finn et al., 2017)	0.571 ± 0.018	0.626 ± 0.011	N/A	N/A

Table 3: Comparison of meta-learning algorithms in terms of test accuracy and calibration error on the *Omniglot* environment with 2-shot and 5-shot 5-way-classification tasks.

with *PACOH-NN-MAP* and *MLAP-S* in the *Sinusoids* environment with varying number of tasks, reporting the maximum memory requirements, as well as the training time. While *MLAP's* memory consumption and compute time grows linearly and becomes prohibitively large even for less than 100 tasks, *PACOH-NN* maintains a nearly constant memory and compute load as the number of tasks grow.

6.2 META-LEARNING FOR BANDITS - VACCINE DEVELOPMENT

We showcase how a relevant real-world application such as vaccine design can benefit from our proposed method. In particular, the goal is to discover peptide sequences which bind to major histocompatibility complex class-I molecules (MHC-I). MHC-I molecules present fragments of proteins from within a cell to T-cells, allowing the immune system to distinguish between healthy and infected cells. Following the bandit setup of Krause & Ong (2011), each task corresponds to searching for maximally binding peptides, a vital step in the design of peptide-based vaccines. The tasks differ in their targeted MHC-I allele, i.e., correspond to different genetic variants of the MHC-I protein. We use data from Widmer et al. (2010) which con-

Figure 3: MHC-I peptide design task: Regret for different priors and bandit algorithms. A meta-learned *PACOH-NN* prior substantially improves the regret, compared to a standard BNN/GP prior.

tains the binding affinities (IC_{50} values) of many peptide candidates to the MHC-I alleles. The peptide candidates are encoded as 45-dimensional feature vector and the binding affinities were standardized.

We use 5 alleles (tasks) to meta-learn a BNN prior with *PACOH-NN* and leave the most genetically dissimilar allele (A-6901) for our bandit task. In each iteration, the experimenter (i.e. bandit algorithm) chooses to test one peptide among the pool of more than 800 candidates and receives its binding affinity as a reward feedback. In particular, we employ UCB (Lattimore & Szepesvari, 2020) and Thompson-Sampling (TS) (Thompson, 1933) as bandit algorithms, comparing the BNN-based bandits with meta-learned prior (*PACOH-UCB/TS*) against a zero-centered Gaussian BNN prior (*BNN-UCB/TS*) and a Gaussian process (*GP-UCB*) (Srinivas et al., 2009).

Figure 3 reports the respective average regret and maximum regret over 50 iterations. Unlike the bandit algorithms with standard BNN/GP prior, *PACOH-UCB/TS* reaches near optimal regret within less than 10 iterations and after 50 iterations still maintains a significant performance advantage. This highlights the importance of *transfer (learning)* for solving real-world problems and demonstrates the effectiveness of *PACOH-NN* to this end. While the majority of meta-learning methods rely on a large number of meta-training tasks (Qin et al., 2018), *PACOH-NN* allows us to achieve promising positive transfer, even in complex real-world scenarios with only a handful (here 5) tasks.

7 CONCLUSION

In this paper, we present a novel, scalable algorithm for meta-learning BNN priors based on PAC-Bayesian theory. In that, we overcome previous issues of nested optimization by deriving the closed-form solution of the PAC-Bayesian meta-learning problem (i.e. the *PACOH*). To make approximations of the *PACOH* tractable for BNNs, we introduce a numerically stable score estimator for the generalized marginal log-likelihood. Our experiments are limited to diagonal Gaussian priors and SVGD as approximate inference method. Thus, future work may explore more recent approaches in variational inference such as functional SVGD (Wang et al., 2019) or consider more expressive priors such as normalizing flows (Rezende & Mohamed, 2015). A key aspect of our approach is its principled treatment of uncertainty, making it particularly amenable to interactive machine learning systems. Thus, we consider it promising to further explore the use of meta-learned *PACOH-NN* priors for Bayesian optimization and reinforcement learning.

REFERENCES

Pierre Alquier, James Ridgway, and Nicolas Chopin. On the properties of variational approximations of Gibbs posteriors. *Journal of Machine Learning Research*, 17(236):1–41, 2016.

Ron Amit and Ron Meir. Meta-learning by adjusting priors based on extended pac-bayes theory. In *ICML*, 2018.

Marcin Andrychowicz, Misha Denil, Sergio Gmez Colmenarejo, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. *arXix preprint arXix:1606.04474*, 2016.

Jonathan Baxter. A model of inductive bias learning. *Journal of artificial intelligence research*, 12: 149–198, 2000.

James Bergstra, Daniel Yamins, and David Cox. Making a science of model search: Hyperparameter optimization in hundreds of dimensions for vision architectures. In Sanjoy Dasgupta and David McAllester (eds.), *ICML*, volume 28 of *Proceedings of Machine Learning Research*, pp. 115–123, Atlanta, Georgia, USA, 17–19 Jun 2013. PMLR.

David M. Blei, Alp Kucukelbir, and Jon D. McAuliffe. Variational Inference: A Review for Statisticians. jan 2016. doi: 10.1080/01621459.2017.1285773.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. 2015.

Stephane Boucheron, Gabor Lugosi, and Pascal Massart. *Concentration inequalities : a nonasymptotic theory of independence*. Oxford University Press, 2013. ISBN 9780199535255.

Olivier Catoni. Pac-bayesian supervised classification: the thermodynamics of statistical learning. *arXiv preprint arXiv:0712.0248*, 2007.

Yutian Chen, Matthew W Hoffman, Sergio Gmez Colmenarejo, Misha Denil, Timothy P Lillicrap, Matt Botvinick, and Nando De Freitas. Learning to Learn without Gradient Descent by Gradient Descent. In *ICML*, 2017.

Gintare Karolina Dziugaite and Daniel M Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. In *UAI*, 2016.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1126–1135. JMLR. org, 2017.

Chelsea Finn, Kelvin Xu, and Sergey Levine. Probabilistic model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*, pp. 9516–9527, 2018.

Vincent Fortuin and Gunnar Rätsch. Deep mean functions for meta-learning in gaussian processes. *arXiv preprint arXiv:1901.08098*, 2019.

Vincent Fortuin, Gunnar Rätsch, and Stephan Mandt. Multivariate time series imputation with variational autoencoders. *arXiv preprint arXiv:1907.04155*, 2019.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *ICML*, pp. 10501059, 2016.

Marta Garnelo, Jonathan Schwarz, Dan Rosenbaum, Fabio Viola, Danilo J Rezende, SM Eslami, and Yee Whye Teh. Neural processes. *arXiv preprint arXiv:1807.01622*, 2018.

Pascal Germain, Francis Bach, Alexandre Lacoste, and Simon Lacoste-Julien. Pac-bayesian theory meets bayesian inference. In *Advances in Neural Information Processing Systems*, pp. 1884–1892, 2016.

Soumya Ghosh and Finale Doshi-Velez. Model selection in bayesian neural networks via horseshoe priors. *arXiv preprint arXiv:1705.10388*, 2017.

Alex Graves. Practical variational inference for neural networks. In *NeurIPS*, pp. 2348–2356, 2011.

Benjamin Guedj. A primer on pac-bayesian learning. *arXiv preprint arXiv:1901.05353*, 2019.

José Miguel Hernández-Lobato and Ryan P. Adams. Probabilistic backpropagation for scalable learning of bayesian neural networks. In *ICML*, pp. 18611869, 2015.

Sepp Hochreiter, A. Steven Younger, and Peter R. Conwell. Learning To Learn Using Gradient Descent. In *ICANN*, pp. 87–94, 2001.

Chin-Wei Huang, Ahmed Touati, Pascal Vincent, Gintare Karolina Dziugaite, Alexandre Lacoste, and Aaron Courville. Stochastic neural network with kronecker flow. 2020.

Taesup Kim, Jaesik Yoon, Ousmane Dia, Sungwoong Kim, Yoshua Bengio, and Sungjin Ahn. Bayesian model-agnostic meta-learning. In *NeurIPS*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *ICLR*, 2014.

Johannes Kirschner, Mojmir Mutný, Nicole Hiller, Rasmus Ischebeck, and Andreas Krause. Adaptive and safe bayesian optimization in high dimensions via one-dimensional subspaces. In *Proc. International Conference for Machine Learning (ICML)*, June 2019a.

Johannes Kirschner, Manuel Nonnenmacher, Mojmir Mutný, Nicole Hiller, Andreas Adelmann, Rasmus Ischebeck, and Andreas Krause. Bayesian optimization for fast and safe parameter tuning of swissfel. In *Proc. International Free-Electron Laser Conference (FEL2019)*, June 2019b.

Andreas Krause and Cheng S Ong. Contextual gaussian process bandit optimization. In *NIPS*, pp. 2447–2455, 2011.

Volodymyr Kuleshov, Nathan Fenner, and Stefano Ermon. Accurate uncertainties for deep learning using calibrated regression. In *ICML*, 2018.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

Tor Lattimore and Csaba Szepesvari. *Bandit Algorithms*. Cambridge University Press, 2020.

Guy Lever, François Laviolette, and John Shawe-Taylor. Tighter PAC-Bayes bounds through distribution-dependent priors. *Theoretical Computer Science*, 473:4–28, feb 2013. ISSN 0304-3975. doi: 10.1016/J.TCS.2012.10.013.

Qiang Liu and Dilin Wang. Stein Variational Gradient Descent: A General Purpose Bayesian Inference Algorithm. aug 2016. URL http://arxiv.org/abs/1608.04471.

Christos Louizos and Max Welling. Structured and efficient variational deep learning with matrix gaussian posteriors. In *ICML*, pp. 1708–1716, 2016.

Samuel Madden. Intel lab data. http://db.csail.mit.edu/labdata/labdata.html, 2004. Accessed: Sep 8, 2020.

David A McAllester. Some pac-bayesian theorems. *Machine Learning*, 37(3):355–363, 1999.

Christopher J Milne, Thomas Schietinger, Masamitsu Aiba, Arturo Alarcon, Jürgen Alex, Alexander Anghel, Vladimir Arsov, Carl Beard, Paul Beaud, Simona Bettoni, et al. Swissfel: the swiss x-ray free electron laser. *Applied Sciences*, 7(7):720, 2017.

Aaron Mishkin, Frederik Kunstner, Didrik Nielsen, Mark Schmidt, and Mohammad Emtiyaz Khan. Slang: Fast structured covariance approximations for bayesian deep learning with natural gradient. In *NeurIPS*, pp. 6245–6255, 2018.

Radford M. Neal. *Bayesian Learning for Neural Networks*. Springer-Verlag, Berlin, Heidelberg, 1996. ISBN 0387947248.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms, 2018.

Emilio Parrado-Hernandez, Amiran Ambroladze, John Shawe-Taylor, and Shiliang Sun. Pac-bayes bounds with data dependent priors. *JMLR*, 13(112):3507–3531, 2012.

Tim Pearce, Russell Tsuchida, Mohamed Zaki, Alexandra Brintrup, and Andy Neely. Expressive priors in bayesian neural networks: Kernel combinations and periodic functions. In *UAI*, pp. 134–144, 2020.

Anastasia Pentina and Christoph Lampert. A pac-bayesian bound for lifelong learning. In *International Conference on Machine Learning*, pp. 991–999, 2014.

Yunxiao Qin, Weiguo Zhang, Chenxu Zhao, Zezheng Wang, Hailin Shi, Guojun Qi, Jingping Shi, and Zhen Lei. Rethink and redesign meta learning. *arXiv preprint arXiv:1812.04955*, 2018.

Danilo Jimenez Rezende and Shakir Mohamed. Variational inference with normalizing flows. *ICML*, 2015.

Carlos Riquelme, George Tucker, and Jasper Snoek. Deep bayesian bandits showdown: An empirical comparison of bayesian deep networks for thompson sampling. In *ICLR*, 2018.

Jonas Rothfuss, Dennis Lee, Ignasi Clavera, Tamim Asfour, and Pieter Abbeel. Promp: Proximal meta-policy search. In *ICLR*, 2019.

Jonas Rothfuss, Vincent Fortuin, and Andreas Krause. Pacoh: Bayes-optimal meta-learning with pac-guarantees. *arXiv preprint arXiv:2002.05551*, 2020.

Juergen Schmidhuber. *Evolutionary principles in self-referential learning. On learning how to learn: The meta-meta-... hook*. PhD thesis, Technische Universitaet Munchen, 1987.

Ikaro Silva, George Moody, Daniel J Scott, Leo A Celi, and Roger G Mark. Predicting in-hospital mortality of icu patients: The physionet/computing in cardiology challenge 2012. In *2012 Computing in Cardiology*, pp. 245–248. IEEE, 2012.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *NIPS*, pp. 4077–4087, 2017.

Niranjan Srinivas, Andreas Krause, Sham M Kakade, and Matthias Seeger. Gaussian process optimization in the bandit setting: No regret and experimental design. In *ICML*, 2009.

Nicholas Syring and Ryan Martin. Calibrating general posterior credible regions. *Biometrika*, 106(2): 479–486, 12 2018. ISSN 0006-3444. doi: 10.1093/biomet/asy054. URL https://doi.org/10.1093/biomet/asy054.

William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

Sebastian Thrun and Lorien Pratt (eds.). *Learning to Learn*. Kluwer Academic Publishers, USA, 1998. ISBN 0792380479.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *NIPS*, pp. 3630–3638, 2016.

Mariia Vladimirova, Jakob Verbeek, Pablo Mesejo, and Julyan Arbel. Understanding priors in Bayesian neural networks at the unit level. In *ICML*, pp. 6458–6467, 2019.

Ziyu Wang, Tongzheng Ren, Jun Zhu, and Bo Zhang. Function space particle optimization for bayesian neural networks. *arXiv preprint arXiv:1902.09754*, 2019.

Florian Wenzel, Kevin Roth, Bastiaan S Veeling, Jakub Swikatkowski, Linh Tran, Stephan Mandt, Jasper Snoek, Tim Salimans, Rodolphe Jenatton, and Sebastian Nowozin. How good is the bayes posterior in deep neural networks really? *arXiv preprint arXiv:2002.02405*, 2020.

Christian Widmer, Nora C Toussaint, Yasemin Altun, and Gunnar Rätsch. Inferring latent task structure for multitask learning by multiple kernel learning. *BMC bioinformatics*, 11(S8):S5, 2010.

APPENDIX

A PROOFS AND DERIVATIONS

A.1 PROOF OF THEOREM 2

Lemma 2. *(Change of measure inequality) Let f be a random variable taking values in a set A and let $X_1, ..., X_l$ be independent random variables, with $X_k \in A$ with distribution μ_k. For functions $g_k : A \times A \to \mathbb{R}, k = 1, ..., l$, let $\xi_k(f) = \mathbb{E}_{X_k \sim \mu_k}[g_k(f, X_k)]$ denote the expectation of g_k under μ_k for any fixed $f \in A$. Then for any fixed distribution π on A and any $\lambda > 0$, we have that*

$$\mathbb{E}_{f \sim \rho}\left[\sum_{k=1}^{l} \xi_k(f) - g_k(f, X_k)\right] \leq \frac{1}{\lambda}\left(D_{KL}(\rho||\pi) + \ln \mathbb{E}_{f \sim \pi}\left[e^{\lambda\left(\sum_{k=1}^{l} \xi_k(f) - g_k(f, X_k)\right)}\right]\right). \tag{10}$$

Proof of Theorem 2 To proof the Theorem, we need to bound the difference between *transfer error* $\mathcal{L}(\mathcal{Q}, \mathcal{T})$ and the *empirical multi-task error* $\hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n)$. To this end, we introduce an intermediate quantity, the *expected multi-task error*:

$$\tilde{\mathcal{L}}(\mathcal{Q}, \mathcal{D}_1, ..., \mathcal{D}_n) = \mathbb{E}_{P \sim \mathcal{Q}}\left[\frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_{S \sim D_i^{m_i}}[\mathcal{L}(Q(S, P), \mathcal{D}_i)]\right] \tag{11}$$

In the following we invoke Lemma 2 twice. First, in step 1, we bound the difference between $\tilde{\mathcal{L}}(\mathcal{Q}, \mathcal{D}_1, ..., \mathcal{D}_n)$ and $\hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n)$, then, in step 2, the difference between $\mathcal{L}(\mathcal{Q}, \mathcal{T})$ and $\tilde{\mathcal{L}}(\mathcal{Q}, \mathcal{D}_1, ..., \mathcal{D}_n)$. Finally, in step 3, we use a union bound argument to combine both results.

Step 1 (Task specific generalization) First, we bound the generalization error of the observed tasks $\tau_i = (\mathcal{D}_i, m_i)$, $i = 1, ..., n$, when using a learning algorithm $Q : \mathcal{M} \times \mathcal{Z}^{m_i} \to \mathcal{M}$, which outputs a posterior distribution $Q_i = Q(S_i, P)$ over hypotheses θ, given a prior distribution P and a data set $S_i \sim \mathcal{D}_i^{m_i}$ of size m_i.

In particular, we apply Lemma 2 to the union of all training sets $S' = \bigcup_{i=1}^{n} S_i$ with $l = \sum_{i=1}^{n} m_i$. Hence, each X_k corresponds to one data point, i.e. $X_k = z_{ij}$ and $\mu_k = \mathcal{D}_i$. Further, we set $f = (P, h_1, ..., h_n)$ to be a tuple of one prior and n base hypotheses. This can be understood as a two-level hypothesis, wherein P constitutes a hypothesis of the meta-learning problem and h_i a hypothesis for solving the supervised task τ_i. Correspondingly, we take $\pi = (\mathcal{Q}, Q^n) = \mathcal{P} \cdot \prod_{i=1}^{n} P$ and $\rho = (\mathcal{Q}, Q^n) = \mathcal{Q} \cdot \prod_{i=1}^{n} Q_i$ as joint two-level distributions and $g_k(f, X_k) = \frac{1}{nm_i} l(h_i, z_{ij})$ as summand of the empirical multi-task error. We can now invoke Lemma 2 to obtain that (12) and (15)

$$\frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_{P \sim \mathcal{Q}}[\mathcal{L}(Q_i, D_i)] \leq \frac{1}{n}\sum_{i=1}^{n}\mathbb{E}_{P \sim \mathcal{Q}}[\mathcal{L}(Q_i, S_i)] + \frac{1}{\lambda}\left(D_{KL}[(\mathcal{Q}, Q^n)||(\mathcal{P}, P^n)]\right.$$
$$\left. + \ln \mathbb{E}_{P \sim \mathcal{P}}\mathbb{E}_{h \sim P}\left[e^{\frac{\lambda}{n}\sum_{i=1}^{n}(\mathcal{L}(h, \mathcal{D}_i) - \hat{\mathcal{L}}(h, S_i))}\right]\right) \tag{12}$$

Using the above definitions, the KL-divergence term can be re-written in the following way:

$$D_{KL}[(\mathcal{Q}, Q^n)||(\mathcal{P}, P^n)] = \mathbb{E}_{P \sim \mathcal{Q}}\left[\mathbb{E}_{h \sim Q_i}\left[\ln \frac{\mathcal{Q}(P)\prod_{i=1}^{n}\prod Q_i(h)}{\mathcal{P}(P)\prod_{i=1}^{n} P(h)}\right]\right] \tag{13}$$

$$= \mathbb{E}_{P \sim \mathcal{Q}}\left[\ln \frac{\mathcal{Q}(P)}{\mathcal{P}(P)}\right] + \sum_{i=1}^{n}\mathbb{E}_{P \sim \mathcal{Q}}\left[\mathbb{E}_{h \sim Q_i}\left[\ln \frac{Q_i(h)}{P(h)}\right]\right] \tag{14}$$

$$= D_{KL}(\mathcal{Q}||\mathcal{P}) + \sum_{i=1}^{n}\mathbb{E}_{P \sim \mathcal{Q}}[D_{KL}(Q_i||P)] \tag{15}$$

Using (12) and (15) we can bound the expected multi-task error as follows:

$$\tilde{\mathcal{L}}(\mathcal{Q}, \mathcal{D}_1, ..., \mathcal{D}_n) \leq \hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n) + \frac{1}{\lambda} D_{KL}(\mathcal{Q}||\mathcal{P}) + \frac{1}{\lambda} \sum_{i=1}^{n} \mathbb{E}_{P \sim \mathcal{Q}}\left[D_{KL}(Q_i||P) \right]$$

$$+ \underbrace{\frac{1}{\lambda} \ln \mathbb{E}_{P \sim \mathcal{P}} \mathbb{E}_{h \sim P} \left[e^{\frac{\lambda}{n} \sum_{i=1}^{n} (\mathcal{L}(h, \mathcal{D}_i) - \hat{\mathcal{L}}(h, S_i))} \right]}_{\Upsilon^{\mathrm{I}}(\lambda)} \tag{16}$$

Step 2 (Task environment generalization) Now, we apply Lemma 2 on the meta-level. For that, we treat each task as random variable and instantiate the components as $X_k = \tau_i$, $l = n$ and $\mu_k = \mathcal{T}$. Furthermore, we set $\rho = \mathcal{Q}$, $\pi = \mathcal{P}$, $f = P$ and $g_k(f, X_k) = \frac{1}{n}\mathcal{L}(Q_i, \mathcal{D}_i)$. This allows us to bound the transfer error as

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq \tilde{\mathcal{L}}(\mathcal{Q}, \mathcal{D}_1, ..., \mathcal{D}_n) + \frac{1}{\beta} D_{KL}(\rho||\pi) + \Upsilon^{\mathrm{II}}(\beta) \tag{17}$$

wherein $\Upsilon^{\mathrm{II}}(\beta) = \frac{1}{\beta} \ln \mathbb{E}_{P \sim \mathcal{P}} \left[e^{\frac{\beta}{n} \sum_{i=1}^{n} \mathbb{E}_{(D,S) \sim \mathcal{T}} [\mathcal{L}(Q(P,S), \mathcal{D})] - \mathcal{L}(Q(P,S_i), \mathcal{D}_i)} \right]$.

Combining (16) with (17), we obtain

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq \hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n) + \left(\frac{1}{\beta} + \frac{1}{\lambda} \right) D_{KL}(\mathcal{Q}||\mathcal{P})$$

$$+ \frac{1}{\lambda} \sum_{i=1}^{n} \mathbb{E}_{P \sim \mathcal{Q}} \left[D_{KL}(Q_i||P) \right] + \Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta) \tag{18}$$

Step 3 (Bounding the moment generating functions)

$$e^{(\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta))} = \mathbb{E}_{P \sim \mathcal{P}} \left[e^{\frac{\beta}{n} \sum_{i=1}^{n} \mathbb{E}_{(D,S) \sim \mathcal{T}} [\mathcal{L}(Q(P,S), \mathcal{D})] - \mathcal{L}(Q(P,S_i), \mathcal{D}_i)} \right]^{1/\beta} \cdot$$

$$\mathbb{E}_{P \sim \mathcal{P}} \mathbb{E}_{h \sim P} \left[e^{\frac{\lambda}{n} \sum_{i=1}^{n} (\mathcal{L}(h, \mathcal{D}_i) - \hat{\mathcal{L}}(h, S_i))} \right]^{1/\lambda}$$

$$= \mathbb{E}_{P \sim \mathcal{P}} \left[\prod_{i=1}^{n} e^{\left(\frac{\beta}{n} \mathbb{E}_{(D,S) \sim \mathcal{T}} [\mathcal{L}(Q(P,S), \mathcal{D})] \right) - \mathcal{L}(Q(P,S_i), \mathcal{D}_i)} \right]^{1/\beta} \cdot \tag{19}$$

$$\mathbb{E}_{P \sim \mathcal{P}} \mathbb{E}_{h \sim P} \left[\prod_{i}^{n} \prod_{i}^{m_i} e^{\frac{\lambda}{nm_i} (\mathcal{L}(h, \mathcal{D}_i) - l(h_i, z_{ij}))} \right]^{1/\lambda}$$

Case I: bounded loss

If the loss function $l(h_i, z_{ij})$ is bounded in $[a_k, b_k]$, we can apply Hoeffding's lemma to each factor in (19), obtaining:

$$e^{\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta)} \leq \mathbb{E}_{P \sim \mathcal{P}} \left[e^{\frac{\beta^2}{8n} (b_k - a_k)^2} \right]^{1/\beta} \cdot \mathbb{E}_{P \sim \mathcal{P}} \mathbb{E}_{h \sim P} \left[e^{\frac{\lambda^2}{8n\tilde{m}} (b_k - a_k)^2} \right]^{1/\lambda} \tag{20}$$

$$= e^{\left(\frac{\beta}{8n} + \frac{\lambda}{8n\tilde{m}} \right)(b_k - a_k)^2} \tag{21}$$

Next, we factor out $\sqrt{n}$ from λ and β, obtaining

$$e^{\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta)} = \left(e^{\Upsilon^{\mathrm{I}}(\lambda\sqrt{n}) + \Upsilon^{\mathrm{II}}(\beta\sqrt{n})} \right)^{\frac{1}{\sqrt{n}}} \tag{22}$$

Using

$$\mathbb{E}_{\mathcal{T}} \mathbb{E}_{\mathcal{D}_1} ... \mathbb{E}_{\mathcal{D}_n} \left[e^{\Upsilon^{\mathrm{I}}(\lambda\sqrt{n}) + \Upsilon^{\mathrm{II}}(\beta\sqrt{n})} \right] \leq e^{\left(\frac{\beta}{8\sqrt{n}} + \frac{\lambda}{8\sqrt{n}\tilde{m}} \right)(b_k - a_k)^2} \tag{23}$$

we can apply Markov's inequality w.r.t. the expectations over the task distribution $\mathcal{T}$ and data distributions $\mathcal{D}_i$ to obtain that

$$\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta) \leq \underbrace{\frac{\beta}{8n}(b_k - a_k)^2}_{\Psi^{\mathrm{I}}(\beta)} + \underbrace{\frac{\lambda}{8n\tilde{m}}(b_k - a_k)^2}_{\Psi^{\mathrm{II}}(\lambda)} - \frac{1}{\sqrt{n}} \ln \delta \tag{24}$$

with probability at least $1 - \delta$.

Case II: sub-gamma loss

First, we assume that, $\forall i = 1, ..., n$ the random variables $V_i^{\mathrm{I}} := \mathcal{L}(h, \mathcal{D}_i) - l(h_i, z_{i,j})$ are *sub-gamma* with variance factor s_{I}^2 and scale parameter c_{I} under the two-level prior $(\mathcal{P}, P)$ and the respective data distribution $\mathcal{D}_i$. That is, their moment generating function can be bounded by that of a Gamma distribution $\Gamma(s_{\mathrm{I}}^2, c_{\mathrm{I}})$:

$$\mathbb{E}_{z \sim \mathcal{D}_i} \mathbb{E}_{P \sim \mathcal{P}} \mathbb{E}_{h \sim P} \left[e^{\gamma(\mathcal{L}(h, \mathcal{D}_i) - l(h, z))} \right] \leq \exp \left(\frac{\gamma^2 s_{\mathrm{I}}^2}{2(1 - c_{\mathrm{I}} \gamma)} \right) \quad \forall \gamma \in (0, 1/c_{\mathrm{I}}) \tag{25}$$

Second, we assume that, the random variable $V^{\mathrm{II}} := \mathbb{E}_{(D,S) \sim \mathcal{T}} \left[\mathcal{L}(Q(P, S), \mathcal{D}) \right] - \mathcal{L}(Q(P, S_i), \mathcal{D}_i)$ is *sub-gamma* with variance factor s_{II}^2 and scale parameter c_{II} under the hyper-prior $\mathcal{P}$ and the task distribution $\mathcal{T}$. That is, its moment generating function can be bounded by that of a Gamma distribution $\Gamma(s_{\mathrm{II}}^2, c_{\mathrm{II}})$:

$$\mathbb{E}_{(D,S) \sim \mathcal{T}} \mathbb{E}_{P \sim \mathcal{P}} \left[e^{\gamma \, \mathbb{E}_{(D,S) \sim \mathcal{T}} [\mathcal{L}(Q(P,S), \mathcal{D})] - \mathcal{L}(Q(P,S), \mathcal{D})} \right] \leq \exp \left(\frac{\gamma^2 s_{\mathrm{II}}^2}{2(1 - c_{\mathrm{II}} \gamma)} \right) \quad \forall \gamma \in (0, 1/c_{\mathrm{II}}) \tag{26}$$

These two assumptions allow us to bound the expectation of (19) as follows:

$$\mathbb{E} \left[e^{\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta)} \right] \leq \exp \left(\frac{\lambda s_{\mathrm{I}}^2}{2n\tilde{m}(1 - c_{\mathrm{I}} \lambda/(n\tilde{m}))} \right) \cdot \exp \left(\frac{\beta s_{\mathrm{II}}^2}{2n(1 - c_{\mathrm{II}} \beta/n)} \right) \tag{27}$$

Next, we factor out $\sqrt{n}$ from λ and β, obtaining

$$e^{\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta)} = \left(e^{\Upsilon^{\mathrm{I}}(\lambda\sqrt{n}) + \Upsilon^{\mathrm{II}}(\beta\sqrt{n})} \right)^{\frac{1}{\sqrt{n}}} \tag{28}$$

Finally, by using Markov's inequality we obtain that

$$\Upsilon^{\mathrm{I}}(\lambda) + \Upsilon^{\mathrm{II}}(\beta) \leq \underbrace{\frac{\lambda s_{\mathrm{I}}^2}{2n\tilde{m}(1 - c_{\mathrm{I}} \lambda/(n\tilde{m}))}}_{\Psi^{\mathrm{I}}(\beta)} + \underbrace{\frac{\beta s_{\mathrm{II}}^2}{2n(1 - c_{\mathrm{II}} \beta/n)}}_{\Psi^{\mathrm{II}}(\lambda)} - \frac{1}{\sqrt{n}} \ln \delta \tag{29}$$

with probability at least $1 - \delta$.

To conclude the proof, we choose $\lambda = n\sqrt{\tilde{m}}$ and $\beta = \sqrt{n}$.

A.2 PROOF OF COROLLARY 1

Lemma 3. *(Catoni, 2007) Let A be a set, $g : A \to \mathbb{R}$ a function, and $\rho \in \mathcal{M}(A)$ and $\pi \in \mathcal{M}(A)$ probability densities over A. Then for any $\beta > 0$ and $\forall a \in A$,*

$$\rho^*(a) := \frac{\pi(a) e^{-\beta g(a)}}{Z} = \frac{\pi(a) e^{-\beta g(a)}}{\mathbb{E}_{a \sim \pi} \left[e^{-\beta g(a)} \right]} \tag{30}$$

is the minimizing probability density

$$\underset{\rho \in \mathcal{M}(A)}{\arg \min} \ \beta \mathbb{E}_{a \sim \rho} \left[g(a) \right] + D_{KL}(\rho || \pi) . \tag{31}$$

Proof of Corollary 1 When we choose the posterior Q as the optimal Gibbs posterior $Q_i^* := Q^*(S_i, P)$, it follows that

$$\hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n) + \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \mathbb{E}_{P \sim \mathcal{Q}} \left[D_{KL}(Q_i^* || P) \right] \tag{32}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \left(\mathbb{E}_{P \sim \mathcal{Q}} \mathbb{E}_{h \sim Q_i^*} \left[\hat{\mathcal{L}}(h, S_i) \right] + \frac{1}{\sqrt{\tilde{m}}} \left(\mathbb{E}_{P \sim \mathcal{Q}} \left[D_{KL}(Q_i^* || P) \right] \right) \right) \tag{33}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \left(\mathbb{E}_{P \sim \mathcal{Q}} \mathbb{E}_{h \sim Q_i^*} \left[\sqrt{\tilde{m}} \hat{\mathcal{L}}(h, S_i) + \ln \frac{Q_i^*(h)}{P(h)} \right] \right) \tag{34}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \left(\mathbb{E}_{P \sim \mathcal{Q}} \mathbb{E}_{h \sim Q_i^*} \left[\frac{1}{\sqrt{\tilde{m}}} \sum_{j=1}^{m} l(h, z_i) + \ln \frac{P(h)e^{-\frac{1}{\sqrt{\tilde{m}}} \sum_{j=1}^{m} l(h, z_i)}}{P(h)Z(S_i, P)} \right] \right) \tag{35}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \left(-\mathbb{E}_{P \sim \mathcal{Q}} \left[\ln Z(S_i, P) \right] \right) . \tag{36}$$

This allows us to write the inequality in (4) as

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq - \frac{1}{n} \sum_{i=1}^{n} \frac{1}{m_i} \mathbb{E}_{P \sim \mathcal{Q}} \left[\ln Z(S_i, P) \right] + \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q} || \mathcal{P}) + C(\delta, n, \tilde{m}) . \tag{37}$$

According to Lemma 3, the Gibbs posterior $Q^*(S_i, P)$ is the minimizer of (34), in particular $\forall P \in \mathcal{M}(\mathcal{H}), \forall i = 1, ..., n$:

$$Q^*(S_i, P) = \frac{P(h)e^{-\sqrt{\tilde{m}} \hat{\mathcal{L}}(h, S_i)}}{Z(S_i, P)} = \underset{Q \in \mathcal{M}(\mathcal{H})}{\arg \min} \mathbb{E}_{h \sim Q} \left[\hat{\mathcal{L}}(h, S_i) \right] + \frac{1}{\sqrt{\tilde{m}}} D_{KL}(Q || P) . \tag{38}$$

Hence, we can write

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq - \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \mathbb{E}_{P \sim \mathcal{Q}} \left[\ln Z(S_i, P) \right] + \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q} || \mathcal{P}) + C(\delta, n, \tilde{m}) \tag{39}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \mathbb{E}_{P \sim \mathcal{Q}} \left[\min_{Q \in \mathcal{M}(\mathcal{H})} \hat{\mathcal{L}}(Q, S_i) + \frac{1}{\sqrt{\tilde{m}}} D_{KL}(Q || P) \right] \tag{40}$$

$$+ \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) + C(\delta, n, \tilde{m}) \tag{41}$$

$$\leq \frac{1}{n} \sum_{i=1}^{n} \mathbb{E}_{P \sim \mathcal{Q}} \left[\hat{\mathcal{L}}(Q, S_i) + \frac{1}{\sqrt{\tilde{m}}} D_{KL}(Q || P) \right] \tag{42}$$

$$+ \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q} || \mathcal{P}) + C(\delta, n, \tilde{m}) \tag{43}$$

$$= \hat{\mathcal{L}}(\mathcal{Q}, S_1, ..., S_n) + \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q} || \mathcal{P}) \tag{44}$$

$$+ \frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \mathbb{E}_{P \sim \mathcal{Q}} \left[D_{KL}(Q_i || P) \right] + C(\delta, n, \tilde{m}) , \tag{45}$$

which proves that the bound for Gibbs-optimal base learners in (37) and (5) is tighter than the bound in Theorem 2 which holds uniformly for all $Q \in \mathcal{M}(\mathcal{H})$.

Figure S1: Overview of our meta-learning framework with environment $\mathcal{T}$, meta-task distributions $\mathcal{D}_i$, target task distribution $\mathcal{D}$, hyper-prior $\mathcal{P}$, hyper-posterior $\mathcal{Q}$, target prior P, target posterior Q, data sets S, and data points $z = (x, y)$.

A.3 PROOF OF PROPOSITION 1: PAC-OPTIMAL HYPER-POSTERIOR

An objective function corresponding to (5) reads as

$$J(\mathcal{Q}) = -\mathbb{E}_{\mathcal{Q}} \left[\frac{1}{\sqrt{n\tilde{m}} + 1} \sum_{i=1}^{n} \ln Z(S_i, P) \right] + D_{KL}(\mathcal{Q}||\mathcal{P}) \ . \tag{46}$$

To obtain $J(\mathcal{Q})$, we omit all additive terms from (5) that do not depend on $\mathcal{Q}$ and multiply by the scaling factor $\frac{n\sqrt{\tilde{m}}}{\sqrt{\tilde{m}}n+1}$. Since the described transformations are monotone, the minimizing distribution of $J(\mathcal{Q})$, that is,

$$\mathcal{Q}^* = \underset{\mathcal{Q} \in \mathcal{M}(\mathcal{M}(\mathcal{H}))}{\arg\min} J(\mathcal{Q}) \ , \tag{47}$$

is also the minimizer of (5). More importantly, $J(\mathcal{Q})$ is structurally similar to the generic minimization problem in (31). Hence, we can invoke Lemma 3 with $A = \mathcal{M}(\mathcal{H})$, $g(a) = -\sum_{i=1}^{n} \ln Z(S_i, P)$, $\beta = \frac{1}{\sqrt{n\tilde{m}}+1}$, to show that the optimal hyper-posterior is

$$\mathcal{Q}^*(P) = \frac{\mathcal{P}(P) \exp\left(\frac{1}{\sqrt{n\tilde{m}}+1} \sum_{i=1}^{n} \ln Z(S_i, P)\right)}{Z^{\mathrm{II}}(S_1, ..., S_n, \mathcal{P})} \ , \tag{48}$$

wherein

$$Z^{\mathrm{II}}(S_1, ..., S_n, \mathcal{P}) = \mathbb{E}_{P \sim \mathcal{P}} \left[\exp\left(\frac{1}{\sqrt{n\tilde{m}}+1} \sum_{i=1}^{n} \ln Z(S_i, P) \right) \right] \ .$$

$\square$

Technically, this concludes the proof of Proposition 1. However, we want to remark the following result:

If we choose $\mathcal{Q} = \mathcal{Q}^*$, the PAC-Bayes bound in (5) can be expressed in terms of the meta-level partition function Z^{II}, that is,

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq -\left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) \ln Z^{\mathrm{II}}(S_1, ..., S_n, \mathcal{P}) + C(\delta, n, \tilde{m}) \ . \tag{49}$$

We omit a detailed derivation of (49) since it is similar to the one for Corollary 1.

B PACOH-NN: A SCALABLE ALGORITHM FOR LEARNING BNN PRIORS

Proposition 2. *In expectation, replacing* $\ln Z(S_i, P_\phi)$ *in (5) by the Monte Carlo estimate* $\ln \tilde{Z}(S_i, P) := \ln \frac{1}{L} \sum_{l=1}^{L} e^{-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S)}$, $\theta_l \sim P$ *still yields an valid upper bound of the transfer error. In particular, it holds that*

$$\mathcal{L}(\mathcal{Q}, \mathcal{T}) \leq -\frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \mathbb{E}_{P \sim \mathcal{Q}} \left[\ln Z(S_i, P) \right] + \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q}||\mathcal{P}) + C(\delta, n, \tilde{m})$$

$$\leq -\frac{1}{n} \sum_{i=1}^{n} \frac{1}{\sqrt{\tilde{m}}} \mathbb{E}_{P \sim \mathcal{Q}} \left[\mathbb{E}_{\theta_1, ..., \theta_l \sim P} \left[\ln \tilde{Z}(S_i, P) \right] \right] + \left(\frac{1}{\sqrt{n}} + \frac{1}{n\sqrt{\tilde{m}}} \right) D_{KL}(\mathcal{Q}||\mathcal{P}) + C(\delta, n, \tilde{m}).$$

Proof. Firsts, we show that:

$$\mathbb{E}_{\theta_1,...,\theta_l \sim P}\left[\ln \tilde{Z}(S_i, P)\right] = \mathbb{E}_{\theta_1,...,\theta_l \sim P}\left[\ln \frac{1}{L}\sum_{l=1}^{L} e^{-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S)}\right]$$

$$\leq \ln \frac{1}{L}\sum_{l=1}^{L}\mathbb{E}_{\theta_l \sim P}\left[e^{-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S)}\right]$$

$$= \ln \mathbb{E}_{\theta \sim P}\left[e^{-\sqrt{m}\hat{\mathcal{L}}(\theta, S)}\right]$$

$$= \ln Z(S_i, P) \tag{50}$$

which follows directly from Jensen's inequality and the concavity of the logarithm. Now, Proposition 2 follows directly from (50).

Algorithm 1 PACOH-NN: meta-training

Input: hyper-prior $\mathcal{P}$, datasets $S_1, ..., S_n$
Input: kernel function $k(\cdot, \cdot)$, SVGD step size η, number of particles K
$\{\phi_1, ..., \phi_K\} \sim \mathcal{P}$ // Initialize prior particles
while not converged **do**
  for $k = 1, ..., K$ **do**
    $\{\theta_1, ..., \theta_L\} \sim P_{\phi_k}$ // sample NN-parameters from prior
    for $n = 1, ..., n$ **do**
      $\ln \tilde{Z}(S_i, P_{\phi_k}) \leftarrow \text{LSE}_{l=1}^{L}\left(-\sqrt{m}\hat{\mathcal{L}}(\theta_l, S_i)\right) - \ln L$ // estimate generalized MLL
    end for
    $\nabla_{\phi_k}\tilde{\mathcal{Q}}^*(\phi_k) \leftarrow \nabla_{\phi_k}\ln\mathcal{P}(\phi_k) + \frac{1}{\sqrt{n\tilde{m}}+1}\sum_{i=1}^{n}\nabla_{\phi_k}\ln\tilde{Z}(S_i, P_{\phi_k})$ // compute score
    $\phi_k \leftarrow \phi_k + \eta\frac{1}{K}\sum_{k'=1}^{K}\left[k(\phi_{k'}, \phi_k)\nabla_{\phi_{k'}}\ln\tilde{\mathcal{Q}}^*(\phi_{k'}) + \nabla_{\phi'_k}k(\phi_{k'}, \phi_k)\right]$ // update particles
  end for
end while
Output: set of priors $\{P_{\phi_1}, ..., P_{\phi_K}\}$

Algorithm 2 PACOH-NN: meta-testing

Input: set of priors $\{P_{\phi_1}, ..., P_{\phi_K}\}$, target training dataset $\tilde{S}$, evaluation point x^*
Input: kernel function $k(\cdot, \cdot)$, SVGD step size ν, number of particles L
for $k = 1, ..., K$ **do**
  $\{\theta_1^k, ..., \theta_L^k\} \sim P_{\phi_k}$ // initialize NN posterior particles from k-th prior
  while not converged **do**
    for $l = 1, ..., L$ **do**
      $\nabla_{\theta_l^k}Q^*(\theta_l^k)) \leftarrow \nabla_{\theta_l^k}\ln P_{\phi_k}(\theta_l^k)) + \sqrt{m}\,\nabla_{\theta_l^k}\mathcal{L}(l, \tilde{S})$ // compute score
      $\theta_l^k \leftarrow \theta_l^k + \frac{\nu}{L}\sum_{l'=1}^{L}\left[k(\theta_{l'}^k, \theta_l^k)\nabla_{\theta_{l'}^k}\ln Q^*(\theta_{l'}^k) + \nabla_{\theta_{l'}^k}k(\theta_{l'}^k, \theta_l^k)\right]$ // update particles
    end for
  end while
end for
$\tilde{p}(y^*|x^*, \tilde{S}) \leftarrow \frac{1}{K \cdot L}\sum_{k=1}^{K}\sum_{l=1}^{L}p(y^*|h_{\theta_l^k}(x^*))$ // form mixture of predictive NN distibutions
Output: predictive distribution $\tilde{p}(y^*|x^*, \tilde{S})$

$\square$

	Sinusoid	Cauchy	SwissFEL	Physionet	Berkeley
n	20	20	5	100	36
m_i	5	20	200	4 - 24	288

Table S1: Number of tasks n and samples per task m_i for the different meta-learning environments.

(a) Sinusoid tasks   (b) Cauchy tasks

Figure S2: Depiction of tasks (i.e., functions) sampled from the Sinusoid and Cauchy task environment, respectively. Note that the Cauchy task environment is two-dimensional ($\dim(\mathcal{X}) = 2$), while (b) displays a one-dimensional projection.

C EXPERIMENTS

C.1 META-LEARNING ENVIRONMENTS

In this section, we provide further details on the meta-learning environments used in Section 6. Information about the numbers of tasks and samples in the respective environments can be found in Table S1.

C.1.1 SINUSOIDS

Each task of the sinusoid environment corresponds to a parametric function

$$f_{a,b,c,\beta}(x) = \beta * x + a * \sin(1.5 * (x - b)) + c \,, \tag{51}$$

which, in essence, consists of an affine as well as a sinusoid function. Tasks differ in the function parameters (a, b, c, β) that are sampled from the task environment $\mathcal{T}$ as follows:

$$a \sim \mathcal{U}(0.7, 1.3), \quad b \sim \mathcal{N}(0, 0.1^2), \quad c \sim \mathcal{N}(5.0, 0.1^2), \quad \beta \sim \mathcal{N}(0.5, 0.2^2) \,. \tag{52}$$

Figure S2a depicts functions $f_{a,b,c,\beta}$ with parameters sampled according to (52). To draw training samples from each task, we draw x uniformly from $\mathcal{U}(-5, 5)$ and add Gaussian noise with standard deviation 0.1 to the function values $f(x)$:

$$x \sim \mathcal{U}(-5, 5) \,, \qquad y \sim \mathcal{N}(f_{a,b,c,\beta}(x), 0.1^2) \,. \tag{53}$$

C.1.2 CAUCHY

Each task of the Cauchy environment can be interpreted as a two dimensional mixture of Cauchy distributions plus a function sampled from a Gaussian process prior with zero mean and SE kernel function $k(x, x') = \exp\left(\frac{||x-x'||_2^2}{2l}\right)$ with $l = 0.2$. The (unnormalized) mixture of Cauchy densities is defined as:

$$m(x) = \frac{6}{\pi \cdot (1 + ||x - \mu_1||_2^2)} + \frac{3}{\pi \cdot (1 + ||x - \mu_2||_2^2)} \,, \tag{54}$$

with $\mu_1 = (-1, -1)^\top$ and $\mu_2 = (2, 2)^\top$.

Figure S3: Accelerator of the Swiss Free-Electron Laser (SwissFEL).

Functions from the task environments are sampled as follows:

$$f(x) = m(x) + g(x), \qquad g \sim \mathcal{GP}(0, k(x, x')).$$ (55)

Figure S2b depicts a one-dimensional projection of functions sampled according to (55). To draw training samples from each task, we draw x from a truncated normal distribution and add Gaussian noise with standard deviation 0.05 to the function values $f(x)$:

$$x := \min\{\max\{\tilde{x}, 2\}, -3\}, \quad \tilde{x} \sim \mathcal{N}(0, 2.5^2), \qquad y \sim \mathcal{N}(f(x), 0.05^2).$$ (56)

C.1.3 SWISSFEL

Free-electron lasers (FELs) accelerate electrons to very high speed in order to generate shortly pulsed laser beams with wavelengths in the X-ray spectrum. These X-ray pulses can be used to map nanometer scale structures, thus facilitating experiments in molecular biology and material science. The accelerator and the electron beam line of a FEL consist of multiple magnets and other adjustable components, each of which has several parameters that experts adjust to maximize the pulse energy (Kirschner et al., 2019a). Due do different operational modes, parameter drift, and changing (latent) conditions, the laser's pulse energy function, in response to its parameters, changes across time. As a result, optimizing the laser's parameters is a recurrent task.

Overall, our meta-learning environment consists of different parameter optimization runs (i.e., tasks) on the SwissFEL, an 800 meter long laser located in Switzerland (Milne et al., 2017). A picture of the SwissFEL is shown in Figure S3. The input space, corresponding to the laser's parameters, has 12 dimensions whereas the regression target is the pulse energy (1-dimensional). For details on the individual parameters, we refer to Kirschner et al. (2019b). For each run, we have around 2000 data points. Since these data-points are generated with online optimization methods, the data are non-i.i.d. and get successively less diverse throughout the optimization. As we are concerned with meta-learning with limited data and want to avoid issues with highly dependent data points, we only take the first 400 data points per run and split them into training and test subsets of size 200. Overall, we have 9 runs (tasks) available. 5 of those runs are used for meta-training and the remaining 4 runs are used for meta-testing.

C.1.4 PHYSIONET

The 2012 Physionet competition (Silva et al., 2012) published an open-access data set of patient stays on the intensive care unit (ICU). Each patient stay consists of a time series over 48 hours, where up to 37 clinical variables are measured. The original task in the competition was binary classification of patient mortality, but due to the large number of missing values (around 80 % across all features), the data set is also popular as a test bed for time series prediction methods, especially using Gaussian processes (Fortuin & Rätsch, 2019; Fortuin et al., 2019).

In this work, we treat each patient as a separate task and the different clinical variables as different environments. We use the Glasgow coma scale (GCS) and hematocrit value (HCT) as environments for our study, since they are among the most frequently measured variables in this data set. From the dataset, we remove all patients where less than four measurements of CGS (and HCT respectively)

are available. From the remaining patients we use 100 patients for meta-training and 500 patients each for meta-validation and meta-testing. Here, each patient corresponds to a task. Since the number of available measurements differs across patients, the number of training points m_i ranges between 4 and 24.

C.2 BERKELEY-SENSOR

We use data from 46 sensors deployed in different locations at the Intel Research lab in Berkeley (Madden, 2004). The dataset contains 4 days of data, sampled at 10 minute intervals. Each task corresponds to one of the 46 sensors and requires auto-regressive prediction, in particular, predicting the next temperature measurement given the last 10 measurement values. In that, 36 sensors (tasks) with data for the first two days are use for meta-training and whereas the remaining 10 sensors with data for the last two days are employed for meta-testing. Note, that we separate meta-training and -testing data both temporally and spatially since the data is non-i.i.d. For the meta-testing, we use the 3rd day as context data, i.e. for target training and the remaining data for target testing.

C.3 EXPERIMENTAL METHODOLOGY

In the following, we describe our experimental methodology and provide details on how the empirical results reported in Section 6 were generated. Overall, evaluating a meta-learner consists of two phases, *meta-training* and *meta-testing*. The latter can be further sub-divided into *target training* and *target testing*. Figure S1 illustrates these different stages for our PAC-Bayesian meta-learning framework.

Meta-training The meta-learner is provided with a set of datasets $S_1, ..., S_2$ and optimizes its respective meta-objective, for instance in case of *PACOH-NN* by performing SVGD on the $\mathcal{Q}^*$ (see Algorithm 1).

Meta-testing This phase aims to evaluate the empirical generalization properties of the meta-learned prior knowledge. In particular, we evaluate how well the base learner, instatiated with the prior knowledge, performs on multiple unseen tasks $\tau = (\mathcal{D}, m) \sim \mathcal{T}$. For that, two steps are required: In the *target-training* phase, the base learner is given a training dataset $\tilde{S} \sim \mathcal{D}$ and performs (normal) inference. In case of *PACOH-NN*, this means approximating the generalized Bayesian posterior $Q^*(S, P)$ (see Algorithm 2). Then, in *target-testing*, we evaluate its predictions on a test dataset $\tilde{S}^* \sim \mathcal{D}$ from the same task. For PACOH-NN, NPs and MLAP the respective predictor outputs a probability distribution $\hat{p}(y^*|x^*, \tilde{S})$ for the x^* in $\tilde{S}^*$. The respective mean prediction corresponds to the expectation of $\hat{p}$, that is $\hat{y} = \hat{\mathbb{E}}(y^*|x^*, \tilde{S})$. In the case of MAML, only a mean prediction is available. Based on the mean predictions, we compute the *root mean-squared error (RMSE)*:

$$\text{RMSE} = \sqrt{\frac{1}{|\tilde{S}^*|} \sum_{(x^*, y^*) \in S^*} (y^* - \hat{y})^2} \ . \tag{57}$$

Similarly, we compute the *average log-likelihood*:

$$\text{LL} = \frac{1}{|\tilde{S}^*|} \sum_{(x^*, y^*) \in S^*} \ln \hat{p}(y^*|x^*, \tilde{S}) \ , \tag{58}$$

and the *calibration error* (see Appendix C.3.1).

The described meta-training and meta-testing procedure is repeated for five random seeds that influence both the initialization and gradient-estimates of the concerned algorithms. The averages and standard deviations reported in Figure S2a as well as Tables 1, 2 and **??** are based on the results obtained for different seeds.

C.3.1 CALIBRATION ERROR

The concept of calibration applies to probabilistic predictors that, given a new target input x_i, produce a probability distribution $\hat{p}(y_i|x_i)$ over predicted target values y_i. Corresponding to the predictive

density, we denote a predictor's cumulative density function (CDF) as $\hat{F}(y_j|x_j) = \int_{-\infty}^{y_j} \hat{p}(y|x_i)dy$. For confidence levels $0 \leq q_h < ... < q_H \leq 1$, we can compute the corresponding empirical frequency

$$\hat{q}_h = \frac{|\{y_j \mid \hat{F}(y_j|x_j) \leq q_h, j = 1, ..., m\}|}{m} \ , \tag{59}$$

based on dataset $S = \{(x_i, y_i)\}_{i=1}^m$ of m samples. If we have calibrated predictions we would expect that $\hat{q}_h \rightarrow q_h$ as $m \rightarrow \infty$. Similar to (Kuleshov et al., 2018), we can define the calibration error as a function of residuals $\hat{q}_h - q_h$, in particular,

$$\text{calib-err} = \frac{1}{H} \sum_{h=1}^H |\hat{q}_h - q_h| \ . \tag{60}$$

Note that we while (Kuleshov et al., 2018) reports the average of squared residuals $|\hat{q}_h - q_h|^2$, we report the average of absolute residuals $|\hat{q}_h - q_h|$ in order to preserve the units and keep the calibration error easier to interpret. In our experiments, we compute (60) with $K = 20$ equally spaced confidence levels between 0 and 1.

C.4 HYPER-PARAMETER SELECTION

For each of the meta-environments and algorithms, we ran a separate hyper-parameter search to select the hyper-parameters. In particular, we use the `hyperopt`[1] package (Bergstra et al., 2013) which performs Bayesian optimization based on regression trees. As optimization metric, we employ the average log-likelihood, evaluated on a separate validation set of tasks.

The scripts for reproducing the hyper-parameter search are included in our code repository[2] For the results, reported in the Tables 1, 2 and **??**, we provide the selected hyper-parameters and detailed evaluation results under `[Link will be made added upon acceptance]`

---

[1]http://hyperopt.github.io/hyperopt/
[2][Link will be made added upon acceptance]