TRACE: Tensorizing and Generalizing Supernets from Neural Architecture Search

Abstract

Recently, a special kind of graph, i.e., supernet, which allows two nodes connected by multi-choice edges, has exhibited its power in neural architecture search (NAS) by searching better architectures for computer vision (CV) and natural language processing (NLP) tasks. In this paper, we discover that the design of such discrete architectures also appears in many other important learning tasks, e.g., logic chain inference in knowledge graphs (KGs) and meta-path discovery in heterogeneous information networks (HINs). Thus, we are motivated to *generalize the supernet* search problem on a broader horizon. However, none of the existing works are effective since the supernet's topology is highly task-dependent and diverse. To address this issue, we propose to *tensorize the supernet*, i.e., unify the above problems by a tensor formulation and encode the topology inside the supernet by a tensor network. We further propose an efficient algorithm that admits both stochastic and deterministic objectives to solve the search problem. Finally, we perform extensive experiments on diverse learning tasks, i.e., architecture design for CV, logic inference for KG, and meta-path discovery for HIN. Empirical results demonstrate that our method leads to better performance and architectures.

1 Introduction

Deep learning (Goodfellow et al., 2017) has been successfully applied in many machine learning tasks, such as image classification for computer vision (CV) (LeCun et al., 1998; Krizhevsky et al., 2012; He et al., 2016; Huang et al., 2017) and language modeling for natural language processing (NLP) (Mikolov et al., 2013; Devlin et al., 2018). While the architecture design is of great importance to deep learning, manually designing proper architectures for a certain task is hard and requires lots of human efforts or sometimes even impossible (Zoph & Le, 2017; Baker et al., 2016).

Recently, neural architecture search (NAS) techniques (Elsken et al., 2019) have been developed to alleviate this issue, which mainly focuses on CV and NLP tasks. Behind existing NAS methods, a multi-graph (Skiena., 1992) structure, i.e., supernet (Zoph et al., 2017; Pham et al., 2018; Liu et al., 2018), where nodes are connected by edges with multiple choices, has played a central role. In such context, the choices on each edge are different operations, and the subnets correspond to different neural architectures. The objective here is to find a suitable subnet in this supernet, i.e. better neural architectures for a given task.

However, the supernet does not only arise in CV/NLP field and we find it also emerge in many other deep learning areas (see Table 1). An example is logic chain inference on knowledge graphs (Yang et al., 2017; Sadeghian et al., 2019; Qu & Tang, 2019), where the construction logical rules can be modeled by a supernet. Another example is meta-path discovery in heterogeneous information networks (Yun et al., 2019; Wan et al., 2020), where the discovery of meta-paths can also be modeled by a supernet. Therefore, we propose to broaden the horizon of NAS, i.e., generalize it to many deep learning fields and solve the new NAS problem under a unified framework.

Since subnets are discrete objects (choices on each edge are discrete), it has been a common approach (Liu et al., 2018; Sadeghian et al., 2019; Yun et al., 2019) to transform it into a continuous optimization problem. Previous methods often introduce continuous parameters separately for each edge. However, this formulation cannot generalize to different supernets as the topological structures of supernets are highly task-dependent and diverse. Therefore, it will fail to capture the supernet's topology and hence be ineffective.

Table 1: A comparison of existing NAS/non-NAS works for designing discrete architectures based on our tensorized formulation for the supernet. "Topology" indicate topological structure of the supernet is utilized or not.

	representative method	domain	supernet encoding	topology	optimization algorithm
existing NAS works	NASNet (Zoph et al., 2017)	CV	RNN	$\times$	policy gradient
	ENAS (Pham et al., 2018)	CV/NLP	RNN	$\times$	policy gradient
	DARTS (Liu et al., 2018)	CV/NLP	rank-1 CP	$\times$	gradient descent
	SNAS (Xie et al., 2018)	CV	rank-1 CP	$\times$	gradient descent
	NASP (Yao et al., 2020)	CV/NLP	rank-1 CP	$\times$	proximal algorithm
non-NAS works	DRUM (Sadeghian et al., 2019)	KG	rank-n CP	$\times$	gradient descent
	GTN (Yun et al., 2019)	HIN	rank-1 CP	$\times$	gradient descent
proposed	TRACE	all	TN	$\checkmark$	gradient descent

In this paper, we propose a novel method *TRACE (TensoRizing ArchiteCture sEarch)* to introduce a continuous parameter for each *subnet* (all these parameters will form a tensor). And we propose to construct a tensor network (TN) (Cichocki et al., 2016; 2017) based on the topological structure of supernet. For different tensor networks, we introduce a unified efficient algorithm for optimization on supernets. Extensive experiments are conducted on diverse deep learning tasks. And empirical results demonstrate that TRACE performs better than the state-of-the-art methods in each domain. As a summary, our contributions are as follows:

- We broaden the horizon of existing supernet-based NAS methods. Specifically, we *generalize* the concept of supernet in NAS to other deep learning tasks that have graph-like structures and propose to solve them in a unified framework of supernet.
- We propose a novel formulation for optimization on supernet by introducing a tensor on supernet (*tensorizing supernets*), and optimize this tensor to find the optimal subnet on the supernet
- While existing supernet-based NAS methods ignore the topological structure of the supernet, we encode the supernet in a topology-aware manner based on the tensor network and propose an efficient algorithm to solve the search problem.
- We conduct extensive experiments on various learning tasks, i.e., architecture design for CV, logic inference for KG, and meta-path discovery for HIN. Empirical results demonstrate that our method can find better architectures, which lead to state-of-the-art performance on various applications.

Notations. In this paper, we will use $\mathcal{S}$ to denote a supernet, and $\mathcal{P}$ to denote a subnet in supernet. For a supernet $\mathcal{S}$ with T edges, we let all edges be indexed by $e_1, \ldots, e_T$, and define C_t to be the number of choices on edge e_t with $t \in \{1, \ldots, T\}$. With subscript $i_1, \ldots, i_T$ denoted by i_- for short, we use $\mathcal{S}_{i_-}$ to denote the subnet with choices $i_1 \in \{1, \ldots, C_1\}, \ldots, i_T \in \{1, \ldots, C_T\}$. $\mathcal{N}(\mathcal{S})$ denotes the set of nodes in this supernet while $\mathcal{N}'(\mathcal{S}) \subseteq \mathcal{N}(\mathcal{S})$ denotes the set of nodes that are connected to more than one edge. $f(\boldsymbol{w}, \mathcal{P})$ stands for a learning model with parameter $\boldsymbol{w}$ and subnet $\mathcal{P}$. $\mathcal{L}(f(\boldsymbol{w}, \mathcal{P}), \mathcal{D})$ represents the loss and $\mathcal{M}(f(\boldsymbol{w}, \mathcal{P}), \mathcal{D})$ represents the performance of learning model $f(\boldsymbol{w}, \mathcal{P})$ on dataset $\mathcal{D}$. And we use $\text{softmax}(\boldsymbol{o}_i) = \exp(\boldsymbol{o}_i) / \sum_{j=1}^{n} \exp(\boldsymbol{o}_j)$ to denote the softmax operation over a vector $\boldsymbol{o}_i \in \mathbb{R}^n$.

2 RELATED WORKS

2.1 SUPERNET IN NEURAL ARCHITECTURE SEARCH (NAS)

There have been numerous algorithms proposed to solve the NAS problem. The first NAS work, NASRL (Zoph & Le, 2017), models the NAS problem as a multiple decision making problem and proposes to use reinforcement learning (RL) (Sutton & Barto, 2018) to solve this problem. However, this formulation does not consider the repetitively stacked nature of neural architectures and is very inefficient as it has to train many different networks to converge. To alleviate this issue, NASNet (Zoph et al., 2017) first models NAS as an optimization problem on supernet. The supernet formulation enables searching for transferrable architectures across different datasets and improves the searching efficiency. Later, based on the supernet formulation, ENAS (Pham et al., 2018) proposes weight-sharing techniques, which shares the weight of each subnet in a supernet.

This technique further improves searching efficiency and many different methods have been proposed under this framework (see Table 1), including DARTS (Liu et al., 2018), SNAS (Xie et al., 2018), and NASP (Yao et al., 2020). DARTS is the first to introduce deterministic formulation to NAS field, and SNAS uses a similar parametrized method with DARTS under stochastic formulation. NASP improves upon DARTS by using proximal operator (Parikh & Boyd, 2014) and activates only one subnets in each iteration to avoid co-adaptation between subnets.

2.2 Tensor Methods in Machine Learning

A tensor (Kolda & Bader, 2009) is a multi-dimensional array as an extension to a vector or matrix. Tensor methods have found wide applications in machine learning and deep learning, including network compression (Novikov et al., 2015; Wang et al., 2018) and knowledge graph completion (Liu et al., 2020). Recently, Cichocki et al. (2016; 2017) have proposed a unified framework called *tensor network (TN)*, which uses an undirected graph to represent tensor decomposition methods. By using different graphs, TN can cover many tensor decomposition methods as a special case, e.g., CP (Bro, 1997), Tucker (Tucker, 1966), tensor train (Oseledets, 2011), and tensor ring decomposition (Zhao et al., 2016). However, it is not an easy task to construct a tensor network for a given problem, as the topological structure of tensor network is hard to design (Li & Sun, 2020).

3 Proposed Method

Here, we describe our method for the supernet search problem. Section 3.1-3.2 introduce how we *tensorize* the supernets. Section 3.3 propose an optimization algorithm for the search problem which can be utilized for both stochastic and deterministic objectives. Finally, how supernet appears beyond existing NAS works and can be *generalized* to these new tasks are presented in Section 3.4.

3.1 A Tensor Formulation for Supernet

While existing works (Liu et al., 2018; Zoph et al., 2017; Pham et al., 2018) introduce parameters separately for each edge e_t, since edges may correlate with each other, a more general and natural approach is to introduce a continuous parameter directly for each *subnet* $\mathcal{P} \in \mathcal{S}$. Note that a subnet $\mathcal{P}$ can be distinguished by its choices on each edge, we propose to encode all possible choices into a tensor $\mathcal{T} \in \mathbb{R}^{C_1 \times \cdots \times C_T}$ and take these choices as indices, i.e., i_- to the tensor. As a consequence, the architecture of the subnet $\mathcal{P}$ is indexed as $\mathcal{S}_{i_-}$, and $\mathcal{T}_{i_-} \in [0, 1]$ represent how "good" $\mathcal{P}$ can be.

Figure 1: An example of supernet and two subnets with index i_-.

Under this tensor formulation, our objective will have the following form:

$$\max_{\mathcal{P}} \mathcal{J}(\mathcal{T}; f(\boldsymbol{w}^*(\mathcal{P}), \mathcal{P}), \mathcal{D}_{\text{val}}) \quad \text{s.t.} \quad \boldsymbol{w}^*(\mathcal{P}) = \arg\min_{\boldsymbol{w}} \mathcal{L}(f(\boldsymbol{w}, \mathcal{P}), \mathcal{D}_{\text{tr}}), \quad (1)$$

where the architecture $\mathcal{P}$ is searched in the upper-level, the network weight $\boldsymbol{w}$ is trained in the lower-level, $\mathcal{D}_{\text{tr}}$ is the training set and $\mathcal{D}_{\text{val}}$ is the validation set.

Equation (1) also allows us to have a unified view of deterministic formulation (Liu et al., 2018; Yao et al., 2020; Zela et al., 2020) and stochastic formulation (Xie et al., 2018; Pham et al., 2018; Akimoto et al., 2019) for NAS (see Section 2.1), which are popular in existing works. Specifically,

1). *Deterministic formulations* uses $\mathcal{T}$ as the weights on subnets, and the objective $\mathcal{J}$ will be like:

$$\mathcal{J}(\mathcal{T}; f(\boldsymbol{w}^*(\mathcal{P}), \mathcal{P}), \mathcal{D}_{\text{val}}) = \mathcal{M}(\sum\nolimits_{i_-} \mathcal{T}_{i_-} \cdot f(\boldsymbol{w}^*(\mathcal{S}_{i_-}), \mathcal{S}_{i_-}), \mathcal{D}_{\text{val}}). \quad (2)$$

2). *Stochastic formulation* uses $\mathcal{T}$ as the probabilities on subnets (i.e., $\sum_{i_-} \mathcal{T}_{i_-} = 1$), and formulate $\mathcal{J}$ as the "expectation" over all subnets:

$$\mathcal{J}(\mathcal{T}; f(\boldsymbol{w}^*(\mathcal{P}), \mathcal{P}), \mathcal{D}_{\text{val}}) = \sum\nolimits_{i_-} \mathcal{M}\left(f(\boldsymbol{w}^*(\mathcal{S}_{i_-}), \mathcal{S}_{i_-}), \mathcal{D}_{\text{val}}\right) \cdot \mathcal{T}_{i_-}. \quad (3)$$

In subsequent Section 3.3, we will present an algorithm that can solve both deterministic and stochastic formulation of (1) in a unified way.

| (a) Linear supernet. | (b) TN for (a). | (c) Full supernet. | (d) TN for (c). |

Figure 2: Some example of supernets and the corresponding tensor networks (TNs). Information flows in supernet (a) (c) follow the order of number in blocks. Circles in (b) and (d) represent core tensors and edges represent indices. Edges connected by two circles indicate index summation on $r_{N_1(t)}$ or $r_{N_2(t)}$, where $N_1(t)/N_2(t)$ is the index of nodes in supernet ($1, 2$ in (a) and $0, 1, 2$ in (c)). The formula of (b) is $\mathcal{T}_{i_1, i_2, i_3} = \sum_{r_1, r_2} \theta^1_{i_1, r_1} \theta^2_{r_1, i_2, r_2} \theta^3_{i_3, r_2}$ and the formula of (d) is $\mathcal{T}_{i_1, i_2, i_3} = \sum_{r_0, r_1, r_2} \theta^1_{r_0, i_1, r_1} \theta^2_{r_1, i_2, r_2} \theta^3_{r_2, i_3, r_0}$.

3.2 Encoding Supernet Topology by Tensor Network (TN)

Current methods consider each edge separately and can be seen as rank-1 factorization of the full tensor $\mathcal{T}$ (see Table 1) under our formulation (1), i.e. $\mathcal{T}_{i_-} = \alpha^1_{i_1} \ldots \alpha^T_{i_T}$ where $\alpha^t_{i_t} \in \mathbb{R}$ is the continuous parameter for choice i_t on edge t. However, their decomposition method does not consider the topological structure of supernets, and hence can be ineffective. Motivated by the limitation of current methods, we propose to introduce tensor network (TN) for better encoding the topological structure of supernet. Recall that how to properly construct a predefined graph is important for TN, we propose to design our TN following two principles:

- Our TN must reflect the topological structure of supernets; and
- Motivated by the success of previous methods (e.g., DARTS, SNAS and ENAS), our TN should include their encoding methods as special cases.

Thus, we propose to use the following routine (Algorithm 1) to tensorize the supernet. To illustrate our tensorizing process for some specific supernets, we give two examples in [1]Figure 2.

Algorithm 1 Construction of TN's computation graph for supernet encoding.

Input: Supernet $\mathcal{S}$;
1: Introduce a core tensor $\theta^t \in \mathbb{R}^{R_{N_1(t)} \times C_t \times R_{N_2(t)}}$ for each edge e_t with $N_1(t), N_2(t) \in \mathcal{N}(\mathcal{S})$ being nodes connected by e_t;
2: Compute $\mathcal{T}_{i_-}$ by $\mathcal{T}_{i_-} = \sum^{R_n}_{r_n, n \in \mathcal{N}'(\mathcal{S})} \prod^T_{t=1} \theta^t_{r_{N_1(t)}, i_t, r_{N_2(t)}}$;
3: **return** encoded supernet $\mathcal{T}_{i_-}$;

The reason of using $\mathcal{N}'(\mathcal{S})$ instead of $\mathcal{N}(\mathcal{S})$ is Proposition 1, which shows that using $\mathcal{N}'(\mathcal{S})$ will not restrict the expressive power but allows the usage of less parameters. The proof is in Appendix B.

Proposition 1. *Any tensors that can be expressed by* $\mathcal{T}_{i_-} = \sum^{R_n}_{r_n, n \in \mathcal{N}(\mathcal{S})} \prod^T_{t=1} \theta^t_{r_{N_1(t)}, i_t, r_{N_2(t)}}$ *can also be expressed by* $\mathcal{T}_{i_-} = \sum^{R_n}_{r_n, n \in \mathcal{N}'(\mathcal{S})} \prod^T_{t=1} \theta^t_{r_{N_1(t)}, i_t, r_{N_2(t)}}$.

3.3 Search Algorithm

To handle architecture design problems for various learning tasks (Table 1) in a unified manner, we will introduce an algorithm that can solve the generalized supernet search problem for both deterministic and stochastic formulation in (2) and (3). However, the new problem is hard to solve, as we need to handle the constraint on $\mathcal{T}$, i.e., $\sum_{i_-} \mathcal{T}_{i_-} = 1$. To address this issue, we propose to re-parameterize $\mathcal{T}$ using softmax trick, i.e.,

$$\bar{\mathcal{T}}_{i_-} = {}^1/\prod_{n \in \mathcal{N}'(\mathcal{S})} R_n \sum^{R_n}_{r_n, n \in \mathcal{N}'(\mathcal{S})} \prod^T_{t=1} \text{softmax}(\beta^{(t)}_{r_{N_1(t)}, i_t, r_{N_2(t)}}). \tag{4}$$

---

[1]Figure 2(b) and (d) also follow the diagram figure of tensor network, reader may refer (Cichocki et al., 2017) for more details.

Then, the optimization objective $\mathcal{J}$ in (1) becomes

$$\max_\beta \mathcal{J}_\beta(\beta; f(\boldsymbol{w}^*(\beta), \mathcal{P}(\beta)), \mathcal{D}_{\text{val}}), \quad \text{s.t.} \quad \boldsymbol{w}^*(\beta) = \arg\min_{\boldsymbol{w}} \mathcal{L}(f(\boldsymbol{w}, \mathcal{P}(\beta)), \mathcal{D}_{\text{tr}}). \quad (5)$$

where we have substitute discrete subnets $\mathcal{P}$ with continuous parameters β. As shown in Proposition 2, we can now solve a unconstrained problem on β, while keeping the constraint on $\mathcal{T}$ satisfied.

Proposition 2. $\sum_{i_-} \bar{\mathcal{T}}_{i_-} = 1$, where $\bar{\mathcal{T}}$ is given in (4).

Thus, gradient-based training strategies can be reused, which makes the optimization very efficient. And the complete steps for optimizing (5) are presented in Algorithm 2. Our algorithm covers both deterministic and stochastic formulation in a unified framework. And after the optimization of β is converged, we obtain $\mathcal{P}^*$ from tensor $\bar{\mathcal{T}}$ and retrain the model to obtain $\boldsymbol{w}^*$.

Algorithm 2 TRACE: TensoRizing ArchiteCture sEarch

Input: An architecture design task with training set $\mathcal{D}_{\text{tr}}$, validation set $\mathcal{D}_{\text{val}}$ and supernet $\mathcal{S}$;
1: Tensorize the supernet $\mathcal{T}$ with Algorithm 1;
2: Re-parameterize $\mathcal{T}$ to $\bar{\mathcal{T}}$ using (4);
3: **while** not converged **do**
4:     Obtain a subnet $\mathcal{P}$ from $\bar{\mathcal{T}}$ (deterministic or stochastic);
5:     Solve $\boldsymbol{w}^*(\beta) = \arg\min_{\boldsymbol{w}} \mathcal{L}(f(\boldsymbol{w}, \beta), \mathcal{D}_{\text{tr}})$;
6:     Update supernet parameters $\{\beta\}$ by gradient ascending $\nabla_\beta \mathcal{J}_\beta$;
7: **end while**
8: Obtain $\mathcal{P}^* = \mathcal{S}_{i_-}$ from the final $\bar{\mathcal{T}}$ by setting $i_- = \arg\max_{i_-} \bar{\mathcal{T}}_{i_-}$;
9: Obtain $\boldsymbol{w}^*(\mathcal{P}^*) = \arg\min_{\boldsymbol{w}}; \mathcal{L}(f(\boldsymbol{w}, \mathcal{P}^*), \mathcal{D}_{\text{tr}})$ by retraining $f(\boldsymbol{w}, \mathcal{P}^*)$;
10: **return** $\mathcal{P}^*$ (searched architecture) and $\boldsymbol{w}^*$ (fine-tuned parameters);

3.4 APPLICATION EXAMPLES BEYOND NAS

Despite NAS, there are many important problems in deep learning that have a graph-like structure. Examples include meta-path discovery (Yang et al., 2018; Yun et al., 2019; Wan et al., 2020), logic chain inference (Yang et al., 2017; Sadeghian et al., 2019) and structure learning between data points (Franceschi et al., 2019). Inspired by the recent work that exploits graph-like structures in NAS (Oh et al., 2019; Li et al., 2020; You et al., 2020), we propose to model them also as a search problem on supernets.

Meta-path discovery. Heterogeneous information networks (HINs) (Sun & Han, 2012; Shi et al., 2017) are networks whose nodes and edges have multiple types. HIN has been widely used in many real-world network mining scenarios, e.g., node classification (Wang et al., 2019) and recommendation (Zhao et al., 2017). For a heterogeneous network, a meta-path (Sun et al., 2011) is a path defined on it with multiple edge types. Intuitively, different meta-paths capture different semantic information from a heterogeneous network and it is important to find suitable meta-paths for different applications on HINs. However, designing a meta-path on a HIN is not a trivial task and requires much human effort and domain knowledge (Zhao et al., 2017; Yang et al., 2018). Thus, we propose to automatically discover informative meta-paths instead of to manually design.

To solve the meta-path discovery problem under the supernet framework, we first construct a supernet $\mathcal{S}$ (see Figure 2(a)) and a subnet $\mathcal{P} \in \mathcal{S}$ will be a meta-path on HIN. While GTN (Yun et al., 2019) introduces weights separately for each edge, our model $f(\boldsymbol{w}, \mathcal{P})$ uses a tensor $\mathcal{T}$ to model $\mathcal{P}$ as a whole. The performance metric $\mathcal{L}(\cdot)$ and $\mathcal{M}(\cdot)$ will depend on the downstream task. In our experiments on node classification, we use cross-entropy loss for $\mathcal{L}(\cdot)$ and macro F1 score for $\mathcal{M}(\cdot)$.

Logic chain inference. A knowledge graph (KG) (Singhal, 2012; Wang et al., 2017) is a multi-relational graph composed of entities (nodes) and relations (different types of edges). KG has found wide applications in many different areas, including question answering (Lukovnikov et al., 2017) and recommendation (Zhang et al., 2016). An important method to understand semantics in KG is logic chain inference, which aims to find underlying logic rules in KG. Specifically, a logic chain is a path on knowledge graph with the following form $x \xrightarrow{\;\;}_{B_1} z_1 \xrightarrow{\;\;} _{B_2} \ldots \xrightarrow{\;\;} _{B_T} y$, where $x, y, z_1, \ldots$ are entities and $B_1, B_2, \ldots, B_T$ are different relations in the knowledge graph. And logic chain inference is to use a logic chain to approximate a relation in KG. Obviously, different logic chains can have

Table 2: Comparison with NAS methods in stand-alone setting on NAS-Bench-201.

Method	CIFAR-10		CIFAR-100		ImageNet-16-120	
	validation	test	validation	test	validation	test
ResNet (He et al., 2016)	90.83	93.97	70.42	70.86	44.53	43.63
Random	90.93±0.36	93.70±0.36	70.60±1.37	70.65±1.38	42.92±2.00	42.96±2.15
REINFORCE	91.09±0.37	93.85±0.37	71.61±1.12	71.71±1.09	45.05±1.02	45.24±1.18
BOHB	90.82±0.53	93.61±0.52	70.74±1.29	70.85±1.28	44.26±1.36	44.42±1.49
REA	91.19±0.31	93.92±0.30	71.81±1.12	71.84±0.99	45.15±0.89	45.54±1.03
TRACE	**91.33±0.19**	**94.20±0.17**	**73.26±0.22**	**73.29±0.20**	**46.19±0.16**	**46.19±0.15**
TRACE (Best)	91.53	**94.37**	**73.49**	**73.51**	46.37	46.34
Best in Bench-201	91.61	94.37	73.49	73.51	46.77	47.31

critical influence on KG as incorrect logic rules will lead to wrong facts. However, directly solving the inference problem will have a exponential complexity as we have to enumerate all relations (Hamilton et al., 2018). Thus, we propose to model it as a supernet search problem to reduce complexity.

Since logic chain has a chain structure, we construct a supernet as in Figure 2(a). Denote our target relation as B_r, the adjacency matrix of relation B_r as $\mathbf{A}_{B_r}$, and the one-hot vector corresponding to entity x as $\mathbf{v}_x$. Our learning model $f(\boldsymbol{w}, \mathcal{P})$ now has no model parameter $\boldsymbol{w}$, and the original bi-level problem is reduced to a single-level one with the following performance measure $\mathcal{M}(f(\boldsymbol{w}, \mathcal{P}), \mathcal{D}) = \sum_{B_r(x,y)=1 \text{ in } \mathcal{D}} \mathbf{v}_x^\top (\prod_{i=1}^{T} \mathbf{A}_{B_i}) \mathbf{v}_y$, which counts the number of pairs (x, y) that has relation B_r and is predicted by logic chain $x \longrightarrow_{B_1} z_1 \longrightarrow_{B_2} \cdots \longrightarrow_{B_T} y$ in dataset (knowledge graph) $\mathcal{D}$.

4 EXPERIMENTS

All experiments are implemented on PyTorch (Paszke et al., 2017) except for logic chain inference, which is implemented on TensorFlow (Abadi et al., 2016) following DRUM (Sadeghian et al., 2019). And we have done all experiments on a single NVIDIA RTX 2080 Ti GPU.

4.1 BENCHMARK PERFORMANCE COMPARISON

Here, we compare our proposed method with the state-of-the-art methods on three different applications that need a design of architectures, i.e., neural architecture design for image classification, logic chain inference from KG, and meta-path discovery in HIN.

4.1.1 DESIGNING CONVOLUTIONAL NEURAL NETWORK (CNN) ARCHITECTURES

We first apply TRACE to the architecture design problem on CNN for image classification, which is currently the most famous application for supernet-based methods. We consider the following two different settings for our NAS experiments: (i). Stand-alone (Zoph & Le, 2017; Zoph et al., 2017): train each architecture to converge to obtain separate $\boldsymbol{w}^*(\mathcal{P})$; (ii). Weight-sharing (Liu et al., 2018; Xie et al., 2018; Yao et al., 2020): share the same parameter $\boldsymbol{w}$ across different architectures during searching. And for both stand-alone and weight-sharing experiments, we repeat our method for five times and report the mean±std of test accuracy of searched architectures.

Stand-alone setting. To enable comparison under stand-alone setting, we use the NAS-Bench-201 dataset (Dong & Yang, 2020) where the authors exhaustively trained all subnets in a supernet and obtain a complete record of each subnet's accuracy on three different datasets: CIFAR-10, CIFAR-100 and ImageNet-16-120 (details in Appendix C.1). We use the stochastic formulation and compare our method with (i) Random Search (Yu et al., 2020); (ii) REINFORCE (policy gradient) (Zoph & Le, 2017); (iii) BOHB (Falkner et al., 2018) and (iv) REA (regularized evolution) (Real et al., 2018). Results are in Table 2, and we can see that our method achieves better results than all existing stand-alone NAS methods and even finds the optimal architecture on CIFAR-10 and CIFAR-100 dataset.

Table 3: Comparison with NAS methods in weight-sharing setting on CIFAR-10.

Architecture	Test Error (%)	Params (M)	Search Cost (GPU Days)	Search Method
DenseNet-BC (Huang et al., 2017)	3.46	25.6	-	manual
ENAS (Pham et al., 2018)	2.89	4.6	0.5	RL
DARTS (1st) (Liu et al., 2018)	3.00±0.14	3.3	1.5	gradient
DARTS (2nd)	**2.76±0.09**	3.3	4	gradient
SNAS (Xie et al., 2018)	2.85±0.02	2.8	1.5	gradient
GDAS (Dong & Yang, 2019)	2.93	3.4	0.21	gradient
BayesNAS (Zhou et al., 2019)	2.81±0.04	3.4	0.2	gradient
ASNG-NAS (Akimoto et al., 2019)	2.83±0.14	2.9	0.11	natural gradient
NASP (Yao et al., 2020)	2.83±0.09	3.3	0.1	proximal algorithm
R-DARTS (Zela et al., 2020)	2.95±0.21	-	1.6	gradient descent
TRACE	**2.78±0.12**	3.3	0.6	gradient

Table 4: Experiment results on logic chain inference.

Dataset	Family				UMLS				Kinship			
		Hits @				Hits @				Hits @		
	MRR	10	3	1	MRR	10	3	1	MRR	10	3	1
Neural LP	0.88	0.98	0.95	0.80	0.72	0.93	0.84	0.58	0.55	0.87	0.63	0.41
DRUM	**0.95**	**0.99**	**0.98**	0.91	0.80	**0.98**	0.94	0.66	0.59	**0.91**	0.68	0.44
GraIL	0.87	0.96	0.95	0.79	0.73	0.94	0.86	0.55	0.57	0.89	0.65	**0.45**
TRACE	0.92	**0.99**	**0.98**	**0.92**	**0.81**	**0.98**	**0.95**	**0.67**	**0.61**	**0.91**	**0.69**	**0.45**

Table 5: Evaluation results on the node classification task (F1 score).

Dataset	DeepWalk	metapath2vec	GCN	GAT	HAN	GTN	TRACE
DBLP	63.18	85.53	87.30	93.71	92.83	93.98	**94.42**
ACM	67.42	87.61	91.60	92.33	90.96	91.89	**92.62**
IMDB	32.08	35.21	56.89	58.14	56.77	58.92	**61.31**

Weight-sharing setting. We use the deterministic formulation, construct supernet follows (Liu et al., 2018), and evaluate all methods on CIFAR-10 dataset (details are in Appendix C.1). These are the most popular setups for weight-sharing NAS. Results are in Table 3, we can see that TRACE achieves comparable performances with existing weight-sharing NAS methods.

4.1.2 LOGIC CHAIN INFERENCE FROM KNOWLEDGE GRAPH (KG)

For logic chain inference, we use the deterministic formulation and compare our method with the following methods: Neural LP (Yang et al., 2017), DRUM (Sadeghian et al., 2019), and GraIL (Teru et al., 2020). Neural LP and DRUM are restricted to logic chain inference, while GraIL considers more complex graph structures. We do not compare our method with embedding-based methods, e.g. RotatE (Sun et al., 2019) as those methods all need embeddings for entities and cannot generalize found rules to unseen entities.

Following the setting of DRUM, we conduct experiments on three KG datasets: Family, UMLS and Kinship (details are in Appendix C.2), and report the best mean reciprocal rank (MRR), Hits at $1, 3, 10$ across 5 different runs. Results are in Table 4, which demonstrates that our proposed method achieves better results than all existing methods. Besides, case studies in Section 4.2 further demonstrate that TRACE can find more accurate rules than others.

4.1.3 META-PATH DISCOVERY IN HETEROGENEOUS INFORMATION NETWORK (HIN)

Finally, we apply TRACE to meta-path discovery problem on HINs. Following existing works (Wang et al., 2019; Yun et al., 2019), we use the deterministic formulation and conduct experiments on three benchmark datasets: DBLP, ACM and IMDB (details are in Appendix C.3) and compare our methods with the baselines in GTN (Yun et al., 2019), i.e., DeepWalk (Perozzi et al., 2014), metapath2vec (Dong et al., 2017), GCN (Kipf & Welling, 2016), GAT (Veličković et al., 2018), HAN (Wang et al., 2019). Results on different datasets are in Table 5, which demonstrate that TRACE performs better than other methods on different HINs.

4.2 Case Study

To further investigate the performance of TRACE, we list the top rules found by TRACE and other methods in Table 6. This result demonstrates that our method can find more accurate logic rules than other baselines, which contributes to the superior performance of our method. We also give the architectures and meta-paths found by TRACE in Appendix D.

Table 6: An example of top 3 rules obtained by each method on Family dataset.

Neural-LP	son(C, A) ← brother(C, B) , son(B, A)
	son(B, A) ← brother(B, A)
	son(C, A) ← son(C, B), mother(B, A)
DRUM	*son(C, A) ← nephew(C, B), brother(B, A)*
	son(C, A) ← brother(C, B), son(B, A)
	son(C, A) ← brother(C, B), daughter(B, A)
TRACE	son(C, A) ← son(C, B), wife(B, A)
	son(C, A) ← brother(C, B), son(B, A)
	son(C, A) ← nephew(C, B), brother(B, A)

4.3 Ablation Study

4.3.1 Impact of encoding approach

We compare TRACE with the following encoding methods on supernet: (i) DARTS, which introduces continuous parameters for each edge separately; (ii) RNN, which uses a RNN to compute the weights for each edge; (iii) CP decomposition, which generalizes DARTS to higher rank; (iv) TRACE(Full), which does not adopt Proposition 1 in Algorithm 1. Results on NAS-Bench-201 using CIFAR-100 are shown in Figure 3(a), and we can see that DARTS performs worse than other methods (CP and TRACE) due to insufficient expressive power. And TRACE achieves better results than CP by being topological aware. It also shows that our simplified encoding scheme does not harm the final performance, as verified in Proposition 1.

(a) Encoding methods. (b) TN ranks. (c) Re-parametrization.

Figure 3: Ablation studies on NAS-Bench-201, CIFAR-100 is used

4.3.2 Impact of rank of tensor network

We also investigate the impact of R_n's, which are ranks in tensor network (TN) on supernets. For simplicity, we restrict R_n to be equal for all nodes $n \in \mathcal{N}(\mathcal{S})$ and compare the performance of different ranks with previous state-of-the-art REA (see Table 2) in Figure 3(b). Results demonstrate that while the rank can influence the final performance, it is easy to set rank properly for TRACE to beat other methods. We also adopt $R_n = 2$ for all other experiments.

4.3.3 Optimization algorithms

Finally, we compare TRACE with proximal algorithm (Parikh & Boyd, 2014), which is a popular and general algorithm for constrained optimization. Specifically, proximal algorithm is used to solve (1) with the constraint $\sum_{i_-} \mathcal{T}_{i_-} = 1$ without Proposition 2. We solve the proximal step iteratively and numerically since there is no closed-form solutions. The comparison is in Figure 3(c), and we can see that TRACE beats proximal algorithm by a large margin, which demonstrates that the re-parameterized by Proposition 2 is useful for optimization.

5 Conclusion

In this paper, we *generalize* supernet from neural architecture search (NAS) to other machine learning tasks. To expressively model the supernet, we introduce a tensor formulation to the supernet and represent it by tensor network (*tensorizing supernets*). We further propose an efficient gradient-based algorithm to solve the new supernet search problem. Empirical results across various applications demonstrate that our approach has superior performance on these machine learning tasks.

REFERENCES

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek G. Murray, Benoit Steiner, Paul Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. Tensorflow: A system for large-scale machine learning. In *OSDI*, 2016.

Youhei Akimoto, Shinichi Shirakawa, Nozomu Yoshinari, Kento Uchida, Shota Saito, and Kouhei Nishida. Adaptive stochastic natural gradient method for one-shot neural architecture search. In *ICML*, 2019.

Bowen Baker, Otkrist Gupta, Nikhil Naik, and Ramesh Raskar. Designing neural network architectures using reinforcement learning. *arXiv preprint arXiv:1611.02167*, 2016.

Rasmus Bro. PARAFAC tutorial and applications. *Chemometrics and Intelligent Laboratory Systems*, 1997.

Andrzej. Cichocki, Namgil. Lee, Ivan. Oseledets, Anh-Huy Phan, Qibin Zhao, and Danilo Mandic. Tensor networks for dimensionality reduction and large-scale optimization: Part 1 low-rank tensor decompositions. *Foundations and Trends in Machine Learning*, 2016.

Andrzej. Cichocki, Anh-Huy. Phan, Qibin. Zhao, Namgil. Lee, Ivan. Oseledets, Masashi. Sugiyama, and Danilo Mandic. Tensor networks for dimensionality reduction and large-scale optimization: Part 2 applications and future perspectives. *Foundations and Trends in Machine Learning*, 2017.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Xuanyi Dong and Yi Yang. Searching for a robust neural architecture in four gpu hours. In *CVPR*, June 2019.

Xuanyi Dong and Yi Yang. Nas-bench-201: Extending the scope of reproducible neural architecture search. In *ICLR*, 2020.

Yuxiao Dong, Nitesh V. Chawla, and Ananthram Swami. metapath2vec: Scalable representation learning for heterogeneous networks. In *KDD*, 2017.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *Journal of Machine Learning Research*, 2019.

Stefan Falkner, Aaron Klein, and Frank Hutter. BOHB: Robust and efficient hyperparameter optimization at scale. In *ICML*, 2018.

Luca Franceschi, Mathias Niepert, Massimiliano Pontil, and Xiao He. Learning discrete structures for graph neural networks. In *ICML*, 2019.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2017.

Will Hamilton, Payal Bajaj, Marinka Zitnik, Dan Jurafsky, and Jure Leskovec. Embedding logical queries on knowledge graphs. In *NIPS*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Gao Huang, Zhuang Liu, and Kilian Weinberger. Densely connected convolutional networks. In *CVPR*, 2017.

Thomas N. Kipf and Max Welling. Semi-Supervised Classification with Graph Convolutional Networks. In *ICLR*, 2016.

Tamara G. Kolda and Brett W. Bader. Tensor decompositions and applications. *SIAM Review*, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NIPS*, 2012.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 1998.

Chao Li and Zhun Sun. Evolutionary topology search for tensor network decomposition. In *ICML*, 2020.

Wei Li, Shaogang Gong, and Xiatian Zhu. Neural graph embedding for neural architecture search. In *AAAI*, 2020.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable architecture search. In *ICLR*, 2018.

Yu Liu, Quanming Yao, and Yong Li. Generalizing tensor decomposition for n-ary relational knowledge bases. In *WWW*, 2020.

Denis Lukovnikov, Asja Fischer, Jens Lehmann, and Sören Auer. Neural network-based question answering over knowledge graphs on word and character level. In *WWW*, 2017.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *NIPS*, 2013.

Alexander Novikov, Dmitrii Podoprikhin, Anton Osokin, and Dmitry P Vetrov. Tensorizing neural networks. In *NIPS*, 2015.

Changyong Oh, Jakub Tomczak, Efstratios Gavves, and Max Welling. Combinatorial bayesian optimization using the graph cartesian product. In *NeurIPS*, pp. 2914–2924. 2019.

Ivan V. Oseledets. Tensor-train decomposition. *SIAM Journal on Scientific Computing*, 2011.

Neal Parikh and Stephen Boyd. Proximal algorithms. *Foundations and Trends in optimization*, 1(3): 127–239, 2014.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. In *NIPS Workshop on Automatic Differentiation*, 2017.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *KDD*, 2014.

Hieu Pham, Melody Guan, Barret Zoph, Quoc Le, and Jeff Dean. Efficient neural architecture search via parameters sharing. In *ICML*, 2018.

Meng Qu and Jian Tang. Probabilistic logic neural networks for reasoning. In *NeurIPS*. 2019.

Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V Le. Regularized evolution for image classifier architecture search. In *AAAI*, 2018.

Ali Sadeghian, Mohammadreza Armandpour, Patrick Ding, and Daisy Zhe Wang. DRUM: End-to-end differentiable rule mining on knowledge graphs. In *NIPS*, 2019.

Chaun Shi, Yitong Li, Jiawei Zhang, Yizhou Sun, and Philip S. Yu. A survey of heterogeneous information network analysis. *IEEE Transactions on Knowledge and Data Engineering*, 2017.

Amit Singhal. Introducing the knowledge graph: things, not strings. *Official google blog*, 5, 2012.

Steven Skiena. Implementing discrete mathematics: combinatorics and graph theory with mathematica. *The Mathematical Gazette*, 1992.

Yizhou Sun and Jiawei Han. Mining heterogeneous information networks: principles and methodologies. *Synthesis Lectures on Data Mining and Knowledge Discovery*, 2012.

Yizhou Sun, Jiawei Han, Xifeng Yan, Philip S. Yu, and Tianyi Wu. Pathsim: Meta path-based top-k similarity search in heterogeneous information networks. *Proceedings of the VLDB Endowment*, 2011.

Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In *ICLR*, 2019.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. MIT Press, 2018.

Komal K. Teru, Etienne Denis, and William L. Hamilton. Inductive relation prediction by subgraph reasoning. In *ICML*, 2020.

Ledyard Tucker. Some mathematical notes on three-mode factor analysis. *Psychometrika*, 1966.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *ICLR*, 2018.

Guojia Wan, Bo Du, Shirui Pan, and Gholamreza Haffari. Reinforcement learning based meta-path discovery in large-scale heterogeneous information networks. In *AAAI*, 2020.

Quan Wang, Zhendong Mao, Bin Wang, and Li Guo. Knowledge graph embedding: A survey of approaches and applications. *IEEE Transactions on Knowledge and Data Engineering*, 2017.

Wenqi Wang, Yifan Sun, Brian Eriksson, Wenlin Wang, and Vaneet Aggarwal. Wide compression: Tensor ring nets. In *CVPR*, June 2018.

Xiao Wang, Houye Ji, Chuan Shi, Bai Wang, Yanfang Ye, Peng Cui, and Philip S Yu. Heterogeneous graph attention network. In *WWW*, 2019.

Sirui Xie, Hehui Zheng, Chunxiao Liu, and Liang Lin. SNAS: stochastic neural architecture search. In *ICLR*, 2018.

Carl Yang, Mengxiong Liu, Frank He, Xikun Zhang, Jian Peng, and Jiawei Han. Similarity modeling on heterogeneous networks via automatic path discovery. In *ECML-PKDD*, 2018.

Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. In *NIPS*. 2017.

Quanming Yao, Ju Xu, Wei-Wei Tu, and Zhanxing Zhu. Efficient neural architecture search via proximal iterations. In *AAAI*, 2020.

Jiaxuan You, Jure Leskovec, Kaiming He, and Saining Xie. Graph structure of neural networks. In *ICML*, 2020.

Kaicheng Yu, Christian Sciuto, Martin Jaggi, Claudiu Musat, and Mathieu Salzmann. Evaluating the search phase of neural architecture search. In *ICLR*, 2020.

Seongjun Yun, Minbyul Jeong, Raehyun Kim, Jaewoo Kang, and Hyunwoo J Kim. Graph transformer networks. In *NIPS*. 2019.

Arber Zela, Thomas Elsken, Tonmoy Saikia, Yassine Marrakchi, Thomas Brox, and Frank Hutter. Understanding and robustifying differentiable architecture search. In *ICLR*, 2020.

Fuzheng Zhang, Nicholas Jing Yuan, Defu Lian, Xing Xie, and Wei-Ying Ma. Collaborative knowledge base embedding for recommender systems. In *KDD*, 2016.

Huan Zhao, Quanming Yao, Jianda Li, Yangqiu Song, and Dik Lun Lee. Meta-graph based recommendation fusion over heterogeneous information networks. In *KDD*, 2017.

Qibin Zhao, Guoxu Zhou, Shengli Xie, Liqing Zhang, and Andrzej Cichocki. Tensor Ring Decomposition. *arXiv e-prints*, pp. arXiv:1606.05535, June 2016.

Hongpeng Zhou, Minghao Yang, Jun Wang, and Wei Pan. BayesNAS: A Bayesian approach for neural architecture search. In *ICML*, 2019.

Barret Zoph and Quoc V. Le. Neural architecture search with reinforcement learning. In *ICLR*, 2017.

Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V. Le. Learning transferable architectures for scalable image recognition. In *ICCV*, 2017.

A   COMPLETE ALGORITHMS OF OPTIMIZATION ON TENSORIZED SUPERNET

Here, we give a more detailed description for our algorithm under deterministic and stochastic formulation in Algorithm 3 and 4, respectively. In our experiments, we use the stochastic formulation for NAS under standalone setting, and deterministic formulation for others.

Algorithm 3 TRACE (deterministic formulation with weight-sharing)

Input: Training set $\mathcal{D}_{\text{tr}}$, Validation set $\mathcal{D}_{\text{val}}$
 1: Tensorize the supernet $\mathcal{T}$ with Algorithm 1;
 2: Re-parameterize $\mathcal{T}$ to $\bar{\mathcal{T}}$ using (4);
 3: **while** not converged **do**
 4:      Update model parameters $\boldsymbol{w}(\beta)$ by gradient descending $\nabla_{\boldsymbol{w}} \mathcal{L}\left(f(\boldsymbol{w}, \beta), \mathcal{D}_{\text{tr}}\right)$
 5:      Update supernet parameters $\{\beta\}$ by gradient ascending $\nabla_{\beta} \mathcal{J}_{\beta}$
 6: **end while**
 7: Obtain $\mathcal{P}^* = \mathcal{S}_{i_-}$ from the final $\bar{\mathcal{T}}$ by setting $i_- = \arg\max_{i_-} \bar{\mathcal{T}}_{i_-}$;
 8: Obtain $\boldsymbol{w}^*(\mathcal{P}^*) = \arg\min_{\boldsymbol{w}}; \mathcal{L}\left(f(\boldsymbol{w}, \mathcal{P}^*), \mathcal{D}_{\text{tr}}\right)$ by retraining $f(\boldsymbol{w}, \mathcal{P}^*)$;
 9: **return** $\boldsymbol{w}^*, \mathcal{P}^*$;

Algorithm 4 TRACE (stochastic formulation)

Input: Training set $\mathcal{D}_{\text{tr}}$, Validation set $\mathcal{D}_{\text{val}}$
 1: Tensorize the supernet $\mathcal{T}$ with Algorithm 1;
 2: Re-parameterize $\mathcal{T}$ to $\bar{\mathcal{T}}$ using (4);
 3: **while** not converged **do**
 4:      Sample a subnet $\mathcal{P}$ from the probability distribution given by $\bar{\mathcal{T}}$
 5:      Solve $\boldsymbol{w}^*(\mathcal{P}) = \arg\min_{\boldsymbol{w}} \mathcal{L}\left(f(\boldsymbol{w}, \mathcal{P}), \mathcal{D}_{\text{tr}}\right)$
 6:      Update supernet parameters $\{\beta\}$ by gradient ascending $\nabla_{\beta} \mathcal{J}_{\beta}$
 7:      Save the best $\boldsymbol{w}^*(\mathcal{P}), \mathcal{P}$ so far
 8: **end while**
 9: **return** best $\boldsymbol{w}^*(\mathcal{P}), \mathcal{P}$ in Step 7;

B   PROOFS

B.1   PROPOSITION 1

Proof. Denote those nodes in supernet whose degree is greater than one (connected by more than one edges) as $\mathcal{N}'(\mathcal{S})$. Thus, $\mathcal{N}(\mathcal{S}) \setminus \mathcal{N}'(\mathcal{S})$ denotes all degree-1 nodes in supernet. Suppose one node $N_1(t)$ is only connected by edge t, while $N_2(t)$ is not, [2] then we can rewrite $\mathcal{T}_{i_-} = \sum_{r_n, n \in \mathcal{N}(\mathcal{S})}^{R_n} \prod_{t=1}^{T} \theta_{r_{N_1(t)}, i_t, r_{N_2(t)}}^t$ as follows:

$$
\begin{aligned}
\mathcal{T}_{i_-} &= \sum_{r_n, n \in \mathcal{N}(\mathcal{S})} \prod_{t=1}^{T} \alpha_{r_{N_1(t)}, i_t, r_{N_2(t)}}^t \\
&= \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})} \sum_{r_n, n \in \mathcal{N}(\mathcal{S}) \setminus \mathcal{N}'(\mathcal{S})} \prod_{t=1}^{T} \alpha_{r_{N_1(t)}, i_t, r_{N_2(t)}}^t \\
&= \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})} \prod_{t=1}^{T} \sum_{r_n, n \in \mathcal{N}(\mathcal{S}) \setminus \mathcal{N}'(\mathcal{S})} \alpha_{r_{N_1(t)}, i_t, r_{N_2(t)}}^t \\
&= \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})} \ldots \big(\sum_{r_{N_1(t)}} \alpha_{r_{N_1(t)}, i_t, r_{N_2(t)}}^t \big) \ldots \\
&= \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})} \ldots \tilde{\alpha}_{i_t, r_{N_2(t)}}^{(t)} \ldots
\end{aligned}
$$

---

[2]If $N_1(t)$ is only connected by edge t (degree is 1), $N_2(t)$ cannot be only connected by edge t unless the supernet has only one edge t connecting two nodes $N_1(t), N_2(t)$, which is a trivial case.

where similar process is done for all edges. Thus, only nodes whose degree is greater than 1 is actually needed for index contraction. And for $n \in \mathcal{N}(\mathcal{S}) \setminus \mathcal{N}'(\mathcal{S})$, we can simply set $R_n = 1$ without loss of expressive power. $\qquad \square$

B.2 PROPOSITION 2

Proof. Following (4), we can have:

$$
\begin{aligned}
\sum_{i_-} \mathcal{T}_{i_-} &= \frac{1}{\prod_{n \in \mathcal{N}'(\mathcal{S})} R_n} \sum_{i_-} \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})}^{R_n} \prod_{t=1}^{T} \frac{\exp(\alpha^t_{r_{N_1(t)}, i_t, r_{N_2(t)}})}{\sum_j \exp(\alpha^t_{r_{N_1(t)}, j, r_{N_2(t)}})} \\
&= \frac{1}{\prod_{n \in \mathcal{N}'(\mathcal{S})} R_n} \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})}^{R_n} \prod_{t=1}^{T} \left(\sum_{i_t} \frac{\exp(\alpha^t_{r_{N_1(t)}, i_t, r_{N_2(t)}})}{\sum_j \exp(\alpha^t_{r_{N_1(t)}, j, r_{N_2(t)}})} \right) \\
&= \frac{1}{\prod_{n \in \mathcal{N}'(\mathcal{S})} R_n} \sum_{r_n, n \in \mathcal{N}'(\mathcal{S})}^{R_n} 1^T \\
&= \frac{1}{\prod_{n \in \mathcal{N}'(\mathcal{S})} R_n} \prod_{n \in \mathcal{N}'(\mathcal{S})} R_n = 1.
\end{aligned}
$$

$\qquad \square$

C EXPERIMENT DETAILS

C.1 NEURAL ARCHITECTURE SEARCH (NAS)

Stand-alone setting The supernet used in NAS-Bench-201 has 3 nodes, and each pair of nodes is connected by a directed edge, which gives 6 edges in total. And for each edge, we have 5 different operations ("choices"): zero, skip connect, 1×1 convolution, 3×3 convolution and 3×3 average pooling. And the details of datasets used in NAS-Bench-201 are in Table 7.

Table 7: Dataset statistics of three image classification dataset for NAS.

	Image size	# Classes	# Training	# Validation	# Test
CIFAR-10	32×32	10	25K	25K	5K
CIFAR-100	32×32	100	50K	5K	5K
ImageNet-16-120	16×16	120	151.7K	3K	3K

Weight-sharing setting Our construction of supernet follows (Liu et al., 2018). The supernet has 7 nodes, where the first two nodes are the output from previous two cells, respectively, and the last node performs depthwise concatenation to the output of the rest four nodes. Thus, the supernet has 8 edges with multiple choices (operations), and for each edge, we consider 8 different operations: zero, skip connect, 3×3 and 5×5 separable convolution, 3×3 and 5×5 dilated separable convolution, 3×3 max pooling and 3×3 average pooling. We evaluate all weight-sharing methods on CIFAR-10 dataset and the dataset division is the same as in Table 7.

C.2 LOGIC CHAIN INFERENCE

In our experiments, we follow the setting in DRUM (Sadeghian et al., 2019) and set the max length of rules T to be 3 for all datasets. And we set the rank L to be 4 in DRUM based on best validation performances. The details of KG datasets used in experiments are in Table 8.

Table 8: Dataset statistics for three KG dataset.

	# Triplets	# Relations	# Entities
Family	28356	12	3007
UMLS	5960	46	135
Kinship	9587	25	104

C.3 META-PATH DISCOVERY

The details of HIN datasets used in our experiments are in Table 9.

Table 9: Dataset statistics for three heterogeneous information network dataset.

	# Nodes	# Edges	# Edge types	# Features	# Training	# Validation	# Test
DBLP	18405	67946	4	334	800	400	2857
ACM	8994	25922	4	1902	600	300	2125
IMDB	12772	37288	4	1256	300	300	2339

D MORE EXPERIMENT RESULTS

D.1 CASE STUDIES

(a) CIFAR-10

(b) CIFAR-100

(c) ImageNet-16-120

Figure 4: Architectures found by TRACE on NAS-Bench-201 for different datasets.

(a) Normal Cell

(b) Reduction Cell

Figure 5: Architectures found by TRACE on weight-sharing setting.

Table 10: Meta-paths found by GTN and TRACE on different HIN.

Dataset	predefined meta-path	Top-3 meta-paths	
		GTN	TRACE
DBLP	APCPA, APA	CPCPA, APCPA, CP	CPCA, APCPA, APA
ACM	PAP, PSP	APAP, APA, SPAP	PSP, APAP, PAP
IMDB	MAM, MDM	DM, AM, MDM	MDM, MDMAM, MAM

D.2 RUNNING PLOTS

(a) Family   (b) UMLS   (c) Kinship

Figure 6: Validation MRR during training on three KG datasets.

Figure 7: Validation macro F1 score during training on three HIN datasets.

D.3 ABLATION STUDIES

Figure 8: Ablation studies on NAS-Bench-201, CIFAR-10 is used

Figure 9: Ablation studies on NAS-Bench-201, ImageNet-16-120 is used