Scalable Infomin Learning

Abstract

The task of infomin learning aims to learn a representation with high utility while being uninformative about a specified target, with the latter achieved by minimising the mutual information between the representation and the target. It has broad applications, ranging from training fair prediction models against protected attributes, to unsupervised learning with disentangled representations. Recent works on infomin learning mainly use adversarial training, which involves training a neural network to estimate mutual information or its proxy and thus is slow and difficult to optimise. Drawing on recent advances in slicing techniques, we propose a new infomin learning approach, which uses a novel proxy metric to mutual information. We further derive an accurate and analytically computable approximation to this proxy metric, thereby removing the need of constructing neural network-based mutual information estimators. Compared to baselines, experiments on independence tests, disentangled representation learning and algorithmic fairness tasks demonstrates that our new method has better utility and higher scalability.

1 Introduction

Learning representations that are uninformative about some target but still useful for downstream applications is an important task in machine learning with many applications in areas including algorithmic fairness [1, 2, 3, 4], disentangled representation learning [5, 6, 7, 8], information bottle-neck [9, 10], and invariant representation learning [11, 12, 13].

A popular method for the above task is adversarial training [1, 3, 4, 7, 14, 2, 11], where two neural networks, namely the encoder and the adversary, are trained jointly to compete with each other. The encoder's goal is to learn a representation with high utility but contains no information about the target. The adversary, on the contrary, tries to recover information about the target from the learned representation as much as possible. This leads to a minmax game similar to that in generative adversarial networks [15]. Adversarial training is effective with a strong adversary, however, it is often challenging to train the adversary thoroughly in practice, due to time constraints and/or optimisation difficulties [16, 17]. In fact, recent studies have revealed that adversarial approaches may not faithfully produce an infomin representation [18, 19, 17, 20, 21]. This motivates us to seek a good, adversarial training-free alternative for scalable infomin learning.

In this work, we propose a new method for infomin learning which is almost as powerful as using a strong adversary but is highly scalable. Our method is inspired by recent advances in information theory which proposes to estimate mutual information in the sliced space [22]. We highlight the following contributions:

- We show that for infomin learning, a general, accurate estimate of mutual information or its bound is unnecessary: testing and minimising dependence randomly in some sliced space is sufficient;
- We develop an analytical approximation to the aforementioned sliced independence test, along with a scalable training algorithm based on this approximation. No adversarial training is needed.

Importantly, the proposed method can be applied to a wide range of infomin learning tasks without any constraints on the form of variables or any assumption about the distributions. This contrasts our method to other adversarial training-free methods which are either tailored for discrete or univariate variables [23, 24, 24, 25, 21] or rely on variational approximation to densities [10, 26, 18, 12].

2   Background

Infomin representation learning. Let $X \in \mathbb{R}^D$ be the data, $Y \in \mathbb{R}^{D'}$ be the target we want to predict from X. The task we consider here is to learn some representation $Z = f(X)$ that is useful for predicting Y but is uninformative about some target $T \in \mathbb{R}^d$. Formally, this can be written as

$$\min_f \mathcal{L}(f(X); Y) + \beta \cdot I(f(X); T) \tag{1}$$

where f is an encoder, $\mathcal{L}$ is some loss function quantifying the utility of Z for predicting Y and $I(f(X); T)$ quantifies the amount of information left in Z about T. β controls the trade-off between utility and uninformativeness. Many tasks in machine learning can be seen as special cases of this objective. For example, by setting T to be (a set of) sensitive attributes e.g. race, gender or age, we arrive at fair representation learning [27, 1, 2, 20]. When using a stochastic encoder, by setting Y to be X and T to be some generative factors e.g., a class label, we arrive at disentangled representation learning [5, 6, 7, 8]. Similarly, the information bottleneck method [9, 10] corresponds to setting $T = X$, which learns representations expressive for predicting Y while being compressive about X.

Adversarial training for infomin learning. A key ingredient in objective (1) is to quantify $I(f(X); T)$ as the informativeness between $f(X)$ and T. One solution is to train a predictor for T from $f(X)$ and use the prediction error as a measure of $I(f(X); T)$ [1, 3, 4]. Another approach is to first train a classifier to distinguish between samples from $p(Z, T)$ vs. $p(Z)p(T)$ [7, 14] or to distinguish samples $Z \sim p(Z|T)$ with different T [2, 11], then use the classification error to quantify $I(f(X); T)$. All these methods involve the training of a neural network t to provide a lower-bound estimate to $I(f(X); T)$, yielding a minmax optimisation problem

$$\min_f \max_t \mathcal{L}(f(X); Y) + \beta \cdot \hat{I}_t(f(X); T) \tag{2}$$

where $\hat{I}_t(f(X); T)$ is an estimator constructed using t that lower-bounds $I(f(X); T)$. The time complexity of optimising (2) is $O(L_1 L_2)$ where L_1 and L_2 are the number of gradient steps for the outer and inner loop respectively. The strength of t is crucial for the quality of the learned representation [18, 19, 17, 20, 21]. For a strong adversary, a large L_2 is possibly needed, but this means a long training time. Conversely, a weak adversary may not produce a truly infomin representation.

3   Methodology

We propose an alternative to adversarial training for optimising (1). Our idea is to learn representation by the following objective, which replaces $I(f(X); T)$ in objective (1) with its 'sliced' version:

$$\min_f \mathcal{L}(f(X); Y) + \beta \cdot SI(f(X); T), \tag{3}$$

where SI denotes the sliced mutual information, which was also considered in [22]. Informally, SI is a 'facet' of mutual information that is much easier to estimate (ideally has closed form) but can still to some extent reflect the dependence between Z and T. Optimising (3) is then equivalent to testing and minimising the dependence between Z and T from one facet. Importantly, while testing dependence through only a single facet may be insufficient, by testing and minimising dependence through various facets across a large number of mini-batches we eventually see $I(Z; T) \to 0$.

We show one instance for realising SI whose empirical approximation $\hat{SI}$ has an analytic expression. The core of our method is Theorem 1, which is inspired by [4, 22].

Theorem 1. Let $Z \in \mathbb{R}^D$ and $T \in \mathbb{R}^d$ are two random variables that have moments. Z and T are statistically independent if and only if $SI(Z, T) = 0$ where $SI(Z, T)$ is defined as follows

$$SI(Z; T) = \sup_{h, g, \theta, \phi} \rho(h(\theta^\top Z), g(\phi^\top T)), \tag{4}$$

where ρ is the Pearson correlation, $h, g : \mathbb{R} \to \mathbb{R}$ are Borel-measurable non-constant functions, and $\theta \in \mathbb{S}^{D-1}, \phi \in \mathbb{S}^{d-1}$ are vectors on the surfaces on D-dimensional and d-dimensional hyperspheres.

81 *Proof.* See the Appendix. □

82 We sketch here how our result relates to [4, 22]. [22] considers $\overline{SI}(Z;T)$, defined as the ex-
83 pected mutual information $\mathbb{E}[I(\theta^\top Z, \phi^\top T)]$ of slices of Z and T, where the expectation is taken
84 over respective Haar measures $\theta \in \mathbb{S}^{D-1}$, $\phi \in \mathbb{S}^{d-1}$. Proposition 1 in [22] shows that: (1)
85 $\overline{SI}(Z;T) \geq 0$ with equality iff Z and T are independent; and (2) $\overline{SI}(Z;T) \leq \sup_{\theta,\phi} I(\theta^\top Z, \phi^\top T)$.
86 Our result uses some similar proof techniques, but instead of considering the mutual information
87 $I(\theta^\top Z, \phi^\top T)$, we handle the Pearson correlation of the sup over functions h, g as defined above,
88 which links to Rényi's maximal correlation [4, 28, 29, 30] and has closed form as shown below.

89 We call θ and ϕ the slices for Z and T respectively, and $\theta^\top Z$, $\phi^\top T$ the sliced Z and T respectively.

90 Intuitively, Theorem 1 says that in order to achieve $I(Z;T) \to 0$, we need not estimate $I(Z;T)$ in
91 the original space; rather we can test (and optimise) independence in the sliced space as realised by
92 (4). Note other realisations of the sliced mutual information SI can also be used. The major merit of
93 the realisation (4) is it has an analytic expression for its empirical approximation, as shown below.

94 **Analytic approximation to *SI*.** An empirical approximation to (4) is

$$\sup_{i,j} \sup_{h_i, g_j} \rho(h_i(\theta_i^\top Z), g_j(\phi_j^\top T)),$$

95
$$\text{where} \quad \theta_i \sim \mathcal{U}(\mathbb{S}^{D-1}), \ i = 1, ..., S, \qquad \phi_j \sim \mathcal{U}(\mathbb{S}^{d-1}), \ j = 1, ..., S. \tag{5}$$

96 i.e., we approximate (4) by randomly sampling a number of slices θ, ϕ uniformly from the surface
97 of two hyperspheres $\mathbb{S}^{D-1}$ and $\mathbb{S}^{d-1}$ and pick those slices where the sliced Z and the sliced T
98 are maximally associated. With a large number of slices, it is expected that (5) will approximate (4)
99 well. We refer to [22] for a theoretical analysis on the number of required slices in estimator-agnostic
100 settings. In Appendix B we also investigate empirically how this number will affect performance.

101 For each slicing direction, we further assume that the supreme functions $h_i, g_j : \mathbb{R} \to \mathbb{R}$ for that
102 direction can be well approximated by K-order polynomials, i.e.

$$h_i(a) \approx \hat{h}_i(a) = \sum_{k=0}^K w_{ik}\sigma(a)^k, \qquad g_j(a) \approx \hat{g}_j(a) = \sum_{k=0}^K v_{jk}\sigma(a)^k,$$

103 where $\sigma(\cdot)$ is a monotonic function which maps the input to the range of $[-1, 1]$. Its role is to ensure
104 that $\sigma(a)$ always has finite moments, so that the polynomial approximation is well-behaved. Note no
105 information is lost by applying $\sigma(\cdot)$. Here we take $\sigma(\cdot)$ as the tanh function. Other approximations
106 can also be used (e.g. those based on random features [31]), which can be explored in the future.

107 One may wonder if ignoring the higher-order terms $\sigma(a)^{k'}, k' > K$ will cause inaccuracy in inde-
108 pendence testing. In Appendix A we show that if $|\hat{h}_i(a) - h_i(a)| \leq \epsilon$ and $|\hat{g}_j(a) - g_j(a)| \leq \epsilon$ for
109 $\forall i, j, a$, then as $\epsilon \to 0$ we have $|\rho_{ij}^* - \hat{\rho}_{ij}^*| = o(\epsilon)$ where $\rho_{ij}^* = \rho(h_i(\theta_i^\top Z), g_j(\phi_j^\top T))$ is the true
110 correlation and $\hat{\rho}_{ij}^*$ is its K-order approximation. In such case we have $\hat{\rho}_{ij}^* \approx 0$ whenever $\rho_{ij}^* \approx 0$.

111 With this polynomial approximation, the solving of each h_i, g_j reduces to finding their weights:

$$w_i, v_j = \arg\max_{w,v} \rho(w^\top Z_i', v^\top T_j'),$$

112
$$Z_i' = [\sigma(\theta_i^\top Z)^k]_{k=1}^K, \qquad T_j' = [\sigma(\phi_j^\top T)^k]_{k=1}^K$$

113 This is known as canonical correlation analysis [32] and can be solved analytically by eigendecom-
114 position. Hence we can find the weights for all pairs of h_i, g_j by doing S^2 eigendecompositions.

115 In fact, the functions h_i, g_j for all i, j can be solved simultaneously by performing a larger eigende-
116 composition only once. We do this by finding w, v that maximise the following quantity:

$$\hat{SI}_{\Theta,\Phi}(Z;T) = \sup_{w,v} \rho(w^\top Z', v^\top T'), \tag{6}$$

117
$$\text{where} \quad Z_i' = [\sigma(\theta_i^\top Z)^k]_{k=1}^K, \qquad T_j' = [\sigma(\phi_j^\top T)^k]_{k=1}^K,$$

118
$$\theta_i \sim \mathcal{U}(\mathbb{S}^{D-1}), \ i = 1, ..., S, \qquad \phi_j \sim \mathcal{U}(\mathbb{S}^{d-1}), \ j = 1, ..., S.$$

119 The benefits for solving f_i, g_j for all slices jointly are two-fold. The first is stronger test power.
120 More specifically, it allows us to unify the power of different slices: while some sliced directions

may be weak for detecting dependence, they together as a whole (by treating them as a 'big slice') can compensate for each other, yielding a powerful test. We highlight that this joint-solving strategy will not violate our original objective (i.e. minimising (5)), as backed up by Theorem 2 below. The intuition is that if all Z_i' and T_j' together cannot achieve a high correlation, they alone can not either:

Theorem 2. Provided that each h_i, g_j in (5) are K-order polynomials , given the sampled $\Theta = \{\theta_i\}_{i=1}^S, \Phi = \{\phi_j\}_{j=1}^S$, we have $\hat{SI}_{\Theta,\Phi}(Z;T) \leq \epsilon \Rightarrow \sup_{i,j} \sup_{h_i,g_j} \rho(h_i(\theta_i^\top Z), g_j(\phi_j^\top T)) \leq \epsilon$.

Proof. See Appendix A. □

Theorem 2 says that the solution of (6) yields an upper bound of (5). This essentially means that we are safe to replace (5) with (6) which may be a more powerful independence test. Another potential benefit for solving g_j, h_j jointly is its better efficiency in practice, as it avoids invoking a for loop and has better affinity to modern deep learning infrastructure and libraries which are optimised for matrix-based operations. For these reasons, we use $\hat{SI}_{\Theta,\Phi}(Z;T)$ as an approximation to $SI(Z;T)$.

Algorithm 1 Adversarial Infomin Learning	**Algorithm 2** Slice Infomin Learning
Input: data $\mathcal{D} = \{X^{(n)}, Y^{(n)}, T^{(n)}\}_{n=1}^N$	**Input:** data $\mathcal{D} = \{X^{(n)}, Y^{(n)}, T^{(n)}\}_{n=1}^N$
Output: $Z = f(X)$ that optimises (1)	**Output:** $Z = f(X)$ that optimises (1)
Hyperparams: β, N', L_1, L_2	**Hyperparams:** β, N', L, S
Parameters: encoder f, MI estimator t	**Parameters:** encoder f, weights w, v in $\hat{SI}$
for l_1 in 1 to L_1 **do**	**for** l in 1 to L **do**
sample mini-batch $\mathcal{B}$ from $\mathcal{D}$	sample mini-batch $\mathcal{B}$ from $\mathcal{D}$
sample $\mathcal{D}'$ from $\mathcal{D}$ whose size $N' < N$	sample $\mathcal{D}'$ from $\mathcal{D}$ whose size $N' < N$
// *Max-step*	// *Max-step*
for l_2 in 1 to L_2 **do**	sample S slices $\Theta = \{\theta_i\}_{i=1}^S, \Phi = \{\phi_j\}_{j=1}^S$
$t \leftarrow t + \eta\nabla_t \hat{I}_t(f(X);T)$ with data in $\mathcal{D}'$	solve the parameters w, v in $\hat{SI}$ analytically
end for	with $\Theta, \Phi, \mathcal{D}'$ by eigendecomposition
// *Min-step*	// *Min-step*
$f \leftarrow f - \eta\nabla_f[\mathcal{L}(f(X);Y) + \beta\hat{I}_t(f(X);T)]$	$f \leftarrow f - \eta\nabla_f[\mathcal{L}(f(X);Y) + \beta\hat{SI}(f(X);T)]$
with data in $\mathcal{B}$	with data in $\mathcal{B}$
end for	**end for**
return $Z = f(X)$	**return** $Z = f(X)$

Mini-batch learning algorithm. Given the above approximation (6) to SI, we can now elaborate the details of mini-batch learning. For each mini-batch $\mathcal{B}$, we execute the following steps:

- *Max-step.* Sample S slices $\Theta = \{\theta_i\}_{i=1}^S, \Phi = \{\phi_j\}_{j=1}^S$ and a subset of the data $\mathcal{D}' \subset \mathcal{D}$ (here $|\mathcal{D}'|$ can be larger than $|\mathcal{B}|$). Learn the weights w, v of (6) with $\Theta, \Phi, \mathcal{D}'$ by eigendecomposition;

- *Min-step.* Set $\hat{SI}(Z,T) = \rho(w^\top Z', v^\top T')$ with w, v solved in the max-step and Z', T' defined in (6). Update f by SGD: $f \leftarrow f - \eta\nabla_f[\mathcal{L}(f(X),Y) + \beta\hat{SI}(f(X),T)]$ with the mini-batch data.

The whole learning procedure is shown in Algorithm 2. Compared to that of adversarial methods [2, 11, 1, 3, 20, 4] as shown in Algorithm 1, we replace the optimisation of neural net in the max step with an analytical eigendecomposition step. The time complexity for eigendecomposition is $O(S^3)$.

As an optional strategy, one may actively seek informative slices for dependence detection. This can be done by optimising $\hat{SI}$ w.r.t the sampled slices by a few gradient steps (e.g. 2-4) in the max-step:

$$\Theta \leftarrow \Theta - \xi\nabla_\Theta \hat{SI}_{\Theta,\Phi}(Z,T), \qquad \Phi \leftarrow \Phi - \xi\nabla_\Phi \hat{SI}_{\Theta,\Phi}(Z,T) \tag{7}$$

We can do this after solving $\hat{SI}$ analytically. Such a strategy is particularly useful when most of the sampled slices are weak in detecting dependence, which typically happens in late iterations of learning where $I(Z;T) \approx 0$. Since the optimisation of slices only happens in late iterations, and that we only apply a small number of gradient steps, the increased execution time will be negligible.

4 Related works

Neural mutual information estimators. A set of neural network-based methods [33, 34, 35, 36] have been proposed to estimate the mutual information (MI) between two random variable, most of which work by maximising a lower bound of MI [37]. These neural MI estimators are in general more powerful than non-parametric methods [38, 39, 40, 41] when trained thoroughly, yet the time spent on training may become the computational bottleneck when applied to infomin learning.

Upper bound for mutual information. Another line of method for realising the goal of infomin learning without adversarial training is to find an upper bound for mutual information [10, 18, 12, 42]. However, unlike lower bound estimate, upper bound often requires knowledge of either the conditional densities or the marginal densities [37] which are generally not available in practice. As such, most of these methods introduce a variational approximation to these densities whose choice/estimate may be difficult. Our method on the contrary needs not to approximate any densities.

Slicing techniques. A series of successes have been witnessed for the use of slicing methods in machine learning and statistics [43], with applications in generative modelling [44, 45, 46, 47], statistical test [48] and mutual information estimate [22]. Among them, the work [22] who proposes the concept of sliced mutual information is very related to this work and directly inspires our method. Our contribution is a novel realisation of sliced mutual information suitable for infomin learning.

Fair machine learning. One application of our method is to encourage the fairness of a predictor. Much efforts have been devoted for the same purpose, however most of the existing methods can either only work at the classifier level [24, 23, 4, 49], or only focus on the case where the sensitive attribute is discrete or univariate [21, 50, 25, 49, 27], or require adversarial training [2, 11, 1, 3, 20, 4]. Our method on the contrary has no restriction on the form of the sensitive attribute, can be used in both representation level and classifier level, and require no adversarial training of neural networks.

Disentangled representation learning. Most of the methods in this field work by penalising the discrepancy between the joint distribution $P = q(Z)$ and the product of marginals $Q = \prod_d^D q(Z_d)$ [6, 51, 26, 52, 7] [1]. However, such discrepancy is often non-trivial to estimate, so one has to resort to Monte Carlo estimate (β-TCVAE [26]), to train a neural network estimator (FactorVAE [7]) or to assess the discrepancy between P and Q by only their moments (DIP-VAE [51]). Our method avoids assessing distribution discrepancy directly and instead perform independence test in the sliced space.

5 Experiments

We evaluate our approach on three tasks: independence testing, fairness machine learning and disentangled representation learning. Code for reproducing our results is in the supplementary material.

Evaluation metric. To assess how much information is left in the learned representation $Z \in \mathbb{R}^D$ about the target $T \in \mathbb{R}^K$, we calculate the maximal Rényi correlation $\rho^*(Z, T)$ between Z and T:

$$\rho^*(Z, T) = \sup_{h,g} \rho(h(Z), g(T)) \tag{8}$$

which has the properties $\rho^*(Z, T) = 0$ if and only if $Z \perp T$ and $\rho^*(Z, T) = 1$ if $h(Z) = g(T)$ for some deterministic functions h, g [28]. One can also understand this metric as the easiness of predicting (the transformed) T from Z, or vice versa.[2] As there is no analytic solution for the supremum in (8), we approximate them by two neural networks h, g trained with SGD. Early stopping and dropout are applied to avoid overfitting. The reliability of this neural approximation has been verified by the literature [4] and is also confirmed by our experiments; see Appendix B.

This metric is closely related to existing metrics used in fairness and disentangled representation learning such as demographic parity (DP) [23] and total correlation (TC) [7]. For example, if $\rho^*(Z, T) \rightarrow 0$ then it is guaranteed that $\hat{Y} \perp T$ for any predictor $\hat{Y} = F(Z)$, so $\rho^*(Z, T)$ is an upper bound for DP . Similarly, $\rho^*(Z, T)$ coincides with TC which also assesses whether $Z \perp T$.

Baselines. We compare the proposed method (denoted as "Slice") with the following approaches:

---

[1]Note there exist methods based on group theory [53, 54, 55] which do not assess distribution discrepancy.

[2]It can be shown $\rho^*(Z, T)$ is equivalent to the normalised mean square error between $h(Z)$ and $g(T)$.

Figure 1: Comparison of the test power of different independence test methods. The x-axis corresponds to different values for the dependence level α and the y-axis corresponds to the test power.

- *Pearson*, which quantifies $I(Z;T)$ by the Pearson correlation coefficient $\frac{1}{DK}\sum_d^D\sum_k^K\rho(Z_d;T_k)$. It was used in [5, 51] to learn disentangled representations;

- *dCorr*, a non-parametric method for assessing independence based on the correlation between the pairwise distances [41]. It was applied in [36] as a surrogate to MI for representation learning;

- *Neural Rényi*, an adversarial method for fair machine learning [24] which quantifies $I(Z;T)$ by the Rényi correlation $\rho^*(Z,T) = \sup_{h,g}\rho(h(Z),g(T))$ with h,g approximated by neural networks. Many existing methods [1, 2, 3, 4] can be seen as variant of this approach;

- *Neural TC*, an adversarial method for learning disentangled representation [7, 56] which quantifies $I(Z;T)$ by the total correlation $TC(Z,T) = KL[p(Z,T)\|p(Z)p(T)]$. To computes TC, a (neural network) classifier is trained to classify samples from $p(Z,T)$ and samples from $p(Z)p(T)$. Many existing methods [57, 1] can be show to some extent t equivalent to this method (see Appendix B).

- *VB*, i.e. variational upper bound, which introduces a (learnable) variational distribution $q(T|Z)$ to form an upper bound of MI [42]: $I(Z;T) \leq \mathbb{E}_{p(Z,T)}[\log q(T|Z)] - \mathbb{E}_{p(Z)p(T)}[\log q(T|Z)]$.

For a fair comparison, for adversarial training-based approaches (i.e. Neural Rényi, Neural TC), we ensure that the training time of the neural networks in these method are at least the same as the execution time of our method or longer. We do this by controlling the adversarial steps L_2 in (2) and Algorithm 1. The same setup is used for VB. See each experiment for the detailed execution time.

Hyperparameter settings. throughout our experiments, we use 200 slices. We find that this setting is robust across different tasks. An ablation study on the number of slices is given in Appendix B. The number of samples used to learn the parameter of w,v in (6) is 10,000 sample and is kept fixed. The order of the polynomial used in (6) namely K is set as $K = 3$ and is fixed across different tasks.

Computational resource. All experiments are done with a single Nvidia GeForce Tesla T4 GPU.

5.1 Independence testing

We first verify the efficacy of our method as a light-weight but powerful independence test. For this purpose, we investigate the test power of the proposed method on various synthetic dataset with different association patterns between two random variables $X \in \mathbb{R}^{10}, Y \in \mathbb{R}^{10}$ and compared to that of the baselines. The test power is defined as the ability to discern samples from the joint distribution $p(X,Y)$ and samples from the product of marginal $p(X)p(Y)$ and is expressed as a probability $p \in [0,1]$. The data is generated as $Y = (1-\alpha)\langle t(\mathbf{A}X)\rangle + \alpha\epsilon, X_d \sim \mathcal{U}[-3,3], \mathbf{A}_{dd} = 1, \mathbf{A}_{dk} = 0.2, \epsilon \sim \mathcal{N}(\epsilon;\mathbf{0},\mathbf{I}), \alpha \in (0,1)$ and $\langle\cdot\rangle$ is a scaling operation that scales the operand to the range of $[0,1]$ according to the minimum and maximum values in the population. The function $t(\cdot)$ determines the association pattern between X and Y and is chosen from one of the following: $t(a) = a, a^2, \sin(a), \tanh(a)$. The factor α controls the strength of dependence between X and Y.

All tests are done on 250 samples and are repeated 1,000 times. We choose this sample number as it is a typical batch size in mini-batch learning. For methods involving the learning of parameters (i.e. Slice, Neural Rényi, Neural TC), we learn their parameters from 10,000 samples. The time for learning the parameters of Slice, Neural Rényi and Neural TC are 0.14s, 14.37s, 30.18s respectively. For completeness, we also compare with the 'optimal test' which calculates the Rényi correlation $\rho^*(X,Y) = \rho(h(X),g(Y))$ with the functions h,g exactly the same as the data generating process.

Table 1: Learning fair representations on the US Census Demographic dataset. Here the utility of the representation is measured by $\rho^*(Z, Y)$, while $\rho^*(Z, T)$ is used to quantify the fairness of the representation. Training time is also provided as the seconds required per iteration.

	N/A	Pearson	dCorr	Slice	Neural Rényi	Neural TC	VB
$\rho^*(Z, Y) \uparrow$	0.94 ± 0.01	0.94 ± 0.02	0.93 ± 0.03	0.93 ± 0.02	0.92 ± 0.01	0.91 ± 0.04	0.93 ± 0.02
$\rho^*(Z, T) \downarrow$	0.92 ± 0.02	0.84 ± 0.08	0.47 ± 0.08	0.07 ± 0.02	0.23 ± 0.10	0.27 ± 0.03	0.16 ± 0.10
time (sec./iter)	0.000	0.012	0.087	0.102	0.092	0.097	0.134

Figure 1 shows the power of different methods under various association patterns t and dependence levels α. Overall, we see that the proposed method can effectively detect dependence in all cases, and has a test power comparable to neural network-based methods. Non-parametric tests, by contrast, fail to detect dependence in quadratic and periodic cases, possibly due to insufficient power. Neural TC is the most powerful test among all the methods considered, yet it requires the longest time to train. We also see that the proposed method is relatively less powerful when $\alpha \geq 0.8$, but in such cases the mutual information between X and Y is indeed very low (see Appendix B). The results suggest that our slice method can provide effective training signals for the task of infomin learning.

5.2 Fairness

For this task, we aim to learn fair representations $Z \in \mathbb{R}^{80}$ that are minimally informative about some sensitive attribute T. We quantify how sensitive Z is w.r.t T by Rényi correlation $\rho^*(Z, T)$ calculated using two neural nets. Smaller $\rho^*(Z, T)$ is better. The utility of the learned representation i.e., $\mathcal{L}(Z; Y)$ is quantified by $\rho^*(Z, Y)$. This formulation for utility, as aforementioned, is equivalent to measuring how well we can predict Y from Z. In summary, the learning objective is:

$$\max \rho^*(Z; Y) - \beta \hat{I}(Z; T), \qquad (9)$$

where $I(Z; T)$ is estimated by the methods in test or replaced by a proxy. For each dataset considered, we use 20,000 data for training and 5,000 data for testing respectively. We carefully tune the hyperparameter β for each method so that the utility $\rho^*(Z; Y)$ in that method is close to that in the plain model (i.e. the model trained with $\beta = 0$, denoted as N/A below. Other experiments below have the same setup). All figures are reported on the test set.

US Census Demographic data. This dataset is an extraction of the 2015 American Community Survey, with 37 features about 74,000 census tracts. The target Y to predict is the percentage of children below poverty line in a tract, and the sensitive attribute T is the ratio of women in that tract.

The result is shown in Table 1. From the table we see that the proposed slice method produces highly fair representation with good utility. The low $\rho^*(Z, T)$ value indicates that it is unlikely to predict T from Z in our method. While adversarial methods can also to some extent achieve fairness, it is still not comparable to our method, possibly because the allocated training time is insufficient (we verify this in Appendix B). Non-parameteric methods can not produce truly fair representation, despite they are fast to execute. VB, which minimises the upper bound of MI, achieves better fairness than adversarial methods on average, but has a higher variance, possibly due to the reason shown in [58].

UCI Adult data. This dataset contains census data for 48,842 instances, with 14 attributes describing their education background, age, race, marital status, etc. Here, the target Y to predict is whether the income of an instance is higher than 50,000 USD, and the sensitive attribute T is the race.

Table 2: Learning fair representations on the UCI Adult dataset. Here the utility of the representation is measured by $\rho^*(Z, Y)$, while $\rho^*(Z, T)$ is used to quantify the fairness of the representation.

	N/A	Pearson	dCorr	Slice	Neural Rényi	Neural TC	VB
$\rho^*(Z, Y) \uparrow$	0.99 ± 0.00	0.99 ± 0.00	0.97 ± 0.01	0.98 ± 0.01	0.97 ± 0.01	0.98 ± 0.02	0.97 ± 0.02
$\rho^*(Z, T) \downarrow$	0.94 ± 0.02	0.91 ± 0.06	0.71 ± 0.06	0.08 ± 0.02	0.17 ± 0.08	0.36 ± 0.13	0.26 ± 0.12
time (sec./iter)	0.000	0.015	0.071	0.112	0.107	0.131	0.132

Figure 2: Label swapping experiments on Dsprite dataset. Left: the original image X. Middle: reconstructing X using the true label T. Right: reconstructing X with a swapped label $T' \neq T$. Images that share the same column index before and after label swapping have the same Z values.

Figure 3: Label swapping experiments on CMU-PIE dataset. Left: the original image X. Middle: reconstructing X using the true label T. Right: reconstructing X with a swapped label $T' \neq T$. Images that share the same column index before and after label swapping have the same Z values.

The result is summarised in Table 2. Again, we see that the proposed slice method outperforms other methods in terms of both fairness and utility. For this dataset, Neural Rényi also achieves good fairness, although the gap to our method is still large. Neural TC, by contrast, can not achieve a comparable level of fairness under the time budget given; a phenomenon also observed in the US Census dataset. This is possibly because the networks in Neural TC require longer time to train. VB-based method does not work very satisfactorily on this task, possibly because the allocated time to learn the variational distribution $q(Z|T)$ is not enough, leading to a loose upper bound of $I(Z;T)$.

5.3 Disentangled representation learning

We next apply our method to the task of disentangled representation learning, where we wish to discover some latent generative factors irrelevant to the class label T. Here, we train a conditional autoencoder $X \approx G(Z, T)$ to learn representation $Z = E(X)$ which encodes label-irrelevant information of X. The target to recover is $Y = X$. The utility of Z is therefore quantified as the reconstruction error: $\mathcal{L}(Z; Y) = \mathbb{E}[\|G(Z, T) - X\|_2^2]$, resulting in the following learning objective:

$$\max \mathbb{E}[\|G(Z, T) - X\|_2^2] - \beta \hat{I}(Z; T). \tag{10}$$

The conditional autoencoder uses a architecture similar to that of a convolutional GAN [59], with the difference being that we insert an adaption layer $Z' = \text{MLP}(Z, T)$ before feeding the features to the decoder. See Appendix B for the details of its architecture. All images are resized to 32×32.

Dsprite. A 2D shape dataset [60] where each image is generated by 4 latent factors: shape, rotation, scale, locations. Here the class label T is the shape, which ranges from (square, ellipse, heart). For this dataset, we train the autoencoder with 100 iterations with a batch size of 512. The dimensionality of the representation for this task is 20 i.e. $Z \in \mathbb{R}^{20}$.

As in the previous experiments, we provide quantitative comparisons of the utility and disentanglement of different methods in Table 3. In addition, we provide a qualitative comparison in Figure

Table 3: Learning label-irrelevant representations on the Dsprite dataset. Here the utility of the representation is measured by MSE, while $\rho^*(Z,T)$ is used to quantify the level of disentanglement of the representation. Training time is also provided as the seconds required per iteration.

	N/A	Pearson	dCorr	Slice	Neural Rényi	Neural TC	VB
MSE $\downarrow$	0.37 ± 0.01	0.44 ± 0.02	0.55 ± 0.03	0.50 ± 0.01	0.61 ± 0.04	0.49 ± 0.03	0.65 ± 0.04
$\rho^*(Z,T) \downarrow$	0.91 ± 0.03	0.81 ± 0.07	0.62 ± 0.07	0.08 ± 0.02	0.48 ± 0.05	0.34 ± 0.06	0.22 ± 0.08
time (sec./iter)	0.000	0.201	0.412	0.602	0.791	0.812	0.689

Table 4: Learning label-irrelevant representations on the CMU-PIE dataset. Here the utility of the representation is measured by MSE, while $\rho^*(Z,T)$ is used to quantify the level of disentanglement of the representation. Training time is also provided as the seconds required per iteration.

	N/A	Pearson	dCorr	Slice	Neural Rényi	Neural TC	VB
MSE $\downarrow$	1.81 ± 0.04	1.85 ± 0.05	2.08 ± 0.08	2.15 ± 0.07	2.46 ± 0.06	1.99 ± 0.12	2.02 ± 0.10
$\rho^*(Z,T) \downarrow$	0.76 ± 0.04	0.55 ± 0.03	0.27 ± 0.07	0.07 ± 0.01	0.36 ± 0.04	0.39 ± 0.06	0.15 ± 0.04
time (sec./iter)	0.000	0.184	0.332	0.581	0.750	0.841	0.621

2 which visualises the original image, the reconstructed image and the reconstructed image with a swapped label. From Table 3, we see that the proposed method achieve very low $\rho^*(Z,T)$ while maintaining good MSE, suggesting that we may have discovered the true label-irrelevant generative factor for this dataset. This is confirmed visually by Figure 2(b), where by changing T in reconstruction we only change the style. The separation between T and Z is less evident in adversarial approach, as can be seen from Table 3 as well as Figure 2(a) (see e.g. the reconstructed ellipses in the third column. They are more like a interpolation between ellipses and squares). For this task, VB method indeed works quite well, being the second best performing method on this task.

CMU-PIE. A colored face image dataset [61] where each face image has different pose, illumination and expression. We here consider a cropped version of it [62]. Here the class label T is the expression, which ranges from (neutral, smile, blinking). We train an autoencoder with 200 iteration and a batch size of 128. The dimensionality of the representation for this task is 128 i.e. $Z \in \mathbb{R}^{128}$.

Figure 3 and Table 4 shows the qualitative and quantitative results respectively. From Figure 3, we see that our method can well disentangle expression and non-expression representations: one can easily modify the expression of an image by only changing T in reconstruction. Other contents of the image e.g. the pose, illumination, identity are not changed. Adversarial approach can also to some extent achieve disentanglement between Z and T, however such disentanglement is imperfect: not all of the instances can change the expression by only modifying T. This is also confirmed quantitatively by Table 4, where one can see the relatively high $\rho^*(Z,T)$ values in adversarial methods. VI method, which optimises the upper bound of MI, again achieves a good performance on this task, being much better than adversarial methods. However, the proposed method still performs the best.

6 Conclusion

This work proposes a new method for infomin learning without adversarial training. A major challenge is how to estimate mutual information accurately and efficiently, as MI is generally intractable. We sidestep this challenge by only testing and minimising dependence in a sliced space, which can be achieved analytically, and we showed is sufficient for our goal. Experiments on algorithmic fairness and disentangled representation learning demonstrate the method's effectiveness of our method.

Through our controlled experiments, we also verify that adversarial approaches indeed may not produce truly infomin representation – an observation consistent with recent studies. This suggests that existing adversarial approaches may not converge to good solutions, or may need more time for convergence, with more gradient steps needed to train the adversary fully. The result also hints at the potential of diverse randomisation methods as an alternative to adversarial training in some cases.

While we believe our method can be used in many applications for societal benefit (e.g. for promoting fairness), since it is a general technique, one must always be careful to prevent societal harms.

References

[1] David Madras, Elliot Creager, Toniann Pitassi, and Richard Zemel. Learning adversarially fair and transferable representations. In *International Conference on Machine Learning*, pages 3384–3393. PMLR, 2018.

[2] Harrison Edwards and Amos Storkey. Censoring representations with an adversary. In *ICLR*, 2016.

[3] Yanai Elazar and Yoav Goldberg. Adversarial removal of demographic attributes from text data. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 11–21, 2018.

[4] Vincent Grari, Boris Ruf, Sylvain Lamprier, and Marcin Detyniecki. Fairness-aware neural Réyni minimization for continuous features. *arXiv preprint arXiv:1911.04929*, 2019.

[5] Brian Cheung, Jesse A Livezey, Arjun K Bansal, and Bruno A Olshausen. Discovering hidden factors of variation in deep networks. *arXiv preprint arXiv:1412.6583*, 2014.

[6] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-VAE: Learning basic visual concepts with a constrained variational framework. 2016.

[7] Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pages 2649–2658. PMLR, 2018.

[8] Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *International Conference on Machine Learning*, pages 4114–4124. PMLR, 2019.

[9] Naftali Tishby and Noga Zaslavsky. Deep learning and the information bottleneck principle. In *2015 IEEE information theory workshop (ITW)*, pages 1–5. IEEE, 2015.

[10] Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. *arXiv preprint arXiv:1612.00410*, 2016.

[11] Qizhe Xie, Zihang Dai, Yulun Du, Eduard Hovy, and Graham Neubig. Controllable invariance through adversarial feature learning. *Advances in neural information processing systems*, 30, 2017.

[12] Proteek Chandan Roy and Vishnu Naresh Boddeti. Mitigating information leakage in image representations: A maximum entropy approach. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2586–2594, 2019.

[13] Ayush Jaiswal, Daniel Moyer, Greg Ver Steeg, Wael AbdAlmageed, and Premkumar Natarajan. Invariant representations through adversarial forgetting. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 4272–4279, 2020.

[14] Pengyu Cheng, Weituo Hao, and Lawrence Carin. Estimating total correlation with mutual information bounds. *arXiv preprint arXiv:2011.04794*, 2020.

[15] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

[16] Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.

[17] Congzheng Song and Vitaly Shmatikov. Overlearning reveals sensitive attributes. *arXiv preprint arXiv:1905.11742*, 2019.

[18] Daniel Moyer, Shuyang Gao, Rob Brekelmans, Aram Galstyan, and Greg Ver Steeg. Invariant representations without adversarial training. *Advances in Neural Information Processing Systems*, 31, 2018.

[19] Rui Feng, Yang Yang, Yuehan Lyu, Chenhao Tan, Yizhou Sun, and Chunping Wang. Learning fair representations via an adversarial framework. *arXiv preprint arXiv:1904.13341*, 2019.

[20] Jiaming Song, Pratyusha Kalluri, Aditya Grover, Shengjia Zhao, and Stefano Ermon. Learning controllable fair representations. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 2164–2173. PMLR, 2019.

[21] Mislav Balunovic, Anian Ruoss, and Martin Vechev. Fair normalizing flows. In *International Conference on Learning Representations*, 2021.

[22] Ziv Goldfeld and Kristjan Greenewald. Sliced mutual information: A scalable measure of statistical dependence. *Advances in Neural Information Processing Systems*, 34, 2021.

[23] Jérémie Mary, Clément Calauzenes, and Noureddine El Karoui. Fairness-aware learning for continuous attributes and treatments. In *International Conference on Machine Learning*, pages 4382–4391. PMLR, 2019.

[24] Sina Baharlouei, Maher Nouiehed, Ahmad Beirami, and Meisam Razaviyayn. R\'enyi fair inference. *arXiv preprint arXiv:1906.12005*, 2019.

[25] Ray Jiang, Aldo Pacchiano, Tom Stepleton, Heinrich Jiang, and Silvia Chiappa. Wasserstein fair classification. In *Uncertainty in Artificial Intelligence*, pages 862–872. PMLR, 2020.

[26] Ricky TQ Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. *Advances in neural information processing systems*, 31, 2018.

[27] Rich Zemel, Yu Wu, Kevin Swersky, Toni Pitassi, and Cynthia Dwork. Learning fair representations. In *International conference on machine learning*, pages 325–333. PMLR, 2013.

[28] Alfréd Rényi. On measures of dependence. *Acta mathematica hungarica*, 10(3-4):441–451, 1959.

[29] Hans Gebelein. Das statistische problem der korrelation als variations-und eigenwertproblem und sein zusammenhang mit der ausgleichsrechnung. *ZAMM-Journal of Applied Mathematics and Mechanics/Zeitschrift für Angewandte Mathematik und Mechanik*, 21(6):364–379, 1941.

[30] Hermann O Hirschfeld. A connection between correlation and contingency. In *Mathematical Proceedings of the Cambridge Philosophical Society*, volume 31, pages 520–524. Cambridge University Press, 1935.

[31] David Lopez-Paz, Philipp Hennig, and Bernhard Schölkopf. The randomized dependence coefficient. *Advances in neural information processing systems*, 26, 2013.

[32] Harold Hotelling. Relations between two sets of variates. *Biometrika*, 28(3/4):321–377, 1936.

[33] Mohamed Ishmael Belghazi, Aristide Baratin, Sai Rajeshwar, Sherjil Ozair, Yoshua Bengio, Aaron Courville, and Devon Hjelm. Mutual information neural estimation. In *International conference on machine learning*, pages 531–540. PMLR, 2018.

[34] R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. *arXiv preprint arXiv:1808.06670*, 2018.

[35] Aaron Van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv e-prints*, pages arXiv–1807, 2018.

[36] Yanzhi Chen, Dinghuai Zhang, Michael Gutmann, Aaron Courville, and Zhanxing Zhu. Neural approximate sufficient statistics for implicit models. *arXiv preprint arXiv:2010.10079*, 2020.

[37] Ben Poole, Sherjil Ozair, Aaron Van Den Oord, Alex Alemi, and George Tucker. On variational bounds of mutual information. In *International Conference on Machine Learning*, pages 5171–5180. PMLR, 2019.

[38] Arthur Gretton, Kenji Fukumizu, Choon Teo, Le Song, Bernhard Schölkopf, and Alex Smola. A kernel statistical test of independence. *Advances in neural information processing systems*, 20, 2007.

[39] Francis R Bach and Michael I Jordan. Kernel independent component analysis. *Journal of machine learning research*, 3(Jul):1–48, 2002.

[40] Barnabás Póczos, Zoubin Ghahramani, and Jeff Schneider. Copula-based kernel dependency measures. *arXiv preprint arXiv:1206.4682*, 2012.

[41] Gábor J Székely and Maria L Rizzo. Partial distance correlation with methods for dissimilarities. *The Annals of Statistics*, 42(6):2382–2412, 2014.

[42] Pengyu Cheng, Weituo Hao, Shuyang Dai, Jiachang Liu, Zhe Gan, and Lawrence Carin. Club: A contrastive log-ratio upper bound of mutual information. In *International conference on machine learning*, pages 1779–1788. PMLR, 2020.

[43] Kimia Nadjahi, Alain Durmus, Lénaïc Chizat, Soheil Kolouri, Shahin Shahrampour, and Umut Simsekli. Statistical and topological properties of sliced probability divergences. *Advances in Neural Information Processing Systems*, 33:20802–20812, 2020.

[44] Ishan Deshpande, Ziyu Zhang, and Alexander G Schwing. Generative modeling using the sliced wasserstein distance. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3483–3491, 2018.

[45] Soheil Kolouri, Phillip E Pope, Charles E Martin, and Gustavo K Rohde. Sliced wasserstein auto-encoders. In *International Conference on Learning Representations*, 2018.

[46] Mark Rowland, Jiri Hron, Yunhao Tang, Krzysztof Choromanski, Tamas Sarlos, and Adrian Weller. Orthogonal estimation of wasserstein distances. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 186–195. PMLR, 2019.

[47] Yang Song, Sahaj Garg, Jiaxin Shi, and Stefano Ermon. Sliced score matching: A scalable approach to density and score estimation. In *Uncertainty in Artificial Intelligence*, pages 574–584. PMLR, 2020.

[48] Wenbo Gong, Yingzhen Li, and José Miguel Hernández-Lobato. Sliced kernelized stein discrepancy. *arXiv preprint arXiv:2006.16531*, 2020.

[49] Yilun Xu, Hao He, Tianxiao Shen, and Tommi S Jaakkola. Controlling directions orthogonal to a classifier. In *International Conference on Learning Representations*, 2021.

[50] Evgenii Chzhen, Christophe Denis, Mohamed Hebiri, Luca Oneto, and Massimiliano Pontil. Fair regression with wasserstein barycenters. *Advances in Neural Information Processing Systems*, 33:7321–7331, 2020.

[51] Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. *arXiv preprint arXiv:1711.00848*, 2017.

[52] Christopher P Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in β-vae. *arXiv preprint arXiv:1804.03599*, 2018.

[53] Irina Higgins, David Amos, David Pfau, Sebastien Racaniere, Loic Matthey, Danilo Rezende, and Alexander Lerchner. Towards a definition of disentangled representations. *arXiv preprint arXiv:1812.02230*, 2018.

[54] Robin Quessard, Thomas Barrett, and William Clements. Learning disentangled representations and group structure of dynamical environments. *Advances in Neural Information Processing Systems*, 33:19727–19737, 2020.

[55] Xinqi Zhu, Chang Xu, and Dacheng Tao. Commutative lie group vae for disentanglement learning. In *International Conference on Machine Learning*, pages 12924–12934. PMLR, 2021.

[56] Elliot Creager, David Madras, Jörn-Henrik Jacobsen, Marissa Weis, Kevin Swersky, Toniann Pitassi, and Richard Zemel. Flexibly fair representation learning by disentanglement. In *International conference on machine learning*, pages 1436–1445. PMLR, 2019.

[57] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The journal of machine learning research*, 17(1):2096–2030, 2016.

[58] Jiaming Song and Stefano Ermon. Understanding the limitations of variational mutual information estimators. In *International Conference on Learning Representations*, 2019.

[59] Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

[60] Loic Matthey, Irina Higgins, Demis Hassabis, and Alexander Lerchner. dsprites: Disentanglement testing sprites dataset. https://github.com/deepmind/dsprites-dataset/, 2017.

[61] Ralph Gross, Iain Matthews, Jeffrey Cohn, Takeo Kanade, and Simon Baker. Multi-pie. *Image and vision computing*, 28(5):807–813, 2010.

[62] Yu Tian, Xi Peng, Long Zhao, Shaoting Zhang, and Dimitris N Metaxas. Cr-gan: learning complete representations for multi-view generation. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence*, pages 942–948, 2018.