Distilled Gradient Aggregation: Purify Features for Input Attribution in the Deep Neural Network

Abstract

Measuring the attribution of input features toward the model output is one of the popular post-hoc explanations on the Deep Neural Networks (DNNs). Among various approaches to compute the attribution, the gradient-based methods are widely used to generate attributions, because of its ease of implementation and the model-agnostic characteristic. However, existing gradient integration methods such as Integrated Gradients (IG) suffer from (1) the noisy attributions which cause the unreliability of the explanation, and (2) the selection for the integration path which determines the quality of explanations. FullGrad (FG) is an another approach to construct the reliable attributions by focusing the locality of piece-wise linear network with the bias gradient. Although FG has shown reasonable performance for the given input, as the shortage of the global property, FG is vulnerable to the small perturbation, while IG which includes the exploration over the input space is robust. In this work, we design a new input attribution method which adopt the strengths of both local and global attributions. In particular, we propose a novel approach to distill input features using weak and extremely positive contributor masks. We aggregate the intermediate local attributions obtained from the distillation sequence to provide reliable attribution. We perform the quantitative evaluation compared to various attribution methods and show that our method outperforms others. We also provide the qualitative result that our method obtains object-aligned and sharp attribution heatmap.

1 Introduction

Deep Neural Networks (DNNs) are increasingly applied to many fields in human-life such as self-driving, medical predictions and time-series forecasts. Along with these improvements, the recent models get bigger and more complicated that humans cannot investigate and understand the internal decision mechanism of them. Identifying and analyzing the reasons for the model predictions are important because the malfunction or the groundless decision of the model can cause the critical problems. As an effort to provide the evidences on the decisions, the input attribution has been well-studied, especially in visual tasks. Input attribution method aims to measure how much each input feature contributes to the model prediction. Because the output of this method takes the form of heatmap to provide relative importance among input features, it helps to locate the appearance of human-level semantics in the input. Previous work also applies the attribution to debug the model by wiping out Clever Hans of DNNs [Lapuschkin *et al.*, 2019]. However, obtaining the trustful input attribution is still challenging because (1) the highly nonlinear structure of modern DNNs makes it difficult to correctly track the relationship between the input and the output, and (2) quantifying the reliability of attribution methods is non-trivial because the ground-truth is not available.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

(a) Distilled Gradient Aggregation (DGA)   (b) Modules (detailed)

Figure 1: An illustration of Distilled Gradient Aggregation (DGA) and details of modules included in the computation of DGA. DGA generates the discrete sequence of anchor points by distilling the input features. We identify that aggregating the local attributions along the distillation sequence provides the target class (*Dingo*) oriented attribution heatmap. The details are described in the Section 3.2

Gradient-based input attribution is one of the main techniques to derive the relationship between the model decision and the input features. The partial derivative of the output with respect to the input provides the measure of sensitivity, which is easily computed in DNNs. Integrated Gradients (IG) [Sundararajan *et al.*, 2017] is a commonly used gradient-based method, which provides the axiomatic properties to support the reliability of attributions. However, IG inheres the problem of noisy attribution, which originates from the gradient integrating path, and several variants of IG have been proposed to alleviate this issue [Smilkov *et al.*, 2017; Kapishnikov *et al.*, 2019, 2021; Pan *et al.*, 2021]. FullGrad (FG) [Srinivas and Fleuret, 2019] also raises the counter-intuitive behaviors of IG. FG avoids this problem by considering only the local gradients instead of the path integration and proposes to use the bias gradient. But FG is vulnerable to the small perturbation in the inputs due to its locality.

In this work, we provide the analysis on the weakness of (1) FG method which is unavoidable if it considers only single anchor point, and (2) IG method which the continuous path based gradient integration may fail to quantify the intuitive attribution. To complement the shortcomings of the two methods, we propose to aggregate the attribution from the multiple anchors. For the selection of anchor points, we devise an algorithm to sequentially distill the irrelevant features to generate the reliable attribution. The main contributions of our work are,

- Propose a novel feature distillation algorithm based on the intermediate local attribution to generate the sequence of meaningful anchor points.

- Devise Distilled Gradient Aggregation (DGA), an attribution method by aggregating the intermediate local attributions from the distilled input sequence to derive the reliable attribution.

- Qualitative and quantitative evaluations to validate the proposed method outperforms existing gradient-based attribution methods.

2 Related Work

Input attribution is one of the post-hoc explanation methods, which aims to identify the influence of each input feature to the model output on the trained model. There exists a considerable variety of techniques to derive the input attribution. With the property that the feature map obtained by the convolutional layers includes the spatial information, Class Activation Mapping (CAM) methods compute the attribution by the weighted sum of the feature maps [Zhou *et al.*, 2016; Selvaraju *et al.*, 2017]. Layer-wise Relevance Propagation (LRP) method propagates the model output backward to

Figure 2: Attribution heatmaps for the Gaussian noise perturbed images obtained by FullGrad (FG), Integrated Gradient (IG) and Ours. Heatmaps from FG shows inconsistent results while other two methods, which utilizes the global perspective for the attribution. Corresponding pixel perturbation scores also show that FG loses reliability against the simple noise perturbation. The procedure of pixel perturbation is described in Section 4.1

the input [Bach *et al.*, 2015; Nam *et al.*, 2020]. LRP extends the Taylor decomposition to the DNNs and distributes the relevance in layer-wise sense.

There are another approach by measuring the behavior of the model by perturbing the input features. Optimizing the input by gradient ascent gives an example which would maximally activates the target neuron [Erhan *et al.*, 2010; Nguyen *et al.*, 2016; Olah *et al.*, 2018]. Instead of maximizing the target neuron activation, Extremal Perturbation optimizes the mask which removes or reveals the part of the input to localize the attributed part of input [Fong *et al.*, 2019]. It is extended by using Integrated Gradients [Sundararajan *et al.*, 2017] for the optimization to make the optimization more stable [Qi *et al.*, 2019]. By collecting the pair of partially removed inputs and corresponding model ouptuts, training a linear model to resembles the mapping would give the feature importance in terms of linear weights [Ribeiro *et al.*, 2016]. Rather than training a new model, Randomized Input Sampling for Explanation (RISE) computes the attribution by aggregating multiple randomly masked inputs, weighted by the model outputs [Petsiuk *et al.*, 2018].

Based on Aumann-Shapley value [Aumann and Shapley, 2015], which is one solution of the fair distribution in the cooperative game theory, Integrated Gradients (IG) has been proposed [Sundararajan *et al.*, 2017]. IG is equipped with axiomatic properties which are desirable for the attribution methods. IG is computed by integrating gradients over the straight path from the predefined baseline to the input. As the attribution is corrupted by the noisy information along the path, alternatives for the different paths have been proposed [Smilkov *et al.*, 2017; Kapishnikov *et al.*, 2019, 2021]. FullGrad (FG) [Srinivas and Fleuret, 2019], which utilizes the bias-gradient, is proposed to suppress the counter-intuitive behavior of IG which is caused by the weak-dependency between the local linear regions.

3 Distilled Gradient Aggregation Method

In this section, we propose our gradient aggregation method, Distilled Gradient Aggregation (DGA). We first provide an example and analysis about the inconsistency observed by FullGrad, which uses a single anchor point to compute attributions. We also provide the counter-intuitive behavior of IG caused by the continuous gradient integration path. To complement both shortcomings, we propose an aggregation method, which ensembles the local attribution from the sequence of inputs. To reduce computational cost and reinforce the features that are in charge of the model decision, we suggest a sequential feature distillation algorithm, which distill irrelevant features from the input.

(a)   (b)   (c)   (d)

Figure 3: (a) Visualization of color coded logit values for trained f. (b) The linear regions which the trained network comprises. Each colored linear region corresponds to each piece-wise linear function. (c) Selected two linear regions (A and B) and the zero baseline. The dotted lines indicate the perturbations for x_1 axis in the same linear region. (d) Attribution of each method (IG and FG) for each linear region. We identify that for linear region A (include the baseline), the global attribution (IG) is same as the local ones (FG). However, for linear region B, the global and local attribution has different attributions for input samples.

3.1 Analyzing FG and IG on Simple Models

Assume we have the input vector $\mathbf{x}\in\mathbb{R}^2$ and a simple neural network f equipped with partial linear activation (e.g., ReLU). This network f can be regarded as the combination of piece-wise linear functions [Montufar *et al.*, 2014]. Each piece-wise linear function is only defined and feasible in corresponding linear region $\mathcal{R}^{(k)}$, where $\cup_k \mathcal{R}^{(k)} = \mathbb{R}^2$ and $\mathcal{R}^{(k_1)} \cap \mathcal{R}^{(k_2)} = \varnothing$ for any k_1 and k_2. Such piece-wise linear function is formulated as follow,

$$f(\mathbf{x}) = \begin{cases} \mathbf{w}^{(1)T}\mathbf{x} + \mathbf{b}^{(1)} & \mathbf{x} \in \mathcal{R}^{(1)} \\ \cdots \\ \mathbf{w}^{(K)T}\mathbf{x} + \mathbf{b}^{(K)} & \mathbf{x} \in \mathcal{R}^{(K)} \end{cases} \tag{1}$$

where $\mathbf{w}^{(k)}\in\mathbb{R}^2$ and $\mathbf{b}^{(k)}\in\mathbb{R}$ denote weight and bias of k-th linear region respectively. An illustrative example of the this function f is depicted in Figure 3[1].

Vulnerability of FullGrad FullGrad [Srinivas and Fleuret, 2019] suggests that the attribution should be same inside the same linear region $\mathcal{R}^{(k)}$, and this reduces the dependency between the attribution and the input $\mathbf{x}$. This property is introduced as *weak dependency*. However, such weak dependency derives the attribution to be vulnerable to the model perturbation. For example, let we have two inputs, $\mathbf{x}$ and $\mathbf{x}' = \mathbf{x} + \epsilon$, where ϵ be any small enough random perturbation. If we find any $\mathbf{x}$ and $\mathbf{x}'$, such that the model output is same, $f(\mathbf{x}) = f(\mathbf{x}')$, but the region is different, then the attribution on each input should be different. This can be visualized by the simple experiment by generating noise perturbed image $\mathbf{x} + \epsilon$ and measuring the attribution, where $\epsilon \sim N(0, \sigma)$. Figure 2 shows an example where the FullGrad generates inconsistent attribution along with the simple Gaussian noise is added.

Counter-intuitive behavior of IG To visualize the counter-intuitive behavior of IG, we select two linear regions (A, B) in Figure 3c and calculate the attribution in each region. In particular, we select a sequence of data from a (white dot) to b (green dot), which is only shifted in x_1 dimension. Figure 3d illustrates corresponding attribution for two selected linear regions. We observe that only attribution of x_1 changes for the sequence of region A in both IG and FG methods. However, for the sequence of region B, the IG attribution of both x_1 and x_2 changes at the same time, while FG attribution shows attribution change only in x_1. We conjecture this counter-intuitive behavior of IG emerges when the continuous path from the input to $\bar{\mathbf{x}}$ necessarily pass through the regions outside of B. Because in case of region A, which includes $\bar{\mathbf{x}}$, data in A do not required to pass through outside of A to compute IG. As each linear region corresponds to each linear function, passing through the multiple linear region means considering the combination among multiple functions to measure the attribution, which may cause the counter-intuitive attribution.

From these observations, we obtain two insights for the gradient-based attribution: (1) to avoid the vulnerability to the perturbations, considering multiple linear regions in a global view is necessary,

---

[1]The implementation details are described in the Appendix.

(a) The sequence $\tilde{\mathcal{X}}$ with WC mask.   (b) The sequence $\tilde{\mathcal{X}}$ with WC and EPC mask.

Figure 4: Distillation sequence $\tilde{\mathcal{X}}$ with WC mask and EPC mask for the target class *French horn* in the pre-trained VGG-16. The bottom row of (a) and (b) indicates the local attribution $\phi^{UFG}(\tilde{\mathbf{x}}(n))$ for each colored box of first row.

and (2) integrating through the straight continuous path induces the counter-intuitive attribution to explain the model output.

3.2   Sequential Feature Distillation

RISE [Petsiuk *et al.*, 2018]is one approach to alleviate observed issues described in the previous section. RISE aggregates the model output from multiple ablated inputs can be used to measure the importance of each ablated features. However, randomized ablation includes the stochastic process which requires expensive computational cost to achieve reliable attribution. To reduce the computation burden and reinforce the relationship with the important features, we propose the sequential feature distillation algorithm to obtain a sequence of ablated inputs, the sequence of inputs $\tilde{\mathcal{X}} = [\tilde{\mathbf{x}}(0), \tilde{\mathbf{x}}(1), \tilde{\mathbf{x}}(2), \cdots]$, where the irrelevant features are distilled. Motivated by previous work that masking out the irrelevant features using IG [Fong *et al.*, 2019; Qi *et al.*, 2019], we propose to distill the impurities by using the intermediate local attribution obtained along the sequence.

For reliable local attribution, FG proposes the bias gradient with post processing $\Psi(\cdot)$ which includes the normalization and upsampling. As $\Psi(\cdot)$ suggested by FG is usually over-estimated by the bias gradient in deeper layers [Grabska-Barwinska *et al.*, 2021], we redefine $\Psi(\cdot)$ as uniformly distributing function for the bias gradient to alleviate the over-estimation problem.

$$\Psi_u\left(\mathbf{v}\right) = \frac{\mathbf{v}^T \mathbb{1}^{\dim(\mathbf{v})}}{\dim(\mathbf{x})} \mathbb{1}^{\dim(\mathbf{x})} \tag{2}$$

where $\mathbb{1}^d$ denotes a d-dimensional all-ones vector. We call FG with redefined post-processing $\Psi(\cdot)$ as Uniform FullGrad (UFG), $\phi^{UFG}(\cdot)$. Then we use UFG as the intermediate local attribution method throughout the remained paper.

In the sequence $\tilde{\mathcal{X}}$, the relation between n and $n+1$-th ablated input is formalized as,

$$\tilde{\mathbf{x}}(n+1) = \mathcal{M}(\tilde{\mathbf{x}}(n)) \odot \tilde{\mathbf{x}}(0) \tag{3}$$

where $\tilde{\mathbf{x}}(0) = \mathbf{x}$ and $\mathcal{M}(\cdot)$ is a mask extractor. To distill off the uninformative features, we build a mask to zero out the features with low magnitude of local attribution. We define this mask extractor as the Weak Contributor (WC) mask, $\mathcal{M}^{WC}$. The level of the WC mask increases along the distillation sequence $\mathcal{X}$ with the pre-defined number of steps N and finally the entire pixels become zero (i.e., $\tilde{\mathbf{x}}(N) = 0$). We define $\mathcal{M}_j^{WC}(\cdot)$ for each feature j as,

$$\mathbb{S}_j^{WC}(\mathbf{x}) = \left\{ k \middle| \ \left|\phi_k^{UFG}(\mathbf{x})\right| \leq \left|\phi_j^{UFG}(\mathbf{x})\right| \right\} \tag{4}$$

$$\mathcal{M}_j^{WC}(\mathbf{x}, n; N) = \begin{cases} 0 & \text{if } \frac{|\mathbb{S}_j^{WC}(\mathbf{x})|}{dim(x)} \leq \frac{n}{N} \\ 1 & \text{otherwise} \end{cases} \tag{5}$$

where $\mathbb{S}_j^{WC}(\mathbf{x})$ is a set of feature indices that the magnitude of corresponding local attribution is smaller than $|\phi_j^{UFG}(\mathbf{x})|$. Practically, $\mathcal{M}_j^{WC}(x, n; N)$ can be equivalently derived by thresholding with n/N quantile of absolute local attributions. To implement the smooth change of features, we

---
Algorithm 1 Distilled Gradient Aggregation

Input: Model f, Input $\mathbf{x}$
Parameter: # of steps N, EPC threshold q, Negative scale β
Output: Attribution $\phi^{DGA}(\mathbf{x})$
1: Let $\tilde{\mathbf{x}}(0) = \mathbf{x}$, $\Phi = \emptyset$
2: **for** n **in** $\{0 \ldots N\}$ **do**
3:    $\Phi = \Phi \cup \{\phi^{UFG}(\tilde{\mathbf{x}}(n))\}$
4:    $\mathcal{M} = \frac{n}{N}\mathcal{M}^{WC}(\tilde{\mathbf{x}}(n), n; N) + (1 - \frac{n}{N})\mathcal{M}^{EPC}(\tilde{\mathbf{x}}(n); q)$
5:    $\tilde{\mathbf{x}}(n + 1) = \tilde{\mathbf{x}}(0) \odot \mathcal{M}$
6: **end for**
7: $\phi^{DGA}(\mathbf{x}) = \sum_{\phi \in \Phi} (\max(\phi, 0) + \beta \cdot \min(\phi, 0))$
8: **return** $\phi^{DGA}(\mathbf{x})$
---

gradually apply the mask with the scale factor proportional to the current step n. The sequential relation with WC mask is defined as,

$$\tilde{\mathbf{x}}(n+1) = \frac{n}{N}\mathcal{M}^{WC}(\tilde{\mathbf{x}}(n), n; N) \odot \tilde{\mathbf{x}}(0). \tag{6}$$

Figure 4 (a) depicts the sequence of distilled inputs $\tilde{\mathcal{X}}$ with WC mask. We can identify that the distillation by WC mask can remove the uninformative information (e.g., human body) to predict the object class, *French horn*.

However, we observe that considering only WC mask can reassign the same attributions to the same pixels, which makes the overall attribution to be saturated. In Figure 4 (a), the human face (red box) remains until the end of the distillation with strong attribution. We identify that when the strong local attribution is assigned temporarily to irrelevant features, WC mask is hard to distill these features in remaining steps. The saturated distillation sequence $\tilde{\mathcal{X}}$ disturbs the strength of multiple ablated inputs to build reliable attribution. We conjecture that this phenomenon is caused when the noise exists in the gradient or the value of feature itself is too large, the pixels can have extremely high contribution although the pixels do not have relevant information to predict the target class.

We define additional mask to reduce the saturation by filtering out features with extremely strong attribution. We call this mask as Extreme Positive Contributor (EPC) mask $\mathcal{M}^{EPC}(\cdot)$ and it is formulated as,

$$\mathbb{S}_j^{EPC}(\mathbf{x}) = \left\{ k \,\middle|\, \phi_k^{UFG}(\mathbf{x}) \leq \phi_j^{UFG}(\mathbf{x}) \right\} \tag{7}$$

$$\mathcal{M}_j^{EPC}(\mathbf{x}; q) = \begin{cases} 1 & \text{if } \frac{|\mathbb{S}_j^{EPC}(\mathbf{x})|}{dim(\mathbf{x})} \leq q \\ 0 & \text{otherwise .} \end{cases} \tag{8}$$

where q is EPC threshold to control the ratio of ablation. Finally, we combine two masks for our distillation algorithm with relative weights w.r.t. the current step n as,

$$\tilde{\mathbf{x}}(n + 1) = \left(\frac{n}{N}\mathcal{M}^{WC}(\tilde{\mathbf{x}}(n), n; N) + (1 - \frac{n}{N})\mathcal{M}^{EPC}(\tilde{\mathbf{x}}(n); q) \right) \odot \tilde{\mathbf{x}}(0) \tag{9}$$

We note that in early distillation step, EPC mask takes high weight to reduce saturation at too highly attributed feature. In the late stage, WC mask gains high weight to remain the relevant features. The distillation sequence $\tilde{\mathcal{X}}$ with WC and EPC masks is shown in Figure 4 (b). We identify that using both WC and EPC masks removes irrelevant features (red box) and iteratively assign the attribution to relevant features (blue box).

3.3 Attribution Aggregation

With N distillation steps, we obtain N local attributions. The remaining question is how to aggregate these local attributions to acquire the final attribution. Likewise previous studies [Selvaraju *et al.*,

Table 1: Comparison of various attribution methods with LeRF and MoRF on three models.

		G*I	GBP	IG	FG	GIG	DGA
LeRF (↑ is better)	VGG-16	0.078	0.094	0.096	0.415	0.110	**0.434**
	ResNet-18	0.171	0.145	0.243	0.558	0.255	**0.691**
	Inception-V3	0.114	0.124	0.158	0.448	0.185	**0.533**
MoRF (↓ is better)	VGG-16	0.045	0.113	0.036	0.110	0.029	**0.023**
	ResNet-18	0.105	0.162	0.066	0.175	0.061	**0.041**
	Inception-V3	0.050	0.145	0.038	0.131	0.029	**0.019**

2017; Kindermans *et al.*, 2018; Bach *et al.*, 2015], we desire to take the positive contribution from each local attribution. Thus, we take the ReLU before the aggregation.

$$\phi^{DGA}(\mathbf{x}) = \frac{1}{Z} \sum_{n=1}^{N} \mathrm{ReLU}(\phi^{UFG}(\tilde{\mathbf{x}}(n))). \tag{10}$$

Finally, we call the unification of preceding modules as Distilled Gradient Aggregation (DGA) method. DGA method consist of the distillation algorithm with WC and EPC mask to generate the ablated inputs to achieve the local attribution, and the aggregation process considering features with the positive and the negative attributions. The illustration of the overall structure is depicted in Figure 1 and pseudo code is provided in Algorithm 1.

4 Experiments

In this section, we validate the effectiveness of DGA by both quantitative and qualitative comparison. We first provide the quantitative comparison using two metrics: (1) pixel perturbation [Samek *et al.*, 2017], and (2) RemOve-And-Retrain (ROAR) [Hooker *et al.*, 2019] to verify the proposed method can assign more model-relevant attribution. Then we provide the qualitative comparison among different attribution methods. In the following experiments, we set the hyperparameters for DGA as $N{=}30$, $q{=}0.9$ and $\beta{=}0$ with simple grid search. The details for the hyperparameter exploration is available in Appendix. We select various gradient-based attribution methods as the baselines: Gradient*Input (G*I), Guided BackPropagation (GBP), Integrated Gradients (IG), FullGrad (FG), and GuidedIG (GIG).

4.1 Pixel Perturbation

Pixel perturbation is widely used method to benchmark the attribution methods if they correctly capture the relevance between the input features and the model output. To quantify the relevance between the input features and the model output, pixel perturbation method removes the pixel values in order of relevance obtained by attribution methods. Then it measures the change of softmax output for the target class with the perturbation. There is two orders of removal, Most-Relevant-First (MoRF) to remove the pixels with top $k\%$ relevance and Least-Relevant-First (LeRF) to remove the pixels with bottom $k\%$ relevance. If input feature is actually highly related to the model prediction, the softmax output should decrease steeply when it is removed. Thus, MoRF is better if it is lower. In the same manner, higher LeRF is better.

We use 50k images of the validation set provided by ImageNet [Russakovsky *et al.*, 2015]. We use three publicly available pre-trained models: VGG-16 [Simonyan and Zisserman, 2015], Inception-v3 [Szegedy *et al.*, 2016], ResNet-18 [He *et al.*, 2016]. Table 1 indicates MoRF and LeRF results for the various attribution methods and model architectures. We identify that DGA shows the best performance in both MoRF and LeRF measure on entire architectures.

4.2 RemOve-And-Retrain (ROAR)

ROAR is another metric to evaluate how well the attribution method captures the relevance of feature in the perspective of the model training. ROAR is performed by measuring the performance of the

Figure 5: Qualitative comparison among various attribution methods for VGG-16 in the validation dataset of ImageNet. Upper rows describe the heatmaps obtained by each methods and lower rows shows top 10% most relevant input features. DGA generates sharp and object-oriented attribution heatmap in the almost examples. See more examples in Appendix.

re-trained model with inputs modified according to relative ordering of the attribution. Each input in the dataset is modified by removing pixels with top $k\%$ attribution and replacing them with the average pixel value of the input. We perform ROAR experiment with simple CNN (6 Conv + 3 Linear) trained on 50k images of training set provided by CIFAR-10 dataset [Krizhevsky *et al.*, 2009] using Adam optimizer with learning rate 3e-4 and 100 epochs. After training, the performance of the model is quantified using the standard test dataset with 10k images. We note that the attribution method captures more relevant features if the test accuracy is lower. We provide the average performance over 10 trials for each attribution method, where the parameters are random initialized at each trial and fixed between attribution methods. Figure 6 shows the test accuracy measure in the ROAR experiment for each attribution method. The result indicates that the model trained on the modified

dataset with DGA steeply decreases the test accuracy even with 10% removed. We conclude that
DGA can extract the features which are relevant to training procedure in DNNs.

Figure 6: Comparison of ROAR experiment results on CIFAR-10 dataset among various attribution
methods. The test accuracy for corresponding the percentage of removal.

4.3 Qualitative comparison

We qualitatively compare the various attribution methods by visualizing the attribution heatmap and
top 10% most relevant feature at the same time. In Figure 5, we provide the result of randomly
selected images from the validation set of ImageNet with the pre-trained VGG-16. We can identify
that the attributions are more aligned the object comparing other methods. For example, in the
right-top row, DGA focuses the person who grabs a paddle while almost methods distribute the
relevant pixels to sky and ocean. Although FG concentrates to the person, the relevant patch has less
sharp than patch of DGA. We provide more examples and results for different models in Appendix.

5 Discussion

In this paper, we propose a novel gradient-based attribution method, Distilled Gradient Aggregation
(DGA). We provide the vulnerability of FG against the input perturbation and the counter-intuitive
behavior of IG due to the continuous integration path. To complement the weakness of both methods,
we propose the gradient aggregation method along the distillation sequence that generates the impurity
distilled inputs. Our method obtains high quality attributions with its sharpness and object-alignment,
and we verify the method through pixel perturbation and ROAR evaluation metrics. We believe that
our DGA method can be broadly applied to explain a decision of various DNNs.

Broader Impact Transparency of deep models is a matter of the highest priority for the application
of such models in the real world, e.g., medical diagnosis [Caruana *et al.*, 2015] and autonomous
driving [Yurtsever *et al.*, 2020]. We believe that providing the evidence which is well-aligned with
the model decision would help the users of such applications to place great trust and the developers
to improve or fix the model for better performance. Discovering unintended biases in the model is
another issue [Stock and Cisse, 2018]. Such biases may occur from the dataset [Kim *et al.*, 2018]
or the model itself. Identifying the root cause and removing such biases would be another expected
future work, beyond the explanation on the input features.

Limitation Although our method has empirically outperformed in qualitative comparison and various
quantitative experiments compared to previous work, the notion of better input attribution method
is still vague. In this work, we adaptively find the sequence of inputs by using local attribution, but
there would exist better justification of the sequence or the set of inputs that are essential clues for
identifying the core features in the input.

References

Robert J Aumann and Lloyd S Shapley. *Values of non-atomic games*. 2015.

Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus-Robert Müller, and Wojciech Samek. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 2015.

Rich Caruana, Yin Lou, Johannes Gehrke, Paul Koch, Marc Sturm, and Noemie Elhadad. Intelligible models for healthcare: Predicting pneumonia risk and hospital 30-day readmission. In *Proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining*, pages 1721–1730, 2015.

D. Erhan, Aaron C. Courville, and Yoshua Bengio. Understanding representations learned in deep architectures. 2010.

Ruth Fong, Mandela Patrick, and Andrea Vedaldi. Understanding deep networks via extremal perturbations and smooth masks. *ICCV*, 2019.

Agnieszka Grabska-Barwinska, Amal Rannen-Triki, Omar Rivasplata, and András György. Towards better visual explanations for deep image classifiers. In *eXplainable AI approaches for debugging and diagnosis.*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Sara Hooker, D. Erhan, Pieter-Jan Kindermans, and Been Kim. A benchmark for interpretability methods in deep neural networks. In *NeurIPS*, 2019.

Andrei Kapishnikov, Tolga Bolukbasi, Fernanda Viégas, and Michael Terry. Xrai: Better attributions through regions. In *ICCV*, 2019.

Andrei Kapishnikov, Subhashini Venugopalan, Besim Avci, Ben Wedin, Michael Terry, and Tolga Bolukbasi. Guided integrated gradients: An adaptive path method for removing noise. In *CVPR*, 2021.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *ICML*, 2018.

Pieter-Jan Kindermans, Kristof T Schütt, Maximilian Alber, Klaus-Robert Müller, Dumitru Erhan, Been Kim, and Sven Dähne. Learning how to explain neural networks: Patternnet and patternattribution. In *ICLR*, 2018.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Sebastian Lapuschkin, Stephan Wäldchen, Alexander Binder, Grégoire Montavon, Wojciech Samek, and Klaus-Robert Müller. Unmasking clever hans predictors and assessing what machines really learn. *Nature Communications*, 2019.

Guido F Montufar, Razvan Pascanu, Kyunghyun Cho, and Yoshua Bengio. On the number of linear regions of deep neural networks. *Advances in neural information processing systems*, 27, 2014.

Woo-Jeoung Nam, Shir Gur, Jaesik Choi, Lior Wolf, and Seong-Whan Lee. Relative attributing propagation: Interpreting the comparative contributions of individual units in deep neural networks. In *AAAI*, 2020.

Anh Nguyen, Alexey Dosovitskiy, Jason Yosinski, Thomas Brox, and Jeff Clune. Synthesizing the preferred inputs for neurons in neural networks via deep generator networks. *NeurIPS*, 2016.

Chris Olah, Arvind Satyanarayan, Ian Johnson, Shan Carter, Ludwig Schubert, Katherine Ye, and Alexander Mordvintsev. The building blocks of interpretability. *Distill*, 2018.

Deng Pan, Xin Li, and Dongxiao Zhu. Explaining deep neural network models with adversarial gradient integration. In *IJCAI*, 2021.

Vitali Petsiuk, Abir Das, and Kate Saenko. RISE: randomized input sampling for explanation of black-box models. In *BMVC*, 2018.

Zhongang Qi, Saeed Khorram, and Fuxin Li. Visualizing deep networks by optimizing with integrated gradients. In *CVPR Workshops*, volume 2, 2019.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Why should i trust you?: Explaining the predictions of any classifier. In *ACM SIGKDD*. ACM, 2016.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 2015.

Wojciech Samek, Alexander Binder, Grégoire Montavon, Sebastian Lapuschkin, and Klaus-Robert Müller. Evaluating the visualization of what a deep neural network has learned. *IEEE Transactions on Neural Networks and Learning Systems*, 2017.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *ICCV*, 2017.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. 2015.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda Viégas, and Martin Wattenberg. Smoothgrad: removing noise by adding noise. *arXiv preprint arXiv:1706.03825*, 2017.

Suraj Srinivas and François Fleuret. Full-gradient representation for neural network visualization. *Advances in neural information processing systems*, 32, 2019.

Pierre Stock and Moustapha Cisse. Convnets and imagenet beyond accuracy: Understanding mistakes and uncovering biases. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 498–512, 2018.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *ICML*. PMLR, 2017.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *CVPR*, 2016.

Ekim Yurtsever, Jacob Lambert, Alexander Carballo, and Kazuya Takeda. A survey of autonomous driving: Common practices and emerging technologies. *IEEE access*, 8:58443–58469, 2020.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2921–2929, 2016.