Multiplicative Filter Networks

Rizal Fathony[*]
Bosch Center for Artificial Intelligence
Pittsburgh, PA
rizal@fathony.com

Anit Kumar Sahu[*†]
Amazon Alexa AI
Seattle, WA
anit.sahu@gmail.com

Devin Willmott[*]
Bosch Center for Artificial Intelligence
Pittsburgh, PA
devin.willmott@us.bosch.com

J. Zico Kolter
Bosch Center for Artificial Intelligence
Carnegie Mellon University
Pittsburgh, PA
zkolter@cs.cmu.edu

Abstract

Although deep networks are typically used to approximate functions over high dimensional inputs, recent work has increased interest in neural networks as function approximators for low-dimensional-but-complex functions, such as representing images as a function of pixel coordinates, solving differential equations, or representing signed distance functions or neural radiance fields. Key to these recent successes has been the use of new elements such as sinusoidal nonlinearities or Fourier features in positional encodings, which vastly outperform simple ReLU networks. In this paper, we propose and empirically demonstrate that an arguably simpler class of function approximators can work just as well for such problems: multiplicative filter networks. In these networks, we avoid traditional compositional depth altogether, and simply multiply together (linear functions of) sinusoidal or Gabor wavelet functions applied to the input. This representation has the notable advantage that the entire function can simply be viewed as a linear function approximator over an exponential number of Fourier or Gabor basis functions, respectively. Despite this simplicity, when compared to recent approaches that use Fourier features with ReLU networks or sinusoidal activation networks, we show that these multiplicative filter networks largely outperform or match the performance of these approaches on the domains highlighted in these past works.

1 Introduction

Neural networks are most commonly used to approximate functions over high-dimensional input spaces, such as functions that operate on images or long text sequences. However, there has been a recent growing interest in neural networks used to approximate low-dimensional-but-complex functions: for example, one could represent a continuous image as a function $f : \mathbb{R}^2 \to \mathbb{R}^3$ where the input to this function specifies (x, y) coordinates of a location in the image, and the output specifies the RGB value of the pixel at that location. However, two recent papers in particular have argued that specific architectural changes are required to make (fully-connected) deep networks suitable to this task: Sitzmann et al. (2020) employ sinusoidal activation functions within a multi-layer networks (called the SIREN architecture); and Tancik et al. (2020) propose random Fourier features input to a traditional ReLU-based network. Both papers show that the resulting networks can approximate these low-dimensional functions much better than simple feedforward ReLU networks, and achieve striking results in representing fairly complex functions (e.g. 3D signed distance fields or neural radiance fields) with a high degree of fidelity. However, the precise benefit of sinusoidal bases or a first layer of Fourier features seems difficult to characterize, and it remains unclear why such representations work well for these tasks.

---

[*]The first three authors contributed equally.
[†]Work done while at Bosch Center for Artificial Intelligence.

In this paper, however, we argue and empirically demonstrate that an arguably simpler class of functions can work as well or better than these previously-proposed networks on this task. Specifically, we propose an architecture we call the *multiplicative filter network* (MFN). Unlike a traditional multi-layer network that achieves representation power through compositional depth, the MFN instead simply repeatedly applies nonlinear filters (such as a sinusoid or a Gabor wavelet function) to the network's input, then multiplies together linear functions of these features. The notable advantage of this representation that, owing to the multiplicative properties of Fourier and Gabor filters, the entire function is ultimately just a linear function of (an exponential number of) these Fourier or Gabor features of the input. Indeed, we can express the exact linear form of these MFNs, which can make their analysis considerably simpler than that for deep networks, where compositions of nonlinear activation's make the entire function difficult to characterize.

In this work, we show that despite this simplicity, the proposed networks often perform as well or better than the previously proposed SIREN or Fourier feature networks. Specifically, we compare our approach on networks with comparable numbers of parameters to the exact benchmarks proposed in the SIREN and Fourier features papers. We show that MFNs achieve better performance deltas when increasing the depth or width of the networks. Despite this, we do emphasize that SIREN networks, in particular, appear to retain some notable advantages over MFNs, such as a bias towards smoother regions in the represented function and its gradients. However, especially given the fact that MFNs ultimately just correspond to a linear Fourier or Wavelet representation of a low-dimensional function, we believe they should be considered a standard benchmark for future work on such problems, to indicate where the compositional depth of typical deep networks can propose a substantial benefit.

2 BACKGROUND AND RELATED WORK

Our approach is related to many previous works in Fourier and Wavelet transforms, random Fourier features, and implicit neural representations. We explore the connection among the areas below.

Fourier and Wavelet transforms. Transforming time or space domain signals to frequency domain using transforms such as Fourier and Wavelet transforms have been at the heart of many developments in image processing, signal processing, and computer vision. In particular, the Fourier transform (Bracewell & Bracewell, 1986; Vetterli et al., 2014) and its various forms have found usage in myriad applications, such as spectroscopy, quantum mechanics, signal processing. Wavelet transforms, which in particular aid in multi-scale analysis, have been found to be particularly useful in data compression, JPEG2000 (Rabbani, 2002) being one example.

Random Fourier features. A seminal work by Rahimi & Recht (2008) demonstrates the power of Fourier transform in machine learning applications. They show that simply projecting the original dataset into random Fourier bases vastly improves the expressiveness of models as it approximates kernel computations. Many subsequent works apply the Fourier features and variations (Rahimi & Recht, 2009; Le et al., 2013; Yu et al., 2016) to improve machine learning algorithm performance in many domain areas, including classification (Sun et al., 2018; Rawat et al., 2019), regression (Avron et al., 2017; Brault et al., 2016), clustering (Chitta et al., 2012; Liu et al., 2019), online learning (Lin et al., 2014; Hu et al., 2015), and deep learning (Xue et al., 2019; Mehrkanoon & Suykens, 2018; Rick Chang et al., 2016; Mairal et al., 2014; Jacot et al., 2018; Tancik et al., 2020).

Implicit neural representations. A recent line of work in representing signals as a continuous function parameterized by neural network (instead of using the traditional discrete representation) is gaining popularity. This strategy has been used to represent different objects such as images (Nguyen et al., 2015; Stanley, 2007), shapes (Park et al., 2019; Genova et al., 2019; Chen & Zhang, 2019; Chabra et al., 2020), scenes (Mildenhall et al., 2020; Sitzmann et al., 2019; Jiang et al., 2020; Niemeyer et al., 2020), and textures (Oechsle et al., 2019; Henzler et al., 2020). In most of these applications, the standard neural networks architecture with multi-layer perceptrons and ReLU activation function is often used. Recently, motivated by the success of Fourier transform in machine learning, a few papers have suggested architectural changes that integrate periodic nonlinearities into the network. Mildenhall et al. (2020); Zhong et al. (2020); Tancik et al. (2020) proposed the use of sinusoidal mapping of the input features (Rahimi & Recht, 2008) that uses positional encoding and Gaussian random distribution in the mapping. Others (Klocek et al., 2019; Sitzmann et al., 2020) have proposed the use of sinusoidal activation function within a multi-layer perceptron architecture.

Both of these strategies are demonstrated to vastly improve the results on many object representation tasks.

3 Multiplicative filter networks

A traditional k-layer deep network $f : \mathbb{R}^n \to \mathbb{R}^m$ is typically defined by a recurrence such as:

$$z^{(1)} = x$$
$$z^{(i+1)} = \sigma\left(W^{(i)} z^{(i)} + b^{(i)}\right), \ i = 1, \ldots, k-1 \tag{1}$$
$$f(x) = W^{(k)} z^{(k)} + b^{(k)}$$

where σ denotes a nonlinearity applied elementwise, $W^{(i)} \in \mathbb{R}^{d_{i+1} \times d_i}$ and $b^{(i)} \in \mathbb{R}^{d_{i+1}}$ denote the weight and bias of the ith layer, and $z^{(i)} \in \mathbb{R}^{d_i}$ denotes the hidden unit at layer i. We refer to these networks as compositional depth networks, because each nonlinearity is applied compositionally to outputs of the previous nonlinearity in order to achieve its representational complexity.

The SIREN or Fourier feature networks of (Sitzmann et al., 2020) and Tancik et al. (2020) respectively can be viewed as simple specializations of this structure. In a SIREN network, one uses the sinusoid $\sigma(x) = \sin(x)$ as the nonlinearity, plus proper initialization of the weights and scaling of the input. In a Fourier features network, one replaces the input layer with

$$z^{(1)} = \left[\begin{array}{c} \sin(\Omega x + \phi) \\ \cos(\Omega x + \phi) \end{array}\right] \tag{2}$$

where $\Omega \in \mathbb{R}^{\frac{d_1}{2} \times n}$ is matrix of random $\mathcal{N}(0, \tau^2)$ variables (τ being a hyperparameter of the method), but with the typical ReLU nonlinearities $\sigma(x) = \mathrm{ReLU}(x)$.

Our proposed *multiplicative filter network*, in contrast, uses a different recursion that never results in composition of nonlinear functions. Specifically, an MFN is defined via the following recursion

$$z^{(1)} = g\left(x; \theta^{(1)}\right)$$
$$z^{(i+1)} = \left(W^{(i)} z^{(i)} + b^{(i)}\right) \circ g\left(x; \theta^{(i+1)}\right), \ i = 1, \ldots, k-1 \tag{3}$$
$$f(x) = W^{(k)} z^{(k)} + b^{(k)}$$

where $\circ$ denotes elementwise multiplication, $W^{(i)}$, $b^{(i)}$, $z^{(i)}$ are all defined as above, but where $g : \mathbb{R}^n \to \mathbb{R}^{d_i}$ is parameterized by parameters $\theta^{(i)}$ (the size of $\theta^{(i)}$ can vary to implicitly define the output dimensions d_i) and denotes a *nonlinear filter* applied to the input directly. Of immediate importance here is that in such a network, we never apply a nonlinearity to the output of a previous nonlinearity. All the nonlinearity of the network occurs within the g functions; layers $z^{(i)}$, after passing through a linear function, are simply multiplied by new filters of the input. This results in a considerably different type of function that is currently employed by most multi-layer networks, and indeed it is largely only by convention that we refer to such a function as a "network" at all.

We now present two instantiations of the MFN, using sinusoids or a Gabor wavelet as the filter g; we call these two networks the FourierNet and GaborNet respectively. As we show, the crucial property of a function f represented by a FourierNet or GaborNet is that the entire function f can also be written as a linear combination of sinusoids and Gabor wavelets of the input respectively (albeit an exponentially large number of such features, but of course also with a highly reduced space of allowable coefficients on this exponential number of terms, since there are only a polynomial number of parameters that define the MFN). Thus, we would claim that the MFN really looks more like a (rich) Fourier or Wavelet representation of the underlying signal, just one that happens to have a similar parameterization as deep networks (and which can be tuned by typical gradient descent methods).

3.1 Multiplicative Fourier Networks

As our first instantiation of the MFN, we consider using a simple sinusoidal filter

$$g(x; \theta^{(i)}) = \sin(\omega^{(i)} x + \phi^{(i)}) \tag{4}$$

with parameters $\theta^{(i)} = \{\omega^{(i)} \in \mathbb{R}^{d_i \times n}, \phi^{(i)} \in \mathbb{R}^{d_i}\}$. We term such a network the FOURIERNET, as the sinusoidal activation (with arbitrary phase shifts, to represent sine or cosine functions equally) corresponds naturally to a Fourier random feature representation of the entire function.

An immediate and compelling feature of the FOURIERNET, compared to networks based upon composition, is that its output can be directly viewed as a linear function of (an exponential number of) Fourier bases, with a low-rank set of coefficients determined by the parameters of the network. This is conveyed by the following theorem.

Theorem 1. *The output of a Fourier Network is given by a linear combination of sinusoidal bases,*

$$f_j(x) = \sum_{t=1}^{T} \bar{\alpha}_t \sin(\bar{\omega}_t x + \bar{\phi}_t) + \bar{b}, \tag{5}$$

for some coefficients $\bar{\alpha}_{1:T}$, frequencies $\bar{\omega}_{1:T}$, phase offsets $\bar{\phi}_{1:T}$, and bias term $\bar{b}$.

In other words, the FOURIERNET represents its final function as a linear combination of traditional Fourier bases, just as do "classical" random Fourier features, for instance. The key element of the proof (given in the appendix) is the fact that for two Fourier filters, with parameters ω, ϕ and τ, ψ respectively, their elementwise product can be transformed to a *sum* of the same type of filters

$$\sin(\omega x + \phi) \circ \sin(\tau x + \psi) = \frac{1}{2}\cos\left((\omega - \tau)x + \phi - \psi\right) - \frac{1}{2}\cos\left((\omega + \tau)x + \phi + \psi\right) \tag{6}$$

(note that the cosine can be expressed as a sine with a separate phase offset). Moreover, an inspection of the proof also lets us compute the exact coefficients of the linear expansion, as a function of the network parameters. This is shown in the following corollary.

Corollary 1. *Let $i_1, i_2, \ldots, i_{k-1}$ range over all $\prod_{j=1}^{k-1} d_j$ possible indices of each hidden unit of each layer of an MFN, and let $s_2, \ldots, s_k \in \{-1, +1\}$ range over all 2^{k-1} possible binary signs; then the expansion of $z_{i_k}^{(k)}$ from (2) is given by all the terms*

$$\begin{aligned}
\bar{\alpha} &= \left\{ \frac{1}{2^{k-1}} W_{i_k, i_{k-1}}^{(k-1)} \ldots W_{i_3, i_2}^{(2)} W_{i_2, i_1}^{(1)} \right\} \\
\bar{\omega} &= \left\{ s_k \omega_{i_k}^{(k)} + \ldots + s_2 \omega_{i_2}^{(2)} + \omega_{i_1}^{(1)} \right\} \\
\bar{\phi} &= \left\{ s_k \phi_{i_k}^{(k)} + \ldots + s_2 \phi_{i_2}^{(2)} + \phi_{i_1}^{(1)} + \frac{\pi}{2} \sum_{i=2}^{k} s_k \right\}.
\end{aligned} \tag{7}$$

with a similar form for terms that begin at the $i > 1$ layer, multiplied by the corresponding $b_{i_j}^{(j)}$ term.

This corollary follows simply by inspection of the proof in the appendix, noting that each additional multiplicative layer creates both a positive and negative combination of frequencies in the sinusoid terms, and a multiplication of the corresponding entries of W. In other words, the multiplicative "depth" of the FOURIERNET allows it to represent an exponential number of sinusoidal functions, but with the constraint that the actual number of coefficients on these features is given by a "low-rank" tensor consisting mainly of the coefficients in the W matrices. This expansion also suggests a method for initializing parameters specific to this network in a manner that scales appropriately with the network size. Specifically, however $W^{(i)}$s are initialized (typically random uniform or Gaussian, though here with an additional scaling factor that depends on the relative scale of the input), one should divide these terms by $\sqrt{k}$, to ensure that the variance of the final frequency ω_t is independent of the number of layers.

3.2 MULTIPLICATIVE GABOR NETWORKS

A well-known deficiency of the pure Fourier bases is that they have global support, and thus may have difficulty representing more local features. A common alternative to these bases is the use of Gabor filter to capture both a frequency and spatial locality component. Specifically, we consider a Gabor filter of the form

$$g_j(x; \theta^{(i)}) = \exp\left(-\frac{\gamma_j^{(i)}}{2} \left\| x - \mu_j^{(i)} \right\|_2^2 \right) \sin\left(\omega_j^{(i)} x + \phi_j^{(i)}\right) \tag{8}$$

Figure 1: Left: Performance of various models on an image representation task (top row) and three frames from a video representation task (remaining rows). Leftmost column shows ground truth. Right: PSNR of each model in the image reconstruction task for the first 1000 training iterations.

with parameters $\theta^{(i)} = \left\{ \gamma_{1:d_i}^{(i)} \in \mathbb{R}, \mu_{1:d_i}^{(i)} \in \mathbb{R}^n, \omega_{1:d_i}^{(i)} \in \mathbb{R}^n, \phi_{1:d_i}^{(i)} \in \mathbb{R} \right\}$ (here $\mu_j^{(i)}$ denotes the mean of the jth Gabor filter and $\gamma_j^{(i)}$ denotes the scale term), and where for simplicity we specify the functional form of each $j = 1 \ldots, d_i$ coordinates of the function $g : \mathbb{R}^n \to \mathbb{R}^{d_i}$. We call the MFN using this filter the *GaborNet*.

As with the FourierNet, a compelling feature of the Gabor network is that the final function f can be represented as a linear combination of Gabor filters. This is captured by the following theorem:

Theorem 2. *The output of a Gabor Network is given by a linear combination of Gabor bases,*

$$f_j(x) = \sum_{t=1}^{T} \bar{\alpha}_t \exp \left(-\frac{1}{2} \bar{\gamma}_t \|x - \bar{\mu}_t\|^2 \right) \sin(\bar{\omega}_t x + \bar{\phi}_t) + \bar{b}, \tag{9}$$

for coefficients $\bar{\alpha}_{1:T}$, scales $\bar{\gamma}_{1:T}$, means $\bar{\mu}_{1:T}$, frequencies $\bar{\omega}_{1:T}$, phase offsets $\bar{\phi}_{1:T}$, and bias term $\bar{b}$.

The proof is given in the appendix, but the basic procedure is the same as the above: using the fact that just like Fourier filters, the product of Gabor filters is also a linear combination of (a different set of) Gabor filters. Likewise, we can also compute the explicit form of the coefficients and for this linear basis expansion, with the explicit form again given in the appendix. One relevant point, though, is how we choose initializations for the γ and μ parameters. Since γ effectively acts as an inverse covariance term of a Gaussian, a $\mathrm{Gamma}(\alpha, \beta)$ random variable (the conjugate prior of the Gaussian inverse covariance), is a reasonable choice for this parameter. And since the $\bar{\gamma}$ functions in the final linear expansion end up being a *sum* of the individual random $\gamma^{(i)}$ terms at each layer, we scale each layer's α term by $1/k$ to effectively control this parameter at the final layer. We also simply choose each $\mu^{(i)}$ to be uniformly distributed over the range of the allowable input space x.

4 EXPERIMENTAL RESULTS

We test MFNs on a broad range of representation tasks, showing that the relative simplicity of MFNs improves upon the performance of existing neural representation methods. Our set of experiments draws from those presented in Sitzmann et al. (2020) alongside SIREN (image representation, shape representation, and differential equation experiments) and in Tancik et al. (2020) alongside Fourier feature networks with Gaussian random features, which we call FF Gaussian (image generalization and 3D inverse rendering experiments). In each case, we compare against the set of models tested in the original experiment (generally, either SIREN or FF Gaussian, along with a basic ReLU MLP). A PyTorch implementation of MFN is available at `https://github.com/boschresearch/multiplicative-filter-networks`, and full details on hyperparameters and training specifications are available in the appendix.

Figure 2: Image generalization samples from the *Natural* and *Text* datasets.

4.1 IMAGE REPRESENTATION & GENERALIZATION

We first examine the ability of several networks architectures in the task of image representation as described in Section 1, where we fit the network to a function $f : \mathbb{R}^2 \to \mathbb{R}^c$ using a dataset where input coordinates (x, y) corresponding to the output pixel value at those coordinates (with $c = 1$ or 3 for grayscale or RGB images, respectively). To demonstrate this, we construct such a dataset from a 256×256 pixel grayscale image and fit various models using a simple mean squared error (MSE) loss, including SIREN, GABORNET, FOURIERNET, and ReLU MLPs with and without positional encoding (PE). Visual results and a plot of PSNR early in training are shown in (Figure 1). In particular, both FOURIERNET and GABOR-NET show quicker initial convergence than other architectures.

Table 1: PSNR of each model's reconstruction in image and video representation tasks after 10,000 training iterations. For video representation, mean $\pm$ standard deviation over all frames is reported.

Method	PSNR (in dB)	
	Image	Video
FF Basic	20.13	24.09 ± 1.03
FF Positional	40.09	27.90 ± 0.99
SIREN	56.54	$\mathbf{30.58 \pm 0.93}$
FOURIERNET	43.32	27.93 ± 0.91
GABORNET	$\mathbf{73.98}$	29.83 ± 0.71

PSNRs after training (Table 1) show that SIREN eventually outperforms FOURIERNET, while GABORNET remains the best model throughout the training. Indeed, after only 1000 training iterations, GABORNET performs reconstruction better than all other models trained for 10 times longer.

We can broaden the task above to represent video by appending a third dimension to the input: the output corresponding to the input (x, y, t) is the pixel value at (x, y) at frame t. We aim to represent a 300 frame color video with 512×512 resolution in this manner, testing all of the architectures used in the previous experiment. As shown in Figure 1, SIREN and GABORNET are most capable of reproducing fine details of the original video, such as whiskers and and eye color. This is reflected in the PSNR of these reconstructions (Table 1); SIREN performs best with a PSNR over 30 dB, while the GABORNET reconstruction comes within 1 dB of SIREN and exhibits much lower variation across frames than any other model.

In addition to representing images, we demonstrate that the MFNs are able to generalize the representation to unseen pixels. We train the networks using only 25% of the image pixels (every other pixel in the width and height dimensions) and evaluate using the complete images. We compare the results of our methods with the Fourier feature networks on two datasets (natural and text images) presented in Tancik et al. (2020). The peak signal-to-noise ratio (PSNR) metric is used to evaluate the performance. As we can see from Table 2, both FOURIERNET and GABOR-

Table 2: Image generalization results (mean $\pm$ standard deviation of PSNR).

Method	Natural	Text
FF Basic	21.61 ± 2.62	20.50 ± 2.13
FF Positional	25.13 ± 4.01	26.49 ± 3.11
FF Gaussian	25.57 ± 4.18	30.46 ± 1.97
FOURIERNET	26.03 ± 2.77	31.02 ± 2.04
GABORNET	$\mathbf{26.18 \pm 2.95}$	$\mathbf{31.19 \pm 2.00}$

NET outperform all versions of the Fourier feature networks that uses basic, positional encoding, and random Gaussian features. Some examples of the generated images are presented in Figure

Table 3: Total training loss after training for differential equations, where the iterations column refers to the number of iterations for which the networks were trained. PLI and PGI refer to Poisson equation based image reconstruction using Laplacians and gradients respectively. Helmholtz and wave refer to the single source inversion task.

Problem	Iters	SIREN	FOURIERNET	GABORNET
PGI	10000	0.55	1.16	**0.46**
PLI	10000	3432.56	76663.52	**107.129**
Helmholtz	50000	84949.92	46486.0	**18845.75**
Wave	10000	2090.15	691.34	**441.13**

(a) Poisson Image Reconstruction: Gradients   (b) Poisson Image Reconstruction: Laplacians

Figure 3: Poisson Image Reconstruction: In the left and right figures, an image on the left is reconstructed using gradients and Laplacians respectively; the top row depicts the reconstructed images, while the bottom row indicates the fitted gradients and the fitted Laplacians.

2, with additional images in Appendix B.2. Visually, the MFNs' generated images also have better quality over the baselines, particularly in *Text* datasets. Some parts of the text are missing in the baselines images (highlighted with red rectangles in Figure 2), whereas the MFNs completely generate all parts of the text in the images.

4.2 DIFFERENTIAL EQUATIONS

In this section, we aim to solve boundary value problems which are supervised by different forms of gradient information from the functional at hand. We first focus on the Poisson equation, where we demonstrate image reconstruction in two settings where the supervision for the model is brought about by gradients and Laplacians respectively. It is worth noting that the model is never presented with real function values. We then focus on two 2nd order differential equations, namely, the Helmholtz equation and the wave equation, where we solve for the wave field, where the network is supervised by a known source function.

We demonstrate image reconstruction using gradients and compare the performance of FOURIER-NET and GABORNET with SIREN and ReLU MLP for the Poisson equation. We use the same loss function as in (Sitzmann et al., 2020) in (5). Figures 3a and 3b show that the image is reconstructed successfully when the networks are trained while being supervised by gradients and Laplacians respectively, while ReLU fails spectacularly. Table 3 depicts the losses of each method after 10000 iterations, where it can be seen that GABORNET beats other baselines in terms of performance.

The Helmholtz and wave equations are related to the physical modeling of diffusion and waves and are closely related to a Fourier transform. Hence, we focus our attention on describing the Helmholtz equation. We aim to solve for the wave field and compare the performance of FOURIERNET and GABORNET with SIREN and ReLU MLP. To accommodate for complex-valued solutions, the network is configured to output two values which can be interpreted as the real and imaginary parts. We use the same loss function as used in (Sitzmann et al., 2020) (see Section 4.3 of (Sitzmann et al., 2020) for details). Figure 4 shows the magnitude and the phase of the reconstructed wave front for a single Gaussian source placed at the center of a medium with uniform wave propagation velocity. Table 3 depicts the losses of each method after 50000 iterations, and shows that GABORNET beats FOURIERNET and SIREN in terms of performance, while, as previously shown in (Sitzmann et al., 2020), ReLU MLP fails miserably. Details pertaining to the network and training are relegated to Appendix B.3.

Figure 5: Shape representations from fitting signed distance functions (a). 2D rendered photographs from view synthesis experiments (b).

4.3 SHAPE REPRESENTATION VIA SIGNED DISTANCE FIELDS

Recent work (Park et al., 2019) has explored the problem of 3D shape representation with neural architectures, often with surprisingly effective results. This is done by training on raw geometric data: given an oriented point cloud, we seek to learn a function $f : \mathbb{R}^3 \rightarrow \mathbb{R}$ that takes points as input such that the zero level set $\{x \mid f(x) = 0\}$ of the network accurately represents the surfaces of the shape. Effective training objectives for this task has been explored in considerable depth; we use the training loss presented by Park et al. (2019) and used in Sitzmann et al. (2020), which includes terms involving the

Figure 4: Solving Helmholtz equation for a single point source placed at the center of a medium with uniform wave propagation velocity. The top row presents the magnitude, while the bottom row presents the phase.

network's output (penalties to encourage SDF values near and away from 0 for surface and off-surface points, respectively) as well as its gradients (a term encouraging the gradient to match the surface points' normals, and a gradient norm penalty throughout the entire 3D space). A complete description of the loss function is left to the appendix.

Figure 5a shows the results of our shape representation task on SIREN, a standard ReLU MLP, and both variants of MFN. As can be seen, the ReLU network's fails to represent some features of the scene entirely, such as doorways, picture frames, and pillows. Both MFN architectures far outperform this baseline, and are able to reconstruct the room and objects within it to a recognizable degree. However, likely owing to its strong ability to produce smooth outputs and gradients, SIREN is largely able to avoid the visual artifacts on flat surfaces like walls that remain in reconstructions by FOURIERNET and, to a lesser extent, GABORNET.

4.4 3D INVERSE RENDERING FOR VIEW SYNTHESIS

In this view synthesis task, we aim to reconstruct 3D representation from the observed 2D photographs. Using the reconstructed 3D representation, we then render 2D images from new viewpoints. We use the "simplified Neural Radiance Fields (NeRF)" task on *Lego* dataset presented in Tancik et al. (2020). The networks are trained to predict the color (in RGB format) and the volume density at a given 3D location of the viewpoint. Volumetric rendering is then used to re-render the 2D image photograph at the viewpoint. The training loss is computed as the mean squared error between the rendered photograph and the actual 2D image observations. The results in Table 4 show that both MFNs perform competitively in the task. GABORNET has a slight advantage over

the baselines and FOURIERNET in terms of the overall PSNR metric. It also arguably produces a slightly better image rendering quality as shown in Figure 5b and other images in Appendix B.5.

5 CONCLUSION

We have introduced multiplicative filter networks (MFNs), a class of neural representation architectures that forego the usual compositional notion of network depth in favor of a similarly expressive multiplicative operation. They also admit a natural signal processing interpretation, as in the two instantiations of MFNs, FOURIERNET and GABORNET, which are proven to be exactly equivalent to a linear combination of sinusoidal or Gabor wavelet bases, respectively. In experiments, we show that, despite their simplicity relative to other deep architectures designed for implicit representation, MFNs stand up to or surpass the previous state of the art on a battery of representation tasks.

Table 4: View synthesis results (mean $\pm$ st.d. of PSNR).

Method	PSNR
FF Basic	23.37 ± 0.96
FF Positional	25.76 ± 0.79
FF Gaussian	25.76 ± 0.92
FOURIERNET	25.20 ± 0.72
GABORNET	$\mathbf{25.81 \pm 0.76}$

REFERENCES

Haim Avron, Michael Kapralov, Cameron Musco, Christopher Musco, Ameya Velingker, and Amir Zandieh. Random fourier features for kernel ridge regression: Approximation bounds and statistical guarantees. In *International Conference on Machine Learning*, pp. 253–262, 2017.

Ronald Newbold Bracewell and Ronald N Bracewell. *The Fourier transform and its applications*, volume 31999. McGraw-Hill New York, 1986.

Romain Brault, Markus Heinonen, and Florence Buc. Random fourier features for operator-valued kernels. In *Asian Conference on Machine Learning*, pp. 110–125, 2016.

Rohan Chabra, Jan Eric Lenssen, Eddy Ilg, Tanner Schmidt, Julian Straub, Steven Lovegrove, and Richard Newcombe. Deep local shapes: Learning local sdf priors for detailed 3d reconstruction. *arXiv preprint arXiv:2003.10983*, 2020.

Zhiqin Chen and Hao Zhang. Learning implicit fields for generative shape modeling. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5939–5948, 2019.

Radha Chitta, Rong Jin, and Anil K Jain. Efficient kernel clustering using random fourier features. In *2012 IEEE 12th International Conference on Data Mining*, pp. 161–170. IEEE, 2012.

Kyle Genova, Forrester Cole, Daniel Vlasic, Aaron Sarna, William T Freeman, and Thomas Funkhouser. Learning shape templates with structured implicit functions. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 7154–7164, 2019.

Philipp Henzler, Niloy J Mitra, and Tobias Ritschel. Learning a neural 3d texture space from 2d exemplars. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8356–8364, 2020.

Zhen Hu, Ming Lin, and Changshui Zhang. Dependent online kernel learning with constant number of random fourier features. *IEEE transactions on neural networks and learning systems*, 26(10): 2464–2476, 2015.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in neural information processing systems*, pp. 8571–8580, 2018.

Chiyu Jiang, Avneesh Sud, Ameesh Makadia, Jingwei Huang, Matthias Nießner, and Thomas Funkhouser. Local implicit grid representations for 3d scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6001–6010, 2020.

Sylwester Klocek, Łukasz Maziarka, Maciej Wołczyk, Jacek Tabor, Jakub Nowak, and Marek Śmieja. Hypernetwork functional image representation. In *International Conference on Artificial Neural Networks*, pp. 496–510. Springer, 2019.

Quoc Le, Tamás Sarlós, and Alex Smola. Fastfood-approximating kernel expansions in loglinear time. In *Proceedings of the international conference on machine learning*, volume 85, 2013.

Ming Lin, Shifeng Weng, and Changshui Zhang. On the sample complexity of random fourier features for online learning: How many random fourier features do we need? *ACM Transactions on Knowledge Discovery from Data (TKDD)*, 8(3):1–19, 2014.

Jingshu Liu, Li Wang, and Jinglei Liu. Efficient preference clustering via random fourier features. *Big Data Mining and Analytics*, 2(3):195–204, 2019.

Julien Mairal, Piotr Koniusz, Zaid Harchaoui, and Cordelia Schmid. Convolutional kernel networks. In *Advances in neural information processing systems*, pp. 2627–2635, 2014.

Siamak Mehrkanoon and Johan AK Suykens. Deep hybrid neural-kernel networks using random fourier features. *Neurocomputing*, 298:46–54, 2018.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. *arXiv preprint arXiv:2003.08934*, 2020.

Anh Nguyen, Jason Yosinski, and Jeff Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 427–436, 2015.

Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3504–3515, 2020.

Michael Oechsle, Lars Mescheder, Michael Niemeyer, Thilo Strauss, and Andreas Geiger. Texture fields: Learning texture representations in function space. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 4531–4540, 2019.

Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 165–174, 2019.

Majid Rabbani. Jpeg2000: Image compression fundamentals, standards and practice. *Journal of Electronic Imaging*, 11(2):286, 2002.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Advances in neural information processing systems*, pp. 1177–1184, 2008.

Ali Rahimi and Benjamin Recht. Weighted sums of random kitchen sinks: Replacing minimization with randomization in learning. In *Advances in neural information processing systems*, pp. 1313–1320, 2009.

Ankit Singh Rawat, Jiecao Chen, Felix Xinnan X Yu, Ananda Theertha Suresh, and Sanjiv Kumar. Sampled softmax with random fourier features. In *Advances in Neural Information Processing Systems*, pp. 13857–13867, 2019.

Jen-Hao Rick Chang, Aswin C Sankaranarayanan, and BVK Vijaya Kumar. Random features for sparse signal classification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5404–5412, 2016.

Vincent Sitzmann, Michael Zollhöfer, and Gordon Wetzstein. Scene representation networks: Continuous 3d-structure-aware neural scene representations. In *Advances in Neural Information Processing Systems*, pp. 1121–1132, 2019.

Vincent Sitzmann, Julien NP Martel, Alexander W Bergman, David B Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. *arXiv preprint arXiv:2006.09661*, 2020.

Kenneth O Stanley. Compositional pattern producing networks: A novel abstraction of development. *Genetic programming and evolvable machines*, 8(2):131–162, 2007.

Yitong Sun, Anna Gilbert, and Ambuj Tewari. But how does it work in theory? linear svm with random features. In *Advances in Neural Information Processing Systems*, pp. 3379–3388, 2018.

Matthew Tancik, Pratul P Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. *arXiv preprint arXiv:2006.10739*, 2020.

Martin Vetterli, Jelena Kovačević, and Vivek K Goyal. *Foundations of signal processing*. Cambridge University Press, 2014.

Hui Xue, Zheng-Fan Wu, and Wei-Xiang Sun. Deep spectral kernel learning. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence*, pp. 4019–4025. AAAI Press, 2019.

Felix Xinnan X Yu, Ananda Theertha Suresh, Krzysztof M Choromanski, Daniel N Holtmann-Rice, and Sanjiv Kumar. Orthogonal random features. In *Advances in Neural Information Processing Systems*, pp. 1975–1983, 2016.

Ellen D Zhong, Tristan Bepler, Joseph H Davis, and Bonnie Berger. Reconstructing continuous distributions of 3d protein structure from cryo-em images. In *ICLR*, 2020.

A   PROOFS AND DERIVATIONS

We begin by stating the general condition under which an MFN can ultimately be expressed as a linear combination of the original filter function: the fact that elementwise multiplication of the bases results in a *sum* of the same bases with different parameters.

Definition 1. *A filter $g(x; \theta)$ satisfies the multiplicative sum property if for some $\theta^{(1)}$ and $\theta^{(2)}$ we have that*

$$g(x; \theta^{(1)}) \circ g(x; \theta^{(2)}) = \sum_{i=1}^{N} \beta_i g(x; \bar{\theta}^{(i)}) \tag{10}$$

for some alternative set of parameters $\bar{\theta}^{(1:N)}$ and coefficients $\beta_{1:N}$.

We now state the general theorem that if the filter used in an MFN satisfies the multiplicative sum property, then the function represented by the MFN can also be expressed as a linear combination of the filter bases applies to the input.

Theorem 3. *Let f by an MFN defined by the recurrence*

$$z^{(1)} = g\left(x; \theta^{(1)}\right)$$

$$z^{(i+1)} = \left(W^{(i)} z^{(i)} + b^{(i)}\right) \circ g\left(x; \theta^{(i+1)}\right), \ i = 1, \dots, k-1$$

$$f(x) = W^{(k)} z^{(k)} + b^{(k)}$$

with a filter g that satisfies the multiplicative sum property. Then f can be expressed as

$$f_j(x) = \sum_{t=1}^{T} \alpha_t g(x; \tau_j^{(t)}) + c. \tag{11}$$

where we use the notation $g(x; \tau_j^{(t)})$ to denote a scalar-valued application of the filter, specific to the jth coordinate.

Proof. The proof follows by induction on i. The base case of $z^{(1)}$ follows immediately from the definition (and in fact without any bias term b). Now suppose that for layer $i-1$, for each $z_j^{(i-1)}$ we have

$$z_j^{(i-1)} = \sum_{t=1}^{N} \alpha_t^j g(x; \tau_j^{(t)}) \tag{12}$$

Then we have that

$$z_j^{(i)} = \left(\sum_{p=1}^{d_i} W_{jp}^{(i)} z_p^{(i-1)} + b^{(i)}\right) g(x; \theta_j^{(i)}) \tag{13}$$

$$= \left(\sum_{p=1}^{d_i} W_{jp}^{(i)} \sum_{t=1}^{T} \alpha_t^p g(x; \tau_p^{(t)}) + b_j^{(i)}\right) g(x; \theta_j^{(i)}) \tag{14}$$

$$= \sum_{p=1}^{d_i} \sum_{t=1}^{T} W_{jp}^{(i)} \alpha_t^p g(x; \tau_p^{(t)}) g(x; \theta_j^{(i)}) + b_j^{(i)} g(x; \theta_j^{(i)}) \tag{15}$$

$$= \sum_{p=1}^{d_i} \sum_{t=1}^{T} W_{jp}^{(i)} \alpha_t^p \sum_{q=1}^{N} \beta_q g(x; \bar{\tau}_p^{(t,q)}) g(x; \theta_j^{(i)}) + b_j^{(i)} g(x; \theta_j^{(i)}) \tag{16}$$

$$= \sum_{t=1}^{T'} \bar{\alpha}_t g(x; \bar{\tau}_j^{(t)}) \tag{17}$$

where the line (15) to (16) follows from the multiplicative sum instruction. The final output $f(x)$ is simply a linear function of the final hidden layer $z^{(k)}$, and thus also satisfies the condition of the theorem. $\square$

We now prove the multiplicative sum property for both the Fourier and Gabor filters. This, together with the theorem above, proves the results in the main text, stated for the FourierNet and GaborNet functions explicitly.

A.1 FOURIER NETWORKS

Theorem 4. *The Fourier basis function*

$$g(x; \theta^{(i)}) = \sin(\omega^{(i)} x + \phi^{(i)}) \tag{18}$$

satisfies the multiplicative sum property with β and $\bar{\theta}^{(1:2)} = \{\bar{\omega}^{(1:2)}, \bar{\phi}^{(1:2)}\}$ given bvy

$$
\begin{aligned}
\beta_1 &= \beta_2 = \frac{1}{2} \\
\bar{\omega}^{(1)} &= \omega^{(1)} - \omega^{(2)} \\
\bar{\omega}^{(2)} &= \omega^{(1)} + \omega^{(2)} \\
\bar{\phi}^{(1)} &= \phi^{(1)} - \phi^{(2)} - \frac{\pi}{2} \\
\bar{\phi}^{(2)} &= \phi^{(1)} + \phi^{(2)} + \frac{\pi}{2}.
\end{aligned}
\tag{19}
$$

Proof. This fact follows from simple rules for sum of sinusoidal function, and was also highlighted in the main text

$$
\begin{aligned}
g(x; \theta^{(1)}) \circ g(x; \theta^{(2)}) &= \sin(\omega^{(1)} x + \phi^{(1)}) \circ \sin(\omega^{(2)} x + \phi^{(2)}) \\
&= \frac{1}{2} \cos\left((\omega^{(1)} - \omega^{(2)})x + \phi^{(1)} - \phi^{(1)}\right) - \\
&\quad \frac{1}{2} \cos\left((\omega^{(1)} + \omega^{(2)})x + \phi^{(1)} + \phi^{(1)}\right) \\
&= \frac{1}{2} \sin\left((\omega^{(1)} - \omega^{(2)})x + \phi^{(1)} - \phi^{(1)} - \frac{\pi}{2}\right) + \\
&\quad \frac{1}{2} \sin\left((\omega^{(1)} + \omega^{(2)})x + \phi^{(1)} + \phi^{(1)} + \frac{\pi}{2}\right) \\
&= \beta_1 g(x; \bar{\theta}^{(1)}) + \beta_2 g(x; \bar{\theta}^{(2)})
\end{aligned}
\tag{20}
$$

with the parameters defined as in the theorem statement. $\square$

An inspection of the two theorems above directly leads to the explicit expansion of the terms in the sequence as well, which we restate here.

Corollary 2. *Let $i_1, i_2, \ldots, i_{k-1}$ range over all $\prod_{j=1}^{k-1} d_j$ possible indices of each hidden unit of each layer of an MFN, and let $s_2, \ldots, s_k \in \{-1, +1\}$ range over all 2^{k-1} possible binary signs; then the expansion of $z_{i_k}^{(k)}$ given is given by all the terms*

$$
\begin{aligned}
\bar{\alpha} &= \left\{ \frac{1}{2^{k-1}} W_{i_k, i_{k-1}}^{(k-1)} \ldots W_{i_3, i_2}^{(2)} W_{i_2, i_1}^{(1)} \right\} \\
\bar{\omega} &= \left\{ s_k \omega_{i_k}^{(k)} + \ldots + s_2 \omega_{i_2}^{(2)} + \omega_{i_1}^{(1)} \right\} \\
\bar{\phi} &= \left\{ s_k \phi_{i_k}^{(k)} + \ldots + s_2 \phi_{i_2}^{(2)} + \phi_{i_1}^{(1)} + \frac{\pi}{2} \sum_{i=2}^{k} s_k \right\}.
\end{aligned}
\tag{21}
$$

with a similar form for terms that begin at the $i > 1$ layer, multiplied by the corresponding $b_{i_j}^{(j)}$ term.

A.2 GABOR NETWORKS

We now prove similar properties for the Gabor Network.

Theorem 5. *The Gabor basis function*

$$g_j(x; \theta^{(i)}) = \exp\left(-\frac{\gamma_j^{(i)}}{2}\left\|x - \mu_j^{(i)}\right\|_2^2\right)\sin\left(\omega_j^{(i)}x + \phi_j^{(i)}\right)\tag{22}$$

satisfies the multiplicative sum property with β and $\bar{\theta}^{(1:2)} = \left\{\bar{\gamma}^{(1:2)}, \bar{\mu}^{(1:2)}, \bar{\omega}^{(1:2)}, \bar{\phi}^{(1:2)}\right\}$ given by

$$
\begin{aligned}
\beta_1 = \beta_2 &= \frac{1}{2}\exp\left(\frac{-\gamma^{(1)}\gamma^{(2)}\|\mu^{(1)} - \mu^{(2)}\|^2}{2(\gamma^{(1)} + \gamma^{(2)})}\right)\\
\bar{\gamma}^{(1)} = \bar{\gamma}^{(2)} &= \gamma^{(1)} + \gamma^{(2)}\\
\bar{\mu}^{(1)} = \bar{\mu}^{(2)} &= \frac{\gamma^{(1)}\mu^{(1)} + \gamma^{(2)}\mu^{(2)}}{\gamma^{(1)} + \gamma^{(2)}}\\
\bar{\omega}^{(1)} &= \omega^{(1)} - \omega^{(2)}\\
\bar{\omega}^{(2)} &= \omega^{(1)} + \omega^{(2)}\\
\bar{\phi}^{(1)} &= \phi^{(1)} - \phi^{(2)} - \frac{\pi}{2}\\
\bar{\phi}^{(2)} &= \phi^{(1)} + \phi^{(2)} + \frac{\pi}{2}.
\end{aligned}
\tag{23}
$$

Proof. The sinusoidal terms in the Gabor filter proceed in the exact same manner as for the Fourier filter. The exponential terms follow from the fact, well known from Gaussian distributions, that

$$
\begin{aligned}
&\exp\left(-\frac{1}{2}\gamma^{(1)}\|x - \mu^{(1)}\|_2^2\right)\exp\left(-\frac{1}{2}\gamma^{(2)}\|x - \mu^{(2)}\|_2^2\right) =\\
&\exp\left(\frac{-\gamma^{(1)}\gamma^{(2)}\|\mu^{(1)} - \mu^{(2)}\|^2}{2(\gamma^{(1)} + \gamma^{(2)})})\right)\exp\left(-\frac{1}{2}(\gamma^{(1)} + \gamma^{(2)})\left\|x - \frac{\gamma^{(1)}\mu^{(1)} + \gamma^{(2)}\mu^{(2)}}{\gamma^{(1)} + \gamma^{(2)}}\right\|_2^2\right)
\end{aligned}
\tag{24}
$$

The first term is a constant, and so can be folded into the β terms, while the second is the exponential term of a Gabor filter with the parameters given above. $\square$

Finally, just as for the FourierNet, we can also provide precise characterizations of each term in the final Gabor filter expansion. This corollary follows immediately from the proof above, plus some algebraic simplification.

Corollary 3. *Let $i_1, i_2, \ldots, i_{k-1}$ range over all $\prod_{j=1}^{k-1} d_j$ possible indices of each hidden unit of each layer of an MFN, and let $s_2, \ldots, s_k \in \{-1, +1\}$ range over all 2^{k-1} possible binary signs; then the expansion of $z_{i_k}^{(k)}$ given is given by all the terms*

$$
\begin{aligned}
\bar{\alpha} &= \left\{\frac{1}{2^{k-1}}W_{i_k,i_{k-1}}^{(k-1)}\ldots W_{i_3,i_2}^{(2)}W_{i_2,i_1}^{(1)}\exp\left(-\frac{\sum_{p=1,q\neq p}^k \gamma_{i_q}^{(q)}\gamma_{i_p}^{(p)}\|\mu_{i_p}^{(p)} - \mu_{i_q}^{(q)}\|_2^2}{2\sum_{p=1}^k \gamma_{i_p}^{(p)}}\right)\right\}\\
\bar{\gamma} &= \left\{\gamma_{i_k}^{(k)} + \ldots + \gamma_{i_2}^{(2)} + \gamma_{i_1}^{(1)}\right\}\\
\bar{\mu} &= \left\{\frac{\gamma_{i_k}^{(k)}\mu_{i_k}^{(k)} + \ldots + \gamma_{i_2}^{(2)}\mu_{i_2}^{(2)} + \gamma_{i_1}^{(1)}\mu_{i_1}^{(1)}}{\gamma_{i_k}^{(k)} + \ldots + \gamma_{i_2}^{(2)} + \gamma_{i_1}^{(1)}}\right\}\\
\bar{\omega} &= \left\{s_k\omega_{i_k}^{(k)} + \ldots + s_2\omega_{i_2}^{(2)} + \omega_{i_1}^{(1)}\right\}\\
\bar{\phi} &= \left\{s_k\phi_{i_k}^{(k)} + \ldots + s_2\phi_{i_2}^{(2)} + \phi_{i_1}^{(1)} + \frac{\pi}{2}\sum_{i=2}^k s_k\right\}.
\end{aligned}
\tag{25}
$$

with a similar form for terms that begin at the $i > 1$ layer, multiplied by the corresponding $b_{i_j}^{(j)}$ term.

B ADDITIONAL EXPERIMENTAL DETAILS AND RESULTS

B.1 IMAGE REPRESENTATION

Figure 6: Plot of training loss (mean squared error) over time for models in the video representation task.

In the image representation task, all models used were 3 layers with 256 hidden units per layer, and were trained for 10000 iterations. All models were trained with the Adam optimizer, with a learning rate of 10^{-2} for the two MFNs and a learning rate of 10^{-4} for all other models. Both MFN models used an input scaling factor of 256.

The cat video used in the video representation task is available at the following url:

`https://www.pexels.com/video/the-full-facial-features-of-a-pet-cat-3040808`

Models used for video representation were 3 layers with 1024 hidden units per layer, and were trained for 10000 iterations. We performed an exponentially grid search over learning rates for each model, testing a learning rate of 10^{-i} for $i \in \{2, 3, 4, 5, 6\}$, and found the best performance when using $1e-5$ for SIREN and 10^{-3} for all other models. Both MFN architectures used a scaling factor γ of 256.

B.2 IMAGE GENERALIZATION

In the image generalization experiments, we use two datasets (*Natural* and *Text* datasets); each contains 16 images with a size of 512×512 pixels. We use 25% of the pixels resulting 256×256 images to train the models and use the full image size in the evaluation. We construct and train the models separately for each image. The models are trained to map the input of (x, y) coordinates to the corresponding RGB values. We train all the models in 2000 epochs. The final result is computed by averaging the results over the 16 images in each dataset. For each of the MFNs and Fourier feature networks, we construct a 4 hidden layer network with 256 nodes in each hidden layer.

For both FOURIERNET and GABORNET, we set the input scaling factor to 256, with the value of α in GABORNET set to 3.0. We use Adam optimizer with learning rate of 3e-3 and no weight decay. For the Fourier feature models, we use the hyperparameters presented in the code repository published by the authors. The optimizer used in the Fourier feature models is the Adam optimizer with learning rate of 1e-3 and no weight decay. All the Fourier feature models use 256 as the embedding size for the random features. The scaling factor for the Fourier feature networks with positional encoding is set to 6 for the *Natural* dataset and 5 for the *Text* dataset. The scaling factor for the Fourier feature networks with Gaussian random features is set to 10 for the *Natural* dataset

Figure 7: Image generalization samples from *Natural* datasets.

and 14 for the *Text* dataset. As in the code implementation published by (Tancik et al., 2020), we implement our model in Python using JAX as the deep learning framework.

In addition to the experimental results presented in Section 4.1, we show additional generated images for *Natural* dataset in Figure 7 and *Text* dataset in Figure 8. We can similarly see from the figure that the quality of generated images by the MFNs are superior to the baselines in *Text* dataset and competitive in the *Natural* dataset. The Fourier feature networks (especially with basic and positional encoding) failed to generate some parts of the texts in the images. The use of Gaussian random features improves the generated images, but still fails to generate small portions of the texts. In contrast, both FOURIERNET and GABORNET correctly generate all parts of the texts. Figure 8 also highlights the parts of the texts that are failed to be generated by the baselines methods. In the *Natural* dataset, all of the models except the Fourier feature networks using basic encoding performs equally well with very similar visual results.

Comparison with the traditional Fourier transform. In addition to the experiments above, we also run the standard upsampling technique that performs FFT on the 256×256 pixels images and then performs inverse FFT on the extended frequency domains that outputs 512×512 pixels images. We then measure the PSNR on the unseen pixels, similar to the experiments on the MFNs and Fourier feature networks. This traditional FFT upsampling method performs quite well on both *Natural* and *Text* dataset with 73.80 ± 12.20 and 66.78 ± 8.14 PSNRs respectively. However, the standard Fourier analysis on the traditional upsampling methods serves a different purpose compared to the one in the implicit neural representations (the MFNs, SIRENs, and Fourier feature networks). The standard Fourier analysis does not scale well to higher dimensions, or it does not admit to backpropagation through more complex loss functions (e.g., in neural rendering fields). The lack of scalability and non-differentiability hinders the usage of FFT based upsampling methods in an end-to-end manner and hence adds significant barriers to such methods being employed in generic tasks. In contrast, the MFNs (and other implicit neural representations) provides generic methods that apply to generic tasks where we can learn based upon derivatives, as shown in our paper and the related works (Sitzmann et al., 2020; Tancik et al., 2020; Mildenhall et al., 2020).

Figure 8: Image generalization samples from *Text* datasets.

B.3 Differential Equations

B.3.1 Poisson Equation

For the image reconstruction tasks using the supervision of gradients and Laplacians of the ground truth, we use 5 layer networks with a hidden size of 256. The networks were trained using Adam Optimizer. For the image reconstruction task using gradients, the learning rate chosen for Fourier-Net and GaborNet was 1e-3, which was chosen by grid search. The batch size was chosen to be 16384, as in SIREN. For SIREN, we used the reference implementation of it, which also uses 5 layer networks with a hidden size of 256. The same architecture was also used for ReLU MLP. All the networks were trained for 10000 iterations. For the image reconstruction task using Laplacians, the learning rates chosen for FourierNet and GaborNet were 5e-3 and 3.5e-3 respectively, which was chosen by grid search. The batch size was chosen to be 16384, same as SIREN. For SIREN, we used the reference implementation of it. All the networks were trained for 10000 iterations.

B.3.2 Helmholtz and Wave Equation

For the single source inversion task corresponding to the Helmholtz equation, we use 5 layer networks for both FourierNet and GaborNet with a hidden size of 256. The networks pertaining to SIREN, ReLU MLP, FourierNet and GaborNet are trained using randomly sampled points from a ℓ_∞ ball $\in \mathbb{R}^2$ of radius 1. The networks were trained using Adam optimizer. The learning rates chosen for FourierNet and GaborNet were 2.5e-4 and 5e-4 respectively, which was chosen by grid search. The batch size was chosen to be 32, same as SIREN. For SIREN, we used the reference implementation of it, which also uses 5 layer networks with a hidden size of 256. The same architecture was also used for ReLU MLP. All the networks were trained for 50000 iterations. For the wave equation, we use 5 layer networks for both FourierNet and GaborNet with a hidden size of 512. The networks were trained using Adam optimizer. The learning rates is chosen for FourierNet and GaborNet were 1e-4 and 2e-4 respectively, which was chosen by grid search. The batch size was chosen to be 32, same as SIREN. For SIREN, we used the reference implementation of it, which also uses 5 layer networks with a hidden size of 512. All the networks were trained for 10000 iterations.

B.4 SHAPE REPRESENTATION AND SDF FITTING

The 3D room oriented point cloud used in our shape representation is freely available at

`http://www.turbosquid.com`

The loss function used to train models on this task is identical to the one presented in Sitzmann et al. (2020); namely, for a model N training on points $x \in \Omega$ in an oriented point cloud with surface Ω_0, we use

$$L = \sum_{x \in \Omega} \lambda_1 \|1 - |\nabla_x N(x)|\| + \sum_{x \in \Omega_0} \lambda_2 \|N(x)\| + \lambda_3 \left(1 - \langle \nabla_x N(x), n(x) \rangle\right) + \sum_{x \notin \Omega_0} \lambda_4 \exp(-\alpha |N(x)|)$$

(26)

where $n(x)$ is the normal of the SDF f (i.e. $n(x) = \nabla_x f(x)$, and we use the following prescribed values for the scaling factors of the various terms: $\lambda_1 = 50$, $\lambda_2 = 3000$, $\lambda_3 = 100$, $\lambda_4 = 3000$, and $\alpha = 100$.

Models used to fit SDFs were 5 layers with 512 hidden units per layer, and were trained for 50 epochs (roughly 175k iterations). We performed a grid search to tune the learning rate for each model, searching over $\{a \times 10^{-i} \mid a \in \{1, 5\}, i \in \{2, 3, 4, 5, 6\}\}$. This revealed best performance for FOURIERNET at 10^{-4}, GABORNET and ReLU at 5×10^{-4}, and SIREN at 10^{-5}. Input scaling factors used for FOURIERNET and GABORNET were 128 and 256, respectively.

Figure 9: Plot of training losses (Equation (26)) over time for SIREN, GaborNet, and FourierNet.

B.5 3D INVERSE RENDERING FOR VIEW SYNTHESIS

In the view synthesis task, we aim to reconstruct 3D representation from the observed 2D photographs. The input to the models is a 3D coordinate (x, y, z) of a viewpoint. The models need to predict the corresponding 4D vector (r, g, b, v) where (r, g, b) corresponds to the predicted color in RGB format, and v corresponds to the volume density. The outputs of the models are then used as the input for the volumetric rendering procedure, which outputs the final rendered images from the viewpoint. The loss is computed as the mean squared error between the generated images and the observed 2D photograph. Since the rendering procedure is fully differentiable, all the training can be done end-to-end.

The *Lego* dataset in the "simplified NeRF" task contains 2D photographs from 120 viewpoints downsampled to 400×400 pixel resolution. We split the datasets into 100 training images, 7 validation

Figure 10: Additional examples of 2D rendered photographs from the *Lego* dataset experiment.

Figure 11: Plot of the PSNR over time for the Fourier feature networks, GaborNet, and FourierNet

images, and 13 test images. All the results in Table 4, rendered images in Figure 5b, as well as additional rendered images in Figure 10 are computed from the test set. In all models, we use a 4 hidden layer network with 256 nodes in each hidden layer. For both FOURIERNET and GABORNET, we set the input scaling factor to 180, with the value of α in GABORNET set to 1.0. We use Adam optimizer with learning rate of 1e-3 and no weight decay. For the Fourier feature models, we use the hyperparameters presented in the code repository published by the authors. The optimizer used in the Fourier feature models is Adam optimizer with learning rate of 5e-4 and no weight decay. All the Fourier feature models use 256 as the embedding size for the random features. All models use 2048 batches of rays, except GABORNET that uses 1440 batches of rays due to memory restriction.