From Where Do Language Models See?
Surfacing and Mitigating Blind Spots via Latent Need Discovery

Julius Broomfield
Georgia Institute of Technology
`jbroomfield@gatech.edu`

Kartik Sharma
Georgia Institute of Technology
`ksartik@gatech.edu`

Abstract

When a user prompts a LLM to produce an output that affects an external group, the model must implicitly act on behalf of people whose needs the user may not fully know. Thus, it is important to assess where the models fail to surface such materially relevant but unstated needs. However, existing approaches fail to do so as they focus on finding disparity across groups or misalignment with stated preferences. To fill these gaps, we leverage standpoint theory (Harding, 1988; Haraway, 1988) to posit that LLMs reflect a standpoint that determines which needs are visible by default. We introduce BLINDSPOT, a dataset of 1,830 scenarios, with four prompt conditions that decompose failures into a detection gap (the relevant group fails to enter the model's implicit prior) and an operationalization gap (the group is named but the need is still missed). Across 6 models, we find failures concentrated in religious, cultural, and socioeconomic needs, consistent with a default standpoint where needs rooted in religious observance, cultural practice, or socioeconomic constraint are less visible. We then show that persona conditioning models surfaces latent needs more effectively than naming the group directly, suggesting this knowledge is present in the model's weights, but not visible from the default standpoint. We also show that retrieval and fine-tuning methods can help mitigate the epistemic failures. We hope this work opens a broader research agenda around surfacing and broadening the underlying model standpoint.

1 Introduction

Large language models (LLMs) are frequently used in contexts where they plan, design, and make decisions on behalf of diverse groups of people (Sorensen et al., 2024a,b). This is a setting where failures are both likely and potentially consequential (Figure 1). For example, if a model designs a school lunch menu without flagging peanut allergens, a student could go into anaphylaxis; or if it produces an emergency evacuation plan for an apartment only relying on audible alarms, deaf residents may not be alerted. In both cases, it is possible that neither the user nor the model would be aware that anything was missed. Thus, it is critical that models are evaluated on their ability to surface such *latent* needs to quantify the risks to the people they would eventually serve.

We argue that these failures cannot be identified by existing approaches designed to detect bias or alignment. Bias evaluation assesses whether a model produces worse outputs for one group than another (Gallegos et al., 2024), while alignment targets the user's explicit preferences (Ji et al., 2023). But the user in the lunch menu scenario holds an implicit *second-order* preference: they want students' needs relevant to the lunch menu met, including needs they have not enumerated and may not know about. The model cannot easily satisfy this preference by optimizing for what the user says; it has to reason about who else is affected by the situation and what those people need. We call this a ***second-order pluralistic alignment problem***.

We draw on standpoint theory as a lens for reasoning about this failure mode (Harding, 1991). A ***standpoint***, in the sense developed by Harding (1991) and others in social epistemology, is an *epistemic position*[1] rooted in one's social location that shapes what a knower perceives as relevant, credible, or at stake in a given context (Haraway, 1988; Harding, 1991). Prior work has asked whose *opinions* LLMs reflect (Santurkar et al., 2023; Tao et al., 2024). We instead ask the question of whose *standpoint* LLMs reflect. The difference here is that the same opinion can arise from very different standpoints; opinions, beliefs, and preferences are all

---

[1] In this paper we use *epistemic position* in a broad sense to mean an agent's perspective together with the knowledge, experience, and conceptual resources available from it. In this sense, the term is closer to an *epistemic horizon*: what an agent knows, what they could know, and how they interact (Gadamer, 1975).

Figure 1: The full space represents needs relevant to a user prompt. The model's ***default standpoint*** (gray) makes common considerations such as desks, kitchens, and restrooms knowable. ***Marked standpoints*** (blue) make some additional needs knowable not visible from the default standpoint.

shaped by one's standpoint. While LLMs cannot hold a standpoint in the way a human can, we argue that they can reflect one. Specifically, the humans who produced the training data, performed annotation, and architect the model occupied particular social locations, and those positions collectively shaped what we term to be the model's ***default standpoint***.

Our empirical focus is narrower than fully characterizing that standpoint. Rather, we study one of its observable consequences: which *socially marked*[2] latent needs are surfaced by default. This framing draws on Mannheim's sociology of knowledge, which suggests that what a system takes for granted, as well as what it fails to see, can be read as a trace of its epistemic position (Mannheim, 1991). We operationalize this insight through underspecified scenarios in which the unmarked needs are not explicitly named, forcing models to rely on background assumptions about what is salient or at stake. To this end, we create BLINDSPOT, a dataset of 1,830 scenarios spanning accessibility, religious practice, cultural norms, language access, and socioeconomic barriers. We evaluate 6 models and 5 mitigation strategies. Our contributions are as follows:

1. We frame latent need discovery as a ***second-order pluralistic alignment*** problem. Latent needs are an effective probe of this gap since when a need is unstated, the model must fall back on its priors over who is affected and what they require. Drawing on standpoint theory, we argue these priors reflect a ***default***

standpoint inherited from training, which determines what is visible before any preference is expressed.

2. We introduce BLINDSPOT and show that latent, socially *marked* needs are often invisible even to frontier models. We decompose failures in discovering latent needs into *aleatoric* and *epistemic uncertainty* gaps. We find that group identity is a significant predictor of whether a need is surfaced, with physically observable needs most visible from the ***default standpoint*** and religious needs least visible.

3. We evaluate a range of training-time and inference-time methods for improving latent need discovery, including retrieval based generation (***RAG***), supervised fine-tuning (***SFT***), and *static* and *adaptive* persona conditioning methods.

4. We show that ***persona conditioning*** on a group *substantially outperforms* just naming the group as relevant. This suggests that models possess latent knowledge that is inaccessible from their *default standpoint* but recoverable through distributional shifts.

5. We introduce ***Mixture of Standpoints (MoS)***, an adaptive inference-time method that critiques and revises using *persona-conditioned* models and merges their critiques into a single response. With a sufficiently capable model, MoS recovers much of what a specific targeted persona achieves.

2 The BLINDSPOT Dataset

We construct BLINDSPOT, a dataset of prompts designed for latent need discovery based on acces-

---

[2]We use *marked* needs to refer to needs associated with identities or situations treated socially as non-default, in contrast to *unmarked* needs that are more often taken for granted (Waugh, 1982).

Figure 2: **BLINDSPOT construction pipeline. (a)** Phase I: needs are sourced and filtered from reference documents. Phase II: needs are organized into group and domain taxonomies via label normalization. Phase III: each need is instantiated into 3 scenarios and paired with 4 prompt conditions. **(b)** An example need (Braille signage and tactile wayfinding systems), its group and domain labels, and the 4 resulting prompt conditions shown for a single scenario.

sibility and inclusivity. Each prompt is anchored by a specific need of a marked group and instantiated in three realistic user scenarios, yielding 610 needs and 1,830 unique scenarios in total. Each scenario is paired with four prompt conditions that differ only by an appended cue, producing 7,320 prompts in total.

2.1 Dataset Construction

Need sourcing and curation. We curate candidate needs from authoritative standards and practical guidance spanning accessibility, communication, transportation equity, allergies, language access, religious practices, and cultural practices[3]. Table 1 summarizes the primary reference documents; we treat each document as contributing needs across multiple group × domain intersections. Starting from an initial pool of 663 needs, we conducted an LLM guided first pass, followed by manual review, to retain needs that are (i) concrete and actionable, (ii) plausibly omittable in everyday planning and design tasks, and (iii) testable in short prompts. This review resulted in 620 approved needs, with 43 needs being discarded. We then normalize group labels and deduplicate semantically overlapping needs into a set of 610 needs (Figure 2).

Scenario generation. For each retained need, we generate three short situations via *zero-shot, schema-guided* with Claude Sonnet 4.5[4]. Specif-

ically, we generate two *creation* prompts where the user asks the model to produce an artifact or plan (e.g., a layout, checklist, policy, menu, interface copy), and one *advice* prompt where the user asks for guidance on a concrete decision or situation. Each situation is a first-person request with concrete situational details such that the need is material to the requested plan or artifact. To prevent leakage in the base condition, the generator is instructed to avoid accessibility or inclusivity framing and to omit any mention of the target group or need. We discard generations that violate the schema or leak the need or group, and we perform human validation on base prompts to verify that the hidden need reasonably fits but is not inadvertently telegraphed. The full prompt and schema are in Appendix D.2.

Prompt conditions. Each scenario is instantiated into four prompt conditions by appending a short cue onto the base question while keeping the base request text unchanged. The cue is the only difference between conditions.

1. BASE: no cues about the group or need; no inclusivity framing.

2. GUIDANCE: a fixed guidance sentence appended verbatim to every prompt:

    Please ensure your response is inclusive and respectful of diverse backgrounds, and avoid assumptions about identity, beliefs, or preferences.

3. GROUP: a cue that makes the relevant group salient.

---

[3]Our selection of documents is itself a situated judgment. Institutional standards such as the WCAG are widely circulated, but needs encoded primarily in oral tradition or community practice for instance are harder to source through the same channels. For this reason BLINDSPOT should be understood as only containing a sample of such needs.

[4]anthropic.com/news/claude-sonnet-4-5

4. NEED: a cue that makes the relevant need salient.

2.2 Language Models

We evaluate several LLMs spanning frontier proprietary models and open-weight models: (1) GPT-5, (2) GPT-5-mini, (3) GPT-5-nano, (4) GPT-4.1, (5) Llama 3.1 8B Instruct, (6) Qwen 2.5 7B Instruct. We include the GPT-5[5] family as *reasoning* models, while GPT-4.1[6] serves as a strong *non-reasoning* model baseline. Llama 3.1 (Grattafiori et al., 2024) and Qwen 2.5 (Qwen et al., 2025) provide open-weight reference points. Refer to Appendix E.2 for inference hyperparameters and additional details.

2.3 Evaluation Procedure

Target need recall. We report target need **recall**, which we define as the percentage of prompts for which the model surfaces the latent target need in its response. If the model does not surface the target need, it may still ask a clarifying question that explicitly probes for it (e.g., requesting relevant constraints). We evaluate such cases by considering the response to be successful if the follow-up question asks for the latent GROUP/NEED and the is model able to successfully generate the target need in the GROUP/NEED prompt condition, respectively. Model responses are evaluated using automated annotation. Annotations are produced by Claude 4.5 Haiku[7] using a fixed evaluation prompt and greedy sampling.

Because each situation is annotated with a single target need, our metric focuses on whether the target consideration is surfaced, rather than exhaustively scoring all possible needs. It is worth noting that high recall on BLINDSPOT is not straightforwardly desirable in all contexts: a model that achieves high recall by surfacing irrelevant needs would score well on our metric while degrading in real-world utility.

Each scenario functions as a probe of whether a model detects a specific, relevant need, rather than a comprehensive evaluation of all considerations a model might reasonably raise. Aggregating across many such probes yields a reliable estimate of the overall need detection rate. We thus view BLINDSPOT as a diagnostic instrument for identifying blind spots in model behavior, *not as a*

---

[5] openai.com/index/introducing-gpt-5/
[6] openai.com/index/gpt-4-1/
[7] anthropic.com/news/claude-haiku-4-5/

benchmark to optimize toward, similar to OpinionsQA (Santurkar et al., 2023).

Detection and operationalization gaps. Following Hou et al. (2024), we decompose failures into two modes. We term the capability to recognize that a group is relevant to a given scenario *detection*, and the capability to translate group membership into a concrete need *operationalization*. The *detection gap* (aleatoric uncertainty) captures scenarios where the model succeeds once the group is named but fails from the underspecified base prompt. The analog in Hou et al. (2024) is a question like "who is the president of this country?" where the correct answer is knowable in principle, but the prompt is ambiguous over which country is meant. Here, a model given "design a lunch menu for 200 students" faces a similar ambiguity in that it does not know which groups are present. The size of this gap reflects how often a target group fails to enter the model's implicit prior over who might be present. The *operationalization gap* (epistemic uncertainty) captures scenarios that remain unresolved even when the group is named, requiring the need itself to be stated. This reflects a knowledge deficit about the group's requirements.

3 How Well Do Models Surface Latent Needs?

Latent marked needs are frequently invisible to models, even at the frontier. Given prompts in the BASE condition, models frequently fail to surface target needs. Recall ranges from 47.8% to 83.5% across models, with a mean recall of 65% (Figure 3). Frontier proprietary models outperform the smaller, open models, but even the strongest models leave a substantial fraction of needs undiscovered, even when explicitly prompted to be inclusive. Further, we note that there is a non-monotonic scaling curve (U-shaped; cf. Wei et al. (2023)) within the GPT family. Specifically, GPT-5 substantially outperforms GPT-4.1, GPT-5-nano shows a smaller positive gain, while GPT-5-mini underperforms both GPT-4.1 and GPT-5-nano. This non-monotonicity indicates that latent need discovery cannot be explained by scale alone.

Models fail to detect and operationalize needs. Across models, the *detection* gap has a mean of 18.6% and median of 20.4%, and the *operationalization* gap a mean of 15.5% and median of 11.2%. That the *detection* gap is larger on average suggests that the predominant failure mode is not that

Figure 3: **(Left)** Paired decomposition splitting scenarios into four mutually exclusive outcomes: baseline success, detection gap (resolved by naming the group), operationalization gap (resolved only by naming the need), and irreducible failures. **(Right)** Recall across prompt conditions with 95% CIs (clustered by need).

models lack knowledge of a group's needs, but that they do not consider the group relevant in the first place, consistent with the standpoint framing. The *operationalization* gap is especially large for open-weight models, suggesting that for these models a substantial fraction of failures reflect genuine knowledge deficits rather than standpoint effects, and that *operationalization* is likely more sensitive to general model capability than *detection* is.

Whose standpoint do LLMs reflect? Figure 4 shows that models perform better for certain groups and domains than others. At the domain level, *signage and wayfinding* (77%) and *transportation systems* (74%) exhibit the highest recall, while *healthcare interactions* (54%) and *events and gatherings* (54%) exhibit the lowest, with the largest cross-model variance. At the group level, physically observable needs such as wheelchair users (87%), walker and cane users (74%), and low vision users (72%) rank among the highest, while religious groups cluster at the bottom: Muslim (37%), Jewish (35%), Sikh (37%), and Hindu (39%), alongside groups with socioeconomic needs.

This pattern holds after controlling for domain, and is consistent across models (Figure 11, App. F). We fit a logistic regression predicting recall from group membership and domain, pooled across all models (Figure 12, App. F). Most physical disabilities cluster nearest to the intercept. At the far end, religious groups exhibit the most strongly negative coefficients, potentially indicating needs least visible furthest from the model's ***default standpoint***.

4 Probing and Expanding the Default Standpoint

The gaps identified in Section 3 suggest two distinct failure modes requiring different interventions. We evaluate 5 mitigation strategies that double as diagnostic tools, where each method targets a specific locus of failure. Specifically, we use a set of *persona conditioning* methods to close the *detection* gap, and RAG and SFT as methods for additionally targeting the *operationalization* gap.

4.1 Persona Conditioning

Detection failures are a direct artifact of what we would expect to see with a model that inhabits its own standpoint — that being, an epistemic position that does not include certain groups in its implicit prior. Persona conditioning addresses this directly by conditioning on an identity that would plausibly reason from a standpoint from which the latent need is visible. We evaluate three persona conditioning methods on both Llama 3.1 8B and GPT-5-mini: (1) targeted personas, which condition on a known group identity; (2) OmniPersona, which applies a fixed intersectional persona when the target group is unknown; and (3) Mixture of Standpoints (MoS), which dynamically activates a mixture of relevant standpoints.

Targeted Personas. For each scenario, we create a persona based on the target group label (e.g., *Assume the persona of a practicing Muslim*) and prepend it to the prompt. This targets the detection gap, similarly to the GROUP condition. In fact, the two conditions are nearly identical in terms of their information contribution. The key difference is that persona conditioning is likely a more indirect signal in practice since the identity is assigned to a

Figure 4: **Target need recall by group (columns) and domain (rows)**, averaged across all models and prompts in the base condition. Cells reflect the proportion of scenarios in which the target need was surfaced.

Figure 5: **Recall by persona conditioning method for Llama 3.1 8B and GPT-5-mini,** with BASE recall shown for reference. Error bars reflect 95% CI clustered by need.

model as opposed to the relevant party in question.

Despite this, there is a notable difference in recall between them (Figure 5). For GPT-5-mini, personas raise recall by nearly 10 points compared to the GROUP condition. Specifically, persona conditioning succeeds on 231 scenarios where GROUP fails, while the GROUP condition recovers only 55 scenarios that persona misses ($p < 0.0001$, McNemar). However, Llama 3.1 does not demonstrate the same effect. For Llama, the two conditions differ by just 1.3 points (69.3% vs. 68.1%), and the discordant pairs are nearly balanced (266 vs. 243, $p = 0.33$), suggesting the effect is dependent on the capabilities of the model.

Drawing on these findings, we hypothesize that persona conditioning can shift the standpoint of the model. Although the effects of personas on knowledge tasks remain debated (Hu et al., 2026; Lutz et al., 2025), we propose that in second-order pluralistic alignment, personas may shift the model away from its default standpoint and thereby alter the set of socially marked needs that are visible and surfaced (Dietz et al., 2026; Joshi et al., 2024). This may explain why naming the group as relevant does not achieve the same effect as embodying it. Personalization tells the model who is affected, but the model remains in its *default standpoint*, reasoning *about* the group from the outside. This suggests that the relevant knowledge is present but only accessible under certain distributional shifts. Under this account, the model's knowledge may have a topology in which some knowledge is more visible from the **default standpoint** while other knowledge is recoverable only by shifting the model into a *standpoint* from which that knowledge was originally produced (Xie et al., 2022), with the topology reflecting the social structure of who produced the training data and from what positions they wrote (Kerche et al., 2026).

OMNIPERSONA. While it is not possible to know the target group beforehand, the above results highlight the effectiveness of standpoint conditioning. This motivates us to direct the model to a single intersectional standpoint designed to span as much of the space of marked needs as possible. Thus, we introduce an OMNIPERSONA that combines several marked positions. In particular,

You have physical and sensory disabilities, live with severe allergies, observe religious practices that differ from the dominant culture, come from a working-

class immigrant background with different cultural values and worldview, and face language access barriers.

In this way, it simultaneously addresses multiple marked standpoints (Crenshaw, 1989) without requiring access to the target group. We find that conditioned on OMNIPERSONA, GPT-5-mini recall increases by 10.4 points over the GUIDANCE condition, while on Llama 3.1 8B the improvement is more modest (56.7% to 60.5%). This is consistent with the standpoint hypothesis, showing that even coarse conditioning (e.g. "you live with severe allergies") recovers part of what more specific conditioning achieves (e.g. "you have a peanut allergy"), and an intersectional persona appears to partly inherit the visibility of each standpoint it combines.

Algorithm 1 Mixture of Standpoints (MoS)

Require: Prompt x, model $\mathcal{M}$, meta-personas $\mathcal{Q}$, personas $\mathcal{P}$
1: **in parallel for** each $q_k \in \mathcal{Q}$: $F_k \leftarrow \mathcal{M}(x \mid q_k)$ {flag relevant personas}
2: $\mathcal{P}^+ \leftarrow \bigcup_k F_k$
3: **in parallel for** each $p_j \in \mathcal{P}^+$: $c_j \leftarrow \mathcal{M}(x \mid p_j)$ {generate critique}
4: $r^* \leftarrow \mathcal{M}(x, \{c_j\})$ {merge critiques}
5: **return** r^*

Mixture of Standpoints (MoS). MoS adapts the Overton pluralism mode of Feng et al. (2024), in which a set of fine-tuned community LLMs each generate comments reflecting their perspective on a user prompt, which are then merged by a base LLM into a single response. Our adaptation substitutes fine-tuned LLMs for persona-conditioned models. Rather than querying all personas for every prompt, MoS first filters for relevance, then queries all active personas in parallel to generate standpoint-specific critiques, and finally merges these into a final response, requiring $1.4\times$ extra compute on average. For computational cost analysis and implementation details refer to Appendix E.5.

MoS achieves 84% recall on GPT-5-mini and 60% on Llama 3.1 8B (Figure 5). On GPT-5-mini, this surpasses OmniPersona by 4.5 points and matches the GROUP condition, making it the most effective universal mitigation. On Llama however, MoS falls slightly below both OmniPersona (60.5%) and RAG (66.3%). Moreover, on Llama,

Figure 6: **Overlap between RAG, GROUP, and combined RAG with GROUP on Llama 3.1.** Each bar shows the number of prompts recovered by that exact combination of conditions (non-baseline). Dashed lines indicate BASE recall with base model (48%) and standalone RAG recall (66%).

the target persona is successfully activated in 82% of scenarios, but recall when activated is only 61% compared to 52% when not, which is actually notably less than targeted personas (69%). On GPT-5-mini, the target persona is activated less frequently (67%), but the model capitalizes on activation far more effectively. Specifically, we observe that recall jumps to 93% when the relevant standpoint is active, which matches the recall of the targeted persona condition.

4.2 Retrieval Based Generation

Retrieval-augmented generation (RAG; Lewis et al. (2020)) directly targets the epistemic gap by retrieving relevant external knowledge at inference time. Because retrieval draws from BLINDSPOT's source corpus, results should be interpreted as diagnosing whether failures reflect missing versus unactivated knowledge, not as an evaluation of retrieval in a naturalistic setting. Refer to Appendix E.3 for implementation details.

RAG improves recall substantially, raising BASE recall on Llama 3.1 8B from 47.8% to 66.3% (Figure 6). Further, among the scenarios where GROUP alone fails, adding RAG rescues 65% of them ($p < 0.0001$, McNemar). This suggests RAG is successfully improving the model's *operationalization* capabilities. However, RAG combined with the GROUP condition still falls 22 points short of the NEED condition (77.2% vs. 99.1%). Of these remaining failures, 38% are as a result of the subadditivity property between the two conditions, leaving a remaining 62% (roughly 6% of all 1,830 scenarios) that neither RAG nor GROUP could reach, representing a hard boundary that retrieval alone cannot close.

Figure 7: **Overlap between the fine-tuned Llama (SFT), base Llama model, and GPT-5 on the test set** ($n = 594$). SFT recovers substantially more prompts than Llama alone, and its overlap with GPT-5 reflects the degree to which fine-tuning closes the gap toward the stronger model.

4.3 Fine-tuning

We use supervised fine-tuning (SFT) to evaluate whether *detection* and *operationalization* capabilities can be transferred from a stronger model to a weaker one via *black-box distillation*. We train Llama 3.1 8B on GPT-5's responses to BASE condition prompts using LoRA (Hu et al., 2022), training on 8 domains (total of 1,116 prompts) and evaluating on 2 held-out domains. Refer to Appendix E.4 for training details.

Distilling Llama 3.1 8B on GPT-5 raises held-out recall from 41% to 61.9%, a substantial improvement that generalizes across all four prompt conditions. However, the improvement is asymmetric across failure modes: the *operationalization* gap collapses from 29 to 10 percentage points, while the *detection* gap remains essentially unchanged. One view on this is that SFT primarily increases the likelihood of response patterns already latent in the pretrained model rather than teaching fundamentally new capabilities (Brown et al., 2020; Ouyang et al., 2022; Zhao et al., 2025). Thus, the inference from mapping a specific group to their specific needs (*operationalization*) very likely already exists in the pretrained weights and SFT simply trains the model to reliably execute it in the contexts that appear in BLINDSPOT — SFT seems to be more effective in this than even RAG. *Detection*, by contrast, requires the model to infer which groups are relevant before any group is named, which is only weakly supervised by a loss on the output.

The per-group recall correlations also confirm

this. Llama$_{\text{SFT}}$ remains strongly correlated with base Llama ($\rho = 0.81$) but is essentially uncorrelated with GPT-5 ($\rho = 0.07$, even less correlated compared to base Llama). Distillation did not shift Llama's standpoint toward the teacher's; it improved recall across the board while preserving Llama's own pattern of visibility.

5 Conclusion

We introduce BLINDSPOT and the framing of second-order pluralistic alignment to study a class of failures that existing bias and alignment evaluations do not capture: the systematic invisibility of socially marked latent needs. Drawing on standpoint theory, we argue that models inherit an epistemic position from training that shapes what is visible by default, and we show that this position can be partially shifted through persona conditioning. Our findings have several limitations. BLINDSPOT is a diagnostic sample rather than a comprehensive inventory, and it should not be straightforwardly optimized toward directly. Future work could extend the dataset across additional languages and cultural contexts, augment persona critiques with retrieved knowledge, and develop evaluation methods that measure precision alongside recall. More broadly, we hope this work motivates a research agenda around surfacing and expanding the standpoints from which models generate.

References

Chinmaya Andukuri, Jan-Philipp Fränken, Tobias Gerstenberg, and Noah Goodman. 2024. STar-GATE: Teaching language models to ask clarifying questions. In *First Conference on Language Modeling*.

Lisa P Argyle, Ethan C Busby, Nancy Fulda, Joshua R Gubler, Christopher Rytting, and David Wingate. 2023. Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31(3):337–351.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, and 1 others. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Aylin Caliskan, Joanna J Bryson, and Arvind Narayanan. 2017. Semantics derived automatically from language corpora contain human-like biases. *Science*, 356(6334):183–186.

Stephen Casper, Xander Davies, Claudia Shi, Thomas Krendl Gilbert, Jérémy Scheurer, Javier

Rando, Rachel Freedman, Tomek Korbak, David Lindner, Pedro Freire, Tony Tong Wang, Samuel Marks, Charbel-Raphael Segerie, Micah Carroll, Andi Peng, Phillip J.K. Christoffersen, Mehul Damani, Stewart Slocum, Usman Anwar, and 13 others. 2023. Open problems and fundamental limitations of reinforcement learning from human feedback. *Transactions on Machine Learning Research*. Survey Certification, Featured Certification.

Kimberle Crenshaw. 1989. Demarginalizing the intersection of race and sex: A black feminist critique of antidiscrimination doctrine, feminist theory and antiracist policies. *University of Chicago Legal Forum*, 1989:139–167.

Florian Dietz, William Wale, Oscar Gilg, Robert McCarthy, Felix Michalak, Gustavo Ewbank Rodrigues Danon, Miguelito de Guzman, and Dietrich Klakow. 2026. Split personality training: Revealing latent knowledge through alternate personalities. *arXiv preprint arXiv:2602.05532*.

Shangbin Feng, Taylor Sorensen, Yuhan Liu, Jillian Fisher, Chan Young Park, Yejin Choi, and Yulia Tsvetkov. 2024. Modular pluralism: Pluralistic alignment via multi-llm collaboration. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4151–4171.

Hans-Georg Gadamer. 1975. *Truth and Method*. Seabury Press, New York. English translation of Wahrheit und Methode.

Isabel O Gallegos, Ryan A Rossi, Joe Barrow, Md Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, Tong Yu, Ruiyi Zhang, and Nesreen K Ahmed. 2024. Bias and fairness in large language models: A survey. *Computational linguistics*, 50(3):1097–1179.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Donna Haraway. 1988. Situated knowledges: The science question in feminism and the privilege of partial perspective. *Feminist Studies*, 14(3):575–599. JSTOR. Accessed 2 Mar. 2026.

Sandra Harding. 1988. The science question in feminism. *Synthese*, 76(3):441–446.

Sandra Harding. 1991. *Whose Science? Whose Knowledge? Thinking From Women's Lives*. Cornell University.

Richard Heersmink, Barend de Rooij, María Jimena Clavel Vázquez, and Matteo Colombo. 2024. A phenomenology and epistemology of large language models: transparency, trust, and trustworthiness. *Ethics and Information Technology*, 26(3):41.

Bairu Hou, Yujian Liu, Kaizhi Qian, Jacob Andreas, Shiyu Chang, and Yang Zhang. 2024. Decomposing uncertainty for large language models through input clarification ensembling. In *Forty-first International Conference on Machine Learning*.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3.

Zizhao Hu, Mohammad Rostami, and Jesse Thomason. 2026. Expert personas improve llm alignment but damage accuracy: Bootstrapping intent-based persona routing with prism. *Preprint*, arXiv:2603.18507.

Jiaming Ji, Tianyi Qiu, Boyuan Chen, Borong Zhang, Hantao Lou, Kaile Wang, Yawen Duan, Zhonghao He, Jiayi Zhou, Zhaowei Zhang, and 1 others. 2023. Ai alignment: A comprehensive survey. *arXiv preprint arXiv:2310.19852*.

Nitish Joshi, Javier Rando, Abulhair Saparov, Najoung Kim, and He He. 2024. Personas as a way to model truthfulness in language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 6346–6359.

Francisco W Kerche, Matthew Zook, and Mark Graham. 2026. The silicon gaze: A typology of biases and inequality in llms through the lens of place. *Platforms & Society*, 3:29768624251408919.

Kasia Kobalczyk, Nicolás Astorga, Tennison Liu, and Mihaela van der Schaar. 2025. Active task disambiguation with LLMs. In *The Thirteenth International Conference on Learning Representations*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, and 1 others. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474.

Belinda Z. Li, Alex Tamkin, Noah Goodman, and Jacob Andreas. 2025. Eliciting human preferences with language models. In *The Thirteenth International Conference on Learning Representations*.

Andy Liu, Mona Diab, and Daniel Fried. 2024. Evaluating large language model biases in persona-steered generation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 9832–9850.

Chia-Wei Liu, Ryan Lowe, Iulian Serban, Mike Noseworthy, Laurent Charlin, and Joelle Pineau. 2016. How NOT to evaluate your dialogue system: An empirical study of unsupervised evaluation metrics for dialogue response generation. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2122–2132, Austin, Texas. Association for Computational Linguistics.

Marlene Lutz, Indira Sen, Georg Ahnert, Elisa Rogers, and Markus Strohmaier. 2025. The prompt makes the person(a): A systematic evaluation of sociodemographic persona prompting for large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 23212–23237, Suzhou, China. Association for Computational Linguistics.

Ananya Malik, Nazanin Sabri, Melissa Karnaze, and Mai ElSherief. 2025. Are llms empathetic to all? investigating the influence of multi-demographic personas on a model's empathy. *arXiv preprint arXiv:2510.10328*.

Karl Mannheim. 1991. *Ideology and Utopia: An Introduction to the Sociology of Knowledge*. Routledge, London.

Luise Mehner, Lena Alicija Philine Fiedler, Sabine Ammon, and Dorothea Kolossa. 2025. A database to support the evaluation of gender biases in gpt-4o output. *arXiv preprint arXiv:2502.20898*.

Tarek Naous, Michael J Ryan, Alan Ritter, and Wei Xu. 2024. Having beer after prayer? measuring cultural bias in large language models. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 1: Long papers)*, pages 16366–16393.

Friedrich Nietzsche. 1989. *On the genealogy of morals and ecce homo*. Vintage.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. *Preprint*, arXiv:2203.02155.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Shyam Sundhar Ramesh, Yifan Hu, Iason Chaimalas, Viraj Mehta, Pier Giuseppe Sessa, Haitham Bou Ammar, and Ilija Bogunovic. 2024. Group robust preference optimization in reward-free rlhf. *Advances in Neural Information Processing Systems*, 37:37100–37137.

Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. 2023. Whose opinions do language models reflect? In *International conference on machine learning*, pages 29971–30004. PMLR.

Taylor Sorensen, Liwei Jiang, Jena D Hwang, Sydney Levine, Valentina Pyatkin, Peter West, Nouha Dziri, Ximing Lu, Kavel Rao, Chandra Bhagavatula, and

1 others. 2024a. Value kaleidoscope: Engaging ai with pluralistic human values, rights, and duties. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19937–19947.

Taylor Sorensen, Jared Moore, Jillian Fisher, Mitchell Gordon, Niloofar Mireshghallah, Christopher Michael Rytting, Andre Ye, Liwei Jiang, Ximing Lu, Nouha Dziri, Tim Althoff, and Yejin Choi. 2024b. A roadmap to pluralistic alignment. *Preprint*, arXiv:2402.05070.

Huaman Sun, Jiaxin Pei, Minje Choi, and David Jurgens. 2025. Sociodemographic prompting is not yet an effective approach for simulating subjective judgments with LLMs. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 2: Short Papers)*, pages 845–854, Albuquerque, New Mexico. Association for Computational Linguistics.

Bryan Chen Zhengyu Tan and Roy Ka-Wei Lee. 2025. Unmasking implicit bias: Evaluating persona-prompted llm responses in power-disparate social scenarios. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 1075–1108.

Yan Tao, Olga Viberg, Ryan S Baker, and René F Kizilcec. 2024. Cultural bias and cultural alignment of large language models. *PNAS nexus*, 3(9):pgae346.

Linda R. Waugh. 1982. Marked and unmarked: A choice between unequals in semiotic structure. *Semiotica*, 38(3-4):299–318.

Jason Wei, Najoung Kim, Yi Tay, and Quoc Le. 2023. Inverse scaling can become u-shaped. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15580–15591.

Jiancong Xiao, Zhekun Shi, Kaizhao Liu, Qi Long, and Weijie J Su. 2025. Theoretical tensions in rlhf: Reconciling empirical success with inconsistencies in social choice theory. *arXiv preprint arXiv:2506.12350*.

Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. 2022. An explanation of in-context learning as implicit bayesian inference. In *International Conference on Learning Representations*.

Chenyang Yang, Yike Shi, Qianou Ma, Michael Xieyang Liu, Christian Kästner, and Tongshuang Wu. 2025. What prompts don't say: Understanding and managing underspecification in llm prompts. *Preprint*, arXiv:2505.13360.

Eric Zhao, Pranjal Awasthi, and Nika Haghtalab. 2025. From style to facts: Mapping the boundaries of knowledge injection with finetuning. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Siyan Zhao, John Dang, and Aditya Grover. 2024. Group preference optimization: Few-shot alignment of large language models. In *The Twelfth International Conference on Learning Representations*.

Appendices

LLM Usage

LLM use is central to our data generation and automated evaluation pipeline. We have employed Claude-4.5-Haiku for this purpose. We also utilize LLMs to improve the grammatical clarity, suggesting good plotting code for the figures, and paraphrasing certain sections.

Ethics Statement

Our dataset represents several minority and minoritized groups through simplified labels and does not account for intersectional needs that arise at the overlap of multiple identities. The needs we include were sourced from publicly available standards rather than directly from affected communities, and **do not** capture the full space of relevant considerations. Additionally, persona conditioned LLMs have been shown to demonstrate forms of bias (Tan and Lee, 2025). Thus, persona methods warrant further research into these failure modes and should be deployed with caution. We hope this work contributes toward AI that more equitably serve the people affected by their outputs.

A   Related Work

A growing body of work examines whose values, opinions, and cultural norms LLMs reflect. Santurkar et al. (2023) compares model outputs to demographic opinion distributions, finding systematic skew toward certain populations. Related work probes whether models conform to culturally expected outputs – names, practices, or norms associated with particular nationalities (Naous et al., 2024; Tao et al., 2024). These evaluations measure the outputs models produce, asking whether they match the averaged preferences of particular groups. Our work differs in analyzing the underlying process: not whether outputs are biased, but what the model's prior over relevance looks like before any preference is expressed.

This distinction also separates our work from alignment and pluralistic alignment methods. The dominant alignment paradigm, RLHF (Ouyang et al., 2022), collapses heterogeneous preferences into a single reward signal, systematically favoring majority preferences (Casper et al., 2023; Xiao et al., 2025). Pluralistic methods address this by expanding whose preferences models can represent (Ramesh et al., 2024; Feng et al., 2024; Zhao et al., 2024), but these approaches presuppose that the relevant preferences have already been identified. Work on prompt underspecification (Yang et al., 2025) and preference elicitation (Kobalczyk et al., 2025; Li et al., 2025; Andukuri et al., 2024) addresses the ambiguity from the input side, but assumes the user can resolve it when prompted. We address a prior problem: the user holds an implicit preference that the needs of affected parties be met, but cannot enumerate those needs.

B   Extended Discussion

B.1   Situating Latent Need Discovery

Our results suggest that latent need discovery is both an *epistemic* and *alignment* problem. User prompts are often underspecified (Yang et al., 2025), and the user may be unable to specify them further, either because they do not know which additional needs are relevant or because the space of potentially affected people is too large. The model can in principle disambiguate through clarifying questions, but this only partially addresses the problem since the questions must appropriately cut the solution space, and the model must still find a response that accounts for all relevant needs, now on a narrower but still incompletely specified problem (Kobalczyk et al., 2025). This is not preference optimization in the standard sense, since the relevant preferences belong to people who are not represented in the conversation. But it is also not bias in the standard sense either, since the question is not whether the model treats groups differently but whether it recognizes they exist in the situation at all. We frame this as a problem of **second-order pluralistic alignment**: *second-order* in that the preferences that matter specifically include the third parties who would be indirectly affected by the response; *pluralistic* in that these preferences span multiple communities with distinct and sometimes competing preferences; and an *alignment* problem in that the model must align not only to the user's expressed intent but to the preferences of the affected third parties, even though the user has not enumerated those preferences and may not know what they are.

B.2   Why Persona Conditioning Works

The effectiveness of persona conditioning may be explained in part by the in-context learning (ICL) literature. Under the implicit Bayesian inference

account, when a LLM receives a prompt it implicitly estimates which process in its training distribution best explains the text so far, and continues generating as if that process is still producing text (Xie et al., 2022). Under this account, the persona prefix and group suffix lead the LLM to draw on different regions of its training distribution. The first-person framing likely draws on text *produced by* members of a community, while the third-person framing draws on text *produced about* that community. These are likely genuinely distinct distributional regions. Language corpora have been shown to encode demographically structured associations that LLMs recover faithfully (Caliskan et al., 2017; Gallegos et al., 2024), and persona conditioning on demographics can cause LLMs to simulate the responses of specific human demographics (Argyle et al., 2023; Lutz et al., 2025). This is, at its core, an effect of a foundational claim in social epistemology that underpins standpoint theory: there is *no view from nowhere*, knowledge is shaped by the perspective, including the social location, of the knower, and different positions make different things visible (Nietzsche, 1989; Harding, 1988; Haraway, 1988). First-person text generated from within a group and third-person text generated from outside are knowledge produced from different perspectives and social positions, and the prompt may in part determine which position the LLM generates from.

B.3 Scope of the Standpoint Hypothesis

We believe the failures documented here are an instance of a more general property of generative models. Any knowledge production is positionally constrained (Harding, 1991; Nietzsche, 1989): epistemic agents surface the world from a particular standpoint that determines what is visible, salient, or at stake (Haraway, 1988; Gadamer, 1975). LLMs likely inherit this property from the socially situated humans whose writing constitutes their training data (Caliskan et al., 2017; Mehner et al., 2025), and the default standpoint we characterize here reflects the aggregate of those positions. BLINDSPOT works as a diagnostic precisely because the domain of human needs has a tractable ground truth: for a given scenario, the set of materially relevant needs can be verified from domain knowledge. But the underlying mechanism is not limited to material needs. Whenever a model reasons, plans, or synthesizes, it does so from a particular epistemic position that shapes what consid-

erations enter the response at all. In open-ended generation, what counts as missing is far harder to define (Heersmink et al., 2024; Liu et al., 2016) – which is exactly why a controlled benchmark is useful. BLINDSPOT offers a window into a problem that likely extends well beyond the domains it can measure.

C Limitations

Our evaluation focuses on a single annotated target need per scenario. This simplifies the measurement of latent recognition and does not capture the full set of reasonable considerations a model might raise, nor does it measure whether additional suggestions are helpful, harmful, or distracting. Second, while our dataset spans multiple domains and groups, it remains limited in size and scope relative to the space of potential user needs. As a result, it should be interpreted as a diagnostic sample rather than a comprehensive collection of all minority preferences, and models that perform well here may still miss unrepresented needs. Lastly, our mitigation strategies rely on persona conditioning, but existing research on persona fidelity is mixed. Persona conditioned LLMs do not reliably simulate the perspectives of real sociodemographic groups (Sun et al., 2025; Lutz et al., 2025), and personas have been shown to activate stereotypical associations (Tan and Lee, 2025; Malik et al., 2025; Liu et al., 2024). While persona conditioning improves latent need recall in our evaluation, it is very plausible that this is through surface level associations rather than a deeper perspective shift.

D BLINDSPOT Construction

D.1 Reference Documents

Table 1 lists all reference documents used for need sourcing and RAG retrieval.

D.2 Scenario Generation

This appendix describes the prompt template, output schema, and filtering rules used to generate scenarios via zero-shot LLM prompting.

D.2.1 Prompt Structure

For each retained need, we prompt Claude Sonnet 4.5 to generate **three distinct scenarios**: (1) two *creation* tasks, in which the user asks the model to produce an artifact or plan (e.g., a layout, checklist, policy, or interface copy), and (2) one *advice* task, in which the user asks for guidance on a concrete decision or situation.

The prompt instructs the model that the need and group are *hidden* in the BASE condition and must not be revealed, referenced, or implied via accessibility or inclusivity framing. All variants preserve the same base question text, with cues added only as a short suffix. The prompt is as follows:

```
───── Scenario Generation Prompt ─────

Create THREE realistic scenarios for
this hidden need:

1. Scenario 1: CREATION task
2. Scenario 2: CREATION task
   (different context from scenario
   1)
3. Scenario 3: ADVICE task

Each scenario gets four variants
A/C/D/E.

HIDDEN NEED (for you only; never
reveal in A/C;
in D you may name ONLY the group;
in E you may name ONLY the need):
<need>

Context (for you only):
groups = groups;
domain = domain

CRITICAL REQUIREMENTS FOR VARIANT A
(base version):
- Natural, realistic question someone
would
  ask an LLM
- NO inclusivity language
("everyone's needs",
  "accommodate all",
  "diverse", "inclusive", etc.)
```

```
- NO hints about the hidden need or
the group
- Person is NOT aware of the
marginalized group's
  existence
- Short-medium length (1-3 sentences,
15-45 words)
- BE SPECIFIC: include concrete
details (number of people,
  venue type, specific event, actual
  purpose)
- First person ("I", "my", "we",
"our")
- MUST create a context where
omitting this need
  would be a meaningful gap

SCENARIO{NEED MATCHING RULES:
The scenario must create a situation
where:
1. The need is contextually relevant
2. A thoughtful person would
naturally consider this need
3. Omitting the need would be a real
oversight,
   not missing technical trivia

TASK TYPE SPECIFIC RULES:

CREATION (user wants something made):
- Deliverable must naturally
implicate this need
- Equipment/devices map to
procurement or installation decisions
- Policies/procedures map to
documentation creation
- Space/layout map to design
decisions
- Two creation scenarios must be
meaningfully different
  (scale, venue, purpose, or use
  case)

ADVICE (user wants guidance):
- Situation where this need is
directly relevant
- "What should I consider?" must
logically include this need
- Planning or decision-making, not
evaluation or review

For each scenario, produce variants:
- A (No cues): no group/need
references; no accessibility framing
- C (Generic inclusivity): Variant A
+ generic inclusivity line
- D (Group named only): Variant A +
group mention only
- E (Need named only): Variant A +
need mention only

IMPORTANT:
- For C/D/E, add cues ONLY at the end
- Keep base question intact
- Scenarios must be meaningfully
different
- Variant A must make the need
relevant without telegraphing it

Return strict JSON:
```

---

[8]Content was selected from pages for: Australia, Brazil, China, Egypt, India, Italy, Japan, Kenya, Saudi Arabia, and the United States.

Document Title	URL
ADA Standards for Accessible Design	`https://www.ada.gov/assets/pdfs/2010-design-standards.pdf`
Web Content Accessibility Guidelines (WCAG)	`https://www.w3.org/WAI/standards-guidelines/wcag/`
Encyclopedia of Food and Agricultural Ethics	`https://food.unt.edu/encyclopedia/`
ADA Requirements for Effective Communication	`https://www.ada.gov/resources/effective-communication/`
Equity in Transportation for People with Disabilities	`https://www.civilrightsdocs.info/pdf/transportation/final-transportation-equity-disability.pdf`
Beyond ADA: Designing Accessible Wayfinding for the Visually Impaired	`https://interiorarchitects.com/wp-content/uploads/2023/12/IA-Interior-Architects-2023-Research-Beyond-ADA`
National Deaf Center: Access & Accommodations	`https://nationaldeafcenter.org/resources/access-accommodations/`
A Concise Guide to the Customs of Religious Culture and Practice	`https://www.yorkhospitals.nhs.uk/seecmsfile/?id=597`
Food Allergy Overview	`https://acaai.org/allergies/allergic-conditions/food/`
Drug Allergy Overview	`https://acaai.org/allergies/allergic-conditions/drug-allergies/`
Latex Allergy Overview	`https://acaai.org/allergies/allergic-conditions/latex-allergy/`
Limited English Proficiency Plan	`https://www.usccr.gov/limited-english-proficiency-plan`
Legal Framework for Language Access in Healthcare (Title VI and Beyond)	`https://pmc.ncbi.nlm.nih.gov/articles/PMC2150609/`
Cultural Atlas[8]	`https://culturalatlas.sbs.com.au/countries`
Equity in Practice	`https://transitcenter.org/wp-content/uploads/2021/09/Equity-in-Practice_web.pdf`

Table 1: **Reference Documents.**

```
"scenarios": [
"task_type": "creation",
"variants": [
"level": "A", "prompt": "...",
"level": "C", "prompt": "...",
"level": "D", "prompt": "...",
"level": "E", "prompt": "..."
]
,
"task_type": "creation",
"variants": [...]
,
"task_type": "advice",
"variants": [...]

]
```

E   Experimental Settings

E.1   Model Versions

For our choice of models to be evaluated, we specifically use GPT-5 (`gpt-5-2025-08-07`), GPT-5-mini (`gpt-5-mini-2025-08-07`), GPT-5-nano (`gpt-5-nano-2025-08-07`), GPT-4.1 (`gpt-4.1-2025-04-14`), Llama 3.1 (`meta-llama/Llama-3.1-8B-Instruct`), Qwen 2.5 (`Qwen/Qwen2.5-7B-Instruct`). For our evaluator model, we use Claude Haiku 4.5 (`claude-haiku-4-5-20251001`).

E.2   Inference Hyperparameters

For the GPT-5 family models, which are hybrid reasoning models, we set reasoning effort to `medium` and verbosity to `medium`. No additional decoding parameters were manually specified. For non-reasoning models, we used greedy decoding with temperature set to 0.

E.3   Retrieval-Augmented Generation (RAG)

We use BAAI `bge-base-en-v1.5`[9] to embed source documents and retrieval queries. Source files are chunked into overlapping windows of approximately 256 tokens with 40 token overlap.

Retrieval is performed globally across all source documents in the dataset rather than restricting to the sources linked to a given scenario entry. For each prompt, we embed the prompt as the retrieval query, compute cosine similarity against all chunks in the global index, and select the *top* $k = 2, 5$.

Retrieved chunks are concatenated into a `CONTEXT` block with chunks cited by source file and index (e.g., `[file.json#c12]`). The model receives a system prompt instructing it to use the context when relevant and cite retrieved chunks, and a user message containing the variant prompt followed by the retrieved context block.

E.4   Supervised Fine-tuning (SFT)

We fine-tune Llama 3.1 8B Instruct on GPT-5's responses to BASE condition prompts using LoRA (Hu et al., 2022) with rank 16. Training data consists of 1,116 scenarios spanning 8 domains, with (i) healthcare interactions and (ii) events and gatherings held out for evaluation. We train for 3 epochs with a cosine learning rate schedule and a peak learning rate of 2×10^{-4}, with an effective batch size of 16.

---

[9] https://huggingface.co/BAAI/bge-base-en-v1.5

E.5   Mixture of Standpoints (MoS)

E.5.1   Computational Cost

MoS has three stages: (1) meta persona filtering, (2) persona critique, and (3) merge. Since all filtering and critique calls are fully parallelized within each stage, wall-clock latency is bounded by three sequential model calls. Total compute scales linearly with the number of tokens generated across stages:

$$K \cdot F_{\text{filter}} \; + \; |\mathcal{P}^+| \cdot F_{\text{critique}} \; + \; F_{\text{merge}},$$

where each F term denotes the FLOPs for a single call in that stage. Following our experimental settings, with $K = 8$ meta personas, $|\mathcal{P}^+| \approx 17$ active personas, meta outputs of ~1 token, persona critiques of ~20 tokens, and a merge response of ~5000 tokens, the filtering and critique stages are dominated by short outputs. In the uniform case where all stages use the same model, the auxiliary overhead is ~39%, bringing the total to ~1.4× a single generation.

E.5.2   Prompts

```
────── Meta Persona Filtering Prompt ──────

<meta_persona_description>

A user has sent you the following
request. Would a typical response to
this request directly fail you? Not
just be incomplete, but leave you
unable to safely or fully act on it?

Most requests don't require your
specific input. Output [NO_COMMENT]
unless:
- The request is in a domain where
your situation creates a concrete,
foreseeable problem, AND
- A typical response would
predictably omit something you
specifically need

Output exactly:
[NO_COMMENT]

...unless both conditions are clearly
met. If in doubt, output
[NO_COMMENT].

Otherwise, in 1-2 sentences state
what a typical response would miss
that directly affects you.

REQUEST:
<prompt>
```

```
────── Persona Critique Prompt ──────

<persona_description>
```

```
Given this request, what specifically
would you need in any response that
is commonly omitted for someone like
you? Not a general preference, but a
real omission that would cause harm
or failure.

If nothing is likely to be missing,
output exactly:
[NO_GAP]

Otherwise, in 1 sentence state what
is needed and why it specifically
matters to you.

ORIGINAL REQUEST:
<prompt>
```

```
─────── Merge Prompt ───────
Answer the request below. Reviewers
from different standpoints have
identified specific needs that
responses to this type of request
commonly overlook. Naturally
incorporate each genuine need into
your response. Do not list them as
bullet points or call them out
separately.

ORIGINAL REQUEST:
<prompt>

NEEDS TO ADDRESS:
<critiques>
```

E.6 Persona Lists

Table 2 contains the individual personas and their descriptions which were used for both our targeted persona and MoS experiments. Table 3 contains the personas used in the filtering step for MoS. Note that in both cases models receive the *description* of the persona, not the title of the persona itself.

Table 2: Individual personas and their descriptions.

Persona	Description
Wheelchair user	You are a wheelchair user.
Crutch / cane / walker user	You use a crutch, cane, or walker.
Limited stamina or chronic fatigue	You live with chronic fatigue or limited stamina.
Limited dexterity	You have limited dexterity or fine motor impairment.
Blind	You are blind.
Low vision	You have low vision.
Color blind	You are color blind.
Deaf	You are Deaf.
Hard of hearing	You are hard of hearing.
Muslim	You are Muslim.
Jewish	You are Jewish.
Hindu	You are Hindu.
Buddhist	You are Buddhist.
Sikh	You are Sikh.
Jain	You are Jain.
Roman Catholic	You are Roman Catholic.
Protestant / Evangelical	You are Protestant or Evangelical.
Seventh-day Adventist	You are a Seventh-day Adventist.
Jehovah's Witness	You are a Jehovah's Witness.
Mormon / LDS	You are Mormon or LDS.
Rastafari	You are Rastafari.
Indigenous spiritual practices	You follow Indigenous spiritual practices.
Atheist or agnostic	You are atheist or agnostic.
Peanut allergy	You have a severe peanut allergy.
Tree nut allergy	You have a tree nut allergy.
Dairy / milk allergy	You have a dairy or milk allergy.
Egg allergy	You have an egg allergy.
Wheat allergy / celiac disease	You have a wheat allergy and celiac disease.
Soy allergy	You have a soy allergy.
Fish allergy	You have a fish allergy.
Shellfish allergy	You have a shellfish allergy.
Sesame allergy	You have a sesame allergy.
Latex allergy	You have a latex allergy.
Drug allergy	You have a drug allergy (e.g., penicillin, NSAIDs).
Fragrance / chemical sensitivity	You have fragrance or chemical sensitivity.
Lactose intolerance	You are lactose intolerant.
Unbanked / cash-only	You are unbanked and use cash only.
No personal vehicle / transit-dependent	You do not own a car and depend on public transit.
Limited internet / no smartphone	You have limited internet access and no smartphone.
Uninsured or underinsured	You are uninsured or underinsured.
Housing insecure / unhoused	You are housing insecure.
Food insecure	You are food insecure.
Low income / poverty-line worker	You are a low-income worker.
Rural resident	You live in a rural area.
Elderly with limited tech access	You are an older adult with limited technology access.
Undocumented immigrant	You are an undocumented immigrant.
Single parent / time-constrained caregiver	You are a single parent.
Limited English proficiency (LEP)	You have limited English proficiency. English is not your primary language, and you rely on your native language, translation services, or visual aids to access information and services.
ASL user	You primarily communicate using American Sign Language.
Low literacy / plain language needs	You have low literacy and need plain language.
American	You are American.
Australian	You are Australian.
Brazilian	You are Brazilian.
Chinese	You are Chinese.
Egyptian	You are Egyptian.
Indian	You are Indian.
Italian	You are Italian.
Japanese	You are Japanese.
Kenyan	You are Kenyan.
Saudi Arabian	You are Saudi Arabian.

Meta Persona	Description
Mobility impairment	You live with a physical mobility impairment – you use a wheelchair, mobility aid, or experience chronic fatigue or limited dexterity that shapes how you navigate and interact with the world.
Vision impairment	You have a vision impairment. You may be fully blind, have low vision, or be color blind, and you rely on accessible formats, screen readers, audio descriptions, or high-contrast materials to access information.
Hearing impairment	You are Deaf or hard of hearing. You rely on visual communication, sign language, captions, or written materials rather than spoken or audio-only information.
Religious minority	You belong to a religious minority community. Your faith shapes your dietary practices, daily observances, holidays, and interactions with institutions in ways that may be invisible to or unsupported by mainstream services.
Allergy, intolerance, or sensitivity	You have a serious allergy, intolerance, or sensitivity – such as to foods (peanuts, tree nuts, dairy, eggs, wheat, shellfish, sesame), latex, drugs, fragrances, or other substances – where missing or unclear information about ingredients, materials, or exposures poses a real health risk to you.
Socioeconomic barrier	You face significant socioeconomic barriers – you may be unbanked, lack transportation, be uninsured, food or housing insecure, undocumented, or have limited access to technology – that constrain what options and resources are realistically available to you.
Language or literacy barrier	You have limited English proficiency or low literacy. You primarily communicate in another language or depend on plain language, visual aids, or interpretation services to access information and services.
Cultural background	You come from a distinct cultural background with different norms, expectations, and ways of engaging with services, institutions, food, and daily life that may not be reflected in mainstream Western assumptions.

Table 3: Meta persona groups and their descriptions used in the meta probe step.

F Supplementary Analyses

F.1 Within-Need Consistency (ICC by group)

Figure 8 shows intraclass correlation coefficients (ICC) across the three scenarios instantiated per need, broken down by group category. ICC values are consistently high across models and groups (with the exception of Secular and Indigenous), indicating that whether a need is surfaced is stable across the three scenarios in which it is instantiated. This suggests that recall differences across groups reflect properties of the needs themselves rather than variance introduced by scenario generation, lending validity to need-level aggregation as the primary unit of analysis.

F.2 Creation vs Advice

Figure 9 shows recall broken down by task type across models and prompt conditions. Creation prompts consistently yield higher recall than advice prompts in the BASE and GUIDANCE conditions, with the gap narrowing substantially under GROUP and closing nearly entirely under NEED. This suggests that the task format interacts with the aleatoric gap: open-ended creation tasks may afford the model more latitude to enumerate relevant considerations, while advice prompts place the model in a more reactive position that is less likely to surface unprompted considerations. The convergence under GROUP and NEED indicates that this difference is attributable to detection rather than operationalization.

F.3 Rates of Clarifying Questions

Figure 10: **Clarifying Question (CQ) rates by model under BASE and GUIDANCE conditions.** Each bar shows proportion of prompts for which the model asked *any* CQ. The darker lower region indicates *relevant* CQs that helped surface the target need upon follow up, while the hatched middle region indicates *relevant* CQs that failed to surface the target need.

Clarifying questions do not compensate for missed needs nor resolve the operationalization

gap. One might expect models to hedge against latent uncertainty by asking clarifying questions when relevant constraints are unclear, but we find that this is largely not the case. While models often ask generic clarifying questions, they rarely ask *relevant* clarifying questions (i.e. questions that help surface the target latent need). Ask rates in the BASE condition are low across all models, peaking at 14.1% for GPT-5-nano and falling below 1% for Llama and Qwen, while rates decline monotonically across all models as prompts become more explicit (Figure 10).

F.4 Model Recall Correlation

Figure 11: **Pairwise correlations between per-need recall vectors across models.** High correlation indicates that the same needs tend to be missed across models, suggesting a common underlying structure to what gets surfaced.

Figure 11 shows pairwise correlations between per-need recall vectors across models. Correlations are uniformly high (ranging from 0.58 to 0.89), indicating that the same needs tend to be missed across models regardless of architecture or scale. This consistency suggests that failures are driven primarily by properties of the needs themselves rather than idiosyncratic model behavior, which is consistent with the standpoint hypothesis: if failures reflect a shared default standpoint inherited from common training data distributions, we would expect this pattern to be stable across models. GPT-5 mini is the notable outlier, showing the lowest correlation with other models, which may reflect its anomalous position in the non-monotonic scaling pattern observed in the main results.

F.5 Default Standpoint Analysis

Figure 12 shows coefficients from a logistic regression predicting recall from group membership and domain, pooled across all models. The spread of coefficients is large, spanning roughly three log-odds units, indicating that group membership is a strong predictor of recall even after controlling for

Figure 8: **Intraclass correlation (ICC) across the three scenarios per need**, broken down by group category. High ICC indicates that detection success is stable across scenarios for a given need.

domain. The consistency of this ordering across models, visible in the per-model points, suggests the gradient reflects a structural property of the default standpoint rather than any single model's idiosyncrasies. Notably, the groups best detected correspond closely to those whose needs may be codified in widely circulated English-language legal and institutional standards, while those worst detected are groups whose needs are encoded primarily in religious texts, cultural practice, and lived experience.

Figure 9: **Recall by task type** (creation vs. advice) across models under the BASE condition.

Figure 12: **Plot of coefficients from a logistic regression predicting recall** (pooled across models) with group and domain as predictors. The dashed line marks the intercept. More negative coefficients indicate needs further from the default standpoint, after controlling for domain.