Learning Transferable Sub-Goals by Hypothesizing Generalizing Features

Abstract

Although transfer is a key promise of hierarchical reinforcement learning, current methods discover nontransferable skills. Typically, skills are defined over all state features simultaneously, preventing generalization as some state features reliably support generalization while others do not. For an agent to effectively transfer a skill it must identify features that generalize and define the skill over this subset. However, this task is under-specified from a single context as the agent has no prior knowledge of what future tasks may be introduced. Since successful transfer requires a skill to reliably achieve a sub-goal from different states, we focus our attention on ensuring sub-goals are represented in a transferable way. For each sub-goal, we train an ensemble of classifiers while explicitly incentivizing them to use minimally overlapping features. Each ensemble member represents a unique hypothesis about the transferable features of a sub-goal that the agent can use to learn a skill in previously unseen portions of the environment. Environment reward then determines which hypothesis is most transferable for the given task, based on the intuition that transferable sub-goals lead to better reward maximization. We apply these reusable sub-goals to MiniGrid and Montezuma's Revenge, allowing us to learn previously defined skills in unseen parts of the state-space.

1 Introduction

Hierarchical reinforcement learning (HRL) (Barto & Mahadevan, 2003) is a promising approach for scaling RL to challenging, long-horizon problems. HRL methods learn temporally extended *skills* that abstract away the details of low-level action executions. The most popular HRL framework, the *options* framework (Sutton et al., 1999), models skills using three components: a set of states from which execution can begin, a policy which picks low-level actions, and a collection of states where execution ceases, which can be represented by a *sub-goal*.

To fully realize the benefits of HRL, learned options should be transferable. For example, a robot trained to open a door in a factory should be able to open doors in a user's home with minimal additional training. However, existing HRL generalization methods are unable to generalize an option from a single context to another, either requiring large libraries of prelearned skills or assume access to a distribution of relevant tasks. This is primarily because all three components of the option are conditioned on the *entire* state—which includes spurious features unnecessary for successful execution—making generalization from *one example* challenging. However, if these components are defined over generalizable features of the state, the option can transfer to novel contexts from a single instance. For example, if the agent learns that the color of the door is irrelevant for identifying a sub-goal, it is transferred with relative ease. The core problem here is that, in practice, an option will first be discovered in a single context (like a factory) without foreknowledge of the circumstances under which it can be applied again in the future.

How can the agent learn a state representation that will result in seamless transfer? This problem can be easily tackled in supervised learning by incorporating data from different contexts or by applying class-preserving data augmentations. However, this luxury is not afforded to an RL agent, which must interact with the world in an online, incremental fashion, without any foreknowledge of the types of states it might encounter in the future. Instead, we propose that the RL agent maintain several, diverse *hypotheses* over which features of the state might generalize to upcoming tasks. The

agent then selects from among these hypotheses, testing them in the environment, and updates its beliefs over which members of the ensemble have learned transferable features.

We focus on transferring sub-goals, since the agent can learn an option given a sub-goal (as we argue in Section 3). We begin by assuming access to a non-transferable sub-goal (potentially discovered using an off-the-shelf option discovery method), defined for a single context. This sub-goal is used to generate labeled data which acts as a training set for an ensemble of classifiers. Each ensemble member maintains a unique hypothesis of the generalizing state-features and is, individually, a new sub-goal; then, for each hypothesis, we learn a low-level policy that aims to reach the hypothesized sub-goal. Finally, a high-level policy selects among the low-level policies to maximize extrinsic reward.

We test our approach in two simulated environments: MONTEZUMASREVENGE (Bellemare et al., 2013; Machado et al., 2018) and MINIGRID (Chevalier-Boisvert et al., 2023). Given a set of options and their execution data from the first room of MONTEZUMASREVENGE, we show that our algorithm can successfully transfer those options to other, visually dissimilar rooms. In MINIGRID, we demonstrate how our agent learns transferable options and uses them to rapidly solve a challenging exploration problem.

2 BACKGROUND AND RELATED WORK

We consider Markov Decision Processes (MDP) $M = (S, A, r, p, \gamma)$ where S denotes the state-space, A is the action-space, $p(s_{t+1}|s_t, a_t)$ denotes the transition dynamics and $r(s_t, a_t)$ is the scalar reward function. The RL objective is to find a policy $\pi(a|s)$ that maximizes the cumulative discounted reward over the lifetime of the agent.

An **option** o is a temporally extended action and, for this work, is defined by a tuple (I_o, π_o, β_o). The initiation set, $I_o : S \to \{0, 1\}$, is the set of states in which option o can initiate. The termination set, $\beta_o : S \to \{0, 1\}$ is the set of states in which option o successfully terminates. The option policy $\pi_o : S \to A$ is a controller that transitions the agent from states in I_o to states in β_o.

Identifying Sub-goals. For this definition, the option termination set is analogous to a sub-goal. Identifying sub-goals is an important aspect of hierarchical reinforcement learning. One popular method by Andrychowicz et al. (2017) is a simple but powerful technique of generating goals from previously visited states and has lead to several branch-off works (Pitis et al., 2020; Fang et al., 2019). Nair et al. (2020) learn a latent dynamics model to generate sub-goals and Florensa et al. (2018) focus on selecting solvable sub-goals. Bagaria et al. (2023) generate a protogoal space which consists of many possibly useful sub-goals and an adaptive function to map this space to a small set of useful goals. All these methods focus on the initial discovery of sub-goals while our work focuses on transferring an existing sub-goal and so can be used in tandem with any of these methods.

Learning transferable skills. A task is defined by a goal an agent must achieve in the environment. For example, a task can be navigating to a location or obtaining an object. Sub-goals can exist along the trajectory towards the goal, which are intermediate goals that must be first achieved before a final goal can be completed, or a set of unrelated goals the agent is tasked with completing. An option can be used to achieve these sub-goals, by setting the termination set to be a sub-goal. The use of options promises to aid in task learning as we only need to learn to reach each sub-goal once but may need to reach this sub-goal many times in future. However, in their most basic formulation, options do not generalize. This is because an option is defined over a specific subset of the state space and has no prior knowledge about what features are needed for successful transfer. One approach to transfer is via derived input spaces with transferable semantics. Konidaris & Barto (2007) showed that an agent-centric representation, analogous to an egocentric space, would be sufficient for option generalization but requires a hand-designed agent-centric input. Dayan (1993) and Barreto et al. (2018) use successor features to learn policies that generalize across reward functions but not changes in transition dynamics. Other attempts at skill transfer learn from demonstration (Konidaris et al., 2011; Ranchod et al., 2015), using demonstrations from several tasks to identify and learn common skills. Wang et al. (2014); Barreto et al. (2019) require first learning a large number of skills and retroactively compressing these skills into a single transferable skill and sub-goal. A common approach to skill generalization Agarwal et al. (2021); Frans et al. (2017); Gomez et al. (2022); Touati et al. (2022) assumes access to a distribution of relevant tasks that can be sampled from during train-

ing. These methods leverage this distribution to either learn useful state representations or general policies and sub-goals, however, carry an implicit assumption that an expert has predefined which tasks should be generalized to. These works all require either a large library of skills or assume a distribution of relevant tasks. As such, these methods either delay the gain of generalized skills or assume the skill has already been predefined and so are not compatible with existing skill discovery methods. These works are all retroactive, looking backwards on what has been learned or provided. We wish to generalize *forward*—transferring a sub-goal from a single option instance.

Unsupervised Representation Learning. Representation learning is often used to compress high dimensional data to aid future learning (Bengio et al., 2013). One method to learn a useful representation is leveraging auxiliary tasks such as Denton et al. (2017) who use the downstream tasks such as classification and video prediction to learn a compact representation. Higgins et al. (2017) learn a disentangled representation of the state space to improve an agents domain adaptation. Representation learning has also been used to represent goals to improve exploration (Laversanne-Finot et al., 2018) and sample efficiency (Nair et al., 2018). Our work differs from these by learning multiple hypotheses, each of which is a unique state representation.

The **Diversity-By-disAgreement Training (D-BAT)** algorithm from Pagliardini et al. (2022) is designed to learn a classifier able to transfer to out-of-distribution data. This is done by making use of both labeled and unlabeled data in a semi-supervised setting. The labeled data is sampled from a subset of the distribution while the unlabeled data is collected from the full distribution. D-BAT is an ensemble method, which encourages each ensemble member to lower classification loss on the labeled data while encouraging disagreement among members on the unlabeled data. The members of the resulting ensemble each maintain a unique hypothesis over the relevant features. Given a sub-goal, we generate a set of labeled data with the intention of generalizing this option to unseen contexts.

3 LEARNING TRANSFERABLE SUB-GOALS

Hierarchical reinforcement learning simplifies complex problems by splitting a single task into multiple sub-tasks, each of which can be defined by a sub-goal which can be provided to the agent or discovered through a skill discovery algorithm. These sub-goals are used to learn a policy to complete the corresponding sub-task, giving rise to a skill. These sub-goals can be represented in many ways, for example a sub-goal to reach the door of a room can be defined over the agent's (x, y) location or the agent's distance from the door. While both feature sets can be used to effectively learn an option in the discovering context, the agent's position sub-goal will not generalize to new states. Many previous works tackle skill transfer retroactively, learning a large collection of skills that are then compressed into a small collection of reusable skills or assuming a predefined distribution of relevant tasks. These skills are either found after countless interactions with the environment— delaying access to a transferable skill for a long time and still need to answer the question of when to group a collection of skills—or require an expert to define a set of tasks. Instead, we propose generalizing *forwards*, making these skills available to the agent after their initial discovery and allows us to leverage the rich collection of existing skill discovery algorithms.

Sub-goals are commonly modeled as classifiers. The classifier returns 1 for sub-goal states and 0 otherwise; when executing a skill the agent runs a policy until reaching a sub-goal state, where it receives a reward. This is the most important component of the skill and the output of most skill acquisition algorithms. With only a transferable skill policy, it is not clear when this policy has completed. A transferable initiation set only tells us some policy can be started to reach some sub-goal but this information alone has no value. However, if the agent has access to a transferable termination set, the agent can learn a policy and initiation set that achieves the same sub-goal in a new context.

3.1 HYPOTHESIS GENERATION

Given state space $\mathcal{S}$, we sample a dataset $\mathcal{D}$ which defines a space of functions $\mathcal{F}$, consisting of all functions that accurately fit all points in $\mathcal{D}$. This space of functions is very large as there are many ways to define a function that accurately fits some set of points. A function's ability to generalize is measured by how accurately the function can predict data points that have not been included in

$\mathcal{D}$. When learning a classifier to approximate one of these functions, the burden of generalization is placed on the quality of data collection; which must fully encompass the tasks you wish to generalize to in $\mathcal{S}$. If the collected data does not accurately represent the full distribution of relevant contexts, the classifier cannot generalize reliably. Unfortunately, this is precisely the scenario RL agents find themselves in when generalizing forwards.

We therefore propose that, instead of sampling a single function from $\mathcal{F}$, we can instead sample multiple functions, which form a collection of *hypotheses*, $\mathcal{H}$. Each function, $h \in \mathcal{H}$, describes different features of $\mathcal{S}$ which accurately describe $\mathcal{D}$. By creating hypotheses over $\mathcal{D}$ we increase the chance of learning generalizable features. For example consider an agent learning to open a cupboard door and all training samples have been collected on the same cupboard which contains a red ball. One hypothesis attends to the red ball inside the cupboard—which is only visible if the door is open—while another learns to distinguish the location of the cupboard door when it is open or closed. Both of these hypotheses accurately describe the training data $\mathcal{D}$ but make use of different sets of features. To further improve the quality of $\mathcal{H}$, we can require that our sampling process focuses on diverse functions, ensuring each function h differs meaningfully on the features of our data $\mathcal{D}$.

We leverage the D-BAT algorithm to ensure diversity among $h \in \mathcal{H}$, however, any algorithm that would result in a collection of diverse functions can be used instead. This algorithm makes use of labeled data $\mathcal{D}$ but also requires a set of unlabeled data $\mathcal{U} \in \mathcal{S}$ to train an ensemble of classifiers. Each ensemble member is encouraged to reduce labeled loss while also decreasing agreement on $\mathcal{U}$. As a result, we learn an ensemble which is our collection of hypotheses $\mathcal{H}$, with each ensemble member attending to different sets of features in $\mathcal{S}$, informed by $\mathcal{U}$. Given some discovered sub-goal, we collect labeled data which—due to the nature of discovered sub-goals—is collected from a small subset of states in the state-space. We can leverage the exploration required during policy learning to collect an unlabeled dataset which contains states in which the sub-goal is not defined.

3.2 OPTION LEARNING FOR MULTIPLE HYPOTHESES

Each hypothesis $h \in \mathcal{H}$ maps to a new sub-goal, each of which is transferable if applied to a relevant set of tasks. For example, consider Figure 1. This figure shows three states in an environment, the

Figure 1: Given that the first image is *False* and the second image is *True* is the third image *True* or *False*?

first image is outside the defining sub-goal while the second is inside the sub-goal. Given these two images, what is the sub-goal these images define? One possible hypothesis is that the red key must be removed, which accurately describes the given data. We can raise another hypothesis; the yellow key must be at a specific grid location. Another possible hypothesis may be that two keys are present at all times, regardless of color or location. All three of these hypotheses are consistent with the training data. Each of these hypotheses can be used to learn a distinct skill policy, one which collects the red key, one which places the yellow key at a specific grid location and one that ensures two keys are always present. As such, we learn a separate option policy for each ensemble member as all members correspond to valid sub-goals which may not overlap.

3.3 HYPOTHESIS SELECTION

Once we have learned $\mathcal{H}$, we must select the best hypothesis. This task however is challenging and cannot be done without additional information. Returning to the example in Figure 1, can you determine if the third state satisfies the original sub-goal? The answer is it depends; the red key is present, so our red key sub-goal is not satisfied. Similarly the yellow key has been collected so our yellow key sub-goal is also not satisfied. There are, however, two keys in the environment so our two key sub-goal has been met. Which hypothesis is correct? If we were an agent in the environment, how do we decide which hypothesis is most beneficial? It is very likely that only one of these hypotheses is transferable given our task, however, without knowledge of what that task is, we cannot confidently select the most general hypothesis. But in an RL problem, the task is encoded in the environment reward. Therefore, we propose that the most transferable hypothesis will lead to higher external reward. We provide a high-level policy with an action space that contains options defined by all $h \in \mathcal{H}$, providing one option for each hypothesis. This high-level policy then learns to maximize the extrinsic reward, which encodes the task. As this high-level policy begins reward maximization, it will naturally begin selecting hypotheses that best support transfer.

4 RESULTS

Our experiments are designed to first individually validate each component of our algorithm, and finally to test a consolidated RL agent on a challenging sparse-reward problem. Specifically, we seek to answer the following questions through our experiments:

1. Does the D-BAT algorithm produce accurate classifiers? Do the different ensemble members attend to different, diverse parts of the input-space?

2. How much *labeled* training data is needed to successfully generalize an option's sub-goal classifier to previously unseen contexts?

3. Are sub-goals generated by the D-BAT ensemble sufficient for learning useful option policies?

4. Can an agent equipped with transferable options learned using our algorithm solve challenging reinforcement learning problems?

5. Does the reward-maximizing high-level policy eventually prefer transferable options over non-transferable ones?

We define all sub-goals using expert collected trajectories to ensure we can accurately evaluate the quality of transfer during all experiments.

4.1 D-BAT EVALUATION FOR SUB-GOAL GENERALIZATION

We begin by confirming that each ensemble member is learning a unique hypothesis for a single sub-goal. MONTEZUMASREVENGE is an Atari game in which the player must traverse through several rooms, collecting treasure or keys to open future doors while avoiding enemies and hazards. Each screen in the game has a unique layout and looks visually different, making sub-goal generalization challenging from pixel input. All classifiers are given a gray-scale stack of the four previous frames resized to size 84×84. We begin by providing the D-BAT ensemble with labeled data from the starting room, which contains three ladders, and unlabeled data from one other room containing a ladder and one room without a ladder. We then use DeepLift (Shrikumar et al., 2017) to identify the most important features for each ensemble head for an unseen state. From Figure 2 we see these ensemble members have attended to different features of the image. Ensemble member 0 focuses on the ladder and player while ensemble member 4 has mainly attends to the lava below the floor. In this example, attending to the lava would not prevent the classifier from correctly identifying this sub-goal but will prevent generalization to future ladder instances if no lava is present.

Next we evaluate the accuracy of the classifiers produced by the D-BAT ensemble as well as how much labeled data is required for successful sub-goal generalization. MONTEZUMASREVENGE has multiple ladders located throughout the game, each in a visually distinct room. We define the CLIMBDOWNLADDER sub-goal as met when the agent is at the base of any ladder. The purpose

Figure 2: Saliency map showing that different ensemble members attend to different parts of the same image. Pixels marked as positive contribute to the classifier's final prediction; negative features contribute to the class the classifier did not predict. For simplicity, only one frame is shown. The attribution plot for all frames for each ensemble member can be seen in Appendix A Figure 9.

of learning an ensemble of classifiers is to obtain at least one classifier defined over a generalizing set of features. Therefore, only the accuracy of the best performing ensemble member need to be considered. We compare against a one-headed ensemble, or standard CNN because traditionally sub-goals are represented with a single classifier providing a clear comparison against what is often done in practice and is equivalent to sampling a single hypothesis. We also compare against the D-BAT ensemble with a diversity weight of 0 to show the effect of diversity on hypothesis sampling.

Figure 3 shows the accuracy of all classifiers improves greatly after seeing two rooms. However, because we intend to generalize forwards, the performance of the ensemble when provided labeled data for a *single ladder instance* is most significant as a skill discovery algorithm will only provide one example. For this case the D-BAT ensemble outperforms the standard ensemble by almost 10% and leads the CNN by 20%. We should note that because the state comprises of four previous frames, our current state is dependent on the previous four actions, making the space is very large. As such, our collected data does not fully encompass all possible states which an agent may encounter during policy learning, therefore, a high classification accuracy may not result in a useful option. For example, if a 90% accuracy classifier includes the top of the ladder as part of the sub-goal, the resulting policy will transport the agent one or two steps down the ladder which is not a useful CLIMBDOWNLADDER skill.

4.2 D-BAT EVALUATION FOR POLICY LEARNING

It was previously shown that the D-BAT algorithm results in an accurate and diverse ensemble but this may not be enough for effectively training future skill policies. We again use the CLIMB-DOWNLADDER sub-goal, incrementally evaluating on larger labeled datasets, while now including skill policy learning. The agent is placed at the top of each ladder instance in the game, training a skill for each ensemble member for 3×10^5 environment steps per ladder. Each policy is given a reward of 1 if the sub-goal is satisfied and 0 otherwise. A new policy is trained for each ladder and the state is equivalent to the classifier input. After policy training, we average the Manhattan distance between the final termination location and the closest true termination for the last 100 option runs and again average the performance for each ladder to get a single distance. Because we use a frame skip of 4, the Manhattan distance is equivalent to 4 times the number of actions away from the true termination. If an option starts in the termination set—the classifier predicts the top of the ladder as part of the sub-goal—the Manhattan distance is set to 300 which is the mode ladder length. We again consider only the best performing head for evaluation.

Figure 4 shows that, while the classifier accuracy is relatively close for all classifiers after training on two ladders, there is a significant difference in the Manhattan distance. The D-BAT ensemble outperforms the no diversity ensemble even when the classifiers have seen all ladders in the game, with exception to the two ladder case where they are close. Additionally, the D-BAT ensemble reaches similar performance after seeing one ladder as the CNN after seeing all ladders in the game. This means we achieve similar performance to a retroactive method that perfectly identified all ladder

Figure 3: Accuracy of the best performing ensemble member as the ensemble is given labeled data from more ladders across the Montezuma's Revenge game. Results are averaged over 3 seeds and bands represent the standard deviation.

Figure 4: Average Manhattan distance between the state in which option execution terminated and the sub-goal region of the option; bars represent mean and standard deviation over the last 100 option executions (lower is better) averaged over 3 seeds.

bases and trained a sub-goal classifier with labeled data from every ladder instance in MONTEZUMASREVENGE.

Figure 5: Scatter plot of termination locations. These are the locations of the agent for the last 100 skill executions for a single sub-goal and policy seeing data from two ladders. The agent starts on top of the ladder in the middle room. If the agent climbs down the ladder, they will arrive in the room to the right while traveling left from the starting room will place the agent in the left room. Only the best performing member is shown. We see the ensemble methods outperform the CNN, with the D-BAT ensemble resulting in more compact termination sub-goals.

While the Manhattan distance decreases as more ladder instances are introduced, it does not intuitively confirmed that our learned CLIMBDOWNLADDER policies are useful. To further investigate the quality of the sub-goals defined by the D-BAT ensemble, we plot the final 100 termination locations for the best performing member after exposure to two ladders on a previously unseen partition of the environment. Looking at Figure 5, we see both ensemble methods terminate at the base of the leftmost ladder, with the diversity ensemble leading to a more compact termination set. The ensemble methods also identify the rightmost ladder, which continues through the floor of the room. During training, the classifiers see no labeled instances of ladders continuing through the floor as we leave these states unlabeled, showing that both ensembles have generalized to this case without seeing similar labeled examples. The CNN never identifies the right ladder termination and is less successful at identifying ladder bases despite having an accuracy of 90% on our expert collected data. Both ensemble members also rarely terminate erroneously in the middle of the ladder. From

Figure 6: Average undiscounted reward for the modified MINIGRID DOORKEY environment. All results are averaged over 3 seeds and bands represent the standard error.

these experiments we can conclude that both ensemble sub-goals can be used to learn policies that transfer the initial option, however, the D-BAT ensemble has significantly better performance.

4.3 CONSOLIDATED REINFORCEMENT LEARNING AGENT IN MINIGRID

Although, we previously showed that a collection of hypotheses can be used to learn option policies that transfer to new ladder instances in MONTEZUMASREVENGE, this is not significant unless these transferred sub-goals can be used by an agent to solve reinforcement learning problems. MINIGRID is a 2-dimensional grid-world environment consisting of goal-oriented tasks. The DOORKEY environment places the agent in one of two rooms separated by a locked door. The agent must collect the key to unlock the door and travel to the goal location in the other room. Traditionally, this environment has a red door and a single red key. We modify this task to include a blue and green key to increase the difficulty of the task. The agent must collect the correct key—the red key—to unlock the door and reach the goal to receive a reward of 1 or 0 for every other time step, making this a sparse reward problem. We use the full RGB image as our state.

We define 5 sub-goals; COLLECTBLUEKEY, COLLECTGREENKEY, COLLECTREDKEY, OPENREDDOOR and GOTOGOAL. Labeled data is collected from seed 0 and unlabeled data is collected from seeds 1 and 2. Data from test seeds is not shared among agents. The lower-level ensemble policies are not pre-trained, and must be learned in conjunction with the higher-level policy. We use a PPO (Schulman et al., 2017) agent with access to only the option policies, each of which is a Deep-Q Network (Van Hasselt et al., 2016) with a prioritized replay buffer (Schaul et al., 2015). Each ensemble member is an executable skill, with an independent low-level policy. The PPO agent has an action space of size 15, consisting of 3 hypotheses for all 5 original sub-goals. We aim to show that giving the agent skills that are not aligned with the overall task will not irreparably damage policy learning, and the strong performance of our ensemble agent cannot be explained by our use of DQN and PPO. As such we evaluate against a DQN and a PPO agent, each of which have access to the original environment actions. All agents are run for 1.5 million environment steps with a maximum episode length of 500 steps.

Figure 6 shows the option agent is able to learn to reach the goal consistently, while the DQN and PPO agents fail to complete the task. We can conclude that ensembling helps the agent complete the goal by allowing the agent to leverage the provided sub-goals, simplifying the original task.

(a) Ensemble member 2 which is the least picked by the agent. (b) Ensemble member 3 which is the most picked by the agent.

Figure 7: Overlaid termination states identified by members of the D-BAT ensemble for the OPENREDDOOR sub-goal.

(a) Ensemble member 1, tied for most picked. (b) Ensemble member 3, tied for most picked.

Figure 8: Overlaid termination states identified by members of the D-BAT ensemble for the GOTO-GOAL sub-goal.

4.4 HYPOTHESIS SELECTION THROUGH REWARD OPTIMIZATION

Our previous experiments have shown that we can learn *at least one* generalizing hypothesis but has not yet shown how to identify the corresponding ensemble member. We previously claimed that reward maximization is a useful proxy for identifying the hypothesis that best transfers. To evaluate this claim, we compare the termination sets of the most and least selected ensemble members. Overall, we find that the most popular hypothesis closely resembles our hand-defined generalized sub-goals. Figure 7 overlays multiple termination sets for two members of the OPENREDDOOR sub-goal. For the least selected ensemble member, the sub-goal does not fully correlate with our definition of the OPENREDDOOR sub-goal; i.e. positioned in front of an open door. On the other hand, Figure 7a shows the most picked ensemble member which requires the agent always stands at the open door, matching our hand-defined OPENREDDOOR sub-goal.

For the GOTOGOAL sub-goal, shown in Figure 8, we show two ensemble members, neither of which seems to be favored. Both of these sub-goals require the agent to be standing on the goal position which again aligns with our previously defined sub-goal. The final member of this ensemble, which has a significantly lower selection probability, does not trigger for this DOORKEY environment seed. This supports our statement that reward maximization leads to the selection of the most generalized sub-goals. We can conclude that, not only does diversity allow for successful sub-goal generalization for a given option but also that reward maximization is a good measure for identifying the most transferable hypothesis.

5 CONCLUSION

In this work we tackle sub-goal generalization from a single instance; the most crucial step for forward skill generalization. We do this by learning an ensemble of diverse hypotheses over generalizing feature sets using the D-BAT algorithm. Our experiments show that this ensemble can successfully transfer the CLIMBDOWNLADDER sub-goal in MONTEZUMASREVENGE with 70% accuracy when exposed to a single set of ladders in the game. These classifiers can be used to learn options that takes the agent to the bottom of ladders throughout MONTEZUMASREVENGE. We also show that these sub-goal classifiers can be used for learning a modified DOORKEY task in MINIGRID and reward maximization can be used to identify the hypothesis that best supports transfer.

REFERENCES

Rishabh Agarwal, Marlos C Machado, Pablo Samuel Castro, and Marc G Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. *arXiv preprint arXiv:2101.05265*, 2021.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. *Advances in neural information processing systems*, 30, 2017.

Akhil Bagaria, Ray Jiang, Ramana Kumar, and Tom Schaul. Scaling goal-based exploration via pruning proto-goals. *arXiv preprint arXiv:2302.04693*, 2023.

Andre Barreto, Diana Borsa, John Quan, Tom Schaul, David Silver, Matteo Hessel, Daniel Mankowitz, Augustin Zidek, and Remi Munos. Transfer in deep reinforcement learning using successor features and generalised policy improvement. In *International Conference on Machine Learning*, pp. 501–510. PMLR, 2018.

André Barreto, Diana Borsa, Shaobo Hou, Gheorghe Comanici, Eser Aygün, Philippe Hamel, Daniel Toyama, Shibl Mourad, David Silver, Doina Precup, et al. The option keyboard: Combining skills in reinforcement learning. *Advances in Neural Information Processing Systems*, 32, 2019.

Andrew G Barto and Sridhar Mahadevan. Recent advances in hierarchical reinforcement learning. *Discrete event dynamic systems*, 13(1):41–77, 2003.

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, jun 2013.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Maxime Chevalier-Boisvert, Bolun Dai, Mark Towers, Rodrigo de Lazcano, Lucas Willems, Salem Lahlou, Suman Pal, Pablo Samuel Castro, and Jordan Terry. Minigrid & miniworld: Modular & customizable reinforcement learning environments for goal-oriented tasks. *CoRR*, abs/2306.13831, 2023.

Peter Dayan. Improving generalization for temporal difference learning: The successor representation. *Neural computation*, 5(4):613–624, 1993.

Emily L Denton et al. Unsupervised learning of disentangled representations from video. *Advances in neural information processing systems*, 30, 2017.

Meng Fang, Tianyi Zhou, Yali Du, Lei Han, and Zhengyou Zhang. Curriculum-guided hindsight experience replay. *Advances in neural information processing systems*, 32, 2019.

Carlos Florensa, David Held, Xinyang Geng, and Pieter Abbeel. Automatic goal generation for reinforcement learning agents. In *International conference on machine learning*, pp. 1515–1528. PMLR, 2018.

Kevin Frans, Jonathan Ho, Xi Chen, Pieter Abbeel, and John Schulman. Meta learning shared hierarchies. *arXiv preprint arXiv:1710.09767*, 2017.

Diego Gomez, Nicanor Quijano, and Luis Felipe Giraldo. Information optimization and transferable state abstractions in deep reinforcement learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(4):4782–4793, 2022.

Irina Higgins, Arka Pal, Andrei Rusu, Loic Matthey, Christopher Burgess, Alexander Pritzel, Matthew Botvinick, Charles Blundell, and Alexander Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. In *International Conference on Machine Learning*, pp. 1480–1490. PMLR, 2017.

George Konidaris, Scott Kuindersma, Roderic Grupen, and Andrew Barto. Autonomous skill acquisition on a mobile manipulator. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 25, pp. 1468–1473, 2011.

George Dimitri Konidaris and Andrew G Barto. Building portable options: Skill transfer in reinforcement learning. In *IJCAI*, volume 7, pp. 895–900, 2007.

Adrien Laversanne-Finot, Alexandre Pere, and Pierre-Yves Oudeyer. Curiosity driven exploration of learned disentangled goal spaces. In *Conference on Robot Learning*, pp. 487–504. PMLR, 2018.

Marlos C. Machado, Marc G. Bellemare, Erik Talvitie, Joel Veness, Matthew J. Hausknecht, and Michael Bowling. Revisiting the arcade learning environment: Evaluation protocols and open problems for general agents. *Journal of Artificial Intelligence Research*, 61:523–562, 2018.

Ashvin V Nair, Vitchyr Pong, Murtaza Dalal, Shikhar Bahl, Steven Lin, and Sergey Levine. Visual reinforcement learning with imagined goals. *Advances in neural information processing systems*, 31, 2018.

Suraj Nair, Silvio Savarese, and Chelsea Finn. Goal-aware prediction: Learning to model what matters. In *International Conference on Machine Learning*, pp. 7207–7219. PMLR, 2020.

Matteo Pagliardini, Martin Jaggi, François Fleuret, and Sai Praneeth Karimireddy. Agree to disagree: Diversity through disagreement for better transferability. *arXiv preprint arXiv:2202.04414*, 2022.

Silviu Pitis, Harris Chan, Stephen Zhao, Bradly Stadie, and Jimmy Ba. Maximum entropy gain exploration for long horizon multi-goal reinforcement learning. In *International Conference on Machine Learning*, pp. 7750–7761. PMLR, 2020.

Pravesh Ranchod, Benjamin Rosman, and George Konidaris. Nonparametric bayesian reward segmentation for skill discovery using inverse reinforcement learning. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 471–477. IEEE, 2015.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *arXiv preprint arXiv:1511.05952*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *International conference on machine learning*, pp. 3145–3153. PMlR, 2017.

Richard S Sutton, Doina Precup, and Satinder Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2):181–211, 1999.

Ahmed Touati, Jérémy Rapin, and Yann Ollivier. Does zero-shot reinforcement learning exist? *arXiv preprint arXiv:2209.14935*, 2022.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30, 2016.

Hao Wang, Shunguo Fan, Jinhua Song, Yang Gao, and Xingguo Chen. Reinforcement learning transfer based on subgoal discovery and subtask similarity. *IEEE/CAA Journal of Automatica Sinica*, 1(3):257–266, 2014.

A   ADDITIONAL RESULTS

Figure 9: Feature importance of a sample forall ensemble members. Features marked as positive contribute to the classifier's final prediction. Negative features contribute to the class the classifier did not predict. We also include the label and precitions for each ensemble member.

B HYPERPARAMETERS

B.1 MONTEZUMA'SREVENGE HYPERPARAMETERS.

All classifier models consist of three CNN layers, with batch normalization and ReLU activations between. The CNN layers then feed into two dense layers before final classification. We use the Adam optimizer and a cross entropy classification loss for labelled data. Unlabelled data is optimized using the Kullback-Liebler divergence.

Table 1: MONTEZUMA'SREVENGE D-BAT Ensemble Hyperparameters.

Hyperparameter	D-BAT	D-BAT - no diversity	CNN
Learning Rate	5×10^{-4}	5×10^{-4}	5×10^{-4}
Diversity Weight	3×10^{-4}	0.0	3×10^{-4}
Member Number	6	6	1
L2 Regularization Weight	5×10^{-4}	5×10^{-4}	5×10^{-4}
Class weighting	0.8 negative 0.2 positive	0.8 negative 0.2 positive	0.8 negative 0.2 positive
Batchsize	64		

We use a Deep-Q network for all policy training. The network consists of two CNN layers, each followed by a batch normalization layer, ReLU activation and max pooling layer. This is fed to a Gated Recurrent Unit before passing through two dense layers for action selection, optimized using the Adam optimizer. All options were allowed to run for 200 time steps before terminating if they did not reach the sub-goal defined by the classifier.

Table 2: MONTEZUMA'SREVENGE Policy Hyperparameters.

Hyperparameter	Value
Replay buffer length	1×10^5
Update interval	4
Q-target update interval	10
Final Exploration frame	4×10^5 decaying from 1 to 0.01
Learning rate	2.5×10^{-4}
Batchsize	32

B.2 MINIGRID DOORKEY HYPERPARAMETERS.

All classifier models consist of two CNN layers, with batch normalization and ReLU activations between. The CNN layers then feed into three dense layers before final classification. We use the Adam optimizer and a cross entropy classification loss for labelled data. Unlabelled data is optimized using the Kullback-Liebler divergence.

We use a Deep-Q network for all policy training. The network consists of two CNN layers, each followed by a batch normalization layer, ReLU activation and max pooling layer. This is fed to a Gated Recurrent Unit before passing through two dense layers for action selection, optimized using the Adam optimizer. All options were allowed to run for 10 time steps before terminating if they did not reach the sub-goal defined by the classifier.

We train a PPO agent to reach the goal for DOORKEY MINIGRID. The PPO agent has three CNN layers reperated by ReLU activations fed into a dense layer. These layers are shared between the actor and critic layers. The actor has an additional gaussian policy head and the critic has a single dense layer.

Table 3: MINIGRID DOORKEY D-BAT Ensemble Hyperparameters.

Hyperparameter	Values
Learning Rate	$2 \times 10^{-}4$
Diversity Weight	$1 \times 10^{-}4$
Member Number	3
L2 Regularization Weight	$1 \times 10^{-}4$
Class weighting	0.5 negative 0.5 positive
Batchsize	64

Table 4: MINIGRID DOORKEY DQN Hyperparameters.

Hyperparameter	Value
Replay buffer length	1×10^5
Update interval	4
Q-target update interval	10
Final Exploration frame	8×10^3 decaying from 1 to 0.01
Learning rate	$2.5 \times 10^{-}4$
Batchsize	32

Table 5: MINIGRID DOORKEY PPO Hyperparameters.

Hyperparameter	Value
Replay buffer length	1×10^5
Update interval	100
Entropy coefficient	0.01
Lambda	0.97
Batchsize	64
Epochs per update	10