Convolutional Normalization: Improving Deep Convolutional Network Robustness and Training

Abstract

Normalization techniques have become a basic component in modern convolutional neural networks (ConvNets). In particular, many recent works demonstrate that promoting the orthogonality of the weights helps train deep models and improve robustness. For ConvNets, most existing methods are based on penalizing or normalizing weight matrices derived from concatenating or flattening the convolutional kernels. These methods often destroy or ignore the benign convolutional structure of the kernels; therefore, they are often expensive or impractical for deep ConvNets. In contrast, we introduce a simple and efficient "Convolutional Normalization" (ConvNorm) method that can fully exploit the convolutional structure in the Fourier domain and serve as a simple plug-and-play module to be conveniently incorporated into any ConvNets. Our method is inspired by recent work on preconditioning methods for convolutional sparse coding and can effectively promote each layer's channel-wise isometry. Furthermore, we show that our ConvNorm can reduce the layerwise spectral norm of the weight matrices and hence improve the Lipschitzness of the network, leading to easier training and improved robustness for deep ConvNets. Applied to classification under noise corruptions and generative adversarial network (GAN), we show that the ConvNorm improves the robustness of common ConvNets such as ResNet and the performance of GAN. We verify our findings via numerical experiments on CIFAR and ImageNet.

1 Introduction

In the past decade, Convolutional Neural Networks (ConvNets) have achieved phenomenal success in many machine learning and computer vision applications [1–7]. Normalization is one of the most important components of modern network architectures [8]. Early normalization techniques, such as batch normalization (BatchNorm) [4], are cornerstones for effective training of models beyond a few layers. Since then, the values of normalization for optimization and learning is extensively studied, and many normalization techniques, such as layer normalization [9], instance normalization [10], and group normalization [11] are proposed. Many of such normalization techniques are based on estimating certain statistics of neuron inputs from training data. However, precise estimations of the statistics may not always be possible. For example, BatchNorm becomes ineffective when the batch size is small [12], or batch samples are statistically dependent [13].

Weight normalization [14] is a powerful alternative to BatchNorm that improves the conditioning of neural network training without the need to estimate statistics from neuron inputs. Weight normalization operates by either reparameterizing or regularizing the network weights so that all the weights have unit Euclidean norm. Since then, various forms of normalization for network weights are proposed and become critical for many tasks such as training Generative Adversarial Networks (GANs) [15] and obtaining robustness to input perturbations [16, 17]. One of the most popular forms of weight normalization is enforcing orthogonality, which has drawn attention from a diverse range

of research topics. The idea is that weights in each layer should be orthogonal and energy-preserving. Orthogonality is argued to play a central role for training ultra-deep models [18–22], optimizing recurrent models [23–26], improving generalization [27], obtaining robustness [28, 29], learning disentangled features [30, 31], improving the quality of GANs [32, 33], learning low-dimensional embedding [34], etc.

Exploiting convolution structures for normalization. Our work is motivated by the pivotal role of weight normalization in deep learning. In the context of ConvNets, the network weights are multi-dimensional (e.g., 4-dimensional for a 2D ConvNet) convolutional kernels. A vast majority of existing literature [27, 28, 35–39] imposes orthogonal weight regularization for ConvNets by treating multi-dimensional convolutional kernels as 2D matrices (e.g., by flattening certain dimensions) and imposing orthogonality of the matrix. However, this choice ignores the translation-invariance properties of convolutional operators and, as shown in [22], does not guarantee energy preservation. On the other hand, these methods often involve dealing with matrix inversions that are computationally expensive for deep and highly overparametrized networks.

Figure 1: **Comparison between BatchNorm and ConvNorm** on activations of $k = 1, \ldots, C$ channels. BatchNorm subtracts and multiplies the activations of each channel by computed scalars: mean μ and variance σ^2, before a per-channel affine transform parameterized by learned parameters β and γ; ConvNorm performs per-channel convolution with precomputed kernel v to normalize the spectrum of the weight matrix for the convolution layer, following with a channel-wise convolution with learned kernel r as the affine transform.

In contrast, in this work we introduce a new normalization method dedicated to ConvNets, which explicitly exploits translation-invariance properties of convolutional operators. Therefore, we term our method as *Convolutional Normalization* (ConvNorm). We normalize each output channel for each layer of ConvNets, similar to recent preconditioning methods for convolutional sparse coding [40]. The ConvNorm can be viewed as a reparameterization approach for the kernels, that actually it normalizes the weight of each channel to be tight frame.[1] While extra mathematical hassles do exist in incorporating translation-invariance properties, and it turns out to be a blessing, rather than a curse, in terms of computation, as it allows us to carry out the inversion operation in our ConvNorm via fast Fourier transform (FFT) in the frequency domain, for which the computation complexity can be significantly reduced.

Highlights of our method. In summary, for ConvNets our approach enjoys several clear advantages over classical normalization methods [41–43], that we list below:

- **Easy to implement.** In contrast to weight regularization methods that often require hyperparameter tuning and heavy computation [41, 43], the ConvNorm has no parameter to tune and is efficient to compute. Moreover, the ConvNorm can serve as a simple plug-and-play module that can be conveniently incorporated into training almost any ConvNets.
- **Improving network robustness.** Although the ConvNorm operates on each output channel separately, we show that it actually improves the overall layer-wise Lipschitzness of the ConvNets. Therefore, as demonstrated by our experiments, it has superior robustness performance against noise corruptions and adversarial attacks.
- **Improving network training.** We numerically demonstrate that the ConvNorm accelerates training on standard image datasets such as CIFAR [44] and ImageNet [45]. Inspired by the work [40, 46], our high-level intuition is that the ConvNorm improves the optimization landscape that optimization algorithms converge faster to the desired solutions.

Related work. Besides our work, a few very recent work also exploits the translation-invariance for designing the normalization techniques of ConvNets. We summarize and explain the difference with our method below.

- The work [22, 43] derived a similar notion of orthogonality for convolutional kernels, and adopted a penalty based method to enforce orthogonality for network weights. These penalty methods often require careful tuning of the strength of the penalty on a case-by-case basis. In contrast, our method

---

[1]Tight frame can be viewed as a generalization of orthogonality for overcomplete matrices, which is also energy preserving.

93 is parameter-free and thus easier to use. Our method also shows better empirical performance in
94 terms of robustness.

95 • Very recent work by [29] presented a method to enforce *strict* orthogonality of convolutional
96 weights by using Cayley transform. Like our approach, a sub-step of their method utilizes the
97 idea of performing the computation in the Fourier domain. However, as they normalize the
98 whole unstructured weight matrix, computing expensive matrix inversion is inevitable, so that
99 their running time and memory consumption is prohibitive for large networks.[2] In contrast, our
100 method is "orthogonalizing" the weight of each channel instead of the whole layer, so that we
101 can exploit the convolutional structure to avoid expensive matrix inversion with a much lower
102 computational burden. In the meanwhile, we show that this channel-wise normalization can still
103 improve layer-wise Lipschitz condition.

104 **Organizations.** The rest of our paper is organized as follows. In Section 2, we introduce the
105 basic notations and provide a brief overview of ConvNets. In Section 3, we introduce the design of
106 the proposed ConvNorm and discuss the key intuitions and advantages. In Section 4, we perform
107 extensive experiments on various applications verifying the effectiveness of the proposed method.
108 Finally, we conclude and point to some interesting future directions in Section 5. To streamline our
109 presentation, some technical details are deferred to the Appendices.

2 Preliminary

111 **Review of deep networks.** A deep network is essentially a *nonlinear* mapping $f(\cdot) : \boldsymbol{x} \mapsto \boldsymbol{y}$,
112 which can be modeled by a composition of a series of simple maps: $f(\boldsymbol{x}) = f^{L-1} \circ \cdots \circ f^1 \circ f^0(\boldsymbol{x})$,
113 where every $f^\ell(\cdot)$ $(1 \le \ell \le L)$ is called one "layer". Each layer is composed of a linear transform,
114 followed by a simple nonlinear activation function $\varphi(\cdot)$.[3] More precisely, a basic deep network of L
115 layers can be defined recursively by interleaving linear and nonlinear activation layers as

$$\boldsymbol{z}^{\ell+1} = f^\ell(\boldsymbol{z}^\ell) = \varphi \circ \mathcal{A}^\ell(\boldsymbol{z}^\ell) \tag{1}$$

116 for $\ell = 0, 1, \ldots, L-1$, with $\boldsymbol{z}_0 = \boldsymbol{x}$. Here $\mathcal{A}^\ell(\cdot)$ denotes the linear transform and will be described
117 in detail soon. For convenience, let us use $\boldsymbol{\theta}$ to denote all network parameters in $\left\{\mathcal{A}^\ell(\cdot)\right\}_{\ell=0}^{L-1}$. The
118 goal of deep learning is to fit the observation $\boldsymbol{y}$ with the output $f(\boldsymbol{x}, \boldsymbol{\theta})$ for any sample $\boldsymbol{x}$ from a
119 distribution $\mathcal{D}$, by learning $\boldsymbol{\theta}$. This can be achieved by optimizing a certain loss function $\ell(\cdot)$, i.e.,

$$\min_{\boldsymbol{\theta} \in \boldsymbol{\Theta}} L(\boldsymbol{\theta}; \left\{\left(\boldsymbol{x}^i, \boldsymbol{y}^i\right)\right\}_{i=1}^m) := \frac{1}{m} \sum_{i=1}^m \ell\left(f(\boldsymbol{x}^i, \boldsymbol{\theta}), \boldsymbol{y}^i\right),$$

120 given a (large) training dataset $\left\{\left(\boldsymbol{x}^i, \boldsymbol{y}^i\right)\right\}_{i=1}^m$. For example, for a typical classification task, the class
121 label of a sample $\boldsymbol{x}$ is represented by a one-hot vector $\boldsymbol{y} \in \mathbb{R}^k$ representing its membership in k
122 classes. The loss can be chosen to be either the cross-entropy or ℓ_2-loss [48]. In the following, we
123 use $(\boldsymbol{x}, \boldsymbol{y})$ to present one training sample.

124 **An overview of ConvNets.** The ConvNet [49] is a special deep network architecture, where each
125 of its linear layer can be implemented much more efficiently via convolutions in comparison to fully
126 connected networks [50]. Because of its efficiency and popularity in machine learning, for the rest of
127 the paper, we focus on ConvNets. Suppose the input data $\boldsymbol{x}$ has C channels, represented as

$$\boldsymbol{x} = (\boldsymbol{x}_1, \boldsymbol{x}_2, \cdots, \boldsymbol{x}_C), \tag{2}$$

128 where for 1D signal $\boldsymbol{x}_k \in \mathbb{R}^m$ denotes the kth channel feature of $\boldsymbol{x}$.[4] For the ℓth layer $(0 \le \ell \le L-1)$
129 of ConvNets, the linear operator $\mathcal{A}^\ell(\cdot) : \mathbb{R}^{C_\ell \times m} \mapsto \mathbb{R}^{C_{\ell+1} \times m}$ in (1) is a convolution operation with
130 $C_{\ell+1}$ output channels,

$$\boldsymbol{z}^{\ell+1} = \left(\boldsymbol{z}_1^{\ell+1}, \boldsymbol{z}_2^{\ell+1}, \cdots, \boldsymbol{z}_{C_{\ell+1}}^{\ell+1}\right),$$

$$\boldsymbol{z}_k^{\ell+1} = \varphi\left(\sum_{j=1}^{C_\ell} \boldsymbol{a}_{kj}^\ell * \boldsymbol{z}_j^\ell\right) \quad (1 \le k \le C_{\ell+1}),$$

---

[2]In [29], the results are reported based on ResNet9, whereas our method can be easily added to larger networks, e.g. ResNet18 and ResNet50.

[3]The nonlinearity could contain BatchNorm [4], pooling, dropout [47], and stride, etc.

[4]If the data is 2D, we can assume $\boldsymbol{x} \in \mathbb{R}^{m_1 \times m_2}$. For simplicity, we present our idea based on 1D signal.

where $*$ denotes the convolution between two items that we will discuss below in more detail. Thus, for the ℓth layer with C_ℓ input channels and $C_{\ell+1}$ output channels, we can organize the convolution kernels $\{\boldsymbol{a}_{kj}\}$ as

$$
\boldsymbol{A}^\ell \;=\; \begin{bmatrix}
\boldsymbol{a}_{11}^\ell & \boldsymbol{a}_{12}^\ell & \cdots & \boldsymbol{a}_{1C_\ell}^\ell \\
\boldsymbol{a}_{21}^\ell & \boldsymbol{a}_{22}^\ell & \cdots & \boldsymbol{a}_{2C_\ell}^\ell \\
\vdots & \vdots & \ddots & \vdots \\
\boldsymbol{a}_{C_{\ell+1}1}^\ell & \boldsymbol{a}_{C_{\ell+1}2}^\ell & \cdots & \boldsymbol{a}_{C_{\ell+1}C_\ell}^\ell
\end{bmatrix}.
$$

Convolution operators. For the simplicity of presentation and analysis, we adopt *circular* convolution instead of linear convolution.[5] For 1D signal, given a kernel $\boldsymbol{a} \in \mathbb{R}^n$ and an input signal $\boldsymbol{x} \in \mathbb{R}^m$ (in many cases $m \gg n$), a circular convolution $*$ between $\boldsymbol{a}$ and $\boldsymbol{x}$ can be written in a simple matrix-vector product form via

$$
\boldsymbol{y} \;=\; \boldsymbol{a} * \boldsymbol{x} \;=\; \boldsymbol{C_a} \cdot \boldsymbol{x},
$$

where $\boldsymbol{C_a}$ denotes a circulant matrix of (zero-padded) $\boldsymbol{a}$,

$$
\boldsymbol{C_a} \;:=\; \begin{bmatrix} \mathrm{s}_0\,[\boldsymbol{a}] & \mathrm{s}_1\,[\boldsymbol{a}] & \cdots & \mathrm{s}_{m-1}\,[\boldsymbol{a}] \end{bmatrix},
$$

which is the concatenation of all cyclic shifts $\mathrm{s}_k\,[\boldsymbol{a}]$ $(0 \le k \le m-1)$ of length k of the (zero-padded) vector $\boldsymbol{a}$. Since $\boldsymbol{C_a}$ can be decomposed via the discrete Fourier transform (DFT) matrix $\boldsymbol{F}$:

$$
\boldsymbol{C_a} \;=\; \boldsymbol{F}^* \operatorname{diag}(\widehat{\boldsymbol{a}})\,\boldsymbol{F}, \quad \widehat{\boldsymbol{a}} \;=\; \boldsymbol{F}\boldsymbol{a}, \tag{3}
$$

where $\widehat{\boldsymbol{a}}$ denotes the Fourier transform of a vector $\boldsymbol{a}$. The computation of $\boldsymbol{a} * \boldsymbol{x}$ can be carried out efficiently via fast Fourier transform (FFT) in the frequency domain. We refer the readers to the appendix for more technical details.

3 Convolutional Normalization

In the following, we introduce the proposed ConvNorm, that can fully exploit benign convolution structures of ConvNets. It can be efficiently implemented in the frequency domain, and reduce the layer-wise Lipschitz constant. First of all, we build intuitions of the new design from the simplest setting. From this, we show how to expand the idea to practical ConvNets and discuss its advantages for training and robustness.

3.1 A warm-up study

Let us build some intuitions by zooming into one layer of ConvNets with both input and output being *single-channel*,

$$
\boldsymbol{z}_{out} \;=\; \mathcal{A}_L(\boldsymbol{z}) \;=\; \boldsymbol{a} * \boldsymbol{z}_{in}, \tag{4}
$$

where $\boldsymbol{z}_{in}$ is the input signal, $\boldsymbol{a}$ is a single kernel, and $\boldsymbol{z}_{out}$ denotes the output before the nonlinear activation. The form (4) is closely related to recent work on blind deconvolution [46]. More specifically, the work showed that normalizing the output $\boldsymbol{z}_{out}$ via *preconditioning* eliminates bad local minimizers and dramatically improves the optimization landscapes for learning the kernel $\boldsymbol{a}$. The basic idea is to multiply a preconditioning matrix which approximates the following form[6]

$$
\boldsymbol{P} \;=\; \left(\boldsymbol{C_a}\boldsymbol{C_a}^\top\right)^{-1/2}. \tag{5}
$$

As we observe

$$
\widetilde{\boldsymbol{z}}_{out} \;=\; \boldsymbol{P}\boldsymbol{z}_{out} \;=\; \underbrace{\left(\boldsymbol{C_a}\boldsymbol{C_a}^\top\right)^{-1/2}\boldsymbol{C_a}}_{\boldsymbol{Q}(\boldsymbol{a})} \cdot \boldsymbol{z}_{in},
$$

the ConvNorm is essentially *reparametrizing* the circulant matrix $\boldsymbol{C_a}$ of the kernel $\boldsymbol{a}$ to an *orthogonal* circulant matrix $\boldsymbol{Q}(\boldsymbol{a}) = \left(\boldsymbol{C_a}\boldsymbol{C_a}^\top\right)^{-1/2}\boldsymbol{C_a}$, with $\boldsymbol{Q}\boldsymbol{Q}^\top = \boldsymbol{I}$. Thus, the ConvNorm is improving the

---

[5]Although there are slight differences between linear and circulant convolutions on the boundaries, actually any linear convolution can be *reduced* to circular convolution simply via zero-padding.

[6]In the work [46], they cook up a matrix by using output samples $\widetilde{\boldsymbol{P}} = \left(\frac{C}{m}\sum_{i=1}^m \boldsymbol{C}_{\boldsymbol{z}_{out}^i}(\boldsymbol{C}_{\boldsymbol{z}_{out}^i})^\top\right)^{-1/2}$. When the input samples $\boldsymbol{z}_{in}^i$ are i.i.d. zero mean, it can be showed that $\widetilde{\boldsymbol{P}} \approx \boldsymbol{P}$ for large m. For ConvNets, we can just use the learned kernel $\boldsymbol{a}$ for cooking up $\boldsymbol{P}$.

conditioning of the *vanilla* problem and reducing the Lipschitz constant of the operator $\mathcal{A}_L(\cdot)$ in (4). On the other hand, the benefits of this normalization can also be observed in the frequency domain. Based on (3), we have $\boldsymbol{P} = \boldsymbol{F}^* \operatorname{diag}(\boldsymbol{v}) \boldsymbol{F} = \boldsymbol{C}_{\boldsymbol{v}}$ with $\boldsymbol{v} = \boldsymbol{F}^{-1}\left(|\widehat{\boldsymbol{a}}|^{\odot -1}\right)$. Thus, we also have

$$\boldsymbol{Q}(\boldsymbol{a}) = \boldsymbol{C}_{\boldsymbol{v}} \cdot \boldsymbol{C}_{\boldsymbol{a}} = \boldsymbol{C}_{\boldsymbol{v}*\boldsymbol{a}} = \boldsymbol{F}^* \operatorname{diag}(\widehat{\boldsymbol{g}}(\boldsymbol{a}))\boldsymbol{F}, \quad \widehat{\boldsymbol{g}}(\boldsymbol{a}) = \widehat{\boldsymbol{a}} \odot |\widehat{\boldsymbol{a}}|^{\odot -1},$$

with $\odot$ denoting entrywise operation and $\boldsymbol{g} = \boldsymbol{F}^{-1}\left(\widehat{\boldsymbol{a}} \odot |\widehat{\boldsymbol{a}}|^{\odot -1}\right)$. Thus, we can see that:

- Although the reparameterization involves matrix inversion, which is typically expensive to compute, for convolution it can actually be much more efficiently implemented in the frequency domain via FFT, reducing the complexity from $O(n^3)$ to $O(n \log n)$.
- The reparametrized kernel $\boldsymbol{g}$ is effectively an *all-pass* filter with flat normalized spectrum $\widehat{\boldsymbol{a}} \odot |\widehat{\boldsymbol{a}}|^{\odot -1}$.[7] From an information theory perspective, this implies that it can better preserve (in particular, high-frequency) information of the input feature from the previous layer.

3.2 ConvNorm for multiple channels

So far, we only considered one layer ConvNets with single-channel input and output. However, recall from Section 2, modern deep ConvNets are usually designed with many layers; each typical layer is constructed with a linear transformation with *multiple* input and output channels, followed by strides, normalization, and nonlinear activation. Extension of the normalization approach in Section 3.1 from one layer to multiple layers is easy, which can be done by applying the same normalization repetitively for all the layers. However, generalizing our method from a single channel to multiple channels is not obvious, that we discuss below.

In [40], the work introduced a preconditioning method for normalizing multiple kernels in convolutional sparse coding. In the following, we show that such an idea can be adapted to normalize each output channel, reduce the Lipschitz constant of the weight matrix in each layer, and improve training and network robustness. Let us consider any layer ℓ ($1 \leq \ell \leq L$) within a *vanilla* ConvNet using 1-stride, and take one channel (e.g., k-th channel) of that layer as an example. For simplicity of presentation, we hide the layer number ℓ. Given $\boldsymbol{z}_{k,out} = \sum_{j=1}^{C_I} \boldsymbol{a}_{kj} * \boldsymbol{z}_{j,in}$, the k-th output channel can be written as

$$\boldsymbol{z}_{k,out} = \underbrace{\begin{bmatrix} \boldsymbol{C}_{\boldsymbol{a}_{k1}} & \boldsymbol{C}_{\boldsymbol{a}_{k2}} & \cdots & \boldsymbol{C}_{\boldsymbol{a}_{kC_I}} \end{bmatrix}}_{\boldsymbol{A}_k} \cdot \underbrace{\begin{bmatrix} \boldsymbol{z}_{1,in} \\ \boldsymbol{z}_{2,in} \\ \vdots \\ \boldsymbol{z}_{C_I,in} \end{bmatrix}}_{\boldsymbol{z}_{in}},$$

with C_I and C_O being the numbers of input and output channels, respectively. For each channel $k = 1, \cdots, C_O$, we normalize the output by

$$\boxed{\boldsymbol{P}_k = \left(\sum_{j=1}^{C_I} \boldsymbol{C}_{\boldsymbol{a}_{kj}} \boldsymbol{C}_{\boldsymbol{a}_{kj}}^\top\right)^{-1/2} = \left(\boldsymbol{A}_k \boldsymbol{A}_k^\top\right)^{-1/2},} \tag{6}$$

so that

$$\widetilde{\boldsymbol{z}}_{k,out} = \boldsymbol{P}_k \boldsymbol{z}_{k,out} = \underbrace{\left(\boldsymbol{A}_k \boldsymbol{A}_k^\top\right)^{-1/2} \boldsymbol{A}_k}_{\boldsymbol{Q}_k(\boldsymbol{A}_k)} \cdot \boldsymbol{z}_{in}. \tag{7}$$

Thus, we can see the ConvNorm is essentially a reparameterization of the kernels $\{\boldsymbol{a}_{kj}\}_{j=1}^{C_I}$ for the k-th channel. Similar to Section 3.1, the operation can be rewritten in the form of convolutions

$$\boldsymbol{Q}_k(\boldsymbol{A}_k) = \boldsymbol{P}_k \boldsymbol{A}_k = \begin{bmatrix} \boldsymbol{C}_{\boldsymbol{v}_k * \boldsymbol{a}_{k1}} & \cdots & \boldsymbol{C}_{\boldsymbol{v}_k * \boldsymbol{a}_{kC_I}} \end{bmatrix}$$

with $\boldsymbol{P}_k = \boldsymbol{C}_{\boldsymbol{v}_k}$ and $\boldsymbol{v}_k = \boldsymbol{F}^{-1}\left(\sum_{i=1}^{C_I} |\widehat{\boldsymbol{a}}_{ki}|^{\odot 2}\right)^{\odot -1/2}$; it can be efficiently implemented via FFT.

Here, as for multiple kernels the matrix $\boldsymbol{A}_k$ is *overcomplete* (i.e., $\boldsymbol{A}_k$ is a wide rectangular matrix), we *cannot* normalize the channel-wise weight matrix $\boldsymbol{A}_k$ to exact orthogonal. However, it can be normalized to *tight frame* with $\boldsymbol{Q}_k \boldsymbol{Q}_k^\top = \boldsymbol{I}$. This further implies that we can normalize the spectral norm $\|\boldsymbol{Q}_k\|$ of the weight matrix $\boldsymbol{Q}_k$ in each channel to unity (see Figure 2 (Left)).

---

[7]An all-pass filter is a signal processing filter that passes all frequencies equally in gain, but can change the phase relationship among various frequencies.

Combining the operation for all the channels, the ConvNorm for each layer overall can be summarized as follows:

$$
\widetilde{\boldsymbol{z}}_{out} \;=\; \begin{bmatrix} \boldsymbol{P}_1 \boldsymbol{z}_{1,out} \\ \vdots \\ \boldsymbol{P}_{C_O} \boldsymbol{z}_{C_O,out} \end{bmatrix} \;=\; \underbrace{\begin{bmatrix} \boldsymbol{Q}_1 \\ \vdots \\ \boldsymbol{Q}_{C_O} \end{bmatrix}}_{\boldsymbol{Q}} \boldsymbol{z}_{in},
$$
(8)

Figure 2: **Condition number for each channel (averaged over all channels) (Left), and spectral norm for each layer (Right)** on ResNet18 except for skip connection layers. ConvNorm normalizes the channel-wise condition number to 1 and reduces the layer-wise spectral norm. We use the method in [51] to calculate the singular values of the weight matrix.

that we normalize each output channel k by different matrix $\boldsymbol{P}_k$. The proposed ConvNorm has several advantages that we discuss below.

Proposition 3.1 *The spectral norm of $\boldsymbol{Q}$ introduced in* (8) *can be bounded by*

$$
\|\boldsymbol{Q}\| \;\leq\; \sqrt{\sum_{k=1}^{C_O} \|\boldsymbol{Q}_k\|^2},
$$

that spectral norm of $\boldsymbol{Q}$ is bounded by the spectral norms of all the weights $\{\boldsymbol{Q}_k\}_{k=1}^{C_O}$.

Proof We defer the proof to the Appendix A.3. ∎

- **Efficient implementations.** There are many existing results [29, 39, 41] trying to normalize the whole layerwise weight matrix. For ConvNets, as the matrix is neither circulant nor block circulant, computing its inversion is often computationally prohibitive. Here, for each layer, we only normalize the weight matrix of the individual output channel. Thus similar to Section 3.1, the inversion in (6) can be much more efficiently computed via FFT by exploiting the benign convolutional structure.
- **Improving layer-wise Lipschitzness.** As we can see from Proposition 3.1, although ConvNorm only normalized the spectral norm of each channel, it can actually reduce the spectral norm of the whole weight matrix, improving the Lipschitzness of each layer; see Figure 2 (Right) for a numerical demonstration on ResNet18. As extensively investigated [28, 29, 42], improving the Lipschitzness of the weights for ConvNets will lead to enhanced robustness against data corruptions, for which we will demonstrate on the proposed ConvNorm in Section 4.1.
- **Easier training and better generalization.** For deconvolution and convolutional sparse coding problems, the work [40, 46] showed that ConvNorm could dramatically improve the corresponding nonconvex optimization landscapes. On the other hand, from an algorithmic unrolling perspective for neural network design [52, 53], the ConvNorm is analogous to the preconditioned or conjugate gradient methods [54] which often substantially boost algorithmic convergence. Therefore, we conjecture that the ConvNorm also leads to better optimization landscapes for training ConvNets, that they can be optimized faster to better solution qualities of generalization. We empirically show this in Section 4.2.

3.3 Extra technical details

To achieve the full performance and efficiency potentials of the proposed ConvNorm, we discuss some essential implementation details in the following.

Efficient back-propagation. For ConvNorm, as the normalization matrix in (6) is constructed from the learned kernels, it complicates the computation of the gradient in back-propagation when training the network. Fortunately, we observe that treating the normalization matrices $\{\boldsymbol{P}_k\}$ as constants during back-propagation usually does *not* affect the training and generalization performances, so that the computational complexity in training is not increased. We noticed that such a technique has also been recently considered in [55] for self-supervised learning, which is termed as *stop-gradient*.

Learnable affine tranform. For each channel, we include an (optional) *affine transform* after the normalization $\boldsymbol{P}_k \cdot \boldsymbol{z}_{k,out} = \boldsymbol{C}_{\boldsymbol{v}_k} \cdot \boldsymbol{z}_{k,out} = \boldsymbol{v}_k * \boldsymbol{z}_{k,out}$ in (7) as follows:

$$
\overline{\boldsymbol{z}}_k \;=\; \boldsymbol{r}_k * \widetilde{\boldsymbol{z}}_{k,out} \;=\; \boldsymbol{r}_k * \boldsymbol{v}_k * \boldsymbol{z}_{k,out},
$$

where the extra convolutional kernel $\boldsymbol{r}_k$ is learned along with the original model parameters. The idea of including this affine transform is analogous to including a learnable rescaling in BatchNorm, which can be considered as an "undo" operation to make sure the identity transform can be represented [4].

The difference between our affine transform and BatchNorm is that we apply channel-wise convolutions instead of simple rescaling (see Figure 1). Note that when r_k is an inverse kernel of v_k (i.e., $r_k * v_k = 1$), the overall transformation becomes an identity. The effectiveness of affine transform is demonstrated in the ablation study in Appendix C.4.

Dealing with stride and 2D convolution. There are extra technicalities that we briefly discuss below. For more details, we refer the readers to Appendix B.

- *Extension to 2D convolution.* Although we introduced the ConvNorm based on 1D convolution for the simplicity of presentations, it should be noted that our approach can be easily extended to the 2D case via 2D FFT.

- *Dealing with stride.* Strided convolutions are universal in modern ConvNet architectures such as the ResNet [5], which can be viewed as downsampling after unstrided convolution. To deal with stride for our ConvNorm, we first perform an unstrided convolution, normalizing the activations using ConvNorm and then downsampling the normalized activations. In comparison, the method proposed in [29] is incompatible with strided convolutions.

4 Experiments & Results

In this section, we run extensive experiments on CIFAR and ImageNet, empirically demonstrating two major advantages of our approach: *(i)* it improves the *robustness* against adversarial attacks, data scarcity, and label noise corruptions [56–58], and *(ii)* it makes deep ConvNets *easier to train* and perform better on problems such as classification and GANs [59]. The rest of this section is organized as follows. First, we introduce baseline methods for comparisons, and describe the setups of network architectures, datasets, and training. In Section 4.1 and Section 4.2, we demonstrate the effectiveness of our approach on robustness and training, respectively.

Baseline methods for comparisons. We compare our method with three representative methods.

- **Spectral normalization (SN).** For each layer of ConvNets, the work [15] treats multi-dimensional convolutional kernels as 2D matrices (e.g., by flattening certain dimensions) and normalizes its spectrum (i.e., singular values). It estimates the matrix's maximum singular value via a power method and then uses it to normalize all the singular values. As we discussed in Section 1, the method does not exploit convolutional structures of ConvNets.

- **Orthogonalization by Newton's Iteration (ONI).** The work [39] whitens the same reshaped matrices as SN, so that the reshaped matrices are reparametrized to orthogonality. However, the method needs to compute full inversions of covariance matrices, which is approximated by Newton's iterations. Again, no convolutional structure is utilized.

- **Orthogonal ConvNets (OCNN).** Few methods that exploit convolutional structures are [22, 43], which enforce orthogonality on doubly block circulant matrices of kernels via penalties on the loss. Here, we compare with [43].

Setups of dataset, network and training. For all experiments, if not otherwise mentioned, CIFAR-10 and CIFAR-100 datasets are processed with standard augmentations, i.e., random cropping and flipping. We use 10% of the training set for validation and treat the validation set as a held-out test set. For ImageNet, we perform standard random resizing and flipping. For training, we observe our ConvNorm is not sensitive to the learning rate, and thus we fix the initial learning rate to 0.1 for all experiments.[8] For experiments on CIFAR-10, we run 120 epochs and divide the learning rate by 10 at the 40th and 80th epochs; for CIFAR-100, we run 150 epochs and divide the learning rate by 10 at the 60th and 120th epoch; for ImageNet,we run 90 epochs and divide the learning rate by 10 at the 30th and 90th epochs. The optimization is done using SGD with a momentum of 0.9 and a weight decay of 0.0001 for all datasets. For networks we use two backbone networks: VGG16 [60] and ResNet18 [5]. We adopt Xavier uniform initialization [61] which is the default initialization in PyTorch for all networks.

4.1 Improved robustness

In this section, we demonstrate our method is more robust to various kinds of adversarial attacks, as well as random label corruptions and small training datasets.

Robustness against adversarial attacks. Existing results [29, 43] show that controlling the layer-wise Lipschitz constants for deep networks improves robustness against adversarial attack. Since our method improves the Lipschitzness of weights (see Figure 2), we demonstrate its robustness under

---

[8]For experiments with ONI, we use learning rate 0.01 since the loss would be trained to NaN if with 0.1.

ϵ	Test Acc.	SN	BN	ONI	OCNN	ConvNorm
0	Clean	82.52 ± 0.22	82.13 ± 0.67	80.70 ± 0.14	82.90 ± 0.31	$\mathbf{83.23 \pm 0.25}$
	FGSM	52.34 ± 0.33	51.72 ± 0.52	48.33 ± 0.16	52.49 ± 0.21	$\mathbf{52.87 \pm 0.24}$
$\frac{8}{255}$	PGD-10	45.68 ± 0.40	45.31 ± 0.29	42.30 ± 0.24	45.74 ± 0.13	$\mathbf{46.12 \pm 0.26}$
	PGD-20	44.47 ± 0.37	44.04 ± 0.24	41.08 ± 0.30	44.53 ± 0.10	$\mathbf{44.75 \pm 0.30}$

Table 1: **Comparison of ConvNorm to baseline methods under different gradient based attacks.** Models are robustly trained following the procedure in [62] using a ResNet18 backbone. Experiments are conducted on CIFAR-10 dataset. Results are averaged over 4 random seeds.

adversarial attack on the CIFAR-10 dataset. We adopt both white-box (gradient based) attack [57, 58] and black-box attack [56] to test the robustness of our proposed method and other baseline methods. The results are presented in Table 1 and Table 2. For the ease of presentation, all technical details about model training and generation of the adversarial examples are postponed to Appendix C.

In the case of gradient based attacks, we follow the training procedure described in [62] to train models with our ConvNorm and other baseline methods. We report the performances of the robustly trained models on both the clean test dataset and datasets that are perturbed by Fast Gradient Sign Method (FGSM) [57] and Projected Gradient Method (PGD) [58]. As shown in Table 1, our ConvNorm outperforms other methods in terms of robustness under white-box attack while maintaining a good performance on clean test accuracy.

Method	Average Queries	Attack Success rate (%)
SN	2519.32	60.60
ONI	2817.09	55.90
OCNN	2892.81	54.50
ConvNorm	**2966.16**	**53.50**

Table 2: **Comparison of ConvNorm to baseline methods on SimBA black box attack.** The mean value of average queries (the higher, the better) and attack success rate (the lower, the better) throughout 3 runs are reported. Models are trained using a ResNet18 backbone without BN layers.

For black-box attack, we adopt a popular black-box adversarial attack method, Simple Black-box Adversarial Attacks (SimBA) [56]. By submitting queries to a model for updated test accuracy, the attack method iteratively finds a perturbation where the confidence score drops the most. We report the average queries and success rate after 3072 iterations in Table 2. As we can see, the ConvNorm resists the most queries, and that the SimBA has the lowest attack success rate for ConvNorm compared with other baseline methods.

Robustness against label noise and data scarcity. It has been widely observed that overparameterized ConvNets tend to overfit when label noise presents or the amount of training labels is limited [63–66]. Recent work [67] shows that normalizing the weights enforces certain regularizations, which can improve generalization performance against both label noise and data scarcity. Since our method is essentially reparametrizing and normalizing the weights, we demonstrate the robustness of our approach under these settings on CIFAR-10 with ResNet18 backbone.

Figure 3: **Test accuracy for noisy label (Left) and insufficient training data (Right)**. Experiments are conducted on CIFAR-10 dataset using a ResNet18 backbone. Error bars corresponding to standard deviations over 3 runs.

- *Robustness against label noise.* Following the scheme proposed in [68], we simulate noisy labels by randomly flipping 20% to 80% of the labels in the training set. As shown in Figure 3 (Left), our method outperforms the others on most noisy rates by a hefty margin when the noise level is high.

- *Robustness against data scarcity.* We test our method on training the network with varying sizes of the training set, obtained by randomly sampling. The results in Figure 3 (Right) show that our ConvNorm achieves on par performance compared with baseline methods, and its performance stays high even when the size of the training data is tiny (e.g., 4500 examples).

Figure 4: **ConvNorm accelerates convergence.** VGG16 trained on CIFAR-10 (Left), and ResNet18 (Middle) trained on CIFAR-10 and ImageNet (Right), with and without ConvNorm or BatchNorm. We do not use data augmentation, weight decay, or any other regularization in this experiment to isolate the effects of the normalization techniques. Error bars correspond to min/max over 4 runs.

4.2 Easier training on classification and GAN

Finally, we compare training convergence speed for classification and performances on GAN. Extra experiments on better generalization performance and ablation study can be found in Appendix C.4.

Improved training on supervised learning. We test our method on image classification tasks with two backbone architectures: VGG16 and ResNet18. We show that ConvNorm accelerates the convergence of training. To isolate the effects of the normalization layers for training, we train on CIFAR-10 and ImageNet without using any augmentation, regularization, and learning rate decay. In Figure 4, we show that adding ConvNorm consistently results in faster convergence, stable training (less variance in accuracy), and superior performance. On CIFAR-10, there is a wide performance gap after the first few iterations of training: 1000 iterations of training with ConvNorm lead to generalization performance comparable to 8000 iterations of training using BatchNorm. In the case of standard settings where data augmentation, regularization and learning rate decay are added, we notice that using ConvNorm and BatchNorm together also yield better test performances compared to only using BatchNorm (See Appendix C.4 for details).

Improved performance for GANs. It has been found that improving the Lipschitz condition of the discriminator of GAN stabilizes its training [69]. For instance, WGAN-GP [70] demonstrates that adding a gradient penalty (1-GP) regularization to enforce the 1-Lipschitzness of the discriminator stabilizes GAN training and prevents mode collapse. Subsequent works [71, 72] using variants of the 1-GP regularization also show their improvement in GAN. Later on, [15] further reveals the performance of GAN can be significantly improved if the spectral norm (Lipschitz condition) of the discriminator network is strictly enforced to 1. As shown in Figure 2, the proposed ConvNorm also controls the Lipschitz condition of ConvNets. Therefore, we expect our method to also ameliorates the performance of GAN.

To demonstrate the effectiveness of the ConvNorm on GAN, we compare it with other baseline methods introduced previously. In our experiments, we adopt the same settings and architecture suggested in [15] without any modification, and we use the inception score (IS) [73], and FID [74] score for quantitative evaluation. As shown in Table 3, our ConvNorm achieves the second-best performance to SN.[9]

Metric	SN	ONI	OCNN	Vanilla	ConvNorm
IS	**8.12**	7.07	7.54	7.13	7.62
FID	**14.53**	29.49	22.15	29.47	21.37

Table 3: **Comparison of ConvNorm to baseline methods on GAN training.** Inception score (IS) (the higher, the better) and FID score (the lower, the better) of ResNet with different normalizations. For each pair of model and method, we generate $50k$ images 10 times and compute the mean of IS.

5 Discussions & Conclusion

In this work, we introduced a new normalization approach for ConvNets, which explicitly exploits translation-invariance properties of convolutional operators, leading to efficient implementation and boosted performances in training, generalization, and robustness. Our work has opened several interesting directions to be further exploited for normalization design of ConvNets: *(i)* although we provided some high-level intuitions why our ConvNorm works, theoretical justifications are needed; *(ii)* as our ConvNorm only promotes channel-wise "orthogonality", it would be interesting to utilize similar ideas to efficiently normalize the layerwise weight matrices by exploiting convolutional structures. We leave these questions for future investigations.

---

[9]The performance of GANs is highly sensitive to the computational budget and the hyperparameters of the networks [75], and the hyperparameters of SN is fine-tuned for CIFAR-10 while we use the same hyperparameters as SN.

References

[1] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.

[2] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[3] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1–9, 2015.

[4] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, pages 448–456, 2015.

[5] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[6] Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1492–1500, 2017.

[7] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4700–4708, 2017.

[8] Lei Huang, Jie Qin, Yi Zhou, Fan Zhu, Li Liu, and Ling Shao. Normalization techniques in training dnns: Methodology, analysis and application. *arXiv preprint arXiv:2009.12836*, 2020.

[9] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[10] Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Instance normalization: The missing ingredient for fast stylization. *arXiv preprint arXiv:1607.08022*, 2016.

[11] Yuxin Wu and Kaiming He. Group normalization. In *Proceedings of the European conference on computer vision (ECCV)*, pages 3–19, 2018.

[12] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pages 2961–2969, 2017.

[13] Yu Sun, Xiaolong Wang, Zhuang Liu, John Miller, Alexei Efros, and Moritz Hardt. Test-time training with self-supervision for generalization under distribution shifts. In *International Conference on Machine Learning*, pages 9229–9248. PMLR, 2020.

[14] Tim Salimans and Diederik P Kingma. Weight normalization: A simple reparameterization to accelerate training of deep neural networks. *arXiv preprint arXiv:1602.07868*, 2016.

[15] Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. *arXiv preprint arXiv:1802.05957*, 2018.

[16] Alexandre Araujo, Benjamin Negrevergne, Yann Chevaleyre, and Jamal Atif. On lipschitz regularization of convolutional layers using toeplitz matrix theory. 2021.

[17] Haifeng Qian and Mark N Wegman. L2-nonexpansive neural networks. In *International Conference on Learning Representations*, 2018.

[18] Andrew M Saxe, James L McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks. *arXiv preprint arXiv:1312.6120*, 2013.

[19] Jeffrey Pennington, Samuel Schoenholz, and Surya Ganguli. The emergence of spectral universality in deep networks. In *International Conference on Artificial Intelligence and Statistics*, pages 1924–1932, 2018.

[20] Lechao Xiao, Yasaman Bahri, Jascha Sohl-Dickstein, Samuel Schoenholz, and Jeffrey Pennington. Dynamical isometry and a mean field theory of cnns: How to train 10,000-layer vanilla convolutional neural networks. In *International Conference on Machine Learning*, pages 5393–5402, 2018.

[21] Wei Hu, Lechao Xiao, and Jeffrey Pennington. Provable benefit of orthogonal initialization in optimizing deep linear networks. In *International Conference on Learning Representations*, 2020.

[22] Haozhi Qi, Chong You, Xiaolong Wang, Yi Ma, and Jitendra Malik. Deep isometric learning for visual recognition. In *International Conference on Machine Learning*, pages 7824–7835. PMLR, 2020.

[23] Martin Arjovsky, Amar Shah, and Yoshua Bengio. Unitary evolution recurrent neural networks. In *International Conference on Machine Learning*, pages 1120–1128, 2016.

[24] Eugene Vorontsov, Chiheb Trabelsi, Samuel Kadoury, and Chris Pal. On orthogonality and learning recurrent networks with long term dependencies. In *International Conference on Machine Learning*, pages 3570–3578, 2017.

[25] Kyle Helfrich, Devin Willmott, and Qiang Ye. Orthogonal recurrent neural networks with scaled cayley transform. In *International Conference on Machine Learning*, pages 1969–1978. PMLR, 2018.

[26] Mario Lezcano-Casado and David Martınez-Rubio. Cheap orthogonal constraints in neural networks: A simple parametrization of the orthogonal and unitary group. In *International Conference on Machine Learning*, pages 3794–3803, 2019.

[27] Kui Jia, Shuai Li, Yuxin Wen, Tongliang Liu, and Dacheng Tao. Orthogonal deep neural networks. *IEEE transactions on pattern analysis and machine intelligence*, 2019.

[28] Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. *arXiv preprint arXiv:1704.08847*, 2017.

[29] Asher Trockman and J Zico Kolter. Orthogonalizing convolutional layers with the cayley transform. In *International Conference on Learning Representations*, 2021.

[30] Bingchen Liu, Yizhe Zhu, Zuohui Fu, Gerard de Melo, and Ahmed Elgammal. Oogan: Disentangling gan with one-hot sampling and orthogonal regularization. In *AAAI*, pages 4836–4843, 2020.

[31] Chengxi Ye, Matthew Evanusa, Hua He, Anton Mitrokhin, Tom Goldstein, James A. Yorke, Cornelia Fermuller, and Yiannis Aloimonos. Network deconvolution. In *International Conference on Learning Representations*, 2020.

[32] Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. In *International Conference on Learning Representations*, 2018.

[33] Augustus Odena, Jacob Buckman, Catherine Olsson, Tom B Brown, Christopher Olah, Colin Raffel, and Ian Goodfellow. Is generator conditioning causally related to gan performance? *arXiv preprint arXiv:1802.08768*, 2018.

[34] Matan Atzmon, Amos Gropp, and Yaron Lipman. Isometric autoencoders. *arXiv preprint arXiv:2006.09289*, 2020.

[35] Mehrtash Harandi and Basura Fernando. Generalized backpropagation, Étude de cas: Orthogonality. *arXiv*, 2016.

[36] Nitin Bansal, Xiaohan Chen, and Zhangyang Wang. Can we gain more from orthogonality regularizations in training deep cnns? In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 4266–4276. Curran Associates Inc., 2018.

[37] Guoqiang Zhang, Kenta Niwa, and W. B. Kleijn. Approximated orthonormal normalisation in training neural networks, 2019.

[38] Jun Li, Fuxin Li, and Sinisa Todorovic. Efficient riemannian optimization on the stiefel manifold via the cayley transform. In *International Conference on Learning Representations*, 2020.

[39] Lei Huang, Li Liu, Fan Zhu, Diwen Wan, Zehuan Yuan, Bo Li, and Ling Shao. Controllable orthogonalization in training dnns, 2020.

[40] Qing Qu, Yuexiang Zhai, Xiao Li, Yuqian Zhang, and Zhihui Zhu. Geometric analysis of nonconvex optimization landscapes for overcomplete learning. In *International Conference on Learning Representations*, 2020.

[41] Lei Huang, Xianglong Liu, Bo Lang, Adams Wei Yu, and Bo Li. Orthogonal weight normalization: Solution to optimization over multiple dependent stiefel manifolds in deep neural networks. *CoRR*, abs/1709.06079, 2017.

[42] Qiyang Li, Saminul Haque, Cem Anil, James Lucas, Roger Grosse, and Jörn-Henrik Jacobsen. Preventing gradient attenuation in lipschitz constrained convolutional networks. *Conference on Neural Information Processing Systems*, 2019.

[43] Jiayun Wang, Yubei Chen, Rudrasis Chakraborty, and Stella X. Yu. Orthogonal convolutional neural networks, 2019.

[44] Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

[45] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

[46] Qing Qu, Xiao Li, and Zhihui Zhu. A nonconvex approach for exact and efficient multichannel sparse blind deconvolution. In *Advances in Neural Information Processing Systems*, pages 4017–4028, 2019.

[47] Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

[48] Katarzyna Janocha and Wojciech Marian Czarnecki. On loss functions for deep neural networks in classification. *arXiv preprint arXiv:1702.05659*, 2017.

[49] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[50] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[51] Hanie Sedghi, Vineet Gupta, and Philip M Long. The singular values of convolutional layers. *arXiv preprint arXiv:1805.10408*, 2018.

[52] Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *ICML*, pages 399–406, 2010.

[53] Vishal Monga, Yuelong Li, and Yonina C Eldar. Algorithm unrolling: Interpretable, efficient deep learning for signal and image processing. *arXiv preprint arXiv:1912.10557*, 2019.

[54] Jorge Nocedal and Stephen J. Wright. *Numerical Optimization*. Springer, New York, NY, USA, second edition, 2006.

[55] Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. *arXiv preprint arXiv:2011.10566*, 2020.

[56] Chuan Guo, Jacob Gardner, Yurong You, Andrew Gordon Wilson, and Kilian Weinberger. Simple black-box adversarial attacks. In *Proceedings of the 36th International Conference on Machine Learning*, pages 2484–2493, 2019.

[57] Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015.

[58] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

[59] Ian J. Goodfellow, Jean Pouget-Abadie, M. Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron C. Courville, and Yoshua Bengio. Generative adversarial nets. In *NIPS*, 2014.

[60] K. Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, abs/1409.1556, 2015.

[61] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *AISTATS*, 2010.

[62] Ali Shafahi, Mahyar Najibi, Mohammad Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *Advances in neural information processing systems*, volume 32, 2019.

[63] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2818–2826, 2016.

[64] Devansh Arpit, Stanisław Jastrzębski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, et al. A closer look at memorization in deep networks. In *International Conference on Machine Learning*, pages 233–242. PMLR, 2017.

[65] Mingchen Li, Mahdi Soltanolkotabi, and Samet Oymak. Gradient descent with early stopping is provably robust to label noise for overparameterized neural networks. In *International Conference on Artificial Intelligence and Statistics*, pages 4313–4324. PMLR, 2020.

[66] Sheng Liu, Jonathan Niles-Weed, Narges Razavian, and Carlos Fernandez-Granda. Early-learning regularization prevents memorization of noisy labels. *Advances in Neural Information Processing Systems*, 33, 2020.

[67] Wei Hu, Zhiyuan Li, and Dingli Yu. Simple and effective regularization methods for training on noisily labeled data with generalization guarantee. *arXiv preprint arXiv:1905.11368*, 2019.

[68] Giorgio Patrini, Alessandro Rozza, Aditya Krishna Menon, Richard Nock, and Lizhen Qu. Making deep neural networks robust to label noise: A loss correction approach. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1944–1952, 2017.

[69] Zhiming Zhou, J. Liang, Yuxuan Song, Lantao Yu, Hongwei Wang, W. Zhang, Y. Yu, and Z. Zhang. Lipschitz generative adversarial nets. In *ICML*, 2019.

[70] Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein GANs. In *Advances in neural information processing systems*, pages 5767–5777, 2017.

[71] Naveen Kodali, Jacob Abernethy, James Hays, and Zsolt Kira. On convergence and stability of GANs. *arXiv preprint arXiv:1705.07215*, 2017.

[72] Henning Petzka, Asja Fischer, and Denis Lukovnikov. On the regularization of wasserstein GANs. In *International Conference on Learning Representations*, 2018.

[73] Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *arXiv preprint arXiv:1606.03498*, 2016.

[74] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in neural information processing systems*, pages 6626–6637, 2017.

[75] Mario Lucic, Karol Kurach, Marcin Michalski, Sylvain Gelly, and Olivier Bousquet. Are GANs created equal? a large-scale study. In *Advances in neural information processing systems*, pages 700–709, 2018.

[76] Chen Kong and Simon Lucey. Take it in your stride: Do we need striding in cnns? *arXiv preprint arXiv:1712.02502*, 2017.