A Contextualized BERT model for Knowledge Graph Completion

Haji Gul
School of Digital Science,
Universiti Brunei Darussalam
23h1710@ubd.edu.bn

Abul Ghani Haji Naim
School of Digital Science,
Universiti Brunei Darussalam
ghani.naim@ubd.edu.bn

Ajaz Ahmad Bhat
School of Digital Science,
Universiti Brunei Darussalam
ajaz.bhat@ubd.edu.bn

Abstract

Knowledge graphs (KGs) are valuable for representing structured, interconnected information across domains, enabling tasks like semantic search, recommendation systems and inference. A pertinent challenge with KGs, however, is that many entities (i.e., heads, tails) or relationships are unknown. Knowledge Graph Completion (KGC) addresses this by predicting these missing nodes or links, enhancing the graph's informational depth and utility. Traditional methods like TransE and ComplEx predict tail entities but struggle with unseen entities. Textual-based models leverage additional semantics but come with high computational costs, semantic inconsistencies, and data imbalance issues. Recent LLM-based models show improvement but overlook contextual information and rely heavily on entity descriptions. In this study, we introduce a contextualized BERT model for KGC that overcomes these limitations by utilizing the contextual information from neighbouring entities and relationships to predict tail entities. Our model eliminates the need for entity descriptions and negative triplet sampling, reducing computational demands while improving performance. Our model outperforms state-of-the-art methods on standard datasets, improving Hit@1 by 5.3% and 4.88% on FB15k-237 and WN18RR respectively, setting a new benchmark in KGC. [1]

1 Introduction

A knowledge graph (KG) is a structured representation of entities (as nodes) and relationships (as links) that supports search, recommendation and other downstream reasoning tasks. However, KGs are often incomplete, with many entities (heads/tails) or relationships missing, limiting their utility in real-world applications [1]. Consequently, Knowledge Graph Completion (KGC)—predicting a missing tail entity $(h, r, ?)$, head entity $(?, r, t)$, or relationship $(h, ?, t)$ in a triplet—has become a critical research objective, with numerous methodologies proposed to tackle this issue.

Embedding-based methods, for instance, learn vector embeddings for entities and relationships from training data, but these methods struggle to generalize to *unseen* entities or relationships, impairing performance in tail prediction during testing [2]. Recently, large language model (LLM)-based approaches for KGC have shown potential in overcoming this limitation by leveraging LLMs trained on extensive datasets to capture complex semantic relationships and generalize better to unseen

---

[1]The main paper for this work has been submitted to ICLR 2025 for consideration.

Submitted to 38th Conference on Neural Information Processing Systems (NeurIPS 2024). Do not distribute.

entities [3, 10, 5, 10]. Despite these strengths, LLM-based models are computationally demanding, often overlook relationa context,xt, and depend heavily on entity descriptions and negative sampling. More recent LLM prompting-based approaches encode KGs into prompts[10], but injecting all relevant facts from a KG into prompts is labor-intensive, and generic LLMs often struggle with domain-specific KGs. Additionally, textual information-based methods like NN-KGC and Sim-KGC utilize neighborhood information for KGC, but they often require entity descriptions, which may not be available in many datasets, and add computational overhead [6, 7]. To address these limitations, we propose a Context-Aware BERT for Knowledge Graph Completion (CAB-KGC) [9] that extracts contextual information associated with the operational relationship, its neighboring entities and relationships associated with the head entity. This context is then integrated with the BERT model to enhance the prediction of tail entities. To summarise, this study makes the following contributions to the KG domain:

- We introduce the CAB-KGC approach [9] to address the KGC problem, leveraging graph features of head entity context and relationship context, and BERT model. The CAB-KGC approach outperforms SOTA KGC methods.
- CAB-KGC eliminates reliance on entity descriptions, focusing solely on head and relationship contexts for improved predictions available in all KGs.
- CAB-KGC does not require negative sample training, enhancing training speed and resilience against negative sample selection.
- Extensive experiments on various benchmark datasets demonstrate that CAB-KGC reliably excels in tail entity prediction.

2 Methodology

Problem Formulation (see Table 1 for notations): Consider a knowledge graph $G(E, R)$ as a collection of triplets (h, r, t), where $h \epsilon E$ is the head entity, $t \epsilon E$ is the tail entity, and $r \epsilon R$ represents the relationship between them, our CAB-KGC model predicts a missing tail t (represented by ?) given an incomplete triple $(h, r, ?)$.

Table 1: Mathematical Notations and Symbols

Notation	Description	Notation	Description
e	entity or node	r	relationship
h	head entity node	t	tail entity node
E	Entities Set	R	Relationships Set
H_c	Head (h) or Entity context	R_c	Relationship context
$R(h), E(h)$	relation and entities associated to head h	N_T	Total number of triplets
$p_\theta(t_i \mid h_i, r_i)$	Tail t_i probability given head h_i and relationship r_i	rank_i	Rank of the true tail entity t_i in the prediction
$\downarrow$	Results: Lower is better	$\uparrow$	Results: Higher is better

Figure 1: A concise view of the CAB-KGC Method. Box on the left shows head context H_c calculation; the middle one shows relationship context R_c calculation. H_c and R_c are then fed into the model pipeline shown on the right side.

Figure 1 provides an overview of the CAB-KGC model. It predicts the tail entity t given a head h and a relationship r, in the following steps:

1. **Extract Head Context** H_c: To extract the contextual information for the head i.e. H_c, we first identify the relationships r that are associated with the head entity h, i.e., $R(h)$. If k relationships are associated with the head h from the set R of all relationships r_i in the graph G, then:

$$\mathcal{R}(h) = A_{i=1}^{k} \left(\{r_i \mid (h, r_i, e_j) \in T, \, e_j \in E\} \right) \tag{1}$$

Next, we find the entities e that are neighbours (have a direct connection) with the head entity h, i.e., $E(h)$ using the identified relationships $R(h)$. These neighbour entities can be mathematically expressed as:

$$\mathcal{E}(h) = A_{i=1}^{m} \left(\{e_i \mid (h, r_j, e_i) \in T, \, r_j \in R\} \right) \tag{2}$$

The head context H_c is then calculated as the union of the connected relationships $R(h)$ and the neighbour entities $E(h)$, as shown below in Equation 3.

$$H_c = (\mathcal{R}(h)) \cup (\mathcal{E}(h)) \tag{3}$$

2. **Extract Relationship Context** R_c: To acquire the relationship context R_c, we identify all the entities associated with the operational relationship r in the knowledge Graph G. R_c is given as:

$$R_c = A_{i,j=1}^{l} \left(\{e_i, e_j \mid (e_i, r, e_j) \in T\} \right) \tag{4}$$

3. **Prepare Input Sequence for BERT Classifier**: The contextual information extracted in the above steps forms the input to BERT. Specifically, the input sequence contains h, H_c from Equation 3, r, and R_c from Equation 4, as shown below:

$$\text{Input Sequence} = [CLS] \, h, \, H_c \, [SEP] \, r, \, R_c \tag{5}$$

where [CLS] is BERT's classifier token and [SEP] is the separator token.

4. **Predict and train with BERT Classifier**: A classification layer is added on top of the BERT model, which aims to classify the tail entity $(h , r , ?)$. Once the BERT classifier receives the input, it processes it through various transformer layers, provides a contextualized representation of each token and uses that to classify the input. The classifier model predicts the tail entity by employing a softmax function over the output embedding to calculate the probability for all the available tail entities. The input-output description of the model is given as:

$$(\text{BERT Output}) = \text{BERT(Input Sequence)} \tag{6}$$

$$P(t \mid h, r) = \text{softmax}(W \cdot \text{BERT Output}) \tag{7}$$

where W is a learned weight matrix.

Putting above equations together, the CAB-KGC model can be expressed as:

$$\text{CAB-KGC}(t \mid h, r) = \text{softmax}(W \cdot \text{BERT}(h, H_c, r, R_c)) \tag{8}$$

The CAB-KGC model is trained using cross-entropy loss, which compares the probability distribution of the predicted label with the true label for the tail entity. The cross-entropy loss is given by:

$$L = -\sum_{i=1}^{N} y_i \log P(t_i \mid h, r) g \tag{9}$$

In this equation the one-hot encoded true label for the tail object t_i is indicated as y_i. The predicted probability for the true tail entity could be denoted as $P(t_i \mid h, r)$, where h is the head and r is the relation.

2.1 Experiments Setup

Datasets: We assessed the proposed CAB-KGC model on various commonly used KG datasets. These datasets are briefly explained here:

- FB15k-237 [23] is an updated version subset of the FB15k dataset, where the inverse triplets have been removed to increase the difficulty of the KGC. It has 14541 unique entities and 237 relationships.
- WN18RR [24] is the subset of WN18, where the reverse triplets are removed, making it more complex for the models to incorporate the problem of KGC.

99 **Hyperparameters:** The experiments used a batch size of 16 and a learning rate of 5e-5, Adam as the
100 optimizer and cross-entropy as the loss function. The experiments were accomplished on an NVIDIA
101 GeForce RTX 3090 GPU with 24 GB of memory. Training for the CAB-KGC model was halted once
102 evaluation metrics stabilized to the third decimal place.
103 **Evaluation:** Various standard evaluation metrics in KGC, as given in Equation 10, such as MRR,
104 and Hit@k, are utilized to assess the performance of the proposed method and other state-of-the-art
105 approaches

$$\text{MRR} = \frac{1}{N}\sum_{i=1}^{N}\frac{1}{\text{rank}_i} \quad ; \quad \text{Hits@k} = \frac{1}{N}\sum_{i=1}^{N}\mathbf{1}(\text{rank}_i \leq k) \tag{10}$$

106 where rank_i is the correct entity rank position in the descending order sorted list of predicted scores
107 for the i-th triplet. The function $\mathbf{1}(\text{rank}_i \leq k)$ is a ranking function that outputs one if the true entity
108 is ranked within the top k predictions and 0 otherwise.

2.2 Results

110 Our CAB-KGC approach shows superior results on the FB15k-237 dataset. CAB-KGC's significant
111 performance is its Hits@1 score of 0.322, which improves SOTA by almost 5.3%, showing a superior
112 ability to rank accurate entities in the first place. It obtains a Hits@3 score of 0.399 and improves
113 by 0.5%, notably above other models, indicating that CAB-KGC reliably predicts relevant entities
114 within the top 3 ranks. The CAB-KGC method performed well on the WN18RR dataset, getting an
115 MRR of 0.685, which is an improvement of 1.2% over SOTA models and a Hits@1 of 0.637, an
116 improvement of 4.88%, outperforming state-of-the-art methods. All the results are reported in Table
117 2. Note that we have excluded results from KICGPT[10] during comparison for reasons: (a) the
118 model is prompt-based and not trainable, (b) its performance is highly dependent on the underlying
119 LLM's knowledge base and (c) large KGs cannot be injected as prompts to this model. Furthermore,
120 injecting all relevant facts from different KGs into prompts is labor-intensive, and underlying LLM
121 will oftern struggle with domain-specific KGs when it does not contain enough relevant knowledge.

Table 2: Comparison of the proposed and baseline methods on the datasets FB15k-237 and WN18RR. The optimal outcome for each metric is highlighted in bold, while the second-best result is underlined. The circle symbol ○ denotes that the results have been extracted from the study conducted by Wei et al. [8], while the symbol □ indicates that the results have been extracted from the study conducted by Yao et al. in [3].

Dataset	FB15k-237			WN18RR		
Methods	MRR ↑	Hits@1 ↑	Hits@3 ↑	MRR ↑	Hits@1 ↑	Hits@3 ↑
Embedding-Based Methods						
RESCAL [11] ○	0.356	0.266	0.390	0.467	0.439	0.478
TransE [12] ○	0.279	0.198	0.376	0.243	0.043	0.441
DistMult [13] ○	0.241	0.155	0.263	0.430	0.390	0.440
ComplEx [14] ○	0.247	0.158	0.275	0.440	0.410	0.460
RotatE [15] ○	0.338	0.241	0.375	0.476	0.428	0.492
TuckER [16] ○	**0.358**	0.266	0.394	0.470	0.443	0.482
CompGCN [17] ○	0.355	0.264	0.390	0.479	0.443	0.494
HittER [18] ○	0.344	0.246	0.380	0.496	0.449	0.514
HAKE [19] ○	0.346	0.250	0.381	0.497	0.452	0.516
Text-and Description-Based Methods						
Pretrain-KGE [5] ○	0.332	-	-	0.235	-	-
StAR [20] ○	0.263	0.171	0.287	0.364	0.222	0.436
MEM-KGC (w/o EP) [21] ○	0.339	0.249	0.372	0.533	0.473	0.570
MEM-KGC (w/ EP) [21] ○	0.346	0.253	0.381	0.557	0.475	0.604
SimKGC [6] ○	0.333	0.246	0.363	0.671	0.585	**0.731**
NNKGC [22] ○	0.338	0.252	0.365	0.674	0.596	0.722
LLM-Based Methods						
ChatGPTzero-shot [5] □	-	0.237	-	-	0.190	-
ChatGPTone-shot [5] □	-	0.267	-	-	0.212	-
KICGPT [5] □	0.410	0.321	0.430	0.564	0.478	0.612
Proposed						
Proposed CAB-KGC	0.350	**0.322**	0.399	**0.685**	**0.637**	0.687

3 Conclusion

The proposed CAB-KGC approach exploits the contexual information to outperform existing methods in MRR and Hit@k measures, with improvements of 5.3% and 4.88% over FB15k-237 and WN18RR, respectively.

References

[1] Ding, J. and Jia, W. (2018) The research advances of knowledge graph completion algorithm. *Information and Communication Technology* **1**:56–62.

[2] Xie, R., Liu, Z., Jia, J., Luan, H., and Sun, M. (2016) Representation learning of knowledge graphs with entity descriptions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 30, No. 1.

[3] Yao, L., Mao, C., and Luo, Y. (2019) KG-BERT: BERT for Knowledge Graph Completion. *arXiv preprint* arXiv:1909.03193. Available at: https://arxiv.org/abs/1909.03193.

[4] Wei, Y., Huang, Q., Zhang, Y., and Kwok, J. (2023) KICGPT: Large Language Model with Knowledge in Context for Knowledge Graph Completion. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 8667–8683. Association for Computational Linguistics. Available at: http://dx.doi.org/10.18653/v1/2023.findings-emnlp.580.

[5] Zhang, Z., Liu, X., Zhang, Y., Su, Q., Sun, X., and He, B. (2020) Pretrain-KGE: Learning Knowledge Representation from Pretrained Language Models. In T. Cohn, Y. He, and Y. Liu (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 259–266. Association for Computational Linguistics. Available at: https://aclanthology.org/2020.findings-emnlp.25.

[6] Wang, L., Zhao, W., Wei, Z., and Liu, J. (2022) SimKGC: Simple Contrastive Knowledge Graph Completion with Pre-trained Language Models. *arXiv preprint* arXiv:2203.02167. Available at: https://arxiv.org/abs/2203.02167.

[7] Li, D., Tan, Z., Chen, T., and Liu, H. (2024) Contextualization Distillation from Large Language Model for Knowledge Graph Completion. *arXiv preprint* arXiv:2402.01729. Available at: https://arxiv.org/abs/2402.01729.

[8] Wei, Y., Huang, Q., Kwok, J.T., and Zhang, Y. (2024) Kicgpt: Large language model with knowledge in context for knowledge graph completion. *arXiv preprint* arXiv:2402.02389.

[9] Anonymous Authors. (2025) CAB-KGC: Context-Aware BERT for Knowledge Graph Completion. *Submitted to ICLR 2025 for consideration*

[10] Wei, Y., Huang, Q., Zhang, Y., and Kwok, J. (2023) KICGPT: Large language model with knowledge in context for knowledge graph completion. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 8667–8683. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.580.

[11] Nickel, M., Tresp, V., and Kriegel, H.-P. (2011) A three-way model for collective learning on multi-relational data. In *Proceedings of the 28th International Conference on Machine Learning*, pp. 809–816. Omnipress. Madison, WI, USA.

[12] Bordes, A., Usunier, N., Garcia-Duran, A., Weston, J., and Yakhnenko, O. (2013) Translating embeddings for modeling multi-relational data. In C.J. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, Vol. 26. Curran Associates, Inc.

[13] Yang, B., Yih, W.-t., He, X., Gao, J., and Deng, L. (2014) Embedding entities and relations for learning and inference in knowledge bases. In *International Conference on Learning Representations*. Available at: https://api.semanticscholar.org/CorpusID:2768038.

[14] Trouillon, T., Welbl, J., Riedel, S., Gaussier, É., and Bouchard, G. (2016) Complex embeddings for simple link prediction. *arXiv preprint* arXiv:1606.06357. Available at: https://arxiv.org/abs/1606.06357.

[15] Sun, Z., Deng, Z.-H., Nie, J.-Y., and Tang, J. (2019) RotatE: Knowledge graph embedding by relational rotation in complex space. *arXiv preprint* arXiv:1902.10197. Available at: https://arxiv.org/abs/1902.10197.

[16] Wang, Y., Broscheit, S., and Gemulla, R. (2019) A relational Tucker decomposition for multi-relational link prediction. *arXiv preprint* arXiv:1902.00898. Available at: https://arxiv.org/abs/1902.00898.

[17] Vashishth, S., Sanyal, S., Nitin, V., and Talukdar, P. (2020) Composition-based multi-relational graph convolutional networks. *arXiv preprint* arXiv:1911.03082. Available at: https://arxiv.org/abs/1911.03082.

[18] Chen, S., Liu, X., Gao, J., Jiao, J., Zhang, R., and Ji, Y. (2020) Hitter: Hierarchical transformers for knowledge graph embeddings. *arXiv preprint* arXiv:2008.12813.

[19] Zhang, Z., Cai, J., Zhang, Y., and Wang, J. (2022) Learning hierarchy-aware knowledge graph embeddings for link prediction. *arXiv preprint* arXiv:1911.09419. Available at: https://arxiv.org/abs/1911.09419.

[20] Wang, B., Shen, T., Long, G., Zhou, T., Wang, Y., and Chang, Y. (2021) Structure-augmented text representation learning for efficient knowledge graph completion. In *Proceedings of the Web Conference 2021*, pp. 1737–1748.

[21] Choi, B., Jang, D., and Ko, Y. (2021) MEM-KGC: Masked entity model for knowledge graph completion with pre-trained language model. *IEEE Access* **9**, 132025-132032. Available at: https://api.semanticscholar.org/CorpusID:238243180.

[22] Li, I., and Yang, B. (2023) NNKGC: Improving knowledge graph completion with node neighborhoods. *arXiv preprint* arXiv:2302.06132. Available at: https://arxiv.org/abs/2302.06132.

[23] Bollacker, K., Evans, C., Paritosh, P., Sturge, T., and Taylor, J. (2008) Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD International Conference on Management of Data*, pp. 1247–1250.

[24] Miller, G. A. (1995) WordNet: a lexical database for English. *Communications of the ACM* **38**(11):39–41.