A Survey of Flow Matching in Reinforcement Learning

Abstract

Flow Matching (FM) has recently emerged as a principled and efficient generative modeling framework for reinforcement learning (RL), enabling expressive, multimodal policy parameterizations via deterministic probability transport. Compared to diffusion-based policies that rely on stochastic denoising chains, FM uses sampling based on ordinary differential equations (ODEs), with learned velocity fields, which can substantially reduce inference latency and simplify the incorporation of RL objectives. As research in flow-based RL rapidly accelerates across offline continuous control, online fine-tuning, and foundation model alignment, the literature has become highly fragmented. In this survey, we provide the a comprehensive taxonomy of flow-matching approaches in reinforcement learning. We organize the literature along two axes: the target distribution being modeled (e.g., action policies, value critics, transition dynamics) and the mechanism of RL signal integration (e.g., energy-weighted regression, flow-based policy gradients, and group relative policy optimization). Furthermore, we survey emerging frontiers such as discrete and non-Euclidean action spaces, provide a systematic comparative analysis against Gaussian and diffusion baselines, and outline critical open problems. Ultimately, this survey serves as a foundational roadmap for the next generation of generative reinforcement learning and alignment.

1 Introduction

Flow Matching (FM) and related continuous-time flow models (Lipman et al., 2023; Liu, 2022) have recently emerged as a promising framework for training expressive generative models. Unlike diffusion models (Ho et al., 2020; Song et al., 2021), which learn to reverse stochastic noise processes, flow matching directly learns deterministic vector fields that transport samples from a simple base distribution to a target distribution via ordinary differential equations (ODEs). This formulation converts generative modeling into a supervised regression problem on velocity fields, often simplifying training and enabling efficient sampling with relatively few ODE solver steps. These properties make flow-based models particularly attractive for reinforcement learning (RL), where policies must be both expressive and computationally efficient.

As a result, a rapidly growing literature has begun to explore flow matching based approaches for reinforcement learning from several complementary perspectives. A first line of work studies *flow-based policy learning*, especially in offline RL, where flow policies are trained either by energy or value guided regression toward high return actions (Zhang et al., 2025b; Alles et al., 2025; Zhang et al., 2025a), by combining pretrained flow priors with Q-learning based policy improvement (Park et al., 2025), or by improving efficiency through single-step completion or structural support constraints (Koirala & Fleming, 2025; Zhang et al., 2026). A second line of work considers *online optimization of flow policies*, including likelihood or reward weighted fine tuning (Fan et al., 2025b; Zhang et al., 2025c), direct policy gradient based optimization through the flow ODE (McAllister et al., 2025; Pfrommer et al., 2025; Yang et al., 2026), and more recent group-relative optimization methods for large scale generative flow models (Liu et al., 2025a; He et al., 2025; Yu et al., 2026; Chen et al., 2025b). Beyond action policies, recent studies have also used flow matching to model *critics*, *dynamics*, *preferences*, and *multi-agent joint behaviors*, broadening the role of FM in RL beyond policy representation alone (Agrawalla et al., 2025; Kong et al., 2025; Kim et al., 2024; Zhu et al., 2025; Lee et al., 2025a). Together, these works show that flow matching is developing into a general RL toolkit that spans offline policy learning, online fine tuning, alignment, and structured decision making. While these

individual contributions are significant, the field currently lacks a systematic overview, making it challenging for researchers to connect core algorithmic principles and form a coherent picture of the landscape.

To address this gap, we present a focused survey of flow matching approaches in reinforcement learning. We synthesize a fragmented literature into a cohesive framework, highlighting how diverse methods are connected through policy optimization via deterministic vector fields and clarifying where and how they fundamentally differ. Our goal is to provide a clear understanding of how flow matching is used in RL, how it differs from diffusion based approaches, and where it provides practical and theoretical advantages for policy learning.

1.1 Motivation

A major motivation for integrating generative models into reinforcement learning is the representational limitation of traditional policy parameterizations. In many continuous-control settings, standard RL algorithms parameterize stochastic policies as diagonal Gaussian distributions (Sutton & Barto, 2018). Formally, such policies take the form $\pi_\theta(a|s) = \mathcal{N}(a; \mu_\theta(s), \Sigma_\theta(s))$, where $\mu_\theta(s)$ is the mean action predicted by a neural network and the covariance matrix is constrained to be diagonal, i.e., $\Sigma_\theta(s) = \mathrm{diag}(\sigma^2(s))$.

This diagonal structure implies conditional independence between action dimensions, meaning the policy factorizes into independent one-dimensional Gaussians across each action component. As a result, the policy can only represent a single unimodal distribution centered around $\mu_\theta(s)$.

While this parameterization is computationally convenient and widely used in actor-critic algorithms such as PPO (Schulman et al., 2017) and SAC (Haarnoja et al., 2018), since it is inherently unimodal, it is limited in its ability to represent diverse behaviors. When multiple distinct actions are valid such as navigating either left or right around an obstacle a unimodal policy tends to average across these modes, assigning high probability to intermediate actions that may be unsafe or suboptimal. This phenomenon, often referred to as *mode averaging*, becomes particularly problematic in offline RL and imitation learning settings where datasets may contain multiple valid strategies.

To address this limitation, recent work has explored generative models as expressive policy representations. In particular, diffusion models (Ho et al., 2020; Song et al., 2021) have demonstrated strong empirical performance in offline RL and planning tasks (Janner et al., 2022; Wang et al., 2023). Diffusion-based policies generate actions by iteratively denoising a noisy sample through a sequence of reverse diffusion steps.

However, diffusion models typically require tens or hundreds of iterative denoising steps to produce a single action sample, which introduces significant inference latency. For instance, diffusion-based control policies often require 20–100 neural network evaluations per action (Janner et al., 2022; Wang et al., 2023), compared with a single forward pass for conventional policies. This computational cost can make diffusion models impractical for real-time control tasks such as robotics, where actions must be generated at high frequency.

These limitations motivate the search for more efficient generative policy classes that retain the expressive power of diffusion models while enabling faster inference. Flow matching (Lipman et al., 2023; Liu, 2022) provides one such alternative by replacing stochastic diffusion trajectories with deterministic probability flows. While diffusion models in RL have been the subject of several recent surveys (Zhu et al., 2024; Xu et al., 2025), Flow Matching (FM) in RL represents a distinct mathematical paradigm, rooted in deterministic Optimal Transport (Villani et al., 2009; Peyré & Cuturi, 2019; Lipman et al., 2023) and Ordinary Differential Equations (ODEs), that needs its own dedicated treatment.

The motivation for this survey is threefold:

1. **Algorithmic Distinctiveness:** Unlike diffusion models, which rely on stochastic differential equations (SDEs) and iterative denoising, flow matching operates via deterministic vector field regression. This difference necessitates unique considerations for training stability, inference efficiency, and integration with RL objectives (e.g., Q-learning or Policy Gradients) that are not covered in existing diffusion literature.

2. **Rapid but Fragmented Growth:** As noted, the application of flow matching to control tasks has grown rapidly across disparate subfields. Researchers in offline RL often frame FM as a supervised regression problem, while those in online RL view it as a policy parameterization for actor-critic methods. This survey aims to bridge these communities.

3. **Practical Efficiency:** For real-world robotics and control, the inference speed of generative policies is a critical bottleneck. Flow matching offers a uniquely direct path to acceleration (via ODE solvers and straight flow lines), making it a particularly high-impact area for applied RL researchers.

1.2 Positioning Relative to Existing Surveys

While several recent reviews have examined the intersection of generative modeling and reinforcement learning, none provide a focused and unified analysis of the emerging *flow-matching in reinforcement learning paradigm*. This survey addresses this gap by distinguishing flow-based policies from broader diffusion methods and highlighting their unique theoretical and preactical advantages.

Relation to Diffusion RL Surveys. Foundational surveys such as Zhu et al. (2024) and Xu et al. (2025) establish valuable taxonomies for diffusion-based RL analyzing stochastic diffusion processes (SDEs) and iterative denoising and also categorizing flow matching as an efficient sampling subroutine. We instead provide a detailed look at flow matching in RL from the *deterministic vector-field perspective* that simplifies policy regression and enables direct optimal transport connections.

Relation to Efficient Generative Modeling. Surveys on efficient diffusion models (Shen et al., 2025; Ma et al., 2025) focus on accelerating inference via architectural optimizations and fast solvers. We focus on reinforcement learning objectives, offering insights into how flow trajectories can be guided by value functions or shaped by Bellman updates.

Relation to RL for Generative AI. Finally, reviews on reinforcement learning for generative AI (Cao et al., 2025; Franceschelli & Musolesi, 2024) emphasize RL as a tool for *aligning* pre-trained models (e.g., RLHF). In contrast, this survey centers on flow matching as a *primary policy learning framework*, where the generative model itself acts as the decision-making agent in sequential control tasks.

Scope and Organization of this Survey. This paper focuses specifically on *Continuous Normalizing Flows* and *Flow Matching* approaches applied to sequential decision-making problems, unfolding the literature as a continuous narrative. We begin in Section 2 by establishing the **theoretical foundations**, providing a self-contained introduction to flow matching and its geometric roots in Optimal Transport, explicitly contrasting this deterministic perspective with stochastic diffusion models. Building on this theory, we introduce a **unified taxonomy** in Section 3 to organize the landscape before diving into specific algorithmic paradigms. Section 4 explores the realm of **offline learning**, reviewing how flow matching is utilized for behavioral cloning and offline RL through sophisticated value-guided weighting techniques. The narrative then transitions to **online adaptation** in Section 5, where we examine how agents fine-tune flow policies via active environment interaction, often by backpropagating policy gradients directly through ODE solvers. Finally, Section 6 broadens the scope beyond immediate action selection, discussing the use of flows for **modeling environment dynamics and generating full trajectories** for model-based planning. Ultimately, the goal of this survey is to provide both a theoretical primer for newcomers and a practical guide for researchers looking to implement or extend flow-based algorithms in reinforcement learning.

2 Background

This section provides the necessary background and notations in reinforcement learning, diffusion models, and flow-matching generative modeling.

2.1 Reinforcement Learning Preliminaries

We consider the standard reinforcement learning (RL) framework (Sutton & Barto, 2018). A Markov decision process (MDP) is defined by the tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, r, \gamma)$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, $P(s'|s, a)$ is the transition dynamics, $r(s, a)$ is the reward function, and $\gamma \in (0, 1)$ is the discount factor.

A policy $\pi(a|s)$ induces a distribution over trajectories $\tau = (s_0, a_0, s_1, a_1, \dots)$. The discounted return of a trajectory is

$$G(\tau) = \sum_{t=0}^{\infty} \gamma^t r(s_t, a_t). \tag{1}$$

The associated value and action-value functions are defined as:

$$V^\pi(s) = \mathbb{E}_\pi \left[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t) \,\middle|\, s_0 = s \right], \tag{2}$$

$$Q^\pi(s, a) = r(s, a) + \gamma \, \mathbb{E}_{s' \sim P(s'|s,a)}[V^\pi(s')]. \tag{3}$$

Online Reinforcement Learning. In the online setting, the agent interacts with the environment to collect trajectories and iteratively improve its policy. The objective is to maximize the expected discounted return:

$$J(\pi) = \mathbb{E}_{\tau \sim \pi}[G(\tau)]. \tag{4}$$

A standard route to optimize this objective is via *policy gradient* methods, which update a parameterized policy $\pi_\phi(a|s)$ in the direction

$$\nabla_\phi J(\pi_\phi) = \mathbb{E}_{(s,a) \sim \pi_\phi} \big[\nabla_\phi \log \pi_\phi(a|s) \, \hat{A}(s, a) \big], \tag{5}$$

where $\hat{A}(s, a)$ is an estimator of the *advantage*, measuring how much better action a is than the policy's baseline behavior at state s.

Proximal Policy Optimization (PPO). Among on-policy algorithms, Proximal Policy Optimization (PPO) (Schulman et al., 2017) is particularly important because it will reappear repeatedly in later sections on online flow-based RL. PPO improves stability by replacing the vanilla policy gradient objective with a clipped surrogate objective:

$$\mathcal{L}_{\text{PPO}}(\phi) = \mathbb{E} \left[\min\left(r_t(\phi) \hat{A}_t, \ \text{clip}(r_t(\phi), 1 - \epsilon, 1 + \epsilon) \hat{A}_t \right) \right], \tag{6}$$

where

$$r_t(\phi) = \frac{\pi_\phi(a_t|s_t)}{\pi_{\phi_{\text{old}}}(a_t|s_t)}$$

is the importance ratio between the current and previous policies, and ϵ is a small trust-region parameter. Intuitively, PPO prevents overly large policy updates by clipping the incentive to increase or decrease action probability too aggressively. This makes PPO a natural baseline when adapting expressive generative policies, including flow-matching policies, to online RL.

Group Relative Policy Optimization (GRPO). A more recent variant, Group Relative Policy Optimization (GRPO) (Shao et al., 2024), replaces the explicit value-function baseline with a *group-relative* advantage estimate. Instead of learning a separate critic, GRPO samples a group of candidate actions or outputs $\{a_i\}_{i=1}^G$ for the same context or state and computes a normalized relative advantage:

$$\hat{A}_i = \frac{R_i - \text{mean}(\{R_j\}_{j=1}^G)}{\text{std}(\{R_j\}_{j=1}^G)}, \tag{7}$$

where R_i is the reward assigned to the i-th sample. The policy is then updated using a PPO-style clipped objective, but with these group-normalized advantages instead of critic-based estimates. In other words,

GRPO is a *critic-free* relative-ranking variant of policy optimization: it encourages the policy to increase the probability of samples that are better than their group average and decrease the probability of worse ones. This idea has become especially influential in fine-tuning large generative models, and several flow-based online RL methods surveyed later adopt GRPO-style updates.

Remarks for Flow-Based Policies. When the policy π_ϕ is parameterized by a flow model, evaluating $\log \pi_\phi(a|s)$ or the likelihood ratio $r_t(\phi)$ in equation 6 can be substantially more difficult than for Gaussian policies. This is because the policy is defined implicitly through an ODE or continuous normalizing flow, often requiring either differentiation through the ODE solver, likelihood approximations, or alternative surrogate objectives (Chen et al., 2018). Much of the online flow-RL literature can be understood precisely as designing tractable PPO or GRPO-style updates for these expressive but computationally challenging policy classes.

Offline Reinforcement Learning. In offline RL (Levine et al., 2020), the agent learns from a fixed dataset $\mathcal{D} = \{(s, a, r, s')\}$ collected by a behavior policy $\mu(a|s)$, without further interaction. Policy improvement is often formulated as a constrained optimization problem, maximizing Q-values while penalizing deviation from the behavior policy μ:

$$\max_\pi \ \mathbb{E}_{s \sim \mathcal{D}} \left[\mathbb{E}_{a \sim \pi(\cdot|s)} [\, Q(s,a) \,] - \frac{1}{\beta} \, \mathrm{KL}(\pi(\cdot|s) \,\|\, \mu(\cdot|s)) \right]. \tag{8}$$

The closed-form solution is the energy-based policy $\pi^\star(a|s) \propto \mu(a|s) \exp(\beta Q(s,a))$, which forms the basis for many generative RL methods. This solution assumes access to the true Q-function and serves as an idealized target for generative policy learning.

2.2 Diffusion Models in Reinforcement Learning

Diffusion models (Ho et al., 2020; Song et al., 2021) generate data by learning to reverse a gradual noising process. During training, a forward process progressively corrupts data samples into noise, and a neural network is trained to reverse this process by predicting either the added noise or the score (the gradient of the log-density). At inference time, generation proceeds by iteratively denoising a random noise sample through many small steps, typically formulated as either a discrete reverse chain or a stochastic differential equation (SDE).

Diffusion models (DMs) have become a major paradigm for reinforcement learning because they can represent rich, multi-modal conditional distributions over *actions*, *action sequences*, and even *future trajectories*. These models address the central limitation of unimodal Gaussian policies: the inability to capture diverse, valid behaviors in offline datasets or complex control tasks.

In diffusion-based RL, decision making is implemented by an iterative denoising process that gradually transforms noise into an action (policy view) or an action sequence/trajectory (planning view). Based on recent related survey papers (Zhu et al., 2024; Xu et al., 2025), we provide a categorization of how diffusion models are integrated into RL in Appendix A.

While diffusion policies have achieved strong, and in some cases state of the art performance in offline RL, they remain challenging for control because high-quality generation typically requires tens or hundreds of iterative denoising steps per action, leading to substantial inference latency that can be prohibitive for real-time decision making (Wang et al., 2023; Hansen-Estruch et al., 2023). In addition, the reverse denoising process follows a stochastic trajectory in data space, which can make temporal consistency, controllability, and value-based optimization more difficult.

2.3 Flow Matching

Flow Matching (FM) (Lipman et al., 2023; Liu, 2022) provides a principled and computationally efficient framework for training Continuous Normalizing Flows (CNFs) (Chen et al., 2018), which model probability transport using ordinary differential equations.. Unlike diffusion models, which learn to reverse a stochastic noising process, FM directly learns a deterministic transport map between a simple base distribution and a complex target distribution.

Figure 1: **Flow Matching in a nutshell.** *Top:* flow matching learns approximately straight probability transport from a simple base distribution to the target data distribution. *Bottom left:* training is simulation-free: one samples (x_0, x_1, t), constructs an interpolation point x_t, and regresses the learned velocity field $v_\theta(x_t, t)$ toward the target conditional velocity u_t. For the common linear optimal-transport path, the target velocity is simply $x_1 - x_0$. *Bottom right:* after training, new samples are generated by integrating the learned ODE from base noise to the target distribution.

Figure 1 provides a visual summary of this idea. At a high level, flow matching learns a velocity field that transports samples from a simple base distribution to the target distribution through approximately straight probability paths, while keeping training simulation-free and ODE integration is done for inference.

Simulation-free training. A key advantage of flow matching is that training is *simulation-free*, meaning that it does not require solving the ODE defined by the model during optimization. Instead, the training objective is formulated as a supervised regression problem on sampled interpolation points (x_0, x_1, t), where the model directly learns the target velocity field. This contrasts with likelihood-based training of continuous normalizing flows or diffusion models, which typically require simulating the forward or reverse process during training.

Continuous Normalizing Flows. Let $p_0(x)$ denote a simple base distribution (typically a standard multivariate Gaussian normal distribution $\mathcal{N}(0, I)$ with mean 0 and identity covariance I) and $p_1(x)$ the target data distribution. A continuous normalizing flow defines a time-dependent transformation x_t governed by an ordinary differential equation (ODE):

$$\frac{dx_t}{dt} = v_\theta(x_t, t), \qquad x_0 \sim p_0, \tag{9}$$

where $v_\theta(x, t)$ is a neural network parameterizing a velocity field. Solving this ODE from $t = 0$ to $t = 1$ transports samples from p_0 to a learned distribution p_1^θ.

Under mild regularity conditions, the induced density $p_t(x)$ evolves according to the continuity equation:

$$\frac{\partial p_t(x)}{\partial t} + \nabla \cdot \big(p_t(x) v_\theta(x, t)\big) = 0, \tag{10}$$

Algorithm 1 Conditional Flow Matching (CFM) / Rectified Flow (OT path) training

---

1: **Input:** dataset distribution $p_1(x)$, base distribution $p_0(x)$ (e.g., $\mathcal{N}(0, I)$), stepsize η
2: **Initialize:** velocity network $v_\theta(x, t)$
3: **while** not converged **do**
4:     Sample $x_1 \sim p_1(x)$ and $x_0 \sim p_0(x)$
5:     Sample $t \sim \text{Unif}[0, 1]$
6:     **(OT / Rectified path)** set $x_t \leftarrow (1 - t)x_0 + tx_1$
7:     **Target velocity** $u_t \leftarrow x_1 - x_0$ ▷ constant along the linear path
8:     Update $\theta \leftarrow \theta - \eta \nabla_\theta \|v_\theta(x_t, t) - u_t\|_2^2$
9: **end while**
10: **Output:** learned velocity field $v_\theta(x, t)$

---

ensuring conservation of probability mass along the flow.

The Challenge of CNF Training. Directly training CNFs via maximum likelihood requires solving the ODE and computing log-determinants through the instantaneous change-of-variables formula (Chen et al., 2018), which is computationally expensive and unstable in high dimensions. Flow Matching circumvents this by converting density learning into a supervised regression problem on vector fields.

Probability Paths and Conditional Flow Matching. The key idea in flow matching is to define a family of intermediate distributions $\{p_t(x)\}_{t \in [0,1]}$ that smoothly interpolate between p_0 and p_1. Instead of learning the marginal velocity field directly, we define a *conditional probability path* $p_t(x \mid x_1)$ connecting noise to an individual data point $x_1 \sim p_1$.

Let $\psi_t(x_0, x_1)$ denote a deterministic interpolation between $x_0 \sim p_0$ and $x_1 \sim p_1$. The marginal path is:

$$p_t(x) = \int p_t(x \mid x_1) \, p_1(x_1) \, dx_1.$$

The conditional velocity field associated with this path is:

$$u_t(x \mid x_1) = \frac{d}{dt} \psi_t(x_0, x_1) \Big|_{x = \psi_t(x_0, x_1)}.$$

Flow Matching trains v_θ to match this conditional velocity in expectation:

$$\mathcal{L}_{\text{CFM}}(\theta) = \mathbb{E}_{\substack{t \sim \text{Unif}[0,1], \\ x_0 \sim p_0, \\ x_1 \sim p_1}} \left[\left\| v_\theta(\psi_t(x_0, x_1), t) - u_t(\psi_t(x_0, x_1) \mid x_1) \right\|^2 \right]. \tag{11}$$

Crucially, this objective does *not* require solving the ODE during training. It only requires sampling (x_0, x_1, t) and performing standard regression. Lipman et al. (2023) prove that minimizing this objective yields a velocity field whose induced marginal flow matches p_1 exactly under ideal optimization. As illustrated in Figure 1, the training pipeline samples (x_0, x_1, t), constructs an interpolation point x_t, and regresses the learned velocity toward the target conditional velocity, rather than solving the full ODE during optimization. Training is *simulation-free* meaning that equation 11 can be evaluated using only samples (x_0, x_1, t) without integrating the ODE, turning density learning into a standard regression problem.

Optimal Transport and Rectified Flows. A particularly important choice which is adopted in nearly all RL applications is the linear (optimal transport) interpolation:

$$\psi_t(x_0, x_1) = (1 - t)x_0 + tx_1.$$

In this case, the conditional velocity is constant:

$$u_t(x \mid x_1) = x_1 - x_0.$$

This choice corresponds to learning straight-line transport between noise and data and is closely related to the Rectified Flow framework (Liu et al., 2023). Rectified flows can be interpreted as learning a marginal-preserving transport that minimizes path curvature, resulting in nearly straight trajectories. This geometric property is one of the main reasons flow models admit accurate low-step ODE solvers during inference.

Inference. After training, sampling proceeds by solving the learned ODE:

$$\frac{dx_t}{dt} = v_\theta(x_t, t), \qquad x_0 \sim p_0, \tag{12}$$

using a numerical solver (e.g., Euler or Runge-Kutta). Because the learned paths are approximately straight, accurate sampling is often possible with as few as 1–5 function evaluations which is a major advantage over diffusion models, which require tens or hundreds of denoising steps.

Algorithm 2 Sampling with a trained flow (ODE integration)

1: **Input:** learned velocity $v_\theta(\cdot, \cdot)$, base distribution p_0, number of steps K
2: Sample $x_0 \sim p_0$
3: Discretize $0 = t_0 < t_1 < \cdots < t_K = 1$ with $\Delta t_k = t_{k+1} - t_k$
4: **for** $k = 0, 1, \ldots, K-1$ **do**
5: $\quad x_{t_{k+1}} \leftarrow x_{t_k} + \Delta t_k \, v_\theta(x_{t_k}, t_k)$ $\qquad\qquad\qquad\qquad$ ▷ Euler or RK methods can be used
6: **end for**
7: **Return:** $x_1 \approx x_{t_K}$

Conditional Flow Matching forms the mathematical backbone of nearly all flow-based RL methods surveyed in this paper, including energy-weighted offline methods, ODE-differentiated policy gradients, and GRPO-style fine-tuning approaches.

2.4 High-level summary of methods for FM on RL

To use flow matching for control, we need to bridge the gap between *likelihood maximization* (learning to generate realistic samples from data) and *reward maximization* (learning to generate actions that achieve high return). At a high level, the existing literature can be organized into two broad families, depending on *where* the reinforcement learning signal enters the flow model. This high-level organization is summarized in Figure 2. The central distinction is whether the RL signal enters the flow model at *training time*, as in offline value or reward weighted regression, or at *policy-update time*, as in online fine-tuning through policy gradients, stochasticized flows, or GRPO-style updates.

1. Training-Time Guidance (Weighted Regression). Predominant in **Offline RL**, where one learns from a fixed dataset, this approach embeds the RL objective into the generative training loss. Starting from the KL-regularized offline RL objective in equation 8, the corresponding optimal policy can be written explicitly as

$$\pi^\star(a|s) = \frac{\mu(a|s) \exp(\beta Q(s, a))}{\int \mu(a'|s) \exp(\beta Q(s, a')) \, da'},$$

where the denominator is a normalization constant ensuring that $\pi^\star(\cdot|s)$ integrates to one. Hence the closed-form solution is $\pi^\star(a|s) \propto \mu(a|s) \exp(\beta Q(s, a))$ where $\mu(a|s)$ is the behavior policy. Relative to this behavior distribution, actions with larger $Q(s, a)$ values (high-value actions) are exponentially upweighted.

Flow-based offline RL methods use this principle to modify the conditional flow-matching objective so that the learned velocity field preferentially transports noise toward high-value regions of the action space. A generic form is

$$\mathcal{L}_{\text{Weighted-FM}}(\theta) = \mathbb{E}_{(s,a) \sim \mathcal{D}, \, t \sim \text{Unif}[0,1]} \left[w(s, a) \left\| v_\theta(x_t, s, t) - u_t(x_t|a, s) \right\|^2 \right], \tag{13}$$

Figure 2: **How flow matching is integrated with reinforcement learning.** A common flow-policy backbone defines an expressive action generator through a learned velocity field and ODE sampler. In *offline RL*, the reinforcement signal typically enters at *training time*, most often by reweighting the flow-matching objective using value or energy estimates. In *online RL*, the signal enters through *policy optimization* using environment interaction, typically via stochasticized flows, pathwise gradients through the ODE, or group-based updates such as GRPO. Across both settings, additional stabilizers such as KL regularization, Wasserstein anchoring, clipping, and support constraints are often used.

where u_t is the target conditional velocity field and the weight function $w(s, a)$ is typically chosen to increase with $Q(s, a)$ or an advantage estimate. Representative examples include Energy-Weighted Flow Matching (EFM / QIPO), which derives a principled Q-guided flow objective (Zhang et al., 2025b), FlowQ, which reformulates energy guidance through analytically tractable path constructions (Alles et al., 2025), and Flow Q-Learning (FQL), which combines a flow prior with a separate policy-improvement stage (Park et al., 2025). We discuss this family of approaches in detail in Section 4.

2. Sampling-Time Guidance (Policy Gradients). Predominant in **Online RL**, this approach keeps the generative model fixed (or pre-trained) and biases the sampling process. In diffusion, this is often done via classifier guidance $\nabla_x Q(s, x)$. In flow matching, one can differentiate the Q-value with respect to the generated action and backpropagate gradients through the ODE solver to update the flow parameters θ directly.

In online RL, where the flow model acts directly as the policy and is updated through interaction with the environment, the key question is how to optimize a flow-defined policy under policy-gradient style objectives despite the fact that actions are generated implicitly by integrating an ODE.

At a conceptual level, if the generated action is written as

$$a = \Phi_\theta(z, s), \qquad z \sim p_0,$$

where Φ_θ denotes the solution map of the flow ODE

$$\frac{dx_t}{dt} = v_\theta(x_t, s, t), \qquad x_0 = z,$$

and the generated action corresponds to the terminal state $a = x_1$. Therefore Φ_θ denotes the ODE solution map induced by the learned velocity field, then the policy objective can be differentiated through the sampling procedure:

$$\nabla_\theta J(\pi_\theta) = \mathbb{E}_{z \sim p_0} \left[\nabla_a Q(s, a) \frac{\partial \Phi_\theta(z, s)}{\partial \theta} \right]. \tag{14}$$

In practice, existing methods make this idea tractable in different ways: some inject noise into the flow dynamics so that standard likelihood-based methods such as PPO can be used (Zhang et al., 2025c); some backpropagate policy gradients directly through the ODE solver or use flow-matching losses as PPO-compatible surrogates (McAllister et al., 2025; Pfrommer et al., 2025; Yang et al., 2026); and others adopt group-based online optimization strategies such as GRPO-style updates (Liu et al., 2025a; He et al., 2025; Yu et al., 2026; Chen et al., 2025b; Sun et al., 2025). We discuss this family of approaches in detail in Section 5.

Summary. Flow matching occupies a unique position among generative policy classes: it combines the expressiveness of diffusion models with deterministic sampling paths, enabling both efficient inference and stable optimization. In offline RL, this allows reward-weighted regression objectives that avoid backpropagation through long sampling chains. In online RL, deterministic ODEs permit direct differentiation through the policy with reduced variance compared to stochastic diffusion trajectories. These properties make flow matching a natural bridge between classical RL objectives and modern generative modeling. Figure 2 also highlights that, despite their differences, both offline and online flow-based RL methods share the same flow-policy backbone and often rely on related stabilizers such as KL regularization, Wasserstein anchoring, clipping, or support constraints.

3 A Taxonomy of Flow Matching in Reinforcement Learning

Flow matching has rapidly emerged as a principled alternative to diffusion models for decision-making. Unlike diffusion, which relies on stochastic denoising, flow matching learns deterministic transport maps defined by velocity fields (Lipman et al., 2023; Liu, 2022). In RL, this enables efficient sampling, stable differentiation, and direct integration with value-based objectives.

To organize the rapidly growing literature, we propose a taxonomy based on two orthogonal design axes:

1. **What distribution is modeled?** (Actions, Critics, Dynamics, or Preferences).

2. **Where does the RL signal enter?** (Training-time regression, Online gradients, or Fine-tuning).

Figure 3 visualizes this landscape, categorizing the methods discussed in this survey.

Taxonomy of Flow-Based RL Methods. Throughout this survey, we organize the literature along two complementary axes. Sections 4 and 5 categorize methods according to the *learning setting* in which the flow policy is optimized (offline versus online reinforcement learning). Section 6, in contrast, broadens the perspective to consider *what object is modeled by the flow*, including critics, environment dynamics, and preference alignment objectives. This two-axis organization allows us to highlight both the algorithmic differences between offline and online learning as well as the expanding role of flow matching beyond policy parameterization.

Figure 3: **A Taxonomy of Flow Matching in Reinforcement Learning.** We categorize methods by their primary function: Offline Policy Learning (Section 4), Online Policy Optimization (Section 5), and Applications Beyond Policy Learning (Section 6).

3.1 Axis A: What Distribution is Modeled?

Action (Policy) Flows. The most common application is modeling conditional action distributions $\pi(a|s)$. The flow maps a base distribution (e.g., Gaussian noise) to multimodal actions. This paradigm underlies both offline methods like *FlowQ* (Alles et al., 2025) and *Flow Q-Learning* (Park et al., 2025), as well as online methods like *Flow-Based Policy* (Lv et al., 2025). Recent works such as *SSCP* (Koirala & Fleming, 2025) focus on making these action flows efficient via single-step completion.

Multi-Agent Joint Distributions. Extending beyond single agents, flow matching can model the complex joint action distributions of multiple interacting agents. *MAC-Flow* (Lee et al., 2025a) learns a centralized flow-based representation of joint behaviors from offline data, which is then distilled into decentralized one-step policies for fast, independent execution.

Critic Flows. A radical departure from standard RL is modeling the *Q-function itself* as a flow. *floq* (Agrawalla et al., 2025) trains a flow to represent the distribution of returns, allowing for "test-time compute" scaling in value estimation; running the critic flow longer yields more precise value estimates.

Dynamics and Transition Flows. Instead of policies, flow matching can model environment transitions $P(s'|s,a)$. *Composite Flow Matching (CompFlow)* (Kong et al., 2025) uses this to estimate the "dynamics gap" between source and target environments, enabling principled transfer learning under shifted dynamics.

Preference and Reasoning Flows. In alignment tasks, flows model the distribution of "preferred" outputs (e.g., reasoning chains or speech). *FlowRL* (Zhu et al., 2025) and *F5R-TTS* (Sun et al., 2025) use flows to balance diversity and reward maximization in LLMs and Text-to-Speech, respectively.

3.2 Axis B: Where Does the RL Signal Enter?

Training-Time Weighted Regression (Offline). In offline RL, the signal enters via static dataset weighting. Here the optimal policy is interpreted as an energy-based distribution $\pi^\star \propto \mu e^{\beta Q}$. Methods like *QIPO/EFM* (Zhang et al., 2025b) and *ARFM* (Zhang et al., 2025a) weight the flow matching regression loss by the exponential advantage, tilting the flow toward high-value regions without backpropagation through the ODE.

Online Gradients and Fine-Tuning. In online settings, the signal enters via interaction. *ReinFlow* (Zhang et al., 2025c) injects noise to enable likelihood-based updates. Conversely, *FMPG* (McAllister et al., 2025) exploits the differentiability of the ODE solver to backpropagate policy gradients directly through the flow trajectory.

Group Relative Policy Optimization (GRPO). The newest trend avoids both regression and direct backprop. The *GRPO family* including *Flow-GRPO* (Liu et al., 2025a), *TempFlow* (He et al., 2025), *Smart-GRPO* (Yu et al., 2026), and *SuperFlow* (Chen et al., 2025b) samples groups of trajectories and updates the flow to increase the likelihood of the best samples relative to the group average. This has become the dominant paradigm for fine-tuning large-scale generative flow models.

4 Offline RL with Q/Energy-Guided Flow Policies

Offline reinforcement learning learns a policy from a fixed dataset $\mathcal{D} = \{(s, a, r, s')\}$ without further interaction, which makes *distributional shift* the central challenge: if a learned policy proposes actions outside the dataset support (out-of-distribution (OOD) actions), value learning (the learned Q-function) may extrapolate inaccurately, leading to severe overestimation errors. Recent work successfully integrates flow matching into offline RL to simultaneously model highly expressive, multi-modal behavior distributions while safely incorporating value-based policy improvement. The unifying principle across these methods is to learn a generative flow policy whose target distribution is an *energy-reweighted* version of the behavior distribution. These methods can be viewed as special cases of the general guided-flow framework introduced by Feng et al. (2025a), which interprets value guidance as a modification of the flow velocity field which we detail in Section 6.4.

4.1 Regularized Policy Optimization as an Energy-Weighted Target

To prevent OOD actions, many offline RL algorithms constrain the learned policy π to remain close to the behavior policy π_β using a Kullback-Leibler (KL) divergence penalty. KL-regularized offline RL defines an ideal policy improvement target as an energy-reweighted behavior distribution. A common way to formalize "stay close to data while improving" is the following regularized optimization problem:

$$\max_\pi \ \mathbb{E}_{s \sim \mathcal{D}} \left[\mathbb{E}_{a \sim \pi}[Q(s, a)] - \frac{1}{\beta} D_{\mathrm{KL}} \big(\pi(\cdot|s) \, \| \, \pi_\beta(\cdot|s) \big) \right],$$

where $\beta > 0$ acts as an inverse temperature parameter controlling the strength of the behavioral penalty. The closed-form optimal solution to this objective (when Q and π_β are known) is an *energy-weighted distribution*:

$$\pi^*(a|s) = \frac{\pi_\beta(a|s) \exp(\beta Q(s, a))}{Z(s)}, \tag{15}$$

where $Z(s)$ is the intractable partition function (normalizing constant). While this formulation is theoretically nice, direct sampling from $\pi^*(a|s)$ is not possible because the true density π_β is unknown (only accessible through samples, not density evaluation), and the partition function cannot be efficiently computed in continuous action spaces.

Flow matching provides a simulation-free generative framework to directly approximate and sample from this optimal energy-weighted distribution by making use of equation 15 through learning a transport map that can sample from the reweighted target without evaluating partition functions; equation 15 which can be read as an *energy-based* distribution with energy $E(s,a) = -Q(s,a)$ provides a clean "north star" for generative policy learning, because the role of the generative model becomes *sampling from an energy-reweighted dataset distribution* rather than directly optimizing a conventional actor network.

Flow-based offline RL therefore proceeds in two conceptual steps: first learn a high-capacity conditional flow that models the behavior support (a strong π_β surrogate), and then incorporate the energy term $\exp(\beta Q)$ to tilt the learned generative process toward higher-value actions. The remainder of this section can be read as a sequence of increasingly careful answers to the same question: *how should Q enter the flow training/inference so that improvement happens, but OOD actions do not?*

4.2 Energy-Weighted Flow Matching (EFM / QIPO)

Energy-Weighted Flow Matching (EFM) (Zhang et al., 2025b), also referred to as Q-guided Iterative Policy Optimization (QIPO), formalizes the problem of learning a flow from a source noise distribution $p_0(a|s)$ to the optimal energy-weighted target $p_1(a|s) \propto \pi_\beta(a|s)\exp(\beta Q_\psi(s,a))$. Here, the negative Q-value acts as the energy function: $E(a) = -Q_\psi(s,a)$.

EFM/QIPO learns an energy-guided flow *during training* by turning policy improvement into a weighted vector-field regression problem studying the general problem of learning a guided distribution of the form

$$q(x) \;\propto\; p(x)\exp\big(-\beta E(x)\big), \tag{16}$$

and shows how to learn a flow that produces samples from q *without* learning intermediate guidance models along the path. In offline RL, one instantiates $x = a$ (optionally conditioned on s) and chooses the energy as $E(s,a) = -Q_\psi(s,a)$, so the guidance factor becomes $\exp(\beta Q_\psi(s,a))$. The resulting algorithm in Zhang et al. (2025b) is referred to as *Q-weighted Iterative Policy Optimization (QIPO)*, and its distinguishing feature is that policy improvement is performed *without backpropagating through an ODE solver or sampling chain*: the policy update remains a supervised regression update.

Here the key technical obstacle is that the guided marginal path depends on an intractable *intermediate energy $E_t(x)$*. To learn a flow, conceptually choose a base probability path $\{p_t\}_{t\in[0,1]}$ (e.g., the OT/linear path used in conditional flow matching) and seek a *guided* path

$$q_t(x) \;\propto\; p_t(x)\exp\big(-E_t(x)\big),$$

whose terminal distribution matches equation 16. The difficulty is that the intermediate energy $E_t(x)$ is generally not available in closed form, and naively learning it would reintroduce the auxiliary-model burden that this work aims to avoid.

The authors resolve this by proving that optimizing a simple *energy-weighted* flow-matching loss recovers the guided flow without explicitly modeling E_t. Rather than learning E_t, they show that one can directly optimize an energy-weighted regression objective that matches the guided flow field in expectation. A convenient view (especially for offline RL) is through the *conditional* form of the objective: samples are drawn from the *unguided* conditional path, while the loss is reweighted by an energy term evaluated at a terminal sample. Specializing the energy to $E(s,a) = -Q_\psi(s,a)$ yields QIPO's policy improvement update:

$$\mathcal{L}_{\mathrm{QIPO}}(\theta) = \mathbb{E}_{\substack{s\sim\mathcal{D},\, a_1\sim\pi_\beta(\cdot|s) \\ t\sim\mathrm{Unif}[0,1],\, a_t\sim p_t(\cdot|a_1,s)}} \left[\bar{w}_\psi(s,a_1) \left\| v_\theta(a_t,s,t) - u_t(a_t|a_1,s) \right\|_2^2 \right], \tag{17}$$

where u_t is the *base* conditional target field (e.g., OT: $u_t = x_1 - x_0$), and $\bar{w}_\psi$ is a *normalized* energy weight. In practice, $\bar{w}_\psi$ is computed by a softmax over a *finite support set* of candidate actions, which avoids computing partition functions and stabilizes the exponential weighting.

Algorithm 3 Flow-based QIPO / EFM for Offline RL (Zhang et al., 2025b)

Require: Offline dataset $\mathcal{D}$; flow policy velocity $v_\theta(a, s, t)$; critic Q_ψ (and target $\bar{\psi}$); support size M; temperature β; CFM path sampler $a_t \sim p_t(\cdot|a_1, s)$; base target field $u_t(\cdot|a_1, s)$ (e.g., OT).
 1: **(Warm-up)** Train v_θ with standard (unweighted) CFM on $\mathcal{D}$ to model behavior actions.
 2: **(Warm-up)** Train Q_ψ on $\mathcal{D}$ with Bellman regression (e.g., TD target using a policy prior).
 3: **while** not converged **do**
 4:     Sample minibatch $\{(s_i, a_i, r_i, s'_i)\}_{i=1}^B \sim \mathcal{D}$.
 5:     **Critic update:** update ψ to minimize a TD/Bellman loss on $\mathcal{D}$ (with target network $\bar{\psi}$).
 6:     **Support set:** for each s_i, sample candidate actions $\{a_i^{(j)}\}_{j=1}^M$ from the current flow policy (or a behavior flow prior).
 7:     Compute normalized weights $\bar{w}_i^{(j)} \leftarrow \frac{\exp(\beta Q_\psi(s_i, a_i^{(j)}))}{\sum_{k=1}^M \exp(\beta Q_\psi(s_i, a_i^{(k)}))}$.
 8:     **Flow update:** for each $(s_i, a_i^{(j)})$, sample $t \sim \mathrm{Unif}[0, 1]$ and $a_t \sim p_t(\cdot|a_i^{(j)}, s_i)$.
 9:     Update θ by minimizing

$$\sum_{i=1}^B \sum_{j=1}^M \lambda(t)\, \bar{w}_i^{(j)} \big\| v_\theta(a_t, s_i, t) - u_t(a_t|a_i^{(j)}, s_i) \big\|_2^2.$$

10: **end while**
11: **Output:** flow policy obtained by integrating $\dot{a}_t = v_\theta(a_t, s, t)$ from $t = 0 \to 1$ at test time.

The algorithmic backbone of QIPO is an alternating loop of (i) critic learning and (ii) energy-weighted flow regression with support-set normalization. QIPO follows the standard offline RL rhythm: it trains a critic Q_ψ on the dataset using Bellman regression, and periodically performs policy improvement updates that tilt the flow toward high-Q actions. The important implementation detail is that the weights in equation 17 are computed using a *support action set* per state: given a batch of states, one samples M candidate actions (from the current policy or a behavior model), evaluates $Q_\psi(s, a)$ on those candidates, and computes

$$\bar{w}_\psi(s, a^{(j)}) \;=\; \frac{\exp\big(\beta Q_\psi(s, a^{(j)})\big)}{\sum_{k=1}^M \exp\big(\beta Q_\psi(s, a^{(k)})\big)}.$$

This "softmax over a support set" is exactly the step that makes QIPO practical in continuous control: it replaces the intractable partition function by a batch-normalized estimator while keeping the update simulation-free. Algorithm 3 summarizes the backbone of flow-based QIPO/EFM in a form that matches the structure used in Zhang et al. (2025b).

Conceptually, QIPO's "energy guidance" happens by changing *which terminal samples the regression cares about*, not by changing how the flow is numerically integrated. So the ODE solver is not part of training; the only place where Q enters is the weight $\bar{w}$, which selectively emphasizes high-value actions inside the dataset's support. This is precisely why QIPO tends to be stable compared to methods that differentiate through an iterative generative sampler: the policy update is a weighted regression update, and the heavy lifting is done by the critic.

4.3 FlowQ: Approximating Energy-Guided Paths

FlowQ (Alles et al., 2025) refines energy-guided training by approximating the *guided probability path* and deriving an explicit guided conditional velocity field. While QIPO/EFM provides a general energy-weighted objective, FlowQ takes a complementary route: it assumes a guided marginal path of the form

$$\hat{p}_t(x) \;\propto\; p_t(x) \exp\{-\lambda(t) E(x)\},$$

and then derives a tractable *conditional* path and velocity field by approximating $E(x_t)$ with a first-order Taylor expansion around the base-path mean. In offline RL, again $E(s, a) = -Q_\psi(s, a)$, so the guidance favors higher Q-values.

The specific step FlowQ refines relative to QIPO is the modeling of *how guidance distorts the intermediate-time conditionals*. The algorithm discussed in the previous section can be interpreted as "keep the base conditional path but weight terminal samples by $\exp(\beta Q)$", which is powerful but leaves the intermediate path implicit. FlowQ instead explicitly constructs an approximate conditional

$$\hat{p}_t(x_t|x_1) \;\propto\; p_t(x_t|x_1)\exp\{-\lambda(t)E(x_t)\},$$

and shows that, under the standard Gaussian CFM conditional $p_t(x_t|x_1) = \mathcal{N}(x_t; tx_1, (1-t)^2 I)$ and a first-order expansion of E, the guided conditional remains Gaussian with a *shifted mean*. Concretely, the approximation yields

$$\hat{p}_t(x_t|x_1) \approx \mathcal{N}\big(x_t;\; \alpha_c(t,x_1),\; (1-t)^2 I\big), \qquad \alpha_c(t,x_1) = tx_1 - (1-t)^2\lambda(t)\nabla E(tx_1),$$

which induces an explicit guided target velocity $\hat{u}_t(\cdot|x_1)$ for regression. This derivation clarifies *what changes*: the authors in this paper propose modifying the *conditional geometry of the path* through a mean shift that pushes mass toward low energy (high Q) regions, rather than only reweighting endpoints.

In practice, FlowQ preserves the same "simulation-free" training philosophy while using the guided conditional field in place of the base one. Because the guided conditional is still a simple Gaussian under the approximation, this method can sample x_t cheaply and regress v_θ onto the derived $\hat{u}_t$ without integrating an ODE during training. The net result is a policy that internalizes guidance at training time, so that inference can remain plain ODE sampling without additional test-time guidance.

4.4 Flow Q-Learning: One-Step Improvement on Top of a Flow Prior

Flow Q-Learning (FQL) (Park et al., 2025) refines offline flow policies by moving the RL objective from the iterative flow sampler to a separate one-step actor. A direct way to apply actor-critic learning to a flow policy is to treat the generated action as $a = \text{ODE}(z; v_\theta, s)$ and backpropagate $\nabla_a Q(s, a)$ through the ODE solver. The authors in this paper argue that this *recursive backpropagation through time* is often unstable and expensive for iterative generative policies, and proposes a modular alternative: train the flow *only* as a behavior model, and train a *one-step* policy to maximize value while being regularized toward the flow prior.

The backbone of their algorithm is a three-part loop: behavior flow training, critic training, and one-step policy improvement with distillation. FQL begins by training a behavior-cloning flow policy $\mu_\theta(s, z)$ with standard CFM, producing an expressive implicit distribution over actions. It then trains a critic Q_ϕ on the dataset, and finally trains a one-step actor $\mu_\omega(s, z)$ with a reparameterized policy gradient objective augmented with a *distillation* term that keeps μ_ω close to the flow prior:

$$\min_\omega \; \mathbb{E}_{s\sim\mathcal{D},\, z\sim\mathcal{N}(0,I)}\Big[-Q_\phi\big(s, \mu_\omega(s, z)\big) + \alpha\big\|\mu_\omega(s, z) - \mu_\theta(s, z)\big\|_2^2\Big].$$

This design makes the refinement relative to QIPO/FlowQ explicit: instead of changing the flow regression target with Q, FQL *keeps the flow regression purely behavioral* and performs value maximization in a separate policy head. In Algorithm 4 we present the core structure of FQL as given in Park et al. (2025).

In short, FQL replaces "guided generation" with "guided distillation," yielding efficient inference while retaining a rich generative prior. Because the deployed actor is one-step, this method avoids ODE-time inference costs entirely, yet the actor remains expressive because it is trained under a strong flow prior that captures multimodality in the dataset.

4.5 ReFORM: On-Support Improvement via Reflected Noise Manipulation

ReFORM (Zhang et al., 2026) refines offline flow RL by enforcing support constraints *structurally* through bounded noise and reflected flows. Many offline RL methods rely on statistical penalties (e.g., KL or Wasserstein) to keep policies close to behavior, but such penalties do not directly guarantee $\text{supp}(\pi) \subseteq \text{supp}(\pi_\beta)$. ReFORM targets the support constraint head-on by designing the policy as a composition of (i) a behavior-cloning flow with *bounded-support* latent noise and (ii) a *noise generator* that manipulates noise *within the same bounded support*. The key guarantee is nice and simple: if the manipulated noise distribution

---

Algorithm 4 Flow Q-Learning (FQL) for Offline RL (Park et al., 2025)

Require: Offline dataset $\mathcal{D}$; BC flow velocity $v_\theta(a, s, t)$ and induced flow policy $\mu_\theta(s, z)$ (Euler steps M); critic Q_ϕ (target $\bar{\phi}$); one-step actor $\mu_\omega(s, z)$; coefficient α.

1: **while** not converged **do**
2:     Sample minibatch $\{(s, a, r, s')\} \sim \mathcal{D}$.
3:     **Critic update:** sample $z \sim \mathcal{N}(0, I)$, set $a' \leftarrow \mu_\omega(s', z)$, update ϕ using TD loss

$$\left(Q_\phi(s, a) - (r + \gamma Q_{\bar{\phi}}(s', a'))\right)^2.$$

4:     **BC flow update:** sample $x_0 \sim \mathcal{N}(0, I)$, set $x_1 \leftarrow a$, sample $t \sim \text{Unif}[0, 1]$, set $x_t \leftarrow (1 - t)x_0 + tx_1$, update θ to minimize $\|v_\theta(x_t, s, t) - (x_1 - x_0)\|_2^2$ (OT-CFM).
5:     **One-step actor update:** sample $z \sim \mathcal{N}(0, I)$, set $a_\pi \leftarrow \mu_\omega(s, z)$, update ω to minimize

$$-Q_\phi(s, a_\pi) + \alpha\|a_\pi - \mu_\theta(s, z)\|_2^2.$$

6: **end while**
7: **Output:** one-step policy μ_ω for fast inference; μ_θ as an expressive prior.

---

stays inside the original noise support, then pushing it through the BC flow cannot leave the BC policy's action support.

The first pillar of ReFORM is to choose a bounded latent source so that behavior support is approximated by the BC flow's pushforward of that bounded set. Let the BC flow policy be the time-1 map $\psi_{\theta_1}(1, z; s)$ of a flow that transports $z \sim q_{\text{BC}}$ to actions, where q_{BC} has bounded support (e.g., uniform on a ball). ReFORM uses the observation that $\text{supp}(\pi_\beta(\cdot|s))$ can be approximated by $\psi_{\theta_1}(1, \text{supp}(q_{\text{BC}}); s)$, so staying inside $\text{supp}(q_{\text{BC}})$ in latent space is the lever that controls on-support behavior in action space.

The second pillar of their proposed method is a *reflected* flow for noise manipulation that guarantees the manipulated noise stays within the bounded support. ReFORM learns a noise generator flow $\psi_{\theta_2}(t, w; s)$ that transforms base noise w into manipulated noise, but constrains its dynamics via a reflected ODE

$$d\psi_{\theta_2}(t, w; s) = v_{\theta_2}(t, \psi_{\theta_2}(t, w; s); s)\, dt + dL_t,$$

where the reflection term pushes trajectories back inward when they hit the boundary of the support. In implementation, this is realized by a projected/reflected Euler step, achieving essentially the same per-step complexity as standard Euler while enforcing the constraint.

ReFORM's optimization is then cleanly separated into behavior modeling, noise optimization for value, and (optionally) one-step distillation for deployment. This method first trains the BC flow ψ_{θ_1} on the dataset, then trains the constrained noise generator ψ_{θ_2} to increase Q under the composed policy $\psi_{\theta_1}(1, \cdot; s) \circ \psi_{\theta_2}(1, \cdot; s)$, and finally distills the BC flow into a one-step policy for computational efficiency. The distillation loss follows the same spirit as other flow-distillation approaches:

$$\mathcal{L}_{\text{Distill}}(\hat{\theta}_1) = \mathbb{E}_{s \sim \mathcal{D},\, z \sim q_{\text{BC}}}\left\|\hat{\mu}_{\hat{\theta}_1}(s, z) - \psi_{\theta_1}(1, z; s)\right\|_2^2. \tag{18}$$

Algorithm 5 summarizes the high-level pipeline of this method.

The main conceptual payoff of their proposed algorithm is that it turns "stay on support" from a penalty into a construction. Because support containment is ensured by keeping latent noise inside the bounded source support and using reflected dynamics to prevent boundary escape, ReFORM can pursue policy improvement without relying exclusively on statistical regularizers that may either be too weak to prevent OOD or too strong to prevent improvement.

4.6 Efficiency and Stability Add-ons

Recent work complements the core offline algorithms by addressing inference cost and weight variance without changing the overall story. Even when training is simulation-free, deploying a flow policy can incur ODE

Algorithm 5 ReFORM for Offline RL (Zhang et al., 2026)

Require: Offline dataset $\mathcal{D}$; bounded-support latent q_{BC}; BC flow ψ_{θ_1}; reflected noise flow ψ_{θ_2}; critic Q_ψ.
 1: **Train BC flow:** fit ψ_{θ_1} (velocity field) by CFM/OT-CFM on $(s, a) \sim \mathcal{D}$ with $z \sim q_{\text{BC}}$.
 2: **Train critic:** fit Q_ψ on $\mathcal{D}$ with standard Bellman regression.
 3: **while** not converged **do**
 4:     Sample states $s \sim \mathcal{D}$ and base noise $w \sim q_{\text{BC}}$.
 5:     **Reflected noise step:** generate manipulated noise $\tilde{z} = \psi_{\theta_2}(1, w; s)$ by integrating the reflected ODE (projected/reflected Euler).
 6:     **Compose policy:** generate action $a = \psi_{\theta_1}(1, \tilde{z}; s)$.
 7:     Update θ_2 to increase $Q_\psi(s, a)$ subject to the reflection constraint (implemented by the reflected dynamics).
 8: **end while**
 9: **(Optional) Distill:** train one-step policy $\hat{\mu}_{\hat{\theta}_1}$ to match $\psi_{\theta_1}(1, z; s)$ using equation 18.
10: **Output:** on-support policy via composed flows (and optionally one-step distilled policy).

---

integration cost, and exponential Q-weights can have high variance; both issues have motivated practical add-ons that preserve the backbone described above.

Single-step completion distills iterative flow generation into one-shot inference by learning to "complete" the transport from intermediate points. Single-Step Completion Policies (SSCP) (Koirala & Fleming, 2025) modify the supervision signal so that, from an intermediate a_t, the model predicts the completion toward a_1, enabling inference in a single network evaluation while retaining the representational benefits of flow training.

Adaptive balancing targets the bias-variance tradeoff induced by aggressive exponential weighting in offline post-training. Adaptive Reinforced Flow Matching (ARFM) (Zhang et al., 2025a) addresses the practical instability that arises when $\exp(\beta Q)$ weights become overly peaked by adapting the effective scaling of the weight to preserve usable learning signal while controlling gradient variance, which is particularly relevant in large-scale post-training settings.

Summary. Across QIPO/EFM, FlowQ, FQL, and ReFORM, the offline literature can be read as a sequence of increasingly careful design choices about *where* guidance should enter: QIPO/EFM tilts the regression objective with normalized Q-weights, FlowQ explicitly models how guidance distorts intermediate-time conditionals, FQL relocates value maximization to a one-step actor regularized by a flow prior, and ReFORM enforces on-support improvement structurally through bounded latent noise and reflected flows. Table 1 synthesizes the foundational methods in offline flow-based RL, categorizing them by how the energy signal is integrated and how they address computational efficiency and safety constraints.

Algorithm	How Energy Enters	OOD Control Mechanism	Inference Cost
EFM / QIPO (Zhang et al., 2025b)	Modified target velocity field	Implicit (KL/Energy Target)	Moderate (ODE)
FlowQ (Alles et al., 2025)	Advantage-weighted regression	Implicit (KL/Energy Target)	Moderate (ODE)
FQL (Park et al., 2025)	Policy head optimization	Explicit KL-style penalty	Very Low (1-step)
ReFORM (Zhang et al., 2026)	Behavior Cloning base	Structural latent reflection	Moderate (ODE)
ARFM (Zhang et al., 2025a)	Adaptive exponential scaling	Variance-bounded weights	Moderate (ODE)
SSCP (Koirala & Fleming, 2025)	Vector completion target	Implicit (Generative prior)	Very Low (1-step)

Table 1: A unifying comparison of foundational offline flow-matching RL algorithms.

5 Online Reinforcement Learning with Flow-Matching Policies

While offline RL with flow matching methods rely on weighted regression on a fixed dataset, *online RL* requires the agent to explore and update its policy through environment interaction and optimize expected

return. Integrating flow matching into this setting is nontrivial because standard flow models define *deterministic* probability flow ODEs:

$$\frac{dx_t}{dt} = v_\theta(x_t, s, t), \qquad t \in [0, 1],$$

which map noise $x_0 \sim \mathcal{N}(0, I)$ to an action $a = x_1$ without inherent stochasticity during training.

Policy gradient methods, however, require stochastic policies in order to estimate gradients of $J(\theta) = \mathbb{E}_{\tau \sim \pi_\theta}[R(\tau)]$. Therefore, since in traditional RL, exploration is typically achieved by sampling from a stochastic policy (e.g., adding Gaussian noise to a mean action) but a flow policy generates actions through a multi-step Ordinary Differential Equation (ODE) solver, injecting exploration noise and calculating policy gradients is non-trivial. This fundamental mismatch has led to several distinct solutions.

A Unified View. Most online flow-RL methods can be understood through three design choices:

1. **How is stochasticity introduced?**

2. **How is the policy gradient computed?**

3. **How is stability ensured (KL or trust-region regularization)?**

Under this lens, existing methods fall into three representative families: (i) noise-injected stochastic flows, (ii) pathwise policy gradients through the ODE, and (iii) group-based relative optimization. We explain each in detail below.

5.1 Method 1: Noise Injection and Fine-Tuning

ReinFlow (Zhang et al., 2025c) resolves the conflict between deterministic flow-matching policies and policy gradient methods by converting deterministic ODE sampling into a discrete-time Markov process with Gaussian transitions. By injecting learnable noise into each discretized step, the method enables exact and tractable likelihood computation even with a single denoising step. The agent is optimized using a PPO-style clipped objective derived from a policy gradient formulation for Markov processes. This allows the noise network to automatically balance exploration and exploitation during training; once fine-tuning is complete, the noise module is discarded to restore the deterministic efficiency of the flow policy for deployment.

Given the Euler discretization:

$$x_{k+1} = x_k + h\, v_\theta(x_k, s, t_k),$$

ReinFlow injects learnable Gaussian noise:

$$x_{k+1} = x_k + h\, v_\theta(x_k, s, t_k) + \sigma_\phi(x_k, s, t_k)\, \xi_k, \quad \xi_k \sim \mathcal{N}(0, I).$$

This induces a stochastic policy $\pi_\theta(a|s)$ whose likelihood can be evaluated along the trajectory.

Policy Optimization. Because the sampling process is now stochastic, ReinFlow applies standard on-policy objectives such as PPO:

$$L^{\mathrm{PPO}}(\theta) = \mathbb{E}[\min(r_t(\theta)A_t, \mathrm{clip}(r_t(\theta), 1 - \epsilon, 1 + \epsilon)A_t)],$$

where $r_t(\theta)$ is the likelihood ratio under the stochastic flow policy.

Their algorithm works by co-training a lightweight noise injection network alongside the pre-trained flow policy's velocity field. During environment rollouts, the policy generates actions through a sequence of denoising steps where Gaussian noise is added at each stage, as defined by the noise network. This stochasticity allows the researchers to apply a derived Policy Gradient Theorem for Markov Process Policies, optimizing the agent using a clipped surrogate loss (similar to PPO) based on collected rewards. Once fine-tuning is complete, the noise network is discarded, restoring a deterministic, high-performing flow matching policy for rapid inference.

Algorithm 6 ReinFlow (Zhang et al., 2025c) (Noise-Injected Flow RL; rough sketch)

1: Initialize velocity network v_θ and noise network $\sigma_\phi(\cdot)$
2: **for** each batch of environment rollouts **do**
3:     Sample $x_0 \sim \mathcal{N}(0, I)$ $\triangleright$ x_k denotes the intermediate action variable
4:     **for** $k = 0$ to $T - 1$ **do**
5:         $\xi_k \sim \mathcal{N}(0, I)$
6:         $x_{k+1} = x_k + h\, v_\theta(x_k, s, t_k) + \sigma_\phi(s, t_k)\, \xi_k$ $\triangleright$ Gaussian transitions $\Rightarrow$ tractable $\log \pi$ for PPO ratios
7:     **end for**
8:     Execute action $a = x_T$, collect reward
9: **end for**
10: Update θ, ϕ via PPO using likelihood ratios from the Gaussian transitions
11: **Inference:** set $\sigma_\phi \equiv 0$ and use the deterministic ODE

Crucially, noise is required only during training to facilitate exploration and likelihood computation. After convergence, the noise module is removed and the deterministic ODE is used for fast inference enabling efficient action generation. Thus, ReinFlow separates stochastic exploration during learning and deterministic efficiency during deployment preserving classical policy gradient machinery but modifying the generative process itself.

5.2   Method 2: Flow Matching Policy Gradients (FMPG) and PPO

A second family of methods avoids noise injection and instead differentiates *directly through the flow ODE*. Rather than converting the deterministic flow into a stochastic Markov chain, these approaches treat the flow policy as a reparameterized distribution whose parameters influence the final action through the ODE solution map.

Recall that a flow-matching policy generates an action a by solving

$$\frac{dx_t}{dt} = v_\theta(x_t, s, t), \qquad x_0 \sim p_0, \qquad a = x_1,$$

where v_θ is a learned velocity field. The policy distribution $\pi_\theta(a|s)$ is implicitly defined by pushing forward the base distribution p_0 through the ODE solution operator.

The reinforcement learning objective is

$$J(\theta) = \mathbb{E}_{s \sim d^\pi,\, a \sim \pi_\theta(\cdot|s)} \left[R(s, a) \right].$$

Since the flow model is deterministic given x_0, so randomness enters only through the base noise x_0. This enables reparameterization:

$$\nabla_\theta J(\theta) = \mathbb{E}_{x_0 \sim p_0} \left[\nabla_a R(s, a) \frac{\partial a}{\partial \theta} \right], \qquad a = \Phi_\theta(x_0, s), \tag{19}$$

where Φ_θ denotes the ODE solution map. Thus, gradients can be computed by differentiating through the numerical ODE solver.

Common Algorithmic Template.   The methods in this family share a common structure that we provide in Algorithm 7. The main differences between methods lie in (i) how they estimate $\nabla_\theta \log \pi_\theta(a|s)$, (ii) whether they require explicit likelihood computation, and (iii) how they ensure numerical stability.

Flow Matching Policy Gradients (FMPG).   FMPG(McAllister et al., 2025) derives a policy gradient theorem for flow-matching policies by explicitly differentiating through the ODE solution map. Since the action a is a deterministic function of x_0 and θ, the gradient of the expected return can be computed via the pathwise derivative in equation 19. This avoids introducing additional noise into the flow.

Algorithm 7 Generic Flow-Policy Gradient Template

Require: Velocity field v_θ, base distribution p_0

1: **for** each RL iteration **do**
2:     Sample $x_0 \sim p_0$
3:     Integrate $\dot{x}_t = v_\theta(x_t, s, t)$ to obtain $a = x_1$
4:     Execute action a, observe reward and advantage estimate
5:     Compute gradient of $J(\theta)$ by backpropagating through the ODE integration steps
6:     Update θ using policy gradient (or PPO-style objective)
7: **end for**

The key insight is that the divergence of the velocity field governs the change of log-density along trajectories. Thus, likelihood gradients can be expressed in terms of the velocity field and its Jacobian trace. In practice, FMPG differentiates through the ODE solver using automatic differentiation, enabling end-to-end policy optimization without altering the generative process.

Reinforcement Learning for Flow-Matching Policies. Pfrommer et al. (2025) adapt reinforcement learning to flow-matching policies in the context of variable-horizon action chunks. Their approach focuses on two RL formulations: Reward-Weighted Flow Matching (RWFM) and Group Relative Policy Optimization (GRPO).

RWFM modifies the flow-matching loss by weighting trajectories with $\exp(\alpha R)$, producing a density proportional to the reward-weighted demonstration distribution. GRPO instead samples multiple action chunks from the current flow policy, computes normalized group-relative advantages, and inserts these weights into a weighted flow-matching regression objective. Importantly, these methods do *not* differentiate through the ODE likelihood; rather, they retain the flow-matching regression structure while injecting RL signal via reward-based weighting.

PolicyFlow: PPO for Continuous Normalizing Flows. PolicyFlow(Yang et al., 2026) adapts Proximal Policy Optimization (PPO) to continuous normalizing flows. Computing the exact likelihood of a sample requires integrating the divergence of v_θ along the ODE trajectory:

$$\log \pi_\theta(a|s) = \log p_0(x_0) - \int_0^1 \operatorname{div}\big(v_\theta(x_t, s, t)\big)\, dt.$$

Because evaluating this integral and its gradients is computationally expensive for on-policy RL, PolicyFlow approximates the divergence term using the Hutchinson trace estimator. This yields a scalable estimate of the log-likelihood ratio needed for PPO:

$$r_t(\theta) = \exp\big(\log \pi_\theta(a_t|s_t) - \log \pi_{\theta_{\text{old}}}(a_t|s_t)\big).$$

The PPO surrogate objective is then

$$L^{\text{PPO}}(\theta) = \mathbb{E}\left[\min\big(r_t(\theta)A_t, \operatorname{clip}(r_t(\theta), 1-\epsilon, 1+\epsilon)A_t\big)\right].$$

This approach preserves the multi-modal expressivity of flow models while leveraging the stability guarantees of PPO.

Key Differences. These methods differ along three fundamental axes:

- **Gradient computation.** FMPG uses pathwise differentiation through the ODE. PolicyFlow estimates likelihood ratios via divergence approximation. RWFM/GRPO avoid likelihood computation entirely and rely on weighted regression.

- **Need for log-density.** PolicyFlow explicitly approximates $\log \pi_\theta$. FMPG uses ODE sensitivity. RWFM/GRPO do not require density evaluation.

Algorithm 8 Generic GRPO-style training for flow policies

1: **Input:** policy flow $v_\theta(x, t; s)$, prompt/state s, group size G
2: **while** training **do**
3:     **for** $i = 1, \ldots, G$ **do**
4:         Sample base noise $x_0^{(i)} \sim p_0$
5:         Generate action or output via flow sampling

$$a^{(i)} = \Phi_\theta(x_0^{(i)}, s)$$

6:         Evaluate reward $R_i = R(s, a^{(i)})$
7:     **end for**
8:     Compute group-relative advantages

$$\hat{A}_i = \frac{R_i - \mathrm{mean}(\{R_j\})}{\mathrm{std}(\{R_j\})}$$

9:     Update policy using PPO-style objective

$$\max_\theta \mathbb{E}\left[\min\left(r_i(\theta)\hat{A}_i, \ \mathrm{clip}(r_i(\theta), 1 - \epsilon, 1 + \epsilon)\hat{A}_i\right)\right]$$

10: **end while**

- **Stability mechanism.** PolicyFlow inherits PPO clipping. FMPG relies on smooth ODE gradients. RWFM/GRPO rely on weighted regression and advantage normalization.

Conceptually, this family of methods treats the flow as a *differentiable transport map* whose parameters can be optimized either by differentiating through the ODE or by approximating policy gradients via density estimates. They contrast with noise-injection approaches (Section 5.1), which modify the generative process itself to recover tractable likelihoods.

5.3 Method 3: The GRPO Family (Group Relative Policy Optimization)

A rapidly growing family of methods adapts *Group Relative Policy Optimization (GRPO)* (Shao et al., 2024) to flow models. These approaches sample a group of trajectories (using different random noise seeds x_0), evaluate their rewards, and update the flow to increase the likelihood of the best paths.

Algorithm 8 summarizes the common structure shared by GRPO-style flow optimization methods. Instead of estimating advantages using a learned critic, these methods sample a group of candidate outputs generated from different noise seeds, evaluate their rewards, and compute normalized advantages relative to the group mean. The flow policy is then updated using a PPO-style clipped objective so that samples with higher relative reward become more likely while lower-ranked samples are suppressed. The key difference across GRPO-family methods lies in how they improve exploration, credit assignment, or variance reduction within this basic loop.

Several recent works extend this template in different ways:

- **Flow-GRPO** (Liu et al., 2025a) establishes the baseline by converting the flow ODE into an SDE to enable exploration. It demonstrates that simple group-based ranking can align large-scale text-to-image flow models with human preferences.

- **TempFlow-GRPO** (He et al., 2025) critiques the "sparse reward" assumption of standard GRPO. It argues that timing matters: decisions made early in the flow trajectory have different impacts than those made late. TempFlow introduces a temporal credit assignment mechanism to weight updates differently across flow timesteps $t \in [0, 1]$.

- **Smart-GRPO** (Yu et al., 2026) addresses the inefficiency of random exploration. Instead of sampling random noise $x_0 \sim \mathcal{N}(0, I)$, it actively optimizes the noise perturbation to explore high-reward regions, serving as a "smart" exploration strategy for the flow policy.

- **SuperFlow** (Chen et al., 2025b) tackles the variance issue. It observes that fixed group sizes in GRPO are inefficient. SuperFlow introduces variance-aware sampling that dynamically adjusts the number of samples per prompt based on the difficulty of the optimization landscape.

- **F5R-TTS** (Sun et al., 2025) applies GRPO to flow-matching based text-to-speech models. The method first reformulates the deterministic flow outputs as probabilistic Gaussian predictions, enabling likelihood-based RL updates. During fine-tuning, GRPO optimizes speech generation using rewards derived from word error rate (WER) and speaker similarity metrics, improving both intelligibility and voice consistency in zero-shot voice cloning tasks.

5.4 Adaptive Regularization

While reward-weighted regression provides a simple mechanism for aligning flow policies with reward signals, it can suffer from *policy collapse*, where the generative model over-optimizes the reward and converges to a degenerate distribution with low diversity. This issue is particularly severe in online fine-tuning, where the policy repeatedly samples from its own generated distribution.

To address this problem, Fan et al. (2025b) propose **Online Reward-Weighted Conditional Flow Matching with Wasserstein Regularization (ORW-CFM-W2)**, an RL-based framework for fine-tuning flow matching models with arbitrary reward functions. The core idea is to extend reward-weighted flow matching by incorporating a divergence penalty that constrains the fine-tuned model to remain close to a reference distribution.

Specifically, the induced policy update can be interpreted as updating the data distribution according to

$$q_\theta^{(n)}(x_1) \propto q_\theta^{(n-1)}(x_1) \exp\big(\lambda r(x_1) - \beta' D_{n-1}(x_1)\big),$$

where $r(x_1)$ is the reward function, $D_{n-1}(x_1)$ measures the divergence between the current model and the reference model, and λ, β' control the trade-off between reward maximization and regularization. This update closely resembles classical reinforcement learning algorithms such as Advantage-Weighted Regression (AWR) (Peng et al., 2019), where policy probabilities are updated proportionally to exponentiated advantages. The divergence term acts as a stabilizer that prevents overly aggressive policy updates. Fan et al. (2025b) show that without this regularization, the policy can collapse toward a delta distribution that maximizes reward but eliminates generative diversity.

A key challenge in applying divergence regularization to continuous-time flow models is that common measures such as KL divergence are computationally expensive because evaluating likelihoods requires integrating the flow divergence along the entire ODE trajectory. To overcome this difficulty, ORW-CFM-W2 instead uses the Wasserstein-2 (W_2) distance as the regularization metric and derives a tractable upper bound that can be computed directly from the velocity fields of the flow model. This allows the method to control the distance between the fine-tuned model and the pre-trained reference model while avoiding expensive likelihood computations.

Algorithm 9 summarizes the backbone of ORW-CFM-W2: the model samples from its current policy online, reweights updates by reward, and uses a Wasserstein-based penalty to keep the policy close to a reference flow. Compared with offline reward-weighted regression, the crucial difference is that the sampling distribution is updated online from the current policy itself, which improves exploration but also makes regularization essential for preventing collapse.

While ORW-CFM-W2 stabilizes training through a fixed Wasserstein regularization coefficient, choosing a single global penalty introduces a fundamental trade-off: strong regularization preserves diversity but slows reward optimization, while weak regularization enables learning but risks policy collapse. To address this limitation, Fan et al. (2025c) propose **Adaptive Divergence Regularized Policy Optimization (ADRPO)**, which dynamically adjusts the regularization strength using the advantage signal. Intuitively,

---

Algorithm 9 Online Reward-Weighted CFM with Wasserstein Regularization (ORW-CFM-W2) (Fan et al., 2025b)

1: **Input:** reference flow model $v_{\theta_{\mathrm{ref}}}$, initialized policy $v_\theta \leftarrow v_{\theta_{\mathrm{ref}}}$, reward function $r(\cdot)$, weighting map $w(x_1) = F(\tau r(x_1))$, regularization coefficient α

2: **while** not converged **do**

3:     Sample generated targets $x_1 \sim q_\theta(x_1)$ from the current flow policy

4:     Sample $t \sim \mathrm{Unif}[0,1]$ and interpolation point $x \sim p_t(x \mid x_1)$

5:     Compute reward weight $w(x_1)$ from the sampled target

6:     Compute conditional flow-matching loss:

$$\mathcal{L}_{\mathrm{CFM}} = w(x_1)\|v_\theta(t,x) - u_t(x \mid x_1)\|^2$$

7:     Compute Wasserstein regularization surrogate:

$$\mathcal{L}_{W_2} = \alpha\|v_\theta(t,x) - v_{\theta_{\mathrm{ref}}}(t,x)\|^2$$

8:     Update θ by minimizing:

$$\mathcal{L}_{\mathrm{ORW\text{-}CFM\text{-}W2}} = \mathcal{L}_{\mathrm{CFM}} + \mathcal{L}_{W_2}$$

9: **end while**

10: **Return:** fine-tuned flow policy v_θ

Algorithm 10 Adaptive Divergence Regularized Policy Optimization (ADRPO) (Fan et al., 2025c)

1: **Input:** reference flow model $v_{\theta_{\mathrm{ref}}}$, initialized policy $v_\theta \leftarrow v_{\theta_{\mathrm{ref}}}$, reward function $r(\cdot)$, weighting function $F(\cdot)$

2: **while** not converged **do**

3:     Sample generated targets $x_1 \sim q_\theta(x_1)$ from the current flow policy

4:     Compute reward $r(x_1)$ and advantage estimate $A(x_1)$

5:     Sample $t \sim \mathrm{Unif}[0,1]$ and interpolation point $x \sim p_t(x \mid x_1)$

6:     Compute reward weight

$$w(x_1) = F(\tau A(x_1))$$

7:     Compute adaptive regularization coefficient

$$\alpha(x_1) = g(A(x_1))$$

    where $g(\cdot)$ decreases the penalty for high-advantage samples.

8:     Compute weighted flow matching loss

$$\mathcal{L}_{\mathrm{CFM}} = w(x_1)\|v_\theta(t,x) - u_t(x|x_1)\|^2$$

9:     Compute adaptive Wasserstein regularization

$$\mathcal{L}_{W_2} = \alpha(x_1)\|v_\theta(t,x) - v_{\theta_{\mathrm{ref}}}(t,x)\|^2$$

10:     Update θ by minimizing

$$\mathcal{L}_{\mathrm{ADRPO}} = \mathcal{L}_{\mathrm{CFM}} + \mathcal{L}_{W_2}$$

11: **end while**

12: **Return:** fine-tuned flow policy v_θ

---

samples with high advantage are allowed to deviate more from the reference policy, while samples with uncertain or low advantage are constrained more strongly. This adaptive mechanism allows the policy to aggressively exploit reliable reward signals while remaining conservative when the optimization signal is noisy.

Table 2: Comparison of online reward-weighted flow fine-tuning methods.

Method	Regularization	Sampling	Key Idea
ORW-CFM-W2	Fixed W_2 penalty	Online	Reward-weighted flow matching
ADRPO	Adaptive W_2 penalty	Online	Advantage-dependent regularization

Conceptually, ADRPO generalizes ORW-CFM-W2 by replacing the fixed divergence penalty with an advantage-dependent one. Whereas ORW-CFM-W2 applies the same regularization strength to all samples, ADRPO adapts the constraint to the local reward landscape. This improves the exploration-exploitation trade-off: the policy can move more freely toward reliably high-reward regions while remaining anchored to the reference model when the reward signal is ambiguous. Empirically, the authors show that this adaptive regularization improves alignment quality while maintaining diversity in generative outputs.

In practice, ADRPO can be integrated with existing RL fine-tuning frameworks, including GRPO or reward-weighted flow matching, by replacing the fixed divergence penalty with an advantage-dependent coefficient. This simple modification significantly improves the reward-diversity trade-off during training and has been shown to outperform fixed-regularization methods such as ORW-CFM-W2 in tasks such as text-to-image alignment and multimodal reasoning.

5.5 Bridging Diffusion and Flows: Forward Process Optimization

While this survey focuses on flow matching, boundary-crossing methods provide valuable insights into online optimization. For instance, **DiffusionNFT** (Zheng et al., 2025b) tackles the intractable likelihoods of online diffusion RL by optimizing the model directly on the forward process. By contrasting positive and negative generations to define an implicit policy improvement direction, DiffusionNFT translates the reinforcement signal into a supervised flow-matching objective. This demonstrates how flow-matching mechanics can resolve fundamental optimization bottlenecks even in architectures originally designed around diffusion.

6 Beyond Policies: Critics, Dynamics, and Alignment

Flow matching has demonstrated utility beyond acting as a policy, finding applications in critic modeling, dynamics adaptation, and complex reasoning tasks.

6.1 floq: Training Critics via Flow Matching

While most flow-based reinforcement learning methods focus on improving the *policy*, the critic is typically still implemented as a conventional neural network regressor that maps (s, a) directly to a scalar value $Q(s, a)$. **floq** (Agrawalla et al., 2025) proposes a fundamentally different perspective: instead of treating the Q-function as a static mapping, it parameterizes the critic itself as a *flow model*.

Concretely, floq models the Q-value as the output of a continuous transformation of a latent scalar variable z governed by a velocity field. Starting from an initial sample z_0 drawn from a simple base distribution (e.g., $z_0 \sim \text{Unif}[l, u]$), a time-dependent velocity field $v_\theta(t, z \mid s, a)$ transports the sample toward the target Q-value through an ODE integration process. After K integration steps, the final value z_K represents the predicted Q-value:

$$z_{k+1} = z_k + \frac{1}{K} v_\theta\left(\frac{k}{K}, z_k \mid s, a\right), \qquad k = 0, \ldots, K-1,$$

with the critic prediction given by

$$Q_\theta(s, a) = z_K.$$

Intuitively, this formulation views value estimation as a *flow process that progressively refines an initial guess into the correct Q-value*. The velocity field is trained using a temporal-difference objective so that the terminal distribution of z_K concentrates around the true value $Q^\pi(s, a)$. Importantly, because the Q-value

---

Algorithm 11 Flow-Matching Q-Function Training (floq) (Agrawalla et al., 2025)

1: **Input:** dataset $\mathcal{D}$, flow critic parameters θ, policy π_ϕ, integration steps K
2: **while** not converged **do**
3:      Sample transition $(s, a, r, s') \sim \mathcal{D}$
4:      Sample latent value $z_0 \sim \mathrm{Unif}[l, u]$
                                                     ▷ Flow critic forward pass
5:      **for** $k = 0, 1, \ldots, K - 1$ **do**
6:          $z_{k+1} \leftarrow z_k + \frac{1}{K} v_\theta(k/K, z_k \mid s, a)$
7:      **end for**
8:      $Q_\theta(s, a) \leftarrow z_K$
                                             ▷ Temporal-difference target
9:      Sample $a' \sim \pi_\phi(\cdot | s')$
10:     $y \leftarrow r + \gamma Q_{\theta^-}(s', a')$
                                                 ▷ Update velocity field
11:     Update θ using TD loss:
$$\mathcal{L} = (Q_\theta(s, a) - y)^2$$
12: **end while**
13: **Return:** flow critic Q_θ

---

is produced through iterative numerical integration, the number of integration steps K acts as a controllable compute parameter.

This parameterization introduces a useful property absent from conventional critics: *test-time compute scaling*. Increasing the number of integration steps K effectively increases the depth of the computation used to estimate the value function. As a result, floq can improve value estimation accuracy by allocating additional inference compute, similar to iterative reasoning in modern generative models. Empirically, Agrawalla et al. (2025) show that increasing the number of flow steps consistently improves performance on challenging offline RL benchmarks, outperforming critics based on standard monolithic neural networks.

Conceptually, floq differs from earlier flow-based RL methods in that it applies flow matching to the *critic* rather than the policy. Most prior work leverages flows to model expressive action distributions, while leaving the value function unchanged. floq instead introduces iterative computation into value estimation itself. This approach provides a new scaling axis for reinforcement learning: increasing sequential computation in the critic, rather than increasing network width or ensemble size. Although floq focuses on value-based RL, the idea of applying flow models to value estimation opens an interesting research direction for integrating generative modeling with critic learning.

6.2 Dynamics and Transfer

While most flow-based RL work focuses on learning expressive policies or critics, another emerging direction uses flow matching to address *transfer learning under dynamics shift*. In many practical scenarios, an agent has access to an offline dataset collected in a *source environment*, but must operate in a *target environment* whose transition dynamics differ. Formally, the source and target Markov decision processes share the same state and action spaces but differ in transition dynamics:

$$P_{\mathrm{src}}(s'|s, a) \neq P_{\mathrm{tgt}}(s'|s, a).$$

This mismatch, often referred to as the *dynamics gap*, can significantly degrade performance if offline data are used directly for policy learning.

Composite Flow Matching (CompFlow) (Kong et al., 2025) proposes a principled approach for estimating and exploiting this dynamics gap using flow matching and optimal transport. The key idea is to model the transition distributions of the source and target environments using flow-based generative models and compute a transport map that moves samples from the source transition distribution toward the tar-

---

Algorithm 12 Composite Flow Matching for Dynamics Transfer (CompFlow) (Kong et al., 2025)

1: **Input:** offline dataset $\mathcal{D}_{\text{src}}$, target environment
2: Train offline flow model v_θ^{off} to model source transitions
3: **while** interacting with target environment **do**
4:     Collect target transition (s, a, s')
5:     Initialize latent sample $x_0 \sim p_0$
                                                              $\triangleright$ Offline dynamics flow
6:     $x^{\text{src}} \leftarrow \text{Flow}_\theta^{\text{off}}(x_0, s, a)$
                                                              $\triangleright$ Online adaptation flow
7:     $x^{\text{tgt}} \leftarrow \text{Flow}_\phi^{\text{on}}(x^{\text{src}}, s, a)$
8:     Estimate dynamics discrepancy between source and target flows
9:     Use discrepancy signal to guide exploration and policy updates
10: **end while**
11: **Output:** policy adapted to target dynamics

---

get distribution. Because flow matching has a natural connection to optimal transport, the magnitude of the learned transport provides a measure of distributional discrepancy between the two dynamics models. Specifically, the discrepancy can be quantified using the Wasserstein distance between the two transition distributions:

$$W_2^2(P_{\text{src}}, P_{\text{tgt}}) = \inf_{q \in \Pi(P_{\text{src}}, P_{\text{tgt}})} \mathbb{E}_{(x_0, x_1) \sim q} \left[\|x_0 - x_1\|_2^2 \right],$$

where $\Pi(P_{\text{src}}, P_{\text{tgt}})$ denotes the set of couplings between the two transition distributions. In the flow-matching formulation, the learned transport map approximates the optimal transport plan between the two distributions, enabling the Wasserstein distance to be estimated from the flow trajectories.

Composite Flow Architecture. To estimate this dynamics gap robustly, CompFlow constructs a *composite flow model* consisting of two stages. First, an offline flow model learns the transition distribution from the source dataset:

$$\frac{d}{dt} \psi_\theta^{\text{off}}(x_0, t|s, a) = v_\theta^{\text{off}}\big(\psi_\theta^{\text{off}}(x_0, t|s, a), t, s, a\big).$$

This flow transports latent noise x_0 into a representation of the source transition distribution. A second flow model then adapts this representation toward the target transition distribution observed during online interaction:

$$\frac{d}{dt} \psi_\phi^{\text{on}}(x, t|s, a) = v_\phi^{\text{on}}\big(\psi_\phi^{\text{on}}(x, t|s, a), t, s, a\big).$$

By initializing the online flow from the output of the offline flow rather than from a Gaussian prior, the model effectively learns a transport map from the source dynamics to the target dynamics. This composite structure improves generalization when only limited online data are available. The overall procedure of CompFlow is summarized in Algorithm 12.

Using the Dynamics Gap for Exploration. Once the discrepancy between transition distributions is estimated, CompFlow leverages it in two ways. First, offline transitions that exhibit *low dynamics gap* relative to the online environment are preferentially incorporated into policy training, improving sample efficiency. Second, the estimated discrepancy is used as an exploration signal: the agent is encouraged to collect new data in regions where the dynamics gap is large, which correspond to parts of the state-action space that are poorly represented in the offline dataset.

CompFlow demonstrates that flow matching can be used not only for policy generation but also as a principled tool for *distributional discrepancy estimation*. By leveraging the optimal transport interpretation of flow models, the method provides a geometrically meaningful measure of dynamics mismatch and uses it to guide both data selection and exploration in transfer reinforcement learning.

Algorithm 13 Preference Flow Matching (PFM) (Kim et al., 2024)

1: **Input:** preference dataset $\mathcal{D} = \{(x^+, x^-)\}$
2: **while** training **do**
3:     Sample preference pair (x^+, x^-)
4:     Sample interpolation time $t \sim \mathrm{Uniform}(0, 1)$
5:     Construct interpolation
$$x_t = (1 - t)x^- + tx^+$$
6:     Compute target velocity
$$u_t = x^+ - x^-$$
7:     Update flow model by minimizing
$$\|v_\theta(x_t, t) - u_t\|^2$$
8: **end while**

6.3 Preference Alignment and Reasoning

Flow matching is increasingly explored as an alternative to diffusion models for preference alignment tasks, particularly in reinforcement learning from human feedback (RLHF) and reasoning optimization.

Preference Flow Matching (PFM) (Kim et al., 2024) proposes a principled method for aligning generative models directly from preference pairs without explicitly training a reward model. Given a preferred sample x^+ and a rejected sample x^-, the method constructs a *preference transport* objective that encourages the model to transform rejected outputs toward preferred ones along a learned flow trajectory. Instead of optimizing a scalar reward, PFM modifies the flow-matching regression target so that the velocity field points from the rejected sample toward the preferred sample, effectively learning a transport map between preference distributions.

Formally, the model learns a velocity field $v_\theta(x_t, t)$ along interpolation paths between rejected and preferred samples:

$$x_t = (1 - t)x^- + tx^+, \tag{20}$$

with target velocity

$$u_t = x^+ - x^-. \tag{21}$$

The model is trained via a regression objective similar to standard flow matching, but using preference-induced transport targets:

$$\mathcal{L}_{\mathrm{PFM}} = \mathbb{E}\left[\|v_\theta(x_t, t) - u_t\|^2\right]. \tag{22}$$

Algorithm 13 summarizes the training procedure.

Beyond direct preference alignment, flow-based objectives have also been explored for reasoning optimization. **FlowRL** (Zhu et al., 2025) proposes matching the distribution of high-reward reasoning trajectories rather than maximizing scalar rewards. This approach, termed *Flow Balancing*, encourages the model to approximate the full distribution of successful reasoning paths, preserving diversity while improving correctness.

Overall, these works illustrate how flow matching can provide an alternative alignment mechanism that operates directly on distributions of preferred outputs, avoiding explicit reward modeling and potentially offering more stable training dynamics for large generative models.

6.4 General Guidance Frameworks

While many flow-based RL algorithms introduce guidance heuristically (e.g., weighting losses with Q-values or adding gradients from value functions), recent work has begun to formalize a general theory of *guided flow matching*. Feng et al. (2025a) propose the first unified framework for guidance in flow-based generative models.

The central idea is to reinterpret guidance as modifying the *velocity field* that defines the probability transport process. Recall that a flow model generates samples by solving the ODE

$$\frac{dx_t}{dt} = v_t(x_t), \tag{23}$$

which transports samples from a base distribution p_0 to a target distribution p_1.

Suppose we wish to guide generation using an *energy function $J(x)$* (for example, a classifier score, reward function, or value estimate). The desired guided distribution is

$$p'(x) \propto p(x) \exp(-J(x)), \tag{24}$$

which increases the probability of samples with lower energy values.

The key theoretical question is therefore:

> *How should we modify the original vector field $v_t(x)$ so that the resulting flow generates samples from the new distribution $p'(x)$?*

The framework shows that guidance can be implemented by adding a *guidance vector field $g_t(x)$* to the original velocity field:

$$v'_t(x) = v_t(x) + g_t(x), \tag{25}$$

where the modified vector field v'_t transports samples toward the guided distribution $p'(x)$.

Under this formulation, many previously proposed methods can be interpreted as different approximations of the optimal guidance field $g_t(x)$. The paper derives several families of guidance strategies:

- **Monte Carlo guidance (g_{MC}):** an asymptotically exact estimator of the optimal guidance field obtained via sampling.

- **Gradient-based guidance (g_{local}):** an approximation proportional to the gradient of the energy function, similar to classifier or value guidance.

- **Covariance-preconditioned guidance (g_{cov}):** a refined form that scales gradients using the covariance of the conditional distribution along the flow.

- **Training-based guidance (g_ϕ):** methods that learn the guidance vector field with an auxiliary neural network.

Importantly, the authors show that classical techniques such as classifier guidance, energy guidance, and several diffusion-based guidance mechanisms emerge as special cases of this general flow-guidance framework under additional assumptions about the probability path.

From the perspective of reinforcement learning, this theory provides a principled interpretation of many existing algorithms. For example, Q-guided flows and energy-weighted flow matching can be viewed as approximations to the optimal guidance vector field where the energy function corresponds to the negative value function (i.e., $J(x) = -Q(x)$).

Thus, the guided-flow framework provides a unifying lens through which diverse RL algorithms ranging from reward-weighted regression to gradient-guided sampling can be interpreted as modifying the underlying transport dynamics of the flow model.

These developments suggest that flow matching provides a broader framework for integrating guidance signals into generative models, extending beyond policy learning to value estimation, transfer learning, and alignment.

Discussion and Unifying Perspective. Taken together, the works reviewed in this section illustrate that flow matching is not limited to modeling action policies, but can serve as a general computational primitive for reinforcement learning. For instance, **floq** extends flow matching to *value estimation* by parameterizing the critic itself as a flow process, enabling test-time compute scaling for value-based RL. Similarly, **Composite Flow Matching** (CompFlow) leverages transport maps to address *dynamics shifts* in transfer learning, treating environment mismatch as a probability transport problem between transition distributions. In the context of model alignment, methods such as **Preference Flow Matching** reinterpret preference learning as transporting rejected outputs toward preferred ones, while recent work on **guided flows** provides a general theoretical framework for incorporating external signals such as rewards, classifiers, or value functions into the flow dynamics. Viewed through this lens, many seemingly disparate algorithms can be understood as modifying or learning vector fields that reshape probability transport toward desirable regions of the solution space. This perspective suggests a broader research direction in which flow-based transport processes unify policy learning, value estimation, preference alignment, and environment adaptation within a common generative modeling framework.

7 Emerging Frontiers: Architectures, Action Spaces, and Alignment

As flow matching matures within reinforcement learning, researchers are rapidly extending its core principles beyond standard continuous-control benchmarks. Recent literature has focused on scaling flow models to complex action spaces, restructuring the ODE architectures to stabilize off-policy optimization, and refining the alignment of large-scale foundation models. This section surveys these cutting-edge frontiers.

7.1 Structured and Non-Euclidean Action Spaces

Standard flow matching inherently assumes continuous, Euclidean spaces, which limits its applicability to many real-world domains. Recent breakthroughs have adapted flow models to highly structured environments.

Discrete and Multi-Agent Actions. Many traditional RL problems (e.g., board games, routing, or language generation) operate in discrete action spaces where continuous ODEs are ill-defined. To bridge this gap, Khan et al. (2026) introduce a general framework that replaces continuous flows with Continuous-Time Markov Chains (CTMCs). By training a CTMC using a Q-weighted flow matching objective, they enable generative offline RL in discrete spaces. Furthermore, they address the exponential explosion of joint action spaces in multi-agent settings by employing factorized conditional probability paths.

Combinatorial and Spherical Constraints. For problems governed by strict feasibility constraints (e.g., resource allocation), Kong et al. (2026) propose *Latent Spherical Flow Policies.* They learn a stochastic flow on a compact continuous latent sphere and utilize a combinatorial optimization solver to map latent samples to valid structured actions, safely bypassing discontinuous value landscapes.

Riemannian Manifolds for Robotics. In robotic manipulation, end-effector states often reside on non-Euclidean manifolds (e.g., $SE(3)$ for orientation). Braun et al. (2024) introduce Riemannian Flow Matching Policies (RFMP), which natively incorporate geometric awareness into the vector field. Ding et al. (2025) build upon this with Stable RFMP (SRFMP), applying LaSalle's invariance principle to the flow dynamics to mathematically guarantee robust convergence to the target Riemannian distribution.

7.2 Architectural Innovations for Stability and Acceleration

Optimizing flow policies via online RL often suffers from exploding gradients when backpropagating through the multi-step ODE solver. A wave of recent architectures addresses this by reimagining the flow process itself.

Sequential Reparameterization. *SAC Flow* (Zhang et al., 2025d) introduces a paradigm shift by theoretically framing the discretized ODE integration steps as a Recurrent Neural Network (RNN). By reparam-

eterizing the flow's velocity network using modern sequential architectures like GRUs or Transformers, they eliminate the gradient instability inherent in off-policy updates. Similarly, *Reverse Flow Matching (RFM)* (Li et al., 2026) utilizes Langevin Stein operators to formulate online training as a stable posterior mean estimation problem.

Residual and Edit Policies. Instead of differentiating through the flow, several methods freeze a pre-trained flow model and learn a lightweight additive policy. *EXPO* (Dong et al., 2025) learns a Gaussian "edit policy" that shifts the base flow's actions toward high-value regions. *RFS* (Su et al., 2026) applies a similar residual steering approach for dexterous manipulation, allowing local refinement without destroying the global multimodal prior. Wan et al. (2025) adopt a related imitation learning perspective, where a simple student MLP explores the environment guided by an expressive flow-based reward model.

Single-Step Acceleration. To circumvent the inference latency of ODE solvers, *Flow Policy Mirror Descent (FPMD)* (Chen et al., 2025c) exploits the theoretical variance of straight-interpolation flows to enable robust 1-step sampling. Similarly, *One-Step Flow Q-Learning (OFQL)* (Nguyen & Yoo, 2025) and *OM2P* (Li et al., 2025) explicitly train average velocity fields (MeanFlow) that collapse the sampling trajectory into a single function evaluation.

7.3 Generative Value Estimation (Distributional RL)

While much attention is given to generative actors, recent work applies flow matching to the critic. Expanding upon the *floq* architecture (Agrawalla et al., 2025), *Distributional Flow Critic (DFC)* (Chen et al., 2025a) and *FlowCritic* (Zhong et al., 2025) parameterize the Q-function as a generative flow over the distribution of returns. This provides the expressive actor with a rich, distributional Bellman target. *EVOR* (Espinosa-Dice et al., 2025) demonstrates that combining expressive flow actors with expressive flow critics enables scalable offline RL without the compounding errors of policy distillation.

7.4 Fine-Grained Alignment and Trajectory Planning

As flow matching scales to Foundation Models, granular control over the generation process is required.

VLA and Pretraining Alignment. For Vision-Language-Action (VLA) models, Lyu et al. (2025) introduce *Flow Policy Optimization (FPO)*, integrating structure-aware credit assignment to fine-tune massive models like π_0. To ensure RL fine-tuning does not destroy the pre-trained prior, *Advantage Weighted Matching (AWM)* (Xue et al., 2025) unifies the RL objective with the original pre-training flow loss, while *GRPO-Guard* (Wang et al., 2025b) implements regulated clipping to mitigate implicit over-optimization.

Intermediate Feedback. Traditional RL alignment relies on sparse terminal rewards. *Fine-Grained GRPO* (Zhou et al., 2025) and *AC-Flow* (Fan et al., 2025a) introduce mechanisms to evaluate intermediate states along the flow trajectory, solving the temporal credit assignment problem in visual generation and preventing semantic drift.

Trajectory Generation. Finally, flow matching is proving highly effective for modeling temporally extended trajectories rather than single actions. *Generative Trajectory Policies (GTP)* (Feng et al., 2025b) learn the complete ODE solution map for full trajectories, while methods like *Extremum Flow Matching* (Rouxel et al., 2025) and Goal-Conditioned Trajectories (Diao et al., 2025) adapt flow models for offline goal-reaching. *Intention-Conditioned Flow Occupancy Models (InFOM)* (Zheng et al., 2025a) predict future state visitation probabilities, and *CtrlFlow* (Wang et al., 2025a) generates optimal trajectories bounded by non-linear Controllability Gramian matrices.

8 Comparative Analysis: Flows, Diffusion, and Gaussians

To fully contextualize the rise of flow matching in reinforcement learning, we must compare it against the two dominant paradigms it seeks to replace or improve upon: standard unimodal policies (e.g., Gaussian

actors) and diffusion-based policies. This section evaluates these families across four critical dimensions: representational expressivity, trajectory geometry, inference latency, and optimization stability. Table 3 further expands these dimensions into several concrete properties (e.g., path curvature and support bounding) that help clarify the practical differences between Gaussian, diffusion, and flow-based policies.

8.1 Representational Expressivity: The Multimodal Imperative

Classical continuous-control algorithms typically parameterize the policy as a diagonal Gaussian distribution, $\pi(a|s) = \mathcal{N}(\mu_\theta(s), \Sigma_\theta(s))$. While analytically tractable and easy to optimize via REINFORCE or reparameterization, Gaussian policies suffer from severe limitations in offline RL and multi-agent settings (Lee et al., 2025a). When a dataset contains heterogeneous, multimodal behaviors such as navigating around an obstacle by going either left or right a Gaussian policy tends to average the modes, predicting a catastrophic "mean" action (e.g., crashing directly into the obstacle).

Generative policies, both diffusion (Wang et al., 2023) and flow matching (Alles et al., 2025) solve this by learning arbitrary distributions capable of representing multiple distinct modes simultaneously. In terms of pure density estimation and expressivity, flow matching and continuous-time diffusion are theoretically equivalent, as both can universally approximate smooth target distributions. The divergence between them lies entirely in *how* they transport probability mass.

8.2 Trajectory Geometry: Stochastic SDEs vs. Deterministic ODEs

The most fundamental distinction between diffusion models and flow matching lies in the geometry of their sampling trajectories.

Diffusion Models (Stochastic Transport). Diffusion relies on a stochastic differential equation (SDE) that injects and removes Brownian noise. The path from the base distribution to the target action is inherently jagged and non-linear. While this stochasticity acts as a regularizer during image generation, it makes the sampling process in RL difficult to control and strictly binds the model to specific noise schedules (e.g., cosine or linear).

Flow Matching (Deterministic Transport). Flow matching learns a deterministic ordinary differential equation (ODE) represented by a continuous vector field. Crucially, variants like Rectified Flow (Liu, 2022; Liu et al., 2023) explicitly encourage *straight-line paths* between the noise x_0 and the target action x_1. This deterministic geometry provides two major advantages for decision-making:

1. **Support Constraints:** By eliminating SDE noise injection, flow models are less prone to drifting into out-of-distribution (OOD) action spaces. Methods like ReFORM (Zhang et al., 2026) exploit this by applying reflected boundary conditions directly to the ODE, mathematically guaranteeing that generated actions remain within the safe support of the training data.

2. **Action Consistency:** In planning (Zheng et al., 2023), deterministic paths ensure that slight perturbations in the latent noise do not result in wildly different action sequences, making temporal abstraction much easier.

8.3 Inference Latency: The NFE Bottleneck

The primary barrier to deploying generative policies in real-time robotics is inference latency, typically measured by the Number of Function Evaluations (NFE) required per environment step.

- **Diffusion Policies** often require 20 to 100 NFE to generate a single action. While fast solvers (e.g., DDIM, DPM-Solver) exist, applying them in the low-NFE regime (e.g., ≤ 5 steps) generally destroys the structural integrity of the action, leading to severe performance drops in RL benchmarks (Wang et al., 2023).

- **Flow Policies**, owing to their straight-line optimal transport paths, have local truncation errors that are vastly lower than diffusion models. Consequently, they can be solved accurately with large step sizes. Methods like FQL (Park et al., 2025) and SSCP (Koirala & Fleming, 2025) demonstrate that flow policies can be distilled or evaluated in as few as 1 to 4 NFE with minimal degradation in expected return.

For high-frequency control loops (> 50 Hz), flow matching currently offers the only viable path for deploying un-distilled generative policies.

8.4 Optimization Stability and Gradient Estimation

The final dimension of comparison is how these models interact with online reinforcement learning objectives. Updating a generative policy requires estimating the gradient of the expected return, $\nabla_\theta J(\pi_\theta)$.

In diffusion models, differentiating through an unrolled SDE sampling chain suffers from exploding variance, forcing researchers to rely on restrictive reward-weighted regression (Fan et al., 2025b) or complex contrastive forward-process bounds (Zheng et al., 2025b).

Because flow matching relies on deterministic ODEs, it provides cleaner pathways for gradient estimation. As demonstrated by PolicyFlow (Yang et al., 2026), the continuous normalizing flow formulation allows for the use of the Hutchinson trace estimator to approximate changes in the log-likelihood. This enables flow models to be optimized using standard, highly stable clipped objectives like Proximal Policy Optimization (PPO), bridging the gap between highly expressive policy parameterizations and the reliability of classical actor-critic algorithms.

8.5 Summary of Trade-offs

Table 3 summarizes these architectural trade-offs. While Gaussian policies remain the most computationally efficient, Flow Matching strictly dominates Diffusion in RL contexts by offering the same multi-modal expressivity but with vastly superior inference latency, deterministic safety bounds, and stable gradient pathways.

Property	Gaussian Policy	Diffusion Policy	Flow-Matching Policy
Expressivity	Unimodal	Highly Multimodal	Highly Multimodal
Transport Geometry	N/A	Stochastic (SDE)	Deterministic (ODE)
Path Curvature	N/A	Highly Curved	Straight (Rectified)
Inference Latency	1 NFE	20–100 NFE	1–5 NFE
Online Optimization	PPO / SAC (Stable)	High Variance	PPO / GRPO (Stable)
Support Bounding	Clipping	Difficult (Drift)	Exact (e.g., ReFORM)

Table 3: Comparative summary of policy classes in continuous reinforcement learning.

9 Open Problems and Future Directions

While flow matching has demonstrated clear advantages over diffusion models in terms of inference speed and deterministic stability, its integration with reinforcement learning is still in its infancy. In this section, we outline the most pressing theoretical and practical challenges that represent fertile ground for future research.

9.1 Principled Exploration in Deterministic Flows

The most fundamental friction between RL and flow matching lies in exploration. Standard RL relies on stochastic policies (e.g., Gaussian noise) to discover high-reward regions. However, flow matching models

learn deterministic ODEs. Current online methods address this by injecting arbitrary Gaussian noise into the ODE solver (Zhang et al., 2025c) or converting the ODE to an SDE (Liu et al., 2025a). While these heuristics work, they destroy the straight-line optimal transport properties that make flow matching efficient in the first place.

Open Problem: How can we design *exploration-aware vector fields*? Future work can investigate methods that structurally embed exploration into the flow itself; for example, by learning a distribution over vector fields (Bayesian Flow Networks) or utilizing optimistic initialization of the base distribution p_0, rather than relying on post-hoc SDE conversions that introduce noise artifacts.

9.2 Off-Policy and Continuous-Time RL Integration

Most successful online flow-matching RL algorithms, such as PolicyFlow (Yang et al., 2026) and FMPG (McAllister et al., 2025), are built on on-policy algorithms like PPO. This is because evaluating the exact likelihood of a flow-generated action is computationally heavy, making off-policy methods (which require evaluating old actions under the current policy) prohibitively slow.

Open Problem: Scaling flow matching to sample-efficient, off-policy continuous control (e.g., Soft Actor-Critic equivalents for flows) remains unsolved. Furthermore, because ODEs operate in continuous time ($t \in [0,1]$ for the flow), there is an unexplored theoretical opportunity to bridge generative flow steps with continuous-time MDPs, treating the generation process itself as a sequential decision-making problem governed by Bellman equations.

9.3 Scaling to High-Dimensional Visuomotor Control

Currently, many flow-RL benchmarks focus on state-based control or relatively simple image-based tasks. However, the ultimate goal of generative policies is to scale Vision-Language-Action (VLA) models for generalist robotics. While methods like ARFM (Zhang et al., 2025a) begin to address this, flow matching models often struggle with the "curse of dimensionality" when the state/context vector (high-res images) is vastly larger than the action vector.

Open Problem: How can we build efficient conditional flow architectures for pixel-to-action tasks? Research is needed into latent flow matching for RL, where the RL objective operates in a compressed latent space rather than the raw action space and the development of Transformer-based architectures (like DiT) specifically optimized for the high-frequency control loops required by real-world robotics.

9.4 Hardware-Aware Solvers and Single-Step Distillation

Even though flow matching requires significantly fewer Number of Function Evaluations (NFE) than diffusion, running an ODE solver for 3 to 5 steps per environment interaction is still too slow for many real-time robotic systems operating at high frequencies.

Open Problem: While algorithmic distillation techniques like SSCP (Koirala & Fleming, 2025) offer single-step generation, they may be challenged by capacity bottlenecks, losing the multimodal expressivity of the full ODE. Future directions can explore hardware-aware neural ODE solvers and progressive distillation techniques that can dynamically trade off between inference latency and action precision depending on the urgency of the robot's current state.

9.5 Alignment Beyond Scalar Rewards

As flow matching replaces diffusion in alignment tasks (RLHF) for foundation models (Zhu et al., 2025; Sun et al., 2025), the reliance on scalar reward models becomes a bottleneck. Scalar rewards often lead to mode-collapse, where the model only generates the single "safest" response.

Open Problem: Can flow matching directly optimize for multi-dimensional preferences or human-in-the-loop feedback without intermediate scalar reward models? Techniques like Preference Flow Matching (PFM) (Kim et al., 2024) hint at this by treating alignment as a transport problem from "rejected" to "preferred" dis-

tributions, but scaling this geometrically-grounded alignment to diverse reasoning and coding tasks remains an open frontier.

10 Conclusion

The integration of generative models into reinforcement learning has fundamentally expanded the capabilities of autonomous agents, allowing them to model highly complex, multimodal behaviors. As this survey demonstrates, the field is currently undergoing a critical transition from diffusion-based models to *flow matching* architectures. By replacing stochastic denoising processes with deterministic, optimal transport guided ODEs, flow matching resolves the primary bottlenecks of generative RL: it drastically reduces inference latency, provides structurally bounded generation paths, and enables stable gradient estimation for online policy optimization.

We provided a unified taxonomy to organize this rapidly expanding literature, categorizing methods along two orthogonal axes: the distribution being modeled (ranging from single-step actions to transition dynamics and critic values) and the mechanism of RL signal integration (from offline energy-weighted regression to online group relative policy optimization). This framework clarifies the deep theoretical connections between seemingly disparate algorithms, illustrating how deterministic probability transport serves as a general-purpose tool for decision-making.

While challenges remain, particularly concerning principled exploration, off-policy scaling, and hardware-aware acceleration, the trajectory of the research is clear. Flow matching may become the standard generative backbone not only for continuous control and robotics but also for the alignment of large-scale foundation models. We hope this survey serves as a conceptual foundation and a practical roadmap for researchers interested in flow matching in reinforcement learning.

Broader Impact Statement

This survey systematizes recent algorithmic advances in flow matching for reinforcement learning. While the foundational nature of this work does not directly introduce new societal risks, the algorithms discussed herein are actively used to train autonomous systems, robotics, and large language models. Improvements in the sample efficiency and alignment of these models carry dual-use implications. Ensuring that reward-guided flow models are aligned with safe and ethical human preferences, particularly as these models are deployed in physical environments or user-facing AI systems remains a critical responsibility for the research community.

References

Suzan Ece Ada, Erhan Oztop, and Emre Ugur. Diffusion policies for out-of-distribution generalization in offline reinforcement learning. *IEEE Robotics and Automation Letters*, 9(4):3116–3123, 2024.

Bhavya Kumar Agrawalla, Michal Nauman, Khush Agrawal, and Aviral Kumar. floq: Training critics via flow-matching for scaling compute in value-based rl. In *NeurIPS 2025 Workshop: Second Workshop on Aligning Reinforcement Learning Experimentalists and Theorists*, 2025.

Marvin Alles, Nutan Chen, Patrick van der Smagt, and Botond Cseke. Flowq: Energy-guided flow policies for offline reinforcement learning. *arXiv preprint arXiv:2505.14139*, 2025.

Eloi Alonso, Adam Jelley, Vincent Micheli, Anssi Kanervisto, Amos J Storkey, Tim Pearce, and François Fleuret. Diffusion for world modeling: Visual details matter in atari. *Advances in Neural Information Processing Systems*, 37:58757–58791, 2024.

Kevin Black, Michael Janner, Yilun Du, Ilya Kostrikov, and Sergey Levine. Training diffusion models with reinforcement learning. In *The Twelfth International Conference on Learning Representations*, 2024.

Max Braun, Noémie Jaquier, Leonel Rozo, and Tamim Asfour. Riemannian flow matching policy for robot motion learning. In *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5144–5151. IEEE, 2024.

Yuanjiang Cao, Quan Z. Sheng, Julian McAuley, and Lina Yao. Reinforcement learning for generative ai: A survey, 2025. URL `https://arxiv.org/abs/2308.14328`.

Chang Chen, Fei Deng, Kenji Kawaguchi, Caglar Gulcehre, and Sungjin Ahn. Simple hierarchical planning with diffusion. In *The Twelfth International Conference on Learning Representations*, 2024.

Deshu Chen, Yuchen Liu, Zhijian Zhou, Chao Qu, and Yuan Qi. Unleashing flow policies with distributional critics. *arXiv preprint arXiv:2509.23087*, 2025a.

Kaijie Chen, Zhiyang Xu, Ying Shen, Zihao Lin, Yuguang Yao, and Lifu Huang. Superflow: Training flow matching models with rl on the fly. *arXiv preprint arXiv:2512.17951*, 2025b.

Lili Chen, Shikhar Bahl, and Deepak Pathak. Playfusion: Skill acquisition via diffusion from language-annotated play. In *Conference on Robot Learning*, pp. 2012–2029. PMLR, 2023a.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

Tianyi Chen, Haitong Ma, Na Li, Kai Wang, and Bo Dai. One-step flow policy mirror descent. *arXiv preprint arXiv:2507.23675*, 2025c.

Yuhui Chen, Haoran Li, and Dongbin Zhao. Boosting continuous control with consistency policy. *arXiv preprint arXiv:2310.06343*, 2023b.

Zoey Chen, Sho Kiami, Abhishek Gupta, and Vikash Kumar. Genaug: Retargeting behaviors to unseen situations via generative augmentation. *arXiv preprint arXiv:2302.06671*, 2023c.

Cheng Chi, Siyuan Feng, Yilun Du, Zhenjia Xu, Eric Cousineau, Benjamin Burchfiel, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion. In *Robotics: Science and Systems*, 2023.

He Diao, Jingkui Zhang, Ping Zhang, and Bei Peng. Goal-conditioned trajectory generation for planning with flow matching in offline rl. In *2025 IEEE International Conference on Unmanned Systems (ICUS)*, pp. 695–701. IEEE, 2025.

Haoran Ding, Noémie Jaquier, Jan Peters, and Leonel Rozo. Fast and robust visuomotor riemannian flow matching policy. *IEEE Transactions on robotics*, 2025.

Zihan Ding and Chi Jin. Consistency models as a rich and efficient policy class for reinforcement learning. In *The Twelfth International Conference on Learning Representations*, 2024.

Perry Dong, Qiyang Li, Dorsa Sadigh, and Chelsea Finn. Expo: Stable reinforcement learning with expressive policies. *arXiv preprint arXiv:2507.07986*, 2025.

Zibin Dong, Yifu Yuan, Fei Ni, Yao Mu, YAN ZHENG, Yujing Hu, Tangjie Lv, Changjie Fan, Zhipeng Hu, et al. Aligndiff: Aligning diverse human preferences via behavior-customisable diffusion model. In *The Twelfth International Conference on Learning Representations*, 2024.

Nicolas Espinosa-Dice, Kiante Brantley, and Wen Sun. Expressive value learning for scalable offline rein-forcement learning. *arXiv preprint arXiv:2510.08218*, 2025.

Jiajun Fan, Chaoran Cheng, Shuaike Shen, Xiangxin Zhou, and Ge Liu. Fine-tuning flow matching generative models with intermediate feedback. *arXiv preprint arXiv:2510.18072*, 2025a.

Jiajun Fan, Shuaike Shen, Chaoran Cheng, Yuxin Chen, Chumeng Liang, and Ge Liu. Online reward-weighted fine-tuning of flow matching with wasserstein regularization. In *The Thirteenth International Conference on Learning Representations*, 2025b.

Jiajun Fan, Tong Wei, Chaoran Cheng, Yuxin Chen, and Ge Liu. Adaptive divergence regularized policy optimization for fine-tuning generative models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025c.

Ying Fan and Kangwook Lee. Optimizing ddpm sampling with shortcut fine-tuning. In *International Conference on Machine Learning*, pp. 9623–9639. PMLR, 2023.

Linjiajie Fang, Ruoxue Liu, Jing Zhang, Wenjia Wang, and Bingyi Jing. Diffusion actor-critic: Formulating constrained policy iteration as diffusion noise regression for offline reinforcement learning. In *The Thirteenth International Conference on Learning Representations*, 2025.

Ruiqi Feng, Chenglei Yu, Wenhao Deng, Peiyan Hu, and Tailin Wu. On the guidance of flow matching. In *International Conference on Machine Learning*, pp. 16993–17029. PMLR, 2025a.

Xinsong Feng, Leshu Tang, Chenan Wang, and Haipeng Chen. Offline reinforcement learning with generative trajectory policies. *arXiv preprint arXiv:2510.11499*, 2025b.

Giorgio Franceschelli and Mirco Musolesi. Reinforcement learning for generative ai: State of the art, opportunities and open research challenges. *Journal of Artificial Intelligence Research*, 79:417–446, 2024. doi: 10.1613/jair.1.15278. URL `https://doi.org/10.1613/jair.1.15278`.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. Pmlr, 2018.

Philippe Hansen-Estruch, Ilya Kostrikov, Michael Janner, Jakub Grudzien Kuba, and Sergey Levine. Idql: Implicit q-learning as an actor-critic method with diffusion policies. *arXiv preprint arXiv:2304.10573*, 2023.

Haoran He, Chenjia Bai, Kang Xu, Zhuoran Yang, Weinan Zhang, Dong Wang, Bin Zhao, and Xuelong Li. Diffusion model is an effective planner and data synthesizer for multi-task reinforcement learning. *Advances in neural information processing systems*, 36:64896–64917, 2023a.

Longxiang He, Li Shen, Linrui Zhang, Junbo Tan, and Xueqian Wang. Diffcps: Diffusion model based constrained policy search for offline reinforcement learning. *arXiv preprint arXiv:2310.05333*, 2023b.

Xiaoxuan He, Siming Fu, Yuke Zhao, Wanli Li, Jian Yang, Dacheng Yin, Fengyun Rao, and Bo Zhang. Tempflow-grpo: When timing matters for grpo in flow models. *arXiv preprint arXiv:2508.04324*, 2025.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Vineet Jain and Siamak Ravanbakhsh. Learning to reach goals via diffusion. In *International Conference on Machine Learning*, pp. 21170–21195. PMLR, 2024.

Michael Janner, Yilun Du, Joshua B Tenenbaum, and Sergey Levine. Planning with diffusion for flexible behavior synthesis. In *International Conference on Machine Learning*, pp. 9902–9915. PMLR, 2022.

Bingyi Kang, Xiao Ma, Chao Du, Tianyu Pang, and Shuicheng Yan. Efficient diffusion policies for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 36:67195–67212, 2023.

Fairoz Nower Khan, Nabuat Zaman Nahim, Ruiquan Huang, Haibo Yang, and Peizhong Ju. Flow matching for offline reinforcement learning with discrete actions. *arXiv preprint arXiv:2602.06138*, 2026.

Donghyeon Ki, JunHyeok Oh, Seong-Woong Shim, and Byung-Jun Lee. Prior-guided diffusion planning for offline reinforcement learning. *arXiv preprint arXiv:2505.10881*, 2025.

Minu Kim, Yongsik Lee, Sehyeok Kang, Jihwan Oh, Song Chong, and Se-Young Yun. Preference alignment with flow matching. *Advances in Neural Information Processing Systems*, 37:35140–35164, 2024.

Prajwal Koirala and Cody Fleming. Flow-based single-step completion for efficient and expressive policy learning. *arXiv preprint arXiv:2506.21427*, 2025.

Lingkai Kong, Haichuan Wang, Tonghan Wang, GUOJUN XIONG, and Milind Tambe. Composite flow matching for reinforcement learning with shifted-dynamics data. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.

Lingkai Kong, Anagha Satish, Hezi Jiang, Akseli Kangaslahti, Andrew Ma, Wenbo Chen, Mingxiao Song, Lily Xu, and Milind Tambe. Latent spherical flow policy for reinforcement learning with combinatorial actions. *arXiv preprint arXiv:2601.22211*, 2026.

Dongsu Lee, Daehee Lee, and Amy Zhang. Multi-agent coordination via flow matching. *arXiv preprint arXiv:2511.05005*, 2025a.

Jia-Hua Lee, Bor-Jiun Lin, Wei-Fang Sun, and Chun-Yi Lee. Edeline: Enhancing memory in diffusion-based world models via linear-time sequence modeling. *arXiv preprint arXiv:2502.00466*, 2025b.

Kyowoon Lee and Jaesik Choi. State-covering trajectory stitching for diffusion planners. *arXiv preprint arXiv:2506.00895*, 2025.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Steven Li, Rickmer Krohn, Tao Chen, Anurag Ajay, Pulkit Agrawal, and Georgia Chalvatzaki. Learning multimodal behaviors from scratch with diffusion policy gradient. *Advances in Neural Information Processing Systems*, 37:38456–38479, 2024.

Wenhao Li. Efficient planning with latent diffusion. In *The Twelfth International Conference on Learning Representations*, 2024.

Zeyang Li, Sunbochen Tang, and Navid Azizan. Reverse flow matching: A unified framework for online reinforcement learning with diffusion and flow policies. *arXiv preprint arXiv:2601.08136*, 2026.

Zhuoran Li, Xun Wang, Hai Zhong, and Longbo Huang. Om2p: Offline multi-agent mean-flow policy. *arXiv preprint arXiv:2508.06269*, 2025.

Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. Flow matching for generative modeling. In *The Eleventh International Conference on Learning Representations*, 2023.

Jie Liu, Gongye Liu, Jiajun Liang, Yangguang Li, Jiaheng Liu, Xintao Wang, Pengfei Wan, Di ZHANG, and Wanli Ouyang. Flow-grpo: Training flow matching models via online rl. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025a.

Kendong Liu, Zhiyu Zhu, Chuanhao Li, Hui Liu, Huanqiang Zeng, and Junhui Hou. Prefpaint: Aligning image inpainting diffusion model with human preference. *Advances in Neural Information Processing Systems*, 37:30554–30589, 2024.

Qiang Liu. Rectified flow: A marginal preserving approach to optimal transport. *arXiv preprint arXiv:2209.14577*, 2022.

Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023.

Zeyuan Liu, Zhihe Yang, Jiawei Xu, Rui Yang, Jiafei Lyu, Baoxiang Wang, Yunjian Xu, and Xiu Li. Adg: Ambient diffusion-guided dataset recovery for corruption-robust offline reinforcement learning. *arXiv preprint arXiv:2505.23871*, 2025b.

Cheng Lu, Yuhao Zhou, Fan Bao, Jianfei Chen, Chongxuan Li, and Jun Zhu. Dpm-solver: A fast ode solver for diffusion probabilistic model sampling in around 10 steps. *Advances in neural information processing systems*, 35:5775–5787, 2022.

Cheng Lu, Huayu Chen, Jianfei Chen, Hang Su, Chongxuan Li, and Jun Zhu. Contrastive energy prediction for exact energy-guided diffusion sampling in offline reinforcement learning. In *International Conference on Machine Learning*, pp. 22825–22855. PMLR, 2023a.

Cong Lu, Philip Ball, Yee Whye Teh, and Jack Parker-Holder. Synthetic experience replay. *Advances in Neural Information Processing Systems*, 36:46323–46344, 2023b.

Haofei Lu, Dongqi Han, Yifei Shen, and Dongsheng Li. What makes a good diffusion planner for decision making? In *ICLR*, 2025.

Lei Lv, Yunfei Li, Yu Luo, Fuchun Sun, Tao Kong, Jiafeng Xu, and Xiao Ma. Flow-based policy for online reinforcement learning. *arXiv preprint arXiv:2506.12811*, 2025.

Mingyang Lyu, Yinqian Sun, Erliang Lin, Huangrui Li, Ruolin Chen, Feifei Zhao, and Yi Zeng. Reinforcement fine-tuning of flow-matching policies for vision-language-action models. *arXiv preprint arXiv:2510.09976*, 2025.

Xiao Ma, Sumit Patidar, Iain Haughton, and Stephen James. Hierarchical diffusion policy for kinematics-aware multi-task robotic manipulation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18081–18090, 2024.

Zhiyuan Ma, Yuzhu Zhang, Guoli Jia, Liangliang Zhao, Yichao Ma, Mingjie Ma, Gaofeng Liu, Kaiyan Zhang, Ning Ding, Jianjun Li, and Bowen Zhou. Efficient diffusion models: A comprehensive survey from principles to practices. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 47(9): 7506–7525, 2025. doi: 10.1109/TPAMI.2025.3569700.

David McAllister, Songwei Ge, Brent Yi, Chung Min Kim, Ethan Weber, Hongsuk Choi, Haiwen Feng, and Angjoo Kanazawa. Flow matching policy gradients. *arXiv preprint arXiv:2507.21053*, 2025.

Eley Ng, Ziang Liu, and Monroe Kennedy. Diffusion co-policy for synergistic human-robot collaborative tasks. *IEEE Robotics and Automation Letters*, 9(1):215–222, 2023.

Thanh Nguyen and Chang D Yoo. Revisiting diffusion q-learning: From iterative denoising to one-step action generation. *arXiv preprint arXiv:2508.13904*, 2025.

Fei Ni, Jianye Hao, Yao Mu, Yifu Yuan, Yan Zheng, Bin Wang, and Zhixuan Liang. Metadiffuser: Diffusion model as conditional planner for offline meta-rl. In *International Conference on Machine Learning*, pp. 26087–26105. PMLR, 2023.

Seohong Park, Qiyang Li, and Sergey Levine. Flow q-learning. In *International Conference on Machine Learning*. PMLR, 2025.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

Gabriel Peyré and Marco Cuturi. *Computational optimal transport: With applications to data science*. Now Foundations and Trends, 2019.

Samuel Pfrommer, Yixiao Huang, and Somayeh Sojoudi. Reinforcement learning for flow-matching policies. *arXiv preprint arXiv:2507.15073*, 2025.

Moritz Reuss, Maximilian Li, Xiaogang Jia, and Rudolf Lioutikov. Goal-conditioned imitation learning using score-based diffusion policies. *arXiv preprint arXiv:2304.02532*, 2023.

M Rigter, J Yamada, and I Posner. World models via policy-guided trajectory diffusion. *Transactions on Machine Learning Research*, 2024(2), 2024.

Quentin Rouxel, Clemente Donoso, Fei Chen, Serena Ivaldi, and Jean-Baptiste Mouret. Extremum flow matching for offline goal conditioned reinforcement learning. In *2025 IEEE-RAS 24th International Conference on Humanoid Robots (Humanoids)*, pp. 981–988. IEEE, 2025.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Hui Shen, Jingxuan Zhang, Boning Xiong, Rui Hu, Shoufa Chen, Zhongwei Wan, Xin Wang, Yu Zhang, Zixuan Gong, Guangyin Bao, et al. Efficient diffusion models: A survey. *Transactions on Machine Learning Research (TMLR)*, 2025.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. *arXiv preprint arXiv:2010.02502*, 2020.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2021.

Yang Song, Prafulla Dhariwal, Mark Chen, and Ilya Sutskever. Consistency models. In *International Conference on Machine Learning*, pp. 32211–32252. PMLR, 2023.

Entong Su, Tyler Westenbroek, Anusha Nagabandi, and Abhishek Gupta. Rfs: Reinforcement learning with residual flow steering for dexterous manipulation. *arXiv preprint arXiv:2602.01789*, 2026.

Xiaohui Sun, Ruitong Xiao, Jianye Mo, Bowen Wu, Qun Yu, and Baoxun Wang. F5r-tts: Improving flow-matching based text-to-speech with group relative policy optimization. *arXiv preprint arXiv:2504.02407*, 2025.

Xiaolin Sun and Zizhan Zheng. Belief-enriched pessimistic q-learning against adversarial state perturbations. *arXiv preprint arXiv:2403.04050*, 2024.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction.* MIT press, 2018.

Siddarth Venkatraman, Moksh Jain, Luca Scimeca, Minsu Kim, Marcin Sendera, Mohsin Hasan, Luke Rowe, Sarthak Mittal, Pablo Lemos, Emmanuel Bengio, et al. Amortizing intractable inference in diffusion models for vision, language, and control. *Advances in neural information processing systems*, 37:76080–76114, 2024.

Cédric Villani et al. *Optimal transport: old and new*, volume 338. Springer, 2009.

Zhenglin Wan, Jingxuan Wu, Xingrui Yu, Chubin Zhang, Mingcong Lei, Bo An, and Ivor Tsang. Fm-irl: Flow-matching for reward modeling and policy regularization in reinforcement learning. *arXiv preprint arXiv:2510.09222*, 2025.

Bin Wang, Boxiang Tao, Haifeng Jing, Hongbo Dou, and Zijian Wang. Controllable flow matching for online reinforcement learning. *arXiv preprint arXiv:2511.06816*, 2025a.

Jing Wang, Jiajun Liang, Jie Liu, Henglin Liu, Gongye Liu, Jun Zheng, Wanyuan Pang, Ao Ma, Zhenyu Xie, Xintao Wang, et al. Grpo-guard: Mitigating implicit over-optimization in flow matching via regulated clipping. *arXiv preprint arXiv:2510.22319*, 2025b.

Yinuo Wang, Likun Wang, Yuxuan Jiang, Wenjun Zou, Tong Liu, Xujie Song, Wenxuan Wang, Liming Xiao, Jiang Wu, Jingliang Duan, et al. Diffusion actor-critic with entropy regulator. *Advances in Neural Information Processing Systems*, 37:54183–54204, 2024.

Zhendong Wang, Jonathan J Hunt, and Mingyuan Zhou. Diffusion policies as an expressive policy class for offline reinforcement learning. In *The Eleventh International Conference on Learning Representations*, 2023.

Changfu Xu, Jianxiong Guo, Yuzhu Liang, Haiyang Huang, Haodong Zou, Xi Zheng, Shui Yu, Xiaowen Chu, Jiannong Cao, and Tian Wang. Diffusion models for reinforcement learning: Foundations, taxonomy, and development, 2025. URL https://arxiv.org/abs/2510.12253.

Mengda Xu, Zhenjia Xu, Cheng Chi, Manuela Veloso, and Shuran Song. Xskill: Cross embodiment skill discovery. In *Conference on robot learning*, pp. 3536–3555. PMLR, 2023.

Shuchen Xue, Chongjian Ge, Shilong Zhang, Yichen Li, and Zhi-Ming Ma. Advantage weighted matching: Aligning rl with pretraining in diffusion models. *arXiv preprint arXiv:2509.25050*, 2025.

Shunpeng Yang, Ben Liu, and Hua Chen. Policyflow: Policy optimization with continuous normalizing flow in reinforcement learning. *arXiv preprint arXiv:2602.01156*, 2026.

Zhihe Yang and Yunjian Xu. Dmbp: Diffusion model-based predictor for robust offline reinforcement learning against state observation perturbations. In *ICLR*, 2024.

Takuma Yoneda, Luzhe Sun, Ge Yang, Bradly C Stadie, and Matthew R Walter. To the noise and back: Diffusion for shared autonomy. In *Robotics: Science and Systems*, 2023.

Sangwoong Yoon, Himchan Hwang, Dohyun Kwon, Yung-Kyun Noh, and Frank Park. Maximum entropy inverse reinforcement learning of diffusion models with energy-based models. *Advances in Neural Information Processing Systems*, 37:24601–24624, 2024.

Benjamin Yu, Ziyang Liu, and Justin Cui. Smart-grpo: Smartly sampling noise for efficient rl of flow-matching models. In *AAAI 2026 Workshop on Assessing and Improving Reliability of Foundation Models in the Real World*, 2026.

Tianhe Yu, Ted Xiao, Austin Stone, Jonathan Tompson, Anthony Brohan, Su Wang, Jaspiar Singh, Clayton Tan, Jodilyn Peralta, Brian Ichter, et al. Scaling robot learning with semantically imagined experience. *arXiv preprint arXiv:2302.11550*, 2023.

Yanjie Ze, Gu Zhang, Kangning Zhang, Chenyuan Hu, Muhan Wang, and Huazhe Xu. 3d diffusion policy: Generalizable visuomotor policy learning via simple 3d representations. *arXiv preprint arXiv:2403.03954*, 2024.

Xianghua Zeng, Hao Peng, Yicheng Pan, Angsheng Li, and Guanlin Wu. Structural information-based hierarchical diffusion for offline reinforcement learning. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.

Hongyin Zhang, Shiyuan Zhang, Junxi Jin, Qixin Zeng, Yifan Qiao, Hongchao Lu, and Donglin Wang. Balancing signal and variance: Adaptive offline rl post-training for vla flow models. *arXiv preprint arXiv:2509.04063*, 2025a.

Lunjun Zhang, Yuwen Xiong, Ze Yang, Sergio Casas, Rui Hu, and Raquel Urtasun. Copilot4d: Learning unsupervised world models for autonomous driving via discrete diffusion. In *The Twelfth International Conference on Learning Representations*, 2024.

Shiyuan Zhang, Weitong Zhang, and Quanquan Gu. Energy-weighted flow matching for offline reinforcement learning. In *The Thirteenth International Conference on Learning Representations*, 2025b.

Songyuan Zhang, Oswin So, HM Ahmad, Eric Yang Yu, Matthew Cleaveland, Mitchell Black, and Chuchu Fan. Reform: Reflected flows for on-support offline rl via noise manipulation. *arXiv preprint arXiv:2602.05051*, 2026.

Tonghe Zhang, Chao Yu, Sichang Su, and Yu Wang. Reinflow: Fine-tuning flow matching policy with online reinforcement learning. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025c.

Yixian Zhang, Shu'ang Yu, Tonghe Zhang, Mo Guang, Haojia Hui, Kaiwen Long, Yu Wang, Chao Yu, and Wenbo Ding. Sac flow: Sample-efficient reinforcement learning of flow-based policies via velocity-reparameterized sequential modeling. *arXiv preprint arXiv:2509.25756*, 2025d.

Zhilong Zhang, Yihao Sun, Junyin Ye, Tian-Shuo Liu, Jiaji Zhang, and Yang Yu. Flow to better: Offline preference-based reinforcement learning via preferred trajectory generation. In *The Twelfth International Conference on Learning Representations*, 2023.

Chongyi Zheng, Seohong Park, Sergey Levine, and Benjamin Eysenbach. Intention-conditioned flow occupancy models. *arXiv preprint arXiv:2506.08902*, 2025a.

Kaiwen Zheng, Huayu Chen, Haotian Ye, Haoxiang Wang, Qinsheng Zhang, Kai Jiang, Hang Su, Stefano Ermon, Jun Zhu, and Ming-Yu Liu. Diffusionnft: Online diffusion reinforcement with forward process. *arXiv preprint arXiv:2509.16117*, 2025b.

Qinqing Zheng, Matt Le, Neta Shaul, Yaron Lipman, Aditya Grover, and Ricky TQ Chen. Guided flows for generative modeling and decision making. *arXiv preprint arXiv:2311.13443*, 2023.

Yinan Zheng, Jianxiong Li, Dongjie Yu, Yujie Yang, Shengbo Eben Li, Xianyuan Zhan, and Jingjing Liu. Safe offline reinforcement learning with feasibility-guided diffusion model. In *The Twelfth International Conference on Learning Representations*, 2024.

Yinan Zheng, Ruiming Liang, Kexin ZHENG, Jinliang Zheng, Liyuan Mao, Jianxiong Li, Weihao Gu, Rui Ai, Shengbo Eben Li, Xianyuan Zhan, et al. Diffusion-based planning for autonomous driving with flexible guidance. In *The Thirteenth International Conference on Learning Representations*, 2025c.

Shan Zhong, Shutong Ding, He Diao, Xiangyu Wang, Kah Chan Teh, and Bei Peng. Flowcritic: Bridging value estimation with flow matching in reinforcement learning. *arXiv preprint arXiv:2510.22686*, 2025.

Ziyuan Zhong, Davis Rempe, Danfei Xu, Yuxiao Chen, Sushant Veer, Tong Che, Baishakhi Ray, and Marco Pavone. Guided conditional diffusion for controllable traffic simulation. In *2023 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3560–3566. IEEE, 2023.

Yujie Zhou, Pengyang Ling, Jiazi Bu, Yibin Wang, Yuhang Zang, Jiaqi Wang, Li Niu, and Guangtao Zhai. Fine-grained grpo for precise preference alignment in flow models. *arXiv preprint arXiv:2510.01982*, 2025.

Xuekai Zhu, Daixuan Cheng, Dinghuai Zhang, Hengli Li, Kaiyan Zhang, Che Jiang, Youbang Sun, Ermo Hua, Yuxin Zuo, Xingtai Lv, et al. Flowrl: Matching reward distributions for llm reasoning. *arXiv preprint arXiv:2509.15207*, 2025.

Zhengbang Zhu, Hanye Zhao, Haoran He, Yichao Zhong, Shenyu Zhang, Haoquan Guo, Tingting Chen, and Weinan Zhang. Diffusion models for reinforcement learning: A survey, 2024. URL https://arxiv.org/abs/2311.01223.

A Diffusion-Based Reinforcement Learning

A.1 Overview of Diffusion in RL methods

Most diffusion-RL methods can be organized by **what object is generated** and **how RL objectives enter**:

(1) Diffusion as a planner (trajectory / action-sequence generation). Here, the model generates an entire sequence of future states and actions $\tau = (s_t, a_t, \ldots, s_{t+H}, a_{t+H})$ simultaneously, treating planning as a data imputation problem. A canonical instance is Janner et al. (2022) introducing *Diffuser*, which uses a temporal U-Net to denoise full trajectories, guiding the process with separate reward classifiers. Subsequent works study planner design choices and extensions such as hierarchical diffusion planning, latent-space planning, trajectory stitching, and prior/guidance mechanisms (Chen et al., 2024; Li, 2024; Lu et al., 2025; Zeng et al., 2025; Ki et al., 2025; Lee & Choi, 2025; Ni et al., 2023). Diffusion planners have also been explored in domains like autonomous driving and traffic simulation (Zheng et al., 2025c; Zhong et al., 2023).

(2) Diffusion as a policy (one-step action generation). These methods use the diffusion model strictly as a conditional policy $\pi(a|s)$, generating a single action a_t given the current state s_t. In offline RL, *Diffusion-QL* (Wang et al., 2023) and *IDQL* (Hansen-Estruch et al., 2023) combine diffusion actors with Q-learning critics to handle multi-modal datasets without the extrapolation error of standard behavior cloning, with many variants targeting robustness and generalization (Ada et al., 2024; Yang & Xu, 2024; Liu et al., 2025b; Sun & Zheng, 2024). In robotics, action diffusion has become a popular policy class for visuomotor control and multi-task manipulation, including extensions to 3D and hierarchical policies (Chi et al., 2023; He et al., 2023a; Ze et al., 2024; Ma et al., 2024).

(3) Diffusion for constrained/safe RL (feasibility and constraints). Several papers incorporate safety/feasibility constraints into the generative process, either as explicit guidance signals or via constrained policy optimization formulations (Fang et al., 2025; Zheng et al., 2024; He et al., 2023b).

(4) Diffusion for imitation learning, skills, and human-in-the-loop control. Beyond offline RL benchmarks, diffusion models are used for goal-conditioned imitation and skill learning, shared autonomy, and human-robot collaboration (Reuss et al., 2023; Jain & Ravanbakhsh, 2024; Yoneda et al., 2023; Ng et al., 2023; Chen et al., 2023a; Xu et al., 2023). Data augmentation and behavior retargeting via generative models is another recurring theme (Chen et al., 2023c; Lu et al., 2023b; Yu et al., 2023).

(5) Diffusion for world models and environment simulation. Diffusion can be used as a dynamics/world model that generates plausible futures, especially in partially observed or visually rich settings. Representative examples include diffusion world modeling in Atari and improved memory/imagination consistency in diffusion world models (Alonso et al., 2024; Lee et al., 2025b; Rigter et al., 2024; Zhang et al., 2024).

(6) Diffusion + preference/reward modeling and RL fine-tuning. A parallel line uses RL-style training to align diffusion models with preferences or task rewards. Examples include preference/customization for diffusion models and reward-driven training pipelines (Dong et al., 2024; Black et al., 2024; Liu et al., 2024; Yoon et al., 2024; Zhang et al., 2023). (These works are conceptually close to RLHF-style alignment, but appear in diffusion-RL bibliographies because they explicitly optimize diffusion generation using RL signals.)

A.2 How RL objectives enter diffusion models: training-time vs sampling-time

A second critical distinction is **when** the RL objective (reward/value signal) is applied:

Training-time integration. Some methods incorporate RL signals directly into learning (e.g., value-weighted objectives, constrained updates, or actor-critic training with diffusion as the policy class), including diffusion actor-critic variants and diffusion policy-gradient style training (Wang et al., 2024; Li et al., 2024; Fang et al., 2025).

Sampling-time guidance. Other methods keep the base diffusion model fixed and bias denoising using an external score/energy/value signal. Energy-guided diffusion for offline RL is a key example (Lu et al., 2023a). Related guidance ideas appear in planning settings (e.g., prior-guided planning and flexible guidance in driving) (Ki et al., 2025; Zheng et al., 2025c).

A.3 Efficiency and fast sampling

A core deployment issue is that diffusion control is often *too slow* if many denoising steps are needed per environment step. Accordingly, diffusion-RL papers frequently adopt faster samplers/solvers and/or distill the reverse process. Learning-free accelerations include DDIM (Song et al., 2020) and high-order ODE solvers such as DPM-Solver (Lu et al., 2022). Learning-based acceleration includes shortcut/few-step training and distillation methods such as consistency-style objectives and policy classes (Song et al., 2023; Ding & Jin, 2024; Chen et al., 2023b; Fan & Lee, 2023). For offline RL specifically, efficiency-driven diffusion policy

variants reduce backpropagation through long chains or approximate sampling during training (Kang et al., 2023; Venkatraman et al., 2024).

A.4 From Diffusion to Flow Matching

Despite their expressivity, diffusion models face deployment challenges in control:

1. **Inference Latency:** Standard diffusion policies require 10–100 denoising steps to generate a single action. While fast solvers like DDIM (Song et al., 2020) or DPM-Solver (Lu et al., 2022) reduce this, they often degrade sample quality in low-step regimes (e.g., < 5 steps).

2. **Stochasticity vs. Control:** The stochastic nature of the reverse process (SDE) complicates the use of precise solvers and makes it difficult to guarantee smooth control updates.

These limitations specifically the conflict between high-quality generation and real-time inference speed directly motivate the adoption of **Flow Matching in RL**, which we detail in this survey. Flow Matching offers the expressivity of diffusion but with deterministic, straight-line trajectories that enable faster and more stable policy learning.