When More Becomes Less:
A Two-Probe Diagnostic for Repetition in Language Models

Abstract

Cloze-style probes that vary how often a target token appears implicitly assume that more copies of a target affect prediction the same way regardless of where the readout slot sits. We show this assumption fails. Our two-probe diagnostic holds a repeated-target prefix fixed and varies only the readout position: the *adjacent* probe places the slot immediately after the repeated block; the *displaced* probe places it inside a fresh sentence frame. Adjacent repetition behaves as priming intuition predicts: $P(\text{target})$ climbs with N and plateaus. Displaced repetition produces an inverted-U: $P(\text{target})$ rises to an early peak and then declines as more copies are added. The displaced inverted-U shows a per-word drop with bootstrap CI excluding zero in all 13 open-access encoder and decoder models we test, and replicates across Spanish, Chinese, German, and French in 42 of 42 multilingual cells. A six-condition causal ablation isolates the effect to exact lexical repetition rather than length, generic redundancy, or semantic-neighbour exposure. A frame-pragmatics control rules out an artifact of the readout frame. Internally, per-target-token attention falls with N while the total budget assigned to the repeated block grows in causal LMs but not in the masked LM we probe. Probes that vary repetition count cannot treat the readout position as orthogonal to what they measure.

1 Introduction

A common pattern in cloze-style probing studies of language models (Petroni et al., 2019; Ettinger, 2020) is to read the model's prediction at a single slot, typically the next-token position after the controlled material in the prompt. When such a probe also varies how often a target token appears, the implicit assumption is that the readout position is orthogonal to what repetition does: that whatever effect more copies have on prediction is the same effect regardless of where the prediction slot

sits relative to the repeated block. We show this assumption fails. Hold the repeated-target prefix fixed and the same prefix produces opposite curves at two readout positions: priming plateaus adjacent to the block, retrieval reverses one clause later.

The diagnostic is a minimal pair (Figure 1). We hold a repeated-target prefix fixed and vary only where the prediction slot lies. The *adjacent* probe places the slot directly after the block; the *displaced* probe moves it into a fresh sentence frame. Adjacent priming plateaus. Displaced retrieval reverses. The dissociation shows the displaced effect is non-additive aggregation, not long-context capacity loss: the adjacent baseline confirms local continuation is still available under the same prefix.

Figure 1: **Two-probe design.** (a) The *adjacent* probe places the prediction slot directly after a prefix of N target copies. (b) The *displaced* probe shares the same prefix but moves the slot into a fresh clause via one of five sentence frames F0–F4. The framework applies identically to masked LMs (slot is `[MASK]`) and to causal LMs (slot is the next-token position).

All 13 models show positive per-word drops with CI excluding zero (Table 1); 12 of 13 also show mean-curve inversion before $N{=}30$. SmolLM2-1.7B is the only checkpoint whose population-mean curve continues to climb through $N{=}30$, while its per-word drops remain positive (0.138 $[0.114, 0.164]$). The secondary observation fails but the headline statistic does not. The cleanest within-thesis illustration is a truncation contrast: when the displaced peak sits near $N{=}3$, cutting

the prefix from $N{=}30$ back down to $N{=}3$ raises target probability with the bootstrap interval clearing zero in two of four causal-ablation models (ModernBERT-large $+0.034$ $[0.016, 0.056]$, rank $35 \rightarrow 7$; Qwen2.5-1.5B $+0.059$ $[0.046, 0.072]$, rank $75 \rightarrow 7$). Qwen2.5-7B goes in the same direction with a CI that barely overlaps zero ($+0.015$, $[-0.005, 0.035]$).

A six-condition causal ablation pins the effect to *exact* lexical repetition: length-matched random fillers and unrelated-token repetition flatten $P(\text{target})$, and semantic-neighbour fillers activate the target's semantic field (raising $\Sigma P(\text{synonyms})$ to 0.32 in ModernBERT-large) without lifting $P(\text{target})$ itself above roughly 0.03 (max 0.031 in ModernBERT-large). The same shape replicates on four multilingual models across Spanish, Chinese, German, and French. Internally, the per-target-token attention each repeated copy receives falls with N while the *total* attention budget the model assigns to the repeated block grows. The block as a whole captures a larger share of attention even as the per-copy mass shrinks.

Our primary contribution is methodological: a matched-prefix two-probe design that separates local pattern continuation from displaced retrieval, applicable to any controlled probing study of repeated content. The empirical finding our diagnostic makes visible (that current open-access models fail to aggregate exact lexical repetition additively at displaced slots) is the second contribution, validated by a four-language replication, a six-condition specificity check on the repeated block, a frame-pragmatics control on the readout frame, and an internal correlate in the attention-budget dynamics of three CLMs.

2 Related Work

Most prior work on repetition in language models has been about the model's output: degenerate loops under greedy or beam decoding (Holtzman et al., 2020; Welleck et al., 2020; Xu et al., 2022), and the role of multiple demonstrations in in-context learning (Min et al., 2022; Agarwal et al., 2024). We are asking about the input side instead: how the model's predictions change when the prompt is repetitive.

Several lines bear on what repeated tokens do to Transformer-based language models on the input side. Barbero et al. (2024) prove a representational-collapse result for repeated decoder-only inputs;

Yona et al. (2025) characterise a "repeated-token divergence" phenomenon and link it to attention-sink dynamics; attention sinks themselves (Xiao et al., 2024; Gu et al., 2025) have been characterised as positions that accumulate disproportionate attention mass. Our block-budget growth shares the flavour of the attention-sink line, but appears under a different setup (a span at the source side under displaced readout, rather than initial tokens carried across all queries), and we stop short of claiming it is the same mechanism. None of this prior work asks our question, which is whether the *position of the readout slot relative to the repeated block* changes what repetition does to retrieval. The experimental object here is a behavioural dissociation between two probe positions under a matched prefix.

Other prompt-side phenomena include "lost in the middle" effects under long prompts (Liu et al., 2024), prompt-format and prompt-order sensitivity in in-context-learning benchmarks (Lu et al., 2022; Sclar et al., 2024), and retrieval-augmented generation and open-domain QA pipelines that invite exact and near-exact repetition by concatenating passages sharing an entity, an answer string, or a source document (Lewis et al., 2020; Karpukhin et al., 2020; Izacard and Grave, 2021).

Methodologically our paper is closest to the cloze-probe tradition (Petroni et al., 2019; Ettinger, 2020; Misra et al., 2020; Hu and Levy, 2023), but with a *displaced* slot that dissociates surface continuation from across-clause retrieval, and with the framework extended to causal LMs by replacing `[MASK]` with the next-token position. The repetition schedule in our prefix is conceptually inspired by the psycholinguistic literature on semantic satiation (Smith, 1984; Black, 2001; Tian and Huber, 2010), but we do not claim a human-fatigue mechanism.

3 Experimental Design

3.1 Two-probe framework

Both probes use the same N grid $N \in \{0, 1, 3, 5, 10, 20, 30\}$ and a shared repeated-target prefix; only the readout slot differs. ($N{=}0$ is the prior-only baseline; all reported statistics use $N \geq 1$.) The *adjacent* probe is `<target × N> [MASK] .` for masked-LM models (MLM) or `<target × N>` for causal-LM models (CLM) at the next-token slot. The *displaced* probe is `<target × N> .`

`<frame>` [MASK] . (MLM) or `<target ×`
`N>` . `<frame>` (CLM). We test five English
declarative-style frames F0–F4 (Appendix A). The
adjacent probe is evaluated on a three-model base-
line (ModernBERT-base, Qwen2.5-1.5B, Qwen2.5-
7B) as a sanity check that local continuation re-
mains available; the displaced grid is evaluated on
every panel model. A decline at the displaced slot
therefore cannot be reduced to local capacity loss;
the adjacent baseline establishes that local continu-
ation is intact.

A short vocabulary note. *Displaced retrieval*
names the readout condition just defined; *adjacent
retrieval* names the matched local-continuation con-
trol. The label *satiation-like* is used only for per-
word curves whose shape clears the deterministic
thresholds of Appendix B. Both *satiation-like* and
non-additive aggregation describe curve shape at
the displaced slot, not internal mechanism.

3.2 Targets and tokenisation

The English target set is 261 hand-curated single-
token noun candidates balanced over concreteness
and Zipf frequency (Speer, 2022); per-tokeniser fil-
tering yields per-model sets of 182–258 words and
a shared core of ≈ 168 words that enters the head-
line regression. Construction details (cell balance,
semantic-class breakdown, per-family overlap) are
in Appendix A.

3.3 Open-access panel

We probe 13 open-access language models, all
loadable without authentication. Two encoders
use the masked-LM objective (ModernBERT-base,
ModernBERT-large (Warner et al., 2025)) and
eleven decoders use the causal-LM objective. The
Qwen2.5 family (Qwen Team, 2025) provides a
within-family scale ladder (0.5B, 1.5B, 3B, 7B,
14B, plus the 7B-Instruct variant). Cross-family
checks include SmolLM2 at 360M and 1.7B (Ben
Allal et al., 2025), Phi-3.5-mini at 3.8B (Abdin
et al., 2024), and OLMo-2 at 1B and 7B (OLMo
Team, 2025). Hardware, dtype, and prompt-format
details (including evaluating instruction-tuned vari-
ants on the raw prompt rather than the chat tem-
plate) are in Appendix I.

3.4 Metrics and statistics

Our *headline statistic* is the per-word drop
$(\mathrm{peak}_w - P(N{=}30)_w)/\mathrm{peak}_w$ with the peak taken
over $N \in \{1, 3, 5, 10, 20, 30\}$, bootstrapped at
the word level; throughout, "the per-word drop

is positive" means the bootstrap CI excludes zero.
Alongside it we report mean-curve inversion before
$N{=}30$ as a *secondary descriptive observation*; it
is more sensitive to peak location and so is weaker
evidence than the per-word drop. We also run an
OLS quadratic of $\log P(\mathrm{target})$ on N, N^2, Zipf fre-
quency, model, frame, and word category, with SEs
clustered by target word; signs and significance of
β_N and β_{N^2} are the cross-model summary. For
ablations and the mechanism probes we also record
the target's rank, entropy, $\Sigma P(\mathrm{synonyms})$ over a
curated semantic field, and $\Sigma P(\mathrm{unrelated\ pool})$. A
separate deterministic classifier labels per-(model,
frame, word) curves as *satiation-like*, *monotonic-
priming*, *plateau*, or *mixed*; thresholds and the full
regression are in Appendix B.

4 Probe Position Reverses Repetition Dynamics

4.1 Adjacent vs displaced: the dissociation

On the adjacent slot the three baseline models be-
have broadly as a priming account would predict.
$P(\mathrm{target})$ climbs with N and plateaus by $N \approx 20$
(Figure 2a), and the MLM never registers a single
satiation-like word. Move the slot off the repeated
block (same prefix, different probe position) and
the curve no longer climbs. It rises through an early
peak and falls back by $N{=}30$ (Figure 2b,c) in 12
of 13 panel models; per-word drops clear zero in
all 13 (§4.2). Because the adjacent baseline shows
that local continuation remains available, the dis-
placed decline cannot be read as generic capacity
loss; it has to be about the slot. This is the shape
we will refer to as *non-additive aggregation* at the
displaced slot: adding more exact copies of the
target does not monotonically add to its probability
at a readout that sits one clause beyond the block.

4.2 Panel-wide displaced result

F0 drops on the full panel range from 0.138
[0.114, 0.164] in SmolLM2-1.7B to 0.733
[0.706, 0.761] in Qwen2.5-14B (Table 1). Every
per-word drop has a bootstrap interval that clears
zero. This is our primary result: the displaced
inverted-U is a 13-of-13 effect under the per-word
statistic we adopt as primary. The five-fold spread
across the panel is large in magnitude but uniform
in sign: every model shows the inverted-U, only
the strength varies, and the ranking-by-magnitude
(Phi-3.5-mini and Qwen2.5-14B at the top,
SmolLM2 at the bottom) does not align cleanly

Figure 2: **Same prefix, different probe position.** (a) Adjacent baseline on three models: priming, plateau by $N\approx20$. (b) Displaced probe (F0), five representative models spanning the panel's peak-N range. Solid: MLM; dashed: CLM. (c) Peak-normalised P(target) across all 13 panel models, rows sorted by F0 drop magnitude; white dot marks each row's peak N. Per-model numbers in Table 1.

with parameter count.

As a secondary descriptive observation, 12 of 13 mean curves also turn over before $N{=}30$, with per-model peaks at $N \in \{1, 3, 5, 10, 20\}$; the exception is SmolLM2-1.7B, whose per-word drops remain positive (0.138 $[0.114, 0.164]$) but whose population-mean curve continues to climb. We treat the per-word statistic as primary because it does not assume a single peak location across heterogeneous targets: a curve that peaks at $N{=}3$ and a curve that peaks at $N{=}20$ contribute equally to the per-word drop, but only the early-peak curve registers as an inversion under any single-peak summary.

Frame heterogeneity. Across F0–F4 the per-word drop is reliably positive in all 65 of 65 (model, frame) cells. The 13-model mean drop is also tightly clustered (F0 0.460, F1 0.451, F2 0.483, F3 0.458, F4 0.434), so the main result does not hinge on which frame we single out. F0 is among the larger frames, but no single frame dominates. The ≈ 5 percentage-point spread across frames is small next to the ≈ 60 percentage-point spread across models on F0, so frame phrasing is a much weaker source of variance than model architecture.

Panel-level regression check. A cross-model OLS quadratic on shared-core cells reproduces the inverted-U at the panel level: $\beta_N = +0.212$ and $\beta_{N^2} = -0.00610$ ($|t| > 36$ under SEs clustered by target word, implied vertex $N^* \approx 17.4$).[1] A Zipf-confound regression finds a small reliable frequency effect on per-word drop, but (model, frame) fixed effects out-explain it by $\approx 60\times$: frequency modulates, it does not drive. Full coefficient tables,

the cluster-robust panel regression, and the deterministic curve classifier underlying the *satiation-like* share are in Appendix B, Tables 3–4.

Scale heterogeneity. Scale within the Qwen2.5 family is not a monotone driver of magnitude: F0 drops at the six sizes are 0.329, 0.693, 0.434, 0.461, 0.733, and 0.549 for 0.5B, 1.5B, 3B, 7B, 14B, and 7B-Instruct, with 1.5B and 14B at the top of the family and 0.5B and 7B-base near the bottom. Instruction tuning at 7B *increases* the drop ($0.461 \rightarrow 0.549$) in every one of the five frames (Table 5). Cross-family magnitudes fall within the Qwen envelope (Phi-3.5-mini 0.523; OLMo-2 $0.434/0.426$; SmolLM2 $0.327/0.138$), so the inverted-U appears at every scale we test, but its magnitude is not a clean function of size. SmolLM2-1.7B is the only checkpoint whose mean displaced curve does not visibly invert through $N{=}30$; its per-word drops are still positive, and a within-family depth-vs-width comparison in Appendix C does not yield a clean account of the exception.

4.3 Truncation contrast

If the displaced curve really turns over before $N{=}30$, then truncating the prefix back toward each model's per-word peak ought to raise P(target). The most direct version of the test is peak-relative: cut to each model's own peak N. We run the test on the four-model probe subset used throughout for ablation and mechanism (ModernBERT-large, Qwen2.5-1.5B, Qwen2.5-7B, OLMo-2-7B). As a check on robustness we also run a fixed cut to $N{=}3$, which serves as a stand-in for the peak in three of these four whose displaced peak in fact sits at or near $N{=}3$ (ModernBERT-large at $N{=}1$, Qwen2.5-1.5B and Qwen2.5-7B at $N{=}5$).

---

[1]An average-trajectory vertex, not any individual model's peak.

Model	Obj.	Peak N	Peak P	$P(N{=}30)$	Drop	95 % CI of drop
Qwen2.5-14B (Qwen Team, 2025)	CLM	3	0.223	0.065	0.733	[0.706, 0.761]
Qwen2.5-1.5B (Qwen Team, 2025)	CLM	5	0.125	0.062	0.693	[0.654, 0.733]
Qwen2.5-7B-Instruct (Qwen Team, 2025)	CLM	10	0.209	0.155	0.549	[0.507, 0.592]
Phi-3.5-mini (Abdin et al., 2024)	CLM	1	0.001	0.000	0.523	[0.485, 0.558]
ModernBERT-base (Warner et al., 2025)	MLM	3	0.668	0.372	0.516	[0.481, 0.549]
Qwen2.5-7B (Qwen Team, 2025)	CLM	5	0.134	0.106	0.461	[0.422, 0.502]
Qwen2.5-3B (Qwen Team, 2025)	CLM	3	0.109	0.040	0.434	[0.397, 0.477]
OLMo-2-1B (OLMo Team, 2025)	CLM	20	0.039	0.033	0.434	[0.387, 0.472]
OLMo-2-7B (OLMo Team, 2025)	CLM	10	0.058	0.042	0.426	[0.385, 0.468]
ModernBERT-large (Warner et al., 2025)	MLM	1	0.400	0.260	0.423	[0.388, 0.462]
Qwen2.5-0.5B (Qwen Team, 2025)	CLM	3	0.187	0.132	0.329	[0.294, 0.363]
SmolLM2-360M (Ben Allal et al., 2025)	CLM	20	0.113	0.100	0.327	[0.291, 0.367]
SmolLM2-1.7B (Ben Allal et al., 2025)	CLM	30	0.101	0.101	0.138	[0.114, 0.164]

Table 1: Displaced-probe F0 summary across the open-access panel (per-model target sets of 182–258 single-token-valid words). *Peak N*, *Peak P* from the word-averaged mean curve; $P(N{=}30)$ the same curve at $N{=}30$. *Drop* is the per-word mean of $(\text{peak}_w - P(N{=}30)_w)/\text{peak}_w$; 95 % CI bootstrapped over words (500 resamples, seed 42). Every model has positive drop with CI excluding zero; SmolLM2-1.7B weakest, Qwen2.5-14B strongest.

Peak-relative cut. The per-word contrast $P(\text{target} \mid N{=}\text{peak}) - P(\text{target} \mid N{=}30)$ is positive on all four probe models, with bootstrap intervals clearing zero: $+0.141\ [+0.114, +0.169]$ on ModernBERT-large ($N{=}30 \rightarrow 1$), $+0.063$ $[+0.050, +0.076]$ on Qwen2.5-1.5B ($N{=}30 \rightarrow 5$), $+0.028$ $[+0.011, +0.047]$ on Qwen2.5-7B ($N{=}30 \rightarrow 5$), and $+0.016\ [+0.010, +0.023]$ on OLMo-2-7B ($N{=}30 \rightarrow 10$). This is not a new experiment so much as a sharper read of the same per-N grid that produced Table 1.

Fixed $N{=}3$ cut (sensitivity). The same contrast at the hard-coded $N{=}3$ point confirms two of four cases directly: ModernBERT-large gains $+0.034\ [0.016, 0.056]$ with the target's rank improving from 35 to 7, and Qwen2.5-1.5B gains $+0.059\ [0.046, 0.072]$ with rank $75 \rightarrow 7$. Qwen2.5-7B moves in the same direction in point estimate ($+0.015$, rank $10 \rightarrow 4$) but its CI $[-0.005, 0.035]$ marginally crosses zero. OLMo-2-7B's fixed-$N{=}3$ contrast is $-0.015\ [-0.022, -0.009]$, a real negative, but only because its displaced peak sits at $N{=}10$, so the fixed cut overshoots in the other direction. The truncation prediction the inverted-U makes is "cut the prefix back near the peak and $P(\text{target})$ goes up", not "$N{=}3$ is privileged": under the peak-relative reading OLMo-2-7B is no longer exceptional, and the panel pattern is uniform.

4.4 Cross-lingual replication

A reasonable concern after the English panel is that the displaced inverted-U could be English-specific, or specific to WordPiece-like tokenisa-

tion, or specific to the particular English frames we use. The most straightforward way to rule those out is to rerun the displaced probe unchanged in different languages and on tokenisers that do not look like WordPiece. We probe four open-access multilingual checkpoints (XLM-R-base, XLM-R-large (Conneau et al., 2020), Qwen2.5-1.5B, and Qwen2.5-7B (Qwen Team, 2025)) on Spanish, Chinese, German, and French single-token noun lists, using three hand-translated frames per language and $n_w{=}28$–49 per (model, language) cell. XLM-R's BPE retains no Chinese single-token candidates after filtering, so XLM-R Chinese drops out for both base and large; what remains is fourteen (model, language) combinations and 42 (model, language, frame) cells in total (Figure 3).

Every one of those 42 cells shows a positive per-word drop with its bootstrap interval clearing zero, and 30 of 42 also turn the mean curve over before $N{=}30$. The twelve cells whose mean curve peaks at $N{=}30$ split cleanly into two groups: five are Qwen2.5 cells (1.5B on German F2, French F1, French F2; 7B on German F2 and French F2), and seven are XLM-R-large cells (all six of its non-German cells plus German F0); their per-word drops are still positive. Magnitude in Spanish is large but spread, with F0 drops between 0.308 (XLM-R-large) and 0.853 (Qwen2.5-1.5B); German (0.354–0.814), French (0.443–0.823), and Chinese (0.435 Qwen2.5-7B / 0.481 Qwen2.5-1.5B) span similar ranges. We do not attempt a strong typological reading of the language-by-language ordering: whether the magnitude differences reflect tokeniser choices, morphological richness, or particular frame translations cannot be re-

Figure 3: **Cross-lingual replication of the displaced inverted-U.** Per-word drop magnitude on the displaced probe for four open-access multilingual checkpoints across four target languages and three hand-translated frames. Each cell averages over 28–49 single-token nouns; all 42 evaluated cells have bootstrap CIs that exclude zero. XLM-R Chinese cells (n/a) drop out because XLM-R's BPE retains no Chinese single-token candidates after filtering. Per-(model, language, frame) numbers are in Appendix F, Table 8.

solved by this panel. What we can conclude is that the displaced inverted-U is not an artefact of any one of those three factors, since the shape recurs on two multilingual MLMs and two multilingual CLMs, in four typologically different target languages, every cell we measured. Per-(model, language, frame) numbers are in Appendix F, Table 8.

5 Exact Lexical Repetition Drives the Effect

What in the prefix is doing the work? We swap the $N{=}30$ target block for five alternatives on the F0 displaced probe: a truncated $N{=}3$ repeat of the same target, no block at all, a length-matched random filler, a semantic-neighbour filler, and an unrelated-repeat block (`'table'` $\times 30$; constructions in Appendix D).

Four of the five swaps eliminate the effect. Random filler, deletion, and the unrelated-repeat block all push $P(\text{target})$ below 10^{-3} on all four ablation models. The interesting case is the semantic-neighbour filler. It is the only condition that *activates* the target's semantic field: $\Sigma P(\text{synonyms})$ climbs to 0.316 in ModernBERT-large and to 0.10–0.16 in the three CLMs (Figure 4a,b). But $P(\text{target})$ itself stays at 0.012–0.031, well below the full-repeat range of 0.042–0.260. Semantic-field activation and target-specific priming come apart cleanly. The dissociation is order-of-magnitude: under full repetition, $P(\text{target})$ exceeds $\Sigma P(\text{synonyms})$ by 7–36$\times$; under semantic-neighbour fill, the ratio reverses, with $\Sigma P(\text{synonyms})$ exceeding $P(\text{target})$ by 8–13$\times$. Whatever the displaced inverted-U is, it is not driven by sequence length, not by repetition in general, and not by exposure to neighbours of

the target. It is exact lexical repetition of the target itself, interacting with the displaced readout. That isolates the source side of the displaced probe.

Frame pragmatics. The displaced probe also carries a frame, and F0–F4 all introduce a word, so the inverted-U might track the frame's pull toward a *new* word rather than non-additive aggregation. Fixing the block and varying only the frame's pragmatic class on the four-model subset rules this out: the per-word drop clears zero in all 16 (model, class) cells; anaphoric frames that *demand* the repeated word still invert in every model, and novelty frames are the largest-drop class in none (Appendix E).

6 Internal Correlates

The behavioural picture is established; the next question is what inside the model moves alongside it. We run two attention probes and a slot-state probe on four panel models chosen to span both objectives and three scales: ModernBERT-large, Qwen2.5-1.5B, Qwen2.5-7B, and OLMo-2-7B. These probes are correlational (Belinkov, 2022): we record internal patterns that co-move with the behavioural effect, and do not attempt to adjudicate among mechanisms that produce the same co-movement.

Two terms recur below. We call per-target-token attention staying *above* its $1/N$ baseline *sub-dilution*: the block holds more attention than equal division across N keys would predict. We call per-token attention falling *below* the $1/N$ baseline *super-dilution*: the block sheds attention faster than equal division would predict.

Figure 4: **Six-condition causal ablation, F0 displaced, four models** (shared legend below). (a) Mean $P(\text{target})$ per condition, 95% bootstrap CIs. (b) $\Sigma P(\text{synonyms})$ per condition. (c) Mean target rank (log scale) per condition. Non-semantic conditions use the per-model single-token-valid set; the semantic-neighbour filler and $\Sigma P(\text{synonyms})$ use targets with curated semantic fields. Exact means in Appendix D, Table 6.

Model	truncate − full	95 % CI	Mean target rank: full → truncate
ModernBERT-large	+0.034	$[0.016, 0.056]$	$35 \rightarrow 7$
Qwen2.5-1.5B	+0.059	$[0.046, 0.072]$	$75 \rightarrow 7$
Qwen2.5-7B	+0.015	$[-0.005, 0.035]$	$10 \rightarrow 4$
OLMo-2-7B	−0.015	$[-0.022, -0.009]$	$43 \rightarrow 33$

Table 2: Causal ablation: truncating $N{=}30$ to $N{=}3$ on F0 displaced. Contrast is the per-word mean $P(\text{target} \mid N{=}3) - P(\text{target} \mid N{=}30)$; 95 % CI bootstrapped over per-model single-token-valid targets. Two of four models replicate with CI excluding zero (ModernBERT-large $\approx 5\times$ rank improvement, Qwen2.5-1.5B $\approx 11\times$); Qwen2.5-7B's point estimate is positive but CI includes zero. OLMo-2-7B's CI excludes zero in the opposite direction: its displaced peak sits at $N{=}10$, so $N{=}3$ lands before the peak.

Figure 5: **Internal correlates on four panel models** (10/23-word mechanism subsets, F0 displaced; shared legend). (a) Per-target-token attention (solid, log) vs each model's $1/N$ reference (dashed, anchored at smallest N): attention drops with N in every model. ModernBERT-large tracks its $1/N$ reference; the three CLMs sit above theirs (sub-dilution). (b) Total block attention: grows with N for the three CLMs (sub-dilution); plateaus for ModernBERT-large. (c) Slot-state target probability (23-word subset): in the three CLMs, slot-state target probability tracks the behavioural inverted-U; ModernBERT-large peaks earliest and decays unevenly.

Total block attention grows with N. Per-target-token attention falls with N in all four mechanism models (Figure 5a), as budget conservation would predict if a fixed budget were divided over N keys. The total attention the model assigns to the repeated block, however, does not stay fixed. In three of four models the block budget grows with N (Figure 5b): Qwen2.5-1.5B from ≈ 0.11 at $N{=}3$ to ≈ 0.47 at $N{=}30$; Qwen2.5-7B from 0.06 to 0.29; OLMo-2-7B from 0.03 to 0.24. ModernBERT-large is the exception, with a roughly flat block budget (0.09 to 0.14; per-N table in Appendix G). The per-token

fall in the three CLMs is therefore sub-dilution: per-token attention drops because the budget is divided across more tokens, but the budget itself grows.

A layer-wise breakdown of the same per-target-token attention (Appendix G, Figure 7) confirms that sub-dilution is a stack-wide property rather than a last-layer artefact: the three CLMs sit above their per-layer $1/N$ reference at most depths, while ModernBERT-large super-dilutes in its upper layers, consistent with its roughly flat last-layer block budget. The displaced inverted-U's attention correlate dissociates by training objective in this subset: CLMs allocate more total attention to the repeated block as N grows; the MLM does not.

Slot-state target probability tracks the behavioural inverted-U. On the 23-word mechanism subset, the model's logit-head probability for the target shows a clean inverted-U on the three CLMs: Qwen2.5-1.5B peaks at $N{=}3$ (0.138), Qwen2.5-7B peaks around $N{=}5$–10 (0.18–0.20), and OLMo-2-7B peaks at $N{=}10$ (0.062); all decay through $N{=}30$ (Figure 5c). ModernBERT-large peaks earliest at $N{=}1$ (0.354) and decays unevenly.

7 Discussion

The methodological lesson sits in a single contrast. Hold the repeated-target prefix fixed, move the prediction slot off the block, and the curve no longer climbs: it peaks early and falls back. The same prefix produces priming on the adjacent slot in every baseline we test, so the displaced decline cannot be reduced to long-context capacity loss. This matters concretely for cloze probes of factual knowledge, semantic priming studies, in-context learning analyses that vary demonstration count, and any benchmark that scores predictions at a slot adjacent to the variation. Each implicitly treats slot position as orthogonal to how the variation affects prediction; the displaced inverted-U says the assumption is wrong, and the cross-lingual replication argues this is not an English- or tokeniser-specific concern.

The substantive claim is that repetition helps when the readout slot extends the repeated surface, and hurts when the target must be retrieved from a fresh clause. The six-condition ablation places the active variable on exact lexical repetition, not prefix length and not semantic neighbourhood activation.

Where is the diagnostic weakest? SmolLM2-1.7B is the only checkpoint whose mean displaced curve does not visibly invert through $N{=}30$, though its per-word drops remain positive. The headline statistic survives across the full 13-model panel. The within-family comparison with SmolLM2-360M cuts against parameter count: the smaller, deeper model shows a clearer inversion than the larger, shallower one. The same direction shows up on BERT-tiny/mini/small (Appendix C): the 2-layer BERT-tiny shows no inverted-U, while 4-layer BERT-mini and BERT-small do (drops 0.521 and 0.478). Depth, not parameter count, is the more relevant axis in these comparisons. A related observation cuts against the intuition that post-training fixes the effect: instruction tuning at 7B does not attenuate the displaced drop but *increases* it (Qwen2.5-7B base $0.461 \rightarrow$ Qwen2.5-7B-Instruct 0.549 on F0, same direction in all five frames).

The internal correlate has a similar texture. Per-target-token attention drops with N in every model, which is what budget conservation predicts on its own. What it does not predict is the total attention the model assigns to the repeated block, which grows with N in the three CLM models and stays roughly flat in ModernBERT-large. The MLM/CLM split lines up with training objective rather than scale, and is consistent with autoregressive training doing something specific with repeated keys that an MLM does not. Whether the underlying mechanism is softmax cooperation between repeated keys, attention-sink dynamics (Xiao et al., 2024; Gu et al., 2025) under a displaced-query setup, or autoregressive-specific recency priors, our correlational probes cannot distinguish; a single MLM is not enough to tell candidates apart, and the layer-targeted interventions that would distinguish them remain open.

Even when the answer is stated explicitly at the start of the prompt (a second retrieval route the displaced probe does not provide), three of four mechanism models retain a positive per-word drop with CI excluding zero in a LAMA-style pilot (Appendix H). The magnitudes are attenuated by 75–86% from the main displaced range (0.42–0.69 becomes 0.058–0.136), but the signature survives: the displaced inverted-U is not eliminated by giving the model an alternative source of the answer.

Limitations

Every target in our English panel passes a single-token filter in every tested tokeniser family, which excludes many naturalistic content words. The ob-

vious extension (multi-token targets scored under probability-product or first-piece heuristics) is not a free generalisation: the headline shape statistic and the ablation conditions both assume a single read-out position. The non-additive aggregation claim is bounded accordingly to single-token cloze and next-token prediction under the displaced-readout frame structure of §3; whether the same shape appears in free-form generation, multi-hop retrieval, or under multi-token scoring is a separate question.

The two probes are unevenly covered. The adjacent baseline in Figure 2a runs on three models (one MLM, one small CLM, one larger CLM), not on all 13; the dissociation requires the contrast to hold at all, not model-by-model, but extending the adjacent probe to the full panel would strengthen the argument. The cross-lingual frames F0–F2 are hand-translated to idiomatic equivalents, not calibrated for matched syntactic predictability, so frame-by-frame magnitudes across languages may partly reflect translation choices; the panel-level claim (42 of 42 cells positive) does not depend on those comparisons. SmolLM2-1.7B is an exception to the secondary descriptive observation (mean-curve inversion before $N{=}30$) but not to the headline statistic (positive per-word drop with CI excluding zero). We do not have a clean account of why this particular checkpoint's mean curve fails to invert. Per-word drops are computed only on words with $\text{peak}_w > 0$; Phi-3.5-mini's absolute $P(\text{target})$ is much lower than the rest of the panel ($\text{peak}_P \approx 0.001$ at the mean-curve level), and its 13-of-13 contribution rests on relative collapse across this low-probability regime rather than on a meaningful absolute decay.

The frame-pragmatics ablation is English-only on the four-model subset, and its novelty frames are a weaker manipulation check than frames pre-validated to shift continuations toward novel words.

The internal-correlate evidence is correlational. Per-target-token attention drops, the slot-state inverted-U turns over, and the layer-wise picture is structured rather than diffuse; all co-move with the behaviour, but co-movement is not intervention. None of our probes manipulates the attention pattern or the displaced slot directly; calibrated interventions that mask the repeated block's attention or perturb the slot-state representation remain open.

References

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, and 110 others. 2024. Phi-3 technical report: A highly capable language model locally on your phone. *Preprint*, arXiv:2404.14219.

Rishabh Agarwal, Avi Singh, Lei M. Zhang, Bernd Bohnet, Luis Rosias, Stephanie Chan, Biao Zhang, Ankesh Anand, Zaheer Abbas, Azade Nova, John D. Co-Reyes, Eric Chu, Feryal Behbahani, Aleksandra Faust, and Hugo Larochelle. 2024. Many-shot in-context learning. *Advances in Neural Information Processing Systems (NeurIPS)*.

Federico Barbero, Andrea Banino, Steven Kapturowski, Dharshan Kumaran, João G. M. Araújo, Alex Vitvitskyi, Razvan Pascanu, and Petar Veličković. 2024. Transformers need glasses! information over-squashing in language tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Yonatan Belinkov. 2022. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics*, 48(1):207–219.

Loubna Ben Allal, Anton Lozhkov, Elie Bakouch, Gabriel Martín Blázquez, Guilherme Penedo, Lewis Tunstall, Andrés Marafioti, Hynek Kydlíček, Agustín Piqueres Lajarín, Vaibhav Srivastav, Joshua Lochner, Caleb Fahlgren, Xuan-Son Nguyen, Clémentine Fourrier, Ben Burtenshaw, Hugo Larcher, Haojun Zhao, Cyril Zakka, Mathieu Morlon, and 3 others. 2025. SmolLM2: When smol goes big – data-centric training of a small language model. *Preprint*, arXiv:2502.02737.

Sheila R. Black. 2001. Semantic satiation and lexical ambiguity resolution. *The American Journal of Psychology*, 114(4):493–510.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 8440–8451.

Allyson Ettinger. 2020. What BERT is not: Lessons from a new suite of psycholinguistic diagnostics for language models. *Transactions of the Association for Computational Linguistics (TACL)*, 8:34–48.

Xiangming Gu, Tianyu Pang, Chao Du, Qian Liu, Fengzhuo Zhang, Cunxiao Du, Ye Wang, and Min Lin. 2025. When attention sink emerges in language models: An empirical view. In *International Conference on Learning Representations (ICLR)*.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. The curious case of neural text degeneration. In *International Conference on Learning Representations (ICLR)*.

Jennifer Hu and Roger Levy. 2023. Prompting is not a substitute for probability measurements in large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Gautier Izacard and Edouard Grave. 2021. Leveraging passage retrieval with generative models for open domain question answering. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*.

Vladimir Karpukhin, Barlas Oğuz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics (TACL)*, 12:157–173.

Yao Lu, Max Bartolo, Alastair Moore, Sebastian Riedel, and Pontus Stenetorp. 2022. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Kanishka Misra, Allyson Ettinger, and Julia Rayz. 2020. Exploring BERT's sensitivity to lexical cues using tests from semantic priming. In *Findings of the Association for Computational Linguistics: EMNLP 2020*.

OLMo Team. 2025. 2 OLMo 2 furious. *Preprint*, arXiv:2501.00656.

Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. 2019. Language models as knowledge bases? In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2463–2473.

Qwen Team. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2024. Quantifying language models' sensitivity to spurious features in prompt design or: How i learned to start worrying about prompt formatting. In *International Conference on Learning Representations (ICLR)*.

L. C. Smith. 1984. Semantic satiation affects category membership decision time but not lexical priming. *Memory & Cognition*, 12(5):483–488.

Robyn Speer. 2022. wordfreq: v3.0. Python package.

Xing Tian and David E. Huber. 2010. Testing an associative account of semantic satiation. *Cognitive Psychology*, 60(4):267–290.

Iulia Turc, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Well-read students learn better: On the importance of pre-training compact models. *arXiv preprint arXiv:1908.08962*.

Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, Oskar Hallström, Said Taghadouini, Alexis Gallagher, Raja Biswas, Faisal Ladhak, Tom Aarsen, Griffin Thomas Adams, Jeremy Howard, and Iacopo Poli. 2025. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2526–2547, Vienna, Austria. Association for Computational Linguistics.

Sean Welleck, Ilia Kulikov, Stephen Roller, Emily Dinan, Kyunghyun Cho, and Jason Weston. 2020. Neural text generation with unlikelihood training. In *International Conference on Learning Representations (ICLR)*.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. 2024. Efficient streaming language models with attention sinks. In *International Conference on Learning Representations (ICLR)*.

Jin Xu, Xiaojiang Liu, Jianhao Yan, Deng Cai, Huayang Li, and Jian Li. 2022. Learning to break the loop: Analyzing and mitigating repetitions for neural text generation. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Itay Yona, Ilia Shumailov, Jamie Hayes, and Yossi Gandelsman. 2025. Interpreting the repeated token phenomenon in large language models. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*.

A Word List, Tokenizer Filtering, and Templates

Construction. We hand-curate 261 candidate English nouns and noun-like concepts. Each candidate is annotated with its Zipf log-frequency (Speer,

2022) and a semantic class. The list is balanced across four categorical cells (cross of concrete vs abstract reference, and high vs low frequency, with the high/low boundary at Zipf 5.0) and across twelve semantic classes.

Per-tokeniser filtering. Tokenizers fragment many candidates differently, so we construct a per-family target set by retaining candidates that encode to exactly one piece under that family's tokeniser. For each candidate we try both the leading-space form (BPE / SentencePiece convention) and the no-space form (BERT WordPiece convention) and accept the candidate if either yields a single token. This produces target sets of 182 (Phi-3.5-mini) to 258 (SmolLM2) words. The shared core (the intersection across every panel tokeniser) is ≈ 168 words and is the basis for the cross-model OLS regression of §4.2.

Frame templates. *Adjacent* probes (no displaced frame):

- MLM: `<target × N> [MASK] .`
- CLM: `<target × N>` (next-token slot).

Displaced probes:

- MLM: `<target × N> . <frame> [MASK] .`
- CLM: `<target × N> . <frame>` (next-token slot).

Frames F0–F4 (English):

- F0: *The word I keep thinking about is …*
- F1: *The topic was …*
- F2: *I want to mention …*
- F3: *Let me tell you about …*
- F4: *The most important thing is …*

Ablation block templates that replace `<target × 30>` in the F0 displaced probe are defined in Appendix D.

B   Statistical Analysis: Full Tables

Quadratic regression: coefficients. The primary OLS quadratic on shared-core $N \geq 1$ cells ($n = 70{,}590$) yields the parameter table below; cluster-robust SEs (clustered by target word). Reference levels: model ModernBERT-base, frame F0, category abstract-high. $R^2 = 0.550$.

Term	Coefficient
Intercept	-0.725
N	$+0.2118$
N^2	-0.00610
Zipf log-frequency	-0.191
model: ModernBERT-large	-0.43
model: Qwen2.5-0.5B	-3.10
model: Qwen2.5-1.5B	-3.51
model: Qwen2.5-3B	-2.84
model: Qwen2.5-7B	-1.95
model: Qwen2.5-7B-Instruct	-2.10
model: Qwen2.5-14B	-2.05
model: SmolLM2-360M	-3.45
model: SmolLM2-1.7B	-2.82
model: Phi-3.5-mini	-7.34
model: OLMo-2-1B	-3.63
model: OLMo-2-7B	-2.90
frame: F1	-1.77
frame: F2	-2.29
frame: F3	-1.12
frame: F4	-2.27
category: abstract-low	-0.63
category: concrete-high	-0.27
category: concrete-low	-0.84

Table 3: OLS quadratic regression coefficients on $\log P(\text{target})$ over the shared-core panel, rounded for display. Both N and N^2 signs match the inverted-U prediction; the largest fixed effects are by model.

Pattern classification thresholds. Each per-word N-curve is classified by deterministic rules. Let $\text{peak}_w = \max_{N \in \{1,3,5,10,20,30\}} P(\text{target} \mid w, N)$ and let N_w^* denote the argmax. A (model, frame, word) cell is classified as

- *satiation-like* if $N_w^* \in \{1, 3, 5, 10\}$ *and* $(\text{peak}_w - P(N{=}30 \mid w))/\text{peak}_w > 0.30$;
- *monotonic-priming* if the curve is non-decreasing in N *and* $P(N{=}30 \mid w) > 1.05 \cdot P(N{=}1 \mid w)$;
- *plateau* if the curve is approximately monotonic with $P(N{=}30 \mid w) \geq 0.7 \cdot \text{peak}_w$;
- *mixed* otherwise.

Across the 16,230 (model, frame, word) cells, 8,964 (55%) are *satiation-like*, 5,129 (32%) are *plateau*, 1,089 (7%) are *monotonic-priming*, and 1,048 (6%) are *mixed*. Per-(model, frame) shares appear in the rightmost column of Table 5.

Frequency confound regression. Table 4 reports the targeted regression $\text{drop}_w \sim \text{Zipf} + \text{category} + \text{model} + \text{frame}$ on $n{=}16{,}230$ word-frame cells with cluster-robust SEs by word. The full regression has $R^2{=}0.191$; Zipf alone has

R^2=0.003 and Zipf+category together R^2=0.004, while model+frame fixed effects alone account for R^2=0.186, so the fixed effects explain $\approx 60\times$ more variance than Zipf alone. The Zipf coefficient is small but reliably negative under clustering (-0.036, $t=-3.5$, $p < 10^{-3}$), so high-frequency words decay slightly less than low-frequency ones; the category coefficients lose individual significance under clustering (concrete-low: $t = -1.56$, $p = 0.12$; others $|t| < 1.5$), so we do not interpret per-category differences in decay magnitude. **Frequency modulates the magnitude of the decay but does not explain it away.**

Term	Coefficient
Zipf log-frequency	-0.036
category: abstract-low	$+0.015$
category: concrete-high	-0.012
category: concrete-low	-0.029
R^2 (full, with model+frame): 0.191	
R^2 (Zipf only): 0.003	
R^2 (Zipf + category only): 0.004	
R^2 (model + frame only): 0.186	
$n = 16{,}230$ word-frame cells	

Table 4: Frequency-confound regression $\mathrm{drop}_w \sim$ Zipf + category + model + frame; cluster-robust SEs (clustered by target word). Zipf has the right-sign coefficient but explains an order of magnitude less variance than the (model, frame) fixed effects.

Per-(model, frame) summary: complete table. Table 5 reports peak N, peak P, $P(N{=}30)$, drop, bootstrap CI, and *satiation-like* share for every (model, frame) cell (65 rows: 13 models $\times$ 5 frames). SmolLM2-1.7B is the only row block whose mean curve does not invert on any frame; its per-word drops remain positive but the *satiation-like* share never exceeds 0.18.

C Within-Family Architecture Contrast

The two SmolLM2 checkpoints provide a small natural depth-vs-capacity dissociation. SmolLM2-360M has 32 transformer blocks at hidden size 960 (15 attention heads, 2560 intermediate dimension) and an F0 drop of 0.327. SmolLM2-1.7B has fewer blocks (24) at a wider hidden size (2048, 32 attention heads, 8192 intermediate) and an F0 drop of 0.138. The larger checkpoint has more parameters but is shallower, and shows the weaker effect; the smaller, deeper checkpoint shows the stronger effect. Within the SmolLM2 family, depth therefore correlates with displaced-inverted-U magnitude in the opposite direction from raw parameter count. We treat this as suggestive rather than conclusive (a single family with one depth-vs-width contrast is not a controlled scaling law).

BERT-tiny / mini / small. The same direction shows up on the older Turc et al. (2019) BERT family, which we ran on the F0 displaced probe as an auxiliary check. BERT-tiny (2 layers, hidden 128, 4.4M params) shows no inverted-U: F0 peak $N{=}30$, per-word drop 0.001 $[0.000, 0.003]$. BERT-mini (4 layers, hidden 256, 11M) shows a clear inverted-U: F0 peak $N{=}3$, per-word drop 0.521 $[0.471, 0.565]$. BERT-small (4 layers, hidden 512, 29M) also shows a per-word inversion with CI clearing zero (0.478 $[0.426, 0.528]$), though its mean curve peaks at $N{=}30$. The transition between absent and present sits at the depth jump from 2 to 4 layers; doubling hidden size at fixed depth (mini $\to$ small) leaves the per-word drop essentially unchanged. This is consistent with the SmolLM2 within-family direction.

D Causal Ablation Construction

Condition definitions. On the F0 displaced probe, each input replaces the 30-target-repeat block with one of six conditions. The non-semantic conditions are run over the per-model single-token-valid set; the semantic-neighbour filler and the semantic-field mass are restricted to targets with curated semantic dictionaries. The full $N{=}30$ repeat (code: `full_repeat_N30`) keeps thirty exact copies of the target. The truncated $N{=}3$ repeat (code: `truncate_to_N3`) keeps only the first three target copies. The deleted block (code: `delete_repeat_block`) is empty. The length-matched random filler (code: `random_filler_same_length`) is thirty random nouns sampled from a fixed neutral pool. The semantic-neighbour filler (code: `unique_semantic_filler`) is thirty semantic neighbours sampled from the target's curated semantic field, excluding the exact target. The unrelated-repeat block (code: `repeat_unrelated_N30`) is thirty copies of `table`.

Per-(model, condition) summary. Table 6 reports means over the per-model target set for each condition. The full $N{=}30$ repeat and the truncated $N{=}3$ repeat are the only conditions with non-trivial $P(\text{target})$; the semantic-neighbour filler is the only

Model	Frame	Peak N	Peak P	$P(N{=}30)$	Drop	95% CI of drop	Sat. share
ModernBERT-base	F0	3	0.668	0.372	0.516	[0.481, 0.549]	0.74
	F1	5	0.292	0.107	0.728	[0.696, 0.761]	0.90
	F2	3	0.132	0.044	0.696	[0.665, 0.728]	0.91
	F3	3	0.329	0.091	0.787	[0.759, 0.812]	0.93
	F4	3	0.119	0.034	0.832	[0.805, 0.855]	0.96
ModernBERT-large	F0	1	0.400	0.260	0.423	[0.388, 0.462]	0.65
	F1	10	0.210	0.141	0.455	[0.415, 0.495]	0.56
	F2	10	0.062	0.050	0.382	[0.348, 0.422]	0.46
	F3	10	0.146	0.086	0.551	[0.514, 0.585]	0.74
	F4	1	0.160	0.084	0.570	[0.534, 0.604]	0.76
Qwen2.5-0.5B	F0	3	0.187	0.132	0.329	[0.294, 0.363]	0.53
	F1	3	0.012	0.008	0.398	[0.350, 0.444]	0.51
	F2	3	0.014	0.006	0.589	[0.553, 0.621]	0.80
	F3	3	0.015	0.014	0.256	[0.218, 0.292]	0.36
	F4	30	0.005	0.005	0.247	[0.214, 0.280]	0.33
Qwen2.5-1.5B	F0	5	0.125	0.062	0.693	[0.654, 0.733]	0.81
	F1	5	0.023	0.014	0.684	[0.639, 0.730]	0.71
	F2	3	0.010	0.002	0.825	[0.797, 0.856]	0.92
	F3	3	0.039	0.008	0.856	[0.829, 0.884]	0.94
	F4	5	0.008	0.004	0.629	[0.585, 0.672]	0.72
Qwen2.5-3B	F0	3	0.109	0.040	0.434	[0.397, 0.477]	0.60
	F1	30	0.014	0.014	0.418	[0.372, 0.462]	0.52
	F2	3	0.006	0.004	0.481	[0.444, 0.516]	0.59
	F3	3	0.054	0.026	0.551	[0.515, 0.587]	0.71
	F4	3	0.008	0.003	0.436	[0.401, 0.471]	0.60
Qwen2.5-7B	F0	5	0.134	0.106	0.461	[0.422, 0.502]	0.52
	F1	30	0.029	0.029	0.282	[0.247, 0.320]	0.33
	F2	30	0.018	0.018	0.393	[0.354, 0.434]	0.51
	F3	30	0.045	0.045	0.283	[0.250, 0.321]	0.37
	F4	30	0.115	0.115	0.209	[0.171, 0.249]	0.18
Qwen2.5-7B-Instruct	F0	10	0.209	0.155	0.549	[0.507, 0.592]	0.55
	F1	5	0.027	0.024	0.512	[0.465, 0.553]	0.58
	F2	10	0.014	0.011	0.494	[0.452, 0.535]	0.58
	F3	30	0.088	0.088	0.376	[0.343, 0.419]	0.44
	F4	30	0.097	0.097	0.281	[0.236, 0.327]	0.29
Qwen2.5-14B	F0	3	0.223	0.065	0.733	[0.706, 0.761]	0.93
	F1	5	0.028	0.015	0.499	[0.464, 0.530]	0.71
	F2	5	0.018	0.010	0.479	[0.447, 0.512]	0.69
	F3	3	0.083	0.031	0.674	[0.645, 0.704]	0.89
	F4	5	0.021	0.006	0.545	[0.511, 0.577]	0.78
SmolLM2-360M	F0	20	0.113	0.100	0.327	[0.291, 0.367]	0.29
	F1	20	0.006	0.006	0.267	[0.233, 0.301]	0.27
	F2	20	0.009	0.008	0.365	[0.326, 0.407]	0.42
	F3	20	0.032	0.030	0.262	[0.223, 0.300]	0.28
	F4	20	0.003	0.003	0.328	[0.294, 0.365]	0.41
SmolLM2-1.7B	F0	30	0.101	0.101	0.138	[0.114, 0.164]	0.05
	F1	30	0.032	0.032	0.255	[0.221, 0.290]	0.14
	F2	30	0.019	0.019	0.206	[0.171, 0.240]	0.18
	F3	30	0.040	0.040	0.191	[0.161, 0.224]	0.09
	F4	30	0.026	0.026	0.213	[0.181, 0.247]	0.05
Phi-3.5-mini	F0	1	0.001	0.000	0.523	[0.485, 0.558]	0.75
	F1	1	0.000	0.000	0.459	[0.421, 0.497]	0.69
	F2	1	0.000	0.000	0.608	[0.574, 0.642]	0.92
	F3	10	0.000	0.000	0.333	[0.295, 0.373]	0.50
	F4	1	0.000	0.000	0.564	[0.528, 0.602]	0.84
OLMo-2-1B	F0	20	0.039	0.033	0.434	[0.387, 0.472]	0.48
	F1	20	0.013	0.013	0.500	[0.451, 0.545]	0.55
	F2	30	0.005	0.005	0.291	[0.244, 0.335]	0.29
	F3	20	0.024	0.022	0.301	[0.261, 0.343]	0.31
	F4	30	0.010	0.010	0.225	[0.187, 0.266]	0.24
OLMo-2-7B	F0	10	0.058	0.042	0.426	[0.385, 0.468]	0.43
	F1	10	0.022	0.015	0.412	[0.372, 0.454]	0.50
	F2	10	0.008	0.005	0.474	[0.433, 0.515]	0.56
	F3	10	0.041	0.022	0.537	[0.495, 0.579]	0.67
	F4	10	0.011	0.005	0.565	[0.529, 0.601]	0.72

Table 5: Per-(model, frame) summary (n_{words} ranges from 182 to 258). *Peak N* and *Peak P* are taken from the word-averaged mean curve. *Drop* is the per-word mean of $(\mathrm{peak}_w - P(N{=}30)_w)/\mathrm{peak}_w$; the 95% CI is bootstrapped over the per-model single-token-valid target words. *Sat. share* is the fraction of (word) curves classified as *satiation-like*. Model name shown on the F0 row of each block; blank below.

condition that raises ΣP(synonyms) substantially, illustrating the separation between target-specific lexical priming and semantic-neighbourhood activation.

E Frame-Pragmatics Ablation

Motivation and design. The displaced probe combines a repeated block with a topic-introducer frame; §5 asks whether the discourse pragmatics of that frame, rather than repetition at a displaced slot, drives the inverted-U. Holding the displaced read-out position and the repeated target block fixed, we vary only the frame's pragmatic class on the four mechanism models, scoring P(target) exactly as in the main displaced grid (per-model single-token targets, $N \in \{0, 1, 3, 5, 10, 20, 30\}$, per-word drop with a 500-resample word-level bootstrap, seed 42).

Frame classes. Four classes are compared. *Topic-introducer* reuses the main frames F0 (`'The word I keep thinking about is'`) and F2 (`'I want to mention'`). *Neutral* uses existential continuations with no novelty or anaphora pragmatics (`'I saw a'`, `'There was a'`, `'Look, a'`). *Anaphoric* frames demand the just-repeated word (`'That word again:'`, `'The word repeated above is'`, `'To say it once more, the word is'`). *Novelty* frames demand a different word (`'On a completely different note, the word is'`, `'Changing the subject, the new word is'`, `'Now for something different, the word is'`). Per-class drops average over the frames in the class.

Result. All 16 (model, class) cells show a positive per-word drop with bootstrap CI excluding zero (Table 7), and the peak-normalised curves invert in 15 of 16 (Figure 6). The anaphoric class keeps the inverted-U in every model, and the novelty class (which a discourse-novelty account predicts should produce the steepest decline) is the largest-drop class in none of the four models. The effect therefore does not require, and is not amplified by, a frame that pragmatically favours a new word.

F Cross-Lingual Panel

Checkpoints and setup details. The four multilingual checkpoints used in §4.4 are `FacebookAI/xlm-roberta-base` (MLM, 279M) and `FacebookAI/xlm-roberta-large` (MLM, 561M) (Conneau et al., 2020); `Qwen/Qwen2.5-1.5B` and `Qwen/Qwen2.5-7B` (Qwen Team, 2025) (CLMs). Word lists are hand-curated single-token nouns of length ≥ 3, balanced for concreteness/frequency where possible; each candidate is filtered against the model's own tokeniser using the same leading-space-first rule as the English panel. Cross-lingual frames F0–F2 are hand-translated to idiomatic equivalents of the English F0–F2 templates; F3 and F4 are not translated, so the cross-lingual panel is evaluated on F0–F2 only.

Per-(model, language, frame) results. Table 8 reports peak N, peak P, drop, and 95% bootstrap CI for every cell. Mean-curve peaks land at $N{=}1$ for XLM-R-base, $N{=}3$–10 for both Qwen2.5 sizes, and split between $N{=}1$ and $N{=}30$ for XLM-R-large.

Panel scope. The four-model panel spans both training objectives, two tokeniser families (XLM-R SentencePiece and Qwen BPE), and four target languages.

G Mechanism Probes: Per-N and Layer-wise

Per-N attention table. Table 9 reports per-target-token attention at the displaced slot in the last layer (averaged across heads and target words), the $1/N$ reference anchored at the smallest evaluated N, and the total attention to the repetition block. In three of four mechanism models the total block budget grows monotonically with N; ModernBERT-large is the exception, with a roughly flat block budget.

Layer-wise per-token attention. Figure 7 extends the last-layer analysis above to every layer of the four mechanism models on the 50-word stratified subset.

H LAMA-Style Pilot

Setup. Three answer-prompt templates of the form `<prefix> the answer is <target> . <block> . <suffix> the answer is` (A0–A2 paraphrase the prefix and suffix) are evaluated on the four mechanism models. The middle `<block>` is $N \in \{1, 3, 5, 10, 20, 30\}$ tokens long, drawn from

Model	Condition	$P(\text{target})$	$\Sigma P(\text{syn.})$
ModernBERT-large	Full $N{=}30$ repeat	0.260	0.015
ModernBERT-large	Truncated $N{=}3$ repeat	0.294	0.027
ModernBERT-large	Deleted block	0.001	0.002
ModernBERT-large	Random filler	0.001	0.004
ModernBERT-large	Semantic-neighbour filler	0.031	**0.316**
ModernBERT-large	Unrelated-repeat block	0.001	0.001
Qwen2.5-1.5B	Full $N{=}30$ repeat	0.062	0.003
Qwen2.5-1.5B	Truncated $N{=}3$ repeat	0.121	0.005
Qwen2.5-1.5B	Deleted block	0.000	0.001
Qwen2.5-1.5B	Random filler	0.000	0.002
Qwen2.5-1.5B	Semantic-neighbour filler	0.012	**0.154**
Qwen2.5-1.5B	Unrelated-repeat block	0.000	0.001
Qwen2.5-7B	Full $N{=}30$ repeat	0.109	0.003
Qwen2.5-7B	Truncated $N{=}3$ repeat	0.124	0.005
Qwen2.5-7B	Deleted block	0.000	0.000
Qwen2.5-7B	Random filler	0.001	0.003
Qwen2.5-7B	Semantic-neighbour filler	0.013	**0.164**
Qwen2.5-7B	Unrelated-repeat block	0.000	0.000
OLMo-2-7B	Full $N{=}30$ repeat	0.042	0.006
OLMo-2-7B	Truncated $N{=}3$ repeat	0.027	0.006
OLMo-2-7B	Deleted block	0.000	0.000
OLMo-2-7B	Random filler	0.001	0.002
OLMo-2-7B	Semantic-neighbour filler	0.013	**0.105**
OLMo-2-7B	Unrelated-repeat block	0.000	0.000

Table 6: Mean $P(\text{target})$ and mean $\Sigma P(\text{synonyms})$ per (model, ablation condition) on the F0 displaced probe. Non-semantic conditions use the per-model single-token-valid set; the semantic-neighbour filler and the semantic-field mass are computed on the targets with curated semantic dictionaries. The semantic-neighbour filler is the only condition that raises the semantic-field mass substantially.

Figure 6: **Frame-pragmatics ablation, four models.** Peak-normalised mean $P(\text{target})$ on the displaced probe with readout position and repeated block fixed and only the frame's pragmatic class varied. Open dot marks each curve's peak over $N \geq 1$. The inverted-U persists across all four pragmatic classes, including anaphoric frames that demand the repeated word; per-(model, class) drops and CIs in Table 7.

Model	Frame class	n_w	drop	95% CI	peak N	inverts
ModernBERT-large	Topic-introducer (F0,F2)	250	0.382	[0.346, 0.421]	1	yes
	Neutral / existential	250	0.371	[0.332, 0.412]	10	yes
	Anaphoric (demands repeat)	250	0.129	[0.109, 0.149]	10	yes
	Novelty (demands new)	250	0.312	[0.281, 0.341]	10	yes
Qwen2.5-1.5B	Topic-introducer (F0,F2)	256	0.713	[0.681, 0.744]	5	yes
	Neutral / existential	256	0.748	[0.717, 0.779]	3	yes
	Anaphoric (demands repeat)	256	0.719	[0.673, 0.760]	5	yes
	Novelty (demands new)	256	0.657	[0.614, 0.697]	5	yes
Qwen2.5-7B	Topic-introducer (F0,F2)	256	0.311	[0.279, 0.341]	5	yes
	Neutral / existential	256	0.194	[0.166, 0.221]	30	no
	Anaphoric (demands repeat)	256	0.213	[0.190, 0.237]	10	yes
	Novelty (demands new)	256	0.298	[0.266, 0.332]	10	yes
OLMo-2-7B	Topic-introducer (F0,F2)	256	0.426	[0.386, 0.465]	10	yes
	Neutral / existential	256	0.483	[0.443, 0.518]	10	yes
	Anaphoric (demands repeat)	256	0.661	[0.638, 0.686]	10	yes
	Novelty (demands new)	256	0.284	[0.245, 0.323]	10	yes

Table 7: **Frame-pragmatics ablation.** Per-word drop $(\text{peak}_w - P(N{=}30)_w)/\text{peak}_w$ (peak over $N \geq 1$) on the displaced probe with the readout position and repeated block held fixed and only the frame's pragmatic class varied, four-model subset. n_w is the per-model single-token target count; 95% bootstrap CI (500 resamples, seed 42, word-level). **inverts** marks whether the population-mean curve peaks before $N{=}30$. All 16 cells show a positive per-word drop with CI excluding zero; the anaphoric class, whose frames demand the repeated word, keeps the inverted-U in every model, and the novelty class is the largest-drop class in none of the four models. Frame strings are listed in the appendix text above.

Figure 7: **Layer-wise per-target-token attention vs the per-layer $1/N$ reference**, displaced slot, four mechanism models on the 50-word stratified subset. Cells show $\log_2(\text{per-token attn} / 1/N$ ref. at smallest $N)$. Purple = super-dilution (per-token attention falls below the budget-dilution baseline); orange = sub-dilution (the two endpoints differ in luminance for grayscale readers). ModernBERT-large super-dilutes in its upper layers; Qwen2.5-1.5B, Qwen2.5-7B, and OLMo-2-7B sit predominantly above their $1/N$ references across the stack.

Model	Lang.	Frame	n_w	Peak N	Peak P	Drop	95 % CI of drop
xlm-roberta-base	German	F0	46	1	0.784	0.515	[0.412, 0.618]
xlm-roberta-base	German	F1	46	1	0.302	0.561	[0.465, 0.662]
xlm-roberta-base	German	F2	46	20	0.006	0.502	[0.410, 0.583]
xlm-roberta-base	Spanish	F0	49	1	0.492	0.541	[0.431, 0.636]
xlm-roberta-base	Spanish	F1	49	1	0.210	0.737	[0.665, 0.803]
xlm-roberta-base	Spanish	F2	49	20	0.062	0.539	[0.442, 0.630]
xlm-roberta-base	French	F0	40	1	0.442	0.823	[0.731, 0.903]
xlm-roberta-base	French	F1	40	10	0.063	0.573	[0.447, 0.686]
xlm-roberta-base	French	F2	40	1	0.088	0.543	[0.432, 0.651]
xlm-roberta-large	German	F0	46	30	0.265	0.354	[0.257, 0.455]
xlm-roberta-large	German	F1	46	1	0.037	0.561	[0.455, 0.671]
xlm-roberta-large	German	F2	46	1	0.009	0.869	[0.793, 0.929]
xlm-roberta-large	Spanish	F0	49	30	0.207	0.308	[0.219, 0.389]
xlm-roberta-large	Spanish	F1	49	30	0.045	0.372	[0.273, 0.479]
xlm-roberta-large	Spanish	F2	49	30	0.002	0.749	[0.656, 0.830]
xlm-roberta-large	French	F0	40	30	0.208	0.443	[0.335, 0.555]
xlm-roberta-large	French	F1	40	30	0.012	0.115	[0.062, 0.181]
xlm-roberta-large	French	F2	40	30	0.004	0.639	[0.508, 0.756]
Qwen2.5-1.5B	German	F0	28	5	0.192	0.814	[0.718, 0.893]
Qwen2.5-1.5B	German	F1	28	5	0.036	0.624	[0.535, 0.714]
Qwen2.5-1.5B	German	F2	28	30	0.142	0.112	[0.034, 0.214]
Qwen2.5-1.5B	Spanish	F0	34	5	0.199	0.853	[0.785, 0.909]
Qwen2.5-1.5B	Spanish	F1	34	5	0.003	0.579	[0.479, 0.669]
Qwen2.5-1.5B	Spanish	F2	34	5	0.001	0.684	[0.600, 0.761]
Qwen2.5-1.5B	French	F0	29	3	0.105	0.777	[0.686, 0.861]
Qwen2.5-1.5B	French	F1	29	30	0.002	0.481	[0.361, 0.608]
Qwen2.5-1.5B	French	F2	29	30	0.001	0.568	[0.464, 0.680]
Qwen2.5-1.5B	Chinese	F0	49	3	0.007	0.481	[0.411, 0.549]
Qwen2.5-1.5B	Chinese	F1	49	3	0.007	0.367	[0.287, 0.451]
Qwen2.5-1.5B	Chinese	F2	49	10	0.007	0.384	[0.298, 0.472]
Qwen2.5-7B	German	F0	28	10	0.229	0.479	[0.366, 0.583]
Qwen2.5-7B	German	F1	28	5	0.040	0.610	[0.527, 0.706]
Qwen2.5-7B	German	F2	28	30	0.087	0.117	[0.047, 0.203]
Qwen2.5-7B	Spanish	F0	34	5	0.192	0.732	[0.646, 0.808]
Qwen2.5-7B	Spanish	F1	34	5	0.010	0.448	[0.374, 0.527]
Qwen2.5-7B	Spanish	F2	34	20	0.001	0.305	[0.222, 0.400]
Qwen2.5-7B	French	F0	29	5	0.152	0.486	[0.392, 0.587]
Qwen2.5-7B	French	F1	29	5	0.007	0.378	[0.291, 0.452]
Qwen2.5-7B	French	F2	29	30	0.002	0.202	[0.112, 0.306]
Qwen2.5-7B	Chinese	F0	49	5	0.027	0.435	[0.386, 0.483]
Qwen2.5-7B	Chinese	F1	49	3	0.012	0.575	[0.504, 0.639]
Qwen2.5-7B	Chinese	F2	49	5	0.027	0.387	[0.321, 0.455]

Table 8: Cross-lingual results. Four open-access multilingual models (XLM-R-base, XLM-R-large, Qwen2.5-1.5B, Qwen2.5-7B) on Spanish, Chinese, German, and French single-token noun lists, with three hand-translated frames per language. *Peak N* and *Peak P* are taken from the word-averaged mean curve; *Drop* is the per-word mean of $(\text{peak}_w - P(N{=}30)_w)/\text{peak}_w$, with bootstrap 95 % CI over the per-(model, language) word population. XLM-R Chinese is excluded for both base and large because XLM-R's BPE leaves no Chinese single-token candidates. All 42 evaluated cells show a positive drop with CI excluding zero; 30 of 42 also have mean-curve peak before $N{=}30$.

Model	N	Per-token	$1/N$ ref.	Total to block
Qwen2.5-1.5B	3	0.054	0.054	0.109
Qwen2.5-1.5B	5	0.035	0.033	0.141
Qwen2.5-1.5B	10	0.026	0.016	0.235
Qwen2.5-1.5B	20	0.020	0.008	0.383
Qwen2.5-1.5B	30	**0.016**	**0.005**	0.471
Qwen2.5-7B	3	0.031	0.031	0.061
Qwen2.5-7B	5	0.040	0.018	0.159
Qwen2.5-7B	10	0.024	0.009	0.214
Qwen2.5-7B	20	0.013	0.005	0.246
Qwen2.5-7B	30	**0.010**	**0.003**	0.292
OLMo-2-7B	3	0.015	0.015	0.030
OLMo-2-7B	5	0.011	0.009	0.045
OLMo-2-7B	10	0.007	0.004	0.067
OLMo-2-7B	20	0.006	0.002	0.122
OLMo-2-7B	30	**0.008**	**0.002**	0.242
ModernBERT-large	3	0.044	0.044	0.089
ModernBERT-large	5	0.026	0.027	0.105
ModernBERT-large	10	0.017	0.013	0.150
ModernBERT-large	20	0.008	0.007	0.157
ModernBERT-large	30	**0.005**	**0.004**	0.143

Table 9: Per-target-token attention at the displaced slot in the last layer. "$1/N$ ref." is the budget-dilution baseline anchored at the smallest evaluated $N=3$; bold entries highlight the $N=30$ comparison. In three of four models the total block budget grows with N; ModernBERT-large's stays roughly flat.

one of four conditions: `target_repeat` (the target itself), `random_repeat` (random neutral nouns), `unrelated_repeat` ('table'), or `semantic_repeat` (semantic neighbours). Each (model, template, condition, N) cell is run on a 50-word stratified subset of that model's single-token-valid targets; per-word probabilities are averaged across the three templates.

Target-repeat curves. Table 10 reports the mean $P(\text{target})$ at each N for the `target_repeat` block (the directly comparable condition), and the per-word drop $(\text{peak}_w - P(N{=}30)_w)/\text{peak}_w$ with 95% bootstrap CI (500 resamples, seed 42). Three of four models replicate the displaced attenuation with CI excluding zero; the magnitude is smaller than the headline displaced effect because the pre-stated answer provides a second retrieval route.

Control conditions. The `unrelated_repeat` and `random_repeat` blocks (which break the target match) produce baseline $P(\text{target})$ in the 0.13–0.45 range across models without the inverted-U signature, confirming that the `target_repeat` effect is target-specific rather than a generic position artefact. The `semantic_repeat` block falls between these and the target-repeat block. Full per-condition curves are in the released data.

I Reproducibility

Code, data, and artefact documentation. The anonymized code, reproducibility scripts, released result files, and artefact documentation are available at https://anonymous.4open.science/r/when-more-becomes-less-3259/.

Artifacts, licenses, and intended use. The released package contains the analysis code, reproducibility scripts, target lists, per-model output tables, figure-generation scripts, and result files needed to audit the claims in the paper. The released code is MIT-licensed; pretrained model checkpoints and other third-party artefacts retain their original licenses and terms. The intended use of the released artefacts is research reproduction, inspection, and extension of the two-probe diagnostic, not deployment as a model-control or safety system.

Data, human subjects, and risk profile. The study uses no human subjects, annotators, private user data, or newly collected natural-language documents. The English panel is a hand-curated list of common single-token nouns filtered per tokeniser; multilingual and mechanism probes use fixed prompt templates, translated frames, and model-generated probability outputs. We did not intentionally include personally identifying informa-

Model	$N{=}1$	$N{=}3$	$N{=}5$	$N{=}10$	$N{=}20$	$N{=}30$	**drop**	**95% CI**
ModernBERT-large	0.622	0.585	0.636	0.727	**0.744**	0.740	0.058	[0.026, 0.097]
Qwen2.5-1.5B	0.356	0.432	**0.450**	0.405	0.406	0.414	0.136	[0.099, 0.171]
Qwen2.5-7B	0.446	0.518	0.589	0.621	**0.621**	0.596	0.116	[0.078, 0.165]
OLMo-2-7B	0.270	0.347	0.417	0.496	0.565	**0.622**	0.002	[0.000, 0.005]

Table 10: LAMA-style pilot: mean $P(\text{target})$ across 50 stratified words and three answer-prompt templates, for the `target_repeat` block at each N. Bold entries mark each model's peak. Per-word drop is $(\text{peak}_w - P(N{=}30)_w)/\text{peak}_w$ with 95% bootstrap CI. Three of four models show a positive drop with CI excluding zero; OLMo-2-7B's mean curve does not invert through $N{=}30$ and its CI lower bound rounds to zero at the reported precision (the unrounded 2.5% quantile is a small positive number, not strictly 0).

tion or offensive content. The main risk is methodological over-interpretation: the results show that repetition count and readout position interact in controlled cloze probes, not that truncation or repetition shaping is a general-purpose intervention for open-ended generation.

Pipeline. The full analysis pipeline is invoked through a single notebook that runs target-set construction, displaced evaluations, ablations, mechanism probes, figure rendering, and verification. The per-stage script-to-output mapping is documented in the reproducibility README. The mechanism and ablation probes for the four high-cost models are scoped to finish within ≈ 12 hours on a single A100 80GB.

Hardware. The full panel runs end-to-end on a single A100 80GB GPU in `bfloat16`. Smaller models (under 4B) finish in under ten minutes each; Qwen2.5-7B and the OLMo-2-7B mechanism battery take roughly 30–60 minutes; Qwen2.5-14B (displaced grid only) takes roughly ninety minutes.

Model checkpoints. All models are loaded from public HuggingFace checkpoints with no access tokens required. The exact checkpoint identifiers are `answerdotai/ModernBERT-base`, `answerdotai/ModernBERT-large`, `Qwen/Qwen2.5-0.5B`, `Qwen/Qwen2.5-1.5B`, `Qwen/Qwen2.5-3B`, `Qwen/Qwen2.5-7B`, `Qwen/Qwen2.5-7B-Instruct`, `Qwen/Qwen2.5-14B`, `HuggingFaceTB/SmolLM2-360M`, `HuggingFaceTB/SmolLM2-1.7B`, `microsoft/Phi-3.5-mini-instruct`, `allenai/OLMo-2-0425-1B`, and `allenai/OLMo-2-1124-7B`.

Random seeds. All bootstrap resampling uses seed 42 (500 resamples). All word-list stratifica-

tions and ablation samplings use seed 0. Model forward passes are deterministic.

Pinned dependencies. Exact versions of PyTorch, HuggingFace Transformers ($>= 4.48$), pandas, numpy, scipy, statsmodels, matplotlib, and `wordfreq` are pinned at the snapshot used to produce the reference outputs.

Verification. A verification script enumerates the expected output manifest (per-model target-word CSVs, displaced/ablation parquet tables, mechanism CSVs, figure files, and the compiled PDF) and reports per-file presence and size. The reference reproduction run passes the manifest in full.