One More Step Towards Reality:
Cooperative Bandits with Imperfect Communication

Abstract

The cooperative bandit problem is increasingly becoming relevant due to its applications in large-scale decision-making. However, most research for this problem focuses exclusively on the setting with perfect communication, whereas in most real-world distributed settings, communication is often over stochastic networks, with arbitrary corruptions and delays. In this paper, we study cooperative bandit learning under three typical real-world communication scenarios, namely, (a) message-passing over stochastic time-varying networks, (b) instantaneous reward-sharing over a network with random delays, and (c) message-passing with adversarially corrupted rewards, including byzantine communication. For each of these environments, we propose decentralized algorithms that achieve competitive performance, along with near-optimal guarantees on the incurred group regret as well. Furthermore, in the setting with perfect communication, we present an improved delayed-update algorithm that outperforms the existing state-of-the-art on various network topologies. Finally, we present tight network-dependent minimax lower bounds on the group regret. Our proposed algorithms are straightforward to implement and obtain competitive empirical performance.

1 Introduction

The cooperative multi-armed bandit problem involves a group of N agents collectively solving a multi-armed bandit while communicating with one another. This problem is relevant for a variety of applications that involve decentralized decision-making, for example, in distributed controls and robotics (Srivastava et al., 2014) and communication (Lai et al., 2008). In the typical formulation of this problem, a group of agents are arranged in a network $G = (\mathcal{V}, \mathcal{E})$, wherein each agent interacts with the bandit, and communicates with its neighbors in G, to maximize the cumulative reward.

A large body of recent work on this problem assumes the communication network G to be fixed (Kolla et al., 2018, Landgren et al., 2016a,b). Furthermore, these algorithms inherently require the precise communication, as they construct careful confidence intervals for cumulative arm statistics across agents, e.g., for stochastic bandits, it has been shown that the standard UCB1 algorithm (Auer et al., 2002) with a *neighborhood* confidence interval is close to optimal (Dubey and Pentland, 2020a, Kolla et al., 2018), and correspondingly, for adversarial bandits, a neighborhood-weighted loss estimator can be utilized with the EXP3 algorithm to provide competitive regret (Cesa-Bianchi et al., 2019). Such approaches are indeed feasible when communication is perfect, e.g., the network G is fixed, and messages are not lost or corrupted. In real-world environments, however, this is rarely true: messages can be lost, agents can be byzantine, and communication networks are rarely static (Leskovec, 2008). This aspect has hence received much attention in the distributed optimization literature (Yang et al., 2019), however, contrary to networked optimization where dynamism in communication can behave synergistically (Hosseini et al., 2016), bandit problems additionally bring a decision-making component requiring a careful explore-exploit tradeoff. As a result, external

randomness and corruption are incompatible with the default optimal approaches, and require careful consideration (Vernade et al., 2017, Lykouris et al., 2018). This motivates us to study the multi-agent bandit problem under real-world communication, which regularly exhibits external randomness, delays and corruptions. Our key contributions include the following.

Contributions. We provide a set of algorithms titled Robust Communication Learning (RCL) for the cooperative stochastic bandit under three real-world communication constraints. First, we study stochastic communication, where the communication network G is time-varying, with each edge being present in G with a known probability p. For this setting, we present a UCB-like algorithm, RCL-LF (Link Failures) that directs agent i to discard messages with an additional probability of $1 - p_i$ in order to control the bias in the (stochastic) reward estimates. RCL-LF obtains a group regret of $\mathcal{O}\left(\left(\sum_{i=1}^{N}(1 - p \cdot p_i) + \bar{\chi}(G) \cdot p \cdot (\max_i p_i)\right)\left(\sum_{k=1}^{K} \frac{\log T}{\Delta_k}\right)\right)$, where $\bar{\chi}(G)$ is the clique covering number of G; the regret exhibits a smooth interpolation between known rates for no communication ($p = 0$) and perfect communication ($p = 1$). Next, we study the case where messages from any agent can be delayed by a random (but bounded) number of trials τ with expectation $\mathbb{E}[\tau]$. For this setting, simple reward-sharing with a natural extension of the UCB algorithm (RCL-SD (Stochastic Delays)) obtains a regret of $\mathcal{O}\left(\bar{\chi}(G) \cdot \left(\sum_{k>1} \frac{\log T}{\Delta_k}\right) + \left(N \cdot \mathbb{E}[\tau] + \log(T) + \sqrt{N \cdot \mathbb{E}[\tau] \log(T)}\right) \cdot \sum_{k>1} \Delta_k\right)$, which is reminiscent of that of single-agent bandits with delays (Joulani et al., 2013) (Remark 4).

Thirdly, we study the *corrupted* setting, where any message can be (perhaps in a byzantine manner) corrupted by an unknown (but bounded) amount ϵ. This setting presents the two-fold challenge of receiving feedback after (variable) delays as well as adversarial corruptions, making existing arm elimination (Lykouris et al., 2018, Gupta et al., 2019b) or cooperative estimation (Dubey and Pentland, 2020a) methods inapplicable. We present an algorithm titled RCL-AC (Adversarial Corruptions), that overcomes this issue by limiting exploration only to well-positioned agents in G, who explore using a *hybrid* robust arm elimination and local confidence bound approach. RCL-AC obtains a regret of $\mathcal{O}\left(\psi(G_\gamma) \cdot \sum_{k=1}^{K} \frac{\log T}{\Delta_k} + N \sum_{k=1}^{K} \frac{\log \log T}{\Delta_k} + NTK\gamma\epsilon\right)$, where $\psi(G_\gamma)$ denotes the domination number of the γ graph power of G, which matches the rates obtained for corrupted single-agent bandits without knowledge of ϵ. Finally, for perfect communication, we present a simple modification of cooperative UCB1 that provide significant empirical improvements, and also provide minimax lower bounds on the group regret of algorithms based on message-passing.

Related Work. A variant of the networked adversarial bandit problem without communication constraints (e.g., delay, corruption) was studied first in the work of Awerbuch and Kleinberg (2008), who demonstrated an average regret bound of order $\sqrt{(1 + {}^K/{}_N)T}$. This line of inquiry was generalized to networked communication with at most γ round delays in the work of (Cesa-Bianchi et al., 2019), that demonstrate an average regret of order $\sqrt{(\gamma + {}^{\alpha(G_\gamma)}/{}_N)KT}$ where $\alpha(G_\gamma)$ denotes the independence number of the γ graph power of the network G. This line of inquiry has been complemented for the stochastic setting with problem-dependent analyses in the work of Kolla et al. (2018) and Dubey and Pentland (2020a). The former presents a UCB1-style algorithm with instantaneous reward-sharing that obtains a regret bound of $\mathcal{O}(\alpha(G) \cdot \sum_{k=1}^{K} \frac{\log T}{\Delta_k})$ that was generalized to message-passing communication with delays in the latter. Alternatively, Landgren et al. (2016a,b) consider the multi-agent bandit where communication is done instead via a *running consensus* protocol, where neighboring agents average their reward estimates using the deGroot consensus model (DeGroot, 1974). This algorithm was refined in the work of Martínez-Rubio et al. (2019) by a delayed mixing scheme that reduces the bias in the consensus reward estimates. A specific setting of Huber contaminated communication was explored in the work of Dubey and Pentland (2020b), however, in contrast to our algorithms, the authors here assume that the total contamination likelihood is known *a priori*. Additionally, multi-agent networked bandits with stochastic communication was considered in Madhushani and Leonard (2019, 2020, 2021), however, only for $d-$regular networks and multi-star networks.

Our work also relates to the aspects of stochastic delayed feedback and corruptions in the context of single-agent multi-armed bandits. There has been considerable research in these areas, beginning from the early work of Weinberger and Ordentlich (2002) that proposes running multiple bandit algorithms parallely to account for (fixed) delayed feedback. Vernade et al. (2017) discuss the multi-armed bandit with stochastic delays, and provide algorithms using optimism indices based on the UCB1 (Auer et al., 2002) and KL-UCB (Garivier and Cappé, 2011) approaches. Stochastic bandits with

Table 1: Quantity (with notation) for any graph G.

Average degree (d)	Maximum degree ($d_{\max}$)	Degree of i (d_i)	Independence number (α)
Message life (γ)	Minimum degree ($d_{\min}$)	Neighborhood of i ($\mathcal{N}_i$)	Domination number (ψ)
k-power of G (G_k)	Diameter ($d_\star$)	$\mathcal{N}_i \cup \{i\}$ ($\mathcal{N}_i^+$)	Clique covering number ($\bar{\chi}$)

adversarial corruptions have also received significant attention recently, where Lykouris et al. (2018) present an arm elimination algorithm that provides a regret that scales linearly with the total amount of corruption, and present lower bounds demonstrating that the linear dependence is inevitable. This was followed up by Gupta et al. (2019a) that introduce the algorithm BARBAR that improves the dependence on the corruption level by a better sampling of worse arms. Alternatively, Altschuler et al. (2019) discuss best-arm identification under contamination, which is a weaker adversary compared to the one discussed in this paper. The corrupted setting discussed in our paper combines both issues of (variable) delayed feedback along with adversarial corruptions, and hence requires a novel approach.

2 Preliminaries

Notation (Table 1). We denote the set $a, ..., b$ as $[a, b]$, and as $[b]$ when $a = 1$. We define the indicator of a Boolean predicate x as $\mathbf{1}\{x\}$. For any graph G with diameter $d_\star(G)$, and any $1 \leq \gamma \leq d_\star(G)$, we define G_γ as the γ-power of G, i.e., the graph with edge (i, j) if they are at most a distance γ.

Problem Setting. We consider the cooperative stochastic multi-armed bandit problem with K arms and a group $\mathcal{V}$ of N agents. In each round $t \in [T]$, each agent $i \in \mathcal{V}$ pulls an arm $A_i(t) \in [K]$ and receives a random reward $X_i(t)$ (realized as $r_i(t)$) drawn i.i.d. from the corresponding arm's distribution. We assume that each reward distribution is sub-Gaussian with an unknown mean μ_k and unknown variance proxy σ_k^2 upper bounded by a known constant σ^2. Without loss of generality we assume that $\mu_1 \geq \mu_2 \ldots \geq \mu_K$ and define $\Delta_k := \mu_1 - \mu_k, \forall k > 1$ to be the suboptimality (in expectation) of arm k. Let $\overline{\Delta} := \min_{k>1} \Delta_k$ be the minimum expected reward gap. For brevity in our theoretical results, we define $g(\xi, \sigma) := 8(\xi + 1)\sigma^2 = o(1)$ and $f(M, G) := M \sum_{k>1} \Delta_k + 4 \sum_{i=1}^{N} \left(3 \log(3(d_i(G) + 1)) + (\log(d_i(G) + 1))\right) \cdot \sum_{k>1} \Delta_k = o((M + N \log N) \cdot \sum_{k>1} \Delta_k)$.

Networked Communication (Figure 1). Let $G = (\mathcal{V}, \mathcal{E})$ be a connected, undirected graph encoding the communication network, where $\mathcal{E}$ contains an edge (i, j) if agents i and j can communicate directly via messages with each other. After each round t, each agent j broadcasts a message $\boldsymbol{m}_j(t)$ to all their neighbors. Each message is forwarded at most γ times through G, after which it is discarded. For any value of $\gamma > 1$, the protocol is called *message-passing* (Linial, 1992), but for $\gamma = 1$ it is called *instantaneous reward sharing*, as this setting has no delays in communication.

Exploration Strategy (Figure 2). For Sections 3 and 4 we use a natural extension of the UCB1 algorithm for exploration. Thus we modify UCB1 (Auer et al., 2002) such that at each time step t for each arm k each agent i constructs an upper confidence bound, i.e., the sum of its estimated expected reward $\widehat{\mu}_k^i(t-1)$ (empirical average of all the observed rewards) and the uncertainty associated with the estimate $C_k^i(t-1) := \sigma \sqrt{\frac{2(\xi+1)\log t}{N_k^i(t-1)}}$ where $\xi > 1$, and pull the arm with the highest bound.

Regret. The performance measure we consider is a straightforward extension of the single-agent idea of *pseudo regret* called *group* regret, which is the regret (in expectation) incurred by the group $\mathcal{V}$ by pulling suboptimal arms. The group regret is given by $\text{Reg}_G(T) = \sum_{i=1}^{N} \sum_{k>1} \Delta_k \cdot \mathbb{E}\left[n_k^i(t)\right]$, where $n_k^i(t)$ is the number of times agent i pulls the suboptimal arm k up to (and including) round t. Before presenting our algorithms and regret upper bounds we present some graph terminology.

Definition 1 (Clique covering number). A clique cover $\mathcal{C}$ of any graph $G = (\mathcal{V}, \mathcal{E})$ is a partition of $\mathcal{V}$ into subgraphs $C \in \mathcal{C}$ such that each subgraph C is fully connected, i.e., a clique. The size of the smallest possible covering $\mathcal{C}^\star$ is known as the *clique covering number* $\bar{\chi}(G)$.

Definition 2 (Independence number). The *independence number* $\alpha(G)$ of $G = (\mathcal{V}, \mathcal{E})$ is the size of the largest subset of $\mathcal{V}_\alpha \subseteq \mathcal{V}$ such that no two vertices in $\mathcal{V}_\alpha$ are connected.

Definition 3 (Domination number). The *domination number* $\psi(G)$ of $G = (\mathcal{V}, \mathcal{E})$ is the size of the smallest subset $\mathcal{V}_\psi \subseteq \mathcal{V}$ such that each vertex not in $\mathcal{V}_\psi$ is adjacent to at least one agent in $\mathcal{V}_\psi$.

Organization. In this paper, we study three specific forms of communication errors. Section 3 discusses the case when, for both *message-passing* and *instantaneous reward-sharing*, any message

---

For $t = 1, 2, ...$ **each agent** $i \in \mathcal{V}$

    1. Plays arm $A_i(t)$, gets reward $r_i(t)$, computes $\boldsymbol{m}_i(t) = \langle A_i(t), r_i(t), i, t \rangle$.

    2. Adds $\boldsymbol{m}_i(t)$ to the set of messages $\mathbf{M}_i(t)$, broadcast all messages in $\mathbf{M}_i(t)$ and receives messages $\mathbf{M}'_i(t)$ from its neighbors.

    3. Computes $\mathbf{M}_i(t+1)$ from $\mathbf{M}'_i(t)$ by discarding all messages sent prior to round $t - \gamma$.

When $\gamma = 1$ we have *instantaneous reward sharing* (no delays), and *message-passing* for $\gamma > 1$.

Figure 1: The cooperative bandit protocol with delay parameter γ.

For $t = 1, 2, ...,$ **each agent** $i \in \mathcal{V}$

    1. Calculates, for each arm $k \in [K]$, $Q_k^i(t-1) = \widehat{\mu}_k^i(t-1) + \sigma \sqrt{\frac{2(\xi+1)\log(t-1)}{N_k^i(t-1)}}$, where $N_k^i(t-1)$ is the number of reward samples available for arm k at time t.

    2. Plays arm $A_i(t) = \arg\max_k Q_k^i(t-1)$

Figure 2: Cooperative `UCB1` which uses additional arm pulls from messages.

forwarding fails independently with probability p, resulting in stochastic communication failures. Section 4 discusses the case when *instantaneous reward-sharing* in fact incurs a random (but bounded) delay. Section 5 discusses the case when the outgoing reward from any message may be corrupted by an adversarial amount at most ϵ. Finally, in Section 6, we discuss an improved algorithm for the case with perfect communication and present minimax lower bounds on the problem. We present all proofs in the Appendix and present proof-sketches highlighting the central ideas in the main paper.

3   Probabilistic Message Selection for Random Communication Failures

The fundamental advantage of cooperative estimation is to leverage observations about sub-optimal arms from neighboring agents to reduce exploration. However, when agents are communicating over an arbitrary graph, the amount of information an agent receives varies according to its connectivity in G. For example, agents with a large number of neighbors receive more information, leading them to begin exploitation earlier than weakly-connected agents. As a result, well-connected agents exhibit better performance early on in the problem. This improved performance has a consequence, however: agents that are poorly connected only observe exploitative arm pulls, which requires them to explore for longer in order to obtain similar estimates for sub-optimal arms, increasing their regret. This disparity is exacerbated in the presence of random *link failures*, where any message sent by an agent can fail to reach its recipient with a failure probability $1 - p$ (drawn i.i.d. for each message).

Indeed, it is natural to expect the group regret to decrease with decreasing link failure probability, i.e., increasing communication probability p. However, what we observe experimentally (Section 7) is that this holds only for graphs G that are *regular* (i.e., each agent has the same degree), or close to regular. When G is irregular, as we increase p from 0 to 1, the group performance oscillates. While, in some cases, the improved performance in the well-connected agents can outweigh the degradation observed in weakly-connected ones (leading to lower *group* regret), it is prudent to consider an approach that mitigates this disparity by regulating information flow in the network.

Information Regulation in Cooperative Bandits. Our approach to regulate information is straightforward: we direct each agent i to discard any incoming message with an agent-specific probability $1 - p_i$, while always utilizing its own observations. For specific values of p_i, we can obtain various weighted combinations of internal vs. group observations. Our first algorithm RCL-LF (Link Failures) is built on this regulation strategy, coupled with `UCB1` exploration using all selected observations for each arm. Essentially, each agent runs `UCB1` using the cumulative set of observations it has received from its network. After pulling an arm, it broadcasts its pulled arm and reward through the network, but incorporates each incoming message *only* with a probability p_i. We first present a regret bound for RCL-LF when run in *instantaneous reward-sharing* protocol.

Theorem 1 (`RCL-LF` Regret with instantaneous reward-sharing)**.** `RCL-LF` *running in an instantaneous reward-sharing protocol, obtains cumulative group regret of*

$$\mathsf{Reg}_G(T) \leq g(\xi, \sigma) \left(\sum_{i=1}^{N} (1 - p_i \cdot p) + \bar{\chi}(G) \cdot (\max_{i \leq N} p_i) \cdot p \right) \left(\sum_{k > 1} \frac{\log T}{\Delta_k} \right) + f(5N, G).$$

Proof sketch. We follow an approach similar to the analysis of `UCB1` by Auer et al. (2002) with a several key modifications. First, we partition the communication graph G into a set of non-overlapping cliques and then analyze the regret of each clique. The group regret can thus obtained by taking the summation of the regret over each clique. Two major technical challenges in proving the regret bound for `RCL-LF` are (a) deriving a tail probability bound for probabilistic communication, and (b) bounding the regret accumulated by agents by losing information due to communication failures and message discarding. We overcome the first challenge by noticing that communication is independent of the decision making process thus $\mathbb{E}\left(\exp\left(\lambda \sum_{\tau=1}^{t} X_\tau^i \mathbf{1}\{A_\tau^i = k\} - \mu_k N_k^i(t) - \frac{\lambda^2 \sigma_k^2}{2} N_k^i(t) \right) \right) \leq 1$ holds under probabilistic communication. We obtain the tail bound by combining this result with Markov inequality and optimizing over λ using a peeling type argument. We address the second challenge by proving that the number of times agents do not share information about any sub-optimal arm k can be bounded by a term that increases logarithmically with time and scales with number of agents, G and communication probabilities as $\sum_{i=1}^{N}(1 - p_i \cdot p) + \bar{\chi}(G) \cdot p \cdot \max_{i \leq N} p_i$. $\qquad\square$

Remark 1 (Regret bound optimality)**.** Under perfect communication ($p = 1$) and no message discarding, i.e., $p_i = p = 1, \forall i \in [N]$ the dominant term in our regret bound scales with $\bar{\chi}(G)$, obtaining identical performance to deterministic communication over G (Dubey and Pentland, 2020a). Alternatively, when $p_i = p = 0$, there evidently is no communication, and hence, the regret bound is $\mathcal{O}(N \log T)$. Theorem 1 quantifies the benefit of communication in reducing the group regret under probabilistic link failure and when agents incorporate observations with an agent-specific probability. With probability $(\max_{i \leq N} p_i) \cdot p$ the regret scales as a perfect communication network with no communication loss, and with probability $\sum_{i=1}^{N}(1 - p_i \cdot p)$ the regret scales as N agents in isolation.

Remark 2 (Controlling information disparity)**.** In order to regulate the information disparity across the network we set $p_i = \frac{d_{\min}(G)}{d_i(G)}$. Thus, the agent(s) with minimum degree $d_{\min}$ incorporate each message they receive with probability 1 and we have that the *expected* number of messages for each agent is the same, i.e., $T \cdot d_{\min}(G)$. Therefore, all the agents receive the same amount of information (in expectation), providing a large performance improvement for irregular graphs (see Section 7).

Message-Passing. Under this communication protocol each agent i communicates with neighbors at distance at most γ, while each hop adds a 1-step delay. Our algorithm `RCL-CF` obtains a similar regret bound in this setting as well, when all agents use the same `UCB1` exploration strategy (Figure 2).

Theorem 2 (`RCL-LF` Regret with message-passing)**.** *Let $\mathcal{C}$ be a minimal clique covering of G_γ. For any $\mathcal{C} \in \mathcal{C}$ and $i, j \in \mathcal{C}$ let $\gamma_i = \max_{j \in \mathcal{C}} d(i, j)$ be the maximum distance (in graph G) between agents i and j. `RCL-LF` running in a message-passing protocol with delay parameter γ obtains, cumulative group regret of*

$$\mathsf{Reg}_G(T) \leq g(\xi, \sigma) \left(\sum_{i=1}^{N} (1 - p_i \cdot p^{\gamma_i}) + \bar{\chi}(G_\gamma) \cdot (\max_{i \leq N} p_i \cdot p^{\gamma_i}) \right) \left(\sum_{k > 1} \frac{\log T}{\Delta_k} \right) + f((\gamma + 4)N, G_\gamma).$$

Proof sketch. We partition the graph G_γ into non-overlapping cliques, analyze the regret of each clique and take the summation of regrets over cliques to obtain group regret. In addition to the challenges encountered in Theorem 1 here we are required to account for having different probabilities of failures for messages due to having multiple paths of different length between agents and account for the delay incurred by each hp when passing messages. We overcome first challenge by considering that agent i receives each message with at least probability p^{γ_i}. We overcome the second challenge by identifying that regret incurred by delays can be upper bounded using $\left(\sum_{i=1}^{N} \gamma_i - N \right) \sum_{k > 1} \Delta_k$. $\square$

Remark 3. Finding an optimal observation probability $\{p_i\}_{1=1}^{N}$ for `RCL-LF` with message-passing is difficult due to the delays added by each hop when forwarding messages. If messages are forwarded without a delay, optimal performance can be obtained by using $p_i = \frac{d_{\min}(G_\gamma)}{d_i(G_\gamma)}$. For dense G_γ, the above choice of observation probability provides *near*-optimal performance.

4 Instantaneous Reward-sharing Under Stochastic Delays

Next, we consider a communication protocol, where any message is received after an arbitrary (but bounded) stochastic delay. We assume for simplicity that each message is sent only once in the network (and not forwarded multiple times as in *message-passing*, and leave the message-passing setting as future work. We assume, furthermore that the delays are identically and independently drawn from a bounded distribution with expectation $\mathbb{E}[\tau]$ (similar to prior work, e.g., Joulani et al. (2013), Vernade et al. (2017). For this setting, we demonstrate that cooperative UCB1 along with incorporating all messages as soon as they are available provides efficient performance, both empirically and theoretically. We denote this algorithm as `RCL-SD` (Stochastic Delays), and demonstrate that this approach incurs only an extra $\mathcal{O}(\sqrt{N \log T} + \log T)$ overhead compared to perfect communication.

Theorem 3 (`RCL-SD` Regret). *Let $D_{total} = N \cdot \mathbb{E}[\tau] + 2 \log T + 2\sqrt{N \cdot \mathbb{E}[\tau] \log T}$ denote an upper bound on the total number of outstanding messages. `RCL-SD` obtains, with probability at least $1 - \frac{1}{T}$, cumulative group regret of*

$$\mathsf{Reg}_G(T) \leq g(\xi, \sigma) \cdot \bar{\chi}(G) \cdot \left(\sum_{k>1} \frac{\log T}{\Delta_k} \right) + D_{total} \cdot \left(\sum_{k>1} \Delta_k \right) + f(5N, G).$$

Proof sketch. We first demonstrate that the additional group regret due to stochastic delays can be bounded by the maximum number of cumulative outstanding messages over all agents at any given time step. Then we apply a result similar to Lemma 2 of Joulani et al. (2013) to bound the total number of outstanding messages using the cumulative expected delay $N \cdot \mathbb{E}[\tau]$, giving the result. $\square$

Remark 4. The D_{total} term is a succinct upper bound on the maximum number of cumulative outstanding messages in all agents, and when the expected delay $\mathbb{E}[\tau] = o(1)$, we see that the contribution of D_{total} is $\mathcal{O}(\sqrt{N \log T} + \log T)$. We conjecture that this is not improvable without restricting communication, as each agent will send T messages in total. The result obtained by Joulani et al. (2013) has a similar dependence for a single agent.

5 Hybrid Arm Elimination for Adversarial Reward Corruptions

In this section, we assume that any reward when transmitted can be corrupted a maximum value of ϵ, i.e., $\max_{t,n} |r_n(t) - \tilde{r}_n(t)| \leq \epsilon$ where $\tilde{r}_n(t)$ denotes the transmitted reward. Furthermore, we assume that the corruptions can be *adaptive*, i.e., can depend on the prior actions and rewards of each agent. This model includes natural settings, where messages can be corrupted during transmission, as well as *byzantine* communication (Dubey and Pentland, 2020b). If ϵ were known, we could then extend algorithms for misspecified bandits (Ghosh et al., 2017) to create a robust estimator and a subsequent UCB1-like algorithm that obtains a regret of $\mathcal{O}(\bar{\chi}(G_\gamma)K(\frac{\log T}{\Delta}) + TNK\epsilon)$. However, this approach has two issues. First, ϵ is typically not known, and the dependence on G_γ can be improved as well. We present an arm-elimination algorithm called `RCL-AC` (Adversarial Corruptions) that provides better guarantees on regret, without knowledge of ϵ in Algorithm 1.

The central motif in `RCL-AC`'s design is to eliminate bad arms by an epoch-based exploration, an idea that has been successful in the past for adversarially-corrupted stochastic bandits (Lykouris et al., 2018, Gupta et al., 2019a). The challenge, however, in a message-passing decentralized setting is two-fold. First, agents have different amounts of information based on their position in the network, and hence badly positioned agents in G may be exploring for much larger periods. Secondly, communication between agents is delayed, and hence any agent naively incorporating stale observations may incur a heavy bias from delays. To ameliorate the first issue, we partition the group of agents into two sets - *exploring agents* ($\mathcal{I}$) and *imitating agents* ($\mathcal{V} \setminus \mathcal{I}$). The idea is to only allow well-positioned agents in $\mathcal{I}$ to direct the exploration strategy for their neighboring agents, and the rest simply imitate their exploration strategy. We select $\mathcal{I}$ as a minimal dominating set of G_γ, hence $|\mathcal{I}| = \psi(G_\gamma)$. Furthermore, since $\mathcal{V} \setminus \mathcal{I}$ is a vertex cover, this ensures that each *imitating* agent is connected (at distance at most γ) to at least one agent in $\mathcal{I}$. Next, observe that there are two sources of delay: first, any *imitating* agent must wait at most γ trials to observe the latest action from its corresponding *exploring* agent, and second, each *exploring* agent must wait an additional γ trials for the feedback from all of its imitating agents. We propose that each *exploring* agent run UCB1 for 2γ rounds after each epoch of arm elimination, using *only* local pulls. This prevents a large bias due to these delays, at a small cost of $\mathcal{O}(\log \log T)$ suboptimal pulls.

Algorithm 1: `CHARM`: Cooperative Hybrid Arm Elimination

Parameters. Confidence $\delta \in (0, 1)$, horizon T, graph G with exploration set $\mathcal{I} \subseteq \mathcal{V}$.

Initialize $T_i(0) = K \forall i \in \mathcal{I} \lambda = 1024 \log \left(\frac{8K\alpha(G_\gamma)}{\delta} \log_2 T \right)$ and $\Delta_k^i(0) = 1, \forall\, k \in [K]$ and $i \in \mathcal{I}$.

for each subgraph $\mathcal{N}_i^+(G_\gamma)$ where $i \in \mathcal{I}$ **do**
  for $t = 1, ..., K$, each agent $j \in \mathcal{N}_i^+(G_\gamma)$ **do**
    Play arm K and get reward $r_j(t)$.
  end for
  for epoch $m_i = 1, 2, ...,$ **do**
    Set $n_k^i(m) = \lambda(\Delta_k^i(m-1))^{-2}\forall k \in [K]$.
    $N_i(m) = \sum_k n_k^i(m)$ and $T_i(m) = T_i(m-1) + N_i(m) + 2\gamma$.
    for agent $j \in \mathcal{N}_i^+(G_\gamma)$ **do**
      for $t = T_i(m_i - 1)$ to $s = T_i(m_i - 1) + 2\gamma$ **do**
        if $j \neq i$ **then**
          if $t \leq K + d(i, j)$ **then**
            Pull random arm.
          else
            Pull $A_j(t) = A_i(t - d(i, j))$ and get reward $r_j(t)$.
          end if
        else
          Pull $A_j(t) = $ `UCB1`(t)
        end if
      end for
      for $t = T_i(m_i - 1) + 2\gamma$ to $T_i(m_i)$ **do**
        if $j \neq i$ **then**
          Pull $A_j(t) = A_i(t - d(i, j))$ and get reward $r_j(t)$.
        else
          Pull an arm $A_i(t) = k \in [K]$ with probability $n_k^i(m)/N_k(m)$.
        end if
      end for
    end for
  end for
end for

Theorem 4 (`RCL-RC` Regret). `RCL-RC` *obtains, with probability at least* $1 - \delta$, *group regret of*

$$\mathrm{Reg}_G(T) = \mathcal{O}\left(KTN\gamma\epsilon + \psi(G_\gamma) \cdot \sum_{k>1} \frac{\log T}{\Delta_k} \log\left(\frac{K\psi(G_\gamma)\log T}{\delta} \right) + N \sum_{k>1} \Delta_k + \sum_{k>1} \frac{N \log(\gamma \log T)}{\Delta_k} \right).$$

Proof sketch. Since the dominating set covers $\mathcal{V}$, we can decompose the group regret into the cumulative regret of the subgraphs corresponding to each agent in $\psi(G_\gamma)$. For each subgraph, we can consider the cumulative regret incurred when the *exploring agent* follows `UCB1` vs. arm elimination. We have that arm elimination occurs for $\log T$ epochs, and since `UCB1` runs for 2γ rounds between succesive epochs, we have that in any subgraph of size n, the cumulative regret from `UCB1` rounds is of $\mathcal{O}(nK \log(\gamma \log T))$. For arm elimination, we can bound the subgraph regret via a modification of the approach in Gupta et al. (2019a): the difference in our approach is to construct a multi-agent filtration for arbitrary (reward-dependent) corruptions from message-passing, and then applying Freedman's bound on the resulting martingale sequence. Subsequently, the regret in each epoch is bound in a manner similar to Gupta et al. (2019a), and finally applying a union bound. $\qquad\square$

Remark 5 (Regret Optimality)**.** Theorem 4 demonstrates a trade-off between communication density and the adversarial error, as seen by the first two terms in the regret bound. The first term ($KTN\gamma\epsilon$) is a bound on the cumulative error introduced due to message-passing, which is increasing in γ, whereas the second term denotes the logarithmic regret due to exploration, where $\psi(G_\gamma)$ decreases as γ increases: for $\gamma = d_\star(G), \psi(G_\gamma) = 1$, matching the lower bound in Dubey and Pentland (2020a). This too, is expected, as fewer exploring agents are needed with a higher communication budget. Furthermore, we conjecture that the first term is optimal (in terms of T, up to graphical constants): a linear lower bound has been demonstrated for the single-agent setting in Lykouris et al. (2018).

Remark 6 (Computational complexity)**.** While the dominating set problem is known to be NP-complete (Karp, 1972), the problem admits a polynomial-time approximation scheme

289 (PTAS) (Crescenzi et al., 1995) for certain graphs, for which our bounds hold exactly. However,
290 RCL-RC can work on any dominating set of size n, and suffer regret of $\widetilde{\mathcal{O}}(KTN\gamma\epsilon + n\sum_{k>1}\frac{\log T}{\Delta_k})$[1].

6 An Algorithm for Perfect Communication and Lower Bounds

292 For perfect communication, we present Delayed MP-UCB, a simple improvement to UCB1 with
293 message-passing where each agent i only incorporates messages originated prior to $\bar{\gamma} \le \gamma$ time steps,
294 reducing disparity in information across agents.

295 **Theorem 5** (Delayed MP-UCB Regret). delayed(MP)-UCB *obtains, cumulative group regret of*

$$\mathsf{Reg}_G(T) \le g(\xi, \sigma)\bar{\chi}(G_\gamma)\left(\sum_{k>1}\frac{\log T}{\Delta_k}\right) + (N - \bar{\chi}(G_\gamma)(\gamma - 1)\sum_{k>1}\Delta_k + f(5N, G_\gamma) + h(G_\gamma, \bar{\gamma})$$

296 *where* $h(G_\gamma, \bar{\gamma}) = \left(\left(N - \bar{\chi}(G_\gamma)\bar{\gamma} + \sum_{t>\bar{\gamma}}^{T}\frac{\log\left(1 - \frac{d_i(G_\gamma)\bar{\gamma}}{(d_i(G_\gamma)+1)t)}\right)}{\log 1.3}\frac{1}{t^{(\xi+1)\left(1-\frac{0.09}{16}\right)}}\right)\sum_{k>1}\Delta_k.$

297 *Proof sketch.* Following a similar approach to the proof of Theorem 2 we partition the graph G_γ to a
298 set of non-overlapping cliques, analyze the regret of each clique via a UCB1 type analysis and take
299 the summation of regrets over cliques. However, using less information (due to delayed information
300 usage) in estimates leads to a large confidence bound $C_k^i(t)$ and this reduces the contribution to the
301 regret from tail probabilities. Note that $\log\left(1 - \frac{d_i(G_\gamma)\bar{\gamma}}{(d_i(G_\gamma)+1)t)}\right)$ is negative $\forall t > \bar{\gamma}$, and hence lower
302 regret is achieved due to low tail probabilities is given by the second term of $h(G_\gamma, \bar{\gamma})$. □

303 **Remark 7.** Incorporating only the messages originated before $\bar{\gamma}$ time steps is similar to communi-
304 cating over $G_{\bar{\gamma}}$ after a delay of $\bar{\gamma}$ time steps. When G is connected and $\bar{\gamma} = \gamma = d_*$ this is similar
305 to communicating over a complete graph with a delay of d_*. Thus Delayed MP-UCB mitigates the
306 disparity in information used by each agent, leading to improved group performance.

307 **Lower Bounds**. Without strict assumptions, a lower bound of $\mathcal{O}\left(\sum_{k>1}\log T/\Delta_k\right)$ has been demon-
308 strated both for $\gamma = 1$ (instantaneous reward-sharing, Kolla et al. (2018)) and $\gamma > 1$ (message-
309 passing, Dubey and Pentland (2020a)), which both suggest that a speedup of $\frac{1}{N}$ is potentially
310 achievable. For a more restrictive class of *individually consistent* and *non-altruistic* policies (i.e., that
311 do not contradict their local feedback), a tighter lower bound of $\mathcal{O}\left(\alpha(G_2)\sum_{k>1}\log T/\Delta_k\right)$ can be
312 demonstrated for reward-sharing (Kolla et al., 2018), and consequently $\mathcal{O}\left(\alpha(G_{\gamma+1})\sum_{k>1}\log T/\Delta_k\right)$
313 for message-passing. To supplement these results, we present a lower bound to characterize the
314 minimax optimal rates for the problem. We present first an assumption on multi-agent policies.

315 **Assumption 1** (Agnostic decentralized policies). *A set of N policies $\pi_1, ..., \pi_N$ are termed agnostic*
316 *decentralized policies, if for every pair (i, j) of agents that communicate in G and each $t \in [T]$, $\pi_i(t)$*
317 *is independent of $\{\pi_j(\tau)\}_{\tau=1}^{t-d(i,j)}$ conditioned on the rewards $\{(A_j(\tau), X_j(\tau))\}_{\tau=1}^{t-d(i,j)}$.*

318 **Theorem 6** (Minimax Rate). *For any policy $\mathcal{A}$, there exists a $K-$armed environment over N agents*
319 *with $\Delta_k \le 1$ for any connected graph G and $\gamma \ge 1$ such that, for some absolute constant c,*

$$\mathsf{Reg}_G(\mathcal{A}, T) \ge c\sqrt{KN(T + \widetilde{d}(G))}.$$

320 *Furthermore, if $\mathcal{A}$ is an agnostic decentralized policy, there exists a $K - armed$ environment over N*
321 *agents with $\Delta_k \le 1$ for any connected graph G and $\gamma \ge 1$ such that, for some absolute constant c'*

$$\mathsf{Reg}_G(\mathcal{A}, T) \ge c'\sqrt{\alpha^\star(G_\gamma)KNT}.$$

322 *Where* $\tilde{d}(G) = \sum_{i=1}^{d^\star(G)}\bar{d}_{=i} \cdot i$ *denotes the average delay incurred by message-passing across the*
323 *network G, and $\alpha^\star(G_\gamma) = \frac{N}{1+\bar{d}_\gamma}$ is Turán's lower bound (Turán, 1941) on $\alpha(G_\gamma)$.*

324 **Remark 8** (Tightness of lower bound). The first minimax bound does not make any assumptions
325 on the policy $\mathcal{A}$, and hence we only see an additive dependence of the average delay incurred by
326 communication over G. This dependence generalizes the minimax rate for delayed multi-armed
327 bandits (Neu et al., 2010) to graphical feedback. For the latter bound, observe that a variety of

---

[1]The $\widetilde{\mathcal{O}}$ notation ignores absolute constants and $\log\log(\cdot)$ factors in T.

Figure 3: Experimental results for various imperfect communication settings.

cooperative extensions of single-agent bandit algorithms (Kolla et al., 2018, Dubey and Pentland, 2020a, Cesa-Bianchi et al., 2019) obey this assumption, where the decision-making for any agent is independent of any other agent, conditioned on the observed rewards. In this setting, agents merely treat messages as additional pulls to construct stronger estimators, and do not strategize collectively. This bound is exact (up to constants) for a variety of communication graphs G. For instance, for linear and circular graphs, $\frac{\alpha^\star(G_\gamma)}{\alpha(G_\gamma)} = o(1)$, and $\alpha^\star(G_\gamma) = \alpha(G_\gamma)$ for $d-$regular graphs (Turán, 1941).

7 Experimental Results

We consider the 10-armed bandit with rewards drawn from Gaussian distributions with $\sigma_k = 1$ for each arm, such that $\mu_1 = 1$ and $\mu_k = 0.5$ for $k \neq 1$, and the number of agents $N = 50$, where we repeat each experiment 100 times with G selected randomly from different families of random graphs. The bottom row Figure 3 corresponds to Erdos-Renyi graphs with $p = 0.7$. The top row of figures (a), (c) and (d) corresponds to multi-star graphs and (b) and (e) corresponds to random tree graphs. We set $\xi = 1.1$ and $\gamma = \max\{3, d_\star(G)/2\}$.

Stochastic Link Failure. Figure-3(a) and Figure-3(b) summarise performance of `RCL(RS)-LF` and `RCL(MP)-LF` comparing it with corresponding reward-sharing and message-passing UCB-like algorithms, in which $p_i = 1 \forall i \in [N]$. for different p values. The group regret is given at $T = 500$. Results validate our claim that probabilistic message discarding improves performance for irregular graphs and provide competitive performance for *near*-regular graphs.

Stochastic Delays. We compare performance of `RCL-SD` with `UCB1`. We draw delays from a bounded distribution with $\mathbb{E}[\tau] = 10$ and $\tau_{\max} = 50$. The results are summarized in Figure 3(c).

Adversarial Communication. We compute the (approximate) dominating set via the algorithm provided in `networkx` for each connected component in G_γ. We draw corruptions uniformly from the range $[0, \epsilon]$ for each message, where ϵ is increased from 10^{-3} to 10^{-2}. The group regret at $T = 500$ against various ϵ is presented in Figure 3(d) against individual `UCB1` and cooperative UCB with message-passing (`MP-UCB`), which incur larger regret increasing linearly with ϵ.

Perfect Communication. We compare the regret curve for $T = 1000$ for our delayed `delayed(MP)-UCB` against regular `MP-UCB` in Figure 3(e). We use $\bar{\gamma} = 2$. It is evident that delayed incorporation of messages markedly improves performance across both networks.

8 Conclusions

In this paper, we studied the cooperative bandit problem with three different imperfect communication settings. For each environment, we proposed algorithms with competitive empirical performance and provided theoretical guarantees on the incurred regret. Further, we provided an algorithm for perfect communication that comfortably outperforms existing baseline approaches. We additionally provided a tighter network-dependent minimax lower bound for problem as well. We believe that our contributions can be of immediate utility in applications, moreover, future inquiry can be pursued in several different directions, e.g., multi-agent reinforcement learning and contextual bandit learning.

Ethical Considerations. Our work is primarily theoretical, and we do not foresee any negative societal consequences arising specifically from our contributions in this paper.

References

J. Altschuler, V.-E. Brunel, and A. Malek. Best arm identification for contaminated bandits. *Journal of Machine Learning Research*, 20(91):1–39, 2019.

P. Auer, N. Cesa-Bianchi, and P. Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

B. Awerbuch and R. Kleinberg. Online linear optimization and adaptive routing. *Journal of Computer and System Sciences*, 74(1):97–114, 2008.

N. Cesa-Bianchi, C. Gentile, and Y. Mansour. Delay and cooperation in nonstochastic bandits. *The Journal of Machine Learning Research*, 20(1):613–650, 2019.

P. Crescenzi, V. Kann, and M. Halldórsson. A compendium of np optimization problems, 1995.

M. H. DeGroot. Reaching a consensus. *Journal of the American Statistical Association*, 69(345): 118–121, 1974.

A. Dubey and A. Pentland. Cooperative multi-agent bandits with heavy tails. In *International Conference on Machine Learning*, pages 2730–2739. PMLR, 2020a.

A. Dubey and A. Pentland. Private and byzantine-proof cooperative decision-making. In *Proceedings of the 19th International Conference on Autonomous Agents and MultiAgent Systems*, pages 357–365, 2020b.

A. Garivier and O. Cappé. The kl-ucb algorithm for bounded stochastic bandits and beyond. In *Proceedings of the 24th annual conference on learning theory*, pages 359–376. JMLR Workshop and Conference Proceedings, 2011.

A. Ghosh, S. R. Chowdhury, and A. Gopalan. Misspecified linear bandits. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

A. Gupta, T. Koren, and K. Talwar. Better algorithms for stochastic bandits with adversarial corruptions. *arXiv preprint arXiv:1902.08647*, 2019a.

S. Gupta, S. Chaudhari, G. Joshi, and O. Yağan. Multi-armed bandits with correlated arms. *arXiv preprint arXiv:1911.03959*, 2019b.

S. Hosseini, A. Chapman, and M. Mesbahi. Online distributed convex optimization on dynamic networks. *IEEE Transactions on Automatic Control*, 61(11):3545–3550, 2016.

P. Joulani, A. Gyorgy, and C. Szepesvári. Online learning under delayed feedback. In *International Conference on Machine Learning*, pages 1453–1461. PMLR, 2013.

R. M. Karp. Reducibility among combinatorial problems. In *Complexity of computer computations*, pages 85–103. Springer, 1972.

R. K. Kolla, K. Jagannathan, and A. Gopalan. Collaborative learning of stochastic bandits over a social network. *IEEE/ACM Transactions on Networking*, 26(4):1782–1795, 2018.

L. Lai, H. Jiang, and H. V. Poor. Medium access in cognitive radio networks: A competitive multi-armed bandit framework. In *2008 42nd Asilomar Conference on Signals, Systems and Computers*, pages 98–102. IEEE, 2008.

P. Landgren, V. Srivastava, and N. E. Leonard. On distributed cooperative decision-making in multiarmed bandits. In *European Control Conference (ECC)*, pages 243–248. IEEE, 2016a.

P. Landgren, V. Srivastava, and N. E. Leonard. Distributed cooperative decision-making in multiarmed bandits: Frequentist and bayesian algorithms. In *2016 IEEE 55th Conference on Decision and Control (CDC)*, pages 167–172. IEEE, 2016b.

J. Leskovec. *Dynamics of large networks*. PhD thesis, Carnegie Mellon University, School of Computer Science, Machine Learning . . . , 2008.

N. Linial. Locality in distributed graph algorithms. *SIAM Journal on computing*, 21(1):193–201, 1992.

T. Lykouris, V. Mirrokni, and R. Paes Leme. Stochastic bandits robust to adversarial corruptions. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pages 114–122, 2018.

U. Madhushani and N. E. Leonard. Heterogeneous stochastic interactions for multiple agents in a multi-armed bandit problem. In *18th European Control Conf.*, pages 3502–3507, 2019.

U. Madhushani and N. E. Leonard. Distributed bandits: Probabilistic communication on d-regular graphs. *arXiv preprint arXiv:2011.07720*, 2020.

U. Madhushani and N. E. Leonard. Heterogeneous explore-exploit strategies on multi-star networks. *IEEE Control Systems Letters*, 5(5):1603–1608, 2021.

D. Martínez-Rubio, V. Kanade, and P. Rebeschini. Decentralized cooperative stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 4531–4542, 2019.

G. Neu, A. Antos, A. György, and C. Szepesvári. Online markov decision processes under bandit feedback. In *Advances in Neural Information Processing Systems*, pages 1804–1812, 2010.

V. Srivastava, P. Reverdy, and N. E. Leonard. Surveillance in an abruptly changing world via multiarmed bandits. In *53rd IEEE Conference on Decision and Control*, pages 692–697. IEEE, 2014.

P. Turán. On an external problem in graph theory. *Mat. Fiz. Lapok*, 48:436–452, 1941.

C. Vernade, O. Cappé, and V. Perchet. Stochastic bandit models for delayed conversions. *arXiv preprint arXiv:1706.09186*, 2017.

M. J. Weinberger and E. Ordentlich. On delayed prediction of individual sequences. *IEEE Transactions on Information Theory*, 48(7):1959–1976, 2002.

T. Yang, X. Yi, J. Wu, Y. Yuan, D. Wu, Z. Meng, Y. Hong, H. Wang, Z. Lin, and K. H. Johansson. A survey of distributed optimization. *Annual Reviews in Control*, 47:278–305, 2019.