Stochastic Policy Optimization with Heuristic Information for Robot Learning

Abstract: Stochastic policy-based deep reinforcement learning (RL) approaches have remarkably succeeded to deal with continuous control tasks. However, applying these methods to manipulation tasks remains a challenge since actuators of a robot manipulator require high dimensional continuous action spaces. In this paper, we propose exploration-bounded exploration actor-critic (EBE-AC), a novel deep RL approach to combine stochastic policy optimization with interpretable human knowledge. The human knowledge is defined as heuristic information based on both physical relationships between a robot and objects and binary signals of whether the robot has achieved certain states. The proposed approach, EBE-AC, combines an off-policy actor-critic algorithm with an entropy maximization based on the heuristic information. On a robotic manipulation task, we demonstrate that EBE-AC outperforms prior state-of-the-art off-policy actor-critic deep RL algorithms in terms of sample efficiency. In addition, we found that EBE-AC can be easily combined with latent information, where EBE-AC with latent information further improved sample efficiency and robustness.

Keywords: Robot manipulation, Reinforcement learning, Stochastic policy

1 Introduction

A challenge to human-level AI [1] is still ongoing and recently deep reinforcement learning (RL) approaches have remarkably shown outstanding results beyond human in the fields of board and video games [2, 3]. As a greatly unexplored area adapting deep RL, robot manipulation is one of the challenging applications due to complex nonlinear dynamics and huge continuous action spaces [4]-[7]. Various and stable robot manipulation skills in real-world environments [8], where the laws of physics are strictly applied, are required to solve complex tasks, such as moving, grasping, pushing, and placing. It is, therefore, still a challenge to solve these complex tasks through deep RL approaches.

In front of the advanced dexterity capabilities of human hands, learning the dexterity with functionality to autonomously pick and place objects has always been a long-standing challenge for robotics [9, 10]. To solve complex manipulation tasks, various approaches have been presented to utilize human knowledge, which includes learning from human demonstrations and optimizing hyper-parameters empirically [11]-[18]. The first improves sample efficiency of learning by providing good expert demonstration data to solve a given task [13]-[16]. In general, the human demonstrations can be used not only as a loss function of inverse RL but also as reusable experience data of off-policy RL. However, it is very expensive to obtain sophisticated real-world demonstrations for every single task.

As the second approach utilizing human knowledge, empirical hyper-parameter tuning [19], has helped optimize learning progress since hyper-parameters are highly related to not only neural network architectures but also reward designs in the deep RL field. On the whole, hyper-parameter tuning is widely used to ensure that learning algorithms gain good performance, however, it typically tends to react very sensitively to initial hyper-parameter settings for each task [18]. This results in the inefficiency of the learning process because it is necessary to perform hyper-parameter tuning every task.

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

A heuristic (informed) strategy using problem-specific knowledge has been generally known as a more efficient solution than an uninformed strategy using only the problem itself [20]. Since manipulation skills are under the laws of physics, informed human knowledge, such as moving in the direction of narrowing the distance, being in alignment with the target object, and grasping the center of gravity of the object, can be helpful to find solutions efficiently in robot manipulation.

In this paper, we propose a novel deep RL approach to combine stochastic policy optimization well with human knowledge, which we call exploration-bounded exploration actor-critic (EBE-AC). EBE-AC applies interpretable human knowledge, heuristic information based on both physical relationships between a robot and objects and binary signals of whether the robot has achieved certain states, to an off-policy actor-critic algorithm. That is, it combines the off-policy actor-critic algorithm with an entropy maximization based on the heuristic information in designing an objective function. Here, since the heuristic information is composed of physics-related human knowledge, it is interpretable from a human perspective and reusable for various but related learning tasks. To verify the performance of EBE-AC, we have conducted experiments on a robotic manipulation task, *Pick-and-Lift*. The experimental results show that EBE-AC outperforms prior state-of-the-art off-policy actor-critic deep RL algorithms in terms of sample efficiency. In addition, we found that EBE-AC can be easily combined with latent information as DIAYN [21] does, where EBE-AC with latent information further improved sample efficiency and robustness.

2 Related Work

Due to the difficulty of obtaining stable and steady improvement of deterministic policy in applying complex and high dimensional tasks, stochastic policy optimization based on information theory has been examined in problems with continuous state-action spaces [22]-[24]. Many works show that applying a stochastic policy's entropy to an objective function results in good performances. In particular, regularizing both policy and value functions with entropy shows the convergence and stability improvements during training processes.

Through maximum entropy RL [23], a policy is encouraged to perform diverse actions to widely explore a state space while maximizing expected returns. Owing to the diverse actions being able to maximize expected returns, the learned policy can have multiple optimal solutions and obtain stable performance regardless of random initial states. In addition, the maximum entropy approaches are also robust to environmental disturbances such as the presence of adversaries and dynamics change over time because these works focus on the entropy of the action distribution for a given state.

In the unsupervised emergence of diverse skills dictating the states [21], the mutual information between states and latent variables is leveraged to autonomously discover diverse skills. To ensure the different skills being distinguishable, the mutual information between actions and skills should be minimized for a given state. By utilizing the mutual information as a metric of the objective function, a stochastic policy can be also stably and steadily improved under the consideration of additional latent variables.

This paper proposes a novel way to combine human knowledge with a stochastic policy by leveraging the mutual information metrics. Unlike reducing the mutual information between actions and latent variables in [21], the proposed method increases the mutual information between actions and heuristic information based on human knowledge. As a result, the dependency between actions and heuristic information will be guaranteed. Based on the proposed method, the sample efficiency in training is also improved and the stochastic policy has the robustness to complex tasks.

3 Preliminaries

In this section, we address notations for an objective function combined with information metrics theoretically derived.

3.1 Notation

A Markov decision process is defined by the tuple $(\mathcal{S}, \mathcal{A}, p, r)$, where $\mathcal{S}$ is a state space, $\mathcal{A}$ is a continuous action space, $p : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow \mathbb{R}_+$ is a transition probability distribution, and $r : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ is a reward function. In episodic tasks, a discounted return at time t is given as

92 $G_t = \sum_{k=t+1}^{T} \gamma^{k-t-1} r(s_k, a_k)$, where T is an episode horizon, γ is a discount factor, and $r(s_k, a_k)$
93 is a reward for the state-action pair (s_k, a_k). A value function for a policy $\pi(a_t|s_t)$ is represented as
94 $v_\pi(s_t) = \mathbb{E}_\pi[G_t]$.

3.2 Objective Function

96 In this paper, we consider combining RL with the theoretical information metrics, which can en-
97 courage policy optimization in both ways to diverse actions and specific actions in a given state.
98 Therefore, we propose an objective function constructed to learn a policy conditioned on heuristic
99 information according to human knowledge, where the policy can select diverse actions considering
100 not only the states but also the heuristic information.

101 First, we define an information theoretic reward as

$$\widetilde{r}(s_t, a_t) = r(s_t, a_t) + w_s I(a_t; z_t|s_t) + w_z h_{\rho_z}(a_t|s_t, z_t) \tag{1}$$
$$= r(s_t, a_t) + w_s\{h_{\rho_s}(a_t|s_t) - h_{\rho_z}(a_t|s_t, z_t)\} + w_z h_{\rho_z}(a_t|s_t, z_t), \tag{2}$$

102 where z_t is heuristic information, $I(a_t; z_t|s_t)$ is a mutual information between a_t and z_t for the
103 given s_t, $h_\rho(\cdot)$ is an entropy for the distribution ρ, w_s and w_z are positive temperatures, and ρ_s and
104 ρ_z are distributions of action a_t conditioned on s_t and (s_t, z_t), respectively. The distributions ρ_s and
105 ρ_z is induced by a policy π. The heuristic information z_t is defined by external function $z_t = f(s_t)$
106 based on s_t, where $f(\cdot)$ can be physical information between a robot and objects in addition to
107 binary signals representing specific states.

108 Maximizing the reward $\widetilde{r}(s_t, a_t)$ in Equation (1) means that a policy has to find an optimal solution
109 to maximize the reward from the environment while guaranteeing high relation between a_t and
110 z_t, and diverse actions for given information s_t and z_t. In episodic tasks, a discounted return for
111 $\widetilde{r}(s_t, a_t)$ is derived as

$$\widetilde{G}_t = \sum_{k=t+1}^{T} \gamma^{k-t-1}\widetilde{r}(s_k, a_k) = G_t + w_s H_{\rho_s}(a_t|s_t) + (w_z - w_s)H_{\rho_z}(a_t|s_t, z_t), \tag{3}$$

112 where $H_\rho(\cdot) = \sum_{k=t+1}^{T} \gamma^{k-t-1} h_\rho(\cdot)$ is a discounted sum of entropy.

113 By using the discounted return in Equation (3), the objective function is defined as follows:

$$J_\pi(s_t) = \mathbb{E}_\pi[\widetilde{G}_t] = v_\pi(s_t) + w_s\overline{H}_{\rho_s}(a_t|s_t) + (w_z - w_s)\overline{H}_{\rho_z}(a_t|s_t, z_t), \tag{4}$$

114 where $\overline{H}_\rho(\cdot) = \mathbb{E}_\pi[H_\rho(\cdot)]$.

115 To maximize the objective function in Equation (4) with a simple and fast way to implement, this
116 paper designs the stochastic policy using two types of policies as follows:

$$\pi = \pi_m = \begin{cases} \pi_s(a_t|s_t), & \text{for } p_\pi(m = s) = 1 - \epsilon \\ \pi_z(a_t|s_t, z_t), & \text{for } p_\pi(m = z) = \epsilon \end{cases}, \tag{5}$$

117 where $p_\pi(m = x)$ is a probability of selecting policy π_x, and ϵ is a positive constant. By Equation
118 (5), the objective function in Equation (4) is reformulated as follows:

$$\begin{aligned} J_{\pi_m}(s_t) &= \mathbb{E}_{m\in\{s,z\}}[v_{\pi_m}(s_t) + \overline{H}_{\pi_m}] \\ &= (1 - \epsilon)\{v_{\pi_s}(s_t) + w_s\overline{H}_{\pi_s}(a_t|s_t)\} \\ &\quad + \epsilon\{v_{\pi_z}(s_t) + (w_z - w_s)\overline{H}_{\pi_z}(a_t|s_t, z_t)\} = J_{\pi_s, \pi_z}(s_t), \end{aligned} \tag{6}$$

119 where

$$\overline{H}_m = \begin{cases} w_s\overline{H}_{\pi_s}(a_t|s_t), & \text{for } m = s \\ (w_z - w_s)\overline{H}_{\pi_z}(a_t|s_t, z_t), & \text{for } m = z \end{cases}. \tag{7}$$

120 Thus, the maximization problem for Equation (6) is represented as

$$\max_{\pi_s, \pi_z} J_{\pi_s, \pi_z}(s_t), \quad \forall s_t \in \mathcal{S}. \tag{8}$$

Figure 1: **EBE-AC Algorithm:** EBE-AC algorithm consists of two types of policies. Each policy shares the replay buffer and updates its own soft Q-function in an off-policy soft actor critic manner. After updating the soft Q-function and policies, the temperatures are updated.

4   Exploration-Bounded Exploration Actor-Critic

For the maximization problem in Equation (8), a problem decomposition method is adopted to simplify the problem, and then an actor-critic method is adopted to solve the problem with continuous state-action spaces.

4.1   Problem decomposition

The maximization problem in Equation (8) is decomposed into two sub-problems: a maximization problem with exploration entropy and a maximization problem with bounded exploration entropy for the policies π_s and π_z, respectively.

4.1.1   Learning with exploration entropy

For the policy π_s, the problem in Equation (8) is reduced as

$$\max_{\pi_s} \quad J_{\pi_s}(s_t), \quad \forall s_t \in \mathcal{S}, \tag{9}$$

where $J_{\pi_s}(s_t) = v_{\pi_s}(s_t) + w_s \overline{H}_{\pi_s}(a_t|s_t)$. By representing $J_{\pi_s}(s_t) = \widetilde{v}_{\pi_s}(s_t)$, Equation (9) can be derived by successor states as follows:

$$
\begin{aligned}
J_{\pi_s}(s_t) = \widetilde{v}_{\pi_s}(s_t) &= \mathbb{E}_{\pi_s}[G_t + w_s H_{\rho_s}(a_t|s_t)] \\
&= \mathbb{E}_{\pi_s}[r(s_t, a_t) + w_s h_{\pi_s}(a_t|s_t) + \gamma\{G_{t+1} + w_s H_{\rho_s}(a_{t+1}|s_{t+1})\}] \\
&= \mathbb{E}_{\pi_s}[r(s_t, a_t) + w_s h_{\pi_s}(a_t|s_t) + \gamma \widetilde{v}_{\pi_s}(s_{t+1})],
\end{aligned}
\tag{10}
$$

where Equation (10) is the Bellman equation for $\widetilde{v}_{\pi_s}(s_t)$. By applying the modified Bellman backup operation in [23] to Equation (10), then $\widetilde{v}_{\pi_s}(s_t)$ is identical to the soft state value function in [23] as

$$J_{\pi_s}(s_t) = \widetilde{v}_{\pi_s}(s_t) = \mathbb{E}_{\pi_s}[\widetilde{q}_{\pi_s}(s_t, a_t) + w_s h_{\pi_s}(a_t|s_t)] \tag{11}$$

where $\widetilde{q}_{\pi_s}(s_t, a_t) = r(s_t, a_t) + \gamma \mathbb{E}_{s_{t+1} \sim p}[\widetilde{v}_{\pi_s}(s_{t+1})]$ is the soft Q-function for π_s. Because the entropy term $w_s h_{\pi_s}(a_t|s_t)$ incentivizes the policy to choose actions with a high variance, the policy learns to be exploratory for given states.

4.1.2 Learning with bounded exploration entropy

For the policy π_z, the problem in Equation (8) is reduced as

$$\max_{\pi_z} \ J_{\pi_z}(s_t), \quad \forall s_t \in \mathcal{S}, \tag{12}$$

where $J_{\pi_z}(s_t) = v_{\pi_z}(s_t) + (w_z - w_s)\overline{H}_{\pi_z}(a_t|s_t, z_t)$. Through the same procedure in Section 4.1.1, the objective function $J_{\pi_z}(s_t)$ is derived as

$$J_{\pi_z}(s_t) = \widetilde{v}_{\pi_z}(s_t) = \mathbb{E}_{\pi_z}[\widetilde{q}_{\pi_z}(s_t, a_t) + (w_z - w_s)h_{\pi_z}(a_t|s_t, z_t)], \tag{13}$$

where $\widetilde{v}_{\pi_s}(s_t)$ and $\widetilde{q}_{\pi_z}(s_t, a_t)$ are the soft value function and soft Q-function for π_z, respectively.

Unlike the entropy term $w_s h_{\pi_s}(a_t|s_t)$ in Equation (11) which incentivizes the policy to have rich exploration, the entropy term $(w_z - w_s)h_{\pi_z}(a_t|s_t, z_t)$ in Equation (13) does not guarantee that the policy has rich exploration. The variance of the policy's actions depends on whether $(w_z - w_s)$ is positive or not. For example, when $(w_z - w_s)$ is negative, the policy gets a penalty for actions with a high variance. Thus, the policy learned from Equation (13) has bounded exploration.

4.2 Automating entropy adjustment

Because an entropy of policy is affected by not only its own distribution but also the type of task and the magnitude of rewards, the entropy of the policy can vary during training. For this reason, the temperatures w_s and w_z needs to be set according to these considerations. As shown in [25], a temperature can be adjusted by optimizing dual problem for a constrained optimization problem.

First, the objective function in Equation (4) can be represented by soft Q-function as follows:

$$J_\pi(s_t) = \mathbb{E}_\pi[\widetilde{q}_\pi(s_t, a_t) + w_s h_{\rho_s}(a_t|s_t) + (w_z - w_s)h_{\rho_z}(a_t|s_t, z_t)], \tag{14}$$

where $\widetilde{q}_\pi(s_t, a_t) = r(s_t, a_t) + \gamma \mathbb{E}_{s_{t+1} \sim p}[\widetilde{v}_\pi(s_{t+1})]$ and $\widetilde{v}_\pi(s_t) = \mathbb{E}_\pi[\widetilde{G}_t]$ are the soft Q-function and soft value function for π, respectively.

For the modified objective function in Equation (14), a constrained optimization problem can be derived as

$$\max_{\pi} \ \mathbb{E}_\pi[\widetilde{q}_\pi(s_t, a_t)] \tag{15}$$
$$\text{s.t.} \ \mathbb{E}_\pi[h_{\rho_s}(a_t|s_t) - h_{\rho_z}(a_t|s_t, z_t)] \geq 0,$$
$$\mathbb{E}_\pi[h_{\rho_z}(a_t|s_t, z_t)] \geq 0.$$

For the constrained optimization problem, each entropy can be the bound condition to each other, i.e., $h_{\rho_s}(a_t|s_t)$ is the upper bound from the perspective of $h_{\rho_z}(a_t|s_t, z_t)$ and $h_{\rho_z}(a_t|s_t, z_t)$ is the lower bound from the perspective of $h_{\rho_s}(a_t|s_t)$. Because $h_{\rho_s}(a_t|s_t)$ does not have an upper bound, the policy is able to pursue diverse actions only using the state. Using the state and heuristic information, however, the policy is limited to get diverse actions due to the upper bound $h_{\rho_s}(a_t|s_t)$. Thus, for the case of the given state and heuristic information, the policy has to find balanced actions between the upper bound $h_{\rho_s}(a_t|s_t)$ and the lower bound 0.

A dual problem for the constrained optimization problem is defined as

$$\min_{w_s, w_z} \ \mathbb{E}_\pi[\widetilde{q}_\pi(s_t, a_t) + w_s h_{\rho_s}(a_t|s_t) + (w_z - w_s)h_{\rho_z}(a_t|s_t, z_t)], \tag{16}$$

where w_s and w_z are the Lagrange multipliers. The primal problem for π and the dual problem for (w_s, w_z) can be solved by using gradient descent method recursively. In practice, the soft Q-function is modeled by function approximation based on deep RL. Under the consideration of a parameterized soft Q-function for a fixed policy, $\widetilde{q}_\pi(s_t, a_t)$ does not affect to the Lagrange multipliers. Then, the optimal Lagrange multipliers for the given policy can be obtained by

$$w_s^*, w_z^* = \arg \min_{w_s, w_z} \ J_{\mathbf{w}}, \tag{17}$$

where $\mathbf{w} = [w_s, w_z]$ and

$$J_{\mathbf{w}} = \mathbb{E}_\pi[w_s h_{\rho_s}(a_t|s_t) + (w_z - w_s)h_{\rho_z}(a_t|s_t, z_t)]. \tag{18}$$

After obtaining the optimal Lagrange multipliers, the optimization for the policy is performed for the given optimal Lagrange multipliers. Therefore, π and $\mathbf{w}$ are updated by such a recursive optimization.

Algorithm 1 EBE-AC

1: Initialize parameters θ_m and ϕ_m for $m \in \{s, z\}$.
2: Initialize temperatures $\mathbf{w}$.
3: Set: $\bar{\theta}_m \leftarrow \theta_m$ and $\mathcal{D} \leftarrow \emptyset$.
4: **for** each iteration **do**
5:     **for** each environment step **do**
6:         Select behavior policy index: $m_t \sim p_\pi(m_t)$
7:         Sample action: $a_t \sim \pi_{m_t}(a_t|s_t)$
8:         Step environment: $(s_{t+1}, r_t) \sim p(s_{t+1}, r_t|s_t, a_t)$
9:         Store a transition: $\mathcal{D} \leftarrow \mathcal{D} \cup (m_t, s_t, a_t, r_t, s_{t+1})$
10:     **end for**
11:     **for** each gradient step **do**
12:         Update soft Q-functions:
13:         $\theta_m \leftarrow \theta_m - \lambda \nabla_{\theta_m} J_{\theta_m}$ for $m \in \{s, z\}$ using Equation (19)
14:         Update policies:
15:         $\phi_m \leftarrow \phi_m - \lambda \nabla_{\phi_m} J_{\phi_m}$ for $m \in \{s, z\}$ using Equations (11) and (13)
16:         Update temperatures:
17:         $\mathbf{w} \leftarrow \mathbf{w} - \lambda \nabla_{\mathbf{w}} J_{\mathbf{w}}$ using Equation (18)
18:         Update target soft Q-functions:
19:         $\bar{\theta}_m \leftarrow \tau \theta_m + (1 - \tau)\bar{\theta}_m$ for $m \in \{s, z\}$
20:     **end for**
21: **end for**

4.3 Exploration-bounded exploration actor-critic algorithm

To solve the optimization problems in Section 4.1, actor-critic method with function approximation is adopted. For function approximations, parameterization method is applied to soft Q-function $\widetilde{q}_{\theta_m}(s_t, a_t)$ and policy π_{ϕ_m} for $m \in \{s, z\}$ in Equations (11) and (13). As shown in [25], the parameterized soft Q-function $\widetilde{q}_{\theta_m}(s_t, a_t)$ is trained to minimize the soft Bellman residual as

$$J_{\theta_m} = \mathbb{E}_{(s_t, a_t) \sim \mathcal{D}}\left[\frac{1}{2}\left\{\widetilde{q}_{\theta_m}(s_t, a_t) - \left(r(s_t, a_t) + \gamma \mathbb{E}_{s_{t+1} \sim p}[\widetilde{v}_{\bar{\theta}_m}(s_{t+1})]\right)\right\}^2\right], \qquad (19)$$

where $\mathcal{D}$ is a replay buffer,

$$\widetilde{v}_{\bar{\theta}_m}(s_{t+1}) = \begin{cases} \widetilde{q}_{\bar{\theta}_s}(s_{t+1}, a_{t+1}) + w_s h_{\pi_{\phi_s}}(a_t|s_t), & \text{for } m = s \\ \widetilde{q}_{\bar{\theta}_z}(s_{t+1}, a_{t+1}) + (w_z - w_s)h_{\pi_{\phi_z}}(a_t|s_t, z_t), & \text{for } m = z \end{cases},$$

and $\bar{\theta}_m$ is the parameters of a target soft Q-function obtained as an exponentially moving average of the soft Q-function parameters. After obtaining the parameterized soft Q-functions, the parameterized policies and temperatures are updated sequentially.

These updates are summarized in Algorithm 1. The soft Q-functions and policies are updated in the same manner in soft actor-critic [25]. As the soft actor-critic uses two soft Q-functions to mitigate positive bias in a policy improvement, we also use two soft Q-functions for each policy. For the simplicity of Algorithm 1, we omit a detailed description of the two soft Q-functions for each policy.

5 Experiments

We implement a robotic manipulation task, *Pick-and-Lift*, modified from that of RLBench [26], where the task environment consists of a single UR3 arm with 6 DoF including the two-finger gripper, a cube object on a table, and a target position, as shown in Figure 2. The manipulation task requires successive hierarchical sub-tasks, such as reaching out the gripper for the target object, grasping stably the object, and lifting the object without pitching, and moving and exactly placing the object to the target position. In addition, we design the reward of *Pick-and-Lift* task as the sum of dense and sparse rewards, in detail the rewards for reaching and moving sub-tasks are given by dense terms of distances among the robot's gripper, the object and the target position, and the rewards for grasping is given by sparse terms of the binary signal according to whether or not to succeed in grasping.

| (a) reaching the object | (b) grasping the object | (c) moving to the target position |

Figure 2: *Pick-and-Lift* task: it requires reaching out the gripper for the target object, grasping stably the object, and moving and exactly placing the object to the target position.

| (a) Episode lengths | (b) Episode rewards | (c) Success rates |

Figure 3: Training curves according to the number of episodes.

To demonstrate our method, we evaluate EBE-AC compared to SAC [25] and DIAYN [21], state-of-the-art methods in the field of stochastic policy based on deep RL. In addition, we evaluate EBE-AC with DIAYN in order to show effects of our method combining with latent information used in DIAYN. In our experiments, the performance is measured by learning from scratch without any pre-trained individual skill models. The total number of steps for training is 10^6 and the maximum steps per episode is 10^2. An episode ends when the task fails or succeeds. Here, the task fails when one of the following cases occurs: (1) the object falls under the table, (2) the robot moves the object by pushing not grasping, and (3) the task does not succeed until the episode reaches the maximum step. In the case of the success that the robot moves the object to the target position, a huge reward is given for the success. Whenever an episode ends, each method updates its own neural network models.

We evaluate EBE-AC(ϵ) with $\epsilon = 0.1$ and 0.2 defined in Equation (5) and EBE-AC(ϵ) combined with DIAYN. Figure 3 represents training curves for episode rewards, episode lengths and success rates. As shown in Figure 3a, each method has a different episode length over the number of episodes due to the terminate conditions[1]. The case of an episode length equal to 100 means the task failure. In other words, many training steps are spent in the episode and it leads to a decrease in opportunities to experience new episodes.

Due to the decrease in opportunities to experience new episodes, the methods having the small number of episodes obtain low episode rewards as shown in Figure 3b. A range of the episode reward in y-axis is roughly divided into three cases as follows:

- *Range 1*. (episode reward < 0): the robot tries to reach the object.
- *Range 2*. ($0 <$ episode reward < 100): the robot tries to grasp the object.
- *Range 3*. ($100 <$ episode reward): the robot tries to move the object to the target position.

Comparing EBE-AC methods, inclusive of EBE-AC with DIAYN, with SAC and DIAYN, EBE-AC methods reach *Range 2* faster than the other methods. However, methods including SAC can not reach *Range 3*. It means that these methods are stuck in local optimums *Range 2* during training.

---

[1]The episode length means the number of steps per episode. For all methods, the sum of the episode lengths over the number of episodes are equal to the total number of steps for training

225 EBE-AC(0.1) and EBE-AC with DIAYN methods reach *Range 3* faster than DIAYN. Especially,
226 EBE-AC(0.2) with DIAYN is noticeably faster than DIAYN. In a part of *Range 3*, DIAYN has more
227 episode rewards than EBE-AC(0.2) with DIAYN owing to exploiting grasping rewards, which will
228 be described in more detail in Figure 4.

229 In Figure 3c which represents the success rate, it is also observed that only the methods reaching
230 *Range 3* have meaningful success rates. EBE-AC(0.2) with DIAYN outperforms the other methods
231 and EBE-AC(0.1) has better success rates than DIAYN. Since EBE-AC is composed of the policy
232 with exploration entropy and the policy with bounded exploration entropy, it can be seen as the
233 combination of SAC's policy with the proposed policy with bounded exploration entropy, where
234 the policies are linked by the temperature optimization. Through the composition characteristics of
235 EBE-AC and experimental results for the fast convergences, therefore, it is shown that our method
236 is able to help the prior works in terms of the sample efficiency.

(a) Reward for reaching
the object

(b) Reward for grasping
the object

(c) Reward for moving the object
to the target position

Figure 4: Training curves according to the number of episodes.

237 Figure 4 represents training curves for three types of rewards, which are the components of the
238 episode rewards[2]. As shown in Figure 4a, all the methods have good rewards for reaching the
239 object. However, the performances of the methods are represented differently in Figures 4a and 4b.
240 Some methods including SAC maintains high rewards for grasping the object, but these methods can
241 not obtain the rewards for moving the object to the target position. The high rewards for grasping
242 means that the robot holds the object in the gripper. This case is shown that these methods are stuck
243 in local optimums. EBE-AC(0.2) with DIAYN, EBE-AC(0.1) and DIAYN do not maintain high
244 rewards for grasping, but obtain the rewards for moving. It means that these methods find better
245 optimums than those of the other methods. EBE-AC(0.2) with DIAYN and EBE-AC(0.1) pass the
246 local optimums before DIAYN in order to pursue the success reward at the end of the episode.
247 However, DIAYN spends more time to obtain the rewards for grasping as shown in Figure 3a. For
248 this reason, EBE-AC(0.2) with DIAYN and EBE-AC(0.1) obtain slightly lower episode rewards than
249 DIAYN in Figure 3b, but our methods reach much faster the success condition than DIAYN.

250 For all Figures, EBE-AC(0.2) with DIAYN has lower variances than the other methods. Especially,
251 EBE-AC(0.2) with DIAYN has very low variances in the rewards for grasping as shown in Figure 4b,
252 which is designed by the sparse reward. It means that EBE-AC combined with DIAYN is improve
253 not only the sample efficiency but also the robustness.

254 6   Conclusion

255 In this paper, we proposed exploration-bounded exploration actor-critic (EBE-AC), a novel deep
256 RL algorithm that can optimize a stochastic policy through the use of heuristic information. The
257 heuristic information includes interpretable human knowledge related to physical relationships be-
258 tween a robot and objects, which can be reused in various but related learning tasks. In a robotic
259 manipulation task, we demonstrated that the proposed algorithm outperformed prior state-of-the-art
260 off-policy actor-critic deep RL algorithms, such as soft actor-critic and DIAYN, in terms of sample
261 efficiency. In addition, we extended the algorithm by means of latent information as DIAYN does
262 such that the extended algorithm can further improve sample efficiency and robustness.

---

[2]Because the success condition is the state that the robot moves the object to the target position, the reward
for moving the object to the target position include the huge success reward at the end of the episode.

References

[1] J. McCarthy. From here to human-level ai. Artificial Intelligence, 171(18):1174–1182, 2007.

[2] O. Vinyals, I. Babuschkin, W. M. Czarnecki, M. Mathieu, A. Dudzik, J. Chung, D. H. Choi, R. Powell, T. Ewalds, P. Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. Nature, 575(7782):350–354, 2019.

[3] C. Berner, G. Brockman, B. Chan, V. Cheung, P. Debiak, C. Dennison, D. Farhi, Q. Fischer, S. Hashme, C. Hesse, R. Józefowicz, S. Gray, C. Olsson, J. Pachocki, M. Petrov, H. P. de Oliveira Pinto, J. Raiman, T. Salimans, J. Schlatter, J. Schneider, S. Sidor, I. Sutskever, J. Tang, F. Wolski, and S. Zhang. Dota 2 with large scale deep reinforcement learning. CoRR, abs/1912.06680, 2019.

[4] P. Henderson, R. Islam, P. Bachman, J. Pineau, D. Precup, and D. Meger. Mastering the game of go with deep neural networks and tree search. Nature, 529:484–489, Jan. 2016.

[5] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. Journal of Machine Learning Research, 17(39):1–40, 2016.

[6] S. Gu, E. Holly, T. Lillicrap, and S. Levine. Deep reinforcement learning for robotic manipulation with asynchronous off-policy updates. 2017 IEEE International Conference on Robotics and Automation, pages 3389–3396, Aug. 2017.

[7] L. Fan, Y. Zhu, J. Zhu, Z. Liu, O. Zeng, A. Gupta, J. Creus-Costa, S. Savarese, and L. Fei-Fei. Surreal: Open-source reinforcement learning framework and robot manipulation benchmark. Proceedings of The 2nd Conference on Robot Learning, 87:767–782, Oct. 2018.

[8] K. Pertsch, Y. Lee, and J. J. Lim. Accelerating reinforcement learning with learned skill priors. Conference on Robot Learning, 2020.

[9] A. Billard and D. Kragic. Trends and challenges in robot manipulation. Science, 364(6446), 2019. doi:10.1126/science.aat8414.

[10] R. Jeong, J. T. Springenberg, J. Kay, D. Zheng, Y. Zhou, A. Galashov, N. Heess, and F. Nori. Learning dexterous manipulation from suboptimal experts. Conference on Robot Learning, 2020.

[11] T. Welschehold, C. Dornhege, and W. Burgard. Learning manipulation actions from human demonstrations. 2016 IEEE/RSJ International Conference on Intelligent Robots and Systems, pages 3772–3777, 2016.

[12] C. Finn, S. Levine, and P. Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. Proceedings of The 33rd International Conference on Machine Learning, 48:49–58, 20–22 Jun 2016.

[13] C. Florensa, D. Held, M. Wulfmeier, M. Zhang, and P. Abbeel. Reverse curriculum generation for reinforcement learning. Proceedings of the 1st Annual Conference on Robot Learning, 78: 482–495, Nov. 2017.

[14] M. Vecerík, T. Hester, J. Scholz, F. Wang, O. Pietquin, B. Piot, N. Heess, T. Rothörl, T. Lampe, and M. A. Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. CoRR, abs/1707.08817, 2017.

[15] T. Hester, M. Vecerik, O. Pietquin, M. Lanctot, T. Schaul, B. Piot, D. Horgan, J. Quan, A. Sendonaris, I. Osband, G. Dulac-Arnold, J. Agapiou, J. Leibo, and A. Gruslys. Deep q-learning from demonstrations. Proceedings of the AAAI Conference on Artificial Intelligence, 32(1), Apr. 2018.

[16] A. Nair, B. McGrew, M. Andrychowicz, W. Zaremba, and P. Abbeel. Overcoming exploration in reinforcement learning with demonstrations. 2018 IEEE International Conference on Robotics and Automation, pages 6292–6299, 2018.

[17] T. Lillicrap, J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra. Continuous control with deep reinforcement learning. arXiv preprint arXiv:1509.02971, 2015.

[18] P. Henderson, R. Islam, P. Bachman, J. Pineau, D. Precup, and D. Meger. Deep reinforcement learning that matters. Proceedings of the AAAI Conference on Artificial Intelligence, 32(1): 1861–1870, Apr. 2018.

[19] M. Kim. Supervised learning-based ddos attacks detection: Tuning hyperparameters. ETRI Journal, 41(5):560–573, 2019. doi:https://doi.org/10.4218/etrij.2019-0156.

[20] S. J. Russell and P. Norvig. Artificial Intelligence: a modern approach. Pearson, 3 edition, 2009.

[21] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine. Diversity is all you need: Learning skills without a reward function. International Conference on Learning Representations, 2019.

[22] T. Haarnoja, H. Tang, P. Abbeel, and S. Levine. Reinforcement learning with deep energy-based policies. Proceedings of the 34th International Conference on Machine Learning, 70: 1352–1361, Aug. 2017.

[23] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. Proceedings of the 35th International Conference on Machine Learning, 80:1861–1870, Jul. 2018.

[24] B. O'Donoghue, R. Munos, K. Kavukcuoglu, and V. Mnih. Combining policy gradient and q-learning. arXiv preprint arXiv:1611.01626v3, 2017.

[25] T. Haarnoja, A. Zhou, K. Hartikainen, G. Tucker, S. Ha, J. Tan, V. Kumar, H. Zhu, A. Gupta, P. Abbeel, and S. Levine. Soft actor-critic algorithms and applications. CoRR, abs/1812.05905, 2018.

[26] S. James, Z. Ma, D. R. Arrojo, and A. J. Davison. Rlbench: The robot learning benchmark learning environment. IEEE Robotics and Automation Letters, 5(2):3019–3026, 2020. doi: 10.1109/LRA.2020.2974707.