INTERACTIVE SEQUENTIAL GENERATIVE MODELS

ABSTRACT

Understanding spatiotemporal relationships among several agents is of considerable relevance for many domains. Team sports represent a particularly interesting real-world proving ground since modeling interacting athletes requires capturing highly dynamic and complex agent-agent dependencies in addition to temporal components. However, existing generative methods in this field either entangle all latent factors into a single variable and are thus constrained in practical applicability, or they focus on uncovering interaction structures, which restricts their generative ability. To address this gap, we propose a framework for multiagent trajectories that augments sequential generative models with latent social structures. First, we derive a novel objective via approximate inference using a disentangled latent space that accurately describes the data generating process in such sequential systems. Based on the proposed training criterion, we then present a model architecture that unifies insights from neural interaction inference and graph-structured variational recurrent neural networks for generating collective movements while allocating latent information. We validate our model on data from professional soccer and basketball. Our framework not only improves upon existing state-of-the-art approaches in forecasting trajectories, but also infers semantically meaningful representations that can be used in downstream tasks.

1 INTRODUCTION

The study of agent behavior governed by temporal and spatial dependencies is of great importance in many different fields, such as autonomous driving (Brown et al., 2020; Rasouli & Tsotsos, 2019), robot navigation (Rudenko et al., 2020), or sports analytics (Tuyls et al., 2021). In particular, accurate detection of implicit causal social structures offers several advantages by removing confounding factors for trajectory forecasting tasks and providing practitioners with interpretable dynamics that can in turn be integrated into downstream decision-making processes or applications.

Modeling the dynamics of multiplayer sports games (Omidshafiei et al., 2022; Le et al., 2017; Yue et al., 2014; Liu et al., 2020) is particularly challenging since accurate trajectory generation in this environment requires capturing highly dynamic and complex underlying modular structures (Makansi et al., 2022). For example, the roles prescribed in a team formation are a poor indicator of the actual behavior observed in a given situation. Moreover, most of the interacting elements inject noise into the forecasting process because they are either irrelevant (e.g., goal keepers) or their influential nature changes as the situation evolves. However, existing methods for modeling sports data rely on graph encoding strategies (Kipf & Welling, 2016; Vaswani et al., 2017) that aggregate social information into only single variables that need to capture all latent stochasticity (Zhan et al., 2018; Yeh et al., 2019; Sun et al., 2019; Omidshafiei et al., 2022).

In recent years, a considerable amount of methods have been proposed that aim to infer interactive components in general multiagent systems via discrete latent variables. These methods are usually formulated as some form of variational autoencoder (Kingma & Welling, 2013; Sohn et al., 2015) that learns latent edge categories of an assumed underlying graph structure (Kipf et al., 2018; Graber & Schwing, 2020; Löwe et al., 2022). However, being the only causal factors specified, the proposed frameworks neglect other potential latent characteristics not originating in mere interactive categories but equally affecting multimodal agent behavior, such as agent intents.

To address previous shortcomings, we propose a novel framework for modeling multiagent trajectory data that enhances existing graph-structured latent variable models by explicitly encoding social

structures in sports games. Since the contemplated spatiotemporal systems are caused by dynamic dependencies among heterogeneous agents, we define this component as a causal graph comprising categorical agent roles and pairwise interactions. Based on the specified generative setting, we then introduce an objective function within the variational autoencoder family and instantiate a concrete architecture for computing the derived training components. Empirically, our model exceeds existing state-of-the-art methods in forecasting trajectories on data from professional soccer and basketball. In addition, we report on extensive quantitative and qualitative analyses wrt. the learned latent variables that show informative properties in generative tasks and downstream applications.

2 BACKGROUND

Given data $\mathcal{D} = \{\boldsymbol{x}_{\leq T}\}_{i=1}^{N}$ consisting of N sequences $\boldsymbol{x}_{\leq T} = \{\boldsymbol{x}_1, ..., \boldsymbol{x}_T\}$, our goal is to estimate the underying data distribution via maximizing the likelihood of the collected evidence, i.e,. $\max p_\theta(\boldsymbol{x}_{\leq T})$. In practice, $p_\theta(\boldsymbol{x}_{\leq T})$ is often highly multimodal, which complicates direct deployment of MLE. A frequently used modeling paradigm for stochasticity in complex multimodal distributions is introducing latent variables and optimizing the variational lower bound on the maginal log-likelihood (Kingma & Welling, 2013; Rezende et al., 2014; Sohn et al., 2015).

Existing conditional variational models for generating highly-structured sequential data $\boldsymbol{x}_{\leq T}$ usually associate a latent variable $\boldsymbol{z}_1, ..., \boldsymbol{z}_T$ with each timestep of the segment to describe the generative process (Bayer & Osendorfer, 2014; Goyal et al., 2017; Fraccaro et al., 2016). The variational RNN (*VRNN*, (Chung et al., 2015)) is one renowned instantiation in this domain that, assuming specific dependency structures in the generative and inference parts, arrives at the following lower bound on $\log p_\theta(\boldsymbol{x}_{\leq T})$:

$$\mathbb{E}_{q_\phi(\boldsymbol{z}_{\leq T}|\boldsymbol{x}_{\leq T})}\Big[\sum_{t=1}^{T} \log p_\theta(\boldsymbol{x}_t|\boldsymbol{z}_{\leq t}, \boldsymbol{x}_{<t}) - \mathcal{KL}[q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{\leq t}, \boldsymbol{z}_{<t}) \,\|\, p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t})]\Big], \quad (1)$$

where the joint distribution $p_\theta(\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t})$ is captured via a recurrent neural network $\boldsymbol{h}_t = f_{RNN}(\boldsymbol{x}_t, \boldsymbol{z}_t, \boldsymbol{h}_{t-1})$. Given the temporal and multimodal notion of human movement, sequential generative models constitute a good starting point for designing a framework tailored to multiagent trajectories. However, such approaches only account for the temporal aspect of the problem, but neglect potential social dependencies at each timestep.

Adding Graph Structure   As a remedy, sequential data can be augmented by a social dimension $\boldsymbol{x}_{\leq T} = \{\boldsymbol{x}_{\leq T}^{(a)}, \forall a \in \mathcal{A}\}$, where $\boldsymbol{x}_t^{(a)} \in \mathbb{R}^d$ denotes a d-dimensional feature representation of agent $a \in \mathcal{A}$ at time t (e.g., its 2D position). Permutation invariant models are a prerequisite for processing sequential sets with potentially divergent cardinality, so a direct adoption of Eq. 1 in multiagent settings would implicitly impose the assumption of social independence across agent trajectories. This assumption is trivially inappropriate for interactive systems; thus, related work proposes sensitive solutions - usually in the form of graph encoding strategies - to capture agent-agent interactions.

Yeh et al. (2019) introduce the graph VRNN (*GVRNN*), which operates within the VRNN framework with graph neural networks (GNNs, Battaglia et al. (2018)) representing agents and their interactions as nodes and edges, respectively. More formally, the architecture for computing the components in Eq. 1 amounts to the following structure:

$$p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}) = \mathcal{N}(\boldsymbol{z}_t; \text{GNN}_{prior}(\boldsymbol{h}_{t-1})) \quad (2)$$

$$q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{\leq t}, \boldsymbol{z}_{<t}) = \mathcal{N}(\boldsymbol{z}_t; \text{GNN}_{enc}([\boldsymbol{x}_t, \boldsymbol{h}_{t-1}])) \quad (3)$$

$$p_\theta(\boldsymbol{x}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{\leq t}) = \mathcal{N}(\boldsymbol{x}_t; \text{GNN}_{dec}([\boldsymbol{z}_t, \boldsymbol{h}_{t-1}])), \quad (4)$$

where $\boldsymbol{h}_t$ is the set of recurrent agent states $\boldsymbol{h}_t^{(a)} = f_{RNN}(\boldsymbol{x}_t^{(a)}, \boldsymbol{z}_t^{(a)}, \boldsymbol{h}_{t-1}^{(a)})$. We emphasize that, although factorized, the latent space is not marginally independent across agents since each $\boldsymbol{z}_t^{(a)}$ is conditioned on information of all other entities via the (assumed) fully-connected graph. However, in many spatiotemporal patterns, most of the observed elements are irrelevant or even distracting, and the specific composition of relevant factors can change rapidly. Thus, a better strategy is to explicitly detect semantic classes that describe the underlying structural component before aggregating social information into the entangled variables.

Figure 1: *Left:* Illustration of the output layer of an interaction module (encoder q_{ϕ_1} or prior p_{θ_2}) for a target agent $a \in \mathcal{A}$ and an neighboring agent $j \in \mathcal{A}$, where $\boldsymbol{v}$ and $\boldsymbol{e}$ are node and edge embeddings, respectively. *Right:* Illustration of an interaction network (decoder p_{θ_1}, prior p_{θ_2}, or encoder q_{ϕ_2}) that is parameterized by realized elements from the discrete latent subspace: $\mathcal{E}_t^{(a)}$ picks from multiple node-to-edge MLPs, and $\mathcal{K}_t^{(a)}$ picks from multiple edge-to-node MLPs run in parallel. Thus, implicit knowledge about fundamentally different interaction patterns is encapsulated in the parameters of the edge MLPs associated with the corresponding class. The encoded neighborhood communication $\boldsymbol{e}^{(a,j)}$ contingent on the predicted interaction type, has different behavioral consequences based on the specific role the target agent is currently adopting. See Appendix B.1 for a formalization of this principle.

3 METHOD

In the following, we derive a novel training criterion to model the joint distribution of agent trajectories $p_\theta(\boldsymbol{x}_{\leq T})$ using latent variables. To address shortcomings of existing methods, our formalization uses disentangled factors of variation that explicitly include a discrete latent subspace describing an assumed social structure inherent in multiagent systems. Having conceptualized our modeling goal, we then instantiate a concrete architecture that computes the derived training components. The architecture draws on insights from neural interaction learning to allocate all latent information into the intended variables. Appendix B.2 details how the model is trained in an end-to-end fashion.

3.1 DERIVING THE TRAINING OBJECTIVE

Latent Variables A good starting point for conceptualizing appropriate modeling solutions is to concretize the assumptions wrt. the causal factors underlying our collected data $\boldsymbol{x}_{\leq T}$. In this context, we argued previously that spatiotemporal multiagent data differ from their 1D sequential counterpart solely in its unknown form of relational patterns. For the multiagent systems contemplated in this work, this interaction form is highly dynamic and varies both in the type of interaction and in the specific role of the interacting participants. For example, in a turnover sequence in soccer, both the role performed (e.g., attacker to defender) and the influential nature (e.g., on the ball agent from ball carrying to pressure exerting) of each player change within a few moments. To reflect such structures in the model, we augment sequential VAEs by introducing latent causal graphs $\mathcal{G}_t = \{\mathcal{K}_t, \mathcal{E}_t\}$, where $\mathcal{K}_t$ represents the set of discrete agent roles at t (e.g., ball, attacker or defender) $\{\mathcal{K}_t^{(a)}, a \in \mathcal{A}\}$[1], and $\mathcal{E}_t$ encodes their (discrete) pairwise strategies in the form of interaction types $\{\mathcal{E}_t^{(a,j)}, (a,j) \in \mathcal{A} \times \mathcal{A}\}$ (e.g., ball handler, intended pass receiver, etc.). To enable the model to selectively exclude potential social confounders, we externally define an interaction type in $\mathcal{E}_t$ as class "no interaction" while the remaining categories are learned from the data.

Stochastic agent behavior is affected not only by the structural state captured in $\mathcal{G}_t$, but also by agent intents, in turn contingent on the inferred communication mechanisms and agent roles. Intuitively, each realization $\boldsymbol{z}_t^{(a)} \in \boldsymbol{z}_t$ thus encodes latent factors of variation in the trajectories not represented by the inferred causal graphs, yet may vary as a function of $\mathcal{G}_t$. Furthermore, it is worth mentioning that via attaching latent variables to individual agents, their respective representative capacity is governed by the cardinality of the agent set. Hence, the complexity of information inherent in larger multi-agent systems can be accounted for in a natural way.

---

[1]For only a single agent type, we have $\mathcal{K}_t = \mathcal{A}$.

Generative Process   We formally express the generative process by incorporating the above description of causal factors into the definition of our modeling goal, i.e., the marginal likelihood $p_\theta(\boldsymbol{x}_{\leq T})$:

$$p_\theta(\boldsymbol{x}_{\leq T}) = \int_{\mathcal{G}_{\leq T}} \int_{\boldsymbol{z}_{\leq T}} p_\theta(\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{\leq T}, \mathcal{G}_{\leq T}) d\boldsymbol{z}_{\leq T} d\mathcal{G}_{\leq T}$$

$$= \sum_{G_{\leq T}} \int_{\boldsymbol{z}_{\leq T}} \prod_{t=1}^{T} p_{\theta_1}(\boldsymbol{x}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{\leq t}, \mathcal{G}_{\leq t}) p_{\theta_2}(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\leq t}) p_{\theta_3}(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) d\boldsymbol{z}_{\leq T},$$

where the model likelihood p_{θ_1} is parameterized using a *decoder*, and p_{θ_2} and p_{θ_3} are the *prior* distributions over the specified latent factors.

Inference Model   Given the generative model, learning representations of data can be seen as learning a variational approximation of the posterior using an *encoder* that constructs the distribution of latent values for a given observation $\boldsymbol{x}_{\leq T}$. We propose the following factorization:

$$q_\phi(\boldsymbol{z}_{\leq T}, \mathcal{G}_{\leq T}|\boldsymbol{x}_{\leq T}) = \prod_{t=1}^{T} q_{\phi_1}(\mathcal{G}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) q_{\phi_2}(\boldsymbol{z}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{\leq t}).$$

Note that, as opposed to the VRNN objective, we do impose restrictions on this approximation when defining its dependency structure by including also future inputs $\boldsymbol{x}_{t+1:T}$ in the conditions of q_{ϕ_1} and q_{ϕ_2}. This has been shown to be empirically beneficial in sequential settings (Goyal et al., 2017; Fraccaro et al., 2016).

Objective Function   We construct an objective function $\mathcal{L}_{DIA}(\boldsymbol{x}_{\leq T}; \phi, \theta)$ for training the introduced concepts p_θ and q_ϕ, by defining a lower-bound on log-likelihood $\log p_\theta(\boldsymbol{x}_{\leq T})$:

$$\mathbb{E}_{q_\phi(\boldsymbol{z}_{\leq T}, \mathcal{G}_{\leq T}|\boldsymbol{x}_{\leq T})} \left[\sum_{t=1}^{T} \log \frac{p_{\theta_1}(\boldsymbol{x}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{\leq t}, \mathcal{G}_{\leq t}) p_{\theta_2}(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\leq t}) p_{\theta_3}(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})}{q_{\phi_1}(\mathcal{G}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) q_{\phi_2}(\boldsymbol{z}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{\leq t})} \right],$$

$$\tag{5}$$

with $q_{\phi_1}(\mathcal{G}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})$ = $q_{\phi_1}(\mathcal{K}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) q_{\phi_1}(\mathcal{E}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})$ and $p_{\theta_3}(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})$ = $p_{\theta_3}(\mathcal{K}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) p_{\theta_3}(\bar{\mathcal{E}}_t|\boldsymbol{x}_{<T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})$.   See Appendix A for a derivation of Eq. 5 and an elaboration of the relationship to Eq. 1.

3.2   Architectural Components

Given past realizations $\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}$, the introduced dependency structure in Eq. 5 requires to first infer the structural component $\mathcal{G}_t$ before subsequently generating variables $\boldsymbol{z}_t$ and $\boldsymbol{x}_t$. Hence, we divide the training procedure at each timestep into two distinct phases, with the first phase addressing the calculation of components over $\mathcal{G}_t$ (p_{θ_3} and q_{ϕ_1}), while the subsequent second phase infers components over $\boldsymbol{z}_t$ and $\boldsymbol{x}_t$ (p_{θ_1}, p_{θ_2} and q_{ϕ_2}). The overall architecture is illustrated in Figure 2. We describe the computations in more detail below.

Interaction Graph Learning   First, we uncover the (dynamic) latent graph space by constructing the encoder (and prior) modules estimating $\mathcal{G}_t$, $\forall t \in \{1, ..., T\}$. Since we defined latent concepts $\mathcal{G}_t = \{\mathcal{K}_t, \mathcal{E}_t\}$ in discrete terms (cf. Section 3.1), it is natural is to model the encoder (and prior) as a multivariate distribution of independent Categoricals:

$$q_{\phi_1}(\mathcal{K}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) = \prod_{a \in \mathcal{A}} \text{Cat}\left(\mathcal{K}_t^{(a)}|f_{enc}^{int}(\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}; \phi_1)\right) \tag{6}$$

$$q_{\phi_1}(\mathcal{E}_t|\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) = \prod_{(i,j) \in \mathcal{A} \times \mathcal{A}} \text{Cat}\left(\mathcal{E}_t^{(i,j)}|f_{enc}^{int}(\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}; \phi_1)\right), \tag{7}$$

where function f_{enc} is an encoder neural net. Since the interaction space contains the defined "no interaction" label, the derived probability values over $\mathcal{E}_t$ in a Bernoulli context can be interpreted as importance values that encode the level of influence of interacting neighbors on target agents.

Figure 2: Illustration of the computational dependencies at a timestep for a system with two interacting agents when using one agent type, i.e., $\mathcal{K}_t = \mathcal{A}$. We only show the first layer of the overall two-layer graph network in the interaction part (left side) to clarify the injection of the GRU states. Red connections denote the parts utilized only during training, orange connections used during inference. We use a diamond shape to indicate the value is deterministic, and use a circle to indicate the variable is stochastic.

While elements in $\mathcal{K}_t$ are anchored to the elements of the agent set, interactive patterns $\mathcal{E}_t$, however, are defined non-symmetrically over all agent pairs. Thus, we impose a function class on f_{enc} that enables learning single-agent as well as pairwise representations based on which we can classify over both node and relation variables. Inspired by Kipf et al. (2018), we employ an adapted variant of GNNs similar to interaction networks (Gilmer et al., 2017) that operates by learning alternating node and edge representations through an iterative process where the learned edge embeddings are used as messages for neighborhood aggregation[2].

We model the input to $f_{enc}(\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})$ via multiple GRU cells (Chung et al., 2014) defined over quantities related to the individual agents. More formally, f_{enc} is given by

$$[\boldsymbol{v}_{enc}^{int}, \boldsymbol{e}_{enc}^{int}] = f_{enc}^{int}(\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) = \text{GNN}_{enc}^{int}([\overrightarrow{\boldsymbol{h}}_{t-1}, \overleftarrow{\boldsymbol{h}}_t], \boldsymbol{h}_{t-1}^{int}; \phi_1), \qquad (8)$$

where $[\cdot, \cdot]$ denotes concatenation, $\overrightarrow{\boldsymbol{h}}_{t-1}$ is a set of forward RNN states $f_{RNN}(\boldsymbol{x}_t^{(a)}, \boldsymbol{z}_t^{(a)}, \overrightarrow{\boldsymbol{h}}_{t-1}^{(a)})$, $\overleftarrow{\boldsymbol{h}}_t$ is a set of backward RNN states $f_{RNN}(\boldsymbol{x}_t^{(a)}, \overleftarrow{\boldsymbol{h}}_{t+1}^{(a)})$, $\boldsymbol{h}_{t-1}^{int}$ is a set of hidden states defined along the edges $f_{RNN}(\mathcal{E}_{t-1}^{(a,j)}, \boldsymbol{h}_{t-1}^{(a,j),int})$ of a fully-connected graph structure, and $\boldsymbol{v}_{enc}^{int}, \boldsymbol{e}_{enc}^{int}$ are the node and edge embeddings of the last/output GNN layer, respectively (cf. Figure 1, left). The concatenated agent sets $[\overrightarrow{\boldsymbol{h}}_{t-1}, \overleftarrow{\boldsymbol{h}}_t]$ refer to the initial node representations of the network and the hidden interaction set $\boldsymbol{h}_{t-1}^{int}$ is concatenated with the edge embeddings of the first GNN layer (cf. Figure 2, left). The usage of multiple message passing rounds (≥ 2) in conjunction with a fully-connected adjacency matrix allows the model to accomodate structural information from the full input when estimating agent and interaction types.

Finally, we model the distributions comprising Eq. (6) and (7) as $q_{\phi_1}(\mathcal{G}_t | \boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) = \text{softmax}(\text{Linear}(f_{enc}^{int}(\boldsymbol{x}_{\leq T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}; \phi_1)))$; see Figure 1. The prior distribution $p_{\theta_3}(\mathcal{G}_t | \boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})$ is derived analogously to the interaction encoder, omitting the summarized future $\overleftarrow{\boldsymbol{h}}_t$ as GNN input.

Adapted GVRNN Once $\mathcal{G}_t \sim q_{\phi_1}$ is generated, the model needs to reason over the remaining components of Eq. (5), while ensuring fully-unsupervised information allocation in latent space wrt. the disentanglment $\{\mathcal{G}_t, \boldsymbol{z}_t\}$. To achieve this, we observe that the functionality of $\mathcal{G}_t$ is grounded

---

[2]See Appendix B.2 for a formalization of the core computations of this GNN variant. Other commonly used graph encoding strategies in the multiagent regime such as graph attention networks Veličković et al. (2017) or transformers Vaswani et al. (2017) update node embeddings via learned attention weights and consequently do not explicitly learn vectorial edge representations, rendering them inappropriate for the problem at-hand.

in uncovering latent social dependencies at every timestep t within a multiagent segment. Thus, the generated $\mathcal{G}_t$ implicitly characterizes the computational graph at specific junctures and, since predictions are carried out autoregressively, encompasses all information required for computing agent states x_t and z_t. Motivated by the previous considerations, we assume $\mathcal{G}_t$ is Markov and thus discard $\mathcal{G}_{<t}$ from the conditions of objects p_{θ_1}, p_{θ_2} and q_{ϕ_2}. The remaining computations of Eq. (5) thereby comply with the structure of $\mathcal{G}_t$-conditional VRNN components (cf. Eq. 1 - 4).

In general, we can use any graph encoding strategy performing forecasting on the inferred latent subspace $\mathcal{G}_t$ to model the distributions over x_t and z_t. An instantiation with interaction networks constitutes a reasonable design choice in the present context, as there is already empirical evidence of their effectiveness for modeling sports tracking data (Yeh et al., 2019; Dick et al., 2022). To accomodate $\mathcal{G}_t$, we parameterize the node and edge functions inherent in each graph network dependent on the predicted values in $\mathcal{K}_t$ and $\mathcal{E}_t$. Consequently, the amount of function approximators the framework can choose from is defined by the externally specified dimensionality in the respective variables. Intuitively, this inductive bias encourages the model to learn semantically meaningful concepts describing distinct movement and interaction patterns and explicitly governs attention towards the important pieces of data when predicting collective movements. See Figure 1 for a detailed visual depiction of the logic and Appendix B.1 for an description of the message passing operations underlying the individual modules. Figure 5b gives an overview of the computational dependencies of the proposed framework.

4 EXPERIMENTS

4.1 SETUP

Data   The *soccer data* contains trajectories of soccer players and the ball extracted from 16 professional soccer matches sampled at 25 frames per second. We assemble a dataset consisting of game excerpts such that the center frames of the sequences at timestep $t = T//2$ correspond to an on-ball event from the set $\mathcal{Y} = \{$pass, other ball action, shot, none$\}$. We choose a sequence length of $2s$ and downsample the data to $10Hz$, i.e., $T = 20$. This extraction process yields a total of roughly 34000 multiagent segments divided into 70% training, 15% validation, and 15% test data. We center and normalize the trajectories onto the range $[-1, 1]$ and transform them so that the team in possession of the ball always plays from left to right.

The STATS SportVU *basketball data* consists of tracking data recorded from the 2016 NBA regular season. Every game sequence has two-dimensional positions of 10 players and the ball sampled at 5 frames per second. The data is split into 60% training, 20% validation, and 20% test sets. All data is translated so that the origin of the underlying coordinate system is mapped onto the top-left corner.

Metrics   We adopt the commonly used Average Displacement Error (ADE) and Final Displacement Error (FDE) metrics to assess the generative performance of future predictions. ADE refers to the l_2 error between the predicted locations and the ground truth averaged over the entire trajectory, while FDE is the l_2 error for the last predicted point (Alahi et al., 2014). Following prior works, we report the minimum over 20 generated samples.

Baselines   We compare our method[3] with a variety of SOTA baselines for modeling sports tracking data: *Weak-Sup* (Zhan et al., 2018), *GVRNN* (Yeh et al., 2019), *dNRI* (Graber & Schwing, 2020), *DAG-Net* (Monti et al., 2021), and *GRIN* (Li et al., 2021b). To enable direct comparison against this diverse set of methods, we benchmark in two experimental configurations.

Firstly, *DAG-Net* and *Weak-Sup* are inherently advantageous in generating agent trajectories by incorporating future locations in form of heuristically generated labels at prediction time. This renders a direct comparison to fully unsupervised generative methods (like ours) biased. To minimize this bias, we report quantitative results on a rather long prediction horizon of $T_{obs} = 10, T_{pred} = 40$ for both methods. Other baselines such as *GRIN* and *dNRI* cannot be trivially tested on these long-term predictions, so we generate results on configuration $T_{obs} = 40, T_{pred} = 10$. Finally, *GVRNN* and our framework (DIA) can be applied to the full range of prediction scenarios since both methods learn spatiotemporal representations autoregressively.

---

[3]The source code will be made publicly available upon acceptance of this manuscript.

	GVRNN	dNRI	GRIN	DIA (Ours)
min ADE	2.60	2.77	3.00	**2.20**
min FDE	5.66	5.52	6.12	**4.51**

	GVRNN	Weak-Sup	DAG-Net	DIA (Ours)
min ADE	9.73	9.47	8.98	**8.29**
min FDE	15.80	16.98	14.08	**12.05**

Table 1: Quantitative results on basketball data (in meters) modeling offensive players for short-term predictions with $T_{pred} = 10$ and $T_{obs} = 40$ (**on top**) and long-term predictions with $T_{pred} = 40$ and $T_{obs} = 10$ (**below**).

MODEL	MINADE	MINFDE
GVRNN	7.48	10.72
DNRI	7.60	10.88
GRIN	7.88	10.54
DIA (OURS)	**7.02**	**9.68**

MODEL	ACCURACY	F1
INTERACTION-RNN-DIAG	0.82	0.85
INTERACTION-RNN-FULL	0.83	0.84
INTERACTION-RNN	**0.88**	**0.91**

Table 2: Results on soccer data. *Left*: Quantitative results for trajectory prediction (in meters) modeling all players with $T_{obs} = 10$ and $T_{pred} = 10$. *Right*: Results for the auxiliary classification task.

4.2 QUANTITATIVE EVALUATION

Baseline Comparisons In the first set of experiments, we benchmark our model against recent generative methods for the task of trajectory forecasting. Our empirical findings are summarized in Table 1 and Table 2 (left). DIA emerges as the best generative tool across all tested tasks improving the best (unsupervised) competitor performance by at least 17.3% minADE and 25.5% minFDE for basketball. The empirical results suggest that our proposed modeling strategy effectively both eliminates interfering social signals and discriminates between different agent and interaction types so that future agent movements can be captured more accurately. In addition, since GRIN represents the only tested method that learns latent variables at sequence level, its comparatively dismal results highlight the hypothesized heterogeneous and dynamic causal nature of multiagent systems in the sports domain. Remarkably, despite its inherent advantages, DIA also outperforms recent supervised generative methods (Weak-Sup and DAG-Net) by at least 8.3% minADE and 16.8% minFDE.

Investigating Latent Structure To quantify the benefit of augmenting the latent space with an explicit causal graph $\mathcal{G}_t$, we compare performance metrics of the GVRNN and an adapted DIA version at varying observation and prediction lengths. For this, we modify the DIA architecture such that the second part of the training procedure is identical to the GVRNN computations. In this way, the resulting performance differences capture only influences originating from the proposed graph mechanism. The left part of figure 3 visualizes the resulting numbers. As can be seen, our DIA version yields substantial performance gains, with the performance difference increasing with task complexity, i.e., prediction horizon. The results highlight that learning agent relationships via information aggregation strategies entangled in single latent variables is insufficient to capture decisive social signals in non-trivial multiagent systems.

The right part of Figure 3 shows predictive results for different agent subgroups when varying the representational capacity of the latent interaction graph $\mathcal{E}_t \in \mathcal{G}_t$. Since separate function approximators are parameterized for each selected interaction class, enlarging the interaction space dimensionality causes overfitting issues, despite higher model expressivity. Thus, the best results are realized by the model configuration with the lowest dimensionality, which still sufficiently encapsulates the underlying system dynamics. Accordingly, this experimental setup can shed light on whether the proposed interaction mechanism $\mathcal{E}_t$ behaves according to our theoretical considerations. For example, in modeling defensive players, we would expect reactive patterns based on the behavior of attacking players, resulting in little intra-group dependencies. Indeed, the results in Figure 3 indicate that our model inherits the expected social behaviors, as the best parameter configuration is

Figure 3: *Left:* Quantitative comparison between GVRNN and an adapted version of our method at different observation and prediction horizons for modeling offensive players. *Right:* Representational capacity of latent $\mathcal{G}_t$ and performance for modeling different agent subgroups. In particular, we fix $\mathcal{K}_t$ and report quantitative results by changing the dimensionality of interaction space $\mathcal{E}_t$.

Figure 4: *Left:* Trajectories of the offensive players and the ball (blue dots) from a data point in the test set of the basketball data. *Top right:* Influence $\mathcal{E}^{(b,r)}$ of the red player r on the ball b. *Bottom right:* Influence of the ball on the red player.

in line with the structural complexity of the different player subgroups. Appendix C.1 provides an analogous discussion for agent types $\mathcal{K}_t \in \mathcal{G}_t$.

Auxiliary Task Finally, we examine the extent to which learned latent categories $\mathcal{G}_t$ serve meaningful semantic contributions beyond trajectory generation tasks. To this end, we report quantitative metrics on a classification task using soccer data. In the first step, we assemble a dataset in which the social context at each time step is defined by the estimated agent-ball influences of a DIA training run. That is, agent locations annotated as "no interaction" when considering influences on the ball node are discarded. We then train a spatiotemporal classification network, termed *Interaction-RNN*, for event detection over $\mathcal{Y}$ on the updated data (more details given in Appendix B.3). We compare our method quantitatively against a diagonal (i.e., using ball trajectories only) and a fully-connected (i.e., using all agents for neighborhood aggregation) version of Interaction-RNN in Table 2 (right). The model configuration trained on the data previously extracted by DIA outperforms both baseline configurations. The results indicate potential advantages of injecting interaction structures induced by DIA in downstream applications, as they facilitate detecting key information for learning spatiotemporal classification tasks.

4.3 QUALITATIVE EVALUATION

To provide more insights in the learned sequential graphs $\mathcal{G}_{\leq T}$ of DIA, we visually depict a multi-agent segment from the test set and estimated probability values within two interaction categories (and one "no interaction" category) in Figure 4. The upper right image shows the influencing factors of the red player on the ball. This interaction structure is mainly characterized by frequent alterna-

tions between the two interaction types with scarce instants of low aggregated influence. Since the interaction values are determined to accurately reflect the input data, the fluctuating pattern observed illustrates highly dynamic social structures in our tested setting.

The figure below encodes the influential structure of the ball as the sending agent on the movements of the red player. Compared to the previous figure, probability values are consistent with one interaction type being active over most of the observed time period. The second interaction type becomes the dominant influential force from the moment the ball is passed to the spatially closest neighbor (green player), and also remains active when the ball reaches the target agent (red player). Thus, the first interaction type encodes more holistic influences, while the second type focuses on more immediate social motion effects. Notably, there are no periods of time in which either of the two interaction modes is inactive. This distinguishes the ball as the central element in basketball and thus affects the movement of all offensive players at any time. The qualitative results provide further evidence for the ability of our model to learn a semantically meaningful discrete latent subspace. More qualitative results are given in Appendix C.3.

5 RELATED WORK

Recent methods for trajectory prediction tasks mostly propose some form of latent variable model, generally formulated as a conditional VAE (Sohn et al., 2015), to capture the stochasticity inherent in future trajectories. At a high level, the concrete approaches differ in their choices of methodological tools for modeling temporal dependencies (e.g. LSTMs (Hochreiter & Schmidhuber, 1997) or GRUs (Chung et al., 2014)) and social relations (e.g., GATs (Veličković et al., 2017) or Transformers (Vaswani et al., 2017)), as well as their latent space characterizations (discrete or continuous). For example, Yeh et al. (2019); Sun et al. (2019); Monti et al. (2021) extend the VRNN to handle agent-agent relations via estimating components of Eq. 1 using graph neural networks. Casas et al. (2020b); Salzmann et al. (2020) choose a similar task formulation as well as interaction encoding strategy Casas et al. (2020a), but generate future trajectories non-autoregressively by flattening the time axis into a single dimension. Other similar approaches (e.g., Girgis et al. (2021); Yuan et al. (2021)) propose transformer-based architectures to encode spatial and temporal relations. There is a plethora of work that aims to improve trajectory forecasting by extending latent information with specific types of agent long-term goals extracted from the trajectory data (Mangalam et al., 2020; 2021; Zhao et al., 2021; Monti et al., 2021; Zhan et al., 2018).

Alternatively, our method can be seen as an novel contribution to the line of research that aims to explicitly infer agent interactions while executing a trajectory prediction task. This task formulation was originally proposed by Kipf et al. (2018), who introduce the NRI framework, a variational autoencoder, where the discrete latent code represents edge predictions in a causal graph. Since the original formulation is limited to learning a single graph for the entire multiagent sequence, several works propose dynamic extensions where the interaction graph can adapt to the conditions per time step (Graber & Schwing, 2020; Li et al., 2020; Gong et al., 2021; Li et al., 2021a). Recently, Löwe et al. (2022) propose to infer causal relations across data points with different underlying interaction graphs but shared dynamics. Other work (Li et al., 2021b) builds upon the NRI framework but leverage a continuous latent space that aims to separate interactive factors from agent intentions.

6 CONCLUSION

In this paper, we presented novel framework for modeling the joint distribution of agent trajectories using latent variables. To alleviate shortcomings of previous works, we described the data generation process using disentangled factors of variation that explicitly include a discrete latent subspace reflecting social structures in sports games. We demonstrated that the emerging architecture performs better in predicting trajectories compared to existing strategies and learns informative latent variables.

AUTHOR CONTRIBUTIONS

If you'd like to, you may include a section for author contributions as is done in many journals. This is optional and at the discretion of the authors.

ACKNOWLEDGMENTS

Use unnumbered third level headings for the acknowledgments. All acknowledgments, including those to funding agencies, go at the end of the paper.

REFERENCES

Alexandre Alahi, Vignesh Ramanathan, and Li Fei-Fei. Socially-aware large-scale crowd forecasting. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2203–2210, 2014.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Justin Bayer and Christian Osendorfer. Learning stochastic recurrent networks. *arXiv preprint arXiv:1411.7610*, 2014.

Samuel R Bowman, Luke Vilnis, Oriol Vinyals, Andrew M Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space. In *20th SIGNLL Conference on Computational Natural Language Learning, CoNLL 2016*, pp. 10–21. Association for Computational Linguistics (ACL), 2016.

Kyle Brown, Katherine Driggs-Campbell, and Mykel J Kochenderfer. A taxonomy and review of algorithms for modeling and predicting human driver behavior. *arXiv preprint arXiv:2006.08832*, 2020.

Sergio Casas, Cole Gulino, Renjie Liao, and Raquel Urtasun. Spagnn: Spatially-aware graph neural networks for relational behavior forecasting from sensor data. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 9491–9497. IEEE, 2020a.

Sergio Casas, Cole Gulino, Simon Suo, Katie Luo, Renjie Liao, and Raquel Urtasun. Implicit latent variable model for scene-consistent motion forecasting. In *European Conference on Computer Vision*, pp. 624–641. Springer, 2020b.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron C Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. *Advances in neural information processing systems*, 28, 2015.

Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. Fast and accurate deep network learning by exponential linear units (elus). *arXiv preprint arXiv:1511.07289*, 2015.

Uwe Dick, Daniel Link, and Ulf Brefeld. Who can receive the pass? a computational model for quantifying availability in soccer. *Data Mining and Knowledge Discovery*, 36(3):987–1014, 2022.

Marco Fraccaro, Søren Kaae Sønderby, Ulrich Paquet, and Ole Winther. Sequential neural models with stochastic layers. *Advances in neural information processing systems*, 29, 2016.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pp. 1263–1272. PMLR, 2017.

Roger Girgis, Florian Golemo, Felipe Codevilla, Martin Weiss, Jim Aldon D'Souza, Samira Ebrahimi Kahou, Felix Heide, and Christopher Pal. Latent variable sequential set transformers for joint multi-agent motion prediction. In *International Conference on Learning Representations*, 2021.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256. JMLR Workshop and Conference Proceedings, 2010.

Dong Gong, Frederic Z Zhang, Javen Qinfeng Shi, and Anton Van Den Hengel. Memory-augmented dynamic neural relational inference. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 11843–11852, 2021.

Anirudh Goyal, Alessandro Sordoni, Marc-Alexandre Côté, Nan Rosemary Ke, and Yoshua Bengio. Z-forcing: Training stochastic recurrent networks. *arXiv preprint arXiv:1711.05411*, 2017.

Colin Graber and Alexander Schwing. Dynamic neural relational inference for forecasting trajectories. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 1018–1019, 2020.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparametrization with gumble-softmax. In *International Conference on Learning Representations (ICLR 2017)*. OpenReview. net, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Thomas Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard Zemel. Neural relational inference for interacting systems. In *International Conference on Machine Learning*, pp. 2688–2697. PMLR, 2018.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Hoang M Le, Yisong Yue, Peter Carr, and Patrick Lucey. Coordinated multi-agent imitation learning. In *International Conference on Machine Learning*, pp. 1995–2003. PMLR, 2017.

Jiachen Li, Fan Yang, Masayoshi Tomizuka, and Chiho Choi. Evolvegraph: Multi-agent trajectory prediction with dynamic relational reasoning. *Advances in neural information processing systems*, 33:19783–19794, 2020.

Jiachen Li, Fan Yang, Hengbo Ma, Srikanth Malla, Masayoshi Tomizuka, and Chiho Choi. Rain: Reinforced hybrid attention inference network for motion forecasting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 16096–16106, 2021a.

Longyuan Li, Jian Yao, Li Wenliang, Tong He, Tianjun Xiao, Junchi Yan, David Wipf, and Zheng Zhang. Grin: Generative relation and intention network for multi-agent trajectory prediction. *Advances in Neural Information Processing Systems*, 34:27107–27118, 2021b.

Guiliang Liu, Oliver Schulte, Pascal Poupart, Mike Rudd, and Mehrsan Javan. Learning agent representations for ice hockey. *Advances in Neural Information Processing Systems*, 33:18704–18715, 2020.

Sindy Löwe, David Madras, Richard Zemel, and Max Welling. Amortized causal discovery: Learning to infer causal graphs from time-series data. In *Conference on Causal Learning and Reasoning*, pp. 509–525. PMLR, 2022.

C Maddison, A Mnih, and Y Teh. The concrete distribution: A continuous relaxation of discrete random variables. In *Proceedings of the international conference on learning Representations*. International Conference on Learning Representations, 2017.

Osama Makansi, J von Kügelgen, F Locatello, P Gehler, D Janzing, Thomas Brox, and B Schölkopf. You mostly walk alone: Analyzing feature attribution in trajectory prediction. In *International Conference on Learning Representations (ICLR)*, 2022.

Karttikeya Mangalam, Harshayu Girase, Shreyas Agarwal, Kuan-Hui Lee, Ehsan Adeli, Jitendra Malik, and Adrien Gaidon. It is not the journey but the destination: Endpoint conditioned trajectory prediction. In *European conference on computer vision*, pp. 759–776. Springer, 2020.

Karttikeya Mangalam, Yang An, Harshayu Girase, and Jitendra Malik. From goals, waypoints & paths to long term human trajectory forecasting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15233–15242, 2021.

Alessio Monti, Alessia Bertugli, Simone Calderara, and Rita Cucchiara. Dag-net: Double attentive graph neural network for trajectory forecasting. In *2020 25th International Conference on Pattern Recognition (ICPR)*, pp. 2551–2558. IEEE, 2021.

Shayegan Omidshafiei, Daniel Hennes, Marta Garnelo, Zhe Wang, Adria Recasens, Eugene Tarassov, Yi Yang, Romuald Elie, Jerome T Connor, Paul Muller, et al. Multiagent off-screen behavior prediction in football. *Scientific reports*, 12(1):1–13, 2022.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

Amir Rasouli and John K Tsotsos. Autonomous vehicles that interact with pedestrians: A survey of theory and practice. *IEEE transactions on intelligent transportation systems*, 21(3):900–918, 2019.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International conference on machine learning*, pp. 1278–1286. PMLR, 2014.

Andrey Rudenko, Luigi Palmieri, Michael Herman, Kris M Kitani, Dariu M Gavrila, and Kai O Arras. Human motion trajectory prediction: A survey. *The International Journal of Robotics Research*, 39(8):895–935, 2020.

Tim Salzmann, Boris Ivanovic, Punarjay Chakravarty, and Marco Pavone. Trajectron++: Dynamically-feasible trajectory forecasting with heterogeneous data. In *European Conference on Computer Vision*, pp. 683–700. Springer, 2020.

Kihyuk Sohn, Honglak Lee, and Xinchen Yan. Learning structured output representation using deep conditional generative models. *Advances in neural information processing systems*, 28, 2015.

Casper Kaae Sønderby, Tapani Raiko, Lars Maaløe, Søren Kaae Sønderby, and Ole Winther. Ladder variational autoencoders. *Advances in neural information processing systems*, 29, 2016.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Chen Sun, Per Karlsson, Jiajun Wu, Joshua B Tenenbaum, and Kevin Murphy. Stochastic prediction of multi-agent interactions from partial observations. *arXiv preprint arXiv:1902.09641*, 2019.

Karl Tuyls, Shayegan Omidshafiei, Paul Muller, Zhe Wang, Jerome Connor, Daniel Hennes, Ian Graham, William Spearman, Tim Waskett, Dafydd Steel, et al. Game plan: What ai can do for football, and what football can do for ai. *Journal of Artificial Intelligence Research*, 71:41–88, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Bing Xu, Naiyan Wang, Tianqi Chen, and Mu Li. Empirical evaluation of rectified activations in convolutional network. *arXiv preprint arXiv:1505.00853*, 2015.

Raymond A Yeh, Alexander G Schwing, Jonathan Huang, and Kevin Murphy. Diverse generation for multi-agent sports games. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4610–4619, 2019.

Ye Yuan, Xinshuo Weng, Yanglan Ou, and Kris M Kitani. Agentformer: Agent-aware transformers for socio-temporal multi-agent forecasting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9813–9823, 2021.

Yisong Yue, Patrick Lucey, Peter Carr, Alina Bialkowski, and Iain Matthews. Learning fine-grained spatial models for dynamic sports play prediction. In *2014 IEEE international conference on data mining*, pp. 670–679. IEEE, 2014.

Eric Zhan, Stephan Zheng, Yisong Yue, Long Sha, and Patrick Lucey. Generating multi-agent trajectories using programmatic weak supervision. *arXiv preprint arXiv:1803.07612*, 2018.

Hang Zhao, Jiyang Gao, Tian Lan, Chen Sun, Ben Sapp, Balakrishnan Varadarajan, Yue Shen, Yi Shen, Yuning Chai, Cordelia Schmid, et al. Tnt: Target-driven trajectory prediction. In *Conference on Robot Learning*, pp. 895–904. PMLR, 2021.

A ALTERNATIVE PERSPECTIVE ON THE OBJECTIVE FUNCTION

Figure 5: Depicting computational dependencies of (a) GVRNN; (b) the proposed interactive sequential latent variable model (DIA); and (c) DIA in relation to GVRNN. Dashed lines indicate the encoding procedures, solid lines the generation process.

Alternatively, Eq. 5 can be written as

$$
\sum_{t=1}^{T} \Big(\log p_{\theta_1}(\boldsymbol{x}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{\le t}, \mathcal{G}_{\le t}) - \mathcal{KL}[q_{\phi_1}(\boldsymbol{z}_t|\boldsymbol{x}_{\le T}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t}) \parallel p_{\theta_2}(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t})]
$$

$$
- \mathcal{KL}[q_{\phi_2}(\mathcal{G}_t|\boldsymbol{x}_{\le T}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) \parallel p_{\theta_3}(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) \Big)
$$

$$
= \sum_{t=1}^{T} \Big(\text{GVRNN}(\overleftarrow{\boldsymbol{h}}_t, \mathcal{G}_t) - \mathcal{KL}[q_{\phi_2}(\mathcal{G}_t(\overleftarrow{\boldsymbol{h}}_t, \overrightarrow{\boldsymbol{h}}_{t-1}, \boldsymbol{h}_{t-1}^{int}) \parallel p_{\theta_3}(\mathcal{G}_t|\overrightarrow{\boldsymbol{h}}_{t-1}, \boldsymbol{h}_{t-1}^{int}) \Big),
$$

where $\mathcal{G}_{\le T}, \boldsymbol{z}_{\le T} \sim q_\phi(\boldsymbol{z}_{\le T}, \mathcal{G}_{\le T}|\boldsymbol{x}_{\le T})$. See also Figure 5. This can be shown as follows:

$$
\int \int q_\phi(\boldsymbol{z}_{\le T}, \mathcal{G}_{\le T}|\boldsymbol{x}_{\le T}) \log \prod_{t=1}^{T} \frac{p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t})p_\theta(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})}{q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le T})q_\phi(\mathcal{G}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{\le t}, \mathcal{G}_{<t})} d\mathcal{G}_{\le T}d\boldsymbol{z}_{\le T}
$$

$$
= \sum_{t=1}^{T} \int \int q_\phi(\boldsymbol{z}_{\le T}, \mathcal{G}_{\le T}|\boldsymbol{x}_{\le T}) \log \frac{p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t})p_\theta(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})}{q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le T})q_\phi(\mathcal{G}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{\le t}, \mathcal{G}_{<t})} d\mathcal{G}_{\le T}d\boldsymbol{z}_{\le T}
$$

$$
= \sum_{t=1}^{T} \int \int q_\phi(\boldsymbol{z}_{\le t}, \mathcal{G}_{\le t}|\boldsymbol{x}_{\le t}) \log \frac{p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t})p_\theta(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})}{q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t})q_\phi(\mathcal{G}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{\le t}, \mathcal{G}_{<t})} d\boldsymbol{z}_{\le t}d\mathcal{G}_{\le t}
$$

$$
= \sum_{t=1}^{T} \int \int q_\phi(\boldsymbol{z}_{<t}, \mathcal{G}_{<t}|\boldsymbol{x}_{<t}) \Big(- \mathbb{E}_{q_\phi(\mathcal{G}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})}\big[\mathcal{KL}[q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le T} \parallel p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})]\big]
$$

$$
- \mathcal{KL}[q_\phi(\mathcal{G}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t}) \parallel p_\theta(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})]\Big)d\boldsymbol{z}_{<t}d\mathcal{G}_{<t}
$$

$$
= \mathbb{E}_{q_\phi(\boldsymbol{z}_{\le T}, \mathcal{G}_{\le T}|\boldsymbol{x}_{\le T})} \bigg[\sum_{t=1}^{T} -\mathcal{KL}[q_\phi(\boldsymbol{z}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le T}) \parallel p_\theta(\boldsymbol{z}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})]
$$

$$
- \mathcal{KL}[q_\phi(\mathcal{G}_t|\boldsymbol{x}_{\le t}, \boldsymbol{z}_{<t}, \mathcal{G}_{\le t}) \parallel p_\theta(\mathcal{G}_t|\boldsymbol{x}_{<t}, \boldsymbol{z}_{<t}, \mathcal{G}_{<t})]\bigg].
$$

B MODEL DETAILS

B.1 ADAPTED GVRNN MODULE

For ease of exposition, we assume an interactive system consisting of two agents and define computations for graph $i \leftarrow j$, where $i \in \mathcal{A}$ and $j \in \mathcal{A}$. Given the predicted class $\mathcal{E}_t^{(i,j)} \in \{1, ..., K\}$, we pick associated parameters for the edge MLP f_e from the set $\{\psi_1, ..., \psi_K\}$ with $\psi_1 = \emptyset$ denoting the manually defined "no interaction" label. Given the predicted class $\mathcal{K}_t^{(i)} \in \{1, ..., M\}$, we pick associated parameters for the node MLP f_v from the set $\{\gamma_1, ..., \gamma_K\}$. The message passing operations for target agent i amount to

$$\boldsymbol{e}^{(i,j)} = f_e([\boldsymbol{v}^{(i)}, \boldsymbol{v}^{(j)}]; \psi_k) \tag{9}$$

$$\boldsymbol{u}^{(i)} = f_v(\boldsymbol{e}^{(i,j)}; \gamma_m). \tag{10}$$

Intuitively, embedding $\boldsymbol{e}^{(i,j)}$ encodes the influence of agent j on target agent i in the form of an vectorial representation. Under the assumption of ceteris paribus, the inferred feature representation varies wrt. the underlying interaction type that instantiates parameter configuration ψ_k. Finally, our module definition realizes role-dependent behavioral patterns on how agent i acts upon the inferred neighborhood influence $\boldsymbol{e}^{(i,j)}$. These patterns are reflected in set $\{\gamma_1, ..., \gamma_M\}$.

B.2 TRAINING & TESTING DETAILS

Instead of absolute positions, our model predicts movements $\Delta \hat{\boldsymbol{x}}_t$ at each timestep. Consequently, we estimate agent locations via $\hat{\boldsymbol{x}}_t = \boldsymbol{x}_{t-1} + \Delta \hat{\boldsymbol{x}}_t$. For simplicity, $\boldsymbol{x}_t$ refers to both relative and absolute positions. For training, the model predicts the next step for the full sequence using samples from the encoder and ground-truth information $\boldsymbol{x}_{\leq T}$. To enable gradient flow through stochastic operations, we use the reparameterization and gumbel-softmax trick (Maddison et al., 2017; Jang et al., 2017) for the continuous $\boldsymbol{z}_t$ and discrete $\mathcal{G}_t$ latent subspace, respectively. At test time, given a mutliagent sequence $\{\boldsymbol{x}_1, ..., \boldsymbol{x}_{T_{obs}}\}$, we get $\hat{\boldsymbol{x}}_{T_{obs}+i}, i \in \mathbb{Z}$ using samples from the prior distributions and take the movement predictions as input.

All models are implemented using PyTorch (Paszke et al., 2019). Training is carried out using Adam (Kingma & Ba, 2014) with default parameters and learning rate of 0.001 and teacher forcing. We select the best performing model using minADE on the validation set. The message passing operations within our graph networks f_e and f_v are 2-layer MLPs with batch normalization (Ioffe & Szegedy, 2015), dropout (Srivastava et al., 2014), and ELU activations (Clevert et al., 2015). In addition, we leverage 2-layer MLPs with LeakyReLU (Xu et al., 2015) activations as feature extractors operating on $\boldsymbol{z}_t$, $\boldsymbol{x}_t$, and $\mathcal{G}_t$. All fully-connected layers are initialized using Xavier initialization (Glorot & Bengio, 2010). For recurrence, we use 2-layer GRU networks (Chung et al., 2014).

The core operations of the GNN modules comprising the DIA can be formally expressed as follows:

$$v \rightarrow e: \quad \boldsymbol{e}^{(i,j)} = f_e([\boldsymbol{v}_i, \boldsymbol{v}_j]), \tag{11}$$

$$e \rightarrow v: \quad \boldsymbol{o}^{(i)} = f_v(\sum_{j \in N(i)} \boldsymbol{e}^{(i,j)}), \tag{12}$$

where $\boldsymbol{v}_i$ is the input feature representation of agent/node i, $\boldsymbol{o}_i$ is the respective node embedding after 1 GNN layer, $N(i)$ denotes the set of agents/nodes that interact with target agent i, $\boldsymbol{e}^{(i,j)}$ is the edge embedding of the first GNN layer, and f_e and f_v are the MLPs described above. For the GNNs of the interaction encoding phase, we define 2 rounds of message passing and utilize additional linear layers operating on the node and edge embeddings of the second GNN layer to output $\mathcal{K}_t$ and $\mathcal{E}_t$, respectively. For the adapted GVRNN modules, we use 1 layer as described in Section B.1 with additional MLPs computing the mean and variance vectors of the Gaussians.

B.3 CLASSIFICATION BASELINE

The proposed classification framework for the spatiotemporal multi-agent regime (*Interaction-RNN*) is essentially geared towards the functionality of an RNN for capturing temporal dependencies of player trajectories. Additionally, to encode interactive agent patterns, we update the inferred RNN

states at each time step using an attention-based graph neural network architecture (Veličković et al., 2017). Thus, the updated feature vectors jointly encode social and temporal information. A final softmax layer is then used for classification and the model is optimized by minimizing the cross-entropy loss. Because the labels denote ball-centric events, we use the output of the ball node for loss computation and evaluation.

C ADDITIONAL RESULTS

C.1 AGENT TYPES

# Agent Types	minADE	minFDE
1	9.18	12.87
2	9.06	12.74
3	8.94	11.64
4	9.00	12.71

Table 3: Quantitative results on basketball data (in meters) modeling all players with $T_{pred} = 40$ and $T_{obs} = 10$ for varying dimensionality of $\mathcal{K}_t$ and a dimensionality of 1 for the interaction space $\mathcal{E}_t$.

To provide further evidence for potential semantic interpretations of the discrete latent space, we examine the effect of capacity change in agent types $\mathcal{K}_t \in \mathcal{G}_t$ on the generative performance. Table 3 summarizes the results for modeling the dynamics of all players on basketball data. Intuitively, we would expect 3 fundamentally different agent types causing the observed movements since the data consists of attacking and defensive players, and the ball. Similar to Section 4.2, the empirical results confirm this intuition.

C.2 CONTINUOUS LATENT VARIABLE

Figure 6: The full training loss $\mathcal{L}_{DIA}$ and KL loss between prior and approximate posterior on $z_{\leq T}$ during a training run on soccer data.

An appropriate local solution in our learning problem accurately describes the data while collecting implicit information into latent space $\{\mathcal{G}_t, z_t\}$. As part of the main paper, we qualitatively and quantitatively investigated the discovered relational structure $\mathcal{G}_t$, finding semantically significant patterns, and demonstrated an accurate approximation of the underlying multimodal data distributions through baseline comparisons. Thus, this section is devoted to quantify the information captured in the continuous subspace z_t.

A potential metric to measure the degree of dependency between x and z i.e., to decide whether the continuous latent variable encodes useful information, is by monitoring the KL divergence between the variational posterior and prior. When naively training VAE architectures that consist of a decoder exhibiting sufficiently powerful function approximators with autoregressive dependencies (e.g., RNNs), existing sequential latent variable models frequently report a phenomenon named

posterior collapse (Chung et al., 2015), where the model tends to converge to regions of the loss surface that contain bad local minima (or saddle points) at $KL = 0$. Since the latent information the decoder receives is then essentially equivalent to Gaussian noise, the model remits to a standard unconditional RNN, i.e., it learns to generate the input solely based on the autoregressive properties independent of the latent information z.

Figure 6 displays (average) values for losses $\mathcal{L}_{DIA}$ and $\mathcal{KL}[q_{\phi_1}(z_t|x_{\leq T}, z_{<t}, \mathcal{G}_{\leq t}) \parallel p_{\theta_2}(z_t|x_{<t}, z_{<t}, \mathcal{G}_{\leq t})]$ during a training run on soccer data. Here we observe a gradual increase in KL loss values that is accompanied by a steady decrease in training loss. Thus, the results indicate an effective exploitation of the continuous subspace z_t to generate future agent movements without the use of common optimization strategies such as cost annealing (Bowman et al., 2016; Sønderby et al., 2016).

C.3 QUALITATIVE EVALUATION

Figure 7: *Top:* Influence of the ball on the green player. *Bottom:* Influence of the green player on the ball.

Figure 7 shows another example of agent-ball interactions for the multi-agent segment from section 4.3. When considering influences on the ball (upper image), we again see a high frequency with respect to the dominant interaction type. When reversing the influence direction, we again observe more constant patterns, where the second interaction type becomes dominant as soon as the ball arrives at the spatially closest agent.

Figure 8: *Left:* Trajectories of two agents. The numbers indicate times at which the probability values of the right graph undergo rapid change. *Right:*

Figure 8 depicts an exemplary timeline for player-player interactions in a Bernoulli setting. Again, our model learns an interpretable semantic structure, which we describe below. The sharp drop in probability values at around $t = 10$ (right plot) is accompanied with the direction change of the blue player (indicated by symbol 1) in the left plot. The probability spike between $t = 20$ and $t = 30$ is caused by the change of direction of the orange player (symbol 2) at the right corner on the pitch.

The spike at around $t = 40$ is caused by the blue player turning towards the orange player (symbol 3); the last increase in probability occurs when the blue player accelerates towards the orange player (symbol 4).