Unleashing Interactive Agent Planning Ability in LLMs via Multi-Trajectory Reinforcement Learning

Abstract

Large Language Models (LLMs) have demonstrated remarkable capabilities across diverse domains, yet they struggle with agent task planning in dynamic environments requiring continuous observation and sequential decision-making. Current methods generate static action sequences from pre-trained knowledge without learning from environmental feedback, limiting their effectiveness in partially observable settings. We present **Interactive Planner-R1**, a novel trajectory-level reinforcement learning framework that enables LLMs to develop interactive planning capabilities through autonomous environmental exploration. Our approach addresses three key challenges: (1) limited exploration diversity by introducing multi-trajectory autonomous exploration through parallel group rollouts, (2) sparse reward signals by developing a completion-driven reward architecture that promotes genuine environmental understanding, and (3) single-step optimization constraints by proposing Interactive Policy Optimization (IPO) that extends group-relative policy optimization for multi-step trajectory learning. Extensive experiments on ALFWorld and ScienceWorld demonstrate that Interactive Planner-R1 achieves substantial improvements over existing approaches, reaching 97.55% completion rate on ALFWorld and 79.92% on ScienceWorld, with strong generalization exhibiting only 3.33% performance gap in unseen environments. Our work establishes a new paradigm for LLM-based interactive planning through trajectory-level policy learning.

1 Introduction

Large Language Models (LLMs) have demonstrated remarkable capabilities across a wide range of tasks, from open-domain dialogue to complex reasoning (Brown et al., 2020; OpenAI, 2023; DeepSeek-AI et al., 2025; Shao et al., 2024; Team et al., 2024; Yang et al., 2024a). However, translating these capabilities into effective planning in in-

Figure 1: Overview of Interactive Planner-R1, which encourages agents to autonomously explore environments and trains them with binary rewards based on task completion status.

teractive environments remains a fundamental challenge. Planning agents must continually perceive, reason about, and act upon their environment, forming a tightly coupled decision-making loop. Current LLMs still lack the situational and interactive awareness required for robust planning. In contrast, humans actively probe their surroundings, learning how actions transform the environment and refining both perception and world understanding through exploration (Gibson, 1979). While intuitive for humans, such exploration-driven learning remains challenging for artificial intelligence—especially when applying LLMs to interactive planning domains, such as robotics and embodied agents.

Traditional LLM-based planners treat the model as a static decision-maker (Chen et al., 2023b; Min et al., 2022), generating fixed action sequences from pre-trained knowledge and ignoring real-time

feedback. While Yao et al. (2023) improved task performance by introducing reasoning processes into planning, these methods still primarily perform offline rollouts based on prior knowledge, failing to establish crucial causal links between actions and environmental feedback during interaction. This limitation is particularly problematic in partially observable or unfamiliar environments, where agents must continually update their world models to succeed. Recent work (Song et al., 2024b; Wang et al., 2024b; Chen et al., 2023a; Zeng et al., 2024a) has attempted to bridge this gap by incorporating human-curated demonstrations or handcrafted knowledge. However, heavy reliance on human priors restricts scalability and limits the overall capability of LLMs. This raises a fundamental question: Can we instead encourage autonomous exploration with minimal supervision, enabling LLMs to acquire robust interaction and generalization abilities?

Inspired by human cognition, we introduce **Interactive Planner-R1**, a reinforcement learning framework that enables LLMs to learn interactive planning through environmental exploration, requiring only minimal task-specific supervision. Unlike previous approaches that depend on dense reward shaping or large demonstration corpora, our framework integrates three key modules: (1) Group Rollout with In-Environment Interaction, which enables efficient parallel exploration of environments, allowing the model to amass diverse interaction experiences; (2) a sparse, completion-driven reward structure, which prevents reward hacking and encourages genuine environmental understanding through direct interaction; and (3) the Interactive Policy Optimization (IPO) algorithm, which leverages group-normalized advantages to efficiently learn from grouped trajectories while maintaining reference to the original model.

Extensive experiments demonstrate the effectiveness of Interactive Planner-R1, achieving 97.55% and 79.92% cumulative reward on the ALFWorld and ScienceWorld benchmarks, respectively, significantly outperforming existing approaches. Notably, our model exhibits robust generalization, with only a -3.33% performance gap in unseen environments—substantially lower than comparable methods. These results validate the framework's capability to foster genuine environmental understanding and adaptive behavior in interactive planning tasks.

In summary, our main contributions are as follows:

- We introduce Interactive Planner-R1, a novel trajectory-level reinforcement learning framework that enables LLMs to learn interactive planning through autonomous environmental exploration with minimal supervision.

- We propose three key technical innovations: (1) parallel group rollouts for diverse trajectory collection, (2) completion-driven sparse rewards that prevent reward hacking while encouraging genuine environmental understanding, and (3) Interactive Policy Optimization (IPO) that extends group-relative optimization to multi-step sequential planning.

- We achieve state-of-the-art performance on ALFWorld (97.55%) and ScienceWorld (79.92%) with superior generalization (only 3.33% performance gap on unseen environments), demonstrating the effectiveness of autonomous exploration over human-supervised approaches.

2 Preliminaries

Following established researches (Qiao et al., 2024), we formalize embodied planning tasks within the framework of a Partially Observable Markov Decision Process (POMDP) due to the agent's inability to directly observe the environment's complete state. Within this framework, the agent interacts within a partially observable environment and develops plans based on environmental feedback. The POMDP is defined by a 7-tuple:

$$(S, A, \Psi, \mathcal{M}, O, R, \gamma), \tag{1}$$

where S represents the state space defined by the environment, A denotes the action space available to the agent, O constitutes the observation space of the agent, $\Psi : S \times A \to S$ is the state transition function determining how actions will have effect on environmental states, $\mathcal{M} : S \to O$ is the observation function of the agent. Due to partial observability constraints, the agent cannot directly access states $s \in S$, but rather obtains partial observations of the current environment via the observation function, such that $o = \mathcal{M}(s)$, where $o \in O$ and $s \in S$. Additionally, R represents the reward function, and γ is the discount factor.

In the context of planning tasks, the agent receives a task q, typically expressed as a natural

language instruction. The agent's objective is to complete this instruction through environmental interaction. During this interaction process, the agent initially obtains an observation o_0 from the environment and initializes a trajectory $\tau_0 = (q, o_0)$. At each time step t, the policy model π_θ generates the current action based on the historical trajectory:

$$a_t = \pi_\theta(\tau_t) = \pi_\theta(q, o_0, a_0, o_1, ..., a_{t-1}, o_t). \quad (2)$$

When performed, the action will lead to a change to the environment, resulting in a new state $s_{t+1} = \Psi(s_t, a_t)$, Following this transition, the agent receives a new partial observation $o_{t+1} = \mathcal{M}(s_{t+1})$. Subsequently, the agent's trajectory, is updated to $\tau_{t+1} = (q, o_0, a_0, o_1, ..., a_t, o_{t+1})$, incorporating all past actions and observations with the new observation. The reward for the agent is defined with a binary signal, where the agent receives a reward of 1 if the new state s_{t+1} meets the predefined goal conditions specified by q, otherwise the reward is 0. This sparse reward, with minimal human priors, encourages the agent to autonomously explore the environment and develop advanced exploration and planning strategies during training.

3   Interactive Planner-R1

3.1   Overview

In this section, we introduce **Interactive Planner-R1**, an end-to-end training framework designed for long-term planning. Interactive Planner-R1 learns solely from outcome-based reward signals without requiring additional human supervision. Our key insight is to unleash the latent reasoning and planning capabilities of large language models (LLMs) through direct interaction with the environment, allowing them to self-evolve via reinforcement learning. To better model the interaction process, we formulate it as **ReAct-style trajectories**, where progress is made through continuous '$Observation \rightarrow Think \rightarrow Action$' cycles until task completion. Interactive Planner-R1 consists of three tightly integrated core components: Firstly, to address the problem of sparse rewards, we develop a parallel sampling strategy that simultaneously generates multiple trajectories forming trajectory groups to establish stable statistical baselines, which we call **Group Rollout with In-Environment Interaction** . Secondly, we design a pure **Completion-based Sparse Reward** structure

that encourages development of genuine environmental understanding through autonomous interaction. Finally, and most importantly, we introduce the **Interactive Policy Optimization** (IPO) algorithm. Unlike Group Relative Policy Optimization (GRPO), which only handles single-turn dialogue, IPO is specifically designed for ReAct-style multi-turn interactions as its POMDP-oriented extension. While maintaining critic-free and group-relative baselines, we redesigned probability ratios and advantage allocation to handle multi-turn ReAct trajectories and extremely sparse rewards, effectively addressing probability degradation in long-sequence training and achieving efficient reward distribution.

3.2   ReAct Paradigm

As described above, at time step t, the agent generates an action based on a trajectory that includes environmental observations and previous actions. However, mapping directly from such a trajectory to action demands complex reasoning capabilities, like task goal decomposition, common sense knowledge application, and extraction of key information from observations is exceptionally challenging. Following Yao et al. (2023), we adopt the ReAct paradigm that introduces the thought process (Wei et al., 2022) into LLM-based planning trajectories, as demonstrated in Figure 3. Unlike traditional approaches, with the historical trajectory as input, the agent generates a thought context:

$$\tau_{t+1} = (q, o_0, m_0, o_1, ..., m_t, o_{t+1}), \quad (3)$$

where m_t denotes the model's response for t-th step, it consists of thoughts and a text-form action:

$$m_t = (\phi_t, a_t). \quad (4)$$

We extract action a_t from m_t, which is then used to interact with the environment to obtain the new observation o_{t+1}.

3.3   Group Rollout with In-Environment Interaction

To effectively train an LLM for solving interactive environment tasks, we introduce a parallel-rollout procedure that enhances exploration efficiency. We begin by sampling K task-environment pairs from distribution $\mathcal{D}$ and creating n parallel replicas for each pair. Each replica is initialized with its reset environment and an empty trajectory buffer. For

Figure 2: The Interactive Planner-R1 consists of three tightly integrated core components: 1) Group Rollout with Environment Interaction, a parallel sampling strategy that simultaneously generates multiple trajectories to form trajectory groups; 2) Completion-driven Sparse Reward; 3) Interactive Policy Optimization algorithm that redesigns probability ratios and advantage allocation, and updates the policy function based on group relative rewards. The KL divergence between policy and reference model serves as a regularization term to prevent over-optimization.

Figure 3: We employ the ReAct paradigm during generation and extract the action from the response m_t.

up to *max_steps* iterations, the frozen policy $\pi_{\theta_{old}}$ generates responses conditioned on both the task prompt and current trajectory. From each response, we parse an action. To enhance the model's planning capabilities and effectively prevent the generation of excessive invalid actions, we introduce a special "done" action to terminate the replica. The model can use "done" when it determines that the task is either unsolvable or already completed; otherwise, the action executes in the environment, generating a new observation that gets appended to the trajectory along with the response. Once all replicas terminate or reach the step limit, we aggregate all trajectories into the global buffer $\mathcal{T}$, compute returns, and update the policy according to Eqs.(7)–(8). We provide the algorithm pseudo code

in Appendix B. This approach efficiently collects diverse multi-turn ReAct trajectories, establishing a robust foundation for policy optimization that generalizes effectively to complex long-horizon planning challenges.

3.4 Completion-driven Reward

To encourage autonomous exploration, we use only a rule-based completion reward without further restriction to optimize the model:

$$r = \begin{cases} 0 & \text{if the task is incomplete,} \\ 1 & \text{if the task is completed.} \end{cases} \quad (5)$$

Unlike previous approaches using that introduced format rewards or length penalty, we do not explicitly provide such constraints. On the one hand, we found that LLMs can maintain a clear response structure with guidance from the system prompt, and only a parsable and valid response can interact with the environment to complete the task. On the other hand, we argue that reducing human priors in reward design can lower the risk of reward hacking and encourage the model to explore autonomously, generating more flexible and diverse trajectories. Therefore, we believe that outcome-based reward can implicitly guide LLMs to develop appropriate output structures, while allowing greater flexibility and freedom during exploration to encourage more natural and effective interactions with the environment.

3.5 Interactive Policy Optimization (IPO)

To enable efficient environment interaction and planning while substantially reducing training

cost, we introduce Interactive Policy Optimization (IPO). IPO relies on the group rollout with In-Environment Interaction to make the policy model π_θ generate multiple trajectories. We employ the group-normalized advantage estimator, which has no learnable critic model, but its probability ratio is calculated over the designated trajectories tokens prefix up to step t, including all preceding thought ϕ and action a tokens:

$$Pr_t(\theta) = \frac{\pi_\theta\left(\phi_t, a_t \mid \tau_{i,<t}\right)}{\pi_{\theta_{\text{old}}}\left(\phi_t, a_t \mid \tau_{i,<t}\right)}. \tag{6}$$

We optimize the policy model by maximizing the following objective function:

$$\mathcal{J}_{\text{IPO}}(\theta) = \mathbb{E}_{(q,e)\sim\mathcal{D},\{\tau_i\}_{i=1}^n \sim \pi_{\theta_{old}}(\mathcal{T}\mid(q,e))}$$
$$\frac{1}{n}\sum_{i=1}^n \frac{1}{|\tau_i|}\sum_{t=1}^{|\tau_i|}\left\{\min\left[Pr_t(\theta)\hat{A}_{i,t}, \text{clip}\left(Pr_t(\theta), 1-\varepsilon, 1+\varepsilon\right)\hat{A}_{i,t}\right] - \beta\mathbb{D}_{KL}\left[\pi_\theta\|\pi_{\text{ref}}\right]\right\}, \tag{7}$$

where $\hat{A}_{i,t}$ is the advantage of i-th trajectory in the group for time step t, which is calculated as follows:

$$\hat{A}_{i,t} = \frac{r_i - \mu_r}{\sigma_r}. \tag{8}$$

where t represents the t-th step of the trajectories, μ_r is the mean reward of the group, and σ_r is the reward deviation of the whole group. Additionally, the objective of IPO integrates a KL divergence penalty term between the training policy and the reference policy to prevent the model from deviating too much (Eq.7).

4 Experiments

4.1 Implementation

Evaluation To assess model capabilities in interactive planning tasks, we conducted systematic evaluations using two text-based embodied world simulator benchmarks: ALFWorld (Shridhar et al., 2021) and ScienceWorld (Wang et al., 2022). ALFWorld encompasses six categories of planning tasks set primarily in home environments, covering not only basic object manipulation (such as "pick and place") but also tasks requiring complex interaction sequences. ScienceWorld presents a more challenging benchmark, requiring models to complete scientific experiments in a highly interactive environment. Each task was evaluated only once, with interaction steps limited to 30 to ensure evaluation efficiency and consistency. More evaluation and benchmark details will introduced Appendix C.1.

Baseline We compared our Interactive Planner-R1 against three state-of-the-art training-based methods: SFT (Zeng et al., 2024a), NAT (Wang et al., 2024b), and ETO (Song et al., 2024b). We also evaluated larger foundation models including GPT-3.5 Turbo (DeepSeek-AI et al., 2024)(DeepSeek-V3-0324), GPT-4 (OpenAI, 2023)(gpt-4o-2024-08-06), DeepSeek-V3 (DeepSeek-AI et al., 2024)(DeepSeek-V3-0324), and InternLM 2.5 20B (Team et al., 2024). All training-based methods are fine-tuned on Qwen2.5-7B-Instruct (Yang et al., 2024a). Detailed baseline descriptions are provided in Appendix C.2.

Training Details We implemented our approach using the verl library and trained on 8 NVIDIA A100 80GB GPUs. Each training step sampled 128 tasks with 5 trajectories per task. Additional implementation details are provided in Appendix C.3.

4.2 Main results

As shown in Table 1, we conducted comprehensive evaluations of prompt-based and training-based approaches on two challenging interactive environments, ALFWorld and ScienceWorld. The experimental results reveal several key findings:

First, current state-of-the-art foundational LLMs demonstrate notable limitations in interactive planning capabilities. While GPT-4 achieved the best performance (55.41% on ALFWorld and 58.18% on ScienceWorld), it still lags behind training-based approaches. GPT-3.5-Turbo showed significantly lower performance (7.30% and 24.83% respectively), indicating the challenges large language models face in environmental interaction tasks.

Compares with other baseline, Interactive Planner-R1 demonstrates consistent improvements across all evaluation metrics. On the ALFWorld benchmark, it achieved accuracy rates of 98.57% and 96.52% in seen and unseen scenarios, respectively, surpassing the ETO by 14.28% and 16.67%. On the ScienceWorld dataset, Interactive Planner-R1 achieved accuracy rates of 83.66% and 76.18% in seen and unseen scenarios, outperforming competitive methods by 28.58% and 18.86%, respectively. The performance improvement from the Qwen2.5-7B-Instruct (averaging 31.05% on ALFWorld and 22.05% on ScienceWorld) to Interactive Planner-R1 demonstrates the effectiveness of our reinforcement learning framework.

Table 1: **Main Results.** The best results are marked in **bold**. We compare our Interactive Planner-R1 with representative baselines including vanilla language models and training-based methods on ALFWorld and ScienceWorld benchmarks, evaluating performance on both seen and unseen task scenarios. See Table 4 for complete comparison with additional baselines.

Method	ALFWorld			ScienceWorld		
	Seen	Unseen	Avg.	Seen	Unseen	Avg.
GPT-3.5-Turbo (Brown et al., 2020)	7.14	7.46	7.30	28.03	21.63	24.83
GPT-4o (OpenAI, 2023)	58.57	52.24	55.41	59.6	56.75	58.18
Deepseek-v3 (DeepSeek-AI et al., 2024)	36.43	31.34	33.89	29.28	27.45	28.37
InternLM 2.5 20B Chat (Team et al., 2024)	7.86	11.94	9.90	33.66	31.15	32.41
Qwen2.5-72B-Instruct (Yang et al., 2024a)	25.71	26.12	25.92	29.38	27.96	28.67
Qwen2.5-7B-Instruct (Yang et al., 2024a)	30.00	32.09	31.05	28.01	16.09	22.05
Qwen2.5-7B-Instruct + SFT(Zeng et al., 2024a)	80.71	79.10	79.91	68.81	55.7	62.26
Qwen2.5-7B-Instruct + NAT(Wang et al., 2024b)	63.57	66.42	65.00	58.56	49.75	54.16
Qwen2.5-7B-Instruct + ETO(Song et al., 2024b)	84.29	79.85	82.07	55.08	57.32	56.20
Qwen2.5-7B-Instruct + Interactive Planner-R1(Ours)	**98.57** $_{\pm0.7}$	**96.52** $_{\pm1.9}$	**97.55**	**83.66** $_{\pm0.5}$	**76.18** $_{\pm0.9}$	**79.92**

Table 2: Ablation study results showing the contribution of different components in Interactive Planner-R1. Δ represents the performance difference compared to the full model.

	Seen	Unseen	Avg.	Δ
Interactive Planner-R1	98.57	96.52	97.55	0
w/o React	96.56	95.71	96.14	-1.41
w/o IPO	21.43	26.11	23.77	-73.78
w/o group	-			-

4.3 Ablation Study

To comprehensively understand the contribution of each component in Interactive Planner-R1, we conduct systematic ablation studies across three key dimensions: policy learning architecture, ReAct paradigm integration, group rollout mechanism. All ablation experiments are performed on ALFWorld to ensure consistent evaluation conditions.

As shown in Table 2, the experimental results reveal several critical insights about our framework design:

Trajectory-level vs. Single-turn Policy Learning The most significant finding concerns the importance of Interactive Policy Optimization (IPO) for multi-turn planning tasks. Removing IPO and replacing it with single-turn optimization (w/o IPO) results in a dramatic performance collapse, dropping from 97.55% to merely 23.77%—a substantial decrease of 73.78%. This stark difference demonstrates that interactive planning fundamentally requires understanding action sequences and their cumulative effects, rather than optimizing each action in isolation. The poor performance of single-turn methods validates our hypothesis that trajectory-level optimization is essential for complex sequential decision-making tasks.

ReAct Paradigm Contribution The structured $Observation \rightarrow Think \rightarrow Action$ paradigm shows measurable but moderate impact on performance. Removing the explicit reasoning chains (w/o React) leads to a 1.41% performance decrease, from 97.55% to 96.14%. While this decline appears modest, it represents consistent degradation across both seen and unseen scenarios, indicating

We evaluate three trajectory-based baselines in ALFWorld that leverage human prior knowledge to construct training datasets and observe their performance clustering around 80%, suggesting a performance ceiling imposed by the reliance on human-annotated data. In contrast, Interactive Planner-R1 easily surpasses this ceiling, achieving over 95% by leveraging reinforcement learning, which enables the model to explore the environment autonomously and generate more diverse and flexible data.

Overall, these findings highlight several important issues: foundational LLMs exhibit significant deficiencies in interactive planning tasks, and while trajectory-based offline training helps narrow this gap, it fails to completely resolve it. Interactive Planner-R1 introduces a novel paradigm based on online exploration, enabling models to achieve exceptional interactive planning capabilities through autonomous exploration. This approach establishes a robust new baseline for future research in interactive planning.

Figure 4: Completion rates of Qwen2.5-7B-Instruct on various ALFWorld tasks, covering both seen and unseen scenarios. We compare the prompt-based method ReAct with the training-based method ETO and Interactive Planner-R1.

that structured reasoning helps the model better understand environmental contexts and maintain performance stability during planning.

Group Rollout Necessity The group rollout mechanism proves fundamental to our approach's functionality. As indicated by the missing results for "w/o group" in Table 2, this ablation becomes infeasible because group-normalized advantages require multiple parallel trajectories for statistical baseline computation. Without diverse trajectory groups, the advantage estimation becomes unstable, preventing effective policy learning entirely. This dependency underscores that parallel exploration is not merely beneficial but architecturally essential for our framework.

These ablation results collectively demonstrate that Interactive Planner-R1's superior performance stems from the synergistic combination of trajectory-level optimization, structured reasoning, and parallel exploration, with IPO serving as the most critical component for achieving effective interactive planning capabilities.

4.4 Training Analysis

Interactive Planner-R1 maintains high-level performance even on more difficult problems and unseen environments. Figure 4 compares the performance differences among various methods across different ALFWorld tasks, revealing clear difficulty hierarchies and capability differentials among the methods. As shown in the Figure, the "Pick" single-object task is relatively the most basic, where all training-based methods perform well, while purely prompt-based methods achieve less than 60% task completion rate. The "Look", "Cool", "Clean", and "Heat" tasks present moderate difficulty as they involve more complex state transitions. The "Pick Two" task is clearly the

Table 3: ETO and Interactive Planner-R1's relative improvement on unseen tasks compared with seen tasks in ALFWorld, where Interactive Planner-R1 maintains strong generalization ability even on unseen tasks.

	Pick	Look	Heat	Clean	Cool	Pick Two	Avg.
ETO	-9.89	-15.82	+6.95	-5.94	+5.39	-24.72	-7.34
Ours	-4.20	-12.50	-4.55	-3.13	0.00	+4.38	-3.33

most challenging, with ReAct performing worst on this task (only 20.8% in seen and 17.6% in unseen), and ETO also showing significant decline (62.5% in seen, 47.05% in unseen). Only Interactive Planner-R1 maintains high-level performance (95.8% in seen, 100% in unseen). This difficulty distribution reflects the challenges drastically increase when tasks involve more object interactions, complex state transitions, or environmental reasoning. However, Interactive Planner-R1 maintains stable performance across the different tasks.

Generalization capabilities in unseen environments. To evaluate the generalization capability of different methods, we define the generalization gap $\Delta(abs)$ as the difference between task completion rates on unseen and seen tasks: $\Delta(abs) = Acc_{unseen} - Acc_{seen}$, as shown in Table 3. Experimental results demonstrate that our method exhibits significant advantages in generalization performance. Overall, our approach achieves a smaller average generalization gap (-3.33%) compared to the baseline method ETO (-7.34%). Notably, in the complex "Pick Two" task, our method not only overcomes the generalization challenge but achieves positive improvement (+4.38%), while ETO shows substantial performance degradation (-24.72%). This superior generalization ability is particularly evident in handling complex tasks. Further analysis reveals that our method also demonstrates stronger stability, with a relatively smaller performance variance across different task types (ranging

| (a) Rewards and response length | (b) Total and invalid action steps | (c) Performance in harder modes |

Figure 5: Training progress of Interactive Planner-R1 in ScienceWorld: (a) shows the rewards and total response length in multi-round exploration; (b) illustrates the decreasing trends in both total and invalid action steps during training; (c) reveals the sustained performance trends across varying difficulty modes.

from -12.50% to +4.38%). Although the "Look" task poses considerable challenges for both methods, our approach maintains a relatively smaller performance drop (-12.5%). These results indicate that Interactive Planner-R1 effectively enhances the model's adaptability to variations in task scenarios while maintaining cross-task stability.

Efficient planning through invalid action reduction. Figure 5 demonstrates how Interactive Planner-R1 achieves efficient planning by systematically reducing invalid actions during training in the ScienceWorld. The reward curve shows steady improvement as the model learns to generate more valid action sequences (see Figure 5a). Notably, the average response length decreases from approximately 900 tokens to 500 tokens by step 50, reflecting more concise and efficient action planning. This efficiency gain is directly linked to the model's ability to avoid invalid actions, as shown in Figure 5b. The total number of action steps (red line) reduces from an initial 20 steps to a consistent 12.5 steps, while invalid actions (blue line) are nearly eliminated after 50 training steps. This substantial reduction in invalid actions indicates that Interactive Planner-R1 has developed a robust understanding of environmental constraints, leading to more efficient planning strategies and more efficient plans. These results demonstrate that Interactive Planner-R1 achieves efficient planning primarily through its ability to avoid invalid actions and systematic exploration, leading to more streamlined and effective task execution.

Robust Performance Under Increased Environment Complexity Level. Figure 5c further validates this capability by comparing learning performance in ScienceWorld under "Easy" and "Normal" difficulty modes. While "Normal" mode requires complete environmental interactions (navigation, container manipulation, fundamental ac-

tions), Interactive Planner-R1 demonstrates notable progress in both settings. Though "Easy" mode shows faster convergence (0.6 reward at 50 steps vs 100 steps) and higher final performance (0.88 vs 0.82), the model successfully adapts to increased complexity, maintaining stable learning trajectories in both modes. This consistent performance across difficulty levels reinforces that Interactive Planner-R1 enables flexible exploration strategies and enhanced planning capabilities even under challenging environmental constraints.

5 Related Work

Our related work is put in Appendix A.

6 Conclusion

In this paper, we propose Interactive Planner-R1, a reinforcement learning framework that enables LLMs to achieve self-evolution in multi-turn environmental interaction planning tasks. Our approach demonstrates that models can autonomously develop effective planning strategies through carefully designed prompt constraints and outcome-based reward mechanisms, without relying on expert trajectories or extensive human priors. Experimental results across multiple environments show that Interactive Planner-R1 significantly outperforms existing baselines, validating the effectiveness of self-evolution via reinforcement learning in complex interactive scenarios. Notably, our analysis reveals that unlike single-turn reasoning tasks, multi-turn interactive planning benefits from shorter context lengths, as performance improves when ineffective actions are reduced. This suggests that interactive planning tasks prioritize efficient action planning over lengthy deliberation or redundant action planning. These findings may provide some insights for LLM-based interactive planning systems.

Limitations

While Interactive Planner-R1 demonstrates strong performance on interactive planning tasks, several limitations merit consideration for future research:

Environment Scope. Our evaluation focuses exclusively on text-based environments (ALFWorld and ScienceWorld). Although the underlying principles of multi-trajectory reinforcement learning are domain-agnostic, empirical validation in multimodal settings—particularly vision-language environments—remains an important direction for establishing broader applicability.

Computational Requirements. The group rollout mechanism, while effective for exploration diversity, introduces substantial computational overhead compared to single-trajectory methods. Training requires 8 A100 GPUs for several hours, which may limit accessibility for researchers with constrained resources. Developing more sample-efficient variants or exploring distributed training strategies could address this scalability concern.

References

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

Baian Chen, Chang Shu, Ehsan Shareghi, Nigel Collier, Karthik Narasimhan, and Shunyu Yao. 2023a. Fireact: Toward language agent fine-tuning. *CoRR*, abs/2310.05915.

Yaran Chen, Wenbo Cui, Yuanwen Chen, Mining Tan, Xinyao Zhang, Dongbin Zhao, and He Wang. 2023b. Robogpt: an intelligent agent of making embodied long-term decisions for daily instruction tasks. *CoRR*, abs/2311.15649.

Sanjiban Choudhury. 2025. Process reward models for LLM agents: Practical framework and directions. *CoRR*, abs/2502.10325.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, and 81 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *CoRR*, abs/2501.12948.

DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, and 81 others. 2024. Deepseek-v3 technical report. *CoRR*, abs/2412.19437.

Jiafei Duan, Samson Yu, Hui Li Tan, Hongyuan Zhu, and Cheston Tan. 2022. A survey of embodied AI: from simulators to research tasks. *IEEE Trans. Emerg. Top. Comput. Intell.*, 6(2):230–244.

James J. Gibson. 1979. *The Ecological Approach to Visual Perception: Classic Edition*. Houghton Mifflin.

Taicheng Guo, Xiuying Chen, Yaqi Wang, Ruidi Chang, Shichao Pei, Nitesh V. Chawla, Olaf Wiest, and Xiangliang Zhang. 2024. Large language model based multi-agents: A survey of progress and challenges. In *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence, IJCAI 2024, Jeju, South Korea, August 3-9, 2024*, pages 8048–8057. ijcai.org.

Jingcheng Hu, Yinmin Zhang, Qi Han, Daxin Jiang, Xiangyu Zhang, and Heung-Yeung Shum. 2025. Open-reasoner-zero: An open source approach to scaling up reinforcement learning on the base model. *CoRR*, abs/2503.24290.

Chengxing Jia, Ziniu Li, Pengyuan Wang, Yi-Chen Li, Zhenyu Hou, Yuxiao Dong, and Yang Yu. 2025. Controlling large language model with latent actions. *ArXiv*, abs/2503.21383.

Bowen Jin, Hansi Zeng, Zhenrui Yue, Dong Wang, Hamed Zamani, and Jiawei Han. 2025. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. *CoRR*, abs/2503.09516.

Xiaoxi Li, Guanting Dong, Jiajie Jin, Yuyao Zhang, Yujia Zhou, Yutao Zhu, Peitian Zhang, and Zhicheng Dou. 2025a. Search-o1: Agentic search-enhanced large reasoning models. *CoRR*, abs/2501.05366.

Zhong-Zhi Li, Duzhen Zhang, Ming-Liang Zhang, Jiaxin Zhang, Zengyan Liu, Yuxuan Yao, Haotian Xu, Junhao Zheng, Pei-Jie Wang, Xiuyi Chen, Yingying Zhang, Fei Yin, Jiahua Dong, Zhijiang Guo, Le Song, and Cheng-Lin Liu. 2025b. From system 1 to system 2: A survey of reasoning large language models. *CoRR*, abs/2502.17419.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2024. Let's verify step by step. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Zongyu Lin, Yao Tang, Xingcheng Yao, Da Yin, Ziniu Hu, Yizhou Sun, and Kai-Wei Chang. 2025. Qlass: Boosting language agent inference via q-guided stepwise search. *ArXiv*, abs/2502.02584.

Yang Liu, Weixing Chen, Yongjie Bai, Guanbin Li, Wen Gao, and Liang Lin. 2024. Aligning cyber space with physical world: A comprehensive survey on embodied AI. *CoRR*, abs/2407.06886.

Yuqi Liu, Bohao Peng, Zhisheng Zhong, Zihao Yue, Fanbin Lu, Bei Yu, and Jiaya Jia. 2025. Seg-zero: Reasoning-chain guided segmentation via cognitive reinforcement. *CoRR*, abs/2503.06520.

Haipeng Luo, Qingfeng Sun, Can Xu, Pu Zhao, Jianguang Lou, Chongyang Tao, Xiubo Geng, Qingwei Lin, Shifeng Chen, and Dongmei Zhang. 2023. Wizardmath: Empowering mathematical reasoning for large language models via reinforced evol-instruct. *CoRR*, abs/2308.09583.

Chengqi Lyu, Songyang Gao, Yuzhe Gu, Wenwei Zhang, Jianfei Gao, Kuikun Liu, Ziyi Wang, Shuaibin Li, Qian Zhao, Haian Huang, Weihan Cao, Jiangning Liu, Hongwei Liu, Junnan Liu, Songyang Zhang, Dahua Lin, and Kai Chen. 2025. Exploring the limit of outcome reward for learning mathematical reasoning. *CoRR*, abs/2502.06781.

So Yeon Min, Devendra Singh Chaplot, Pradeep Kumar Ravikumar, Yonatan Bisk, and Ruslan Salakhutdinov. 2022. FILM: following instructions in language with modular methods. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.

Kolby Nottingham, Bodhisattwa Prasad Majumder, Bhavana Dalvi Mishra, Sameer Singh, Peter Clark, and Roy Fox. 2024. Skill set optimization: Reinforcing language model behavior via transferable skills. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net.

OpenAI. 2023. GPT-4 technical report. *CoRR*, abs/2303.08774.

Jiazhen Pan, Che Liu, Junde Wu, Fenglin Liu, Jiayuan Zhu, Hongwei Bran Li, Chen Chen, Cheng Ouyang, and Daniel Rueckert. 2025. Medvlm-r1: Incentivizing medical reasoning capability of vision-language models (vlms) via reinforcement learning. *CoRR*, abs/2502.19634.

Pranav Putta, Edmund Mills, Naman Garg, Sumeet Motwani, Chelsea Finn, Divyansh Garg, and Rafael Rafailov. 2024. Agent Q: advanced reasoning and learning for autonomous AI agents. *CoRR*, abs/2408.07199.

Shuofei Qiao, Runnan Fang, Ningyu Zhang, Yuqi Zhu, Xiang Chen, Shumin Deng, Yong Jiang, Pengjun Xie, Fei Huang, and Huajun Chen. 2024. Agent planning with world knowledge model. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*.

Gabriel Sarch, Lawrence Jang, Michael J. Tarr, William W. Cohen, Kenneth Marino, and Katerina Fragkiadaki. 2024. VLM agents generate their own memories: Distilling experience into embodied programs of thought. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *CoRR*, abs/2402.03300.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew J. Hausknecht. 2021. Alfworld: Aligning text and embodied environments for interactive learning. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Yifan Song, Weimin Xiong, Xiutian Zhao, Dawei Zhu, Wenhao Wu, Ke Wang, Cheng Li, Wei Peng, and Sujian Li. 2024a. Agentbank: Towards generalized LLM agents via fine-tuning on 50000+ interaction trajectories. In *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024*, pages 2124–2141. Association for Computational Linguistics.

Yifan Song, Da Yin, Xiang Yue, Jie Huang, Sujian Li, and Bill Yuchen Lin. 2024b. Trial and error: Exploration-based trajectory optimization for LLM agents. *CoRR*, abs/2403.02502.

Haotian Sun, Yuchen Zhuang, Lingkai Kong, Bo Dai, and Chao Zhang. 2023a. Adaplanner: Adaptive planning from feedback with language models. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Jiankai Sun, Chuanyang Zheng, Enze Xie, Zhengying Liu, Ruihang Chu, Jianing Qiu, Jiaqi Xu, Mingyu Ding, Hongyang Li, Mengzhe Geng, Yue Wu, Wenhai Wang, Junsong Chen, Zhangyue Yin, Xiaozhe Ren, Jie Fu, Junxian He, Wu Yuan, Qi Liu, and 15 others. 2023b. A survey of reasoning with foundation models. *CoRR*, abs/2312.11562.

InternLM Team, Zheng Cai, Maosong Cao, Haojiong Chen, Kai Chen, Keyu Chen, Xin Chen, Xun Chen, Zehui Chen, Zhi Chen, Pei Chu, Xiaoyi Dong,

Haodong Duan, Qi Fan, Zhaoye Fei, Yang Gao, Jiaye Ge, Chenya Gu, Yuzhe Gu, and 53 others. 2024. Internlm2 technical report. *CoRR*, abs/2403.17297.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, Chuning Tang, Congcong Wang, Dehao Zhang, Enming Yuan, Enzhe Lu, Fengxiang Tang, Flood Sung, Guangda Wei, Guokun Lai, and 75 others. 2025. Kimi k1.5: Scaling reinforcement learning with llms. *CoRR*, abs/2501.12599.

Hanlin Wang, Jian Wang, Chak Tou Leong, and Wenjie Li. 2025a. Steca: Step-level trajectory calibration for llm agent learning. *ArXiv*, abs/2502.14276.

Huaijie Wang, Shibo Hao, Hanze Dong, Shenao Zhang, Yilin Bao, Ziran Yang, and Yi Wu. 2024a. Offline reinforcement learning for LLM multi-step reasoning. *CoRR*, abs/2412.16145.

Renxi Wang, Haonan Li, Xudong Han, Yixuan Zhang, and Timothy Baldwin. 2024b. Learning from failure: Integrating negative examples when fine-tuning large language models as agents. *CoRR*, abs/2402.11651.

Ruoyao Wang, Peter A. Jansen, Marc-Alexandre Côté, and Prithviraj Ammanabrolu. 2022. Scienceworld: Is your agent smarter than a 5th grader? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing, EMNLP 2022, Abu Dhabi, United Arab Emirates, December 7-11, 2022*, pages 11279–11298. Association for Computational Linguistics.

Siyin Wang, Zhaoye Fei, Qinyuan Cheng, Shiduo Zhang, Panpan Cai, Jinlan Fu, and Xipeng Qiu. 2025b. World modeling makes a better planner: Dual preference optimization for embodied task planning. *CoRR*, abs/2503.10480.

Zihao Wang, Shaofei Cai, Anji Liu, Xiaojian Ma, and Yitao Liang. 2023. Describe, explain, plan and select: Interactive planning with large language models enables open-world multi-task agents. *CoRR*, abs/2302.01560.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*.

Zhiheng Xi, Wenxiang Chen, Xin Guo, Wei He, Yiwen Ding, Boyang Hong, Ming Zhang, Junzhe Wang, Senjie Jin, Enyu Zhou, Rui Zheng, Xiaoran Fan, Xiao Wang, Limao Xiong, Yuhao Zhou, Weiran Wang, Changhao Jiang, Yicheng Zou, Xiangyang Liu, and 9 others. 2025. The rise and potential of large language model based agents: a survey. *Sci. China Inf. Sci.*, 68(2).

Zhiheng Xi, Yiwen Ding, Wenxiang Chen, Boyang Hong, Honglin Guo, Junzhe Wang, Dingwen Yang, Chenyang Liao, Xin Guo, Wei He, Songyang Gao, Lu Chen, Rui Zheng, Yicheng Zou, Tao Gui, Qi Zhang, Xipeng Qiu, Xuanjing Huang, Zuxuan Wu, and Yu-Gang Jiang. 2024. Agentgym: Evolving large language model-based agents across diverse environments. *CoRR*, abs/2406.04151.

Tian Xie, Zitian Gao, Qingnan Ren, Haoming Luo, Yuqian Hong, Bryan Dai, Joey Zhou, Kai Qiu, Zhirong Wu, and Chong Luo. 2025. Logic-rl: Unleashing LLM reasoning with rule-based reinforcement learning. *CoRR*, abs/2502.14768.

Weimin Xiong, Yifan Song, Xiutian Zhao, Wenhao Wu, Xun Wang, Ke Wang, Cheng Li, Wei Peng, and Sujian Li. 2024a. Watch every step! LLM agent learning via iterative step-level process refinement. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 1556–1572. Association for Computational Linguistics.

Weimin Xiong, Yifan Song, Xiutian Zhao, Wenhao Wu, Xun Wang, Ke Wang, Cheng Li, Wei Peng, and Sujian Li. 2024b. Watch every step! LLM agent learning via iterative step-level process refinement. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 1556–1572, Miami, Florida, USA. Association for Computational Linguistics.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, and 22 others. 2024a. Qwen2.5 technical report. *CoRR*, abs/2412.15115.

Chen Yang, Chenyang Zhao, Quanquan Gu, and Dongruo Zhou. 2024b. Cops: Empowering LLM agents with provable cross-task experience sharing. *CoRR*, abs/2410.16670.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R. Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net.

Weiran Yao, Shelby Heinecke, Juan Carlos Niebles, Zhiwei Liu, Yihao Feng, Le Xue, Rithesh R. N., Zeyuan Chen, Jianguo Zhang, Devansh Arpit, Ran Xu, Phil Mui, Huan Wang, Caiming Xiong, and Silvio Savarese. 2024. Retroformer: Retrospective large language agents with policy gradient optimization. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.

Da Yin, Faeze Brahman, Abhilasha Ravichander, Khyathi Raghavi Chandu, Kai-Wei Chang, Yejin Choi,

and Bill Yuchen Lin. 2024. Agent lumos: Unified and modular training for open-source language agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 12380–12403. Association for Computational Linguistics.

Huaiyuan Ying, Shuo Zhang, Linyang Li, Zhejian Zhou, Yunfan Shao, Zhaoye Fei, Yichuan Ma, Jiawei Hong, Kuikun Liu, Ziyi Wang, Yudong Wang, Zijian Wu, Shuaibin Li, Fengzhe Zhou, Hongwei Liu, Songyang Zhang, Wenwei Zhang, Hang Yan, Xipeng Qiu, and 3 others. 2024. Internlm-math: Open math large language models toward verifiable reasoning. *CoRR*, abs/2402.06332.

Siyu Yuan, Zehui Chen, Zhiheng Xi, Junjie Ye, Zhengyin Du, and Jiecao Chen. 2025. Agent-r: Training language model agents to reflect via iterative self-training. *CoRR*, abs/2501.11425.

Aohan Zeng, Mingdao Liu, Rui Lu, Bowen Wang, Xiao Liu, Yuxiao Dong, and Jie Tang. 2024a. Agenttuning: Enabling generalized agent abilities for llms. In *Findings of the Association for Computational Linguistics, ACL 2024, Bangkok, Thailand and virtual meeting, August 11-16, 2024*, pages 3053–3077. Association for Computational Linguistics.

Aohan Zeng, Mingdao Liu, Rui Lu, Bowen Wang, Xiao Liu, Yuxiao Dong, and Jie Tang. 2024b. AgentTuning: Enabling generalized agent abilities for LLMs. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 3053–3077, Bangkok, Thailand. Association for Computational Linguistics.

Yuanzhao Zhai, Tingkai Yang, Kele Xu, Dawei Feng, Cheng Yang, Bo Ding, and Huaimin Wang. 2025. Enhancing decision-making for LLM agents via step-level q-value models. In *AAAI-25, Sponsored by the Association for the Advancement of Artificial Intelligence, February 25 - March 4, 2025, Philadelphia, PA, USA*, pages 27161–27169. AAAI Press.

Zirui Zhao, Wee Sun Lee, and David Hsu. 2023. Large language models as commonsense knowledge for large-scale task planning. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Yuxiang Zheng, Dayuan Fu, Xiangkun Hu, Xiaojie Cai, Lyumanshan Ye, Pengrui Lu, and Pengfei Liu. 2025. Deepresearcher: Scaling deep research via reinforcement learning in real-world environments. *Preprint*, arXiv:2504.03160.

Wangchunshu Zhou, Yuchen Eleanor Jiang, Long Li, Jialong Wu, Tiannan Wang, Shi Qiu, Jintian Zhang, Jing Chen, Ruipu Wu, Shuai Wang, Shiding Zhu, Jiyu Chen, Wentao Zhang, Ningyu Zhang, Huajun Chen, Peng Cui, and Mrinmaya Sachan. 2023. Agents: An open-source framework for autonomous language agents. *CoRR*, abs/2309.07870.

Yuqi Zhu, Shuofei Qiao, Yixin Ou, Shumin Deng, Shiwei Lyu, Yue Shen, Lei Liang, Jinjie Gu, Huajun Chen, and Ningyu Zhang. 2025. KnowAgent: Knowledge-augmented planning for LLM-based agents. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 3709–3732, Albuquerque, New Mexico. Association for Computational Linguistics.

A Related Work

A.1 Long-Horizon planning with large language models

The emergence of LLMs has significantly advanced long-horizon planning (Liu et al., 2024; Xi et al., 2025; Duan et al., 2022; Guo et al., 2024; Zhou et al., 2023), enabling models to explore interactive environments and accomplish complex goals autonomously. Current methods can be categorized into two primary approaches: prompt-based methods and training-based methods. Prompt-based methods utilize manually crafted instructions or exemplars to enhance LLMs' planning capabilities without additional training. Yao et al. (2023) proposed ReAct, which guides models to interact with environments through a structured "thinking-action" paradigm, introducing explicit reasoning processes to improve environmental understanding and task performance. Subsequent research has expanded these foundations by developing specialized skill sets (Nottingham et al., 2024; Qiao et al., 2024; Zhao et al., 2023; Yao et al., 2024) and optimizing prompt engineering techniques (Shinn et al., 2023; Sarch et al., 2024; Sun et al., 2023a). While these approaches benefit from flexible deployment without retraining, they demonstrate limited effectiveness in highly complex environments. Training-based methods directly optimize LLMs for environmental interaction through additional training. A common approach is to use behavioral cloning, where an agent learns a policy by mimicking expert trajectories (Yin et al., 2024; Zeng et al., 2024a; Chen et al., 2023a; Qiao et al., 2024; Yuan et al., 2025; Song et al., 2024a; Xi et al., 2024). To obtain more diverse data for model training, some research has also explored incorporating negative trajectories into the training process (Song et al., 2024b; Wang et al., 2024b; Putta et al., 2024; Wang et al., 2025b; Xiong et al., 2024a; Zhai et al., 2025). However, these methods predominantly rely on pre-collected static datasets, which introduce critical limitations: (1) insufficient diversity in training examples, and (2) distribution shifts between training and test environments. Our proposed Interactive Planner-R1 addresses these limitations by generating training data through online environmental interaction. This dynamic approach allows models to actively explore environments and continuously optimize strategies based on direct feedback.

A.2 Self-Evolution via Reinforcement Learning

Reinforcement Learning has been proven to be an effective methodology for enabling LLMs to achieve self-evolution across various capabilities (Sun et al., 2023b; Li et al., 2025b; Lyu et al., 2025; Ying et al., 2024; Lightman et al., 2024; Luo et al., 2023). Recently, DeepSeek-R1 (DeepSeek-AI et al., 2025) discovered that employing simple reward functions for reinforcement learning can effectively drive self-improvement in LLMs, achieving remarkable performance enhancements across various complex reasoning tasks. Building upon this foundation, numerous studies have adopted this approach to attain SOTA performance across multiple domains, including mathematics (Hu et al., 2025; Lyu et al., 2025; Team et al., 2025), logical reasoning (Xie et al., 2025), and even visual domains (Liu et al., 2025; Pan et al., 2025).

While these approaches demonstrate significant self-evolution in reasoning and adaptation within static contexts, interactive planning presents unique challenges that go beyond both single-turn reasoning and retrieval-based dialogues (Zheng et al., 2025; Jin et al., 2025; Li et al., 2025a), as they require continuous interaction with environments to update states and involve planning across diverse action spaces. In these dynamic environments, limited understanding and weak planning capabilities can cause models to get stuck in costly blind trials. Our proposed Interactive Planner-R1 extends self-evolution to these complex planning scenarios, enabling LLMs to iteratively refine their strategies through reinforcement learning as they explore uncertain environments with incomplete information.

B Pseudo Code of Group rollout of interaction with environment

Algorithm 1 presents the detailed procedure for our group rollout strategy, which is a key component of our Interactive Planner-R1 approach. The group rollout mechanism enables efficient data collection by running multiple parallel trajectories for each task, thereby increasing sample diversity and improving training stability.

The algorithm operates in three main phases. First, it freezes the current policy to ensure consistent behavior during the rollout phase and samples a batch of task-environment pairs from the training dataset. Second, for each task in the batch, it creates multiple independent environment instances

---

Algorithm 1 Group rollout of interaction with environment

Input: Initial policy π_{θ_0}, dataset $\mathcal{D} = \{(q, e) : q \in \mathcal{Q}, e \in \mathcal{E}\}$, where $\mathcal{Q}$ is the set of instructions and $\mathcal{E}$ is the set of environments with the group size set to n.

1: Freeze old policy $\pi_{\theta_{\text{old}}} \leftarrow \pi_\theta$
2: Sample batch $\mathcal{B} = \{(q_i, e_i)\}_{i=0}^K \sim \mathcal{D}$
3: Initialize global trajectories buffer $\mathcal{T} \leftarrow \emptyset$
4: **for** $(q_i, e_i) \in \mathcal{B}$ **do**
5:    Create n environment instances $\{e_j\}^n$ copied from e_i
6:    Initialize n trajectory buffers $\{\tau_j\}^n \leftarrow \emptyset$ for environment instances $\{e_j\}^n$
7:    **for** $j = 1$ to n **do**
8:       $o_{j,0} \leftarrow e_j.\text{reset}()$
9:       $\tau_j \leftarrow (q_i, o_{j,0})$
10:    **end for**
11:    **for** $k = 1$ to max steps **do**
12:       Generate responses $\{m_{j,k} \sim \pi_{\theta_{\text{old}}}(\cdot | \tau_j)\}^n$ for each trajectory τ_j
13:       Extract actions $\{a_{j,k}\}^n$ from responses $\{m_{j,k}\}^n$
14:       Get observations $\{o_{j,k}, \text{done}_{j,k} \leftarrow e_j.\text{step}(a_{j,k})\}^n$
15:       Update trajectories $\{\tau_j \leftarrow \tau_j \oplus (m_{j,k}, o_{j,k})\}^n$
16:       **if** all done **then**
17:          **break**
18:       **end if**
19:    **end for**
20:    Save trajectories $\mathcal{T} \leftarrow \mathcal{T} \cup \{\tau_j\}^n$
21: **end for**

Output: The grouped trajectories $\mathcal{T}$

---

and initializes separate trajectory buffers. This parallel setup allows the agent to explore different action sequences for the same task, capturing various solution strategies and potential failure modes. Third, the algorithm executes the interaction loop where the frozen policy generates responses for each trajectory simultaneously, extracts actions from these responses, and updates the environment states accordingly.

The key advantage of this group rollout approach lies in its ability to collect diverse training data efficiently. By running n parallel trajectories for each task, we obtain multiple examples of agent behavior under identical initial conditions, which helps the learning algorithm better understand the consequences of different action choices. The parallel execution also reduces the overall data collection time compared to sequential rollouts. The algorithm terminates when all environments reach their done states or the maximum number of steps is reached, ensuring that we collect complete episodes for training. The collected trajectories are then used in subsequent training phases to update the policy parameters through our reward modeling and optimization procedures.

C Implementation Details

C.1 Evaluation and Benchmark Details

ALFWorld (Shridhar et al., 2021) ALFWorld encompasses six categories of planning tasks set primarily in home environments, covering not only basic object manipulation (such as pick and place) but also tasks requiring complex interaction sequences. For example, the heating task requires models to first identify target objects, move them to heating devices (like microwave), execute the heating operation, and finally place them in designated locations to complete the task.

Following prior research (Yao et al., 2023; Song et al., 2024b), we evaluate model performance under two conditions: seen and unseen scenarios. Seen scenarios consist of task instances from rooms encountered during training, unseen scenarios comprise task instances from entirely new rooms with container arrangements and scene organizations distinctly different from training tasks, designed to evaluate the model's zero-shot generalization capabilities.

ScienceWorld (Wang et al., 2022) Science-World presents a more challenging benchmark, requiring models to complete scientific experiments in a highly interactive environment. This environment contains approximately ten interconnected rooms, over 200 object types, and 25 executable actions. Compared to ALFWorld, ScienceWorld integrates a more sophisticated physics simulation engine, including thermodynamic and electrical systems, which places more rigorous demands on a model's planning capabilities and causal reasoning.

Following prior research (Yao et al., 2023; Song et al., 2024b), we assessed model performance under two conditions: seen and unseen scenarios. Seen scenarios consist of task instances from rooms encountered during training, including the same task types, objects, containers, and room layouts, but with variations in object positions, quantities, and visual features (e.g., two blue pencils on a shelf instead of three red pencils in a drawer as seen in training data). Unseen scenarios comprise task instances from entirely new rooms with container arrangements and scene organizations distinctly different from training tasks, designed to evaluate the model's zero-shot generalization capabilities. During evaluating ScienceWorld, we maintained the "easy" setup consistent with previous work (Song et al., 2024b), enabling all five assistive features: instant teleportation, pre-opened containers, self-watering flower pots, and two additional aids that remove similar micro-action bottlenecks, thus reducing the burden of low-level operations and focusing the evaluation on high-level planning abilities. We also adopted the same balancing strategy as previous work (Song et al., 2024b), implementing fair sampling at the task level.

C.2 Baseline

To benchmark our Interactive Planner-R1 against other training-based approaches, we compared it with three state-of-the-art methods that incorporate human priors: SFT (Zeng et al., 2024a), which fine-tunes on expert trajectories to learn interaction capabilities; NAT (Wang et al., 2024b), which incorporates learning from rejected trajectories; and ETO (Song et al., 2024b), which learns from expert trajectories through DPO. Our evaluation also includes larger models: GPT-3.5 Turbo (Brown et al., 2020)(gpt-3.5-turbo-0125), GPT-4 (OpenAI, 2023)(gpt-4o-2024-08-06), DeepSeek-V3 (DeepSeek-AI et al., 2024)(DeepSeek-V3-0324), and InternLM 2.5 20B (Team et al., 2024), to demonstrate the current performance of foundation large language models (both open-source and closed-source) on interactive planning tasks. All our implemented training-based methods are exclusively fine-tuned on Qwen2.5-7B-Instruct (Yang et al., 2024a), and all models are evaluated using a consistent set of prompts. Additionally, while many methods cannot be directly compared due to differences in models and evaluation approaches, we still provide these results in Table 4 for reference.

C.3 Training Details

We trained our model based on verl[1], a flexible LLM reinforcement learning training library, and implemented an interaction module on this foundation. In each training step, we sampled 128 tasks, with 5 trajectories sampled for each task, and each trajectory containing up to 30 interaction steps. All experiments were conducted on 8 NVIDIA A100 80GB GPUs. Additionally, we used Qwen2.5-7B-Instruct (Yang et al., 2024a)[2] as the backbone model, with training performed at a context length of 4096. The random seed is set to 42, and the KL penalty parameter is set to 0.001. During evaluation, the temperature is set to 1.0. Each experiment is run 5 times, and we report the mean and standard deviation.

D Prompt Design

In our research, prompt engineering accomplishes three interconnected objectives: (i) enumerating permissible action, guiding the model to execute effective commands; (ii) mitigating common hallucinations, preventing the model from falling into blind trial-and-error loops; and (iii) enforcing a concise ReAct paradigm that clearly demonstrates reasoning chains and actions, facilitating straightforward extraction of selected operations. Following (Qiao et al., 2024), we enhanced the system instructions to explicitly highlight the allowable action set, and required output format, while specifically addressing common hallucination patterns. This approach significantly increasing the probability of obtaining initial successful trajectories necessary for guided learning. The prompt is detailed in Figure 6 and Figure 7.

---

[1] https://github.com/volcengine/verl
[2] https://huggingface.co/Qwen/Qwen2.5-7B-Instruct

Figure 6: Prompt for ALFWorld

E   More experimental results

Figure 9a illustrates the metrics of the Interactive Planner-R1 during the training process in ALFWorld, which yields results similar to those in ScienceWorld. The reward curve exhibits a similar upward trend. Meanwhile, the response length significantly decreases from the outset, dropping from approximately 750 tokens initially to around 450 tokens by the end. The relationship between response length and action steps is also evident in Figure 5b, where total actions, invalid actions, and response length show a consistent downward trend. Due to the reduced difficulty compared to ScienceWorld, invalid steps have been almost entirely eliminated in the final results.

In Figure 8, we present the task completion performance of our trained agents in ScienceWorld, alongside a comparison with ReAct and ETO. This comparison underscores the effectiveness and generalization capabilities of our Interactive Planner-

Figure 7: Prompt for ScienceWorld

R1. While prompt-based and previous training-based methods often exhibit strong performance on tasks that emphasize common sense reasoning (e.g., chemistry), their success rates plummet when faced with tasks that heavily rely on environmental interaction (e.g., classification). In fact, many of these tasks remain unsolvable for prompt-based approaches. In contrast, our method demonstrates exceptional completion rates across both seen and unseen tasks, highlighting its robustness and adaptability in complex and varied scenarios.

Table 4 presents a comprehensive comparison of our Interactive Planner-R1 against existing methods on both ALFWorld and ScienceWorld benchmarks. The table is organized into two main sections to ensure fair evaluation: referenced results from original papers (marked with *) and our own implementations using identical experimental set-

tings. The referenced results section includes a wide range of state-of-the-art methods, from traditional approaches like CoLA and IPR to more recent advances such as CoPS and AgentPRM, with some methods achieving impressive performance on ALFWorld (e.g., CoPS reaching 94.0% average completion rate). However, it is important to note that these results may not be directly comparable due to potential differences in experimental configurations, evaluation protocols, or implementation details. Our implementation section provides a controlled comparison using consistent experimental settings across all methods. The results demonstrate that vanilla large language models with ReAcT prompting generally struggle on these tasks, with even GPT-4o achieving only 55.41% on ALFWorld and 58.18% on ScienceWorld. Training-based methods show signif-

Figure 8: Completion rates of Qwen2.5-7B-Instruct on various ScienceWorld tasks, covering both seen and unseen scenarios. We compare the prompt-based method ReAct with the training-based method ETO and Interactive Planner-R1.

(a) Rewards and response length   (b) Total and invalid action steps

Figure 9: Training progress of Interactive Planner-R1 in ALFWorld: (a) shows the rewards (task completion rate) and total response length in multi-round exploration; (b) illustrates the decreasing trends in both total and invalid action steps during training.

icant improvements, with ETO achieving 82.07% on ALFWorld, though its performance on Science-World remains limited at 56.20%. In contrast, our Interactive Planner-R1 achieves remarkable performance across both benchmarks, reaching 97.55% average completion rate on ALFWorld and 79.92% on ScienceWorld. Notably, our method demonstrates strong generalization capabilities, maintaining high performance on both seen and unseen scenarios, with minimal performance degradation between the two settings. This consistent performance across different task distributions highlights the robustness and effectiveness of our approach in complex interactive environments.

F More ablation study

Group Size Analysis The group rollout mechanism is central to Interactive Planner-R1's exploration strategy. We systematically examine how group size affects both exploration diversity and computational efficiency by varying the number of parallel trajectories from 2 to 7 and shown in Table 5.

As the Table 5 shown, the results reveal an interesting pattern: performance initially improves with group size (from 95.27% at size 2 to 97.73% at

Table 4: **Complete experimental results on ALFWorld and ScienceWorld benchmarks.** The best results are marked in **bold**. † indicates vanilla models tested with ReAcT prompting, and * denotes the best results reported in the original papers.

Method	ALFWorld			ScienceWorld		
	Seen	Unseen	Avg.	Seen	Unseen	Avg.
Referenced Results (Not Directly Comparable)						
KnowAgent* (Zhu et al., 2025)	66.71	62.69	64.70	58.67	49.18	53.93
CoLA* (Jia et al., 2025)	77.90	74.60	76.30	28.40	21.80	25.10
IPR* (Xiong et al., 2024b)	70.30	74.70	72.50	-	-	-
STeCa* (Wang et al., 2025a)	74.30	76.10	75.20	-	-	-
Agent-R* (Yuan et al., 2025)	-	-	-	-	-	70.23
DEP* (Wang et al., 2023)	-	-	76.00	-	-	-
WKM* (Qiao et al., 2024)	68.57	65.93	67.25	58.67	49.18	53.93
OREO* (Wang et al., 2024a)	79.10	80.70	79.90	-	-	-
QLASS* (Lin et al., 2025)	77.90	82.80	80.40	75.30	66.40	70.90
AgentLM* (Zeng et al., 2024b)	-	-	86.00	-	-	20.80
AgentPRM* (Choudhury, 2025)	-	-	91.00	-	-	-
AdaPlanner* (Sun et al., 2023a)	-	-	91.79	-	-	-
CoPS* (Yang et al., 2024b)	-	-	94.00	-	-	-
Our Implementation						
GPT-3.5-Turbo†(Brown et al., 2020)	7.14	7.46	7.30	28.03	21.63	24.83
GPT-4o†(OpenAI, 2023)	58.57	52.24	55.41	59.6	56.75	58.18
Deepseek-v3†(DeepSeek-AI et al., 2024)	36.43	31.34	33.89	29.28	27.45	28.37
InternLM 2.5 20B Chat†(Team et al., 2024)	7.86	11.94	9.90	33.66	31.15	32.41
Qwen2.5-7B-Instruct†(Yang et al., 2024a)	30.00	32.09	31.05	28.01	16.09	22.05
Qwen2.5-7B-Instruct + SFT(Zeng et al., 2024a)	80.71	79.10	79.91	68.81	55.7	62.26
Qwen2.5-7B-Instruct + NAT(Wang et al., 2024b)	63.57	66.42	65.00	58.56	49.75	54.16
Qwen2.5-7B-Instruct + ETO(Song et al., 2024b)	84.29	79.85	82.07	55.08	57.32	56.20
Qwen2.5-7B-Instruct + Interactive Planner-R1(Ours)	**98.57** $_{\pm 0.7}$	**96.52** $_{\pm 1.9}$	**97.55**	**83.66** $_{\pm 0.5}$	**76.18** $_{\pm 0.9}$	**79.92**

Table 5: Performance across different group sizes on ALFWorld. Group size 5 provides the optimal balance between exploration diversity and computational efficiency.

Group Size	Seen	Unseen	Avg.
2	97.86 $_{\pm 0.4}$	92.68 $_{\pm 0.8}$	95.27
3	98.14 $_{\pm 0.4}$	97.31 $_{\pm 0.4}$	97.73
5	98.57 $_{\pm 0.7}$	96.52 $_{\pm 1.9}$	97.55
7	98.93 $_{\pm 0.5}$	95.9 $_{\pm 0.5}$	97.41

Table 6: Impact of temperature parameter on ALFWorld performance. Higher temperature enables better exploration while maintaining action quality.

Temperature	Seen	Unseen	Avg.
0.5	96.43 $_{\pm 2}$	94.78 $_{\pm 0.3}$	95.61
0.7	97.86 $_{\pm 2}$	97.02 $_{\pm 1.1}$	97.44
1.0	98.57 $_{\pm 0.7}$	96.52 $_{\pm 1.9}$	97.55

Temperature Sensitivity Analysis Sampling temperature critically controls the exploration-exploitation trade-off during trajectory generation. We evaluate three temperature values to understand how randomness affects both exploration quality and final performance.

Temperature 1.0 achieves the highest overall performance (97.55%), indicating that sufficient exploration randomness is essential for discovering effective action sequences. Lower temperatures (0.5 and 0.7) result in more conservative exploration, limiting the model's ability to discover optimal strategies. Interestingly, temperature 0.7 shows the

size 3), suggesting that increased trajectory diversity enhances learning quality. However, beyond group size 5, we observe diminishing returns, particularly on unseen environments (95.9% for size 7 vs. 96.52% for size 5). This suggests that while larger groups provide more exploration diversity, they may also introduce noise that interferes with policy learning. Group size 5 emerges as the optimal configuration, balancing exploration breadth with learning stability.

best generalization (only 0.84% gap between seen and unseen), while temperature 1.0 provides the best overall performance despite a larger generalization gap (2.05%).

Table 7: Effect of KL penalty on ALFWorld performance. Removing KL constraints yields optimal performance, suggesting sparse rewards provide sufficient regularization.

KL Weight	Seen	Unseen	Avg.
0	99.29 $_{\pm 1}$	96.27 $_{\pm 2.1}$	97.78
0.001	98.57 $_{\pm 0.7}$	96.52 $_{\pm 1.9}$	97.55
0.1	97.15 $_{\pm 1}$	97.01 $_{\pm 1}$	97.08

KL Divergence Constraint Effects Kullback-Leibler (KL) penalty is commonly used in RL to prevent the policy from deviating too far from the reference model. We investigate whether such constraints are necessary given our sparse reward structure.

As shown in Table 7, removing KL penalty entirely ($\beta = 0$ in Equation 7) yields the highest performance (97.78%), outperforming both light ($\beta = 0.001$) and moderate ($\beta = 0.1$) regularization. This finding suggests that our sparse, completion-based reward structure inherently provides sufficient regularization against reward hacking and policy drift. The strong KL constraint (0.1) actually hurts performance by overly restricting policy updates, preventing the model from learning effective exploration strategies. However, we observed some degree of instability in unconstrained training, manifested as significant training curve fluctuations and inconsistent convergence rates. Based on this finding, we adopted light KL regularization ($\beta = 0.001$) as a compromise in our final implementation.

G Case Study: Model's Knowledge about Environment

Beyond the model's successful generalization to both seen and unseen examples, which already indicates its understanding of environmental knowledge, we conducted a case study in ALFWorld to further compare the differences in environmental knowledge mastery between Interactive Planner-R1 and the SFT model.

To demonstrate that the model has acquired environmental knowledge through exploration, we identified an object, CD, that appears in numerous

Figure 10: Comparison between Interactive Planner-R1 and SFT using the original task format, where Interactive Planner-R1 pointed out the possible position of CD and SFT exhibited inconsistency between thought and action .

Figure 11: Comparison between Interactive Planner-R1 and SFT when asked about the location of CD, showing SFT suffered from prior knowledge bias while Interactive Planner-R1 still succeeded.

tasks positioned on dining tables, which contradicts common expectations where CDs would more likely be stored in drawers or on shelves.

In Figure 10, we first maintained the input format used during training and found that although both SFT and Interactive Planner-R1 models made correct actions, the SFT model's thoughts did not strongly correlate with its actions. In contrast, Interactive Planner-R1 demonstrated awareness of CD locations in its thought process.

To further verify that Interactive Planner-R1 has mastered knowledge related to the environment, we modified the input format as shown in the Figure 11, changing the task to ask the model where CDs are most likely to appear. The SFT model failed to complete this type of task, with its thoughts still reflecting the influence of prior knowledge without recognizing that CD locations in ALFWorld differ from common expectations. Interactive Planner-R1, however, still made the correct analysis in its thoughts, proving that the model has successfully captured this implicit spatial relationship during its exploration phase.