RunyaNER: Auxiliary Language Selection for Runyankore NER

Abstract

Cross-lingual zero-shot transfer and multilingual fine-tuning are promising approaches for NLP tasks such as Named Entity Recognition (NER) in low-resource languages, but in the absence of target language benchmarks it is unclear which auxiliary language selection strategy leads to the best transfer. We introduce RunyaNER, the first publicly available NER benchmark for the East African language Runyankore, and use it to investigate the choice of which languages to use for transfer. Created with a semi-automated pipeline and fully manually verified, RunyaNER contains over 237k annotated words across 30k sentences. We benchmark pretrained models on RunyaNER, establishing that our dataset is of sufficient quality and size to produce effective Runyankore NER models. We then use RunyaNER to investigate auxiliary language selection in cross-lingual zero-shot and multilingual fine-tuning settings. Our experiments show that while transfer performance is highly sensitive to auxiliary language selection, embedding-based measures correlate more strongly with downstream transfer performance than traditional linguistic features based on metadata or typology. By releasing RunyaNER and providing a systematic analysis of auxiliary language selection strategies, this work contributes both a new benchmark resource and practical insights for multilingual transfer in low-resource settings.

1 Introduction

Despite rapid advances in NLP, many African languages remain severely underrepresented in computational resources, benchmark datasets, and pretrained language models (PLMs) (Mussandi and Wichert, 2024). This imbalance limits the development of downstream NLP systems for large populations of speakers across the continent. In particular, many African languages still lack the annotated datasets required to train and evaluate PLMs on

Split	Sentences	Tokens	Named entity spans
Train	15,001	118,622	2,720
Dev	7,498	59,028	1,364
Test	7,508	59,426	1,427
Total	30,007	237,076	5,511

Table 1: Summary statistics for RunyaNER.

structured prediction tasks such as Named Entity Recognition (NER).

Runyankore, a Bantu language spoken by over two million people in western Uganda (Namyalo et al., 2016; Eberhard et al., 2025), is one such underrepresented language. It belongs to the Runyakitara macrolanguage, which also includes closely related varieties such as Rukiga, Runyoro, and Rutooro (Bernsten, 1998). Although some efforts have begun to develop computational resources for Runyankore and related languages (Katushemererwe et al., 2020; Bamutura et al., 2020), publicly available benchmark datasets for downstream NLP tasks remain scarce. There is currently no publicly available NER dataset for Runyankore.

Beyond the absence of resources, an additional challenge for low-resource NLP is determining how to effectively leverage supervision from related languages for which annotated datasets are available. Multilingual PLMs (Devlin et al., 2019; Conneau et al., 2020) enable cross-lingual transfer through shared multilingual representations, but transfer performance varies across languages and tasks (Lauscher et al., 2020; Xu et al., 2022). Recent work has emphasised the influence of auxiliary language selection, particularly in zero-shot settings where no target-language supervision is available (Adelani et al., 2022; Eronen et al., 2023). However, it remains unclear which notions of language similarity provide the most reliable guidance for selecting effective transfer languages.

In this work, we address both challenges by introducing RunyaNER, the first publicly available NER

dataset for Runyankore, and using it to systematically study auxiliary language selection for low-resource transfer. RunyaNER consists of 237,076 annotated words (5,511 named entity spans) across 30,007 sentences. The dataset was created by annotating publicly available corpora using a semi-automated human-in-the-loop workflow involving iterative model-assisted annotation and manual verification by a native Runyankore speaker.

We establish the first benchmark for Runyankore NER under monolingual fine-tuning, cross-lingual zero-shot transfer, and multilingual fine-tuning settings. We further investigate auxiliary language selection across 20 African languages from MasakhaNER 2.0 (Adelani et al., 2022), comparing metadata-based, typological, and embedding-based similarity measures. Our goal is to determine whether embedding-based similarity measures provide better guidance for auxiliary language selection than traditional linguistic resources.

Under cross-lingual zero-shot transfer, performance is highly sensitive to auxiliary language choice, with closely related Great Lakes Bantu languages yielding the strongest transfer. However, across the full set of auxiliary languages, embedding-based similarity measures, particularly prototype cosine similarity and Sliced Wasserstein Distance (SWD), correlate more strongly with downstream transfer effectiveness than metadata-based or typological similarity measures. In contrast, once modest amounts of Runyankore supervision are introduced through multilingual fine-tuning, differences between auxiliary language choices become substantially smaller.

To our knowledge, this is the first systematic study of auxiliary language selection for African NER using both linguistic resource- and embedding-based similarity measures. In addition to introducing the first publicly available NER dataset for Runyankore, our findings provide practical guidance for multilingual transfer in low-resource settings and highlight the value of embedding-based similarity for selecting effective auxiliary languages under weak supervision.

2 Background

2.1 NER with Multilingual PLMs

Multilingual PLMs such as mBERT (Devlin et al., 2019) and XLM-R (Conneau et al., 2020) enable cross-lingual transfer by learning shared representations across languages. This allows supervision from high-resource languages to benefit low-resource languages in tasks such as NER (Pires et al., 2019; Lauscher et al., 2020), which has improved NER performance for many African languages (Adelani et al., 2022).

However, transfer performance varies substantially across languages and depends on factors such as tokenisation coverage (Rust et al., 2021), morphological and syntactic divergence (Lin et al., 2019), and the degree of language representation in multilingual pretraining corpora (Conneau et al., 2020; Ogueji et al., 2021). Prior work has also shown that transfer is generally more effective between linguistically related languages (Lauscher et al., 2020; Mahata et al., 2023). Regionally focussed models such as AfriBERTa (Ogueji et al., 2021) and Afro-XLMR (Alabi et al., 2022) further demonstrate the importance of language relatedness in multilingual transfer for African NLP.

2.2 Auxiliary Language Selection for Cross-Lingual Transfer

A key challenge in cross-lingual learning is selecting auxiliary languages that maximise transfer performance. Existing approaches derive similarity metrics either from external linguistic resources or from multilingual representation spaces. Linguistic similarity measures are typically based on resources such as URIEL/lang2Vec (Littell et al., 2017) and LinguaMeta (Ritchie et al., 2024), which capture genealogical, phonological, syntactic, and geographic properties. Embedding-based approaches instead measure similarity directly in multilingual embedding spaces, including cosine similarity between mean-pooled embeddings (Artetxe and Schwenk, 2019) and distribution-based metrics such as Sliced Wasserstein Distance (SWD) (Nguyen et al., 2020).

Several studies have shown that embedding-based similarity metrics correlate more strongly with downstream transfer performance than manually engineered typological or metadata-based features (Shaffer, 2021; Philippy et al., 2023; Yu et al., 2021). However, findings vary across tasks, models, and language families, making it unclear which similarity measures provide the most reliable guidance for realistic low-resource settings such as African-language NER.

Example 1

RUNYANKORE

Elly KaruhangaPER akahwihwisa ahabwa
KadagaPER kutaayaayira faamu ya **Museveni**PER.

ENGLISH

Elly Karuhanga murmurs over **Kadaga**'s trip
to **Museveni**'s ranch.

Example 2

RUNYANKORE

African UnionORG omuri **Addis Ababa**LOC
omukwezi kw'okubanza 2017DATE.

ENGLISH

African Union in **Addis Ababa** in **January
2017**.

---

3 RunyaNER Dataset

RunyaNER[1] is constructed using two publicly
available Runyankore-English parallel corpora: the
Sunbird African Language Technology (SALT) cor-
pus[2] and the Multilingual Parallel Text Corpora
(MPTC) (Babirye et al., 2023). SALT provides
broader domain coverage, including news, public
communication, and conversational content, while
MPTC contributes shorter and structurally more
regular sentences. After preprocessing and filtering,
the combined corpus contains 30,007 annotated
Runyankore sentences, of which approximately
72% originate from SALT and 28% from MPTC.

All sentences were annotated following the
MasakhaNER 2.0 guidelines (Adelani et al., 2022)
using four entity types: PER (person), LOC (lo-
cation), ORG (organisation), and DATE (date).
To reduce annotation time, we adopted a semi-
automated human-in-the-loop workflow in which
all annotation and verification was performed by
one of the authors, a native Runyankore speaker.
An initial seed set of approximately 500 Run-
yankore sentences was annotated manually. We
then fine-tuned XLM-R (Conneau et al., 2020)
on a combination of this seed data and train-
ing data for Luganda (a related language) from
MasakhaNER 2.0, using the resulting model to au-
tomatically pre-annotate the remaining Runyankore
corpus. All predicted labels were subsequently re-

---

[1]Dataset to be released upon publication under a research-
permissive license: `https://anonymous.4open.science/
r/RunyaNER-D6A3/README.md`

[2]`https://github.com/SunbirdAI/
salt-data-archive`

---

viewed and corrected manually using Doccano.[3]

Before annotation, both source corpora were nor-
malised to remove encoding artefacts, irregular
spacing, and malformed punctuation. Sentences
containing severe formatting or structural errors
were discarded. The final dataset was split into
train, development, and test partitions using a strat-
ified procedure to preserve consistent entity dis-
tributions across splits. Table 1 summarises the
dataset statistics, while Examples 1 and 2 illustrate
annotated Runyankore sentences with their corre-
sponding entity labels.

4 Benchmarking PLMs on RunyaNER

This section establishes baseline results for Run-
yankore NER using multilingual PLMs under three
supervision regimes: monolingual fine-tuning,
cross-lingual zero-shot transfer, and multilingual
(bilingual) fine-tuning with one auxiliary language.
The aim is to compare how model pretraining and
supervision regime affect Runyankore NER, and to
provide a controlled empirical foundation for the
auxiliary language selection analysis in Section 5.

4.1 Experimental Setup

We evaluate three encoder-only multilingual PLMs:
mBERT (Devlin et al., 2019), XLM-R (Conneau
et al., 2020), and Afro-XLMR (Alabi et al., 2022).
Afro-XLMR adapts XLM-R through continued pre-
training on 17 African languages, many of which
are related to Runyankore. This comparison al-
lows us to examine whether broad multilingual
coverage alone (mBERT, XLM-R) is sufficient for
Runyankore, or whether regionally adapted pre-
training yields additional gains. We follow the
MasakhaNER fine-tuning setup (Adelani et al.,
2022), training all our models for 10 epochs with
AdamW (Loshchilov and Hutter, 2019), a maxi-
mum sequence length of 164, and a batch size of
32. For evaluation, we report span-level micro-
averaged precision, recall, and F_1.

We consider three fine-tuning regimes. In the
monolingual setting, we fine-tune only on the
RunyaNER training split and evaluate on its test
set. In the zero-shot setting, we fine-tune on
MasakhaNER 2.0 training data for one auxiliary
language and evaluate directly on the RunyaNER
test set without exposure to Runyankore training
data. In multilingual (bilingual) fine-tuning, we
fine-tune on a combination of RunyaNER train-

---

[3]`https://github.com/doccano/doccano`

Model	DATE			LOC			ORG			PER			Overall		
	P	R	F1	P	R	F1	P	R	F1	P	R	F1	P	R	F1
Afro-XLMR	**0.760**	**0.790**	**0.770**	0.870	**0.890**	**0.880**	0.740	**0.720**	**0.730**	0.850	0.820	0.830	0.818	**0.833**	**0.826**
XLM-R	0.750	0.710	0.730	0.870	0.880	0.870	**0.780**	0.670	0.720	0.830	0.820	0.820	**0.823**	0.798	0.810
mBERT	0.720	0.720	0.720	0.850	0.880	0.870	0.730	0.680	0.710	**0.890**	**0.840**	**0.860**	0.804	0.803	0.803

Table 2: Monolingual fine-tuning results on RunyaNER (Baseline). Precision (P), recall (R), and F_1-score (F1) are reported for each entity type and overall.

Code	Language	Subgroup	Zero-shot F_1				Multilingual F_1			
			Afro-XLMR	mBERT	XLM-R	Mean	Afro-XLMR	mBERT	XLM-R	Mean
kin	Kinyarwanda	Bantu (Great Lakes)	0.619	0.576	0.557	0.584	0.820	0.813	0.814	0.816
lug	Luganda	Bantu (Great Lakes)	0.622	0.521	0.495	0.546	0.831	0.817	0.806	0.818
nya	Chichewa/Nyanja	Bantu (Southeast)	0.576	0.462	0.447	0.495	0.814	0.808	0.818	0.813
swa	Kiswahili	Bantu (Swahili)	0.584	0.500	0.341	0.475	0.827	0.812	0.810	0.816
wol	Wolof	Senegambian	0.464	0.481	0.450	0.465	0.821	0.807	0.813	0.814
twi	Akan/Twi	Kwa	0.527	0.398	0.377	0.434	0.817	0.810	0.807	0.811
zul	isiZulu	Bantu (Southern)	0.515	0.415	0.371	0.434	0.814	0.815	0.809	0.813
hau	Hausa	Chadic	0.577	0.294	0.336	0.402	0.828	0.813	0.810	0.817
luo	Luo	Nilotic	0.447	0.323	0.414	0.395	0.818	0.817	0.810	0.815
sna	chiShona	Bantu (Southern)	0.483	0.307	0.352	0.381	0.824	0.816	0.814	0.818
tsn	Setswana	Bantu (Southern)	0.452	0.433	0.241	0.375	0.826	0.817	0.813	0.819
xho	isiXhosa	Bantu (Southern)	0.396	0.417	0.309	0.374	0.813	0.819	0.814	0.815
ewe	Éwé	Kwa	0.389	0.263	0.441	0.364	0.823	0.804	0.793	0.807
fon	Fon	Volta-Niger	0.487	0.383	0.204	0.358	0.819	0.805	0.802	0.809
bam	Bambara	Mande	0.410	0.332	0.277	0.340	0.820	0.807	0.804	0.810
ibo	Igbo	Volta-Niger	0.481	0.243	0.269	0.331	0.828	0.813	0.809	0.817
mos	Mossi (Mooré)	Gur	0.355	0.330	0.263	0.316	0.812	0.810	0.810	0.811
yor	Yorùbá	Volta-Niger	0.475	0.174	0.247	0.299	0.822	0.811	0.810	0.814
pcm	Naijá Pidgin	English-based	0.387	0.170	0.143	0.233	0.826	0.813	0.809	0.816
bbj	Ghomálá'	Grassfields	0.052	0.096	0.025	0.058	0.815	0.803	0.804	0.807

Table 3: Zero-shot cross-lingual and multilingual (bilingual) fine-tuning F_1 results on the RunyaNER test set for all auxiliary languages, ordered by zero-shot mean F_1.

ing data and MasakhaNER 2.0 training data from one auxiliary language, still evaluating on the RunyaNER test set. We experiment with all 20 languages in MasakhaNER 2.0 (listed in Table 3) as auxiliary languages.

4.2 Results

Table 2 reports overall and entity-level results for monolingual fine-tuning. All three models achieve performance levels that reflect reasonably effective NER capabilities, with Afro-XLMR achieving the highest overall F_1, followed by XLM-R and then mBERT. This pattern holds across most entity types and is also reflected across precision and recall, with a small bias towards higher recall in Afro-XLMR. Afro-XLMR is considered a strong and well-established PLM for African languages. The fact that it achieves the best performance here reaffirms the value of regionally focussed multilingual PLMs. Even though Runyankore was not included in Afro-XLMR pretraining or adaptation, related Bantu languages such as Kinyarwanda and Kirundi were, which benefits RunyaNER through cross-lingual transfer.

Table 3 summarises Runyankore NER performance under cross-lingual zero-shot transfer and multilingual fine-tuning. For zero-shot transfer, performance varies greatly across auxiliary languages. The strongest transfer consistently comes from Great Lakes Bantu languages (Luganda and Kinyarwanda), which are geographically and genealogically related to Runyankore. Performance declines for less related languages. This indicates that zero-shot transfer is highly sensitive to auxiliary language similarity. Afro-XLMR is generally more robust than mBERT and XLM-R in this regime, suggesting that regionally adapted pretraining is beneficial when the model must rely entirely on cross-lingual generalisation.

In the multilingual (bilingual) fine-tuning setting, adding one auxiliary language yields only modest improvements over the Runyankore monolingual baseline. The gains are largest for mBERT, whereas Afro-XLMR and XLM-R remain close to their monolingual results. This pattern suggests that models with broader multilingual coverage benefit more from additional cross-lingual supervision, while regionally adapted models already

Metric	mBERT		XLM-R		Afro-XLMR	
	0-shot	multi	0-shot	multi	0-shot	multi
LinguaMeta	0.24	0.34	0.34	0.18	**0.56**	**0.25**
URIEL	**0.53**	**0.51**	**0.41**	**0.51**	0.52	0.10
Cosine	0.595	**0.571**	**0.638**	**0.634**	**0.488**	0.239
SWD	**0.635**	0.561	0.635	0.337	0.466	**0.340**

Table 4: Spearman correlation (ρ) between similarity metrics and Runyankore NER F_1 in 0-shot cross-lingual transfer and multilingual fine-tuning. We **boldface** highest ρ per metric type and **underline** highest ρ overall.

capture much of the transferable signal needed for Runyankore NER. The highest-ranked auxiliaries are again predominantly Bantu languages, although some more distant languages are also competitive once Runyankore supervision is included.

These results show that pretraining choice matters most under weak supervision. When Runyankore training data is available, all three models perform strongly and gaps are relatively small. In cross-lingual zero-shot transfer, however, the choice of model and auxiliary language becomes critical, with Afro-XLMR and closely related Bantu languages providing the strongest results.

5 Auxiliary Language Selection for Cross-Lingual Transfer

The substantial variation in performance across auxiliary languages motivates examining whether useful transfer languages can be identified systematically using metadata-based, typological, or embedding-based similarity signals. In this section, we investigate which measure of language similarity is most predictive for selecting auxiliary languages that optimise transfer for Runyankore NER.

5.1 Language Similarity Metrics

We compare four methods, two of which rely on traditional linguistic resources (metadata and typological features), and two of which are based on model representation (embedding) similarity (cosine similarity and Sliced Wasserstein Distance). We evaluate their ability to predict downstream performance under two regimes: cross-lingual zero-shot transfer and multilingual (bilingual) fine-tuning. Transfer effectiveness is measured using entity-level span F_1, and correlations are computed across 20 auxiliary languages and three encoders (mBERT, XLM-R, Afro-XLMR).

Metadata similarity (LinguaMeta). This method uses structured metadata such as script, geographic region, and language location to estimate cross-lingual relatedness (Ritchie et al., 2024). Individual features are normalised and combined into a single similarity score, capturing coarse-grained signals such as script compatibility and regional overlap. While simple and interpretable, this approach primarily reflects geographic and sociolinguistic proximity rather than linguistic structure.

Typological similarity (URIEL/lang2vec). This method represents languages using typological feature vectors derived from URIEL (Littell et al., 2017), accessed via lang2vec. We use concatenated syntactic and phonological vectors derived from resources such as WALS (Dryer and Haspelmath, 2013) and PHOIBLE (Moran and McCloy, 2019). Similarity is computed using cosine similarity between these vectors, yielding a linguistically grounded measure that reflects structural similarity between languages.

Prototype cosine similarity. This representation-based metric operates directly in multilingual embedding space. For each language, entity spans are encoded using a pretrained multilingual model and aggregated into entity-type prototypes via mean pooling. Similarity is computed as cosine similarity between corresponding prototypes, capturing alignment of named entities in the model's representation space. This method is layer-dependent, and similarity is computed separately at each encoder layer. Recent work has shown that model-based similarity measures can outperform handcrafted feature-based methods for transfer prediction (Deshpande et al., 2022; Dou and Neubig, 2021; Muller et al., 2021; Ebrahimi et al., 2025).

Sliced Wasserstein Distance (SWD). SWD compares full distributions of entity-span embeddings rather than only their means. It approximates the Wasserstein-1 distance by projecting embeddings onto multiple random directions and averaging one-dimensional distances (Nguyen et al., 2020). Unlike cosine similarity, SWD captures higher-order geometric differences such as dispersion and multimodality, providing a richer notion of representational similarity.

Figure 1: Runyankore NER transfer performance by auxiliary language ordered according to LinguaMeta similarity relative to Runyankore. Languages are arranged from highest to lowest similarity. Solid lines indicate cross-lingual zero-shot transfer, while dashed lines indicate multilingual fine-tuning performance.

Figure 2: Runyankore NER transfer performance by auxiliary language ordered according to URIEL typological similarity relative to Runyankore.

5.2 Which similarity metrics predict transfer?

We evaluate predictive usefulness by computing Spearman ρ correlation coefficients between similarity scores and Runyankore NER performance across auxiliary languages. For LinguaMeta and URIEL, we use a single similarity score per language. For prototype cosine similarity and SWD, which are layer-dependent, we report the strongest observed Spearman correlation across layers.

Correlation coefficients are presented in Table 4. All similarity metrics achieve positive correlations with transfer performance. Coefficients are higher for zero-shot transfer than multilingual fine-tuning, confirming that auxiliary language selection is most critical when no Runyankore supervision is available. Among linguistically-informed methods, typological similarity (URIEL) provides a more consistent signal than language metadata (Lin-guaMeta). Embedding-based metrics are the most informative. Prototype cosine similarity achieves the strongest correlations in most instances, but SWD is often competitive. These results show that embedding-based similarity metrics are more reliable predictors of transfer performance, and therefore more informative for auxiliary language selection, than metadata-based or typological similarity measures.

5.3 Similarity ordering and transfer performance

Figures 1, 2, 3, and 4 plot Runyankore NER transfer performance across auxiliary languages, ordered according to each similarity metric. These plots provide a detailed visualisation of the results underlying the trends in Table 4. The weaker correlations of linguistic resource-based methods are

Figure 3: Runyankore NER transfer performance by auxiliary language ordered according to prototype cosine similarity relative to Runyankore.

Figure 4: Runyankore NER transfer performance by auxiliary language ordered according to Sliced Wasserstein Distance (SWD) similarity relative to Runyankore. Lower SWD values indicate stronger representational similarity.

reflected in the more unstable performance patterns of Figures 1 and 2. While these metrics are broadly predictive (very high-similarity languages tend to transfer better than very low-similarity ones), performance varies substantially across individual language rankings.

In contrast, embdding-based similarity measures produce more consistent alignment between similarity ordering and transfer effectiveness, as shown in Figure 3, and 4. This is especially visible for prototype cosine similarity in Figure 3, where we see a clear relationship between similarity and transfer performance for the languages closest to Runyankore in multilingual embedding space. Embedding-based cosine similarity offers a more precise signal than linguistic resource-based metrics, distinguishing between individual top-ranked auxiliary language candidates rather than only separating highly dissimilar languages.

The plots also show a strong regime-dependent pattern. In the cross-lingual zero-shot setting, transfer performance varies substantially across auxiliary languages, indicating that auxiliary language selection is important when no Runyankore supervision is available. In contrast, multilingual fine-tuning produces substantially flatter transfer curves, suggesting that auxiliary language similarity becomes less important once modest amounts of Runyankore supervision are introduced.

5.4 From individual languages to auxiliary language groups

In many multilingual transfer settings, supervision is drawn from groups of auxiliary languages rather than a single source language (Shaffer, 2021; Ebrahimi et al., 2025). We therefore extend the analysis from individual auxiliary languages to auxiliary language quartets. For each similarity met-

Similarity	Auxiliary	Zero-shot F_1				Multilingual F_1			
metric	language(s)	Afro-XLMR	mBERT	XLM-R	Mean	Afro-XLMR	mBERT	XLM-R	Mean
Quartets									
LinguaMeta	lug/kin/swa/luo	0.644	0.615	0.635	0.631	0.817	**0.821**	0.809	0.816
URIEL	tsn/nya/lug/swa	0.593	0.582	0.566	0.580	0.812	0.813	**0.816**	0.814
Cosine	lug/sna/kin/nya	**0.651**	**0.619**	**0.653**	**0.641**	0.825	0.815	0.814	**0.818**
SWD	kin/twi/luo/ibo	0.598	0.515	0.562	0.558	0.817	0.815	0.809	0.814
Single auxiliary									
LinguaMeta	kin	0.619	0.576	0.557	0.584	0.820	0.813	0.814	0.816
URIEL	lug	0.622	0.521	0.495	0.546	**0.831**	0.817	0.806	**0.818**
Cosine	kin	0.619	0.576	0.557	0.584	0.817	0.820	0.814	0.817
SWD	twi	0.527	0.377	0.557	0.487	0.817	0.810	0.807	0.811

Table 5: Runyankore NER performance under different auxiliary language selection schemes. Top-ranked quartets are shown for each similarity scheme, alongside the most similar single auxiliary language per scheme. **Bold** indicates the highest value in each column.

ric, languages were first ranked according to their similarity to Runyankore. We then constructed language quartets by selecting the four highest-ranked auxiliary languages under each similarity scheme (the first two columns of Table 5 list the resulting language groups). For layer-dependent embedding-based metrics, rankings were averaged across all layers and the three multilingual PLMs to obtain a model-agnostic ordering. The resulting quartets therefore represent the strongest auxiliary language groups predicted by each similarity metric.

Table 5 reports F_1 scores for the highest-ranked quartet under each method. We compare these results to the top-ranked single auxiliary language predicted by each similarity metric (similarly averaged for the embedding-based metrics). In the zero-shot setting, using multiple auxiliary languages consistently outperforms using a single auxiliary language, with quartets improving mean F_1 by several points. In multilingual fine-tuning, this advantage largely disappears: differences between quartets and single auxiliaries are small, suggesting that once Runyankore supervision is available, additional auxiliary languages offer little benefit.

The results reaffirm that, in cross-lingual zero-shot transfer, auxiliary language selection is crucial. Cosine-based quartets consistently achieve the best performance across all models, followed by LinguaMeta and SWD. As in individual auxiliary language selection, embedding representation-based similarity is more effective for selecting transfer languages.

Performance differences between quartets are much smaller in multilingual fine-tuning than in zero-shot transfer. Performance converges across grouping strategies, and no single method consis-

tently dominates. As in individual auxiliary language selection, once modest Runyankore supervision is available, the importance of auxiliary group language selection.

These results reinforce the earlier findings. Auxiliary language selection is critical under cross-lingual zero-shot transfer, where embedding-based similarity provides the strongest guidance. Under multilingual fine-tuning, however, the effect of auxiliary choice is substantially reduced.

6 Conclusion

We introduced RunyaNER, the first publicly available NER dataset for Runyankore, and established benchmark results for Runyankore NER using multilingual PLMs under monolingual, zero-shot, and multilingual fine-tuning settings. Our experiments show that auxiliary language selection is particularly important in cross-lingual zero-shot transfer, where closely related Great Lakes Bantu languages yield the strongest transfer performance. Embedding-based similarity measures correlate more strongly with downstream transfer effectiveness than metadata-based or typological approaches, while auxiliary language choice becomes substantially less important once Runyankore supervision is introduced through multilingual fine-tuning. We hope that RunyaNER will support future research on low-resource African NLP and multilingual transfer learning.

Limitations

This study focuses only on Runyankore NER, and the observed auxiliary-language selection patterns may not generalise to other NLP tasks or languages.

Our experiments are limited to three encoder-based multilingual models and twenty African auxiliary languages, which restricts broader architectural and linguistic coverage. In addition, the two sources of the RunyaNER dataset are concentrated in relatively similar domains. Embedding-based similarity measures depend on modelling choices such as encoder layer selection and embedding aggregation, which were not evaluate exhaustively.

References

David Ifeoluwa Adelani, Graham Neubig, Sebastian Ruder, Shruti Rijhwani, Michael Beukman, Chester Palen-Michel, Constantine Lignos, Jesujoba O. Alabi, Shamsuddeen H. Muhammad, Peter Nabende, Cheikh M. Bamba Dione, Andiswa Bukula, Rooweither Mabuya, Bonaventure F. P. Dossou, Blessing Sibanda, Happy Buzaaba, Jonathan Mukiibi, Godson Kalipe, Derguene Mbaye, and 26 others. 2022. MasakhaNER 2.0: Africa-centric transfer learning for named entity recognition. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 4488–4508, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Jesujoba O. Alabi, David Ifeoluwa Adelani, Marius Mosbach, and Dietrich Klakow. 2022. Adapting pre-trained language models to African languages via multilingual adaptive fine-tuning. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 4336–4349, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.

Mikel Artetxe and Holger Schwenk. 2019. Massively multilingual sentence embeddings for zero-shot cross-lingual transfer and beyond. *Transactions of the Association for Computational Linguistics*, 7:597–610.

Claire Babirye, Francis Jeremy Tusubira, Joyce Nakatumba-Nabende, Andrew Katumba, Medadi Ssentanda, Peter Nabende, Jonathan Mukiibi, Eric Peter Wairagala, and Tobius Bateesa. 2023. Multilingual Parallel Text Corpora for East African Languages.

David Bamutura, Peter Ljunglöf, and Peter Nebende. 2020. Towards computational resource grammars for Runyankore and rukiga. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 2846–2854, Marseille, France. European Language Resources Association.

Jan Bernsten. 1998. Runyakitara: Uganda's 'new' language. *Journal of Multilingual and Multicultural Development*, 19(2):93–107.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.

Ameet Deshpande, Partha Talukdar, and Karthik Narasimhan. 2022. When is BERT multilingual? isolating crucial ingredients for cross-lingual transfer. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3610–3623, Seattle, United States. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Zi-Yi Dou and Graham Neubig. 2021. Word alignment by fine-tuning embeddings on parallel corpora. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2112–2128, Online. Association for Computational Linguistics.

Matthew S. Dryer and Martin Haspelmath, editors. 2013. *WALS Online (v2020.4)*. Zenodo.

David M. Eberhard, Gary F. Simons, and Charles D. Fennig, editors. 2025. *Ethnologue: Languages of the World*, twenty-eighth edition. SIL International, Dallas, Texas. Online version: https://www.ethnologue.com/.

Abteen Ebrahimi, Adam Wiemerslage, and Katharina von der Wense. 2025. Model-based ranking of source languages for zero-shot cross-lingual transfer. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 32404–32449, Suzhou, China. Association for Computational Linguistics.

Juuso Eronen, Michal Ptaszynski, and Fumito Masui. 2023. Zero-shot cross-lingual transfer language selection using linguistic similarity. *Information Processing & Management*, 60(3):103250.

Fridah Katushemererwe, Andrew Caines, and Paula Buttery. 2020. Building natural language processing tools for runyakitara. *Applied Linguistics Review*, 12.

Anne Lauscher, Vinit Ravishankar, Ivan Vulić, and Goran Glavaš. 2020. From zero to hero: On the limitations of zero-shot language transfer with multilingual Transformers. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4483–4499, Online. Association for Computational Linguistics.

Yu-Hsiang Lin, Chian-Yu Chen, Jean Lee, Zirui Li, Yuyan Zhang, Mengzhou Xia, Shruti Rijhwani, Junxian He, Zhisong Zhang, Xuezhe Ma, Antonios Anastasopoulos, Patrick Littell, and Graham Neubig. 2019. Choosing transfer languages for cross-lingual learning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3125–3135, Florence, Italy. Association for Computational Linguistics.

Patrick Littell, David R. Mortensen, Ke Lin, Katherine Kairis, Carlisle Turner, and Lori Levin. 2017. URIEL and lang2vec: Representing languages as typological, geographical, and phylogenetic vectors. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pages 8–14, Valencia, Spain. Association for Computational Linguistics.

Ilya Loshchilov and Frank Hutter. 2019. Decoupled weight decay regularization. *Preprint*, arXiv:1711.05101.

Sainik Kumar Mahata, Dipanjan Saha, Dipankar Das, and Sivaji Bandyopadhyay. 2023. Transfer learning in low-resourced MT: An empirical study. In *Proceedings of the 20th International Conference on Natural Language Processing (ICON)*, pages 646–650, Goa University, Goa, India. NLP Association of India (NLPAI).

Steven Moran and Daniel McCloy, editors. 2019. *PHOIBLE 2.0*. Max Planck Institute for the Science of Human History, Jena.

Benjamin Muller, Yanai Elazar, Benoît Sagot, and Djamé Seddah. 2021. First align, then predict: Understanding the cross-lingual ability of multilingual BERT. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2214–2231, Online. Association for Computational Linguistics.

Joaquim Mussandi and Andreas Wichert. 2024. NLP tools for African languages: Overview. In *Proceedings of the 16th International Conference on Computational Processing of Portuguese - Vol. 2*, pages 73–82, Santiago de Compostela, Galicia/Spain. Association for Computational Lingustics.

Saudah Namyalo, Bebwa Isingoma, and Christiane Meierkord. 2016. Towards assessing the space of English in Uganda's linguistic ecology: Facts and issues. In Christiane Meierkord, Bebwa Isingoma, and Saudah Namyalo, editors, *Ugandan English: Its Sociolinguistics, Structure and Uses in a Globalising Post-Protectorate*, volume G59 of *Varieties of English Around the World*, pages 19–50. John Benjamins Publishing Company, Amsterdam.

Khai Nguyen, Nhat Ho, Tung Pham, and Hung Bui. 2020. Distributional sliced-wasserstein and applications to generative modeling. *Preprint*, arXiv:2002.07367.

Kelechi Ogueji, Yuxin Zhu, and Jimmy Lin. 2021. Small data? no problem! exploring the viability of pretrained multilingual language models for low-resourced languages. In *Proceedings of the 1st Workshop on Multilingual Representation Learning*, pages 116–126, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Fred Philippy, Siwen Guo, and Shohreh Haddadan. 2023. Identifying the correlation between language distance and cross-lingual transfer in a multilingual representation space. In *Proceedings of the 5th Workshop on Research in Computational Linguistic Typology and Multilingual NLP*, pages 22–29, Dubrovnik, Croatia. Association for Computational Linguistics.

Telmo Pires, Eva Schlinger, and Dan Garrette. 2019. How multilingual is multilingual BERT? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4996–5001, Florence, Italy. Association for Computational Linguistics.

Sandy Ritchie, Daan van Esch, Uche Okonkwo, Shikhar Vashishth, and Emily Drummond. 2024. Linguameta: Unified metadata for thousands of languages. In *Proceedings of the Joint International Conference on Computational Linguistics, Language Resources and Evaluation*, pages 10530—-10538, Torino, Italy. European Language Resources Association.

Phillip Rust, Jonas Pfeiffer, Ivan Vulić, Sebastian Ruder, and Iryna Gurevych. 2021. How good is your tokenizer? on the monolingual performance of multilingual language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 3118–3135, Online. Association for Computational Linguistics.

Kyle Shaffer. 2021. Language clustering for multilingual named entity recognition. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 40–45, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Ningyu Xu, Tao Gui, Ruotian Ma, Qi Zhang, Jingting Ye, Menghan Zhang, and Xuanjing Huang. 2022. Cross-linguistic syntactic difference in multilingual BERT: How good is it and how does it affect transfer? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 8073–8092, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Dian Yu, Taiqi He, and Kenji Sagae. 2021. Language embeddings for typology and cross-lingual transfer learning. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 7210–7225, Online. Association for Computational Linguistics.

Appendix

A Embedding-Based Similarity Results

Avg. Rank	Code	Language	Subgroup	Afro-XLMR		mBERT		XLM-R	
				Mean ± Std	Rank	Mean ± Std	Rank	Mean ± Std	Rank
1.33	kin	Kinyarwanda	Bantu (Great Lakes)	0.9984±0.0040	(2)	0.9913±0.0069	(1)	0.999989±0.000019	(1)
3.33	lug	Luganda	Bantu (Great Lakes)	0.9979±0.0055	(4)	0.9899±0.0084	(4)	0.999986±0.000030	(2)
4.33	nya	Chichewa/Nyanja	Bantu (Southeast)	0.9976±0.0065	(7)	0.9904±0.0077	(3)	0.999985±0.000029	(3)
4.67	luo	Luo	Nilotic	0.9981±0.0047	(3)	0.9880±0.0096	(7)	0.999982±0.000029	(4)
5.00	twi	Akan/Twi	Kwa	0.9985±0.0033	(1)	0.9891±0.0086	(5)	0.999972±0.000057	(9)
7.00	zul	isiZulu	Bantu (Southern)	0.9975±0.0063	(9)	0.9884±0.0093	(6)	0.999979±0.000045	(6)
7.33	sna	chiShona	Bantu (Southern)	0.9970±0.0081	(12)	0.9910±0.0071	(2)	0.999974±0.000072	(8)
8.67	ibo	Igbo	Volta-Niger	0.9976±0.0065	(8)	0.9879±0.0095	(8)	0.999972±0.000054	(10)
9.67	ewe	Éwé	Kwa	0.9977±0.0053	(6)	0.9815±0.0151	(16)	0.999975±0.000046	(7)
10.67	mos	Mossi (Mooré)	Gur	0.9972±0.0073	(10)	0.9865±0.0108	(11)	0.999971±0.000054	(11)
10.67	wol	Wolof	Senegambian	0.9969±0.0079	(15)	0.9849±0.0118	(12)	0.999979±0.000037	(5)
11.33	tsn	Setswana	Bantu (Southern)	0.9977±0.0053	(5)	0.9825±0.0141	(14)	0.999967±0.000089	(15)
12.33	swa	Kiswahili	Bantu (Swahili)	0.9970±0.0059	(11)	0.9840±0.0135	(13)	0.999970±0.000053	(13)
14.33	hau	Hausa	Chadic	0.9967±0.0071	(16)	0.9878±0.0097	(9)	0.999910±0.000257	(18)
14.67	xho	isiXhosa	Bantu (Southern)	0.9963±0.0098	(20)	0.9877±0.0099	(10)	0.999967±0.000082	(14)
16.00	bbj	Ghomálá'	Grassfields	0.9966±0.0088	(17)	0.9742±0.0220	(19)	0.999971±0.000061	(12)
16.67	bam	Bambara	Mande	0.9966±0.0093	(18)	0.9821±0.0155	(15)	0.999956±0.000086	(17)
16.67	fon	Fon	Volta-Niger	0.9970±0.0072	(14)	0.9766±0.0190	(17)	0.999892±0.000277	(19)
17.67	pcm	Naijá Pidgin	English-based	0.9970±0.0055	(13)	0.9726±0.0233	(20)	0.999828±0.000551	(20)
17.67	yor	Yorùbá	Volta-Niger	0.9965±0.0093	(19)	0.9755±0.0185	(18)	0.999964±0.000064	(16)

Table A.1: Prototype cosine similarity between Runyankore and each auxiliary language, averaged across the 12 layers (mean ± std). Languages are ordered by average rank across Afro-XLMR, mBERT, and XLM-R (lower is better). Each model reports mean cosine similarity (± std) and the within-model rank.

Avg. Rank	Code	Language	Subgroup	Afro-XLMR		mBERT		XLM-R	
				Mean ± Std	Rank	Mean ± Std	Rank	Mean ± Std	Rank
1.33	twi	Akan/Twi	Kwa	0.0058±0.0012	(1)	0.0092±0.0018	(1)	0.0056±0.0015	(2)
1.67	kin	Kinyarwanda	Bantu (Great Lakes)	0.0059±0.0010	(2)	0.0095±0.0018	(2)	0.0054±0.0014	(1)
3.00	luo	Luo	Nilotic	0.0061±0.0011	(3)	0.0097±0.0020	(3)	0.0060±0.0016	(3)
5.33	ibo	Igbo	Volta-Niger	0.0064±0.0011	(7)	0.0103±0.0018	(5)	0.0061±0.0015	(4)
6.33	lug	Luganda	Bantu (Great Lakes)	0.0062±0.0011	(4)	0.0100±0.0018	(4)	0.0068±0.0017	(11)
6.67	tsn	Setswana	Bantu (Southern)	0.0064±0.0011	(6)	0.0106±0.0019	(9)	0.0063±0.0015	(5)
8.33	nya	Chichewa/Nyanja	Bantu (Southeast)	0.0065±0.0011	(8)	0.0104±0.0019	(7)	0.0067±0.0017	(10)
8.33	zul	isiZulu	Bantu (Southern)	0.0066±0.0011	(9)	0.0109±0.0022	(10)	0.0064±0.0017	(6)
8.67	ewe	Éwé	Kwa	0.0063±0.0011	(5)	0.0117±0.0022	(14)	0.0065±0.0018	(7)
9.67	swa	Kiswahili	Bantu (Swahili)	0.0067±0.0011	(10)	0.0103±0.0018	(6)	0.0069±0.0018	(13)
10.00	sna	chiShona	Bantu (Southern)	0.0070±0.0013	(13)	0.0106±0.0021	(8)	0.0066±0.0017	(9)
10.33	wol	Wolof	Senegambian	0.0069±0.0013	(12)	0.0113±0.0021	(11)	0.0066±0.0017	(8)
13.33	pcm	Naijá Pidgin	English-based	0.0068±0.0012	(11)	0.0114±0.0020	(13)	0.0072±0.0019	(16)
15.33	hau	Hausa	Chadic	0.0071±0.0013	(14)	0.0114±0.0022	(12)	0.0078±0.0021	(20)
15.33	xho	isiXhosa	Bantu (Southern)	0.0079±0.0014	(19)	0.0120±0.0021	(15)	0.0068±0.0018	(12)
16.33	fon	Fon	Volta-Niger	0.0073±0.0013	(15)	0.0122±0.0024	(16)	0.0073±0.0021	(18)
16.33	mos	Mossi (Mooré)	Gur	0.0077±0.0014	(18)	0.0124±0.0025	(17)	0.0071±0.0021	(14)
16.67	bbj	Ghomálá'	Grassfields	0.0074±0.0014	(16)	0.0132±0.0026	(19)	0.0071±0.0019	(15)
18.00	bam	Bambara	Mande	0.0076±0.0014	(17)	0.0125±0.0022	(18)	0.0075±0.0020	(19)
19.00	yor	Yorùbá	Volta-Niger	0.0081±0.0015	(20)	0.0146±0.0028	(20)	0.0073±0.0020	(17)

Table A.2: Sliced Wasserstein Distance (SWD) results between Runyankore and each auxiliary language, averaged across the 12 layers (mean ± std). Languages are ordered by average rank across Afro-XLMR, mBERT, and XLM-R (lower is better). Each model reports mean SWD (± std) and the within-model rank.