DR3: Value-Based Deep Reinforcement Learning Requires Explicit Regularization

Abstract

Despite overparameterization, deep networks trained via supervised learning are surprisingly easy to optimize and exhibit excellent generalization. One hypothesis to explain this is that overparameterized deep networks enjoy the benefits of implicit regularization induced by stochastic gradient descent, which favors parsimonious solutions that generalize well on test inputs. It is reasonable to surmise that deep reinforcement learning (RL) methods could also benefit from this effect. In this paper, we discuss how the implicit regularization effect of SGD seen in supervised learning could in fact be harmful in the offline deep RL setting, leading to poor generalization and degenerate feature representations. Our theoretical analysis shows that when existing models of implicit regularization are applied to temporal difference learning, the resulting derived regularizer favors degenerate solutions with excessive aliasing, in stark contrast to the supervised learning case. We back up these findings empirically, showing that feature representations learned by a deep network value function trained via bootstrapping can indeed become degenerate, aliasing the representations for state-action pairs that appear on either side of the Bellman backup. To address this issue, we derive the form of this implicit regularizer and, inspired by this derivation, propose a simple and effective *explicit* regularizer, called DR3, that counteracts the undesirable effects of this implicit regularizer. When combined with existing offline RL methods, DR3 substantially improves performance and stability, alleviating unlearning in Atari 2600 games, D4RL domains and robotic manipulation from images.

1 Introduction

Deep neural networks are overparameterized, which in principle should leave them vulnerable to overfitting. Despite this, supervised learning with deep networks still learn representations that generalize well. A widely held consensus is that deep nets find simple solutions that generalize due to various *implicit* regularization effects (Blanc et al., 2020; Woodworth et al., 2020; Arora et al., 2018; Gunasekar et al., 2017; Wei et al., 2019). We may surmise that using deep nets in reinforcement learning (RL) will work well for the same reason, learning effective representations that generalize due to such implicit regularization effects. But is this actually the case for value functions trained via bootstrapping?

In this paper, we argue that, while implicit regularization leads to effective representations in supervised deep learning, it may lead to poor learned representations when training overparameterized deep network value functions. There is already evidence that value functions trained via bootstrapping learn poor representations: value functions trained with offline deep RL eventually degrade in performance (Agarwal et al., 2020; Kumar et al., 2021) and this degradation is correlated with the emergence of low-rank features in the value network (Kumar et al., 2021).We focus specifically on the offline RL setting, in order to rule out any confounding effects from exploration and non-stationary data. In this paper, we aim to understand the underlying cause of the emergence of poor representations and develop a potential solution. Building on the theoretical framework developed by Blanc et al. (2020); Damian et al. (2021), we characterize the implicit regularizer that arises when training deep value functions with TD learning. This implicit regularizer implies that TD-learning would alias representations of state-action tuples that appear on either side of a Bellman backup.

We show that this theoretically predicted aliasing phenomenon manifests in practice as feature **co-adaptation**, where the features of consecutive state-action tuples learned by the Q-value network

become extremely similar in terms of their dot product (Section 3). This co-adaptation can lead to oscillatory learning dynamics, and potentially to poor performance. We find that even when Q-values are not overestimated, prolonged training in offline RL can result in performance degradation as feature co-adaptation increases. To mitigate the co-adaptation issue that arises as a result of implicit regularization, we propose an *explicit regularizer* that we call DR3 (Section 4). While exactly estimating and cancelling the effects of the theoretically derived implicit regularizer is computationally difficult, DR3 provides a simple and tractable theoretically-inspired approximation, that mitigates the issues discussed above. In practice, DR3 amounts to regularizing the features at consecutive state-action pairs to be dissimilar in terms of their dot-product similarity. Empirically, we find that DR3 allows neural net Q-functions to use their full representational capacity as measured by the rank of the learned features, giving rise to methods that train for longer, reach a better solution, and remain stable at this solution without severe degradation (Section 6).

Our first contribution is the derivation of the implicit regularizer that arises when training deep net value functions via TD learning, and empirically demonstrate it manifests as *feature co-adaptation* in the offline deep RL setting. Feature co-adaptation accounts at least in part for some of the challenges of offline deep RL, including degradation of performance with prolonged training. Second, we propose a simple and effective *explicit* regularizer for offline value-based RL, DR3, which minimizes the feature similarity between state-action pairs appearing in a bootstrapping update. DR3 is inspired by the theoretical derivation of the implicit regularizer, it alleviates co-adaptation and can be easily combined with modern offline RL methods, such as REM (Agarwal et al., 2020), CQL (Kumar et al., 2020b), and BRAC (Wu et al., 2019). Empirically, using DR3 in conjunction with existing offline RL methods provides about **60%** performance improvement on the harder D4RL (Fu et al., 2020) tasks, and **160%** and **25%** stability gains for REM and CQL respectively, on offline RL tasks in 17 Atari 2600 games. Additionally, we observe large improvements on image-based robotic manipulation tasks (Singh et al., 2020).

2 PRELIMINARIES

The goal in RL is to maximize the long-term discounted reward in an MDP, defined as $(\mathcal{S}, \mathcal{A}, R, P, \gamma)$ (Puterman, 1994), with state space $\mathcal{S}$, action space $\mathcal{A}$, a reward function $R(\mathbf{s}, \mathbf{a})$, dynamics $P(\mathbf{s}'|\mathbf{s}, \mathbf{a})$ and a discount factor $\gamma \in [0, 1)$. The Q-function $Q^\pi(\mathbf{s}, \mathbf{a})$ for a policy $\pi(\mathbf{a}|\mathbf{s})$ is the expected sum of discounted rewards obtained by executing action $\mathbf{a}$ at state $\mathbf{s}$ and following $\pi(\mathbf{a}|\mathbf{s})$ thereafter. $Q^\pi(\mathbf{s}, \mathbf{a})$ is the fixed point of $Q(\mathbf{s}, \mathbf{a}) := R(\mathbf{s}, \mathbf{a}) + \gamma \mathbb{E}_{\mathbf{s}' \sim P(\cdot|\mathbf{s}, \mathbf{a}), \mathbf{a}' \sim \pi(\cdot|\mathbf{s}')} [Q(\mathbf{s}', \mathbf{a}')]$. We study the offline RL setting, where the algorithm must learn a policy only using a given dataset $\mathcal{D} = \{(\mathbf{s}_i, \mathbf{a}_i, \mathbf{s}_i', r_i)\}$, generated from some behavior policy, $\pi_\beta(\mathbf{a}|\mathbf{s})$, without active data collection. The Q-function is parameterized with a neural net with parameters θ. We will denote the penultimate layer of the deep network (the learned *features*) $\phi_\theta(\mathbf{s}, \mathbf{a})$, such that $Q_\theta(\mathbf{s}, \mathbf{a}) = \mathbf{w}^T \phi(\mathbf{s}, \mathbf{a})$, where $\mathbf{w} \in \mathbb{R}^d$. Standard deep RL methods (Mnih et al., 2015; Haarnoja et al., 2018) convert the Bellman equation into a squared temporal difference (TD) error objective for Q_θ:

$$\mathcal{L}_{\text{TD}}(\theta) = \sum_{\mathbf{s}, \mathbf{a}, \mathbf{s}' \sim \mathcal{D}} \left(R(\mathbf{s}, \mathbf{a}) + \gamma \overline{Q}_\theta(\mathbf{s}', \mathbf{a}') - Q_\theta(\mathbf{s}, \mathbf{a}) \right)^2, \tag{1}$$

where $\bar{Q}_\theta$ is a delayed copy of same Q-network, referred to as the *target network* and $\mathbf{a}'$ is computed by maximizing the target Q-function at state $\mathbf{s}'$ for Q-learning (i.e., when computing Q^*) and by sampling $\mathbf{a}' \sim \pi(\cdot|\mathbf{s})$ when computing the Q-value Q^π of a policy π.

A major problem in offline RL is the issue of distributional shift between the learned policy and the behavior policy (Levine et al., 2020). Since our goal is to study the effect of implicit regularization in TD-learning and not distributional shift, we build on top of existing offline RL methods in our experiments: CQL (Kumar et al., 2020b), which penalizes erroneous Q-values during training, REM (Agarwal et al., 2020), which utilizes an ensemble of Q-functions, and BRAC (Wu et al., 2019), which applies a policy constraint. An overview of these methods is provided in Appendix E.

3 IMPLICIT REGULARIZATION IN DEEP RL VIA TD-LEARNING

While the "deadly-triad" (Sutton & Barto, 2018) suggests that training value function approximators with bootstrapping can lead to divergence, modern deep RL algorithms have been able to successfully combine these properties (van Hasselt et al., 2018). However, making too many TD updates to the Q-function in offline deep RL is known to sometimes lead to performance degradation and unlearning, even for otherwise effective modern algorithms (Fu et al., 2019; Fedus et al., 2020;

Figure 1: Feature dot-products $\phi(\mathbf{s}, \mathbf{a})^\top \phi(\mathbf{s}', \mathbf{a}')$ increase during training when backing up from *out-of-sample* but in-distribution actions (**TD-learning**: left, **Q-learning**: right), though the average Q-value converges and stays relatively constant. Using only seen state-action pairs for backups (**offline SARSA**) or not performing Bellman backups (i.e., **supervised regression**) avoids this issue, with stable and relatively low dot products. *Left*: TD-learning with high feature dot products eventually destabilizes and produces incorrect Q-values, *Right*: DQN attains extremely large feature dot products, despite a relatively stable trend in Q-values.

Agarwal et al., 2020; Kumar et al., 2021). Such unlearning is not typically observed when training overparameterized models via supervised learning, so what about TD learning is responsible for it? We show that one possible explanation behind this pathology is the implicit regularization induced by minimizing TD error on a deep Q-network. Our theoretical results suggest that this implicit regularization "aliases" the representations of state-action pairs that appear in a Bellman backup, and this aliasing is exacerbated when utilizing unseen state-action pairs for the Bellman backup. Empirically, this typically manifests as "co-adapted" (similar) features for consecutive state-action tuples, even with specialized TD-learning algorithms that account for distributional shift. Highly co-adapted features in turn lead to poor solutions as we will theoretically and empirically show. We first provide empirical evidence of the existence of this co-adaptation phenomenon in Section 3.1 (additional evidence in Appendix A.1) and then theoretically characterize the implicit regularization in TD learning, and discuss how it can explain the co-adaptation phenomenon in Section 3.2.

3.1 FEATURE CO-ADAPTATION AND HOW IT RELATES TO IMPLICIT REGULARIZATION

In this section, we empirically identify a *feature co-adaptation* phenomenon that appears when training value functions via bootstrapping, where the feature representations of consecutive state-action pairs become excessively similar as measured by their dot product $\phi(\mathbf{s}, \mathbf{a})^\top \phi(\mathbf{s}', \mathbf{a}')$. Feature co-adaptation appears even when there is no explicit affinity to increase feature similarity.

Experimental setup. To empirically observe feature co-adaptation, we ran supervised regression and three variants of approximate dynamic programming (ADP) on an offline dataset consisting of 1% of uniformly-sampled data from the replay buffer of DQN on two Atari games, previously used in Agarwal et al. (2020). First, for comparison, we trained a Q-function via **supervised regression** to Monte-Carlo (MC) return estimates on the offline dataset to estimate the value of the behavior policy. Then, we trained variants of ADP which differ in the selection procedure for the action $\mathbf{a}'$ that appears in the target value in $\mathcal{L}_{\mathrm{TD}}(\theta)$ (Equation 1). The **offline SARSA** variant aims to estimate the value of the behavior policy, Q^{π_β}, and sets $\mathbf{a}'$ to the actual action observed at the next time step in the dataset, such that $(\mathbf{s}', \mathbf{a}') \in \mathcal{D}$. The **TD-learning** variant also aims to estimate the value of the behavior policy, but utilizes an action $\mathbf{a}'$ sampled from the learned behavior policy π_β, $\mathbf{a}' \sim \pi_\beta(\cdot|\mathbf{s}')$. We also train **Q-learning**, which chooses the action $\mathbf{a}'$ to maximize the learned Q-function. While Q-learning learns a different Q-function, we can still compare the relative stability of these methods to gain intuition about the learning dynamics. In addition to feature dot products $\phi(\mathbf{s}, \mathbf{a})^\top \phi(\mathbf{s}', \mathbf{a}')$, we also track the average prediction of the Q-network over the dataset to measure whether the predictions diverge or are stable in expectation.

Observing feature co-adaptation empirically. As shown in Figure 1 (right), the average dot product (top row) between features at consecutive state-action tuples continuously increases for both Q-learning and TD-learning (after enough gradient steps), whereas it flatlines and converges to a small value for supervised regression. We might at first think that this is simply a case of Q-learning failing to converge. However, the bottom row shows that the average Q-values do in fact converge

to a stable value. Despite this, the optimizer drives the network towards higher feature dot products. There is no explicit term in the TD error objective that encourages this behavior, indicating the presence of some implicit regularization phenomenon. This *implicit* preference towards maximizing the dot products of features at consecutive state-action tuples is what we call "feature co-adaptation."

When does feature co-adaptation emerge? Observe in Figure 1 (right) that the feature dot products for offline SARSA converge quickly and are relatively flat, similarly to supervised regression. This indicates that utilizing a bootstrapped update alone is not responsible for the increasing dot-products and instability, because while offline SARSA uses backups, it behaves similarly to supervised MC regression. Unlike offline SARSA, feature co-adaptation emerges for TD-learning, which is surprising as TD-learning also aims to estimate the value of the behavior policy, and hence should match offline SARSA in expectation. The key difference is that while offline SARSA always utilizes actions $\mathbf{a}'$ observed in the training dataset for the backup, TD-learning may utilize potentially unseen actions $\mathbf{a}'$ in the backup, even though these actions $\mathbf{a}' \sim \pi_\beta(\cdot|\mathbf{s}')$ are *within* the distribution of the data-generating policy. This suggests that utilizing **out-of-sample** actions, even when they are not out-of-distribution, in the Bellman backup critically alters the learning dynamics. This finding is absent from literature in offline RL which primarily focuses on the impact of out-of-distribution actions (Levine et al., 2020), but not out-of-sample actions. The theoretical model developed in Section 3.2 will provide an explanation for this observation with a discussion about how feature co-adaption caused due to out-of-sample actions can be detrimental in offline RL.

3.2 THEORETICALLY CHARACTERIZING IMPLICIT REGULARIZATION IN TD-LEARNING

Why does feature co-adaptation emerge in TD-learning and what do *out-of-sample* actions have to do with it? To answer this question, we theoretically characterize the implicit regularization effects in TD-learning. We analyze the learning dynamics of TD learning in the overparameterized regime, where there are many different parameter vectors θ that fully minimize the training set temporal difference error. When training an overparameterized $f_\theta(\mathbf{x})$ via supervised regression using the squared loss, many different values of θ will satisfy $L(\theta) = 0$ on the training set due to overparameterization, but Blanc et al. (2020) argue that the dynamics of noisy SGD will result in only those fixed points to be stable that additionally satisfy $\nabla_\theta R(\theta^*) = 0$, for a particular *implicit* regularizer $R(\theta)$. The noisy gradient updates analyzed in this model have the form:

$$\theta_{k+1} \leftarrow \theta_k - \eta\nabla_\theta L(\theta) + \eta\varepsilon_k, \ \ \varepsilon_k \sim \mathcal{N}(0, M), \tag{2}$$

and Blanc et al. (2020); Damian et al. (2021) show that when the regression targets are corrupted with $\mathcal{N}(0,1)$ label noise, then $M = \sum_{i=1}^{|\mathcal{D}|} \nabla_\theta f_\theta(\mathbf{x}_i)\nabla_\theta f_\theta(\mathbf{x}_i)^\top$ and the induced implicit regularizer is given by $R(\theta) = \eta \sum_i^{|\mathcal{D}|} ||\nabla_\theta f_\theta(\mathbf{x}_i)||_2^2$. Any solution θ^* found by Equation 2 must satisfy $\nabla_\theta R(\theta^*) = 0$. This model corroborates empirical findings (Mulayoff & Michaeli, 2020) about the solutions found by SGD with deep nets, which motivates our use of this framework. Following this framework, we analyze the fixed points of noisy TD-learning. We consider noisy pseudo-gradient TD updates with a general noise covariance M:

$$\theta_{k+1} = \theta_k - \eta\underbrace{\left(\sum_i \nabla_\theta Q(\mathbf{s}_i, \mathbf{a}_i)\left(Q_\theta(\mathbf{s}_i, \mathbf{a}_i) - (r_i + \gamma Q_\theta(\mathbf{s}_i', \mathbf{a}_i'))\right)\right)}_{:=g(\theta)} + \eta\varepsilon_k, \ \ \varepsilon_k \sim \mathcal{N}(0, M) \tag{3}$$

We use a deterministic policy $\mathbf{a}_i' = \pi(\mathbf{s}_i')$ to simplify exposition. Following Blanc et al. (2020), we can set the noise model M as $M = \sum_i \nabla_\theta Q(\mathbf{s}_i, \mathbf{a}_i)\nabla_\theta Q(\mathbf{s}_i, \mathbf{a}_i)^\top$, or utilize a different choice of M, but we will derive the general form first. Let θ^* denote a stationary point of the training TD error, such that the pseudo-gradient $g(\theta^*) = 0$. Further, we denote to the derivative of $g(\theta)$ w.r.t. θ as matrix $G(\theta)$ and refer to as the *pseudo-Hessian*: although $G(\theta)$ is not actually the second derivative of any well-defined objective, since TD updates are not proper gradient updates, as we will see it will play a similar role to the Hessian in gradient descent. For brevity, define $G = G(\theta^*)$, $g = g(\theta^*)$ and $\nabla G = \nabla_\theta G(\theta^*)$. Also, $\lambda_i(P)$ denotes the i-th eigenvalue of matrix P.

Assumptions. To simplify analysis, we assume that matrices G and M (i.e., the noise covariance matrix) span the same n-dimensional basis in d-dimensional space, where d is the number of parameters and n is the number of datapoints, and $n \ll d$ due to overparameterization. We also require θ^* to satisfy a technical criterion that requires approximate alignment between the eigenspaces of G and the gradient of the Q-function, without which noisy TD may not be stable at θ^*. We summarize all the assumptions in Appendix C, and first present our regularizer.

Theorem 3.1 (Implicit regularizer at TD fixed points). *Under the assumptions so far, a fixed point of TD-learning, θ^*, where $Q_{\theta^*}(\mathbf{s}_i, \mathbf{a}_i) = r_i + \gamma Q_{\theta^*}(\mathbf{s}'_i, \mathbf{a}'_i)$ for every $(\mathbf{s}_i, \mathbf{a}_i, \mathbf{s}'_i) \in \mathcal{D}$ is stableif: (1) it satisfies $\mathrm{Re}(\lambda_i(G)) \geq 0, \forall i$ and $\mathrm{Re}(\lambda_i(G)) > 0$ if $|\mathrm{Imag}(\lambda_i(G))| > 0$, and (2) θ^* is the stationary point of the induced implicit regularizer,*

$$R_{\mathrm{TD}}(\theta) = \eta \sum_{i=1}^{|\mathcal{D}|} \nabla Q_\theta(\mathbf{s}_i, \mathbf{a}_i)^\top \Sigma_M^* \nabla Q_\theta(\mathbf{s}_i, \mathbf{a}_i) - \eta\gamma \sum_{i=1}^{|\mathcal{D}|} \mathrm{trace}\left(\Sigma_M^* \nabla Q_\theta(\mathbf{s}_i, \mathbf{a}_i) \left[\left[\nabla Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i)^\top\right]\right]\right), \quad (4)$$

where $(\mathbf{s}_i, \mathbf{a}_i)$ and $(\mathbf{s}'_i, \mathbf{a}'_i)$ denote state-action pairs that appear together in a Bellman update, $[[\square]]$ denotes the stop-gradient function, which does not pass partial derivatives w.r.t. θ into $\square$. Σ_M^* is the fixed point of the discrete Lyapunov equation: $\Sigma_M^* := (I - \eta G)\Sigma_M^*(I - \eta G)^\top + \eta^2 M$.

A proof of Theorem 3.1 is provided in Appendix C. Next, we explain the intuition behind this result and provide a proof sketch. To derive the induced implicit regularizer for a stable fixed point θ^* of TD error, we study the learning dynamics of noisy TD learning (Equation 3) initialized at θ^*, and derive conditions under which this noisy update would stay close to θ^* with multiple updates. This gives rise to the two conditions shown in Theorem 3.1 which can be understood as controlling stability in mutually exclusive directions in the parameter space. If condition **(1)** is not satisfied, then even under-parameterized TD will diverge away from θ^*, since $I - \eta G$ would be a non-contraction as the spectral radius, $\rho(I - \eta G) \geq 1$ in that case. Thus, $\theta_k - \theta^*$ will grow or not decrease in some direction. When **(1)** is satisfied for all directions in the parameter space, there are still directions where both the real and imaginary parts of the eigenvalue are 0 due to overparameterization. In such directions, learning is governed by the projection of the noise under the third-order derivative ∇G, which appears in the Taylor expansion of $\theta_k - \theta^*$ around the point θ^*:

$$\theta_{k+1} = \theta_k - \eta\left(g + G(\theta_k - \theta^*) + \frac{1}{2}\nabla G[\theta_k - \theta^*, \theta_k - \theta^*]\right) + \varepsilon_k, \ \ \varepsilon_k \sim \mathcal{N}(0, M) \quad (5)$$

$$\implies \nu_{k+1} = (I - \eta G)\nu_k - \frac{\eta}{2}\nabla G[\nu_k, \nu_k] + \varepsilon_k, \quad (6)$$

where we define $\nu_k := \theta_k - \theta^*$. θ^* is stable if it is a stationary point of the implicit regularizer R_{TD} (condition **(2)**), which ensures that total noise (i.e., accumulated ε_k over iterations k) does not lead to a large deviation in ν_k.

Interpretation of Theorem 3.1. While the choice of the noise model M will change the form of the implicit regularizer, of course, in practice, the form of M is not known. We can consider other choices of M for interpretation, but Theorem 3.1 can be easy to qualitatively interpret for M such that $\Sigma_M^* = I$. In this case, we find that the implicit preference towards local minima of $R_{\mathrm{TD}}(\theta)$ can explain feature co-adaptation. In this case, the regularizer takes a simpler form: $R_{\mathrm{TD}}(\theta) := \sum_i ||\nabla Q_\theta(\mathbf{s}_i, \mathbf{a}_i)||_2^2 - \gamma\nabla Q_\theta(\mathbf{s}_i, \mathbf{a}_i)\nabla[[Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i)]]$. The first term is equal to the squared per-datapoint gradient norm, which is same as the implicit regularizer in supervised learning obtained by Blanc et al. (2020); Damian et al. (2021) with label noise. However, $R_{\mathrm{TD}}(\theta)$ additionally includes a second term that is equal to the dot product of the gradient of the Q-function at the current and next states, $\nabla_\theta Q_\theta(\mathbf{s}_i, \mathbf{a}_i)^\top \nabla_\theta Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i)$, and thus this term is effectively *maximized*. When restricted to the last-layer parameters of a neural network, this term is equal to the dot product of the features at consecutive state-action tuples: $\sum_i \nabla_\theta Q_\theta(\mathbf{s}_i, \mathbf{a}_i)^\top \nabla_\theta Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i) = \sum_i \phi(\mathbf{s}_i, \mathbf{a}_i)^\top \phi(\mathbf{s}'_i, \mathbf{a}'_i)$. The tendency to maximize this quantity to attain a local minimizer of the implicit regularizer corroborates the empirical findings of increased dot product in Section 3.1.

Explaining the difference between utilizing seen and unseen actions in the backup. If all state-action pairs $(\mathbf{s}'_i, \mathbf{a}'_i)$ appearing on the right-hand-side of the Bellman update also appear in the dataset $\mathcal{D}$, as in the case of offline SARSA (Figure 1), the preference to increase dot products will be balanced by the affinity to reduce gradient norm (first term of $R_{\mathrm{TD}}(\theta)$ when $\Sigma_M^* = I$): for example, when $(\mathbf{s}'_i, \mathbf{a}'_i)$ are permutations of $(\mathbf{s}_i, \mathbf{a}_i)$, R_{TD} is lower bounded by $(1 - \gamma)\sum_i ||\nabla_\theta Q_\theta(\mathbf{x}_i)||_2^2$ and hence minimizing $R_{\mathrm{TD}}(\theta)$ would minimize the feature norm instead of maximizing dot products. Note that this also corresponds to the implicit regularizer we would obtain when training Q-functions via supervised learning and hence, our analysis would predict that offline SARSA with in-sample actions (i.e., when $(\mathbf{s}', \mathbf{a}') \in \mathcal{D}$) would behave similarly to supervised regression.

However, the regularizer behaves very differently when unseen state-action pairs $(\mathbf{s}'_i, \mathbf{a}'_i)$ appear only on the right-hand-side of the backup. This happens with any algorithm where $\mathbf{a}'$ is not the dataset action, which is the case for all deep RL algorithms that compute target values by selecting

Figure 2: Even when current offline RL algorithms are initialized at a high-performing checkpoint that attains small feature dot products, feature dot products increase with further training and the performance degrades.

$\mathbf{a}'$ according to the current policy. In this case, we expect the dot product of gradients at $(\mathbf{s}, \mathbf{a})$ and $(\mathbf{s}', \mathbf{a}')$ to be large at any attractive fixed point, since this minimizes $R_{\mathrm{TD}}(\theta)$. This is precisely a form of co-adaptation: *gradients at out-of-sample state-action tuples are highly similar to gradients at observed state-action pairs measured by the dot product*. This observation is also supported by the analysis in Section 3.1. Finally, note that the choice of M is a modelling assumption, and to derive our explicit regularizer, later in the paper, we will make a simplifying choice of M, though we empirically verify that a different M also performs well (Appendix A.4).

Why implicit regularization and hence feature co-adaptation can be detrimental to policy performance? To answer this question, we present theoretical and empirical evidence that depicts the adverse effects of this implicit regularizer in TD-learning. **Empirically,** we ran two algorithms, DQN and CQL initialized from a high-performing Q-function checkpoint obtained using DR3 (Section 4), which attains relatively small feature dot products (i.e., the second term of $R_{\mathrm{TD}}(\theta)$ is small). Our goal is to see if TD updates starting from such a "good" initialization still stay around it or diverge to poorer solutions. Our theoretical analysis in Section 3.2 would predict that TD learning would destabilize from such a solution since it would not be a stable fixed point. Indeed, as shown in Figure 2, the policy starts to degrade right from the beginning, and the the dot-product similarities start to increase. This even happens with CQL, which explicitly corrects for any distributional shift confounds, implying that the performance drop cannot be directly explained by the typical out-of-distribution action explanations. To investigate the reasons behind this drop, we also measured the overall training error for these algorithms (i.e., TD error for DQN and TD error + CQL regularizer for CQL) and find in Figure 2 that the loss values generally exhibit a non-increasing trend for both CQL and DQN. In particular, the values attained by TD error are small and do not increase much with more training significantly, indicating that the preference to increase dot products is a consequence of an implicit phenomenon and is not explained by smaller values of the training loss.

To motivate why co-adapted features can lead to poor performance in TD-learning, we study the convergence of linear TD-learning on co-adapted features. Our theoretical result characterizes a lower bound on the feature dot products in terms of the feature norms for state-action pairs in the dataset $\mathcal{D}$, which if satisfied, will inhibit convergence:

Proposition 3.2 (TD-learning on co-adapted features). *Assume that the features $\Phi = [\phi(\mathbf{s}, \mathbf{a})]_{\mathbf{s}, \mathbf{a}}$ are used for linear TD-learning. Then, if $\sum_{\mathbf{s}, \mathbf{a}, \mathbf{s}' \in \mathcal{D}} \phi(\mathbf{s}, \mathbf{a})^\top \phi(\mathbf{s}', \mathbf{a}') \geq \frac{1}{\gamma} \sum_{\mathbf{s}, \mathbf{a} \in \mathcal{D}} \phi(\mathbf{s}, \mathbf{a})^\top \phi(\mathbf{s}, \mathbf{a})$, linear TD-learning using features Φ will not converge.*

A proof of Proposition 3.2 is provided in Appendix D and it relies on a stability analysis of linear TD. While features change during training for TD-learning with neural networks, and arguably linear TD is a simple model to study consequences of co-adapted features, even in this simple linear setting, Proposition 3.2 indicates that TD-learning may be non-convergent as a result of co-adaptation.

4 DR3: EXPLICIT REGULARIZATION FOR DEEP TD-LEARNING

Since the implicit regularization effects in TD-learning can lead to feature co-adaptation, which in turn is correlated with poor performance, can we instead derive an *explicit* regularizer to alleviate this issue? Inspired by the analysis in the previous section, we will propose an *explicit* regularizer that attempts to counteract the second term in Equation 4, which would otherwise lead to co-adaptation and poor representations. The *explicit* regularizer that offsets the difference between the two implicit regularizers is given by: $\Delta(\theta) = \sum_i \mathrm{trace}\left[\Sigma_M^{*\top} \nabla_\theta Q_\theta(\mathbf{s}_i, \mathbf{a}_i) \nabla_\theta Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i)^\top\right]$, which represents the second term of $R_{\mathrm{TD}}(\theta)$. Note that we drop the stop gradient on $Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i)$ in $\Delta(\theta)$ as it performs slightly better in practice (Table A.1), although as shown in that Table, the version with

the stop gradient also significantly improves over the base method. The first term of $R_{\mathrm{TD}}(\theta)$ corresponds to the regularizer from supervised learning. Our proposed method, DR3, simply combines approximations to $\Delta(\theta)$ with various offline RL algorithms. For any offline RL algorithm, ALG, with objective $\mathcal{L}_{\mathrm{ALG}}(\theta)$, the training objective with DR3 is given by: $\mathcal{L}(\theta) := \mathcal{L}_{\mathrm{ALG}}(\theta) + c_0 \Delta(\theta)$, where c_0 is the DR3 coefficient. See Appendix E.3 for details on how we tune c_0 in this paper.

Practical version of DR3. In order to practically instantiate DR3, we need to choose a particular noise model M. In general, it is not possible to know beforehand the "correct" choice of M (Equation 3), even in supervised learning, as this is a complicated function of the data distribution, neural network architecture and initialization. Therefore, we instantiate DR3 with two heuristic choices of M: **(i)** M induced by label noise studied in prior work for supervised learning and for which we need to run computationally heavy fixed-point computation for M, and **(ii)** a simpler alternative that sets $\Sigma_M^* = I$. We find that both of these variants generally perform equally well empirically (Figure 6), and so we utilize **(ii)** in practice due to low computational costs. Additionally, because computing and backpropagating through per-example gradient dot products is slow, we instead approximate $\Delta(\theta)$ with the contribution only from the last layer parameters (*i.e.*, $\sum_i \nabla_{\mathbf{w}} Q_\theta(\mathbf{s}_i, \mathbf{a}_i)^\top \nabla_{\mathbf{w}} Q_\theta(\mathbf{s}_i', \mathbf{a}_i')$), similarly to tractable Bayesian neural nets. As shown in Appendix A.4, the practical version of DR3 performs similarly to the theoretically derived version.

$$\textbf{Explicit DR3 regularizer}: \qquad \overline{\mathcal{R}}_{\exp}(\theta) = \sum_{i \in \mathcal{D}} \phi(\mathbf{s}_i, \mathbf{a}_i)^\top \phi(\mathbf{s}_i', \mathbf{a}_i'). \tag{7}$$

5 RELATED WORK

Prior analyses of learning dynamics in RL has focused primarily on analyzing error propagation in tabular or linear settings (*e.g.*, Chen & Jiang, 2019; Duan et al., 2020; Xie & Jiang, 2020; Wang et al., 2021a;b; Farahmand et al., 2010; De Farias, 2002), understanding instabilities in deep RL (Achiam et al., 2019; Bengio et al., 2020; Kumar et al., 2020a; Van Hasselt et al., 2018) and deriving weighted TD updates that enjoy convergence guarantees (Maei et al., 2009; Mahmood et al., 2015; Sutton et al., 2016), but these methods do not reason about implicit regularization or any form of representation learning. Ghosh & Bellemare (2020) focuses on understanding the stability of TD-learning in underparameterized linear settings, whereas our focus is on the overparameterized setting, when optimizing TD error and learning representations via SGD. Kumar et al. (2021) studies the learning dynamics of Q-learning and observes that the rank of the feature matrix, Φ, drops during training. While this observation is related, our analysis characterizes the implicit preference of learning towards feature co-adaptation (Theorem 3.1) on out-of-sample actions as the primary culprit for aliasing. Additionally, utilizing DR3 not only outperforms the srank(Φ) penalty in Kumar et al. (2021) by more than **100%**, but it also alleviates rank collapse, with no apparent term that explicitly increases rank. Somewhat related to DR3, Durugkar & Stone (2018); Pohlen et al. (2018) heuristically constrain gradients of TD to prevent changes in target Q-values to prevent divergence. Contrary to such heuristic approaches, DR3 is inspired from a theoretical model of implicit regularization, and does not prevent changes in target values, but rather reduces feature dot products.

6 EXPERIMENTAL EVALUATION OF DR3

Our experiments aim to evaluate the extent to which DR3 improves performance in offline RL in practice, and to study its effect on prior observations of rank collapse and how it compares to the more costly regularizer suggested by our analysis, which requires estimating $\Sigma_M^\star$. To this end, we investigate if DR3 improves offline RL performance and stability on three offline RL benchmarks: Atari 2600 games with discrete actions (Agarwal et al., 2020), continuous control tasks from D4RL (Fu et al., 2020), and image-based robotic manipulation tasks (Singh et al., 2020).

Following prior work (Fu et al., 2020; Gulcehre et al., 2020), we evaluate DR3 in terms of final offline RL performance after a given number of iterations. Additionally, we report *training stability*, which is important in practice as offline RL does not admit cheap validation of trained policies for model selection. To evaluate stability, we train for a large number of gradient steps (2-3x longer than prior work) and either report the **average performance** over the course of training or the final performance at the end of training. We expect that a stable method that does not unlearn with more gradient steps, should have better average performance, as compared to a method that attains good peak performance but degrades with more training. See Appendix E for further details.

Table 1: IQM normalized average performance (training stability) across 17 games, with 95% CIs in parenthesis, after 6.5M gradient steps for the 1% setting and 12.5M gradient steps for the 5%, 10% settings. Individual performances reported in Tables F.4-F.10. DR3 improves the stability over both CQL and REM.

Data	CQL	CQL + DR3	REM	REM + DR3
1%	43.7 (39.6, 48.6)	**56.9** (52.5, 61.2)	4.0 (3.3, 4.8)	**16.5** (14.5, 18.6)
5%	78.1 (74.5, 82.4)	**105.7** (101.9, 110.9)	25.9 (23.4, 28.8)	**60.2** (55.8, 65.1)
10%	59.3 (56.4, 61.9)	**65.8** (63.3, 68.3)	53.3 (51.4, 55.3)	**73.8** (69.3, 78)

Figure 3: **Performance of DR3 + COG** on two manipulation tasks using only 5% and 25% of the data used by Singh et al. (2020) to make these more challenging. COG + DR3 outperforms COG in training and attains higher average and final performance.

Figure 4: **Normalized performance across 17 Atari games for REM + DR3 (top), CQL + DR3 (bottom)**. x-axis represents *gradient steps*; no new data is collected. While naïve REM suffers from a degradation in performance with more training, REM + DR3 not only remains generally stable with more training, but also attains higher final performance. CQL + DR3 attains higher performance than CQL. We report IQM with 95% stratified bootstrap CIs (Agarwal et al., 2021).

Offline RL on Atari 2600 games. We compare DR3 to prior offline RL methods on a set of offline Atari datasets of varying sizes and quality, akin to Agarwal et al. (2020); Kumar et al. (2021). We evaluated on three datasets: **(1)** 1% and 5% samples drawn uniformly at random from DQN replay; **(2)** a dataset with more suboptimal data consisting of the first 10% samples observed by an online DQN. Following Agarwal et al. (2021), we report the interquartile mean (IQM) normalized scores across 17 games over the course of training in Figure 4 and report the IQM average performance in Table 1. Observe that combining DR3 with modern offline RL methods (CQL, REM) attains the best final and average performance across the 17 Atari games tested on, directly improving upon prior methods across all the datasets. When DR3 is used in conjunction with REM, it prevents unlearning and performance degradation with more training. CQL + DR3 improves by **20%** over CQL on final performance and attains **25%** better average performance. We also compare DR3 to the srank(Φ) penalty proposed to counter rank collapse (Kumar et al., 2021). Directly taking median normalized score improvements reported by Kumar et al. (2021), CQL + DR3 improves by over **2x** (31.5%) over naïve CQL relative to the srank penalty (14.1%), indicating DR3's efficacy.

Offline RL on robotic manipulation from images.
Next, we aim to evaluate the efficacy of DR3 on two image-based robotic manipulation tasks (Singh et al., 2020) (visualized on the right) that require composition of skills (e.g., opening a drawer, closing a drawer, picking an obstructive object, placing an object, etc.) over

extended horizons using only a sparse 0-1 reward. As shown in Figure 3, combining DR3 with COG not only improves over COG, but also learns faster and attains a better average performance.

Offline RL on D4RL tasks. Finally, we evaluate DR3 in conjunction with CQL on the harder D4RL (Fu et al., 2020) domains (antmaze, kitchen domains). To assess if DR3 is stable and able to prevent unlearning that eventually appears in CQL, we trained CQL+DR3 for **6x** longer: 2M steps with 3x higher learning rate. Observe in Table 2, that CQL + DR3 outperforms CQL, in some cases substantially, indicating the ability to prevent unlearning that happens for more gradient steps with DR3. Further, we also compare the effect of adding DR3 to a policy constraint method, BRAC (Wu

Figure 5: **Trend of effective rank,** srank(Φ) of features Φ learned by the Q-function when trained with TD error (red, "Without DR3") and with TD error + DR3 (blue, "With DR3") on three Atari games using the 5% dataset. Note that DR3 alleviates rank collapse observed by Kumar et al. (2021), without explicitly aiming to. Effective rank measures the number of directions with significant singular values (Appendix A.3).

Table 2: **Performance of CQL, CQL + DR3 after 2M gradient steps with a learning rate of 3e-4** for the Q-function averaged over 4 seeds. This is training for **6x** longer compared to CQL defaults. Observe that CQL + DR3 outperforms CQL at 2M steps, indicating is efficacy in inducing stability.

D4RL (-v0) Task	CQL	CQL + DR3
`kitchen-mixed`	14.6 ± 20.5	$\mathbf{37.0 \pm 8.0}$
`kitchen-partial`	29.6 ± 19.6	$\mathbf{43.5 \pm 1.9}$
`kitchen-complete`	22.3 ± 17.5	24.8 ± 15.3
`antmaze-med-diverse`	0.7 ± 0.1	$\mathbf{0.9 \pm 0.1}$
`antmaze-med-play`	0.5 ± 0.4	0.4 ± 0.3
`antmaze-lar-diverse`	0.1 ± 0.0	$\mathbf{0.3 \pm 0.16}$
`antmaze-lar-play`	0.06 ± 0.09	0.1 ± 0.01

et al., 2019). DR3 applied on BRAC improves final median normalized score performance by **13.8** and stability by **8.1** across 15 MuJoCo tasks. Numbers for BRAC can be found in Table F.2.

To summarize, these results indicate that DR3 is a versatile explicit regularizer that improves performance and stability of a wide range of offline RL methods, including conservative methods (e.g, CQL, COG), policy constraint methods (e.g., BRAC) and ensemble-based methods (e.g., REM).

DR3 allows utilizing full capacity as measured via feature ranks. Prior work (Kumar et al., 2021) has shown that implicit regularization can lead to a rank collapse issue in TD-learning, preventing Q-networks from using full capacity. To see if DR3 addresses the rank collapse issue, we follow Kumar et al. (2021) and plot the effective rank of learned features with DR3 in Figure 5. While the value of the effective rank decreases during training with naïve bootstrapping, we find that DR3 addresses this issue allowing the Q-function to use its complete representational capacity, despite no explicit term encouraging this. Additionally, we test the robustness/sensitivity of each layer in the learned Q-network to re-initialization (Zhang et al., 2019) during training and find that DR3 alters the representations trained with TD to behave similarly to supervised learning (Figure A.2).

Comparing explicit regularizers for different choices of noise covariance M. Finally, we investigate the behavior of different implicit regularizers derived via two choices of M in Equation 4 and the corresponding explicit regularizers. While the explicit regularizer we use in practice is a simplifying choice that works well, another choice of M is the covariance matrix induced by label noise, which requires explicit computation of Σ_M^*. Observe in Figure 6 that the explicit regularizers derived for both the choices of M are equally effective. This justifies utilizing our simplified, heuristic choice of setting $\Sigma_M^* = I$ in practice. Results on five Atari games are shown in Appendix A.4.

Figure 6: Comparison of the DR3 regularizer corresponding to our simplifying choice of M and M induced by label noise. Note that both of these penalties when applied over CQL improve performance, and generally perform similarly.

7 DISCUSSION

We characterized the implicit preference of TD-learning towards solutions that maximally co-adapt gradients (or features) at consecutive state-action tuples that appear in Bellman backup. This regularization effect is exacerbated when out-of-sample state-action samples are used for the Bellman backup and it can lead to poor policy performance. Inspired by the theory, we propose a practical explicit regularizer, DR3 that aims to counteracts this implicit regularizer. DR3 yields substantial improvements in stability and performance on a wide range of offline RL problems. We believe that understanding the learning dynamics of deep Q-learning and the induced implicit regularization will lead to more robust and stable deep RL algorithms. Furthermore, this understanding can help us to predict the instability issues in value-based RL methods in advance, which can inspire cross-validation and model selection strategies, an important, open challenge in offline RL, for which existing off-policy evaluation techniques are not practically sufficient (Fu et al., 2021). We also note that our analysis does not consider the online RL setting with non-stationary data distributions, and extending our theory and DR3 to online RL is an interesting avenue for future work.

REPRODUCIBILITY STATEMENT

To ensure reproducibility in our empirical results, we provide complete experimental details regarding methods and hyper-parameters used in the Appendix E. Additionally, we follow the recommendations of Agarwal et al. (2021) for reliable evaluation in deep RL and report the statistical uncertainty in reported results including aggregate performance metrics. We provide individual scores in Appendix F and we will release scores for individual runs as well as open-source our code. For theoretical results, we provide explanations of all the assumptions and a complete proof of the claims in Appendix C.

REFERENCES

Joshua Achiam, Ethan Knight, and Pieter Abbeel. Towards characterizing divergence in deep q-learning. *arXiv preprint arXiv:1903.08894*, 2019.

Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An optimistic perspective on offline reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2020.

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems*, 2021.

Sanjeev Arora, Nadav Cohen, and Elad Hazan. On the optimization of deep networks: Implicit acceleration by overparameterization. *arXiv preprint arXiv:1802.06509*, 2018.

Emmanuel Bengio, Joelle Pineau, and Doina Precup. Interference and generalization in temporal difference learning. *arXiv preprint arXiv:2003.06350*, 2020.

Guy Blanc, Neha Gupta, Gregory Valiant, and Paul Valiant. Implicit regularization for deep neural networks driven by an ornstein-uhlenbeck like process. In *Conference on learning theory*, pp. 483–513. PMLR, 2020.

Niladri S Chatterji, Behnam Neyshabur, and Hanie Sedghi. The intriguing role of module criticality in the generalization of deep networks. *arXiv preprint arXiv:1912.00528*, 2019.

Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. *ICML*, 2019.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. *arXiv preprint arXiv:2011.10566*, 2020.

Alex Damian, Tengyu Ma, and Jason Lee. Label noise sgd provably prefers flat global minimizers. *arXiv preprint arXiv:2106.06530*, 2021.

Daniela Pucci De Farias. *The linear programming approach to approximate dynamic programming: Theory and application*. PhD thesis, 2002.

Yaqi Duan, Zeyu Jia, and Mengdi Wang. Minimax-optimal off-policy evaluation with linear function approximation. In *International Conference on Machine Learning*, pp. 2701–2709. PMLR, 2020.

Ishan Durugkar and Peter Stone. Td learning with constrained gradients. 2018.

Amir-massoud Farahmand, Csaba Szepesvári, and Rémi Munos. Error propagation for approximate policy and value iteration. In *Advances in Neural Information Processing Systems (NIPS)*, 2010.

William Fedus, Prajit Ramachandran, Rishabh Agarwal, Yoshua Bengio, Hugo Larochelle, Mark Rowland, and Will Dabney. Revisiting fundamentals of experience replay. *arXiv preprint arXiv:2007.06700*, 2020.

Justin Fu, Aviral Kumar, Matthew Soh, and Sergey Levine. Diagnosing bottlenecks in deep Q-learning algorithms. *arXiv preprint arXiv:1902.10250*, 2019.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

Justin Fu, Mohammad Norouzi, Ofir Nachum, George Tucker, ziyu wang, Alexander Novikov, Mengjiao Yang, Michael R Zhang, Yutian Chen, Aviral Kumar, Cosmin Paduraru, Sergey Levine, and Thomas Paine. Benchmarks for deep off-policy evaluation. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=kWSeGEeHvF8.

Dibya Ghosh and Marc G Bellemare. Representations for stable off-policy reinforcement learning. *arXiv preprint arXiv:2007.05520*, 2020.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

Caglar Gulcehre, Ziyu Wang, Alexander Novikov, Tom Le Paine, Sergio Gómez Colmenarejo, Konrad Zolna, Rishabh Agarwal, Josh Merel, Daniel Mankowitz, Cosmin Paduraru, et al. Rl unplugged: Benchmarks for offline reinforcement learning. 2020.

Suriya Gunasekar, Blake E Woodworth, Srinadh Bhojanapalli, Behnam Neyshabur, and Nati Srebro. Implicit regularization in matrix factorization. In *Advances in Neural Information Processing Systems*, pp. 6151–6159, 2017.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *CoRR*, abs/1801.01290, 2018. URL http://arxiv.org/abs/1801.01290.

Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in Neural Information Processing Systems 31*. 2018.

Aviral Kumar, Abhishek Gupta, and Sergey Levine. Discor: Corrective feedback in reinforcement learning via distribution correction. *arXiv preprint arXiv:2003.07305*, 2020a.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *arXiv preprint arXiv:2006.04779*, 2020b.

Aviral Kumar, Rishabh Agarwal, Dibya Ghosh, and Sergey Levine. Implicit under-parameterization inhibits data-efficient deep reinforcement learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=O9bnihsFfXU.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Hamid R. Maei, Csaba Szepesvári, Shalabh Bhatnagar, Doina Precup, David Silver, and Richard S. Sutton. Convergent temporal-difference learning with arbitrary smooth function approximation. In *Proceedings of the 22nd International Conference on Neural Information Processing Systems*, 2009.

A Rupam Mahmood, Huizhen Yu, Martha White, and Richard S Sutton. Emphatic temporal-difference learning. *arXiv preprint arXiv:1507.01569*, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, feb 2015. ISSN 0028-0836.

Rotem Mulayoff and Tomer Michaeli. Unique properties of flat minima in deep networks. In *International Conference on Machine Learning*, pp. 7108–7118. PMLR, 2020.

Tobias Pohlen, Bilal Piot, Todd Hester, Mohammad Gheshlaghi Azar, Dan Horgan, David Budden, Gabriel Barth-Maron, Hado Van Hasselt, John Quan, Mel Večerík, et al. Observe and look further: Achieving consistent performance on atari. *arXiv preprint arXiv:1805.11593*, 2018.

Martin L Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. John Wiley & Sons, Inc., 1994.

Avi Singh, Albert Yu, Jonathan Yang, Jesse Zhang, Aviral Kumar, and Sergey Levine. Cog: Connecting new skills to past experience with offline reinforcement learning. *arXiv preprint arXiv:2010.14500*, 2020.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. Second edition, 2018.

Richard S. Sutton, A. Rupam Mahmood, and Martha White. An emphatic approach to the problem of off-policy temporal-difference learning. *J. Mach. Learn. Res.*, 17(1):26032631, January 2016. ISSN 1532-4435.

Yuandong Tian, Lantao Yu, Xinlei Chen, and Surya Ganguli. Understanding self-supervised learning with dual deep networks. *arXiv preprint arXiv:2010.00578*, 2020.

Yuandong Tian, Xinlei Chen, and Surya Ganguli. Understanding self-supervised learning dynamics without contrastive pairs. *arXiv preprint arXiv:2102.06810*, 2021.

Hado van Hasselt, Yotam Doron, Florian Strub, Matteo Hessel, Nicolas Sonnerat, and Joseph Modayil. Deep reinforcement learning and the deadly triad. *ArXiv*, abs/1812.02648, 2018.

Hado Van Hasselt, Yotam Doron, Florian Strub, Matteo Hessel, Nicolas Sonnerat, and Joseph Modayil. Deep reinforcement learning and the deadly triad. *arXiv preprint arXiv:1812.02648*, 2018.

Ruosong Wang, Dean Foster, and Sham M. Kakade. What are the statistical limits of offline {rl} with linear function approximation? In *International Conference on Learning Representations*, 2021a. URL https://openreview.net/forum?id=30EvkP2aQLD.

Ruosong Wang, Yifan Wu, Ruslan Salakhutdinov, and Sham M Kakade. Instabilities of offline rl with pre-trained neural representation. *arXiv preprint arXiv:2103.04947*, 2021b.

Colin Wei, Jason Lee, Qiang Liu, and Tengyu Ma. Regularization matters: Generalization and optimization of neural nets vs their induced kernel. 2019.

Blake Woodworth, Suriya Gunasekar, Jason D Lee, Edward Moroshko, Pedro Savarese, Itay Golan, Daniel Soudry, and Nathan Srebro. Kernel and rich regimes in overparametrized models. *arXiv preprint arXiv:2002.09277*, 2020.

Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

Tengyang Xie and Nan Jiang. Q* approximation schemes for batch reinforcement learning: A eoretical comparison. 2020.

Andrea Zanette. Exponential lower bounds for batch reinforcement learning: Batch rl can be exponentially harder than online rl. *arXiv preprint arXiv:2012.08005*, 2020.

Chiyuan Zhang, Samy Bengio, and Yoram Singer. Are all layers created equal? *arXiv preprint arXiv:1902.01996*, 2019.

Appendices

A ADDITIONAL VISUALIZATIONS AND EXPERIMENTS FOR DR3

In this section, we provide visualizations and diagnostic experiments evaluating various aspects of feature co-adaptation and the DR3 regularizer. We first provide more empirical evidence showing the presence of feature co-adaptation in modern deep offline RL algorithms. We will also visualize DR3 inspired from the implicit regularizer term in TD-learning alleviates rank collapse discussed in Kumar et al. (2021). We will compare the efficacies of the explicit regularizer induced for different choices of the noise covariance matrix M (Equation 4), understand the effect of dropping the stop gradient term in ou practical regularizer and finally, perform diagnostic experiments visualizing if the Q-networks learned with DR3 resemble more like neural networks trained via supervised learning, measured in terms of sensitivity and robustness to layer reinitialization (Zhang et al., 2019).

A.1 MORE EMPIRICAL EVIDENCE OF FEATURE CO-ADAPTATION

In this section, we provide more empirical evidence demonstrating the existence of the feature co-adaptation issue in modern offline RL algorithms such as DQN and CQL. As shown below in Figure A.1, while the average dataset Q-value for both CQL and DQN exhibit a flatline trend, the dot product similarity for consecutive state-action tuples generally continues to increase throughout training and does not flatline. While DQN eventually diverges in Seaquest, the dot products increase with more gradient steps even before divergence starts to appear.

Figure A.1: **Demonstrating feature co-adaptation on five Atari games with standard offline DQN and CQL, averaged over 3 seeds.** Observe that the feature dot products continue to rise with more training for both CQL and DQN, indicating the presence of co-adaptation. On the other hand, the average Q-values exhibit a converged trend, except on Seaquest. Further, note that the dot products continue to increase for CQL even though CQL explicitly corrects for out-of-distribution action inputs.

A.2 LAYER-WISE STRUCTURE OF A Q-NETWORK TRAINED WITH DR3

To understand if DR3 indeed makes Q-networks behave as if they were trained via supervised learning, utilizing the empirical analysis tools from Zhang et al. (2019), we test the robustness/sensitivity of each layer in the learned network to re-initialization, while keeping the other layers fixed. This tests if a particular layer is *critical* to the predictions of the learned neural network and enables us to reason about generalization properties (Zhang et al., 2019; Chatterji et al., 2019). We ran CQL and REM and saved all the intermediate checkpoints. Then, as shown in Figure A.2, we first loaded a checkpoint (x-axis), and computed policy performance (shaded color; colorbar) by re-initializing a given layer (y-axis) of the network to its initialization value before training for the same run.

Note in Figure A.2, that while almost all layers are absolutely critical for the base CQL algorithm, utilizing DR3 substantially reduces sensitivity to the latter layers in the Q-network over the course of

Figure A.2: **CQL vs CQL + DR3 and REM vs REM + DR3.** Average robustness of the learned Q-function to re-initialization of all layers to different checkpoints over the course of training created based on the protocol from Zhang et al. (2019). The colors in the heatmap indicate performance of the reinitialized checkpoint, normalized w.r.t. the checkpoint without any change to layers. Note that while CQL and REM are more sensitive (i.e., less robust) to reinitialization of all the layers especially the last layer, CQL + DR3 and REM + DR3 behave closer to supervised learning, in the sense that they are more robust to reinitialization of layers of the network, especially the last layer.

training. This is similar to what Zhang et al. (2019) observed for supervised learning, where the initial layers of a network were the most critical, and the latter layers primarily performed near-random transformations without affecting the performance of the network. This indicates that utilizing DR3 alters the internal layers of a Q-network trained with TD to behave closer to supervised learning.

A.3 RANK COLLAPSE IS ALLEVIATED WITH DR3

Figure A.3: **Comparing the feature ranks for CQL and CQL + DR3.** Observe that utilizing DR3 successfully alleviates the rank collapse issue noted in prior work without explicitly correcting for it.

Prior work (Kumar et al., 2021) has shown that implicit regularization in TD-learning can lead to a feature rank collapse phenomenon in the Q-function, which hinders the Q-function from using its full representational capacity. Such a phenomenon is absent in supervised learning, where the feature rank does not collapse. Since DR3 is inspired by mitigating the effects of the term in the implicit regularizer (Equation 4) that only appears in the case of TD-learning, we wish to understand if utilizing DR3 also alleviates rank collapse. To do so, we compute the effective rank $\text{srank}_\delta(\phi)$

Table A.1: Normalized interquartile mean performance with 95% stratified bootstrap CIs (Agarwal et al., 2021) across 17 Atari games of REM, REM + $\Delta'(\Phi)$ (Stop gradient in DR3), REM + DR3 after 6.5M gradient steps for the 1% setting and 12.5M gradient steps for the 5%, 10% settings. Observe that REM + $\Delta'(\phi)$ also improves over the base REM method significantly, by about 130%, even though $\Delta'(\phi)$ is generally comparable and somewhat worse than the DR3 regularizer used in the main paper.

Data	REM	REM + $\Delta'(\Phi)$	REM+DR3
1%	4.0 (3.3, 4.8)	15.0 (13.4, 16.6)	16.5 (14.5, 18.6)
5%	25.9 (23.4, 28.8)	55.5 (50.8, 59.8)	60.2 (55.8, 65.1)
10%	53.3 (51.4, 55.3)	67.7 (64.7, 71.3)	73.8 (69.3, 78)

metric of the features learned by Q-functions trained via standard Q-learning, standard Q-learning with DR3 explicit regularizer and offline SARSA. As shown in Figure A.3, for the case of five Atari games, utilizing DR3 alleviates the rank collapse issue completely. This is potentially surprising, because no term in the practical DR3 regularizer explicitly aims to increase rank: feature dot products can be made smaller while retaining low ranks by simply controlling the magnitude. But, as we observe, utilizing DR3 enables learning high-rank features, thus likely indicating that correcting for appropriate terms in $R_{TD}(\theta)$ can address some of the previously observed pathologies in TD-learning.

A.4 INDUCED IMPLICIT REGULARIZER: THEORY AND PRACTICE

In this section, we compare the performance of our practical DR3 regularizer to the regularizers (Equation 4) obtained for different choices of M, such as M induced by noise, studied in previous work, and also evaluate the effect of dropping the stop gradient function from the practical version of our regularizer.

Empirically comparing the explicit regularizers for different noise covariance matrices, M. The theoretically derived regularizer (Equation 4) suggests that for a given choice of M, the following equivalent of feature dot products should increase over the course of training:

$$\Delta_M(\theta) := \sum_{\mathbf{s}, \mathbf{a} \in \mathcal{D}} \text{trace}\left[\Sigma_M^* \nabla Q(\mathbf{s}, \mathbf{a}) \nabla Q(\mathbf{s}', \mathbf{a}')^\top\right]. \quad \text{(Generalized dot products)} \quad \text{(A.1)}$$

We evaluate the efficacy of the explicit regularizer that penalizes the generalized dot products, $\Delta_M(\theta)$, in improving the performance of the policy. While Σ_M^* must be explicitly computed by running fixed point iteration for every parameter iterate θ found during TD-learning – which makes this method significantly computationally expensive, we evaluated it on five Atari games. As shown in Figure A.4, the DR3 penalty with the choice of M which corresponds to label noise, and the dot product DR3 penalty used in the paper generally perform similarly on these domains, attaining almost identical learning curves on **4/5 games**, and clearly improving over the base algorithm. This hints at the possibility of utilizing other noise covariance matrices to derive an explicit regularizer.

Figure A.4: **Comparing the performance of explicit penalties for two different choices of the covariance matrix M.** Observe that in all the five games the DR3 regularizer derived for the choice of M from Blanc et al. (2020) also leads to a substantial increase in performance over the base algorithm, and in four of five games, DR3 (label-noise) works just as well as DR3.

Effect of stop gradient. Finally, we investigate the effect of utilizing a stop gradient in the DR3 regularizer. We run a variant of DR3: $\Delta'(\phi) = \sum_{\mathbf{s}, \mathbf{a}, \mathbf{s}'} \phi(\mathbf{s}, \mathbf{a})^\top [[\phi(\mathbf{s}', \mathbf{a}')]]$, with the stop gradient on the second term $(\mathbf{s}', \mathbf{a}')$ and present a comparison to the one without the stop gradient in Table A.1

for REM as the base offline method, averaged over 17 games. Note that this version of DR3, with the stop gradient, also improves upon the baseline offline RL method (i.e., REM) by **130%**. While this performs largely similar, but somewhat worse than the complete version without the stop gradient, these results do indicate that utilizing $\Delta'(\phi)$ can also lead to significant gains in performance.

B   EXTENDED RELATED WORK

In this section, we briefly review some extended related works, and in particular, try to connect feature co-adaptation and implicit regularization to various interesting results pertaining to RL lower-bounds with function approximation and self-supervised learning.

Lower-bounds for offline RL. Zanette (2020) identifies hard instances for offline TD learning of linear value functions when the provided features are "aliased". Note that this work does not consider feature learning or implicit regularization, but their hardness result relies heavily on the fact the given linear features are aliased in a special sense. Aliased features utilized in the hard instance inhibit learning along certain dimensions of the feature space with TD-style updates, necessitating an exponential sample size for near-accurate value estimation, even under strong coverage assumptions. A combination of Zanette (2020)'s argument, which provides a hard instance given aliased features, and our analysis, which studies the emergence of co-adapted/similar features in the offline deep RL setting, could imply that the co-adaptation can lead to failure modes from the hard instance, even on standard Offline RL problems, when provided with limited data.

Connections to self-supervised learning (SSL). Several modern self-supervised learning methods (Grill et al., 2020; Chen & He, 2020) can be viewwed as utilizing some form of bootstrapping where different augmentations of the same input $(\mathbf{x} + \text{Aug}_1, \mathbf{x} + \text{Aug}_2)$ serve as consecutive state-action tuples that appear on two sides of the backup. If we may extrapolate our reasoning of feature co-adaptation to this setting, it would suggest that performing noisy updates on a self-supervised bootstrapping loss will give us feature representations that are highly similar for consecutive state-action tuples, i.e., the representations for $\phi(\mathbf{x}+\text{Aug}_1)^\top \phi(\mathbf{x}+\text{Aug}_2)$ will be high. Intuitively, an easy way for obtaining high feature dot products is for $\phi(\cdot)$ to capture only that information in $\cdot$, which is agnostic to data augmentation, thus giving rise to features that are invariant to transformations. This aligns with what has been shown in self-supervised learning (Tian et al., 2020; 2021). Another interesting point to note is that while such an explanation would indicate that highly co-adapted features are beneficial in SSL, such features can be adverse in value-based RL as discussed in Section 3.

Preventing divergence in deep TD-learning. Finally, we discuss Achiam et al. (2019) which proposes to pre-condition the TD-update using the inverse the neural tangent kernel (Jacot et al., 2018) matrix so that the TD-update is always a contraction, for every θ_k found during TD-learning. Intuitively, this can be overly restrictive in several cases: we do not need to ensure that TD always contracts, but that is eventually stabilizes at good solution over long periods of running noisy TD updates, Our implicit regularizer (Equation'4) derives this condition, and our theoretically-inspired DR3 regularizer shows that empirically, it suffices to penalize the dot product similarity in practice.

C   PROOF OF THEOREM 3.1

In this section, we will derive our implicit regularizer $R_{\text{TD}}(\theta)$ that emerges when performing TD updates with a stochastic noise model with covariance matrix M. We first introduce our notation that we will use throughout the proof, then present our assumptions and finally derive the regularizer. Our proof utilizes the analysis techniques from Blanc et al. (2020) and Damian et al. (2021), which analyze label-noise SGD for supervised learning, however key modifications need to be made to their arguments to account for non-symmetric matrices that emerge in TD learning. As a result, the form of the resulting regularizer is very different. To keep the proof concise, we will appeal to lemmas from these prior works which will allow us to bound certain concentration terms.

C.1   NOTATION

The noisy TD-learning update for training the Q-function is given by:

$$\theta_{k+1} = \theta_k - \eta \underbrace{\left(\sum_i \nabla_\theta Q(\mathbf{s}_i, \mathbf{a}_i) \left(Q_\theta(\mathbf{s}_i, \mathbf{a}_i) - (r_i + \gamma Q_\theta(\mathbf{s}'_i, \mathbf{a}'_i)) \right) \right)}_{:=g(\theta)} + \eta \varepsilon_k, \quad \varepsilon_k \sim \mathcal{N}(0, M) \quad \text{(C.1)}$$

where $g(\theta)$ denotes the parameter update. Note that $g(\theta)$ is not a full gradient of a scalar objective, but it is a form of a "pseudo"-gradient or "semi"-gradient. Let ε_k denote an i.i.d.random noise that is added to each update. This noise is sampled from a zero-mean Gaussian random variable with covariance matrix M, i.e., $\mathcal{N}(0, M)$.

Let θ^* denote a point in the parameter space such that in the vicinity of θ^*, $g(\theta) \leq \mathscr{C}$, for a small enough $\mathscr{C}$. Let $G(\theta)$ denote the derivative of $g(\theta)$ w.r.t. θ: $G(\theta) = \nabla_\theta g(\theta)$ and let $\nabla G(\theta)$ denote the third-order tensor $\nabla_\theta^2 g(\theta)$. For notation clarity, let $G = G(\theta^*), \nabla G = \nabla G(\theta^*)$. Let e_i denote the signed TD error for a given transition $(\mathbf{s}_i, \mathbf{a}_i, \mathbf{s}_i') \in \mathcal{D}$ at θ^*:

$$e_i = Q_{\theta^*}(\mathbf{s}_i, \mathbf{a}_i) - (r_i + \gamma Q_{\theta^*}(\mathbf{s}_i', \mathbf{a}_i')). \tag{C.2}$$

Since θ^* is a fixed point of the training TD error, $e_i = 0$. Following Blanc et al. (2020), we will assume that the learning rate in gradient descent, η, is small and we will ignore terms that scale as $\mathcal{O}(\eta^{1+\delta})$, for $\delta > 0$. Our proof will rely on using a reference Ornstein-Uhlenbeck (OU) process which the TD parameter iterates will be compared to. Let ζ_k denote the k-th iterate of an OU process, which is defined as:

$$\zeta_{k+1} = (I - \eta G)\zeta_k + \eta \varepsilon_k, \quad \varepsilon_k \sim \mathcal{N}(0, M) \tag{C.3}$$

We will drop θ from ∇_θ to indicate that the gradient is being computed at θ^*, and drop $(\mathbf{s}_i, \mathbf{a}_i)$ from $Q(\mathbf{s}_i, \mathbf{a}_i)$ and instead represent it as Q_i for brevity; we will represent $Q(\mathbf{s}_i', \mathbf{a}_i')$ as Q_i'. We assume that $\nabla^2 Q_i$ is $\mathscr{L}_2$-Lipschitz and $\nabla^3 Q_i$ is $\mathscr{L}_3$-Lipschitz throughout the parameter space Θ.

C.2 PROOF STRATEGY

For a given point θ^* to be an attractive fixed point of TD-learning, our proof strategy would be to derive the condition under which it mimics a given OU noise process, which as we will show stays close to the parameter θ^*. This condition would then be interpreted as the gradient of a "induced" implicit regularizer. If the point θ^* is not a stationary point of this regularizer, we will show that the movement θ is large when running the noisy TD updates, indicating that the regularizer, atleast in part guides the dynamics of TD-learning. To show this, we would write out the gradient update, isolate some terms that will give rise to the implicit regularizer, and bound the remaining terms using contraction and concentration arguments. The contraction arguments largely follow prior work (though with key exceptions in handling contraction with asymmetric and complex eigenvalue matrices), while the form of the implicit regularizer is different. Finally, we will interpret the resulting update over large timescales to show that learning is indeed guided by the implicit regularizer.

C.3 ASSUMPTIONS AND CONDITIONS

Next, we present some key assumptions we will need for the proof. Our first assumption is that the matrix $G \in \mathbb{R}^{d \times d}$ is of maximal rank possible, which is equal to the number of datapoints n and $n \ll d$, the dimensionality of the parameter space. Crucially, this assumption do not imply that G is of full rank – it cannot be, because we are in the overparameterized regime.

Assumption A1 (G spans an n-dimensional basis.). *Assume that the matrix G spans n-possible directions in the parameter space and hence, attains the maximal possible rank it can.*

The second condition we require is that the matrices $\sum_i \nabla Q_i \nabla Q_i^\top$ and M share the same n-dimensional basis as matrix G:

Assumption A2. $\sum_i \nabla Q_i \nabla Q_i^\top$, M, *and G span identical n-dimensional subspaces.*

This is a technical condition that is required. If this condition is not met, as we will show the learning dynamics of noisy TD will not be a contraction in certain direction in the parameter space and TD-learning will not stabilize at such a solution θ^*. In fact, we will utilize a stronger version of this statement for TD-learning to converge, and we will discuss this shortly.

C.4 LEMMAS USED IN THE PROOF

Next, we present some lemmas that would be useful for proving the theoretical result.

Lemma C.1 (Expressions for the first and and second-order derivatives of $g(\theta)$.)**.** *The following definitions and expansions apply to our proof:*

$$G(\theta^*) = \sum_i \nabla^2 Q_i e_i + \sum_i \nabla Q_i (\nabla Q_i - \gamma \nabla Q_i')^\top$$

$$\nabla G(\theta^*)[\mathbf{v}, \mathbf{v}] = 2 \sum_i \nabla^2 Q_i \mathbf{v}\mathbf{v}^\top (\nabla Q_i - \gamma \nabla Q_i') + \sum_i \operatorname{tr} \left((\nabla^2 Q_i - \gamma \nabla^2 Q_i') \mathbf{v}\mathbf{v}^\top \right) \nabla Q_i + \nabla^3 Q_i e_i$$

Lemma C.1 presents a decomposition of the matrix G and the directional derivative of the third order tensor $\nabla G[\mathbf{v}, \mathbf{v}]$ in directions $\mathbf{v}$ and $\mathbf{v}$, which will appear in the Taylor expansion layer. Note that at θ^* since $e_i = 0$, the first term in $G(\theta^*)$ and the third term in $\nabla G(\theta^*)[\mathbf{v}, \mathbf{v}]$ vanish. Lemma C.2 derives a fixed-point recursion for the covariance matrix of the total noise accumulated in the OU-process with covariance matrix M and this will appear in our proof.

Lemma C.2 (Covariance of the random noise process ζ_k)**.** *Let ζ_k denote the OU process satisfying: $\zeta_{k+1} = (I - \eta G)\zeta_k + \eta\varepsilon_k$, where $\varepsilon_k \sim \mathcal{N}(0, M)$, where $M \succcurlyeq 0$. Then, $\zeta_{k+1} \sim \mathcal{N}(0, \Sigma)$, where Σ satisfies the discrete Lyapunov equation:*

$$\Sigma_M^* = (I - \eta G)\Sigma_M^* (I - \eta G)^\top + \eta^2 M.$$

Proof. For the OU process, $\zeta_{k+1} = (I - \eta G)\zeta_k + \eta\varepsilon_k$, since ε_k is a Gaussian random variable, by induction so is ζ_{k+1}, and therefore the covariance matrix of ζ_{k+1} is given by:

$$\Sigma_{k+1} := (I - \eta G)\Sigma_k (I - \eta G^\top) + \eta^2 M. \tag{C.4}$$

Solving for the fixed point for Σ_k gives the desired expression. $\qquad\square$

In our proofs, we will require the following contraction lemmas to tightly bound the magnitude of some zero-mean terms that will appear in the noisy TD update under certain scenarios. Unlike the analysis in Damian et al. (2021) and Blanc et al. (2020) for supervised learning with label noise, where the contraction terms like $(I - \eta G)^k G$ are bounded by $\approx \frac{1}{k\eta}$ intuitively because $I - \eta G$ is a contraction in the subspace spanned by matrix G. However, this is not true for TD-learning directly since terms like $(I - \eta G)^k S$ appear for a different matrix S. Therefore, TD-learning will diverge from θ^* unless matrices G and M have their corresponding eigenvectors assigned to the top eigenvalues be approximately "aligned". We formalize this definition next, and then provide a proof of the concentration guarantee.

Definition 1 ((ω, C_0)-alignment)**.** *Given a positive semidefinite matrix A, let $A = U_A \Lambda_A U_A^\top$ denote its eigendecomposition. Without loss of generality assume that the eigenvalues are arranged in decreasing order, i.e., $\forall i > j, \Lambda_A(i) \leq \Lambda_A(j)$. Given another matrix B, let $B = U_B \Lambda_B U_B^H$ denote its complex eigendecomposition, where eigenvalues in Λ_B are arranged in decreasing order of their complex magnitudes, i.e., $\forall i > j, |\Lambda_B(i)| \leq |\Lambda_B(j)|$. Then the matrix pair (A, B) is said to be (ω, C_0)-aligned if $|U_B^H(i)U_A(i)| \leq \omega$ and if $\forall\, i, \Lambda_A(i) \leq C_0 |\Lambda_B(i)|$ for a constant C_0.*

If two matrices are (ω, C_0)-aligned, this means that the corresponding eigenvectors when arranged in decreasing order of eigenvalue magnitude roughly align with each other. This condition would be crucial while deriving the implicit regularizer as it will quantify the rate of contraction of certain terms that define the neighborhood that the iterates of noisy TD-learning will lie in with high probability. We will operate in the setting when the matrix G and $\sum_i \nabla Q_i \nabla Q_i^\top$ are (ω, C_0)-aligned with each other, and matrix M and G are also (ω, C_0)-aligned (note that we can consider ω', C_0'), which will not change our bounds and therefore we go for less notational clutter). Next we utilize this notion of alignment to show a particular contraction bound that extends the weak contraction bound in Damian et al. (2021).

Lemma C.3. *Assume we are given a matrix G such that $|\lambda_i(I - \eta G)| \leq \rho_0 < 1$ for all λ_i such that $\lambda_i \neq 0$. Let $G = U\Lambda U^H$ be the complex eigenvalue decomposition of G (since almost every matrix is complex-diagonalizable). For a positive semi-definite matrix S that is (ω, C_0)-aligned with G, if $S = U_S \Lambda_S U_S^\top$ is its eigenvalue decomposition, the following contraction bound holds:*

$$||(I - \eta G)^k S|| = \mathcal{O}\left(\frac{\omega C_0}{\eta k}\right)$$

Proof. To prove this statement, we can expand $(I - \eta G)$ using its eigenvalue decomposition only in the subspace that is jointly shared by G and M, and then utilize the definition of ω-alignment to bound the terms.

$$||(I - \eta G)^k S|| = ||(I - \eta U \Lambda U^H)^k U_S \Lambda_S U_S^\top|| \tag{C.5}$$

$$= ||(UU^H - \eta U \Lambda_U U^H)^k U_S \Lambda_S U_S^\top|| \tag{C.6}$$

$$= \left|\left| U (I - \eta \Lambda)^k U^H U_S \Lambda_S U_S^\top \right|\right| \tag{C.7}$$

$$\leq \omega \cdot || (I - \eta \Lambda)^k || \cdot \Lambda_S \tag{C.8}$$

$$\leq \omega \cdot C_0 \cdot \left(\max_i \ |1 - \eta \Lambda(i)|^k |\Lambda(i)| \right) \tag{C.9}$$

Now we need to solve for the inner maximization term. When $\Lambda(i)$ is not complex for any i, the term above is $\lesssim 1/\eta k$ using the result from Damian et al. (2021), but when $\Lambda(i)$ is complex, this bound can only hold under certain conditions. To note when this quantity is bounded, we expand $|1 - \eta x|^k$ for some complex number $x = r(\cos \theta + \iota \sin \theta)$:

$$|1 - \eta x|^k = |(1 - \eta r \cos \theta) + \iota \eta r \sin \theta| \tag{C.10}$$

$$= \left[\sqrt{(1 - \eta r \cos \theta)^2 + \eta^2 r^2 \sin^2 \theta} \right]^k = \left(1 + \eta^2 r^2 - 2\eta r \cos \theta\right)^{k/2} \tag{C.11}$$

$$\implies |1 - \eta x|^k |x| = \left(1 + \eta^2 r^2 - 2\eta r \cos \theta\right)^{k/2} r \tag{C.12}$$

$$\lesssim \frac{1}{\eta k} \quad \text{if } \eta \leq \min_i \frac{\text{Re}(\Lambda(i))}{|\Lambda(i)|} \quad \text{and} \quad \infty \text{ otherwise.} \tag{C.13}$$

Plugging back the above expression in the bound above completes the proof. $\square$

The proof of Lemma C.3 indicates that unless the learning rate η and the matrix G are such that the $|\lambda_i(I - \eta G)| \leq \rho < 1$ in directions spanned by matrix S, such an expression may not converge. This is expected since the matrix $I - \eta G$ will not contract in directions of non-zero eigenvalues if the real part $r \cos \theta$ is negative or zero. Additionally, we note that under Definition 1, we can extend several weak-contraction bounds from Damian et al. (2021) (Lemmas 9-14 in Damian et al. (2021)) to our setting.

Next, Lemma C.4 shows that the OU noise iterates are bounded with high probability when Definition 1 holds:

Lemma C.4 (ζ_k is bounded with high probability)**.** *With probability atleast $1 - \delta$ and under Definition 1, $||\zeta_k|| \leq n\omega\sqrt{\eta C_0} \log \frac{1}{\delta} = \mathcal{O}(\sqrt{\eta})$.*

Proof. To prove this lemma, we first bound the trace of the covariance matrix Σ_{k+1} and then apply high probability bounds on the Martingale norm concentration. The trace of the covariance matrix Σ_{k+1} can be bounded as follows (all the equations below are restricted to the dimensions of non-zero eigenvalues of G):

$$\text{tr}\left[\Sigma_{k+1}\right] = \sum_{j \leq k} \text{tr}\left[(I - \eta G)^j M (I - \eta G^\top)^j\right] \tag{C.14}$$

$$= \sum_{j \leq k} \text{tr}\left[(UU^H - \eta U \Lambda U^H)^j M (UU^H - \eta U \Lambda U^H)^j\right] \tag{C.15}$$

$$= \sum_{j \leq k} \text{tr}\left[U(I - \eta \Lambda)^j U^H U_M \Lambda_M U_M^\top U(I - \eta \Lambda)^j U^H\right] \tag{C.16}$$

$$= \sum_{j \leq k} n\omega^2 C_0 \text{tr}\left[|I - \eta \Lambda|^j \cdot |\Lambda| \cdot |I - \eta \Lambda|^j\right] \tag{C.17}$$

$$\leq n\omega^2 C_0 \sum_{j \leq k} n \cdot \max_\lambda(|1 - \eta \lambda|^{2j} \cdot |\lambda|) \leq \eta n^2 C_0 \omega^2 \tag{C.18}$$

Now, we can apply Corollary 1 from Damian et al. (2021) to obtain a bound on $||\zeta_k||$ as with high probability, atleast $1 - \delta$, $||\zeta_k|| \leq \sqrt{2\text{tr}(\Sigma) \log \frac{1}{\delta}} = n\omega\sqrt{\eta C_0} \log \frac{1}{\delta}$. $\square$

C.5   MAIN PROOF OF THEOREM 3.1

In this section, we present the main proof of Theorem 3.1. The proof involves two components: **(1)** the part where we derive the regularizer, and **(2)** bounding additional terms via concentration inequalities. Part **(1)** is specific to TD-learning, while a lot of the machinery for part **(2)** is directly taken from prior work (Damian et al., 2021) and Blanc et al. (2020). We focus on part **(1)** here.

Our strategy is to analyze the learning dynamics of noisy TD updates that originate at θ^*. In a small neighborhood around θ^*, we can expand the noisy TD update (Equation 3) using Taylor's expansion around θ^* which gives:

$$\theta_{k+1} = \theta_k - \eta g(\theta_k) + \eta \varepsilon_k, \ \ \varepsilon_k \sim \mathcal{N}(0, M) \tag{C.19}$$

$$\implies \theta_{k+1} = \theta_k - \eta \left(g + G(\theta_k - \theta^*) - \frac{\eta}{2} G[\theta_k - \theta^*, \theta_k - \theta^*] \right) + \eta \varepsilon_k + \mathcal{O}(\eta ||\theta_k - \theta^*||^3). \tag{C.20}$$

Denoting $\nu_k := \theta_k - \theta^*$, using the fact that $||g(\theta^*)|| \leq \mathscr{C}$, we find that ν_k can be written as:

$$\nu_{k+1} = (I - \eta G)\nu_k + \varepsilon_k + \frac{\eta}{2} G[\nu_k, \nu_k] + \mathcal{O}(\eta ||\nu_k||^3 + \eta \mathscr{C}) \tag{C.21}$$

Since the OU process ζ_k stays in the vicinity of the point θ^*, and follows a similar recursion to the one above, our goal would be to design a regularizer so that Equation C.21 closely follows the OU process. Thus, we would want to bound the difference between the variable ν_k and the variable ζ_k, denoted as r_k to be within a small neighborhood:

$$r_{k+1} = \nu_{k+1} - \zeta_{k+1} = (I - \eta G) \underbrace{(\nu_k - \zeta_k)}_{r_k} + \frac{1}{2} G[\nu_k, \nu_k] + \mathcal{O}(\eta ||\nu_k||^3 + \eta \mathscr{C}).$$

We can write down an expression for r_k summing over all the terms:

$$r_{k+1} = -\frac{\eta}{2} \underbrace{\sum_{j \leq k} (I - \eta G)^{k-j} \nabla G[\nu_k, \nu_k]}_{\text{term (a)}} + \underbrace{\sum_{j \leq k} (I - \eta G)^j \left[\mathcal{O}(\eta ||\nu_k||^3 + \eta \mathscr{C}) \right]}_{\text{term (b)}}. \tag{C.22}$$

Term (a) in the above equation is the one that can induce a displacement in r_k as k increases and would be used to derive the regularizer, whereas term (b) primarily consists of terms that concentrate to 0. We first analyze term (a) and then we will analyze the concentration terms later.

To analyze term (a), note that the term $\nabla G[\nu_k, \nu_k]$, by Lemma C.1, only depends on ν_k via the covariance matrix $\nu_k \nu_k^\top$. So we will partition this term into two terms: **(i)** a term that utilizes the asymptotic covariance matrix of the OU process and **(ii)** errors due to a finite k and stochasticity that will concentrate.

$$2 \times \text{(a)} = \eta \sum_{j \leq k} (I - \eta G)^{k-j} \nabla G[\nu_k, \nu_k] \tag{C.23}$$

$$= \sum_{j \leq k} (I - \eta G)^{k-j} \nabla G[\zeta^*, \zeta^*] + \sum_{j \leq k} (I - \eta G)^{k-j} \nabla G([\nu_k, \nu_k] - [\zeta^*, \zeta^*]), \tag{C.24}$$

The first term is a "bias" term and doesn't concentrate to 0, and will give rise to the regularizer. We can break this term using Lemma C.1 as:

$$\nabla G[\zeta^*, \zeta^*] = 2 \sum_i \nabla^2 Q_i \Sigma_M^* (\nabla Q_i - \gamma \nabla Q_i') + \sum_i \text{tr} \left[(\nabla^2 Q_i - \gamma \nabla^2 Q_i') \Sigma_M^* \right] \nabla Q_i \tag{C.25}$$

The regularizer $R_{\text{TD}}(\theta)$ is the function such that:

$$\nabla_\theta R_{\text{TD}}(\theta) = \sum_i \nabla^2 Q_i \Sigma_M^* (\nabla Q_i - \gamma \nabla Q_i') \tag{C.26}$$

$$\implies R_{\text{TD}}(\theta) = \sum_i \nabla Q_i \Sigma_M^* \nabla Q_i^\top - \gamma \sum_i \text{trace} \left(\Sigma_M^* \nabla Q_i [[\nabla Q_i']]^\top \right), \tag{C.27}$$

where $[[\cdot]]$ denotes the stop gradient operator. If the point θ^* is a stationary point of the regularizer $R_{\text{TD}}(\theta)$, then Equations C.26 and C.27 imply that the first term of Equation C.25 must be 0. Therefore in this case to show that θ^* is attractive, we need to show that the other terms in Equations C.25, C.24 and term (b) in Equation C.22 concentrate around 0 and are bounded in magnitude. The remaining part of the proof shown in Appendix C.7 provides these details, but we first summarize the main takeaways in the proof to conclude the argument.

C.6 SUMMARY OF THE ARGUMENT

We will show how to concentrate terms in Equation C.26 besides the regularizer largely following the techniques from prior work, but we first summarize the entire proof. The overall update to the vector r_k which measures the displacement between the parameter vector $\theta_k - \theta^*$ and the OU-process ζ_k can be written as follows, and it is governed by the derivative of the implicit regularizer (modulo error terms):

$$r_{k+1} = -\frac{\eta}{2} \sum_{j \le k} (I - \eta G)^{k-j} \nabla_\theta R_{\mathrm{TD}}(\theta^*) + \mathcal{O}\left(\sqrt{\eta t} \cdot \mathrm{poly}(\mathscr{C}, \mathscr{L}_2, \mathscr{L}_3, \omega, C_0)\right). \quad \text{(C.28)}$$

An important detail to note here is that since the regularizer consists of Σ_M^* and the size of Σ_M^* (i.e, its eigenvalues), as shown in Lemma C.4 depends on one factor of η. So, effectively the first term in Equation C.28 does depend on two factors of η. Using Equation C.28, we can write the deviation between θ^* and θ_k as:

$$\nu_{k+1} = \zeta_{k+1} - \frac{\eta}{2} \sum_{j \le k} (I - \eta G)^{k-j} \nabla_\theta R_{\mathrm{TD}}(\theta^*) + \mathcal{O}\left(\sqrt{\eta t} \cdot \mathrm{poly}(\mathscr{C}, \mathscr{L}_2, \mathscr{L}_3, \omega, C_0)\right). \quad \text{(C.29)}$$

The OU process ζ_k converges to θ^* in the subspace spanned by G, since the condition $\rho(I - \eta G) < 1$ is active in this subspace (if the condition that $\rho(I - \eta G) < 1$ in the subspace spanned by G is not true, then as Ghosh & Bellemare (2020) show, TD can diverge). Now, given G satisfies this spectral radius condition, ζ_k would converge to θ^* within a timescale of $\mathcal{O}\left(\frac{1}{\eta}\right)$ within this subspace, which as Blanc et al. (2020) put it is the strength of the "mean-reversion" term. On the remaining directions (note that $d \gg n$), the dynamics is guided by the regularizer, although with a smaller weight of η^2.

C.7 ADDITIONAL PROOF DETAILS: CONCENTRATING OTHER TERMS

We first concentrate the terms in Equation C.25. The cumulative effect of the second term in Equation C.25 is given by:

$$\eta \sum_{j \le k} (I - \eta G)^{j-k} \nabla Q_i \mathrm{tr}\left[(\nabla^2 Q_i - \gamma \nabla^2 Q_i') \Sigma_M^*\right] \quad \text{(C.30)}$$

$$\le \eta \sum_{j \le k} (I - \eta G)^{j-k} \nabla Q_i \cdot \mathcal{O}\left(\mathscr{L}_2(1+\gamma)\sigma\right) \le \mathcal{O}\left(\eta \sqrt{\frac{k}{\eta}} \omega_0 C_0 \mathscr{L}_2(1+\gamma)\sigma\right), \quad \text{(C.31)}$$

which follows from the fact that $\nabla^2 Q_i$ is $\mathscr{L}_2$-Lipschitz, and using Lemma C.3 for contracting the remaining terms.

Next, we turn to concentrating the second term in Equation C.24. This term corresponds to the contribution of difference between the empirical covariance matrix $\nu_k \nu_k^\top$ and the asymptotic covariance matrix $\zeta^* \zeta^{*\top}$. We expand this term below using the form of G from Lemma C.1, and bound it one by one.

$$\sum_{j \le k} (I - \eta G)^{k-j} \nabla G([\nu_k, \nu_k] - [\zeta^*, \zeta^*]) \quad \text{(C.32)}$$

$$= \sum_{j \le k} \sum_i (I - \eta G)^{k-j} \nabla^2 Q_i \left(\nu_k \nu_k - \zeta^* \zeta^{*\top}\right) (\nabla Q_i - \gamma \nabla Q_i') + \mathcal{O}\left(\sqrt{\eta k} \omega_0 C_0 \mathscr{L}_2(1+\gamma)\sigma\right)$$

$$\quad \text{(C.33)}$$

Now, we note that the term $\Delta_{k+1} := \nu_{k+1} \nu_{k+1}^\top - \zeta^* \zeta^{*\top}$ can itself be written as a recursion:

$$\Delta_{k+1} = (I - \eta G)(\Delta_k)(I - \eta G)^\top + \underbrace{(I - \eta G)\zeta_k \varepsilon^\top + \varepsilon \zeta_k^\top (I - \eta G)^\top}_{A_k} + \underbrace{\varepsilon \varepsilon^\top - \eta M}_{B_k} \quad \text{(C.34)}$$

Expanding the term Δ_{k+1} in terms of a summation over k, and plugging it into the expression from Equation C.35 we get

$$\sum_i \sum_{j \leq k} (I - \eta G)^{k-j} \nabla^2 Q_i (I - \eta G)^j \Delta_0 (I - \eta G^\top)^j \tag{C.35}$$

$$+ \sum_i \sum_{j \leq k} \sum_{p \leq j} (I - \eta G)^{k-j} \nabla^2 Q_i (I - \eta G)^{j-p-1} (A_p + B_p)(I - \eta G^\top)^{j-p-1}$$

Now by noting that if G and ∇Q_i are (ω, C_0)-aligned, then so are $G^\top$ and ∇Q_i, we can finish the proof by repeating the calculations used by Damian et al. (2021) (Appendix B, Equations 67-73) to bound the terms in Equation C.35 by $\mathcal{O}(\sqrt{\eta k})$, but with an additional factor of $\omega^2 C_0^2$.

Term (b) in Equation C.22. When $\mathscr{C}$ is small enough, we can bound the term (b) using $\mathcal{O}(\sqrt{\eta k})$, similar to Damian et al. (2021).

D   PROOF OF PROPOSITION 3.2

In this section, we will prove Proposition 3.2. First, we refer to Proposition 3.1 in Ghosh & Bellemare (2020), which shows that TD-learning is stable and converges if and only if the matrix $M_\phi = \Phi^\top (\Phi - \gamma \Phi')$ has eigenvalues with all positive real entries. Now note that if,

$$\sum_{\mathbf{s}, \mathbf{a}} \phi(\mathbf{s}, \mathbf{a})^\top \phi(\mathbf{s}, \mathbf{a}) \leq \gamma \sum_{\mathbf{s}, \mathbf{a}, \mathbf{s}'} \phi(\mathbf{s}', \mathbf{a}')^\top \phi(\mathbf{s}, \mathbf{a}) \tag{D.1}$$

$$\implies \text{trace}\left(\Phi^\top \Phi\right) \leq \gamma \text{trace}\left(\Phi^\top \Phi'\right) \tag{D.2}$$

$$\implies \text{trace}\left[\Phi^\top (\Phi - \gamma \Phi')\right] \leq 0. \tag{D.3}$$

Since the trace of a real matrix is the sum of real components of eigenvalues, if for a given matrix M, $\text{trace}(M) \leq 0$, then there exists atleast one eigenvalue λ_i such that $\text{Re}(\lambda_i) \leq 0$. If $\lambda_i < 0$, then the learning dynamics of TD would diverge, while if $\lambda_i = 0$ for all i, then learning will not contract towards the TD fixed point. This concludes the proof of this result.

E   EXPERIMENTAL DETAILS OF APPLYING DR3

In this section, we discuss the practical experimental details and hyperparameters in applying our method, DR3 to various offline RL methods. We first discuss an overview of the offline RL methods we considered in this paper, and then provide a discussion of hyperparameters for DR3.

E.1   BACKGROUND ON VARIOUS OFFLINE RL ALGORITHMS

In this paper, we consider four base offline RL algorithms that we apply DR3 on. These methods are detailed below:

REM. Random ensemble mixture (Agarwal et al., 2020) is an uncertainty-based offline RL algorithm uses multiple parameterized Q-functions to estimate the Q-values. During the Bellman backup, REM computes a random convex combination of the target Q-values and then trains the Q-function to match this randomized target estimate. The randomized target value estimate provides a robust estimate of target values, and delays unlearning and performance degradation that we typically see with standard DQN-style algorithms in the offline setting. For instantiating REM, we follow the instantiation provided by the authors and instantiate a multi-headed Q-function with 200 heads, each of which serves as an estimate of the target value. These multiple heads branch off the last-but-one layer features of the base Q-network. The objective for REM is given by:

$$\min_\theta \mathbb{E}_{\mathbf{s}, \mathbf{a}, r, \mathbf{s}' \sim \mathcal{D}} \left[\mathbb{E}_{\alpha_1, \dots, \alpha_K \sim \Delta} \left[\ell_\lambda \left(\sum_k \alpha_k Q_\theta^k(\mathbf{s}, \mathbf{a}) - r - \gamma \max_{\mathbf{a}'} \sum_k \alpha_k Q_{\theta'}^k(\mathbf{s}', \mathbf{a}') \right) \right] \right] \tag{E.1}$$

where l_λ denotes the Huber loss while P_Δ denotes the probability distribution over the standard (K 1)-simplex.

CQL. Conservative Q-learning (Kumar et al., 2020b) is an offline RL algorithm that learns a conservative value function such that the estimated performance of the policy under this learned value function lower-bounds its true value. CQL modifies the Q-function training to incorporate a term that minimizes the overestimated Q-values in expectation, while maximizing the Q-values observed in the dataset, in addition to standard TD error. This CQL regularizer is typically multiplied by a coefficient α, and we pick $\alpha = 0.1$ for all our Atari experiments following Kumar et al. (2021) and $\alpha = 5.0$ for all our kitchen and antmaze D4RL experiments. Using $\overline{y}_k(\mathbf{s}, \mathbf{a})$ to denote the target values computed via the Bellman backup (we use actor-critic backup for D4RL experiments and the $\max_{\mathbf{a}'}$ backup for standard Q-learning in our Atari experiments following Kumar et al. (2020b)), the objective for training CQL is given by:

$$\min_Q \alpha \left(\mathbb{E}_{\mathbf{s}\sim\mathcal{D}} \left[\log \sum_{\mathbf{a}} \exp(Q(\mathbf{s},\mathbf{a})) \right] - \mathbb{E}_{\mathbf{s},\mathbf{a}\sim\mathcal{D}} \left[Q(\mathbf{s},\mathbf{a}) \right] \right) + \frac{1}{2}\mathbb{E}_{\mathbf{s},\mathbf{a},\mathbf{s}'\sim\mathcal{D}} \left[(Q(\mathbf{s},\mathbf{a}) - \overline{y}_k(\mathbf{s},\mathbf{a}))^2 \right].$$

The deep Q-network utilized by us is a ReLU network with four hidden layers of size $(256, 256, 256, 256)$ for the D4RL experiments, while for Atari we utilize the standard convolutional neural network from Agarwal et al. (2020); Kumar et al. (2021) with 3 convolutional layers borrowed from the nature DQN network and then a hidden feedforward layer of size 512.

BRAC. Behavior-regularized actor-critic (Wu et al., 2019) is a policy-constraint based actor-critic offline RL algorithm which regularizes the policy to stay close to the behavior policy π_β to prevent the selection of "out-of-distribution" actions. In addition, BRAC subtracts this divergence estimate from the target Q-values when performing the backup, to specifically penalize target values that come from out-of-distribution action inputs at the next state $(\mathbf{s}', \mathbf{a}')$.

$$\text{Q-function:} \quad \min_\theta \ \mathbb{E}_{\mathbf{s},\mathbf{a}\sim\mathcal{D}} \left[\left(r(\mathbf{s},\mathbf{a}) + \gamma\mathbb{E}_{\mathbf{a}'\sim\pi_\phi(\cdot|\mathbf{s}')}[\bar{Q}_\theta(\mathbf{s}',\mathbf{a}') + \beta\log\hat{\pi}_\beta(\mathbf{a}'|\mathbf{s}')] - Q_\theta(\mathbf{s},\mathbf{a}) \right)^2 \right].$$

$$\text{Policy:} \quad \max_\phi \ \mathbb{E}_{\mathbf{s}\sim\mathcal{D},\mathbf{a}\sim\pi_\phi(\cdot|\mathbf{s})} \left[Q_\theta(\mathbf{s},\mathbf{a}) + \beta\log\hat{\pi}_\beta(\mathbf{a}|\mathbf{s}) - \alpha\log\pi_\phi(\mathbf{a}|\mathbf{s}) \right]. \quad (\text{E.2})$$

COG. COG (Singh et al., 2020) is an algorithmic framework for utilizing large, unlabeled datasets of diverse behavior to learn generalizable policies via offline RL. Similar to real-world scenarios where large unlabeled datasets are available alongside limited task-specific data, the agent is provided with two types of datasets. The task-specific dataset consists of behavior relevant for the task, but the prior dataset can consist of a number of random or scripted behaviors being executed in the same environment/setting. The goal in this task is to actually stitch together relevant and overlapping parts of different trajectories to obtain a good policy that can work from a new initial condition that was not seen in a trajectory that actually achieved the reward. COG utilizes CQL as the base offline RL algorithm, and following Singh et al. (2020), we fix the hyperparameter $\alpha = 1.0$ in the CQL part for both base COG and COG + DR3. All other hyperparameters including network sizes, etc are kept fixed as the prior work Singh et al. (2020) as well.

E.2 TASKS AND ENVIRONMENTS USED

Atari 2600 games used. For all our experiments, we used the same set of 17 games utilized by Kumar et al. (2021) to test rank collapse. In the case of Atari, we used the 5 standard games (ASTERIX, QBERT, PONG, SEAQUEST, BREAKOUT) for tuning the hyperparameters, a strategy followed by several prior works (Gulcehre et al., 2020; Agarwal et al., 2020; Kumar et al., 2021). The 17 games we test on are: ASTERIX, QBERT, PONG, SEAQUEST, BREAKOUT, DOUBLE DUNK, JAMES BOND, MS. PACMAN, SPACE INVADERS, ZAXXON, WIZARD OF WOR, YARS' REVENGE, ENDURO, ROAD RUNNER, BEAMRIDER, DEMON ATTACK, ICE HOCKEY.

Following Agarwal et al. (2021), we report interquartile mean (IQM) normalized scores across all runs as mean scores can be dominated by performance on a few outlier tasks while median is independent of performance on all except 1 task – zero score on half of the tasks would not affect the median. IQM which corresponds to 25% trimmed mean and considers the performance on middle 50% of the runs. IQM interpolates between mean and median, which correspond to 0% and almost 50% trimmed means across runs.

D4RL tasks used. For our experiments on D4RL, we utilize the Gym-MuJoCo-v0 environments for evaluating BRAC, since BRAC performed somewhat reasonably on these domains (Fu et al., 2020), whereas we use the harder AntMaze and Franka Kitchen domains for evaluating CQL, since these domains are challenging for CQL (Kumar et al., 2020b).

Table E.1: **Hyperparameters used by the offline RL Atari agents in our experiments.** Following Agarwal et al. (2020), the Atari environments used by us are stochastic due to sticky actions, *i.e.*, there is a 25% chance at every time step that the environment will execute the agents previous action again, instead of the new action commanded. We report offline training results with same hyperparameters over 5 random seeds of the offline dataset, game simulator and network initialization.

Hyperparameter	Setting (for both variations)
Sticky actions	Yes
Sticky action probability	0.25
Grey-scaling	True
Observation down-sampling	(84, 84)
Frames stacked	4
Frame skip (Action repetitions)	4
Reward clipping	[-1, 1]
Terminal condition	Game Over
Max frames per episode	108K
Discount factor	0.99
Mini-batch size	32
Target network update period	every 2000 updates
Training environment steps per iteration	250K
Update period every	4 environment steps
Evaluation ϵ	0.001
Evaluation steps per iteration	125K
Q-network: channels	32, 64, 64
Q-network: filter size	$8 \times 8, 4 \times 4, 3 \times 3$
Q-network: stride	4, 2, 1
Q-network: hidden units	512

Robotic manipulation tasks from COG (Singh et al., 2020). These tasks consist of a 6-DoF WidowX robot, placed in front of two drawers and a larger variety of objects. The robot can open or close a drawer, grasp objects from inside the drawer or on the table, and place them anywhere in the scene. The task here consists of taking an object out of a drawer. A reward of +1 is obtained when the object has been taken out, and zero otherwise. There are two variants of this domain: **(1)** in the first variant, the drawer starts out closed, the top drawer starts out open (which blocks the handle for the lower drawer), and an object starts out in front of the closed drawer, which must be moved out of the way before opening, and **(2)** in the second variant, the drawer is blocked by an object, and this object must be removed before the drawer can be opened and the target object can be grasped from the drawer. The prior data for this environment is collected from a collection of scripted randomized policies. These policies are capable of opening and closing both drawers with 40-50% success rates, can grasp objects in the scene with about a 70% success rate, and place those objects at random places in the scene (with a slight bias for putting them in the tray).

E.3 THE DR3 REGULARIZER COEFFICIENT

We utilize identical hyperparameters of the base offline RL algorithms when DR3 is used, where the base hyper-parameters correspond to the ones provided in the corresponding publications. DR3 requires us to tune the additional coefficient c_0, that weights the DR3 explicit regularizer term. In order to find this value on our domains, we followed the tuning strategy typically followed on Atari, where we evaluated four different values of $c_0 \in \{0.001, 0.01, 0.03, 0.3\}$ on 5 games (ASTERIX, SEAQUEST, BREAKOUT, PONG and SPACEINVADERS) on the 5% replay dataset settings, picked c_0 that wprked best on just these domains, and used it to report performance on all 17 games, across all dataset settings (1% replay and 10% initial replay) in Section 6. This protocol is standard in Atari and has been used previously in Agarwal et al. (2020); Gulcehre et al. (2020); Kumar et al. (2021) in the context of offline RL. The value of the coefficient found using this strategy was $c_0 = 0.001$ for REM and $c_0 = 0.03$ for CQL.

For CQL on D4RL, we ran DR3 with multiple values of $c_0 \in \{0.0001, 0.001, 0.01, 0.5, 1.0, 10.0\}$, and picked the smallest value of c_0 which did not lead to eventually divergent (either negatively diverging or positively diverging) Q-values, in average. For the antmaze domains, this corresponded to $c_0 = 0.001$ and for the FrankaKitchen domains, this corresponded to $c_0 = 1.0$.

F   COMPLETE RESULTS ON ALL DOMAINS

In this section, we present the results obtained by running DR3 on the Atari and D4RL domains which were not discussed in the main paper due to lack of space. We first understand the effect of applying DR3 on BRAC (Wu et al., 2019), which was missing from the main paper, and then present the per-game Atari results.

Table F.1: Normalized interquartile mean (IQM) final performance (last iteration return) of CQL, CQL + DR3, REM and REM + DR3 after 6.5M gradient steps for the 1% setting and 12.5M gradient steps for the 5%, 10% settings. Intervals in brackets show 95% CIs computed using stratified percentile bootstrap (Agarwal et al., 2021)

Data	CQL	CQL + DR3	REM	REM + DR3
1%	44.4 (31.0, 54.3)	**61.6** (39.1, 71.5)	0.0 (-0.7, 0.1)	**13.1** (9.9, 18.3)
5%	89.6 (67.9, 98.1)	**100.2** (90.6, 102.7)	3.9 (3.1, 7.6)	**74.8** (59.6, 84.4)
10%	57.4 (53.2, 62.4)	**67.0** (62.8, 73.0)	24.9 (15.0, 29.1)	**72.4** (65.7, 81.7)

Table F.2: **Performance of DR3 when applied in conjunction with BRAC (Wu et al., 2019).** Note that DR3 attains a larger final performance (at the end of 2M steps of training) as well as a higher average performance (i.e. stability score) across all iterations of training.

Task	Average Performance across Iterations		Final Performance	
	BRAC	BRAC + DR3	BRAC	BRAC + DR3
halfcheetah-expert-v0	1.7 ± 1.9	49.9 ± 16.7	2.1 ± 3.3	71.5 ± 24.9
halfcheetah-medium-v0	43.5 ± 0.2	43.2 ± 0.2	45.1 ± 0.8	44.9 ± 0.6
halfcheetah-medium-expert-v0	17.0 ± 5.4	6.0 ± 5.5	24.8 ± 9.3	6.7 ± 7.3
halfcheetah-random-v0	24.4 ± 0.4	18.4 ± 0.3	24.9 ± 0.8	18.2 ± 1.0
halfcheetah-medium-replay-v0	44.9 ± 0.3	44.1 ± 0.4	45.0 ± 1.4	44.9 ± 0.5
hopper-expert-v0	15.7 ± 1.5	21.8 ± 3.2	16.6 ± 6.0	20.8 ± 5.3
hopper-medium-v0	32.8 ± 1.4	46.3 ± 7.1	36.2 ± 1.7	58.3 ± 13.7
hopper-medium-expert-v0	40.2 ± 5.7	37.0 ± 2.9	31.7 ± 11.8	21.8 ± 4.9
hopper-random-v0	11.7 ± 0.0	11.2 ± 0.0	12.2 ± 0.0	11.1 ± 0.0
hopper-medium-replay-v0	31.6 ± 0.3	30.3 ± 0.8	31.3 ± 1.2	36.1 ± 5.7
walker2d-expert-v0	25.5 ± 14.4	33.6 ± 11.8	54.0 ± 31.0	60.6 ± 20.2
walker2d-medium-v0	81.3 ± 0.3	80.8 ± 0.2	83.8 ± 0.2	83.4 ± 0.3
walker2d-medium-expert-v0	5.8 ± 5.2	6.4 ± 3.4	22.4 ± 22.0	39.5 ± 23.3
walker2d-random-v0	1.4 ± 0.8	1.7 ± 0.9	0.0 ± 0.1	2.9 ± 2.1
walker2d-medium-replay-v0	26.1 ± 6.4	47.4 ± 4.1	11.7 ± 7.0	38.7 ± 9.6

Table F.4: **Mean evaluation returns per Atari game across 5 runs with standard deviations for 1% dataset**. The coefficient for DR3 is 0.03 with a CQL coefficient of 1.0. The average performance is computed over 20 checkpoints spaced uniformly over training for 100 iterations where 1 iteration corresponds to 62,500 gradient updates.

Game	Final Performance		Average Performance across Iterations	
	CQL	CQL + DR3	CQL	CQL + DR3
Asterix	656.9 ± 91.0	821.4 ± 75.1	650.2 ± 65.3	814.1 ± 25.1
Breakout	23.9 ± 3.8	32.0 ± 3.2	23.8 ± 0.5	32.8 ± 3.1
Pong	16.7 ± 1.7	14.2 ± 3.3	15.7 ± 2.0	15.1 ± 2.3
Seaquest	449.0 ± 11.0	446.6 ± 26.9	474.5 ± 30.3	456.1 ± 17.0
Qbert	8033.8 ± 1513.2	9162.7 ± 993.6	7980.0 ± 379.9	9000.7 ± 225.2
SpaceInvaders	386.0 ± 123.2	351.9 ± 77.1	371.7 ± 47.5	440.6 ± 29.6
Zaxxon	829.4 ± 813.3	1757.4 ± 879.4	834.6 ± 504.0	1634.0 ± 673.9
YarsRevenge	11848.2 ± 2977.7	16011.3 ± 1409.0	15077.9 ± 1301.9	17741.6 ± 613.6
RoadRunner	37000.7 ± 1148.5	24928.7 ± 7484.5	35899.9 ± 653.1	32063.3 ± 1011.4
MsPacman	1869.8 ± 167.2	2245.7 ± 193.8	1991.9 ± 55.1	2224.1 ± 80.8
BeamRider	780.3 ± 64.5	617.9 ± 25.1	782.0 ± 36.1	619.9 ± 20.9
Jamesbond	558.5 ± 124.8	460.5 ± 102.0	524.6 ± 118.5	484.2 ± 89.4
Enduro	198.4 ± 34.2	253.5 ± 14.2	259.8 ± 16.4	276.1 ± 16.9
WizardOfWor	771.1 ± 358.2	904.6 ± 343.7	833.7 ± 168.4	935.2 ± 174.4
IceHockey	-8.7 ± 1.3	-7.8 ± 0.9	-8.8 ± 0.9	-7.9 ± 0.7
DoubleDunk	-15.1 ± 1.9	-14.0 ± 2.8	-15.3 ± 0.9	-14.5 ± 1.0
DemonAttack	1970.2 ± 161.3	386.2 ± 75.3	1338.8 ± 298.4	414.0 ± 46.0

Table F.5: **Mean evaluation returns per Atari game across 5 runs with standard deviations for 5% dataset.** The coefficient for DR3 is 0.03 with a CQL coefficient of 0.1. The average performance is computed over 20 checkpoints spaced uniformly over training for 200 iterations where 1 iteration corresponds to 62,500 gradient updates.

Game	Final Performance		Average Performance across Iterations	
	CQL	CQL + DR3	CQL	CQL + DR3
Asterix	1798.2 ± 168.6	3318.5 ± 301.7	1812.7 ± 64.0	3790.5 ± 218.0
Breakout	94.1 ± 44.4	166.0 ± 23.1	105.1 ± 10.4	196.5 ± 4.4
Pong	13.1 ± 4.2	17.9 ± 1.1	15.2 ± 1.3	17.4 ± 1.2
Seaquest	1815.9 ± 722.8	2030.7 ± 822.8	1382.3 ± 258.1	3722.3 ± 969.5
Qbert	10595.7 ± 1648.5	9605.6 ± 1593.5	9552.0 ± 925.6	10830.7 ± 783.1
SpaceInvaders	758.9 ± 56.9	1214.6 ± 281.8	662.0 ± 58.1	1323.7 ± 94.4
Zaxxon	1501.0 ± 1165.7	4250.1 ± 626.2	1508.8 ± 437.5	3556.5 ± 531.3
YarsRevenge	24036.7 ± 3370.6	17124.7 ± 2125.6	22733.1 ± 1175.3	18339.8 ± 1299.7
RoadRunner	40728.4 ± 3318.9	38432.6 ± 1539.7	42338.4 ± 471.4	41260.2 ± 1008.6
MsPacman	2975.9 ± 522.1	2790.6 ± 353.1	2923.6 ± 251.3	3101.2 ± 381.6
BeamRider	1897.6 ± 473.7	785.8 ± 43.5	2218.5 ± 242.4	775.9 ± 12.5
Jamesbond	108.8 ± 49.1	96.8 ± 43.2	76.5 ± 4.6	106.1 ± 34.8
Enduro	764.3 ± 168.7	938.5 ± 63.9	797.7 ± 47.8	923.2 ± 40.3
WizardOfWor	943.2 ± 380.3	612.0 ± 343.3	1004.3 ± 314.7	1007.4 ± 313.2
IceHockey	-17.3 ± 0.6	-15.0 ± 0.7	-16.6 ± 0.5	-12.0 ± 0.3
DoubleDunk	-18.1 ± 1.5	-16.2 ± 1.7	-17.3 ± 1.0	-16.0 ± 1.6
DemonAttack	4055.8 ± 499.7	8517.4 ± 1065.9	4062.4 ± 465.8	8396.7 ± 689.4

Table F.6: **Mean returns per Atari game across 5 runs with standard deviations for initial 10% dataset.** The coefficient for DR3 is 0.03 with a CQL coefficient of 0.1. The average performance is computed over 20 checkpoints spaced uniformly over training for 200 iterations.

Game	Final Performance		Average Performance across Iterations	
	CQL	CQL + DR3	CQL	CQL + DR3
Asterix	2803.9 ± 294.6	3906.2 ± 521.3	2903.2 ± 217.7	4692.2 ± 377.0
Breakout	64.7 ± 7.3	70.8 ± 5.5	65.6 ± 5.7	75.4 ± 6.0
Pong	5.3 ± 6.8	5.5 ± 6.2	7.3 ± 5.0	8.1 ± 5.2
Seaquest	222.3 ± 219.5	1313.0 ± 220.0	704.9 ± 254.5	1327.9 ± 250.0
Qbert	4803.2 ± 489.5	5395.3 ± 1003.6	4492.5 ± 240.8	4708.5 ± 463.0
SpaceInvaders	704.9 ± 121.5	938.1 ± 80.3	737.8 ± 23.8	902.1 ± 60.0
Zaxxon	231.6 ± 450.9	836.8 ± 434.7	394.4 ± 385.1	725.7 ± 370.3
YarsRevenge	13076.2 ± 2427.0	12413.9 ± 2869.7	12493.2 ± 543.6	12395.6 ± 1044.2
RoadRunner	45063.5 ± 1749.7	45336.9 ± 1366.7	45522.7 ± 1068.1	44808.0 ± 911.7
MsPacman	2459.5 ± 381.3	2427.5 ± 191.3	2528.1 ± 149.2	2488.3 ± 109.8
BeamRider	4200.7 ± 470.2	3468.0 ± 238.0	4729.5 ± 94.8	3344.3 ± 289.0
Jamesbond	84.6 ± 25.4	89.7 ± 15.6	108.7 ± 34.1	111.7 ± 10.9
Enduro	946.7 ± 289.7	1160.2 ± 81.5	1013.9 ± 29.7	1136.2 ± 32.5
WizardOfWor	520.4 ± 451.2	764.7 ± 250.0	499.8 ± 238.5	792.2 ± 101.3
IceHockey	-18.1 ± 0.7	-16.0 ± 1.3	-17.6 ± 0.5	-15.2 ± 1.0
DoubleDunk	-21.2 ± 1.1	-20.6 ± 1.0	-20.6 ± 0.3	-19.7 ± 0.5
DemonAttack	4145.2 ± 400.6	7152.9 ± 723.2	4839.4 ± 586.7	7278.5 ± 701.3

Table F.7: **Mean returns per Atari game across 5 runs with standard deviations for 1% dataset.** The coefficient for DR3 is 0.001 while we use a multi-headed REM with 200 Q-heads (Agarwal et al., 2020). The average performance is computed over 20 checkpoints spaced uniformly over training for 100 iterations.

Game	Final Performance		Average Performance across Iterations	
	REM	REM + DR3	REM	REM + DR3
Asterix	240.4 ± 29.1	405.7 ± 46.5	304.4 ± 9.3	413.7 ± 39.6
Breakout	0.7 ± 0.7	14.3 ± 2.8	6.3 ± 1.0	10.3 ± 1.1
Pong	-14.2 ± 1.7	-7.7 ± 6.3	-14.1 ± 2.2	-15.3 ± 3.0
Seaquest	81.0 ± 78.5	293.3 ± 191.5	246.6 ± 49.5	489.9 ± 128.6
Qbert	239.6 ± 133.2	436.3 ± 111.5	255.5 ± 76.0	471.0 ± 116.5
SpaceInvaders	152.8 ± 27.5	206.6 ± 77.6	188.6 ± 5.8	262.7 ± 22.4
Zaxxon	534.9 ± 731.3	2596.4 ± 1726.4	1807.9 ± 478.2	707.7 ± 577.4
YarsRevenge	1452.6 ± 1631.0	5480.2 ± 962.3	4018.8 ± 987.8	7352.0 ± 574.7
RoadRunner	0.0 ± 0.0	3872.9 ± 1616.4	1601.2 ± 637.9	14231.9 ± 2406.0
MsPacman	698.8 ± 129.5	1275.1 ± 345.6	690.4 ± 69.7	860.4 ± 57.1
BeamRider	703.0 ± 97.4	522.9 ± 42.2	745.5 ± 30.7	592.2 ± 27.7
Jamesbond	41.0 ± 27.0	157.6 ± 65.0	53.3 ± 12.1	88.8 ± 27.2
Enduro	0.5 ± 0.4	132.4 ± 16.1	21.7 ± 4.0	197.5 ± 19.1
WizardOfWor	362.5 ± 321.8	1663.7 ± 417.8	552.1 ± 253.1	1460.8 ± 194.8
IceHockey	-16.7 ± 0.9	-9.1 ± 5.1	-12.1 ± 0.8	-4.8 ± 1.8
DoubleDunk	-21.8 ± 1.0	-17.6 ± 1.5	-20.4 ± 0.6	-17.1 ± 1.6
DemonAttack	102.0 ± 17.3	162.0 ± 34.7	124.0 ± 10.7	145.6 ± 27.2

Table F.8: **Mean returns per Atari game across 5 runs with standard deviations for the 5% dataset.** The coefficient for DR3 is 0.001 while we use a multi-headed REM with 200 Q-heads (Agarwal et al., 2020). The average performance is computed over 20 checkpoints spaced uniformly over training for 200 iterations.

Game	Final Performance		Average Performance across Iterations	
	REM	REM + DR3	REM	REM + DR3
Asterix	876.8 ± 201.1	2317.0 ± 838.1	958.9 ± 50.9	1252.6 ± 395.1
Breakout	15.2 ± 4.9	33.4 ± 4.0	16.3 ± 3.4	17.7 ± 2.4
Pong	7.5 ± 5.2	-0.7 ± 9.9	-4.7 ± 3.0	-12.0 ± 3.2
Seaquest	1276.0 ± 417.3	2753.6 ± 1119.7	1484.3 ± 367.7	1602.0 ± 603.7
Qbert	2421.4 ± 1841.8	7417.0 ± 2106.7	1330.7 ± 431.0	4045.8 ± 898.9
SpaceInvaders	431.5 ± 23.3	443.5 ± 67.4	349.5 ± 22.6	362.1 ± 33.6
Zaxxon	6738.2 ± 966.6	1609.7 ± 1814.1	3630.7 ± 751.4	346.1 ± 512.1
YarsRevenge	14454.2 ± 1644.4	16930.4 ± 2625.8	14628.3 ± 1945.1	12936.5 ± 1286.0
RoadRunner	15570.9 ± 12795.6	46601.6 ± 2617.2	22740.3 ± 1977.2	33554.1 ± 1880.4
MsPacman	1272.2 ± 215.3	2303.1 ± 202.7	1147.7 ± 126.1	1438.7 ± 140.4
BeamRider	1922.5 ± 589.1	674.8 ± 21.4	886.9 ± 82.1	698.3 ± 21.5
Jamesbond	189.6 ± 77.0	130.5 ± 45.7	120.2 ± 9.3	88.6 ± 41.5
Enduro	172.7 ± 55.9	583.9 ± 108.7	236.8 ± 11.3	457.7 ± 39.3
WizardOfWor	838.4 ± 670.0	2661.6 ± 371.4	1281.3 ± 66.7	1863.7 ± 261.2
IceHockey	-9.7 ± 4.2	-6.5 ± 3.1	-8.1 ± 0.7	-4.1 ± 1.5
DoubleDunk	-18.4 ± 0.9	-17.6 ± 2.6	-19.6 ± 1.0	-17.8 ± 1.9
DemonAttack	507.7 ± 120.1	5602.3 ± 1855.5	581.6 ± 207.0	1452.3 ± 765.0

Table F.9: **Mean returns per Atari game across 5 runs with standard deviations for initial 10% dataset.** The coefficient for DR3 is 0.001 while we use a multi-headed REM with 200 Q-heads (Agarwal et al., 2020). The average performance is computed over 20 checkpoints spaced uniformly over training for 200 iterations.

Game	Final Performance		Average Performance across Iterations	
	REM	REM + DR3	REM	REM + DR3
Asterix	2254.7 ± 403.6	5122.9 ± 328.9	2684.6 ± 184.4	3432.1 ± 257.5
Breakout	81.2 ± 13.9	96.8 ± 21.2	63.5 ± 4.6	62.4 ± 6.1
Pong	8.8 ± 3.1	7.6 ± 11.1	2.6 ± 2.1	-2.5 ± 5.6
Seaquest	1540.2 ± 354.6	981.3 ± 605.9	1029.5 ± 260.6	836.2 ± 234.3
Qbert	4330.7 ± 250.2	4126.2 ± 495.7	3478.0 ± 248.0	3494.7 ± 380.3
SpaceInvaders	895.2 ± 68.3	799.0 ± 28.3	699.7 ± 31.4	653.1 ± 21.5
Zaxxon	950.7 ± 897.4	0.0 ± 0.0	490.2 ± 306.6	0.0 ± 0.0
YarsRevenge	10913.1 ± 1519.1	11924.8 ± 2413.8	11508.5 ± 290.0	10977.7 ± 1026.9
RoadRunner	45521.7 ± 2502.1	49129.4 ± 1887.9	37997.4 ± 638.6	41995.2 ± 1482.1
MsPacman	2177.4 ± 393.0	2268.8 ± 455.0	1930.5 ± 141.7	2126.6 ± 147.6
BeamRider	2921.7 ± 308.7	4154.9 ± 357.2	3727.5 ± 304.3	2871.0 ± 44.3
Jamesbond	197.8 ± 73.8	149.3 ± 304.5	149.0 ± 120.5	83.3 ± 162.4
Enduro	529.5 ± 200.7	832.5 ± 65.5	584.6 ± 85.3	801.8 ± 39.3
WizardOfWor	606.5 ± 823.2	920.0 ± 497.0	838.3 ± 343.7	926.3 ± 318.5
IceHockey	-4.3 ± 0.6	-5.9 ± 5.1	-7.0 ± 1.1	-5.4 ± 3.7
DoubleDunk	-17.7 ± 3.9	-19.5 ± 2.5	-16.9 ± 0.5	-16.7 ± 1.0
DemonAttack	6097.9 ± 1251.3	9674.7 ± 1600.6	4649.1 ± 514.6	5141.9 ± 361.4

Table F.10: Average returns across 5 runs for the random agent and the average performance of the trajectories in the DQN (Nature) dataset. For Atari normalized scores reported in the paper, the random agent is assigned a score of 0 while the average DQN replay is assigned a score of 100. Note that the random agent scores are also evaluated on Atari 2600 games with sticky actions.

Game	Random	Average DQN-Replay
Asterix	279.1	3185.2
Breakout	1.3	104.9
Pong	-20.3	14.5
Seaquest	81.8	1597.4
Qbert	155.0	8249.7
SpaceInvaders	149.5	1529.8
Zaxxon	10.6	1854.1
YarsRevenge	3147.7	21015.0
RoadRunner	15.5	38352.3
MsPacman	248.0	3108.8
BeamRider	362.0	4576.4
Jamesbond	27.6	560.3
Enduro	0.0	671.9
WizardOfWor	686.6	1128.5
IceHockey	-9.8	-8.5
DoubleDunk	-18.4	-11.3
DemonAttack	166.0	4407.5