Learning to Generate Questions by Recovering Answer-containing Sentences

Abstract

To train a question answering model based on machine reading comprehension (MRC), significant effort is required to prepare annotated training data composed of questions and their answers from contexts. To mitigate this issue, recent research has focused on synthetically generating a question from a given context and an annotated (or generated) answer by training an additional generative model, which can be utilized to augment the training data. In light of this research direction, we propose a novel pre-training approach that learns to generate contextually rich questions, by recovering answer-containing sentences. Our approach is composed of two novel components, (1) dynamically determining K answers from a given document and (2) pre-training the question generator on the task of generating the answer-containing sentence. We evaluate our method against existing ones in terms of the quality of generated questions as well as the fine-tuned MRC model accuracy after training on the data synthetically generated by our method. Experimental results demonstrate that our approach consistently improves the question generation capability of existing models such as UniLM, and shows state-of-the-art results on MS MARCO and NewsQA, and comparable results to the state-of-the-art on SQuAD. Additionally, we demonstrate that the data synthetically generated by our approach is beneficial for boosting up the downstream MRC accuracy across a wide range of datasets, such as SQuAD-v1.1, v2.0, and KorQuAD, without any modification to the existing MRC models. Furthermore, our experiments highlight that our method shines especially when a limited amount of training data is given, in terms of both pre-training and downstream MRC data.

1 Introduction

Machine reading comprehension (MRC), which finds the answer to a given question from its accompanying paragraphs (called context), is an essential task in natural language processing. With the release of high-quality human-annotated datasets for this task, such as SQuAD-v1.1 (Rajpurkar et al., 2016), SQuAD-v2.0 (Rajpurkar et al., 2018), and KorQuAD (Lim et al., 2019), researchers have proposed MRC models even surpassing human performance. These datasets commonly involve finding a snippet within a context as an answer to a given question.

However, these datasets require significant amount of human effort to create questions and their relevant answers from given contexts. Often the size of the annotated data is relatively small compared to that of data used in other self-supervised tasks such as language modeling, limiting the accuracy.

To overcome this issue, researchers have studied models for generating synthetic questions from a given context along with annotated (or generated) answers on large corpora such as Wikipedia. Golub et al. (2017) suggest a two-stage network of generating question-answer pairs which first chooses answers conditioned on the paragraph and then generates a question conditioned on the chosen answer. Dong et al. (2019) showed that pre-training on unified language modeling from large corpora including Wikipedia improves the question generation capability. Similarly, Alberti et al. (2019) introduced a self-supervised pre-training technique for question generation via the next-sentence generation task.

However, self-supervised pre-training techniques such as language modeling or next sentence generation are not specifically conditioned on the candidate answer and instead treat it like any other

Figure 1: Architecture of a simple generative model, BertGen. When applying our training method "ASGen" to the model, the question generator takes as input the answer and the context with the answer-containing sentence removed and generates the missing answer-containing sentence.

phrase, despite the candidate answer being a strong conditional restriction for the question generation task. Also, not all sentences from a paragraph may be relevant to the questions or answers, so their generation may not be an ideal candidate question generation tasks. Moreover, choosing the number of candidate answers when they are not annotated will help to avoid generating too few or lower-quality answers.

To address these issues, we propose a novel training method called Answer-containing Sentence Generation (ASGen) for a question generator. ASGen is composed of two steps: (1) dynamically predicting K answers to generate diverse questions and (2) pre-training the question generator on the answer-containing sentence generation task. We evaluate our method against existing ones in terms of the generated question quality as well as the fine-tuned MRC model accuracy after training on the data synthetically generated by our method.

Experimental results demonstrate that our approach consistently improves the question generation quality of existing models such as UniLM (Dong et al., 2019) and shows state-of-the-art results on MS MARCO (Nguyen et al., 2016), NewsQA (Trischler et al., 2017) as well as comparable results to the state-of-the-art on SQuAD. Additionally, we demonstrate that the synthetically generated data by our approach can boost up downstream MRC accuracy across a wide range of datasets, such as SQuAD-v1.1, v2.0, and KorQuAD, without any modification to the existing MRC models. Furthermore, our experiments highlight that our method shines especially when a limited amount of training data is given, in terms of both pre-training and downstream MRC data.

2 PROPOSED METHOD

This section discusses our proposed training method called Answer-containing Sentence Generation (ASGen). While ASGen can be applied to any generative model, we use a simple Transformer (Vaswani et al., 2017) based generative model as our baseline, which we call BertGen. First, we will describe how the BertGen model generates synthetic questions and answers from a context. Next, we will explain the novel components of our methods and how we pre-trained the question generator in BertGen based on them. BertGen encodes given paragraphs with two networks, the answer generator and the question generator.

Answer Generator. To make the contextual embeddings and to predict answer spans for a given context without the question, we utilize a BERT (Devlin et al., 2019) encoder (Fig. 1-(1), BERT Encoder-A). We estimate the number of answer candidates K by applying a fully connected layer on the contextual embedding of BERT's classification token "[CLS]". Depending on the estimated number K, we select the K top candidate answer spans from the context. We use the K selected answer spans as input to the question generator.

Question Generator. Next, we generate a question conditioned on each answer predicted from the answer generator. Specifically, we give as input to a BERT encoder the context and an indicator for the answer span location in the context (Fig. 1-(2), BERT Encoder-Q). Next, a Transformer decoder generates the question word-by-word based on the encoded representation of the context

and the answer span. When pre-training the question generator on an answer-containing sentence generation task, we exclude the answer-containing sentence from the original context and train the model to generate the excluded sentence given the modified context and the answer span as input.

Finally, we generate synthetic questions and answers from a large corpus, e.g., all the paragraphs in Wikipedia. After generating this data, we train the MRC model on the generated data in the first phase and then fine-tune on the downstream MRC dataset (e.g., SQuAD) in the second phase. In this paper, we use BERT as the default MRC model, since BERT or its variants achieve state-of-the-art performance across numerous MRC tasks.

2.1 DYNAMIC ANSWER PREDICTION

We predict the number of answers K in a given context, $W = \{\mathbf{w}_t\}_{t=0}^{T}$, using regression as

$$\{\mathbf{w}_t^{enc}\}_{t=0}^{T} = \text{BERT Encoder-A}(W),$$
$$K = \lfloor f_k(\mathbf{w}_0^{enc}) \rfloor,$$

where T is the number of word tokens in the context, and position 0 reserved for classification token '[CLS]'. f_k represents a fully connected unit with two hidden layers that have hidden dimensions equal to H and 1, respectively, where H is the hidden dimension of BERT Encoder-A. For training, we use the mean squared error loss between K and ground-truth number of answers K^{gt}.

To calculate the score s_i for start index i of a predicted answer span, we compute the dot product of the encoder output with a trainable vector $\mathbf{v}_s$. For each start index i, we calculate the span end index score $e_{i,j}$ for index j in a similar manner with a trainable vector $\mathbf{v}_e$, i.e.,

$$s_i = \mathbf{v}_s \circ \mathbf{w}_i^{enc},$$
$$e_{i,j} = \mathbf{v}_e \circ f_s(\mathbf{w}_j^{enc} \oplus \mathbf{w}_i^{enc}),$$

where f_s represents a fully connected layer with hidden dimension H and $\oplus$ indicates the concatenation operation. For training, we use cross-entropy loss on the s_i, $e_{i,j}$ and ground truth start, end of the answer span for each token. Predicting the number of answers and the answer span are jointly trained to minimize the sum of their respective losses.

During inference, we choose the K top answer spans with the highest score summation of start index score and end index score, i.e.,

$$A^{span} = \{(i,j) \mid 1 \leq i < T \text{ and } i \leq j < T\},$$
$$a_k = \max(\{a \mid \#\{(i,j) \mid (i,j) \in A^{span} \text{ and } s_i + e_{i,j} \geq a\} = K\}),$$
$$A_k^{span} = \{(i,j) \mid (i,j) \in A^{span} \text{ and } s_i + e_{i,j} \geq a_k\}.$$

The K selected answer spans A_k^{span} are then given to the question generator as input in the form of an indication of the answer span location in the given context.

2.2 PRE-TRAINING QUESTION GENERATOR

In order to generate questions conditioned on different answers that may arise in a context, we generate a question for each of the K answers. Alberti et al. (2019) proposed to pre-train this generation model using self-supervised tasks such as language modeling or next-sentence generation. We identify several issues with this approach. This technique is not specifically conditioned on the answer, despite the answer being a strong condition for the question generation task. Also, not all sentences from a paragraph may be relevant to the questions or answers from within that paragraph, so their generation is not an ideal candidate for pre-training question generation model.

To address these issues, we modify the context to exclude the sentence containing the previously generated answer and pre-train the question generation model on the task of generating this excluded answer-containing sentence, conditioned on the answer and the modified context.

Specifically, we exclude answer-containing sentence S^{ans} while retaining the answer, modifying the original context D to D^{ans} as

$$S^{start} = \{p \mid \text{sentence start index} = p\} \cup \{T\},$$
$$S^{ans} = \{(p_s, p_e, i, j) \mid \max(\{p \leq i\})_s, \min(\{p \geq j\})_e\},$$
$$D^{ans} = [D_{[:p_s]}; D_{[i:j]}; D_{[p_e:]}], (p_s, p_e, i, j) \in S^{ans},$$

where $(i, j) \in A_k^{span}$. Note that we change S^{ans} to not exclude the answer-containing sentence for fine-tuning the question generator, i.e.,

$$S^{ans} = \{(p_s, p_e, i, j) | p_s = i, p_e = j\}.$$

In BertGen, we pass the previously generated answer to the generation model in the form of an additional position encoding M^{ans} that indicates the answer location within the context, i.e.,

$$M^{ans} = [\mathbf{m}_0 * p_s; \mathbf{m}_1 * (j - i); \mathbf{m}_0 * (T - p_e)],$$

where $\mathbf{m}_0$ and $\mathbf{m}_1$ indicate trainable vectors corresponding to encoding id 0 and 1, respectively. That is, we assign the encoding id for each word in the context as 0 and each word in the answer as 1. $A * B$ indicates the operation of stacking vector A for B many times.

Next, we generate answer-containing sentence output embedding $W^o = \{\mathbf{w}_t^o\}_0^T$ using as

$$C^{enc} = \text{BERT Encoder-Q}(D^{ans}, M^{ans}),$$
$$\mathbf{w}_t^g = \text{Transformer Decoder}(\{\mathbf{w}_i^g\}_{i=0}^{t-1}, C^{enc}),$$
$$\{\mathbf{w}_t^o\}_{t=0}^T = \{\text{Softmax}(\mathbf{w}_t^g E)\}_{t=0}^T,$$

where C^{enc} is encoded representation of the context and $E \in \mathbb{R}^{d \times D}$ represents a word embedding matrix with vocabulary size D shared between the BERT Encoder-Q and the Transformer decoder.

Finally, we calculate the loss of the generated words using the cross-entropy loss as

$$\mathbb{L} = - \left(\sum_{t=1}^T \sum_{i=1}^D \mathbf{y}_{t,i} \log(\mathbf{w}_{t,i}^o) \right) / T,$$

where $\mathbf{y}$ indicates a ground-truth one-hot vector of the answer-containing sentence word. Note that $\mathbf{y}$ is the question word in the case of fine-tuning.

In this manner, we pre-train the question generation model using a task similar to the final task of conditionally generating the question from a given answer and a context.

3 EXPERIMENTAL SETUP

Pre-training Dataset. To build the dataset for answer-containing sentence generation tasks (AS-Gen) and the synthetic MRC data for pre-training the downstream MRC models, we collect all paragraphs from the entire English Wikipedia dump and synthetically generate questions and answers on these paragraphs. We apply filtering and clean-up steps that are detailed in the appendix.

Using BertGen, we generate 43M triples of question-answer-paragraph for the synthetic data. For pre-training on answer-containing sentence generation, we sample 25M answer-paragraph pairs (Full-Wiki) from the final Wikipedia dataset to avoid extremely short contexts less than 500 characters. For ablation studies on pre-training approaches, we sample 2.5M pairs (Small-Wiki)[1] from Full-Wiki and split 25K pairs (Test-Wiki) to evaluate the pre-training method.

Benchmark Datasets. In most MRC datasets, a question and a context are represented as a sequence of words, and the answer span (indices of start and end words) is annotated from the context words based on the question. Among these datasets, we choose SQuAD as the primary benchmark dataset for question generation, since it is the most popular human-annotated MRC dataset. For fair comparison with existing question generation methods, we use the same splits of SQuAD-v1.1, as previously done in Du et al. (2017), Kim et al. (2019), and Dong et al. (2019). We refer to this dataset as Split1. This split has 77K/10K/10K samples for train/dev/test sets. We also evaluate on the reversed dev-test split, referred to as Split2.[2] Additionally, we evaluate our question generation method on MS MARCO (Nguyen et al., 2016) and NewsQA (Trischler et al., 2017). For these datasets, we follow pre-processing of Tuan et al. (2020), sampling a subset of original data where the answers are sub-spans of their corresponding paragraphs to obtain train/dev/test sets with 51K/6K/7K samples for MS MARCO and 76K/4K/4K samples for NewsQA. To calculate the scores

---

[1] We use the Korean Wikipedia for KorQuAD, which is 15x smaller than English Wikipedia.
[2] We use the same splits as provided by Du et al. (2017)

Table 1: Comparison with existing question generation methods on the test set of SQuAD Split1 and Split2. Models marked as '*' indicate results we reproduced.

Generation Model	Split1			Split2		
	BLEU-4	METEOR	ROUGE-L	BLEU-4	METEOR	ROUGE-L
Du et al. (2017)	12.3	16.6	39.8	-	-	-
Zhao et al. (2018)*	13.0	18.2	41.2	15.1	19.5	43.4
ASs2s (Kim et al., 2019)	16.2	19.9	44.0	-	-	-
Zhao et al. (2018)	-	-	-	16.4	20.3	44.5
UniLM (Dong et al., 2019)	22.1	25.1	51.1	23.8	25.6	52.0
BertGen (Large) + ASGen	22.8	25.3	51.2	24.6	25.8	53.0
UniLM + ASGen	**23.7**	**25.9**	**52.3**	**25.3**	**26.7**	**53.3**

Table 2: Application of ASGen to other existing question generation models. BL-4, MTR, RG-L indicate BLEU-4, METEOR, ROUGE-L.

Test set on Split1	BL-4	MTR	RG-L
Zhao et al. (2018)*	13.0	18.2	41.2
+ ASGen	**14.2**	**19.4**	**42.8**
UniLM	22.1	25.1	51.1
+ ASGen	**23.7**	**25.9**	**52.2**
Test set on Split2	BL-4	MTR	RG-L
Zhao et al. (2018)*	15.1	19.5	43.4
+ ASGen	**16.4**	**20.6**	**44.7**
UniLM	23.8	25.6	52.0
+ ASGen	**25.3**	**26.7**	**53.3**

Table 3: Comparison with existing question generation methods on the test set of MS MARCO and NewsQA. (L) indicate (Large).

MS MARCO	BL-4	MTR	RG-L
Zhao et al. (2018)	17.2	-	-
Tuan et al. (2020)	18.3	19.4	42.8
Ma et al. (2020)	20.5	24.7	49.9
BertGen (L) + ASGen	**22.9**	**26.7**	**51.8**
NewsQA	BL-4	MTR	RG-L
Zhou et al. (2017)	9.9	16.7	42.3
Liu et al. (2019)	11.1	17.4	43.2
Tuan et al. (2020)	12.4	**19.0**	44.1
BertGen (L) + ASGen	**13.8**	18.6	**44.5**

BLEU-4 (Papineni et al., 2002a), METEOR (Banerjee & Lavie, 2005b), and ROUGE-L (Lin, 2004), we use the scripts from Du et al. (2017).

To evaluate the effectiveness of generated synthetic MRC data, we test the fine-tuned MRC model on the downstream MRC dataset after training on the generated synthetic data. We calculate the EM/F1 score of the MRC model on SQuAD-v1.1 and v2.0 development set. We also evaluate on the test set of KorQuAD, a Korean dataset created with the same procedure as SQuAD-v1.1.

Implementation Details. For all experiments and models, we use all official original hyper-parameters unless otherwise stated below. For BertGen model, we use pre-trained BERT (Base and Large) as encoder and 12 stacked layers of Transformer as decoder. For large version of the model, we use 24 layers of the encoder and the decoder with 737M parameters. For the generation of unanswerable questions in SQuAD-v2.0, we separate unanswerable and answerable cases and then train separate generation models. For all BertGen models, we pre-train the question generator for 5 epochs on Wikipedia and fine-tune it for 30 epochs on MRC dataset with batch size of 32. For other question generation models, we pre-train for 1 epoch on Wikipedia. The training time depends on the data size and the model complexity. For Zhao et al. (2018), pre-training on Full-Wiki takes only 48 hours. Pre-training BertGen on Small-Wiki in Table 4 takes 48 hours with 8 Tesla V100 GPU, resulting in 5.1, 4.3 BLEU-4 improvement on Split1, Split2 respectively. The pre-training for BertGen (Large) with Full-Wiki takes 1,224 hours and fine-tuning takes 72 hours. For MRC models, we use BERT (Large and WWM). Mecab (Papineni et al., 2002b) is used for Korean tokenizer.

Comparison of the Pre-training Method. We compare ASGen with a method from Alberti et al. (2019), which is pre-training on next-sentence generation task (NS), and with a method from Golub et al. (2017), which only trains the generative model on the final MRC dataset. We reproduced these methods on BertGen as described in their original work and evaluate question generation scores on the SQuAD splits as well as corresponding sentence generation scores on Test-Wiki.

Comparison of Downstream Results. To check the effectiveness of our method on downstream MRC tasks, we evaluate our generated synthetic data on SQuAD-v1.1, v2.0, and KorQuAD by training MRC models (BERT and BERT+CLKT) on generated data followed by fine-tuning on the

Table 4: Ablation of pre-training methods, i.e., pre-training on NS, ASGen, and ASGen without conditioning on a given answer (w/o A), on the test set of SQuAD splits. "Wiki" indicates the sentence generation score on Test-Wiki.

Table 5: Average of 10 human evaluation scores over 50 randomly picked samples from SQuAD. Each column indicates Syntax (ST), Semantics (SM), Context-Relevance (CR) and Answer-Relevance (AR) in the range 1 to 5.

Pre-train on Small-Wiki	Wiki	Split1	Split2
BertGen (w/o pre-train)	-	15.0	17.1
BertGen+NS	1.4	19.0	20.2
BertGen+ASGen w/o A	**5.2**	19.9	21.0
BertGen+ASGen	**5.2**	**20.1**	**21.4**
Pre-train on Full-Wiki	Wiki	Split1	Split2
BertGen+NS	3.4	20.6	22.6
BertGen+ASGen	8.2	22.2	24.2
BertGen(Large)+ASGen	**8.3**	**22.8**	**24.6**

Model	ST	SM	CR	AR
BertGen	4.04	3.93	4.20	3.25
BertGen+NS	4.60	4.54	4.49	3.63
BertGen+ASGen	**4.71**	**4.69**	**4.74**	**4.14**
UniLM	4.25	4.31	4.54	4.06
UniLM+ASGen	**4.71**	**4.79**	**4.70**	**4.17**

train set for each dataset. The structure of BERT+CLKT model is the same as that of original BERT except that the model is pre-trained for the Korean language. Due to the absence of common pre-trained BERT for Korean, we used this model as a baseline.

4 EXPERIMENTAL RESULTS

4.1 QUESTION AND ANSWER GENERATION

Comparison to Existing Methods. To evaluate ASGen, we fine-tune the question generation models on both SQuAD splits, after pre-training on answer-containing sentence generation task. As shown in Table 1, 'BertGen (Large) + ASGen' and 'UniLM + ASGen' outperforms UniLM on both splits. As shown in Table 3, 'BertGen (Large) + ASGen' outperforms all existing models on all scores on both MS MARCO and NewsQA, except for comparable METEOR scores in NewsQA.

Application to Existing Methods. As shown in Table 2, ASGen consistently improves the performance when applied to other question generation models such as Zhao et al. (2018) and UniLM across all metrics for both splits. In particular, applying ASGen on UniLM further improves its question generation capability, achieving BLEU-4, METEOR, and ROUGE-L as 23.7, 25.9, 52.2, and 25.3, 26.7, 53.3 on both splits, respectively. We reproduce Zhao et al. (2018) and use the official code of UniLM with no architecture changes or additional hyper-parameter tuning.

Ablation Study of Pre-training Task. We also compare the BLEU-4 scores between various pre-training tasks to show the effectiveness of ASGen. As shown in Table 4, ASGen outperforms NS in the recreation score of sentence on Test-Wiki, e.g. 5.2 vs. 1.4 in Small-Wiki and 8.2 vs. 3.4 in Full-Wiki. Also, ASGen outperforms NS in question generation, e.g. 22.2 vs. 20.6 and 24.2 vs. 22.6 in the two splits, respectively. We also observe that conditioning on a given answer improves ASGen, e.g. 20.1 vs. 19.9 in Split1 and 21.4 vs. 21.0 in Split2.

Human Evaluation. Additionally, we also judge the quality of questions by human evaluation involving 10 evaluators over metrics such as syntax, validation of semantics, question to context relevance and question to answer relevance on 50 randomly chosen samples on SQuAD-v1.1 dev set. As shown in Table 5, applying ASGen consistently improves the human evaluation scores.

Answer Prediction. Table 6 shows the effectiveness of our method in generating the number of answers in a given context. In the case of fixed K, the MAE from the ground-truth is smallest at $K^{pred} = 5$ at 1.92 and 0.99 for test set of Split1 and Split2, respectively. Thresholding on the sum of the start and end logits shows an error of 2.31 and 1.12 on the two splits, respectively. In contrast, our method generates an appropriate number of answers, by reducing MAE to 1.24 and 0.76.

Table 6: Mean absolute error (MAE) between prediction K^{pred} and ground-truth K^{gt} on the test set of SQuAD

Approach	MAE	
	Split1	Split2
Thresholding on Logits	2.31	1.12
Fixed-K ($K^{pred} = 5$)	1.92	0.99
Dynamic-K (ASGen)	**1.24**	**0.76**

Table 7: Comparison of downstream MRC task EM/F1 scores after pre-training on the generated synthetic data (syn data). The scores are obtained from the dev set of SQuAD-v1.1 and SQuAD-v2.0, and the dev set and the test set of KorQuAD (KQD).

MRC	Dev-v1.1		Dev-v2.0	
model	EM	F1	EM	F1
BERT (Large)	83.9	90.9	78.8	81.8
+syn data	**86.3**	**92.7**	**84.5**	**87.4**
BERT (WWM)	86.5	92.8	83.1	85.9
+syn data	**87.4**	**93.5**	**85.5**	**88.4**
MRC	Dev-KQD		Test-KQD	
model	EM	F1	EM	F1
BERT+CLKT	87.1	94.5	86.2	94.1
+syn data	**87.8**	**95.0**	**86.7**	**94.6**

Figure 2: F1 scores of BERT (Large) on SQuAD-v1.1 dev by limiting size of MRC and synthetic data.

4.2 Downstream MRC Task Performance

To show the effectiveness of the generated synthetic data, we train MRC models on generated data, before fine-tuning on the downstream data. As shown in Table 7, the synthetic data generated by 'BertGen (Large) + ASGen' consistently improves the performance of BERT (Large, WWM) by a significant margin. Pre-training BERT on synthetic data improves F1 scores by 1.8 on SQuAD-v1.1 and 5.6 on SQuAD-v2.0 for BERT (Large), and 0.7 on SQuAD-v1.1 and 2.5 on SQuAD-v2.0 for BERT (WWM). Synthetic data also improves BERT+CLKT performance on KorQuAD.

4.3 Effects of Downstream and Synthetic Data Size

Fig. 2 shows the effects of varying amounts of downstream MRC data and synthetic data on F1 scores of BERT (Large). In Fig. 2-(a), where we fix the size of synthetic data as 43M, pre-training with 'BertGen + ASGen' consistently outperforms 'BertGen + NS' for all sizes of downstream data. While the performance difference is particularly apparent for smaller sizes of downstream data, it still persists even on using the entire MRC data (SQuAD-v1.1). In Fig. 2-(b), we also conduct experiments by training BERT (Large) using different amounts of generated synthetic data, while using the full size of downstream MRC data. The total number of pre-training steps for all data sizes is kept the same as that of 10M synthetic data. Increasing the amount of synthetic data used consistently improves the accuracy of the MRC model.

4.4 Qualitative Comparison of Questions Generation

We qualitatively compare the generated questions after pre-training BertGen with NS and ASGen to demonstrate the effectiveness of our method. For the correct answer "49.6%" as shown in the first sample in Table 8, the word "Fresno", which is critical to make the question specific, is omitted by NS, while ASGen's question does not suffer from this issue. Note that the word "Fresno" occurs in the answer-containing sentence. This issue also occurs in the second sample, where NS uses the word "available" rather than relevant words from the answer-containing sentence, but ASGen uses many of these words such as "most" and "popular" to generate contextually rich questions. Also, the question from NS is about "two" libraries, while the answer is about "three" libraries, showing the lack of sufficient conditioning on the answer. Similarly, the third example also shows that ASGen generates more contextual questions than NS by including the exact subject "TARDIS" based on the corresponding answer. Based on these observations and from the score improvements in Table 4, we conjecture that ASGen leads the question generation model to better condition on the answer and to generate more contextualized questions than NS.

Table 8: Examples of questions generated on SQuAD-v1.1 development set. We compare generated questions from 'BertGen + ASGen' with 'BertGen + NS'. Colored Text indicates given answers.

Context	(omit) ... The population density was 4,404.5 people per square mile. (1,700.6km). The racial makeup of Fresno was 245,306 (49.6%) White, 40,960 (8.3%) ... (omit)
BertGen + NS	What percent of the population is White?
BertGen + ASGen	What percentage of the Fresno population is White?
Context	(omit) ... in the world. Cabot Science Library, Lamont Library, and Widener Library are three of the most popular libraries for undergraduates to use ... (omit)
BertGen + NS	Which two libraries are available for undergraduates to use?
BertGen + ASGen	What are the three most popular libraries for undergraduates?
Context	(omit) ... in a stolen Mark I Type TARDIS "Time and Relative Dimension in Space" time machine which allows him to travel across time and space. ... (omit)
BertGen + NS	What does the doctor refer to?
BertGen + ASGen	What does the TARDIS stand for?

5 RELATED WORK

Question Generation. Research on question generation has a long history, such as Kalady et al. (2010) and Skalban et al. (2012). Researchers have actively studied question generation for various purposes, including for data augmentation in question answering. Du et al. (2017) proposed an attention-based model for question generation by encoding sentence-level as well as paragraph-level information. Zhao et al. (2018) utilized a gated self-attention encoder with a max-out unit to handle long paragraphs. Song et al. (2018) introduced a query-based generative model to jointly solve question generation and answering tasks. Kim et al. (2019) separately encoded the answer and the rest of the paragraph for question generation. Ma et al. (2020) suggested sentence-level semantic matching and answer-position-aware question generation. Tuan et al. (2020) show that incorporating interactions across multiple sentences enhances question generation performance. Our approach can further improve the question generation quality of these methods by pre-training them with the answer-containing sentence generation task.

Transfer Learning. Pre-training methods are popular in natural language processing for learning contextualized word representations. Open-GPT (Radford et al., 2018), BERT (Devlin et al., 2019), XLNet (Yang et al., 2019), PEGASUS (Zhang et al., 2019), ERNIE-GEN (Xiao et al., 2020), UniLM (Dong et al., 2019) and UniLMv2 (Bao et al., 2020) utilize Transformer (Vaswani et al., 2017) to learn different types of language models on a large dataset followed by fine-tuning on a downstream task. While our approach is similar to these, our pre-training task for the question generator focuses on generating missing answer-containing sentence in the context to learn better representations more suitable to the question generation task.

Synthetic Data Generation. Subramanian et al. (2018) show that neural models generate better candidate answers from a given paragraph than using off-the-shelf tools for selecting named entities and noun phrases. Similar to our method, Golub et al. (2017) proposed to generate questions conditioned on generated answers by separating the answer generation and the question generation. Unlike this paper, they do not estimate the number of answers, and they do not pre-train their question generator. Dong et al. (2019) also show that utilizing synthetic data boosts the performance of MRC models. Inspired by these previous studies, we propose a newly designed pre-training technique that improves capability of question generation models.

6 CONCLUSIONS

We propose a novel pre-training method called ASGen to learn generating contextually rich questions better conditioned on the answers. Our approach improves question generation ability of existing methods, achieves new state-of-the-art results on MS MARCO and NewsQA, and the synthetic data increases downstream MRC accuracy across a wide range of datasets, such as SQuAD-v1.1, v2.0, and KorQuAD, without any modification to the existing MRC models.

REFERENCES

Chris Alberti, Daniel Andor, Emily Pitler, Jacob Devlin, and Michael Collins. Synthetic QA corpora generation with roundtrip consistency. In Anna Korhonen, David R. Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28- August 2, 2019, Volume 1: Long Papers*, pp. 6168–6173. Association for Computational Linguistics, 2019. doi: 10.18653/v1/p19-1620. URL https://doi.org/10.18653/v1/p19-1620.

Satanjeev Banerjee and Alon Lavie. METEOR: an automatic metric for MT evaluation with improved correlation with human judgments. In Jade Goldstein, Alon Lavie, Chin-Yew Lin, and Clare R. Voss (eds.), *Proceedings of the Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization@ACL 2005, Ann Arbor, Michigan, USA, June 29, 2005*, pp. 65–72. Association for Computational Linguistics, 2005a. URL https://www.aclweb.org/anthology/W05-0909/.

Satanjeev Banerjee and Alon Lavie. METEOR: an automatic metric for MT evaluation with improved correlation with human judgments. In Jade Goldstein, Alon Lavie, Chin-Yew Lin, and Clare R. Voss (eds.), *Proceedings of the Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization@ACL 2005, Ann Arbor, Michigan, USA, June 29, 2005*, pp. 65–72. Association for Computational Linguistics, 2005b. URL https://www.aclweb.org/anthology/W05-0909/.

Hangbo Bao, Li Dong, Furu Wei, Wenhui Wang, Nan Yang, Xiaodong Liu, Yu Wang, Songhao Piao, Jianfeng Gao, Ming Zhou, and Hsiao-Wuen Hon. Unilmv2: Pseudo-masked language models for unified language model pre-training. *CoRR*, abs/2002.12804, 2020. URL https://arxiv.org/abs/2002.12804.

Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. ELECTRA: pre-training text encoders as discriminators rather than generators. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=r1xMH1BtvB.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pp. 4171–4186. Association for Computational Linguistics, 2019. doi: 10.18653/v1/n19-1423. URL https://doi.org/10.18653/v1/n19-1423.

Bhuwan Dhingra, Kathryn Mazaitis, and William W. Cohen. Quasar: Datasets for question answering by search and reading. *CoRR*, abs/1707.03904, 2017. URL http://arxiv.org/abs/1707.03904.

Li Dong, Nan Yang, Wenhui Wang, Furu Wei, Xiaodong Liu, Yu Wang, Jianfeng Gao, Ming Zhou, and Hsiao-Wuen Hon. Unified language model pre-training for natural language understanding and generation. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada*, pp. 13042–13054, 2019.

Xinya Du, Junru Shao, and Claire Cardie. Learning to ask: Neural question generation for reading comprehension. In Regina Barzilay and Min-Yen Kan (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics, ACL 2017, Vancouver, Canada, July 30 - August 4, Volume 1: Long Papers*, pp. 1342–1352. Association for Computational Linguistics, 2017. doi: 10.18653/v1/P17-1123. URL https://doi.org/10.18653/v1/P17-1123.

David Golub, Po-Sen Huang, Xiaodong He, and Li Deng. Two-stage synthesis networks for transfer learning in machine comprehension. In Martha Palmer, Rebecca Hwa, and Sebastian Riedel (eds.), *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, EMNLP 2017, Copenhagen, Denmark, September 9-11, 2017*, pp. 835–

844. Association for Computational Linguistics, 2017. doi: 10.18653/v1/d17-1087. URL https://doi.org/10.18653/v1/d17-1087.

Saidalavi Kalady, Ajeesh Elikkottil, and Rajarshi Das. Natural language question generation using syntax and keywords. In *Proceedings of QG2010: The Third Workshop on Question Generation*, volume 2, pp. 5–14, 2010.

Yanghoon Kim, Hwanhee Lee, Joongbo Shin, and Kyomin Jung. Improving neural question generation using answer separation. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pp. 6602–6609. AAAI Press, 2019. doi: 10.1609/aaai.v33i01.33016602. URL https://doi.org/10.1609/aaai.v33i01.33016602.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur P. Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: a benchmark for question answering research. *Trans. Assoc. Comput. Linguistics*, 7:452–466, 2019. URL https://transacl.org/ojs/index.php/tacl/article/view/1455.

Seungyoung Lim, Myungji Kim, and Jooyoul Lee. Korquad1.0: Korean QA dataset for machine reading comprehension. *CoRR*, abs/1909.07005, 2019. URL http://arxiv.org/abs/1909.07005.

Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, 2004.

Bang Liu, Mingjun Zhao, Di Niu, Kunfeng Lai, Yancheng He, Haojie Wei, and Yu Xu. Learning to generate questions by learningwhat not to generate. In Ling Liu, Ryen W. White, Amin Mantrach, Fabrizio Silvestri, Julian J. McAuley, Ricardo Baeza-Yates, and Leila Zia (eds.), *The World Wide Web Conference, WWW 2019, San Francisco, CA, USA, May 13-17, 2019*, pp. 1106–1118. ACM, 2019. doi: 10.1145/3308558.3313737. URL https://doi.org/10.1145/3308558.3313737.

Xiyao Ma, Qile Zhu, Yanlin Zhou, and Xiaolin Li. Improving question generation with sentence-level semantic matching and answer position inferring. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 8464–8471. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/6366.

Tri Nguyen, Mir Rosenberg, Xia Song, Jianfeng Gao, Saurabh Tiwary, Rangan Majumder, and Li Deng. MS MARCO: A human generated machine reading comprehension dataset. In Tarek Richard Besold, Antoine Bordes, Artur S. d'Avila Garcez, and Greg Wayne (eds.), *Proceedings of the Workshop on Cognitive Computation: Integrating neural and symbolic approaches 2016 co-located with the 30th Annual Conference on Neural Information Processing Systems (NIPS 2016), Barcelona, Spain, December 9, 2016*, volume 1773 of *CEUR Workshop Proceedings*. CEUR-WS.org, 2016. URL http://ceur-ws.org/Vol-1773/CoCoNIPS_2016_paper9.pdf.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics, July 6-12, 2002, Philadelphia, PA, USA*, pp. 311–318. ACL, 2002a. doi: 10.3115/1073083.1073135. URL https://www.aclweb.org/anthology/P02-1040/.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics, July 6-12, 2002, Philadelphia, PA, USA*, pp. 311–318. ACL, 2002b. doi: 10.3115/1073083.1073135. URL https://www.aclweb.org/anthology/P02-1040/.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics, July 6-12, 2002, Philadelphia, PA, USA*, pp. 311–318. ACL, 2002c. doi: 10.3115/1073083.1073135. URL https://www.aclweb.org/anthology/P02-1040/.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. Improving language understanding by generative pre-training. *URL https://s3-us-west-2.amazonaws.com/openai-assets/researchcovers/languageunsupervised/language understanding paper.pdf*, 2018.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. Squad: 100, 000+ questions for machine comprehension of text. In Jian Su, Xavier Carreras, and Kevin Duh (eds.), *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing, EMNLP 2016, Austin, Texas, USA, November 1-4, 2016*, pp. 2383–2392. The Association for Computational Linguistics, 2016. doi: 10.18653/v1/d16-1264. URL https://doi.org/10.18653/v1/d16-1264.

Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don't know: Unanswerable questions for squad. In Iryna Gurevych and Yusuke Miyao (eds.), *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics, ACL 2018, Melbourne, Australia, July 15-20, 2018, Volume 2: Short Papers*, pp. 784–789. Association for Computational Linguistics, 2018. doi: 10.18653/v1/P18-2124. URL https://www.aclweb.org/anthology/P18-2124/.

Yvonne Skalban, Le An Ha, Lucia Specia, and Ruslan Mitkov. Automatic question generation in multimedia-based learning. In Martin Kay and Christian Boitet (eds.), *COLING 2012, 24th International Conference on Computational Linguistics, Proceedings of the Conference: Posters, 8-15 December 2012, Mumbai, India*, pp. 1151–1160. Indian Institute of Technology Bombay, 2012. URL https://www.aclweb.org/anthology/C12-2112/.

Linfeng Song, Zhiguo Wang, and Wael Hamza. A unified query-based generative model for question generation and question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2018.

Sandeep Subramanian, Tong Wang, Xingdi Yuan, Saizheng Zhang, Adam Trischler, and Yoshua Bengio. Neural models for key phrase extraction and question generation. In Eunsol Choi, Minjoon Seo, Danqi Chen, Robin Jia, and Jonathan Berant (eds.), *Proceedings of the Workshop on Machine Reading for Question Answering@ACL 2018, Melbourne, Australia, July 19, 2018*, pp. 78–88. Association for Computational Linguistics, 2018. doi: 10.18653/v1/W18-2609. URL https://www.aclweb.org/anthology/W18-2609/.

Adam Trischler, Tong Wang, Xingdi Yuan, Justin Harris, Alessandro Sordoni, Philip Bachman, and Kaheer Suleman. Newsqa: A machine comprehension dataset. In Phil Blunsom, Antoine Bordes, Kyunghyun Cho, Shay B. Cohen, Chris Dyer, Edward Grefenstette, Karl Moritz Hermann, Laura Rimell, Jason Weston, and Scott Yih (eds.), *Proceedings of the 2nd Workshop on Representation Learning for NLP, Rep4NLP@ACL 2017, Vancouver, Canada, August 3, 2017*, pp. 191–200. Association for Computational Linguistics, 2017. doi: 10.18653/v1/w17-2623. URL https://doi.org/10.18653/v1/w17-2623.

Luu Anh Tuan, Darsh J. Shah, and Regina Barzilay. Capturing greater context for question generation. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 9065–9072. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/6440.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long*

Beach, CA, USA, pp. 5998–6008, 2017. URL `http://papers.nips.cc/paper/7181-attention-is-all-you-need`.

Dongling Xiao, Han Zhang, Yu-Kun Li, Yu Sun, Hao Tian, Hua Wu, and Haifeng Wang. ERNIE-GEN: an enhanced multi-flow pre-training and fine-tuning framework for natural language generation. In Christian Bessiere (ed.), *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI 2020*, pp. 3997–4003. ijcai.org, 2020. doi: 10.24963/ijcai.2020/553. URL `https://doi.org/10.24963/ijcai.2020/553`.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime G. Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. Xlnet: Generalized autoregressive pretraining for language understanding. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada*, pp. 5754–5764, 2019.

Jingqing Zhang, Yao Zhao, Mohammad Saleh, and Peter J. Liu. PEGASUS: pre-training with extracted gap-sentences for abstractive summarization. *CoRR*, abs/1912.08777, 2019. URL `http://arxiv.org/abs/1912.08777`.

Yao Zhao, Xiaochuan Ni, Yuanyuan Ding, and Qifa Ke. Paragraph-level neural question generation with maxout pointer and gated self-attention networks. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii (eds.), *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, pp. 3901–3910. Association for Computational Linguistics, 2018. doi: 10.18653/v1/d18-1424. URL `https://doi.org/10.18653/v1/d18-1424`.

Qingyu Zhou, Nan Yang, Furu Wei, Chuanqi Tan, Hangbo Bao, and Ming Zhou. Neural question generation from text: A preliminary study. In Xuanjing Huang, Jing Jiang, Dongyan Zhao, Yansong Feng, and Yu Hong (eds.), *Natural Language Processing and Chinese Computing - 6th CCF International Conference, NLPCC 2017, Dalian, China, November 8-12, 2017, Proceedings*, volume 10619 of *Lecture Notes in Computer Science*, pp. 662–671. Springer, 2017. doi: 10.1007/978-3-319-73618-1_56. URL `https://doi.org/10.1007/978-3-319-73618-1_56`.

APPENDIX

A QUESTION GENERATION ON MORE MRC DATASETS

We also evaluate the question generation model on another data split (Split3) from Zhao et al. (2018). Split3 is obtained by dividing the original development set in SQuAD-v1.1 into two equal halves randomly and choosing one of them as the development set and the other as test set while retaining the train set in SQuAD-v1.1. As shown in Table 9, applying ASGen to the reproduced question generation model from Zhao et al. (2018) improves BLEU-4, METEOR, and ROUGE-L score on Split3 by 1.3, 0.9, and 1.3, respectively.

As shown in Table 10, applying ASGen to BertGen shows improvement in the question generation score in Natural Questions (Kwiatkowski et al., 2019) short answer dataset, where questions are from user query logs used in Google, similar to MS Marco.

Table 9: Additional experiments on the effectiveness of ASGen on the test set of SQuAD Split3. Small-Wiki is used to pre-train the models. Models with '*' indicate those results we reproduced.

Model + pre-training method	BLEU-4	METEOR	ROUGE-L
Zhao et al. (2018)	16.8	20.6	44.9
Zhao et al. (2018)*	16.3	20.3	44.5
Zhao et al. (2018)* + ASGen	**17.6**	**21.2**	**45.8**

Table 10: Ablation study of applying ASGen to question generation model on Natural Questions (Kwiatkowski et al., 2019) short answer dataset. The scores are obtained from the dev set.

Model + pre-training method	BLEU-4	METEOR	ROUGE-L
BertGen (Large)	31.5	30.4	60.2
BertGen (Large) + ASGen	**35.3**	**32.9**	**61.3**

B TRAINING ELECTRA MRC MODEL WITH GENERATED SYNTHETIC DATA

We also apply our synthetic data generated from Small-Wiki to another MRC model, ELECTRA (Clark et al., 2020), which shows the state-of-the-art results. As shown in Table 11, pre-training ELECTRA on the generated synthetic data using ASGen improves 0.5 EM and 0.6 F1 score on the downstream MRC dataset, SQuAD-v2.0, even when using only Small-Wiki.

Table 11: Ablation study of applying our method to ELECTRA (Clark et al., 2020) on SQuAD-v2.0 dev set after pre-training on the generated synthetic data using ASGen with Small-Wiki.

MRC model	Synthetic Data 'Small-Wiki'	Dev set	
		EM	F1
ELECTRA (Large)	-	87.4	90.2
	BertGen+ASGen	**87.9**	**90.8**

C TRANSFER LEARNING TO OTHER DATASETS

To show that our generated data is useful for other MRC datasets, we fine-tune and test the MRC model on QUASAR-T (Dhingra et al., 2017), which is another large-scale MRC dataset, after training on the synthetic data generated from SQuAD-v1.1. In this experiment, we first fine-tune 'Bert-Gen + ASGen' using SQuAD-v1.1, and using synthetic data generated by this model, we train the BERT (Large) MRC model. Afterwards, we fine-tune BERT (Large) for the downstream MRC task using QUASAR-T data. QUASAR-T has two separate datasets, one with short snippets as context, and the other with long paragraphs as context. As shown in Table 12, training with our synthetic data improves the F1 score on the test set by 2.2 and 1.7 for the two cases, respectively.

Table 12: EM/F1 scores of the BERT (Large) fine-tuned on QUASAR-T dataset. The used synthetic data is generated from ASGen trained on SQuAD-v1.1.

Model	Synthetic data	Short(Dev)		Short(Test)	
		EM	F1	EM	F1
BERT	-	74.3	78.6	74.1	77.8
	SQuAD-v1.1	**76.5**	**80.1**	**76.5**	**80.0**

Model	Synthetic data	Long(Dev)		Long(Test)	
		EM	F1	EM	F1
BERT	-	72.1	75.6	72.1	74.8
	SQuAD-v1.1	**74.2**	**77.4**	**73.8**	**76.5**

D DOWNSTREAM MRC ABLATION OF ANSWER GENERATION APPROACHES

We also evaluate the effectiveness of dynamic-K answer prediction by pre-training the BERT (Large) (Devlin et al., 2019) MRC model on our synthetic data from Small-Wiki followed by fine-tuning on the downstream MRC dataset, SQuAD-v2.0. As shown in Table 13, dynamic-K answer prediction shows 0.3 EM and 0.2 F1 score improvements from the baseline approach, fixed-K.

Table 13: Comparison of predicting K answers with downstream BERT (Large) MRC results on SQuAD-v2.0 dev set after pre-training on each generated synthetic data using corresponding answer generation approach with Small-Wiki.

Answer generation approach	Dev set	
	EM	F1
Fixed-K ($K^{pred} = 5$)	81.4	84.4
Dynamic-K (ASGen)	**81.7**	**84.6**

E DETAILS OF WIKIPEDIA PREPROCESSING

To build the answer-containing sentence generation data and the synthetic MRC data for SQuAD (Rajpurkar et al., 2016), we collect all paragraphs from all articles of the entire English Wikipedia dump and generate questions and answers on these paragraphs. We apply extensive filtering and clean-up to only retain the highest-quality paragraphs from Wikipedia, as follows.

To filter out low-quality articles, we remove those with less than 200 cumulative page-views including all re-directions in a two-month period. In order to calculate the number of page-views, official Wikipedia page-view dumps were used. Of the 5.4M original Wikipedia articles, filtering by page-views leaves 2.8M articles. We also remove those articles with less than 500 characters, as they are often low-quality stub articles, which further removes additional 16% of the articles. We remove all "meta" namespace pages such as talk, disambiguation, user pages, portals, etc. as they often contain irrelevant text or casual conversations between editors. In order to extract clean text from the wiki-markup format of the Wikipedia articles, we remove extraneous entities from the markup including table of contents, headers, footers, links/URLs, image captions, IPA double parentheticals, category tables, math equations, unit conversions, HTML escape codes, section headings, double brace templates such as info-boxes, image galleries, HTML tags, HTML comments, and all other tables.

We then split the cleaned text into paragraphs and remove all paragraphs with less than 150 characters or more than 3,500 characters. Paragraphs with the number of characters between 150 to 500 were sub-sampled such that these paragraphs make up 16.5% of the final dataset, as originally done for the SQuAD dataset. Since the majority of the paragraphs in Wikipedia are rather short, out of the 60M paragraphs from the final 2.4M articles, our final Wikipedia dataset contains 8.3M paragraphs. Finally, we generate 43M answer-paragraph pairs from the final Wikipedia dataset with the answer generator of BertGen in this paper.

F CENTRAL TENDENCY AND VARIATION FOR HUMAN EVALUATION

Human evaluation involves 10 evaluators over metrics such as syntax (ST), validation of semantics (SM), question to context relevance (CR) and question to answer relevance (AR) on 50 randomly chosen samples on SQuAD-v1.1 development set. Each score is in the range 1 to 5. Central tendency and variation can be found in Table 14.

Table 14: Central tendency and variation for human evaluation scores. $\pm$ is 95% confidence interval.

Model	ST	SM	CR	AR
BertGen	4.04 $\pm$0.18	3.93 $\pm$0.19	4.20 $\pm$0.16	3.25 $\pm$0.22
BertGen + NS	4.60 $\pm$0.12	4.54 $\pm$0.13	4.49 $\pm$0.14	3.63 $\pm$0.22
BertGen + ASGen	**4.71** $\pm$0.10	**4.69** $\pm$0.11	**4.74** $\pm$0.09	**4.14** $\pm$0.18
UniLM	4.25 $\pm$0.16	4.31 $\pm$0.16	4.54 $\pm$0.12	4.06 $\pm$0.19
UniLM + ASGen	**4.71** $\pm$0.11	**4.79** $\pm$0.09	**4.70** $\pm$0.11	**4.17** $\pm$0.18

G CENTRAL TENDENCY AND VARIATION FOR DOWNSTREAM SQUAD-V1.1 AND V2.0

For the EM and F1 scores on downstream SQuAD-v1.1 and v2.0 development set in Table 7 of our main paper, we selected 5 model checkpoints from the same pre-training on the synthetic data in different numbers of training steps. We then fine-tuned each of these models on the final downstream data three times each, chose the best performing model on the development set, and reported its score. Central tendency and variation can be found in Table 15.

Table 15: Central tendency and variation for the score of our method on downstream SQuAD-v1.1 and v2.0 dataset. ± is standard deviation.

MRC model	Synthetic Data generated by	Dev-v1.1		Dev-v2.0	
		EM	F1	EM	F1
BERT (Large)	BertGen (Large) + ASGen	86.2 ±0.1	92.7 ±0.1	84.4 ±0.2	87.3 ±0.1
BERT (WWM)	BertGen (Large) + ASGen	**87.4** ±0.1	**93.4** ±0.1	**85.5** ±0.1	**88.3** ±0.1

H BLEU-4, METEOR, AND ROGUE-L

BLEU (Papineni et al., 2002c), METEOR (Banerjee & Lavie, 2005a) and ROUGE (Lin, 2004) are widely-used metrics for evaluating the quality of generated text, where the quality indicates the degree of correspondence between generated text and reference texts. BLEU uses modified precision to compare a generated text against the reference texts. BLEU-4 calculates a weighted score of unigram, bigram, trigram, and 4-gram based matching. METEOR uses harmonic mean between precision and recall of unigrams, but with for recall given more importance than precision. Unlike BLEU, METEOR also tries to match synonyms and performs stemming instead of just relying on exact word matching. ROUGE-L is the longest common sub-sequence based word matching. The longest co-occurrence in sequences of n-grams between generated text and reference texts are considered for calculating the score. To calculate these evaluation scores, we follow the script from Du et al. (2017), except for the corresponding scripts from other question generation models when ASGen is applied to them.

I LINKS TO DOWNLOADABLE COMPONENTS

For Wikipedia data, we downloaded English Wikipedia dump in Feb 2019 from (`https://dumps.wikimedia.org/enwiki/latest/enwiki-latest-pages-articles.xml.bz2`). Page views were obtained from (`https://dumps.wikimedia.org/other/pageviews/2019/2019-01/`) and (`https://dumps.wikimedia.org/other/pageviews/2019/2019-02/`). For applying our method to other existing question generation models, we reproduce Zhao et al. (2018) using publicly available code (`https://github.com/seanie12/neural-question-generation`) and use the official code of Dong et al. (2019) (`https://github.com/microsoft/unilm`).