INDUCTIVE RELATION PREDICTION USING ANALOGY SUBGRAPH EMBEDDINGS

ABSTRACT

Prevailing methods for relation prediction in heterogeneous graphs including knowledge graphs aim at learning the latent representations (i.e., embeddings) of observed nodes and relations, and are thus limited to the transductive setting where the relation types must be known during training. In this paper, we propose **AN**alogy Sub**G**raph **E**mbedding **L**earning (GraphANGEL), a novel relation prediction framework that predicts relations between each node pair by checking whether the subgraphs containing the pair are similar to other subgraphs containing the considered relation. Each graph pattern explicitly represents a specific logical rule, which contributes to an inductive bias that facilitates generalization to unseen relation types and leads to more explainable predictive models. Our model consistently outperforms existing models in terms of heterogeneous graph based recommendation as well as knowledge graph completion. We also empirically demonstrate the capability of our model in generalizing to new relation types while producing explainable heat maps of attention scores across the discovered logics.

1 INTRODUCTION

Relation modeling aims to learn the relations between nodes, leading to advances in a wide range of applications, e.g., recommender systems (Koren et al., 2009), knowledge graphs (Bordes et al., 2013), and biology (Yasunaga et al., 2021). As most relational data in the real world is heterogeneous, a principal way is to organize it into a heterogeneous graph. The dominant paradigms for relation prediction can be categorized into matrix factorization techniques (Nickel et al., 2011; 2012), statistical relational learning approaches (Richardson & Domingos, 2006; Singla & Domingos, 2005), and neural-embedding-based methods (Bordes et al., 2013; Dettmers et al., 2018). Among these, neural-embedding-based methods which learn to encode relational information using low-dimensional representations of nodes and relations, have shown good scalability (Bordes et al., 2013) and inductive learning capability (Battaglia et al., 2018) in terms of validating unseen nodes.

Results of such methods show that graph neural networks (GNNs) are able to condense the neighborhood connectivity pattern of each node into a node-specific low-dimensional embedding and successfully exploit such local connectivity patterns and homophily. Recent advances further reveal the logical expressiveness of GNNs (Barceló et al., 2019) and support their inductive ability to generalize to unseen nodes (Teru et al., 2020; Zhang & Chen, 2019).

In contrast, a limited study has been conducted (Yang et al., 2014) on the inductive learning capability for unseen *relation* types. Such inductive ability, if successfully exploited, can directly improve logical expressiveness of GNNs and enable them to effectively capture the underlying logical semantics (e.g., logical rules). Note that this is more challenging than unseen nodes, since it is usually hard to define the "neighborhood" of a relation type topologically.

In this paper, we propose **AN**alogy Sub**G**raph **E**mbedding **L**earning (GraphANGEL), a new relation prediction paradigm that holds a strong inductive bias to generalize to unseen relation types. Given a pair of nodes to predict the existence of a specific relation between them, the core idea is to extract some analogy subgraphs containing the pair, and compare them against other subgraphs sharing similar shapes. We call these shapes *graph patterns*.

Taking Figure 1 as an example, the task is to predict whether `Person E lives in London`. We construct three patterns involving the relation `live`. The first is *target pattern* containing the source

and target nodes, i.e., `Person E` and `London`, for which we are to predict the existence of the relation `live`. The second is *supporting pattern* that includes `live` as evidence *supporting* the existence. The third is *refuting pattern* that does not include `live` as a baseline for comparison. If an edge does exist between the two nodes, the subgraphs matching the target pattern should be more similar to those matching supporting patterns than the refuting patterns. Following the above intuition, we find a set of subgraphs that match each of the patterns. Then we compare the first set against the set matching supporting patterns, and also against the set matching refuting patterns, using a neural network. As shown in the bottom part of the figure, the subgraphs in the second set share the higher similarity with the one in the first set, so the prediction result in this case is that there exists a `live`.

Given a triplet $\langle s, r, t \rangle$, GraphANGEL consists of the following stages: (1) determining target patterns from s, t as well as supporting and refuting patterns from r, (2) retrieving subgraphs matching each pattern, (3) computing the representations of each set and then the similarity between the subgraph set matching target pattern and the set matching supporting/refuting patterns, and the final prediction based on the similarities. For the first stage, our architecture design only involves the graph patterns in pair, 3-cycle, and 4-cycle shapes, which is efficient to match and already shows good results. For the second stage, we introduce efficient searching and sampling techniques to find the subgraphs matching the patterns. We use a GNN with attention in the third stage to combine the sets of subgraphs as well as their node features. The

Figure 1: An illustrative example of motivation.

attention module can simultaneously produce an explainable heat map across the discovered patterns. Notably, none of the above stages requires explicitly learning a representation of r, the relation we are predicting, thus, GraphANGEL naturally generalizes to modeling unseen relation types.

We benchmark GraphANGEL on heterogeneous graph based recommendation and knowledge graph completion tasks with the state-of-the-art methods. For the evaluation of inductive capabilities, we construct several new inductive benchmarks by either removing or adding relations from knowledge graph datasets. Extensive experimental comparisons on these benchmarks exhibit the superiority of our method under both transductive and inductive settings.

2   BRIDGING LOGICAL EXPRESSIONS AND GRAPH PATTERNS

We begin with bridging logical expressions and graph patterns based on two intuitions, both of which come from real world experiences:

- A relation can often be inferred from other relations with a combination of simple logical rules that do not involve too many nodes.
- One can predict relation existence by finding whether the subgraphs containing the pair are similar to the subgraphs containing an edge with the same relation.

Take Figure 1 as an example where we wish to predict whether `Person E` `lives` in `London`. An example of the first intuition goes as follows: if `Person E` `watches` the soccer matches with club `Arsenal`, which is `based` in `London`, then `Person E` may also `live` in `London`. However, such logical rules may not always hold, requiring probabilistic inference. For instance, `Person G` `watches` the matches with `FC Barcelona`, which is `Based` in `Barcelona`, but he does not `live` in the same city. To make more accurate predictions, we need to combine other possible logical rules, such as "Friends often live in the same city" - in this case, `Person E` and `Person H` are `friends`, and `Person H` `lives` in `London`.

The second intuition tells us that we can predict whether `Person E` `lives` in `London` by checking if the subgraphs containing the pair (`Person E`, `London`) (named *target* subgraphs, e.g. `Person E` - `Arsenal` - `London`) are similar to the subgraphs containing a `live` relation (named *supporting*

Figure 2: Illustration of GraphANGEL's relation prediction workflow, where different edge colors in the graph $\mathcal{G}$ represent different relation types, and dashed edges in $\mathcal{G}$ represent the triplet $\langle s, r, t \rangle$ we wish to predict. The left box shows the patterns considered in our implementation, where black edges mean matching edges irrespective of relation types. The bottom boxes show the logical function of the three patterns.

subgraphs, e.g. `Person I - Chelsea - London`). Similarity computation is done by a neural network. To determine whether the two sets of subgraphs are similar, we additionally compare the target subgraphs against another set of subgraphs that do not contain the relation (named *refuting* subgraphs, e.g. `Person E - Person G - Barcelona`) as a baseline. A variety of options exist for selecting the refuting subgraphs, ranging from selecting those having the same topology regardless of the actual relation types, to those having both the same shape and relation types.

In addition, we do not include the edge of `live` in the supporting subgraphs to avoid information leakage. We also require the supporting subgraphs and refuting subgraphs to have the same shape as that of the target subgraphs in order to make similarity computation focus more on the node features and relation types rather than the topology, and that is why we call both supporting subgraphs and refuting subgraphs *analogy* subgraphs. This enables us to predict `live` relation with the pipeline above *without* learning an explicit embedding for `live` relation, unlike prior works. The reason is that the information of `live` relation can be implicitly expressed by the other relations found in the supporting and refuting subgraphs, e.g. `live` can be expressed by `watch` and `based`. This serves as the basis for our model's generalizability to relations that have no occurrence in the training set.

We can describe what kind of subgraphs we are looking for in the above example with logical expressions. The target subgraphs above will have the logical expression $\texttt{Source}(x) \wedge \texttt{Target}(y) \wedge \texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y)$, where $\texttt{Source}(x)$ means if node x is the source node s, $\texttt{Target}(y)$ means if node y is the target node t, and $\texttt{Edge}(x, z)$ means if there exists an edge regardless of relation type between x and z. Our task is to determine whether an edge of relation type r exists between s and t. The supporting subgraphs will have $\texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y) \wedge \texttt{Edge}_r(x, y)$, meaning that the subgraph can be any 3-cycle except that there must be an edge with relation type r. The refuting subgraphs will have $\texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y) \wedge \neg\texttt{Edge}_r(x, y)$, meaning that it can be any 2-path except that the starting node and ending node must not have an edge with relation r in between. This leads to the concept of *graph patterns*, defined as follows:

Definition 1 (Graph Pattern). *A graph pattern is a logical function that takes in a subgraph as input and returns a boolean value, consisting of logical operators ($\neg, \wedge, \vee$) as well as indicator operators determined by the existence of nodes and edges, the latter includes:*

- $\texttt{Source}(x)$ *and* $\texttt{Target}(x)$, *returning* `true` *iff the node x is the source node and target node, respectively.*
- $\texttt{Edge}(x, y)$, *returning* `true` *iff there exists an edge between node x and y.*
- $\texttt{Edge}_r(x, y)$, *returning* `true` *iff there exists an edge of relation r between node x and y.*

We call a subgraph $\mathcal{S}$ *matches* a graph pattern Π if `true` is returned when $\mathcal{S}$ is applied to Π. Such operation is already well supported in graph databases (Francis et al., 2018), and in the following sections we give more efficient algorithms that perform matching with simple patterns.

3 MODELING RELATION WITH ANALOGY SUBGRAPH EMBEDDINGS

For each graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathcal{R})$ where $\mathcal{V}$ denotes node set, $\mathcal{E}$ denotes edge set and $\mathcal{R}$ is relation set, as Figure 2 shows, we outline how GraphANGEL works for each triplet $\langle s, r, t \rangle$ to predict the

Table 1: A summary of how to construct target, supporting, and refuting patterns.

Base Pattern Π_p	Target Pattern Π_p^*	Supporting Pattern Π_p^+	Refuting Pattern Π_p^-
Π_p	$\texttt{Source}(x) \wedge \texttt{Target}(y) \wedge \Pi_p$	$\texttt{Edge}_r(x,y) \wedge \Pi_p$	$\neg\texttt{Edge}_r(x,y) \wedge \Pi_p$

existence for the edge of type r connecting source node s and target node t as follows. (a) We start by determining P *target patterns* denoted as $\Pi_1^*, \cdots, \Pi_P^*$. For each Π_p^* we also determine its corresponding *supporting pattern* Π_p^+ and *refuting pattern* Π_p^-. (b) We then sample a set of K target subgraphs $\{\mathcal{S}_{p,k}^*\}_{k=1}^K$ matching Π_p^*, Q supporting subgraphs $\{\mathcal{S}_{p,q}^+\}_{q=1}^Q$ matching Π_p^+, and Q refuting subgraphs $\{\mathcal{S}_{p,q}^-\}_{q=1}^Q$ matching Π_p^-. (c) For each pattern Π_p, we next compute the representation of each sampled subgraph and obtain the set of target subgraph embeddings $\{e_{p,k}^*\}_{k=1}^K$, supporting subgraph embeddings $\{e_{p,q}^+\}_{q=1}^Q$ and refuting subgraph embeddings $\{e_{p,q}^-\}_{q=1}^Q$. (d) We finally compute a similarity score between the set $\{e_{p,k}^*\}_{p=1,k=1}^{P,K}$ and the set $\{e_{p,q}^+\}_{p=1,q=1}^{P,Q}$, as well as $\{e_{p,k}^*\}_{p=1,k=1}^{P,K}$ and $\{e_{p,q}^-\}_{p=1,q=1}^{P,Q}$, to get the relation prediction result.

We summarize the notations in Appendix A1, show the training algorithm in Algorithm 1 and describe the details in the following subsections.

Pattern Construction. During training, we set for each Π_p the target pattern Π_p^*, the supporting pattern Π_p^+, and the refuting pattern Π_p^- using Table 1. Since pattern matching is NP-complete like subgraph matching (Lewis, 1983), we first designate before training a set of patterns $\{\Pi_p\}_{p=1}^P$ whose pattern matching can be computed in manageable time. In practical, we use *Pairs*, *3-cycles*, and *4-cycles*.

Subgraph Retrieval. Although general graph pattern matching is supported in graph databases (Francis et al., 2018), more efficient solutions exist for simpler graph patterns, especially when we only consider pairs, 3-cycle and 4-cycle shapes.

Algorithm 1: GraphANGEL

Input: Graph $\mathcal{G}$, Patterns $\Pi_1, \ldots, \Pi_P$.
for *each tuple* $\langle s, r, t \rangle$ **do**
    for *each pattern* Π_p **do**
        Construct $\Pi_p^*, \Pi_p^+, \Pi_p^-$.
        Retrieve K subgraphs $\{\mathcal{S}_{p,k}^*\}_{k=1}^K$ matching Π_p^*.
        Retrieve Q subgraphs $\{\mathcal{S}_{p,q}^+\}_{q=1}^Q$ matching Π_p^+.
        Retrieve Q subgraphs $\{\mathcal{S}_{p,q}^-\}_{q=1}^Q$ matching Π_p^-.
        Compute $e_{p,k}^*, e_{p,q}^+, e_{p,q}^-$ via Eq. (1).
    end
    Compute s^+, s^- via Eq. (2).
    Update parameters according to Eq. (3).
end

---

exist for simpler graph patterns, especially when we only consider pairs, 3-cycle and 4-cycle shapes. Searching and retrieving the subgraphs matching patterns in Pair shape is trivial since it reduces to finding edges with a given relation, so the following discussion only involves 3-cycle and 4-cycle patterns. We first precompute and store all subgraphs matching the patterns in 3-cycle and 4-cycle shapes by our algorithm, summarized as follows, with pseudocode, correctness proofs and complexity analysis in Appendix A2.

- *3-cycles.* We first partition the node set by the node degrees into two sets $\mathcal{V} = \mathcal{V}_1 \cup \mathcal{V}_2$. $\mathcal{V}_1$ contains the nodes whose degrees are less than $|\mathcal{E}|^{1/2}$, and $\mathcal{V}_2$ contains the rest. For each $u, v, w \in \mathcal{V}_1$, we check if they form a 3-cycle. Then, for each $u \in \mathcal{V}_2$, we enumerate all pairs of its neighbors and see if they are connected. The overall complexity to find all the subgraphs is $O(|\mathcal{E}|^{3/2})$.
- *4-cycles.* For each node $u \in \mathcal{V}$, we find all 2-paths (u, v, w) whose starting node u has the largest degree, i.e., $d_u = \max(d_u, d_v, d_w)$. Each pair of 2-paths that shares the same ending node forms a 4-cycle. In this way, all 4-cycles can be enumerated by the starting node with the largest degree. The overall complexity to find all subgraphs is $O(\max(|\mathcal{E}|^{3/2}, n_{4\text{-cycle}}))$ where $n_{4\text{-cycle}}$ is the number of the subgraphs.

Then, we perform pattern matching for 3-cycles and 4-cycles for each subgraph as follows.

- *Target patterns.* Matching 3-cycle target patterns reduces to finding common neighbors of s and t, which takes $O(d_s + d_t)$ time where d_s and d_t are degrees of s and t. Matching 4-cycle target pattern reduces to finding whether the neighbors of s and t are connected, taking $O(d_s d_t)$ time.
- *Supporting patterns.* Matching supporting patterns reduces to finding a subgraph containing an edge of type r in the precomputed result. One can efficiently retrieve with a precomputed inverted map with relation r as key and the actual subgraphs containing it as value.
- *Refuting patterns.* Matching refuting patterns reduces to random walks, followed by checking whether the starting node and the ending node has an edge of type r.

Table 2: Patterns Π_p considered in our experiments.

Task	Pair	3-cycle (with type)	4-cycle (with type)
Knowledge Graph Completion	`true`	$\text{Edge}(x,z) \wedge \text{Edge}(z,y)$	$\text{Edge}(x,z) \wedge \text{Edge}(z,w) \wedge \text{Edge}(w,y)$
Heterogeneous Graph Recommendation	`true`	$\text{Edge}_a(x,z) \wedge \text{Edge}_b(z,y)$	$\text{Edge}_a(x,z) \wedge \text{Edge}_b(z,w) \wedge \text{Edge}_c(w,y)$

We further design a series of novel uniform sampling algorithms such that the time complexity of sampling K supporting cases of $\Pi_{4-\text{cycle}}$ reduces to $O(|\mathcal{E}|^{\frac{3}{2}} + K)$, sampling Q refuting cases of $\Pi_{3-\text{cycle}}$ or $\Pi_{4-\text{cycle}}$ reduces to $O(|\mathcal{V}| + |\mathcal{E}| + Q)$. See detailed descriptions in Appendix A2.

Representation Computation. We apply a neural network $\Phi(\cdot)$ over each subgraph $\mathcal{S}^*_{p,k}$, $\mathcal{S}^+_{p,q}$ and $\mathcal{S}^-_{p,q}$ to obtain graph-level representations $\boldsymbol{e}^*_{p,k}$, $\boldsymbol{e}^+_{p,q}$, $\boldsymbol{e}^-_{p,q}$, following

$$\boldsymbol{e}^*_{p,k} = \Phi\left(\mathcal{S}^*_{p,k}\right), \ \boldsymbol{e}^+_{p,q} = \Phi\left(\mathcal{S}^+_{p,q}\right), \ \boldsymbol{e}^-_{p,q} = \Phi\left(\mathcal{S}^-_{p,q}\right). \tag{1}$$

In the implementation, we adopt single layer R-GCN (Schlichtkrull et al., 2018) followed by any readout function, e.g., $\text{Mean}(\cdot)$, $\text{Max}(\cdot)$ as $\Phi(\cdot)$.

Similarity Computation. We deploy a neural network $\Psi(\cdot)$ to measure the similarity s^+ between the set of subgraphs matching $\Pi^*_1, \ldots, \Pi^*_P$ and the set of subgraphs matching $\Pi^+_1, \ldots, \Pi^+_P$; and the similarity s^- between the set of subgraphs matching $\Pi^*_1, \ldots, \Pi^*_P$ and the set of subgraphs matching $\Pi^-_1, \ldots, \Pi^-_P$, which can be formulated as

$$\begin{aligned} s^+ &= \Psi\left(\{\boldsymbol{e}^*_{p,k}, p = 1, \ldots, P; k = 1, \ldots, K\}, \{\boldsymbol{e}^+_{p,q} : p = 1, \ldots, P; q = 1, \ldots, Q\}\right), \\ s^- &= \Psi\left(\{\boldsymbol{e}^*_{p,k} : p = 1, \ldots, P; k = 1, \ldots, K\}, \{\boldsymbol{e}^-_{p,q} : p = 1, \ldots, P; q = 1, \ldots, Q\}\right). \end{aligned} \tag{2}$$

There are many choices of measuring the similarity between two sets. In the implementation, we adopt a co-attention mechanism (Lu et al., 2016) as $\Psi(\cdot)$, because even within the same pattern, the subgraphs having similar node features are more important than others.

We put the concrete formulation of $\Phi(\cdot)$ and $\Psi(\cdot)$ in the Appendix A3.2 and A3.3.

Loss Function. For each tuple $\langle s, r, t \rangle$, we have the binary label y in the training dataset $\mathcal{D}$ to denote the relation existence. We here train the model by logistic loss with negative sampling:

$$L = - \sum_{\langle s,r,t \rangle \in \mathcal{D}} \left(y \log \hat{y} + (1 - y) \log(1 - \hat{y})\right), \tag{3}$$

where $\hat{y}$ is the final prediction calculated with normalized similarity as $\hat{y} = \frac{s^+}{s^+ + s^-}$.

Inference. We perform pattern matching to find the target, supporting, and refuting subgraphs on the testing graph, and compute the prediction score $\hat{y}$ exactly as what we do in training. We predict that an edge exists if $\hat{y}$ is larger than a threshold (as a hyper-parameter, 0.5 in our implementation).

Limitations. There are two main limitations of GraphANGEL. The first one is that GraphANGEL would not work reliably if the assumptions (intuitions) in Section 2 are violated. Examples include when node s and t are disconnected or topologically far away when $\langle s, r, t \rangle$ is removed, so that one may not be able to find 3-cycle or 4-cycle target subgraphs. The prediction in this case can only rely on Pair patterns, i.e., comparing if the source-target pair is similar to the incident nodes of edges with relation r or not. The second one is that current online subgraph sampling algorithms are slow. To make sampling efficient, the subgraph retrieval stage requires finding and storing all 3-cycles and 4-cycles. It is a one-time preprocessing step and it can take lots of space, although the results can be stored on external storage. See further discussions on other limitations in Appendix A4.

4 RELATED WORK

Heterogeneous graphs such as knowledge graphs (Bordes et al., 2013; Schlichtkrull et al., 2018) and social networks (Zhang et al., 2019; Jin et al., 2020) that encode facts about the world surrounding us, have motivated work on automatically predicting new statements based on known ones. Roughly speaking, existing approaches can be summarized into three main branches, namely matrix factorization techniques (Nickel et al., 2011; 2012), statistical relational learning approaches (Richardson & Domingos, 2006; Singla & Domingos, 2005), and neural-embedding-based methods (Bordes et al., 2013; Dettmers et al., 2018). Our work focuses on the study of neural-embedding-based models as they embed nodes and relations into low-dimensional spaces (Bordes et al., 2013; Schlichtkrull et al., 2018; Trouillon et al., 2016; Yan et al., 2019; Teru et al., 2020), showing good scalability and strong generalization ability. One dominant paradigm (Ji et al., 2015; Lin et al., 2015) in this branch is

constructed based on translation (Bordes et al., 2013) or rotation (Sun et al., 2019) assumptions. The key idea behind this kind of models is that for a positive instance, the source node should be as close as possible to the target node through the relation, serving as a translation or rotation.

Although there are multiple successful stories in this line of works, these models are all trained on individual instances, regardless of their local neighborhood structures. As stated in (Schlichtkrull et al., 2018), explicitly modeling local structure can be an important supplement to help recover missing relations. Inspired by the success of GNNs in modeling structured neighborhood information, another line of literature (Schlichtkrull et al., 2018; Zhang & Chen, 2018) learns the relation embedding based on its neighborhood subgraph using graph convolution layers. With a similar approach, recent work (Zhang & Chen, 2019; Teru et al., 2020) illustrates the inductive capabilities of generalization to unseen nodes. However, these approaches fail to generalize to unseen relation types, as it is indirect to introduce the "neighborhood" for a relation type upon the graph structure.

Meanwhile, our work also relates to previous researches (Qu et al., 2019; Qu & Tang, 2019; Zhang et al., 2020; Qi et al., 2018; Zheng et al., 2019) studying to effectively combine GNNs techniques with symbolic logic rule-based approaches (Giarratano & Riley, 1998; Jackson, 1998; Lafferty et al., 2001; Taskar et al., 2012; Richardson & Domingos, 2006; Singla & Domingos, 2005). As logic rule-based approaches are able to leverage domain knowledge but suffer from complicated graph structures while graph embedding methods excel at learning effective relation embeddings but fail to leverage domain knowledge, the basic idea of these works is to combine the advantages of both methods. However, these methods, as originally proposed, are transductive in nature. Unlike our method, they still require learning relation type specific embeddings, whereas we treat the relation prediction as a graph pattern matching problem, independent of any particular relation type identity. There are also other work (Yang et al., 2014) that demonstrates the potential generalization ability of transition-based methods and designs a logical rule extraction approach to mine the underlying rules. As this method can incorporate with various neural-embedding-based models, this set of models constitute our baselines in the inductive setting.

Another popular link prediction approach is to directly infer the likelihood of relation existence using a local neighborhood or a local subgraph (Schlichtkrull et al., 2018; Zhang & Chen, 2018; Hu et al., 2020). A significant difference between those works and our approach is in the formulation of the loss function. Let f_r be any function that maps a vector to a scalar score parametrized by r and ℓ_r be a scalar function, then the prior works' loss function often take the form $L = \sum_{\langle s,r,t \rangle \in \mathcal{D}} \ell(f_r(\boldsymbol{h}^*), y)$, meaning that the score computation explicitly depends on the embedding of relation to be predicted. Ours, in contrast, has the form $L = \sum_{\langle s,r,t \rangle \in \mathcal{D}} \ell(d(\boldsymbol{h}^*, \boldsymbol{h}^+), d(\boldsymbol{h}^*, \boldsymbol{h}^-), y)$ where ℓ is a scalar function and d is a distance function between two vectors, which are embeddings of a set of subgraphs. Consequently, our loss function ℓ does not require representation of r.

5 EXPERIMENT

In this section, as the main advantage of our model is that it can generalize to relation types unseen during training *without fine-tuning*, we both evaluate the overall performance of GraphANGEL in standard relation prediction tasks on heterogeneous graphs and its generalizability to unseen relation types against other state-of-the-art methods. All code will be released at publication time.

5.1 EXPERIMENT SETUP AND COMPARED ALGORITHMS

Recommendation on Heterogeneous Graph. We evaluate our model on four heterogeneous graph benchmark datasets in various fields: LastFM (Hu et al., 2018a), Yelp (Hu et al., 2018b), Amazon (Ni et al., 2019), and Douban Book (Zheng et al., 2017). The baselines we compare against are: HetGNN (Zhang et al., 2019), HAN (Wang et al., 2019b), TAHIN (Bi et al., 2020), HGT (Hu et al., 2020), and R-GCN (Schlichtkrull et al., 2018). As the recommendation task can naturally be regarded as the relation predictions between each user and item pair, for each triplet, we formulate the task as a binary classification task. We split each dataset into 60%, 20%, and 20% for training, validation and test sets, respectively. Following the setting of (Zhang et al., 2019), we generate an equal number of negative triplets with the same relation type in the test set, and report Area Under ROC Curve (AUC), Accuracy (ACC), and F1 score. We also compare the training and inference time of GraphANGEL against baseline models and report results in Appendix A6.4.

Table 3: Result comparisons with baselines on heterogeneous graph recommendation tasks.

Models	LastFM			Yelp			Amazon			Douban Book		
	AUC	ACC	F1	AUC	ACC	F1	AUC	ACC	F1	AUC	ACC	F1
HetGNN	0.7936	0.7258	0.7177	0.9083	0.8297	0.8205	0.7744	0.7108	0.7109	0.8737	0.7912	0.7915
HAN	0.8915	0.8337	0.8296	0.9156	0.8488	0.8426	0.8487	0.7682	0.7572	0.9244	0.8501	0.8458
TAHIN	0.8910	0.8463	0.8337	0.9067	0.8490	0.8393	0.8535	0.7718	0.7644	0.9253	0.8497	0.8373
HGT	0.8394	0.7939	0.7882	0.9006	0.8375	0.8334	0.7125	0.6482	0.6296	0.9132	0.8364	0.8222
R-GCN	0.8526	0.8393	0.8341	0.9098	0.8427	0.8323	0.8130	0.7408	0.7366	0.9203	0.8413	0.8271
GraphANGEL$_{3-\text{cycle}}$	0.8934	0.8519	0.8465	0.9167	0.8498	0.8514	0.8601	0.7746	0.7712	0.9256	0.8512	0.8479
GraphANGEL$_{4-\text{cycle}}$	0.8961	0.8514	0.8467	0.9201	0.8506	0.8521	0.8609	0.7752	0.7716	0.9242	0.8502	0.8378
GraphANGEL	0.8979	0.8524	0.8469	0.9231	0.8512	0.8533	0.8611	0.7790	0.7753	0.9311	0.8601	0.8543
GraphANGEL*	**0.9001**	**0.8611**	**0.8589**	**0.9337**	**0.8701**	**0.8577**	**0.8700**	**0.7810**	**0.7813**	**0.9410**	**0.8640**	**0.8591**

Table 4: Result comparisons with baselines on knowledge graph completion task.

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet	173	0.332	0.237	0.367	0.524	3408	0.441	0.398	0.446	0.537
TransE	181	0.326	0.229	0.363	0.521	3410	0.223	0.135	0.401	0.531
ConvE	244	0.325	0.237	0.356	0.501	4187	0.430	0.400	0.440	0.520
ComplEx	339	0.247	0.158	0.275	0.428	5261	0.440	0.410	0.460	0.510
MLN	1980	0.098	0.067	0.103	0.160	11549	0.259	0.191	0.322	0.361
RotatE	177	0.338	0.241	0.375	0.533	3340	0.476	0.428	0.492	0.571
RNNLogic	232	0.344	0.252	0.380	0.530	4615	0.483	0.446	0.497	0.558
ComplEx-N3	159	0.370	0.272	0.400	0.561	3452	0.491	0.440	0.500	0.581
GraIL	205	0.322	0.223	0.361	0.520	3539	0.401	0.352	0.438	0.501
GraphANGEL$_{3-\text{cycle}}$	159	0.366	0.270	0.398	0.560	2919	0.492	0.463	0.497	0.590
GraphANGEL$_{4-\text{cycle}}$	165	0.351	0.239	0.381	0.548	2914	0.493	0.465	0.502	0.587
GraphANGEL	**152**	**0.372**	**0.275**	**0.407**	**0.563**	**2834**	**0.502**	**0.470**	**0.513**	**0.597**

Knowledge Graph Completion. We compare different methods on two benchmark datasets: FB15k-237 (Toutanova & Chen, 2015) and WN18RR (Dettmers et al., 2018), which are constructed from Freebase (Bollacker et al., 2008) and WordNet (Miller, 1995), respectively. The baselines we compare against are: MLN (Singla & Domingos, 2005), TransE (Bordes et al., 2013), ConvE (Dettmers et al., 2018), ComplEx (Trouillon et al., 2016), pLogicNet (Qu & Tang, 2019), RotatE (Sun et al., 2019), RNNLogic (Qu et al., 2020), ComplEx-N3 (Lacroix et al., 2018) and GraIL (Teru et al., 2020). For each triplet, we mask the source or target node, and let each method predict the masked node. Following (Qu & Tang, 2019; Yang et al., 2014; Bordes et al., 2013), we use the filtered setting during evaluation on the standard training-validation-test split, and report Mean Rank (MR), Mean Reciprocal Rank (MRR), and Hit@K (K=1,3,10).

In each task, we implement GraphANGEL as we proposed in Section 3. Concretely, we imply GraphANGEL with Π_p upon the logical patterns shown in Table 2. For further investigations on the influence of different graph patterns, we here introduce GraphANGEL$_{3-\text{cycle}}$, a variant of GraphANGEL without using patterns in 3-cycle shapes; and GraphANGEL$_{4-\text{cycle}}$, another variant without using patterns in 4-cycle shapes. For recommendation tasks on heterogeneous graphs, since the number of edge types is usually small, we can enumerate all the relation type combination in each pattern. This allows us to make the pattern Π_p specific to relation types. We denote this variant as GraphANGEL*. More details of the datasets and experimental configurations as well as the implementation details for baselines are reported in Appendix A5.1.

5.2 RESULT ANALYSIS OF STANDARD TASKS

Heterogeneous Graph Based Recommendation. In recommendation scenarios, edges between user and item nodes are generally more likely to exist if they share neighboring users or items. In other words, users close in the graph may share similar interests and items close usually share similar attributes. Table 3 summarizes the performances of GraphANGEL and baselines on four different kinds of recommendation tasks. We observe that GraphANGEL significantly outperforms the baselines across all datasets in terms of AUC, ACC, and F1 metrics. Almost all prevailing baseline methods on heterogeneous graph are based on sampling through metapath. One explanation is that given a specific pattern, these metapaths can be roughly regarded as target patterns, but without constructing supporting and refuting patterns in Table 1.

Knowledge Graph Completion. In knowledge graphs, the connection between two nodes is determined by both logic and node attributes. Table 4 summarizes all experimental results. As can be seen, GraphANGEL outperforms all baselines across all datasets. One explanation is that most knowledge graph embedding techniques focus on mining the hidden information in each tuple, which

Table 5: Comparable results with baselines, where there are 20% least frequent relations. Here we only report the results in terms of Hit@K (K=1,3,10). See Appendix A6.1 for the full version. The numbers in brackets show the descent degree comparing to Table 5.

Models	FB15k-237			WN18RR		
	Hit@1	Hit@3	Hit@10	Hit@1	Hit@3	Hit@10
pLogicNet	0.209(11.8%↓)	0.342(6.81%↓)	0.500(4.58%↓)	0.341(14.3%↓)	0.406(8.97%↓)	0.491(8.57%↓)
TransE	0.197(14.0%↓)	0.339(6.61%↓)	0.494(5.18%↓)	0.123(8.89%↓)	0.367(8.48%↓)	0.487(8.29%↓)
ConvE	0.207(12.7%↓)	0.324(8.99%↓)	0.478(4.59%↓)	0.364(9.00%↓)	0.391(11.1%↓)	0.479(7.88%↓)
ComplEx	0.140(11.4%↓)	0.261(5.09%↓)	0.409(4.44%↓)	0.375(8.54%↓)	0.428(6.96%↓)	0.475(6.86%↓)
MLN	0.051(23.9%↓)	0.077(25.2%↓)	0.143(10.6%↓)	0.166(13.1%↓)	0.285(11.5%↓)	0.333(7.76%↓)
RotatE	0.211(12.3%↓)	0.351(6.34%↓)	0.505(5.32%↓)	0.386(9.83%↓)	0.445(9.57%↓)	0.529(7.38%↓)
RNNLogic	0.219(13.2%↓)	0.333(12.5%↓)	0.499(5.76%↓)	0.407(8.61%↓)	0.444(10.7%↓)	0.511(8.42%↓)
ComplEx-N3	0.242(11.1%↓)	0.361(9.85%↓)	0.534(4.85%↓)	0.407(**7.49%**↓)	0.456(8.74%↓)	0.539(7.15%↓)
GraIL	0.197(11.5%↓)	0.315(12.8%↓)	0.484(6.84%↓)	0.307(12.7%↓)	0.387(11.6%↓)	0.458(8.52%↓)
GraphANGEL$_{3-cycle}$	0.243(9.87%↓)	0.384(3.53%↓)	0.539(**3.80%**↓)	0.418(9.78%↓)	0.465(6.42%↓)	0.549(6.93%↓)
GraphANGEL$_{4-cycle}$	0.215(9.96%↓)	0.366(4.04%↓)	0.526(3.94%↓)	0.421(9.37%↓)	0.467(6.92%↓)	0.549(**6.47%**↓)
GraphANGEL	**0.248**(9.62%↓)	**0.394**(**3.27%**↓)	**0.541**(3.84%↓)	**0.429**(8.74%↓)	**0.481**(**6.21%**↓)	**0.557**(6.75%↓)

is similar to only considering the patterns in Pair shapes in Table 1. However, other patterns contain information involving multiple relations, which enables to model the logics.

In order to better illustrate our performance of these relations with few occurrences in the training set, we solely report the results of testing each model on the 20% relations with few occurrence in Table 5. From the comparison between Tables 4 and 5, we can observe that with few shots of relations, GraphANGEL can have a better generalization ability. One reason is that embeddings of the relations with few occurrences cannot be trained with plenty of data samples, resulting in low expressive power of the relations. In contrast, GraphANGEL does not learn the embeddings directly, but learns to represent the relations of the related logics. However, it is still more challenging to model these relations that lead to a drop in performance.

Figure 3: Performance change of GraphANGEL with different number of subgraphs in terms of ACC and AUC.

5.3 EFFECT OF DIFFERENT PATTERNS

In GraphANGEL, three shapes of patterns are used. Next, we systematically investigate the effect of each graph pattern and different numbers of sampled subgraphs used for each pattern. For each dataset, we evaluate the influence of the patterns in 3-cycle and 4-cycle shapes by the performance of GraphANGEL$_{3-cycle}$ and GraphANGEL$_{4-cycle}$. Since different shapes of patterns represent different composition logical rules, as shown in Table 1, patterns in Pair shape are the most general but include the least structure information, while those in 4-cycle shape are rich in the structure but less common. Hence, these patterns have their unique power in representing logics. Although it is hard to determine whether 3-cycle or 4-cycle shaped patterns are more powerful, as shown in Tables 3, 4 and 5, GraphANGEL with patterns in all shapes achieves the best performance. Besides the pattern type, we also investigate how the number of sampled subgraphs influences the performance. Taking the heterogeneous graph datasets Amazon and Douban Book as examples, we show the performance of GraphANGEL under the different K and Q in terms of ACC and AUC in Figure 3. One explanation is that the subgraphs following target patterns are constricted within the neighborhood of source and target nodes, the number of which is much smaller than subgraphs following (analogy) supporting and refuting patterns.

5.4 RESULT ANALYSIS OF GENERALIZATION STUDY

We further evaluate these models in a scenario where generalizing from existing relations to unseen relations is required. Concretely, we use the same datasets with knowledge graph completion and randomly split $\mathcal{R}$ into two partitions $\mathcal{R}_{seen}$ and $\mathcal{R}_{unseen}$. Each model is trained and validated only with the relations in $\mathcal{R}_{seen}$. During testing, the training and validation triplets in $\mathcal{R}_{unseen}$ are added back to the original graph. We report results on test triples with relations in $\mathcal{R}_{unseen}$ only.

Table 6: Result comparisons with baselines on generalization setting by randomly removing 20% relations. Due to space limitation, we only report the results in terms of Hit@K (K=1,3,10). See Appendix A6.2 for full version and Appendix A6.2 for results of dropping 5%, 10%, 15%. The numbers in brackets show the descent degree.

Models	FB15k-237			WN18RR		
	Hit@1	Hit@3	Hit@10	Hit@1	Hit@3	Hit@10
pLogicNet*	0.112(52.7%↓)	0.179(51.2%↓)	0.257(51.0%↓)	0.141(64.6%↓)	0.222(50.2%↓)	0.267(50.3%↓)
TransE*	0.101(55.9%↓)	0.163(55.1%↓)	0.246(52.8%↓)	0.072(46.7%↓)	0.200(50.1%↓)	0.260(51.0%↓)
ConvE*	0.104(56.1%↓)	0.178(50.0%↓)	0.247(50.7%↓)	0.201(49.8%↓)	0.223(49.3%↓)	0.268(48.5%↓)
ComplEx*	0.078(50.6%↓)	0.142(48.4%↓)	0.226(47.2%↓)	0.214(47.8%↓)	0.236(48.7%↓)	0.267(47.6%↓)
MLN*	0.031(53.7%↓)	0.049(52.4%↓)	0.070(56.3%↓)	0.092(51.8%↓)	0.154(52.2%↓)	0.178(50.7%↓)
RotatE*	0.121(49.8%↓)	0.187(50.1%↓)	0.271(49.1%↓)	0.238(44.3%↓)	0.260(47.1%↓)	0.296(48.2%↓)
RNNLogic*	0.124(50.7%↓)	0.172(54.7%↓)	0.240(54.6%↓)	0.244(45.2%↓)	0.260(47.6%↓)	0.281(49.7%↓)
ComplEx-N3*	0.142(47.2%↓)	0.208(49.6%↓)	0.289(48.5%↓)	0.250(43.2%↓)	0.269(46.2%↓)	0.311(46.4%↓)
GraIL*	0.125(43.9%↓)	0.185(48.8%↓)	0.263(49.4%↓)	0.195(44.7%↓)	0.222(49.3%↓)	0.267(46.8%↓)
GraphANGEL$_{3-cycle}$	0.168(37.6%↓)	0.230(42.2%↓)	0.333(40.5%↓)	0.277(40.2%↓)	0.291(**41.4%**↓)	0.329(44.3%↓)
GraphANGEL$_{4-cycle}$	0.147(38.7%↓)	0.222(41.7%↓)	0.328(40.2%↓)	0.278(40.2%↓)	0.291(42.1%↓)	0.326(44.4%↓)
GraphANGEL	**0.173**(**37.2%**↓)	**0.238**(**41.5%**↓)	**0.337**(**40.1%**↓)	**0.284**(**39.5%**↓)	**0.299**(41.8%↓)	**0.334**(**44.1%**↓)

We cannot directly use the baselines above for unseen relations since those relation embeddings are never trained. Therefore, we combine them with EmbedRule, which estimates the relation embedding by finding a number of most common relation sequences that cooccur with the unseen relation, and composing those embeddings thereafter (Yang et al., 2014). We superscript the name with an asterisk for models enhanced by EmbedRule (e.g. TransE*).

Results reported in Table 6 illustrate that our model is significantly less affected than other models when we drop 20% relations from the training and validation sets. We additionally report the results of dropping or adding 5%, 10%, 15% relations in Appendix A6.2. These results on FB15k-237 dataset are summarized in Figure 4. From the figure, we see that our model obtains the better generalization ability against other baselines.

Figure 4: Illustrations of generalization ability for GraphANGEL against baselines.

5.5 RESULT ANALYSIS OF EXPLAINABLE ATTENTION MAP

Besides the performance, we further show that our model can produce explainable heat maps of attention scores across the discovered logic. We here provide an illustration on the recommendation task based on Douban Book graph, where we are required to predict the relation existence between each user and book pair. In Douban Book, we can define the graph patterns based on the node types, such as 4-cycle shaped patterns: User − Book − Author − Book denoted as (b, a), User − Book − Year − Book denoted as (b, y), and User − User − User − Book denoted as (u, u). In Figure 5, the rows represent the supporting subgraphs while the columns represent the target subgraphs. Each cell represents the similarity between a target subgraph (at the top) and a supporting subgraph (at the bottom). The color of each cell shows the attention weight for corresponding pair of supporting and target subgraphs. We can

Figure 5: Illustrations of generated heat map of attention scores. See Appendix A6.3 for the full version with subgraph structure.

observe that the deep color of the cell located at target and supporting subgraphs following (b, a) patterns, which indicates that the logic User ∧ Book ∧ Author ∧ Book ⇒ User ∧ Book has high confidence and can be strong evidence to support the relation prediction.

6 CONCLUSION

We propose a novel relation prediction framework that predicts the relations between each node pair based on the subgraph containing the pair and other subgraphs with identical graph patterns, and has a strong inductive bias for the generalization to unseen relation types. With these graph patterns, we introduce several graph pattern searching and sampling techniques, which can efficiently find subgraphs matching the patterns in triangle and quadrangle shapes. In the future, we plan to further extend GraphANGEL to more complex structures (i.e., compositional logical rules).

REFERENCES

Pablo Barceló, Egor V Kostylev, Mikael Monet, Jorge Pérez, Juan Reutter, and Juan Pablo Silva. The logical expressiveness of graph neural networks. In *International Conference on Learning Representations*, 2019.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Ye Bi, Liqiang Song, Mengqiu Yao, Zhenyu Wu, Jianming Wang, and Jing Xiao. A heterogeneous information network based cross domain insurance recommendation system for cold start users. In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pp. 2211–2220, 2020.

Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pp. 1247–1250, 2008.

Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In *Neural Information Processing Systems (NIPS)*, pp. 1–9, 2013.

Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Nadime Francis, Alastair Green, Paolo Guagliardo, Leonid Libkin, Tobias Lindaaker, Victor Marsault, Stefan Plantikow, Mats Rydberg, Petra Selmer, and Andrés Taylor. Cypher: An evolving query language for property graphs. In *Proceedings of the 2018 International Conference on Management of Data*, pp. 1433–1445, 2018.

Joseph C Giarratano and Gary Riley. *Expert systems*. PWS publishing co., 1998.

William Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/5dd9db5e033da9c6fb5ba83c7a7ebea9-Paper.pdf.

Binbin Hu, Chuan Shi, Wayne Xin Zhao, and Tianchi Yang. Local and global information fusion for top-n recommendation in heterogeneous information network. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management*, pp. 1683–1686, 2018a.

Binbin Hu, Chuan Shi, Wayne Xin Zhao, and Philip S Yu. Leveraging meta-path based context for top-n recommendation with a neural co-attention model. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 1531–1540, 2018b.

Ziniu Hu, Yuxiao Dong, Kuansan Wang, and Yizhou Sun. Heterogeneous graph transformer. In *Proceedings of The Web Conference 2020*, pp. 2704–2710, 2020.

Peter Jackson. *Introduction to expert systems*. Addison-Wesley Longman Publishing Co., Inc., 1998.

Guoliang Ji, Shizhu He, Liheng Xu, Kang Liu, and Jun Zhao. Knowledge graph embedding via dynamic mapping matrix. In *Proceedings of the 53rd annual meeting of the association for computational linguistics and the 7th international joint conference on natural language processing (volume 1: Long papers)*, pp. 687–696, 2015.

Jiarui Jin, Jiarui Qin, Yuchen Fang, Kounianhua Du, Weinan Zhang, Yong Yu, Zheng Zhang, and Alexander J Smola. An efficient neighborhood-based interaction model for recommendation on heterogeneous graph. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 75–84, 2020.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Johannes Klicpera, Aleksandar Bojchevski, and Stephan Günnemann. Predict then propagate: Graph neural networks meet personalized pagerank. *arXiv preprint arXiv:1810.05997*, 2018.

Yehuda Koren, Robert Bell, and Chris Volinsky. Matrix factorization techniques for recommender systems. *Computer*, 42(8):30–37, 2009.

Timothée Lacroix, Nicolas Usunier, and Guillaume Obozinski. Canonical tensor decomposition for knowledge base completion. In *International Conference on Machine Learning*, pp. 2863–2872. PMLR, 2018.

John Lafferty, Andrew McCallum, and Fernando CN Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. 2001.

Harry R Lewis. Computers and intractability. a guide to the theory of np-completeness, 1983.

Yankai Lin, Zhiyuan Liu, Huanbo Luan, Maosong Sun, Siwei Rao, and Song Liu. Modeling relation paths for representation learning of knowledge bases. *arXiv preprint arXiv:1506.00379*, 2015.

Jiasen Lu, Jianwei Yang, Dhruv Batra, and Devi Parikh. Hierarchical question-image co-attention for visual question answering. *arXiv preprint arXiv:1606.00061*, 2016.

George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 38(11): 39–41, 1995.

Pasquale Minervini, Matko Bošnjak, Tim Rocktäschel, Sebastian Riedel, and Edward Grefenstette. Differentiable reasoning on large knowledge bases and natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 5182–5190, 2020a.

Pasquale Minervini, Sebastian Riedel, Pontus Stenetorp, Edward Grefenstette, and Tim Rocktäschel. Learning reasoning strategies in end-to-end differentiable proving. In *International Conference on Machine Learning*, pp. 6938–6949. PMLR, 2020b.

Jianmo Ni, Jiacheng Li, and Julian McAuley. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 188–197, 2019.

Maximilian Nickel, Volker Tresp, and Hans-Peter Kriegel. A three-way model for collective learning on multi-relational data. In *Icml*, 2011.

Maximilian Nickel, Volker Tresp, and Hans-Peter Kriegel. Factorizing yago: scalable machine learning for linked data. In *WWW*, 2012.

Siyuan Qi, Wenguan Wang, Baoxiong Jia, Jianbing Shen, and Song-Chun Zhu. Learning human-object interactions by graph parsing neural networks. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 401–417, 2018.

Meng Qu and Jian Tang. Probabilistic logic neural networks for reasoning. *arXiv preprint arXiv:1906.08495*, 2019.

Meng Qu, Yoshua Bengio, and Jian Tang. Gmnn: Graph markov neural networks. *arXiv preprint arXiv:1905.06214*, 2019.

Meng Qu, Junkun Chen, Louis-Pascal Xhonneux, Yoshua Bengio, and Jian Tang. Rnnlogic: Learning logic rules for reasoning on knowledge graphs. *arXiv preprint arXiv:2010.04029*, 2020.

Matthew Richardson and Pedro Domingos. Markov logic networks. *Machine learning*, 62(1-2): 107–136, 2006.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *European Semantic Web Conference*, pp. 593–607. Springer, 2018.

Parag Singla and Pedro Domingos. Discriminative training of markov logic networks. In *AAAI*, volume 5, pp. 868–873, 2005.

Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. *arXiv preprint arXiv:1902.10197*, 2019.

Ben Taskar, Pieter Abbeel, and Daphne Koller. Discriminative probabilistic models for relational data. *arXiv preprint arXiv:1301.0604*, 2012.

Komal Teru, Etienne Denis, and Will Hamilton. Inductive relation prediction by subgraph reasoning. In *International Conference on Machine Learning*, pp. 9448–9457. PMLR, 2020.

Kristina Toutanova and Danqi Chen. Observed versus latent features for knowledge base and text inference. In *Proceedings of the 3rd workshop on continuous vector space models and their compositionality*, pp. 57–66, 2015.

Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *International Conference on Machine Learning*, pp. 2071–2080. PMLR, 2016.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Alastair J Walker. An efficient method for generating discrete random variables with general distributions. *ACM Transactions on Mathematical Software (TOMS)*, 3(3):253–256, 1977.

Minjie Wang, Da Zheng, Zihao Ye, Quan Gan, Mufei Li, Xiang Song, Jinjing Zhou, Chao Ma, Lingfan Yu, Yu Gai, Tianjun Xiao, Tong He, George Karypis, Jinyang Li, and Zheng Zhang. Deep graph library: A graph-centric, highly-performant package for graph neural networks. *arXiv preprint arXiv:1909.01315*, 2019a.

Xiao Wang, Houye Ji, Chuan Shi, Bai Wang, Yanfang Ye, Peng Cui, and Philip S Yu. Heterogeneous graph attention network. In *The World Wide Web Conference*, pp. 2022–2032, 2019b.

Leon Weber, Pasquale Minervini, Jannes Münchmeyer, Ulf Leser, and Tim Rocktäschel. Nlprolog: Reasoning with weak unification for question answering in natural language. *arXiv preprint arXiv:1906.06187*, 2019.

Bo Yan, Matthew Walker, and Krzysztof Janowicz. A time-aware inductive representation learning strategy for heterogeneous graphs. In *Proceedings of the 15th International Workshop on Mining and Learning with Graphs (MLG'19) at KDD*, volume 19, 2019.

Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. *arXiv preprint arXiv:1412.6575*, 2014.

Michihiro Yasunaga, Hongyu Ren, Antoine Bosselut, Percy Liang, and Jure Leskovec. Qa-gnn: Reasoning with language models and knowledge graphs for question answering. *arXiv preprint arXiv:2104.06378*, 2021.

Chuxu Zhang, Dongjin Song, Chao Huang, Ananthram Swami, and Nitesh V Chawla. Heterogeneous graph neural network. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 793–803, 2019.

Muhan Zhang and Yixin Chen. Link prediction based on graph neural networks. *Advances in Neural Information Processing Systems*, 31:5165–5175, 2018.

Muhan Zhang and Yixin Chen. Inductive matrix completion based on graph neural networks. *arXiv preprint arXiv:1904.12058*, 2019.

Yuyu Zhang, Xinshi Chen, Yuan Yang, Arun Ramamurthy, Bo Li, Yuan Qi, and Le Song. Efficient probabilistic logic reasoning with graph neural networks. *arXiv preprint arXiv:2001.11850*, 2020.

Jing Zheng, Jian Liu, Chuan Shi, Fuzhen Zhuang, Jingzhi Li, and Bin Wu. Recommendation in heterogeneous information network via dual similarity regularization. *International Journal of Data Science and Analytics*, 3(1):35–48, 2017.

Zilong Zheng, Wenguan Wang, Siyuan Qi, and Song-Chun Zhu. Reasoning visual dialogs with structural and partial observations. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6669–6678, 2019.

A1 NOTATIONS

Figure A1: An illustrated example of notations in GraphANGEL.

In this paper, we begin by bridging the logical expression and the graph pattern. Taking Figure A1 as example, we aim to predict the relation live between the source and target nodes (i.e., Person E and London). We consider the 3-cycle graph pattern. Formally, we use Π_p where $p = 1, 2, \ldots, P$ to denote a certain graph pattern. For each Π_p, we use Π_p^* to denote the corresponding target pattern, Π_p^+ to denote the corresponding supporting pattern, Π_p^- to denote the corresponding refuting pattern. Concretely, as shown in Table 1, we can define $\Pi_p = \texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y)$, $\Pi_p^* = \texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y) \wedge \texttt{Source}(x) \wedge \texttt{Target}(y)$, $\Pi_p^+ = \texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y) \wedge \texttt{Edge}_{\texttt{live}}(x, y)$, $\Pi_p^- = \texttt{Edge}(x, z) \wedge \texttt{Edge}(z, y) \wedge \neg\texttt{Edge}_{\texttt{live}}(x, y)$. According to these patterns, we can retrieve the corresponding subgraphs on the graph (as shown in Figure 1) and construct the corresponding subgraph sets. Figure A1 illustrates a target subgraph representing the logical expression Watch(Person E, Arsenal)∧Base(Arsenal, London)∧Source(PersonE) ∧ Target(London). We use $\mathcal{S}_{p,k}^*$ to denote the k-th sampled target subgraph following the target pattern Π_p^* where $k = 1, 2, \ldots, K$, $\mathcal{S}_{p,q}^+$ to denote the q-th sampled supporting subgraph following the supporting pattern Π_p^+, $\mathcal{S}_{p,q}^-$ to dentoe the q-th sampled refuting subgraph following the refuting pattern Π_p^- where $q = 1, 2, \ldots, Q$.

For each Π_p, after applying pattern retrieval and sampling introduced in Appendix A2, we build a set of target subgraphs denoted as $\{\mathcal{S}_{p,k}^*\}_{k=1}^K$, a set of supporting subgraphs denoted as $\{\mathcal{S}_{p,q}^+\}_{q=1}^Q$, a set of refuting subgraphs denoted as $\{\mathcal{S}_{p,q}^-\}_{q=1}^Q$. We then learn a representation for each subgraph, and obtain a set of corresponding target subgraph embeddings denoted as $\{e_{p,k}^*\}_{k=1}^K$, a set of corresponding supporting subgraph embeddings denoted as $\{e_{p,q}^+\}_{q=1}^Q$, a set of corresponding refuting subgraph embeddings denoted as $\{e_{p,q}^-\}_{q=1}^Q$.

A2 PSEUDOCODE, CORRECTNESS PROOFS, AND COMPLEXITY ANALYSIS FOR 3-CYCLE AND 4-CYCLE PATTERN RETRIEVAL AND SAMPLING

In this section, we first summarize the complexity of retrieving and sampling subgraphs following the graph patterns in 3-cycle and 4-cycle with the following theorem:

Theorem 1. (Time Complexity of Retrieval and Sampling in GraphANGEL) *Given a graph* $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ *and a graph pattern* $\Pi_{3-\text{cycle}}$ *in 3-cycle and a graph pattern* $\Pi_{4-\text{cycle}}$ *in 4-cycle, the time complexity of retrieving all the subgraphs satisfying* $\Pi_{3-\text{cycle}}$ *is* $O(|\mathcal{E}|^{\frac{3}{2}})$, *of retrieving all the subgraphs satisfying* $\Pi_{4-\text{cycle}}$ *is* $O(\max(|\mathcal{E}|^{\frac{3}{2}}, N_{4-\text{cycle}}))$ *where* $N_{4-\text{cycle}}$ *is the number of quadratic cycles in* $\mathcal{G}$ *and also the trivial lower bound of the time complexity. For uniform sampling algorithms, the time complexity of sampling* K *supporting cases of* $\Pi_{4-\text{cycle}}$ *is* $O(|\mathcal{E}|^{\frac{3}{2}} + K)$. *As there are usually more refuting cases than supporting ones, the time complexity of sampling* Q *refuting cases of* $\Pi_{3-\text{cycle}}$ *or* $\Pi_{4-\text{cycle}}$ *is* $O(|\mathcal{V}| + |\mathcal{E}| + Q)$.

In the following subsections, we show the proof of Theorem 1 by providing the pseudocode of retrieval and sampling algorithms along with the correctness proof and complexity analysis in Appendix A2.1 and A2.2 respectively.

A2.1 PSEUDOCODE, CORRECTNESS PROOFS, AND COMPLEXITY ANALYSIS FOR 3-CYCLE AND 4-CYCLE PATTERN RETRIEVAL

In this part, we first provide two algorithms for searching and retrieving subgraphs following the graph patterns in 3-cycle (i.e., $\Pi_{3-\text{cycle}}$) in Part 1; and one algorithm for searching and retrieving subgraphs following the graph patterns in 4-cycle (i.e., $\Pi_{4-\text{cycle}}$) in Part 2.

Part 1. In Algorithm 2, we present the pseduocode for searching and retrieving all subgraphs following the pattern $\Pi_{3-\text{cycle}}$. The input is a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ and the output is a set $\mathcal{B}$ containing all subgraphs satisfying $\Pi_{3-\text{cycle}}$. We denote the degree of node u by d_u, and the set of neighbor nodes of node u in graph $\mathcal{G}$ by $\mathcal{N}_{\mathcal{G}}(u)$.

Algorithm 2: $\Pi_{3-\text{cycle}}$ Search and Retrieval Algorithm A

$\mathcal{V}_1 \leftarrow \{u | d_u > |\mathcal{E}|^{\frac{1}{2}}\}, \mathcal{V}_2 \leftarrow \{u | d_u \leq |\mathcal{E}|^{\frac{1}{2}}\}$
$\mathcal{B} \leftarrow \{\}$
foreach $u \in \mathcal{V}_1$ **do**
  foreach $v \in \mathcal{V}_1$ **do**
    foreach $w \in \mathcal{V}_1$ **do**
      if $\langle u, v \rangle \in \mathcal{E}$ and $\langle u, w \rangle \in \mathcal{E}$ and $\langle v, w \rangle \in \mathcal{E}$ **then**
        $\mathcal{B} \leftarrow \mathcal{B} \cup \{(u, v, w)\}$
      end
    end
  end
end
foreach $u \in \mathcal{V}_2$ **do**
  foreach $v \in \mathcal{N}_{\mathcal{G}}(u)$ **do**
    foreach $w \in \mathcal{N}_G(u)$ **do**
      if $\langle v, w \rangle \in E$ **then**
        $\mathcal{B} \leftarrow \mathcal{B} \cup \{(u, v, w)\}$
      end
    end
  end
end

Now, we investigate the correctness and the time complexity of Algorithm 2.

Proof. For any triangle (i.e., 3 nodes connected by 3 edges) (u, v, w), if the degrees of all three nodes are greater than $|\mathcal{E}|^{\frac{1}{2}}$ (i.e., $d_u > |\mathcal{E}|^{\frac{1}{2}}$ and $d_v > |\mathcal{E}|^{\frac{1}{2}}$ and $d_w > |\mathcal{E}|^{\frac{1}{2}}$), it will be enumerated in the first loop. Otherwise, if the degree of any node is not greater than $|\mathcal{E}|^{\frac{1}{2}}$, the triangle will be enumerated in the second loop.

In order to analyze the time complexity, we first investigate an upper bound of $\mathcal{V}_1 = \{u|d_u > |\mathcal{E}|^{\frac{1}{2}}\}$:

$$2|\mathcal{E}| = \sum_{u \in \mathcal{V}} d_u \geq \sum_{u \in \mathcal{V}_1} d_u > \sum_{v \in \mathcal{V}_1} |\mathcal{E}|^{\frac{1}{2}} \Rightarrow |\mathcal{V}_1| < 2|\mathcal{E}|^{\frac{1}{2}}. \tag{4}$$

For the first main loop of the algorithm, we have

$$\sum_{u,v,w \in \mathcal{V}_1} 1 = |\mathcal{V}_1|^3 < 8|\mathcal{E}|^{\frac{3}{2}} = O(|\mathcal{E}^{\frac{3}{2}}|). \tag{5}$$

For the second main loop, we have

$$\sum_{u \in \mathcal{V}_2} \sum_{\langle u,v \rangle \in \mathcal{E}} \sum_{\langle u,v \rangle \in \mathcal{E}} 1 = \sum_{u \in \mathcal{V}_2} d_i^2 \leq \sum_{u \in \mathcal{V}_2} |\mathcal{E}|^{\frac{1}{2}} d_u \leq 2|\mathcal{E}|^{\frac{3}{2}} = O(|\mathcal{E}^{\frac{3}{2}}|). \tag{6}$$

Summarizing the analysis above, we conclude that the overall time complexity is $O(|\mathcal{E}|^{\frac{3}{2}})$. $\qquad\square$

Alternatively, we provide another searching and retrieving algorithm for subgraphs following $\Pi_{3-\texttt{cycle}}$ in Algorithm 3. The inputs and outputs of the algorithm are consistent with Algorithm 2.

Algorithm 3: $\Pi_{3-\texttt{cycle}}$ Search and Retrieval Algorithm B

$\mathcal{B} \leftarrow \{\}$
foreach $u \in \mathcal{V}$ **do**
    foreach $v \in \mathcal{N}_\mathcal{G}(u)$ where $d_v \leq d_u$ **do**
        foreach $w \in \mathcal{N}_\mathcal{G}(v)$ where $d_w \leq d_v$ **do**
            if $\langle u, w \rangle \in \mathcal{E}$ **then**
                $\mathcal{B} \leftarrow \mathcal{B} \cup \{(u, v, w)\}$
            end
        end
    end
end

Next, we analyze and prove the correctness and the time complexity of Algorithm 3.

Proof. It is not difficult to find that each triangle (u, v, w) satisfying $d_u \geq d_v \geq d_w$ is enumerated.

To analyze the time complexity, let us consider how many ws are enumerated:

$$\sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} \sum_{\substack{\langle w,v \rangle \in \mathcal{E} \\ d_w \leq d_v}} 1 \leq \sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} \sum_{\langle w,v \rangle \in \mathcal{E}} 1 = \sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} d_v. \tag{7}$$

From Eq. (4), we know that for each v satisfying $d_v > |\mathcal{E}|^{\frac{1}{2}}$, since $d_u \geq d_v > |\mathcal{E}|^{\frac{1}{2}}$, there are at most $2|\mathcal{E}|^{\frac{1}{2}}$ different us in the outer loop. Hence, we have

$$\begin{aligned}
\sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} d_v &= \sum_{v} d_v \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} 1 \\
&= \sum_{v} \left(\left[d_v \leq |\mathcal{E}|^{\frac{1}{2}} \right] + \left[d_v > |\mathcal{E}|^{\frac{1}{2}} \right] \right) d_v \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} 1 \\
&= \sum_{v} \left(\left[d_v \leq |\mathcal{E}|^{\frac{1}{2}} \right] d_v \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} 1 + \left[d_v > |\mathcal{E}|^{\frac{1}{2}} \right] d_v \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_v \leq d_u}} 1 \right) \\
&\leq \sum_{v} \left(\left[d_v \leq |\mathcal{E}|^{\frac{1}{2}} \right] |\mathcal{E}|^{\frac{1}{2}} d_v + \left[d_v > |\mathcal{E}|^{\frac{1}{2}} \right] |\mathcal{E}|^{\frac{1}{2}} d_v \right) \\
&= |\mathcal{E}|^{\frac{1}{2}} \sum_{v} d_v = 2|\mathcal{E}|^{\frac{3}{2}},
\end{aligned} \tag{8}$$

where $[\cdot]$ represents the boolean indicator function (i.e., $[x] = 1$ if x is true; otherwise false).

Therefore, the overall time complexity is also $O(|\mathcal{E}|^{\frac{3}{2}})$. $\qquad\square$

Part 2. In Algorithm 4, we demonstrate the algorithm for searching and retrieving subgraphs following graph patterns in 4-cycles (i.e., $\Pi_{4-\text{cycle}}$). The inputs, outputs, and notations are similar to those in Algorithm 2.

Algorithm 4: $\Pi_{4-\text{cycle}}$ Search and Retrieval Algorithm

---

$\mathcal{B} \leftarrow \{\}$
foreach $u \in \mathcal{V}$ **do**
    $\mathcal{T}_x \leftarrow \{\}$ for each $x \in \mathcal{V}$
    foreach $v \in \mathcal{N}_{\mathcal{G}}(u)$ where $d_v \leq d_u$ **do**
        foreach $w \in \mathcal{N}_{\mathcal{G}}(v)$ where $d_w \leq d_u$ **do**
            foreach $x \in \mathcal{T}_w$ **do**
                $\mathcal{B} \leftarrow \mathcal{B} \cup \{(u,v,w,x)\}$
            end
            $\mathcal{T}_w \leftarrow \mathcal{T}_w \cup \{v\}$
        end
    end
end

We provide the correctness and the time complexity of Algorithm 4 as follows.

Proof. For correctness, we can see from the algorithm that every quadrangle (u, v, w, x) satisfying $d_u \geq \max(d_v, d_w, d_x)$ is enumerated.

For time complexity, let $N_{4-\text{cycle}}$ denote the number of quadratic cycles in $\mathcal{G}$. We first have the time complexity $\Theta(N_{4-\text{cycle}})$ of the innermost loop. For the outer three loops, let us consider how many ws are enumerated:

$$\sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_u \leq d_v}} \sum_{\substack{\langle w,v \rangle \in \mathcal{E} \\ d_w \leq d_u}} 1 \leq \sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_u \leq d_v}} \sum_{\langle w,v \rangle \in \mathcal{E}} 1 = \sum_{u} \sum_{\substack{\langle u,v \rangle \in \mathcal{E} \\ d_u \leq d_v}} d_v. \tag{9}$$

From Eq. (8), we have

$$\sum_{u} \sum_{\langle u,v \rangle \in \mathcal{E},\, d_u \leq d_v} d_v \leq 2|\mathcal{E}|^{\frac{3}{2}}. \tag{10}$$

Thus, the overall time complexity is $O(\max(|\mathcal{E}|^{\frac{3}{2}}, N_{4-\text{cycle}}))$. $\qquad\square$

A2.2 PSEUDOCODE, CORRECTNESS PROOFS, AND COMPLEXITY ANALYSIS FOR 3-CYCLE AND 4-CYCLE PATTERN SAMPLING

From the subsection above, we know that given a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, we have different algorithmic complexities depending on the graph pattern Π. For $\Pi_{3-\text{cycle}}$ (i.e., 3-cycles), the time complexity of retrieving all subgraphs satisfying $\Pi_{3-\text{cycle}}$ is $O(|\mathcal{E}|^{\frac{3}{2}})$. For $\Pi_{4-\text{cycle}}$ (i.e., 4-cycles), the time complexity is $O(\max(|\mathcal{E}|^{\frac{3}{2}}, N_{4-\text{cycle}}))$, where $N_{4-\text{cycle}}$ indicates the number of quadratic cycles in $\mathcal{G}$.

However, for large-scale graphs, it is impractical to retrieve all quadratic-cycle graph patterns since $N_{4-\text{cycle}}$ could be too large. In addition, the number of refuting cases for both $\Pi_{3-\text{cycle}}$ and $\Pi_{4-\text{cycle}}$ may also be large. These problems may lead to the high computational cost of these search algorithms. Realizing this, we further introduce the technique of uniform sampling to keep the time complexity within an acceptable level.

Therefore, in the following, we first provide one algorithm for uniformly sampling and retrieving graph patterns following $\Pi_{4-\text{cycle}}$ in Part 1; and two algorithms for uniform sampling and retrieving graph patterns following the refuting patterns in 3-cycle shape (i.e., $\Pi_{3-\text{cycle}}^{-}$) and 4-cycle shape (i.e., $\Pi_{4-\text{cycle}}^{-}$) in Part 2. As a reminder, while practical, another approach to obtain graph patterns following $\Pi_{3-\text{cycle}}^{-}$ and $\Pi_{4-\text{cycle}}^{-}$ is random walk, although random walk is often not efficient enough.

Part 1. We present the algorithm for sampling and retrieving graph patterns following $\Pi_{4-\texttt{cycle}}$ in Algorithm 5. The inputs to the algorithm are a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ and K, representing the number of graph patterns to sample. The output is a set $\mathcal{B}$ containing all sampled graph patterns.

Algorithm 5: Uniform Sampling and Retrieval Algorithm for $\Pi_{4-\texttt{cycle}}$

$\mathcal{B} \leftarrow \{\}$
foreach $u \in \mathcal{V}$ **do**
 $\mathcal{T}_{uw} \leftarrow \{\}$ for $w \in \mathcal{V}$
 foreach $v \in \mathcal{N}_{\mathcal{G}}(u)$ where $d_v \leq d_u$ **do**
  foreach $w \in \mathcal{N}_{\mathcal{G}}(v)$ where $d_w \leq d_u$ **do**
   $\mathcal{T}_{uw} \leftarrow \mathcal{T}_{uw} \cup \{v\}$
  end
 end
end
foreach (u, w) where $\mathcal{T}_{uw} \neq \varnothing$ **do**
 $c_{uw} \leftarrow |\mathcal{T}_{uw}|(|\mathcal{T}_{uw}| - 1)$
end
$c \leftarrow \sum_{uw} c_{uw}$
foreach (u, w) where $\mathcal{T}_{uw} \neq \varnothing$ **do**
 $p_{uw} \leftarrow c_{uw}/c$
end
for $k \leftarrow 1$ to K **do**
 Sample (u, w) where $\mathcal{T}_{uw} \neq \varnothing$ with probability p_{uw}
 Uniformly sample two different nodes u and x from $\mathcal{T}_{uw}$
 $\mathcal{B} \leftarrow \mathcal{B} \cup \{(u, v, w, x)\}$
end

We provide the correctness and the time complexity of Algorithm 5 as follows.

Proof. For correctness, we can observe from the algorithm that every quadrangle (u, v, w, x) satisfying $d_u \geq \max(d_v, d_w, d_x)$ is counted in $\mathcal{T}_{uw}$ exactly once, where $v \in \mathcal{T}_{uw}$ and $x \in \mathcal{T}_{uw}$. We sample (u, w) with the probability of occurrence of the quadrangle (u, v, w, x), then sample different v and x uniformly from $\mathcal{T}_{uw}$.

For time complexity, it has been proved in Algorithm 4 that the time complexity of computing $\mathcal{T}$ is $O(|\mathcal{E}|^{\frac{3}{2}})$. Notably, there are $O(|\mathcal{E}|^{\frac{3}{2}})$ non-empty $\mathcal{T}$s.

Therefore, if we sample (u, w) through Alias Method (Walker, 1977), then the overall time complexity is $O(|\mathcal{E}|^{\frac{3}{2}} + K)$. □

Part 2. We further provide two path sampling algorithms. In most practical cases, there are many more refuting examples than supporting ones, and if we assume so, then Algorithm 6 can be used to sample graph patterns following refuting patterns in 3-cycle shape (i.e., $\Pi_{3-\texttt{cycle}}^{-}$), and Algorithm 7 to sample graph patterns following refuting patterns in 4-cycle shape (i.e., $\Pi_{4-\texttt{cycle}}^{-}$).

Algorithm 6 displays the algorithm for uniformly sampling graph patterns following $\Pi_{3-\texttt{cycle}}^{-}$ in $\mathcal{G}$. The inputs, outputs, notations are identical to those in Algorithm 5.
We provide the correctness and the time complexity of Algorithm 5 as follows.

Proof. For correctness, as shown in the algorithm, we formulate the sampling of refuting cases of $\Pi_{3-\texttt{cycle}}$ into uniformly sampling three-node paths, namely (u, v, w). We first sample the intermediate node of the path (i.e., v), where there are $d_v(d_v - 1)/2$ three-node paths with v as its intermediate node. Next, we sample v with probability p_v to ensure uniformity, where $p_v = d_v(d_v - 1)/\sum_v d_v(d_v - 1)$, and then sample its two neighbors to form the path.

For time complexity, using Alias Method, the overall time complexity is $O(|\mathcal{V}| + |\mathcal{E}| + K)$, where the computation for the degree requires $O(|\mathcal{E}|)$, the first two loops require $O(|\mathcal{V}|)$, and the last loop requires $O(K)$. □

Algorithm 6: Uniform Sampling and Retrieval Algorithm for $\Pi_{3-\texttt{cycle}}^-$

$\mathcal{B} \leftarrow \{\}$
foreach $u \in \mathcal{V}$ **do**
$\quad$| $\quad c_u \leftarrow d_u(d_u - 1)$
end
$c \leftarrow \sum_u c_u$
foreach $u \in \mathcal{V}$ **do**
$\quad$| $\quad p_u \leftarrow c_u/c$
end
for $i \leftarrow 1$ to K **do**
$\quad$| $\quad$ Sample v with probability p_v
$\quad$| $\quad$ Uniformly sample two different neighbor nodes (i.e., u and w) of v
$\quad$| $\quad \mathcal{B} \leftarrow \mathcal{B} \cup \{(u, v, w)\}$
end

Algorithm 7: Uniform Sampling and Retrieval Algorithm for $\Pi_{4-\texttt{cycle}}^-$

$\mathcal{B} \leftarrow \{\}$
foreach $\langle u, v \rangle \in \mathcal{E}$ **do**
$\quad$| $\quad$ **if** $d_v = 2$ and $d_u = 2$ and $|\mathcal{N}_{\mathcal{G}}(u) \cap \mathcal{N}_{\mathcal{G}}(v)| = 1$ **then**
$\quad$| $\quad$| $\quad c_{uv} \leftarrow 0$
$\quad$| $\quad$ **end**
$\quad$| $\quad$ **else**
$\quad$| $\quad$| $\quad c_{uv} \leftarrow (d_u - 1) \cdot (d_v - 1)$
$\quad$| $\quad$ **end**
end
$c \leftarrow \sum_{uv} c_{uv}$
foreach $\langle u, v \rangle \in \mathcal{E}$ **do**
$\quad$| $\quad p_{uv} \leftarrow c_{uv}/c$
end
for $i \leftarrow 1$ to K **do**
$\quad$| $\quad$ Sample $\langle v, w \rangle$ with probability p_{vw}
$\quad$| $\quad$ Uniformly sample a neighbor node u of v
$\quad$| $\quad$ Uniformly sample a neighbor node x of w
$\quad$| $\quad$ **if** $u \neq x$ **then**
$\quad$| $\quad$| $\quad \mathcal{B} \leftarrow \mathcal{B} \cup \{(u, v, w, x)\}$
$\quad$| $\quad$ **end**
end

In Algorithm 7, we present the algorithm for uniformly sampling graph patterns following $\Pi_{4-\texttt{cycle}}^-$ in $\mathcal{G}$. We provide the correctness and the time complexity of Algorithm 7 as follows.

Proof. Analogous to Algorithm 6, we formulate the sampling of refuting cases of $\Pi_{4-\texttt{cycle}}$ into uniformly sampling four-node paths namely (u, v, w, x). To first analyze the correctness of the algorithm, we first sample the intermediate edge of the path (i.e., $\langle v, w \rangle$). There are $(d_v - 1) \cdot (d_w - 1)$ three-edge paths (including triangles) where the intermediate edge is $\langle v, w \rangle$. Hence, we sample $\langle v, w \rangle$ with the probability proportional to $(d_v - 1) \cdot (d_w - 1)$, and then sample a neighbor node u from v and another one x from w, and reject the case when it forms a triangle.

To guarantee the time complexity, we do not sample the edge $\langle v, w \rangle$ when v and w have the only common neighbor, thus $\frac{|\mathcal{N}_{\mathcal{G}}(v) \cap \mathcal{N}_{\mathcal{G}}(w)|}{(d_v - 1) \cdot (d_w - 1)} \leq \frac{1}{2}$ when $c \neq 0$, i.e., we reject with probability no more than $\frac{1}{2}$, the expected time complexity is $O(|\mathcal{V}| + |\mathcal{E}| + K)$. $\qquad\square$

Notably, these algorithms are valuable because the number of the refuting cases are considerable in practice, and they make GraphANGEL more relevant for practical deployment.

A3 Implementation Details of GraphANGEL

A3.1 Algorithm for Implementation of GraphANGEL

Algorithm 8: Implementation of GraphANGEL

Input: Graph $\mathcal{G}$, Patterns $\Pi_1, \ldots, \Pi_P$, Source-target node dataset $\mathcal{D}$.
Output: Prediction $\hat{y}$ for each $\langle s, r, t \rangle$.
for *each pattern* Π_p **do**
  Construct $\Pi_p^*, \Pi_p^+, \Pi_p^-$.
  Search/Sample and Retrieve subgraphs following Π_p through Algorithms 2,3,4,6,7,5.
  Store all the subgraphs in $\mathcal{B}$.
end
for *each* $\langle s, r, t \rangle \in \mathcal{D}$ **do**
  for *each logic* Π_p **do**
    Sample and Retrieve K subgraphs $\mathcal{S}_{p,k}^*$ matching Π_p^* in $\mathcal{B}$.
    Sample and Retrieve Q subgraphs $\mathcal{S}_{p,q}^+$ matching Π_p^+ in $\mathcal{B}$.
    Sample and Retrieve Q subgraphs $\mathcal{S}_{p,q}^-$ matching Π_p^- in $\mathcal{B}$.
    Compute $\boldsymbol{e}_{p,k}^*, \boldsymbol{e}_{p,q}^+, \boldsymbol{e}_{p,q}^-$ according to Eq. (1).
  end
  Compute s^+, s^- according to Eq. (2).
  Calculate $\hat{y}$ via $\hat{y} = \frac{s^+}{s^+ + s^-}$.
  Update parameters by minimizing loss L shown in Eq. (3).
end

In Algorithm 1, we retrieve and sample subgraphs for every source-target node pair, which can be time-consuming. Algorithm 8 introduces additional steps that precompute all the graph patterns and their satisfying subgraphs as a *data preprocessing step*.

The intuition behind this is very straightforward that, as shown in Table 2, the graph patterns considered in this paper are quite simple, involving at most four nodes. For knowledge graphs, we can precompute all supporting and refuting patterns easily, retrieve all the subgraphs in 3-cycle and 4-cycle shapes on $\mathcal{G}$ and store them into the buffer $\mathcal{B}$. For heterogeneous graphs, since the graph schema of these graphs are usually not complex. We can cover all possible graph patterns by enumerating on the graph schema. Simiarly, this enables us to precompute the graph patterns and store all the retrieved subgraphs following each graph pattern in the buffer $\mathcal{B}$. We then can build an index of the buffer by the graph patterns as well as the subgraphs following each graph pattern. During training, we sample and retrieve subgraphs in the buffer instead of the whole graph for each source-target node pair. Compared with the original one in Algorithm 1, we reduce the complexity and improve the efficiency.

Note that in the heterogeneous graph based recommendation task, we follow (Hu et al., 2020; Wang et al., 2019b; Zhang et al., 2019) to predict the existence of edge between each given node pair $\langle s, t \rangle$, while in the knowledge graph completion task, we follow (Bordes et al., 2013; Sun et al., 2019; Dettmers et al., 2018) to mask head and tail entities instead of relation prediction. As the input of our model is a triplet $\langle s, r, t \rangle$, one can score all the possible triplets no matter either relation r or tail entity (i.e., node) t is masked. We then rank all these tuples for evaluation.

A3.2 Detailed Formulation of Φ in GraphANGEL

As introduced in Section 3, we apply a neural network $\Phi(\cdot)$ over each subgraph. These subgraphs can be from either target subgraph set $\{\mathcal{S}_{p,k}^*\}_{p=1,k=1}^{P,K}$, supporting subgraph set $\{\mathcal{S}_{p,q}^+\}_{p=1,q=1}^{P,Q}$, or refuting subgraph set $\{\mathcal{S}_{p,q}^-\}_{p=1,q=1}^{P,Q}$, as shown in Eq. (1). Formally, Φ maps each subgraph $\mathcal{S}_{p,k}^*, \mathcal{S}_{p,q}^+$ or $\mathcal{S}_{p,q}^-$ to the corresponding graph-level representations $\boldsymbol{e}_{p,k}^*, \boldsymbol{e}_{p,q}^+$ or $\boldsymbol{e}_{p,q}^-$. In the implementation, we adopt single layer R-GCN (Schlichtkrull et al., 2018) followed by any readout function (e.g., Mean($\cdot$), Max($\cdot$)) as $\Phi(\cdot)$.

(a) GraphANGEL   *(b) GCN, GraphSAGE, GAT*

(c) SEAL   *(d) PPNP, APPNP*

Figure A2: An illustrated example of nodes and edges involved in GraphANGEL and other existing approaches, where nodes and edges in grey are not activated while the other colors of nodes and edges represent their types. As introduced in Table 2, we here show the results of two graph patterns in 3-cycle shape. For clarity and simplicity, in this case, the number of layers of GNN models are constrained as one.

Taking $\mathcal{S}_{p,k}^*$ as an instance, we use $\boldsymbol{h}_{v,p,k}$ to denote the embedding of node v in the subgraph namely $v \in \mathcal{S}_{p,k}^*$, and $\mathcal{N}_{\mathcal{S}_{p,k}}^r(v)$ to denote the set of neighbor nodes of node v in $\mathcal{S}_{p,k}$ regarding relation type r. We compute $\boldsymbol{h}_{v,p,k}$ by

$$\boldsymbol{h}_{v,p,k} = \sigma(\sum_{r \in \mathcal{R}} \sum_{u \in \mathcal{N}_{\mathcal{S}_{p,k}}^r(v)} \boldsymbol{W}_r \boldsymbol{x}_u + \boldsymbol{W}_0 \boldsymbol{x}_v), \tag{11}$$

where $\boldsymbol{x}_.$ denote the input node features or learnable node embeddings, $\boldsymbol{W}_.$ denote trainable parameters, and σ is non-linearity function such as ReLU. After updating the embedding vectors of all the nodes, we further compute $\boldsymbol{e}_{p,k}^*$ by $\boldsymbol{e}_{p,k}^* = \texttt{Mean}(\{\boldsymbol{h}_{v,p,k} | v \in \mathcal{S}_{p,k}^*\})$. Computations of $\boldsymbol{e}_{p,q}^+$ and $\boldsymbol{e}_{p,q}^-$ are similar.

Specifically, in the case of Pair shape, R-GCN reduces to an MLP, and thus Φ here generally would not be worse than what an MLP could achieve.

A3.3 DETAILED FORMULATION OF Ψ IN GRAPHANGEL

As stated in Section 3, we deploy a neural network $\Psi(\cdot)$ to measure the similarity s^+ between the set of subgraphs matching $\Pi_1^*, \Pi_2^*, \ldots, \Pi_P^*$ and the set of subgraphs matching $\Pi_1^+, \Pi_2^+, \ldots, \Pi_P^+$; and the similarity s^- between the set of subgraphs matching $\Pi_1^*, \Pi_2^*, \ldots, \Pi_P^*$ and the set of subgraphs matching $\Pi_1^-, \Pi_2^-, \ldots, \Pi_P^-$.

Take the computation of s^+ as an example. We first reshape the subgraph embedding tensors $\boldsymbol{e}_{p,k}^*$ into matrices: $\boldsymbol{E}^* = \texttt{CONCAT}[\{\boldsymbol{e}_{p,k}^*, p = 1, \ldots, P; k = 1, \ldots, K\}] \in \mathbb{R}^{d \times (P \times K)}$, and similarly form $\boldsymbol{e}_{p,q}^+$ to $\boldsymbol{E}^+ \in \mathbb{R}^{d \times (P \times Q)}$, where d is the hidden representation size. We then compute the affinity

(a) An instance of Heterogeneous Graph

(b) Graph pattern considered in GraphANGEL

(c) Nodes and edges activated in GraphANGEL

(d) An instance of Homogeneous Graph

(e) Graph pattern considered in GraphANGEL

(f) Nodes and edges activated in GraphANGEL

Figure A3: An illustrated example of how GraphANGEL works on both the heterogeneous graph shown in (a) and the homogeneous graph shown in (d), where the colors of the nodes and edges represent their types in the heterogeneous graph. For the heterogeneous graph, GraphANGEL can automatically find the graph pattern by scanning on the graph schema by given shapes (e.g., Pair, 3-cycle, 4-cycle). We show an example graph pattern in (b). Based on the graph and graph pattern, we show the nodes and edges activated in GraphANGEL in (c), where the nodes and edges in colors are activated and those in black are not activated. However, for the homogeneous graph, since there is no graph pattern based on the node and edge type, we design the graph pattern directly based on the shape (i.e., hexagon shape in (e)). We then show the nodes and edges activated in (f), where nodes and edges in red construct a subgraph following target pattern and the green ones compose a subgraph following analogy pattern.

matrix as

$$\boldsymbol{A} = \text{tanh}(\boldsymbol{E^*}^\top \boldsymbol{W}_c \boldsymbol{E}^+) \in \mathbb{R}^{(P \times K) \times (P \times Q)}, \tag{12}$$

where $\boldsymbol{W}_c \in \mathbb{R}^{d \times d}$ are trainable weights. With the affinity matrix $\boldsymbol{A}$, one possible way of computing attention is to simply maximize out the affinity, namely $\boldsymbol{a}^+[j] = \text{Max}_i(\boldsymbol{A}_{i,j})$ and $\boldsymbol{a}^*[i] = \text{Max}_j(\boldsymbol{A}_{i,j})$. Instead of using the max activation, we follow (Lu et al., 2016), considering this affinity matrix as a feature and learning the attention map via following:

$$\boldsymbol{H}^* = \boldsymbol{W}_* \boldsymbol{E}^*, \ \boldsymbol{H}^+ = \boldsymbol{W}_+ \boldsymbol{E}^+ \tag{13}$$

which are used to compute the attention map among $\boldsymbol{E}^*$ and $\boldsymbol{E}^+$ through

$$\boldsymbol{a}^* = \text{softmax}(\boldsymbol{w}_*^\top \text{tanh}(\boldsymbol{H}^* + \boldsymbol{H}^+ \boldsymbol{A})), \ \boldsymbol{a}^+ = \text{softmax}(\boldsymbol{w}_+^\top \text{tanh}(\boldsymbol{H}^+ + \boldsymbol{H}^* \boldsymbol{A})), \tag{14}$$

where $\boldsymbol{W}_* \in \mathbb{R}^{d \times d}$ and $\boldsymbol{W}_+ \in \mathbb{R}^{d \times d}$, $\boldsymbol{w}_* \in \mathbb{R}^d$ and $\boldsymbol{w}_+ \in \mathbb{R}^d$ are the weight parameters. $\boldsymbol{a}^* \in \mathbb{R}^{(P \times K)}$ and $\boldsymbol{a}^+ \in \mathbb{R}^{(P \times Q)}$. We finally obtain the set embedding via

$$\boldsymbol{h}^+ = \boldsymbol{E}^+ \boldsymbol{a}^{+\top}, \ \boldsymbol{h}^* = \boldsymbol{E}^* \boldsymbol{a}^{*\top}, \tag{15}$$

which is the weighted average of the subgraph embeddings in matrix $\boldsymbol{E}^+$ and $\boldsymbol{E}^*$. The similarity of supporting patterns is $s^+ = \boldsymbol{h}^{+\top} \boldsymbol{h}^*$. Computation of s^- is similar.

A4 FURTHER ANALYSIS OF GRAPHANGEL

A4.1 LIMITATIONS OF GRAPHANGEL

In order to further analyse the limitations of GraphANGEL, we first compare our framework with exsiting GNN methods. As shown in Figure A2, we provide an illustrated example of nodes and edges activated and not activated in various GNN models, including GCN (Kipf & Welling, 2016), GraphSAGE (Hamilton et al., 2017), GAT (Veličković et al., 2017), SEAL (Zhang & Chen, 2018), PPNP and APPNP (Approximate PPNP) (Klicpera et al., 2018), and our model GraphANGEL. With

Table A1: Main statistics of heterogeneous graphs.

Datasets	Relations (A-B)	#A	#B	#A-B	Datasets	Relations (A-B)	#A	#B	#A-B
LastFM	User-Artist	2,101	18,746	92,834	Amazon	User-Item	6,170	2,753	146,230
	User-User	2,101	2,101	25,434		Item-View	2,753	3,857	5,694
	User-Tag	2,101	12,648	186,479		Item-Brand	2,753	334	2,753
	Artist-Tag	18,746	12,648	186,479		Item-Category	2,753	22	5,508
Yelp	User-Business	16,239	14,284	198,397	Douban Book	User-Book	13,024	22,347	598,420
	User-User	16,239	16,239	158,590		User-User	13,024	13,024	169,150
	User-City	16,239	47	76,875		User-Group	13,024	2,936	1,189,271
	Business-City	14,284	47	14,267		Book-Author	22,347	10,805	21,907
	Business-Genre	14,284	511	40,009		Book-Publisher	22,347	1,815	21,773

Table A2: Main statistics of knowledge graphs.

Datasets	#Entities	#Relations	#Training	#Validation	#Test
FB15k-237	14,541	237	272,115	17,535	20,466
WN18RR	40,943	11	86,835	3,304	3,134

a limited number of GNN layers, one can easily observe that these existing approaches only involve all context within the "neighborhood". Instead, GraphANGEL searches and retrieves the subgraphs in the whole graph, which not only removes the limitation of neighborhood constriction but also select pattern (i.e., logic) related information.

Although from the analysis above, we can see that GraphANGEL can succeed in those cases where existing GNN models fail; however, leveraging logically-induced graph patterns can also be a limitation of GraphANGEL, especially when it is hard to find or design such graph patterns. For example, if the two nodes for link prediction are far away from each other, the graph patterns considered in our experiments may be not able to cover the cases, and it is also hard to define what a graph pattern should be. We note that such cases are rare in real-world graphs as they are usually scale-free, meaning that the topological distance is usually small.

A4.2 EXTENSIONS OF GRAPHANGEL TO HOMOGENEOUS GRAPH

One may consider that heterogeneous graph may be another potential limitation of GraphANGEL. However, we note that extending GraphANGEL to homogeneous graphs is possible with graph patterns that are not type-sensitive, i.e., not containing type-specific indicator operators $\text{Edge}_r(x, y)$. In other words, the graph patterns will be purely based on topology. For example, we can define 6-cycle for the graph in Figure A3(d).

Following the analysis above, although nodes t and v in both Figure A3(a) and (d) have similar neighborhood structures, our GraphANGEL is able to project these two source-target node pairs (i.e., $\langle s, r, t \rangle$ and $\langle v, r, t \rangle$) into different embeddings on both heterogeneous and homogeneous graphs.

A4.3 EXTENSIONS OF GRAPHANGEL TO COMPLEX LOGIC

Another potential limitation of GraphANGEL is that the graph searching stage limits the model's capability of exploring more complex graph patterns. We admit that the graph pattern involved in our paper is simple and rudimentary, but we argue that efficient finding arbitrary graph patterns including those complex ones should be mainly investigated by graph database and pattern matching literature, which is definitely not the focus of our paper. Our key idea is general since one can pre-define any pattern to search and retrieve subgraphs.

Moreover, the following corollary shows that the representations of complex logical formulas can be derived from those of simpler ones. This, to some extent, provides the theoretical support of only involving simple graph patterns (e.g., Pair, 3-cycle, 4-cycle) in the implementation.

Lemma 1. *(Barceló et al., 2019)* (Expressive Power on Logic Expressions of Nodes) *Each First-Order Classifier with 2 variables (FOC_2) can be captured by Aggregation and Combination GNN formulated as*

$$\boldsymbol{x}_i^{(l)} = \text{COM}(\boldsymbol{x}_i^{(l-1)}, \text{AGG}(\{\boldsymbol{x}_j^{(l-1)} | j \in \mathcal{N}_\mathcal{G}(i)\})), \ \forall i \in \mathcal{V}, \quad (16)$$

where $\text{AGG}(\mathcal{X}) = \sum_{\boldsymbol{x} \in \mathcal{X}} \boldsymbol{x}$ *and* $\text{COM}(\boldsymbol{x}, \boldsymbol{y}) = \sigma(\boldsymbol{x}\boldsymbol{C} + \boldsymbol{y}\boldsymbol{A} + \boldsymbol{b})$.

Corollary 1. (Expressive Power on Logic Expressions of Subgraphs) *Let* $\boldsymbol{e}_x = \{e_1, \ldots, e_P\} \in \mathbb{R}^P$ *be the representation vector of subgraph* $\mathcal{S}_x$*, where* $e_p = 1$ *if subgraph* $\mathcal{S}_x$ *matches graph pattern*

Table A3: Comparable results with baselines, where there are 20% least frequent relations. Here we report the results in term of MR, MRR, Hit@K (K=1,3,10).

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet	192	0.284	0.209	0.342	0.500	3891	0.378	0.341	0.406	0.491
TransE	198	0.296	0.197	0.339	0.494	3713	0.203	0.123	0.367	0.487
ConvE	266	0.295	0.207	0.324	0.478	4561	0.391	0.364	0.391	0.479
ComplEx	367	0.226	0.140	0.261	0.409	5709	0.402	0.375	0.428	0.475
MLN	2235	0.087	0.051	0.077	0.143	13056	0.225	0.166	0.285	0.333
RotatE	200	0.302	0.211	0.351	0.505	3630	0.435	0.386	0.445	0.529
RNNLogic	263	0.302	0.219	0.333	0.499	4659	0.438	0.407	0.444	0.511
ComplEx-N3	177	0.334	0.242	0.361	0.534	3481	0.448	0.407	0.456	0.539
GraIL	230	0.281	0.197	0.315	0.484	3949	0.362	0.307	0.387	0.458
GraphANGEL$_{3-cycle}$	174	0.324	0.243	0.384	0.539	3139	0.445	0.418	0.465	0.549
GraphANGEL$_{4-cycle}$	181	0.317	0.215	0.366	0.526	3169	0.450	0.421	0.467	0.549
GraphANGEL	**167**	**0.336**	**0.248**	**0.394**	**0.541**	**3108**	**0.458**	**0.429**	**0.481**	**0.557**

Π^x_p and $e_p = 0$ otherwise, and $\Pi^x_1, \cdots, \Pi^x_P$ are sub-formulas of Π^x, in the order where if Π^x_k is a sub-formula of Π^x_l then $k \leq l$. Suppose that the representation vectors e_x and e_y of subgraph $\mathcal{S}_x$ and $\mathcal{S}_y$ matching pattern Π^x and Π^y respectively, are given. If Π^z takes either of the following forms:

- $\Pi^z = \neg\Pi^x$
- $\Pi^z = \Pi^x \wedge \Pi^y$
- $\Pi^z = \Pi^x \vee \Pi^y$

Then there exists $\boldsymbol{W}^x \in \mathbb{R}^{P \times P}$, $\boldsymbol{W}^y \in \mathbb{R}^{P \times P}$, and $\boldsymbol{b} \in \mathbb{R}^P$, such that

$$\boldsymbol{e}_z = \min(\max(\boldsymbol{W}^x \boldsymbol{e}_x + \boldsymbol{W}^y \boldsymbol{e}_y + \boldsymbol{b}, 0), 1)$$

is a representation vector of a subgraph $\mathcal{S}_z$ matching Π^z.

Proof. The entries of the p-th columns of $\boldsymbol{W}^x$, $\boldsymbol{W}^y$, and $\boldsymbol{b}$ depend on the formulas of $\Pi^{x,y}$ as follows.

- if $\Pi^{x,x}_p = \Pi^x_i$, then $\boldsymbol{W}^x_{ip} = 1$.
- if $\Pi^{x,y}_p = \Pi^x_i \wedge \Pi^y_j$, then $\boldsymbol{W}^x_{ip} = 1$, $\boldsymbol{W}^x_{jp} = 1$, and $\boldsymbol{b}_p = -1$.
- if $\Pi^{x,y}_p = \Pi^x_i \vee \Pi^y_j$, then $\boldsymbol{W}^x_{ip} = 1$, $\boldsymbol{W}^x_{jp} = 1$, and $\boldsymbol{b}_p = 0$.
- if $\Pi^{x,x}_p = \neg\Pi^x_i$, then $\boldsymbol{W}^x_{ip} = -1$ and $\boldsymbol{b}_p = 1$.

All other values in the p-th columns of $\boldsymbol{W}^x$, $\boldsymbol{W}^y$, and $\boldsymbol{b}$ are 0. Our proof follows the proof of Lemma 1 in (Barceló et al., 2019). The only differences are: (1) as the input of the basic logic formula in (Barceló et al., 2019) is nodes while in our paper is subgraph, thus the basic logic in (Barceló et al., 2019) is the color of nodes (i.e., Col($\cdot$)), but in our setting is the graph pattern for subgraphs; (2) we only involve the basic logical operators $\wedge$, $\vee$ and $\neg$ in our paper. $\square$

Besides the prior literature (Barceló et al., 2019) studying the theoretical expressive power of GNNs, our work is also kind of related to a thread of works (Minervini et al., 2020a;b; Weber et al., 2019) on Neural Theorem Provers, where they first assume template rules and then find which relations can satisfy them. In contrast, our work bridges the connection between logical expression and graph patterns and use the subgraphs to represent the rules. This intuition enables our model empowered by the expressive power of GNNs, and also allows our work to identify new relation types.

A5 DETAILED EXPERIMENTAL SETTINGS

A5.1 DATASET STATISTICS

The statistics of the datasets of heterogeneous graph based recommendation and knowledge graph completion used in our paper are displayed in Table A1 and Table A2, respectively.

A5.2 HYPER-PARAMETERS

For the baseline methods, we employ these baseline methods based on Deep Graph Library (DGL) (Wang et al., 2019a) following their original setting or directly use their original implementations: (1)

Table A4: Result comparisions with baselines on generalization setting by randomly removing 5% relations. Here we report the results in term of MR, MRR, Hit@K (K=1,3,10).

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet*	185	0.309	0.220	0.341	0.487	3646	0.410	0.370	0.414	0.500
TransE*	191	0.306	0.215	0.338	0.489	3614	0.209	0.230	0.378	0.499
ConvE*	268	0.292	0.213	0.320	0.450	4605	0.387	0.361	0.396	0.469
ComplEx*	366	0.227	0.145	0.252	0.393	5681	0.404	0.371	0.423	0.472
MLN*	2277	0.083	0.056	0.087	0.135	13281	0.220	0.168	0.273	0.306
RotatE*	189	0.317	0.227	0.353	0.500	3624	0.439	0.398	0.458	0.531
RNNLogic*	248	0.319	0.235	0.353	0.493	4865	0.456	0.419	0.472	0.523
ComplEx-N3*	167	0.350	0.256	0.380	0.527	3625	0.466	0.418	0.475	0.551
GraIL*	221	0.296	0.205	0.332	0.478	3817	0.372	0.326	0.402	0.459
GraphANGEL$_{3-cycle}$	166	0.349	0.259	0.379	0.532	3061	0.468	0.441	0.472	0.566
GraphANGEL$_{4-cycle}$	173	0.335	0.229	0.365	0.525	3049	0.472	0.446	0.480	0.558
GraphANGEL	**158**	**0.357**	**0.263**	**0.388**	**0.537**	**2948**	**0.482**	**0.450**	**0.492**	**0.572**

Table A5: Result comparisions with baselines on generalization setting by randomly removing 10% relations. Here we report the results in term of MR, MRR, Hit@K (K=1,3,10).

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet*	204	0.272	0.194	0.298	0.429	4021	0.361	0.326	0.365	0.440
TransE*	215	0.264	0.185	0.294	0.422	4057	0.180	0.109	0.324	0.430
ConvE*	290	0.263	0.191	0.285	0.405	4982	0.348	0.324	0.356	0.421
ComplEx*	393	0.207	0.132	0.229	0.359	6102	0.369	0.3444	0.386	0.428
MLN*	2475	0.007	0.05	0.077	0.120	14436	0.194	0.143	0.241	0.270
RotatE*	207	0.279	0.199	0.307	0.437	3941	0.391	0.353	0.403	0.470
RNNLogic*	275	0.280	0.206	0.310	0.431	5469	0.395	0.364	0.408	0.452
ComplEx-N3*	187	0.304	0.224	0.331	0.462	4084	0.404	0.362	0.412	0.479
GraIL*	243	0.261	0.181	0.293	0.423	4208	0.327	0.287	0.359	0.410
GraphANGEL$_{3-cycle}$	184	0.306	0.226	0.333	0.466	3409	0.412	0.386	0.414	0.490
GraphANGEL$_{4-cycle}$	192	0.293	0.200	0.319	0.460	3392	0.414	0.388	0.419	0.489
GraphANGEL	**176**	**0.313**	**0.232**	**0.343**	**0.475**	**3259**	**0.423**	**0.398**	**0.434**	**0.504**

HetGNN (Zhang et al., 2019) is a unified framework that jointly considers heterogeneous structured information as well as heterogeneous content information. (2) HAN (Wang et al., 2019b) is a hierarchical attention mechanism designed on heterogeneous graph to capture node-level and semantic-level information. (3) TAHIN (Bi et al., 2020) is a cross domain model from both source and target domain, which is then incorporated with three-level attention aggregations to get node representation. (4) HGT (Hu et al., 2020) is a heterogeneous graph transformer architecture that characterize the heterogeneous attention over each edge. (5) R-GCN (Schlichtkrull et al., 2018) combines graph neural networks with factorization models for link prediction. (6) pLogicNet (Qu & Tang, 2019) is an EM-based algorithm that simultaneously trains a rule generator as well as reasoning predictor with logic rules. (7) TransE (Bordes et al., 2013) is a translation-based relation prediction model. (8) ConvE (Dettmers et al., 2018) is convolution-based relation prediction model. (9) ComplEx (Trouillon et al., 2016) uses the composition of complex embeddings to handle a large variety of binary relations. (10) MLN (Singla & Domingos, 2005) leverages domain knowledge to predict relations. (11) RotatE (Sun et al., 2019) is a rotation-based relation prediction model. (12) RNNLogic (Qu et al., 2020) defines the joint distribution of all possible triplets by using Markov logic network which can be efficiently optimized with the variational EM algorithm. (13) ComplEx-N3 (Lacroix et al., 2018) introduces a regularizer based on tensor nuclear p-norms for relation prediction. (14) GraIL (Teru et al., 2020) reasons over local subgraph structures and holds a strong inductive bias to learn entity-independent relational semantics.

We keep all hyper-parameter settings in their original implementations, except the following ones for fair comparisons. All models involving GNN layers are set to have similar layers (2 or 3 layers, depending on the performance) and are trained for the same number of epochs. We fix model configurations across all experiments. For all baseline GNN models and GraphANGEL, the dimension size of the embeddings is set to 128, and the learning rate space is {0.001, 0.0001}. The dropout of input is set to 0.6, of edge is set to 0.3. Notably, the results reported in our paper are comparable with those in their original papers. For GraphANGEL, the graph patterns in the implementation are reported in Table 2, the number of target subgraphs K is set as 32 and the number of analogy subgraphs Q (for both supporting and refuting patterns) is set as 64. All experimental comparisons are conducted with 10 different random seeds.

Table A6: Result comparisions with baselines on generalization setting by randomly removing 15% relations. Here we report the results in term of MR, MRR, Hit@K (K=1,3,10).

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet*	230	0.222	0.158	0.245	0.351	4532	0.295	0.266	0.298	0.359
TransE*	249	0.202	0.142	0.224	0.323	4705	0.138	0.083	0.248	0.329
ConvE*	324	0.217	0.158	0.236	0.335	5568	0.288	0.268	0.294	0.348
ComplEx*	444	0.170	0.109	0.189	0.295	6891	0.303	0.282	0.317	0.351
MLN*	2633	0.065	0.044	0.229	0.107	15360	0.173	0.127	0.215	0.241
RotatE*	237	0.221	0.160	0.245	0.352	4482	0.319	0.287	0.325	0.376
RNNLogic*	311	0.225	0.165	0.249	0.350	6221	0.313	0.292	0.327	0.368
ComplEx-N3*	210	0.252	0.185	0.268	0.377	4557	0.334	0.297	0.337	0.392
GraIL*	275	0.213	0.147	0.239	0.347	4728	0.267	0.234	0.291	0.334
GraphANGEL$_{3-cycle}$	210	0.250	0.185	0.273	0.385	3823	0.340	0.319	0.343	0.407
GraphANGEL$_{4-cycle}$	216	0.243	0.165	0.264	0.381	3797	0.344	0.323	0.349	0.407
GraphANGEL	**198**	**0.259**	**0.192**	**0.289**	**0.391**	**3684**	**0.351**	**0.324**	**0.354**	**0.415**

Table A7: Result comparisions with baselines on generalization setting by randomly removing 20% relations. Here we report the results in term of MR, MRR, Hit@K (K=1,3,10).

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet*	261	0.162	0.112	0.179	0.257	5146	0.216	0.141	0.222	0.267
TransE*	280	0.146	0.101	0.163	0.246	5285	0.100	0.072	0.200	0.260
ConvE*	366	0.162	0.104	0.178	0.247	6280	0.215	0.201	0.223	0.268
ComplEx*	501	0.128	0.078	0.142	0.226	7786	0.228	0.214	0.236	0.267
MLN*	3029	0.046	0.031	0.049	0.070	17669	0.121	0.092	0.154	0.178
RotatE*	269	0.176	0.121	0.187	0.271	4849	0.218	0.238	0.260	0.296
RNNLogic*	349	0.151	0.124	0.172	0.240	6728	0.248	0.244	0.260	0.281
ComplEx-N3*	232	0.208	0.142	0.208	0.289	5064	0.259	0.250	0.269	0.311
GraIL*	304	0.173	0.125	0.185	0.263	5315	0.212	0.195	0.222	0.267
GraphANGEL$_{3-cycle}$	223	0.225	0.168	0.230	0.333	4098	0.297	0.277	0.291	0.329
GraphANGEL$_{4-cycle}$	227	0.206	0.147	0.222	0.328	4146	0.297	0.278	0.291	0.326
GraphANGEL	**208**	**0.227**	**0.173**	**0.238**	**0.337**	**3956**	**0.305**	**0.284**	**0.299**	**0.334**

A5.3 HARDWARE SETTINGS

The models are trained under the same hardware settings with an Amazon EC2 p3.8×large instance[1], where the GPU processor is NVIDIA Tesla V100 processor and the CPU processor is Intel Xeon E5-2686 v4 (Broadwell) processor.

A6 ADDITIONAL RESULTS

A6.1 ADDITIONAL RESULTS OF STANDARD TASK

We show the results of comparisons between GraphANGEL against the baseline methods testing with 20% least frequent relations in terms of MR, MRR, Hit@1, Hit@3 and Hit@10 in Table A3.

A6.2 ADDITIONAL RESULTS OF GENERALIZATION STUDY

Table A4 shows the results of performance in terms of MR, MRR, Hit@K (K=1,3,10) after randomly removing 5% relations. We also report the results after randomly dropping 10%, 15% and 20% in Tables A5, A6 and A7. In addition to randomly dropping the relations, we also evaluate the performance when we randomly adding 5% relations by combining the existing relations through Composition Rules, Inverse Rules, Symmetric Rules, Subrelation Rules discussed in (Qu & Tang, 2019). The results are reported in Table A8. These experimental results verify that GraphANGEL is significantly less affected by dropping or adding relations, which demonstrates the better generalizability of our model to unseen relation types against these state-of-the-art methods..

---

[1]Detailed setting of AWS E2 instance can be found at https://aws.amazon.com/ec2/instance-types/?nc1=h_ls.

Table A8: Result comparisions with baselines on generalization setting by randomly adding 5% relations. Here we report the results in terms of MR, MRR, Hit@K (K=1,3,10).

Models	FB15k-237					WN18RR				
	MR	MRR	Hit@1	Hit@3	Hit@10	MR	MRR	Hit@1	Hit@3	Hit@10
pLogicNet*	187	0.305	0.218	0.337	0.482	3680	0.405	0.366	0.410	0.494
TransE*	197	0.296	0.208	0.330	0.474	3716	0.202	0.122	0.364	0.483
ConvE*	275	0.282	0.206	0.309	0.435	4731	0.374	0.348	0.382	0.452
ComplEx*	366	0.227	0.145	0.253	0.393	5681	0.404	0.377	0.423	0.469
MLN*	2277	0.083	0.056	0.087	0.136	13281	0.220	0.162	0.273	0.306
RotatE*	191	0.311	0.222	0.345	0.492	3590	0.438	0.398	0.452	0.526
RNNLogic*	252	0.315	0.231	0.347	0.484	5019	0.442	0.411	0.457	0.513
ComplEx-N3*	171	0.343	0.253	0.370	0.516	3728	0.369	0.323	0.405	0.462
GraIL*	223	0.293	0.213	0.332	0.475	3842	0.368	0.323	0.399	0.457
GraphANGEL$_{3-cycle}$	170	0.340	0.251	0.373	0.525	3104	0.458	0.434	0.465	0.555
GraphANGEL$_{4-cycle}$	176	0.329	0.225	0.354	0.514	3109	0.461	0.434	0.470	0.552
GraphANGEL	**161**	**0.349**	**0.258**	**0.382**	**0.527**	**3004**	**0.471**	**0.440**	**0.480**	**0.558**

Figure A4: Illustrations of generated heat map of attention scores. While Figure 5 can provide a global view for each graph pattern, this figure can see the importance of detailed subgraphs.

A6.3 ADDITIONAL RESULTS OF HEAT MAP

We show the detailed attention heat map of Douban Book dataset in Figure A4 and Figure 5 in the main text is a simplification of this figure. One can see that based on the heat map, we can not only have a global view for each graph pattern, but also see the importance of each subgraph.

Specifically, Figure A4 visualizes the attention heat map between target subgraphs and supporting subgraphs when predicting relations between users and books. The rows represent the supporting subgraphs while the columns represent the target subgraphs. We denote each subgraph as a tuple of node IDs, e.g., $\mathcal{S}_7^+ = (u_{107}, b_{11}, a_{33}, b_{12})$. Each cell represents the similarity between a target subgraph (at the top) and a supporting subgraph (at bottom). The color of each cell shows the attention weight for corresponding pair of supporting and target subgraphs. We can observe that the deep color of the cell located at the interaction of $\mathcal{S}_7^*$ and $\mathcal{S}_{32}^+$ indicates more similarity. We can see from the figure that the cells with darkest color have both target subgraph and supporting subgraph as $(u_., b_., a_., b_.)$, which indicates a subgraph with User − Book − Author − Book pattern, meaning that this particular pattern is more influential in predicting User − Book relation. Notably, this result reveals a simple logic User ∧ Book ∧ Author ∧ Book ⇒ User ∧ Book indicating a simple factor that the users are likely to be interested in the book sharing the same authors with his reading ones. Hence, our method can intuitively be regarded as the a logical collaborative filtering technique working on graph. Similarly, we can find that 3-cycle pattern (Person) − Impersonate^{-1} − (Person) ∧ (Person)−Nationality−(Nation) ⇒ (Person)−Nationality−(Nation) plays an important role in FB15k-237 dataset, where inverse relations are denoted with a superscript^{-1}.

A6.4 ADDITIONAL RESULTS OF TIME COMPLEXITY

As the prevailing methods on knowledge completion task are mainly based on either on translation (Bordes et al., 2013) or rotation (Sun et al., 2019) assumptions regardless of the graph structure, they are naturally much more efficient than GNN based relation prediction models. We here mainly compare the time complexity of GraphANGEL in term of both training and inference times on Amazon dataset against aforementioned baseline methods. Result in Figure A5 reveals that GraphANGEL is more efficient than HGT and HAN in term of training time and is more efficient than R-GCN and HGT in term of inference time. One possible explanation is that HAN, HGT, and R-GCN contain the whole graph, which is much more complex than sampled subgraphs.

Figure A5: Time comparisons of GraphANGEL against baseline models on Amazon dataset.