A Closer Look at the Intervention Procedure of Concept Bottleneck Models

Abstract

Concept bottleneck models (CBMs) [1] are a class of interpretable neural network models that predict the target label of a given input based on its high-level concepts. Unlike other end-to-end deep learning models, CBMs enable domain experts to intervene on the predicted concepts at test time so that more accurate and reliable target predictions can be made. While the intervenability provides a powerful avenue of control, many aspects of the intervention procedure remain underexplored. In this work, we inspect the current intervention practice for its efficiency and reliability. Specifically, we first present an array of new intervention methods to significantly improve the target prediction accuracy for a given budget of intervention expense. We also bring attention to non-trivial yet unknown issues related to reliability and fairness of the intervention and discuss how we can fix these problems in practice.

1 Introduction

Recent advances in deep learning have made remarkable success in various areas of machine learning [2, 3]. However, standard neural network models are still not easily explainable, making it difficult for humans to understand the rationale behind or improve upon the decision-making process of these models. To tackle this issue, various sets of interpretable models have been proposed, for example, using concept activation vectors [4, 5] or building intrinsically interpretable architectures [6].

Concept bottleneck models (CBMs) are among these to empower interpretability [1, 7, 8, 9, 10, 11]. Unlike standard end-to-end models, CBMs seek to learn two-step models that utilize high-level concepts in making their final predictions: it first predicts human-understandable concept values for a given input using the concept predictor g, and then the subsequent prediction is made for the target task using the target predictor f; for example, classify the species of a bird image based on its wing pattern or leg color rather than straight from the input image (see Figure 1a).

Revisited recently by [1], this classic idea further facilitates human-model interaction in addition to plain interpretability, in that it allows one to *intervene* on the predicted concepts at test time, such that the subsequent target prediction can be made based on the rectified concept values. By intervening on the incorrectly predicted concepts and updating their values to correct ones, CBMs can potentially make more accurate and reliable prediction results.

Surprisingly, however, many aspects of the intervention procedure, for example that specifies which concept to intervene first, have not been studied much in the literature despite its potential implications in practice; previous works have rather focused on either increasing the final prediction accuracy of CBMs [8, 9], removing the impact of confounding information [7], or analyzing the information leakage problems [10, 11]. Indeed we find that intervening on mis-predicted concept values can have a potentially critical impact on the final task accuracy (see Figure 1b). Considering the cost of the

Submitted to 2022 Trustworthy and Socially Responsible Machine Learning (TSRML 2022). Do not distribute.

(a) concept bottleneck models

(b) concept vs. task errors

Figure 1: (a) Given an input data a CBM first predicts high-level concepts ($g : x \rightarrow c$), and then based on which it makes final prediction for the target task ($f : c \rightarrow y$). (b) The task error quickly increases with more errors in concept prediction. For example, making one concept prediction wrong (*i.e.*, concept error in number is at 1) leads to about 25% increase in the final task error; in other words, fixing a small number of mis-predicted concepts has the potential to significantly improve the effectiveness of CBMs.

36 intervention process, *i.e.*, having domain experts go over each concept, this result further indicates
37 the necessity of more effective and efficient intervention procedure to ensure the utility of CBMs.

38 In this work, we first evaluate different intervention methods and observe that the existing method,
39 which randomly selects concepts to intervene, can be improved significantly. Furthermore, we
40 find that some factors can threaten the reliability or fairness of CBMs, especially in terms of the
41 intervention, and suggest some techniques to address these problems.

2   Related work

43 There have been some attempts to improve the limitations of the original CBMs [7, 8, 9]. Among
44 them, a very recent work by Zarlenga *et al*. [9] is in some sense similar to ours in that they propose
45 the new model which supports effective intervention; it decreases task error more than original CBMs
46 [1] after intervening all the concept values. To build such model, they adopt the specific technique
47 in training time which helps the model to be effective at intervention. However, our work differs
48 from this one as we focus on improving the intervention method itself. Other previous works try to
49 increase the performance of the model either by removing the impact of confounding information [7]
50 or adding unsupervised concepts [8], but they also do not directly address the intervention procedure.
51 As of our knowledge, our work is the first to analyze CBMs in terms of intervention, one of the most
52 important features of the models.

53 In addition, another line of works aims at analyzing the non-trivial problems lying in CBMs. Specif-
54 ically, [10] and [11] argue that information leakage can occur, *i.e.*, the model can encode more
55 information in the concept predictor g than ground-truth concepts specified in the dataset so as to
56 increase the performance. This problem decreases the interpretability of the model and makes it hard
57 to understand the reason behind the model's prediction. In the similar vein, we further analyze what
58 can threaten the reliability or fairness of the models and discuss some possible solutions.

3   Methods

60 In this section, we introduce the set of intervention methods we consider to be applicable for CBMs.
61 To be specific, each method defines a criterion for determining the order of concepts to be intervened
62 on. We use $g(\cdot)$ and $f(\cdot)$ to denote the concept predictor and the target predictor, respectively. We
63 also use $\hat{c}_i \in [0, 1]$ and $c_i^{\text{GT}} \in \{0, 1\}$ to denote the predicted and the true value of the i-th concept c_i.
64 Note that we are assuming each ground-truth concept as a binary variable representing the existence
65 of the attribute as they are usually in most real-world datasets experimented in [1, 9, 11].

66 **Random**   Following the original work [1], this method randomizes the order of the intervention. To
67 be specific, it samples each concept from a uniform distribution to determine the order.

Concept uncertainty This method first intervenes on the concept with the highest predictive uncertainty from the concept predictor $g(\cdot)$. It is inspired by active learning [12], whose goal is to increase the performance of the model with the minimum amount of labeling cost. Such an idea is applicable to the intervention of CBMs since it also aims at decreasing the task error with the minimum amount of concept labeling cost. Based on [13, 14], this method measures the uncertainty of a binary concept prediction $\hat{c}_i$ as the inverse of its distance to the value 0.5, *i.e.*, it first intervenes on the concept with the minimum value of $|\hat{c}_i - 0.5|$. Note that other popular uncertainty estimation methods like maximum entropy [15], least confidence [16], or smallest margin [17] all leads to the same intervention orders when the concepts take binary values.

Concept importance This method prioritizes the intervention on the concept which is the most "important" for class label prediction, since mis-predicting such a concept results in a significant increase in the task error. In the case when f is 1-layer MLP, we define the concept importance as the product of the predicted value and the sum of related weights, *i.e.*, $\hat{c}_i \sum_{j=1}^{M} |w_{ij}|$, inspired by Grad-CAM [18], . Here, w_{ij} is the weight of the i-th concept to the j-th class in f and M is the number of target classes.

KL divergence Next, we consider intervening on the concept with the most impact on the target predictive distribution when the concept value changes after the intervention. To this end, this method computes the expected distribution of target class prediction after intervening on c_i as follows:

$$\hat{y}_{\text{tti}}^i = \text{Softmax}((1 - \hat{c}_i) \cdot f(\hat{c}; c_i = 0) + \hat{c}_i \cdot f(\hat{c}; c_i = 1)).$$

Here, $f(\hat{c}; c_i = 0)$ and $f(\hat{c}; c_i = 1)$ denote outputs of f when i-th concept is manually set to 0 and 1 respectively. We weight these two values using $\hat{c}_i$, the model's confidence in the presence of i-th concept. Then, this method utilizes Kullback-Leibler (KL) divergence [19] to measure the change between the target predictive distributions before and after the intervention, *i.e.*, $D_{KL}(\hat{y}_{\text{tti}}^i \| \hat{y})$. Finally, it first intervenes on the concept with the largest amount of change.

Smallest margin This method measures the expected uncertainty in the target class with respect to the i-th concept intervention. Among the various candidates for the uncertainty estimation, we consider the smallest margin [17]. This method prioritizes intervening on the concept c_i with the largest margin of $(y_1^*)^{\{i\}} - (y_2^*)^{\{i\}}$ where $(y_1^*)^{\{i\}}$ and $(y_2^*)^{\{i\}}$ denote the first and second largest target class probability in $\hat{y}_{\text{tti}}^i$. Note that we also considered other scores such as maximum entropy [15] and least confidence [16], but the smallest margin performed the best (see Appendix C for the results).

Largest concept loss This method intervenes on the concept with the largest concept prediction loss. This way, it simulates the "oracle" metric for measuring the concept uncertainty. To be specific, it intervenes on the concept in the decreasing order of $|c_i^{\text{GT}} - \hat{c}_i|$. However, we remark that the ground-truth concept values are not available at test time, so it is hard to use this method in practice. Nonetheless, by comparing with the other methods which do not use the ground-truths, it can tell us how much a specific intervention method can be improved.

4 Experimental Setup

Dataset All the experiments are conducted using the CUB dataset [20] which is the standard dataset used to study CBMs. There are 5994 and 5794 examples for train and test sets in total, in which each example consists of the triplet of (image x, concepts c, label y) of a bird species. All the concepts have binary values; for example, the 'wing color:black' for a given bird image can be either 1 (for true) or 0 (for false). Following previous works [1, 8, 9], we perform so-called majority voting as pre-processing so that images of the same class always have the same concept values; for example, if more than half of the crow images have true value for the concept 'wing color:black' then this process converts all concept labels for images belonging to the crow class to have the same true value. Since the original concept labels are too noisy, this procedure helps to increase the overall performance. However, it can be harmful in some cases as we will cover later in Section 6. Also after removing too sparse concepts, we end up with 112 out of 312 concepts remaining (see Appendix D for the details).

113 **Model** Following the standard setup as in [1], we use Inception-v3 [21] pretrained on Imagenet
114 [22] for the concept predictor g and 1-layer MLP for the target predictor f respectively, while both
115 networks are trained with the same training hyperparameters. We choose the Independent CBM (g, f
116 are trained separately) as the intervention process is more effective than the Sequential (f is trained
117 after finishing training g) or Joint models (g, f are trained simultaneously) (see Appendix A for
118 model details). We report task error as the average over 5 training runs with different random seeds.

119 **Group vs. Individual interventions** In previous works the intervention is done group-wise in
120 which concepts within the same group (derived from the dataset collection process) are intervened
121 on altogether; for example, the values for 'wing color:black' and 'wing color:white' are updated
122 at once when intervened. However, we find that the concepts in the CUB dataset are not always
123 mutually exclusive, and multiple concepts can have the same (*e.g.*, true) values at the same time. Since
124 intervening on the related group together requires almost the same amount of effort as intervening on
125 the same number of concepts across different groups, we also evaluate individual-wise intervention
126 by which concepts are intervened one at a time.

5 Main Results

(a) Individual intervention.   (b) Group-wise intervention.   (c) Comparison of two setups.

Figure 2: (a) Comparison of different methods of individual intervention. (b) Comparison of different
methods of group-wise intervention. (c) Comparison of individual and group-wise interventions
(using concept uncertainty) for the effective number of intervened concepts.

128 Here we report evaluation results for different intervention methods developed in Section 3. For
129 the random method, we report the average task error over 5 randomly generated intervention orders.
130 As seen in Figure 2a, the current practice of random intervention is easily outperformed by the
131 alternatives. Notably, utilizing concept uncertainty information helps to improve the target prediction
132 quite significantly. Specifically, correcting 12.5% (14 out of 112) of concepts decreases the task error
133 almost by half while the random method requires 42.9% (48 out of 112) corrections to achieve the
134 same error rate. Other methods consistently outperform the random method as well, except for the
135 smallest margin which becomes less effective later. Overall, we find that the intervention procedure
136 can be much more effective than as it is with the naive current practice.

137 In group-wise intervention, we calculate the mean of the scores for each concept, *e.g.*, uncertainty or
138 concept importance, within the group to determine the order of intervention. As seen in Figure 2b,
139 concept uncertainty method is still more effective than the random method. Specifically, random
140 intervention needs 42.9% (12 out of 28), while concept uncertainty method needs 28.6% (8 out of
141 28) of the groups to be intervened to decrease the task error by half. However, unlike in individual
142 intervention, other methods do not outperform the random method. We suspect that calculating the
143 mean of the scores in group-wise intervention loses some discriminative information, and perhaps a
144 different surrogate needs to be designed.

145 In addition, we find that group-wise intervention is less effective than individual intervention with the
146 same budget of intervention expense (see Figure 2c). To see why, it is worth noting that we cannot
147 provide rich information when only allowed to intervene concepts within the same group at a time.
148 By choosing the same number of concepts across different groups, we can intervene on the concepts
149 more effectively with the same effort.

Although the uncertainty method shows promising results, we also notice a significant gap from the largest concept loss method. Specifically, the latter only needs 4.5% (5 out of 112) concepts to decrease the task error by half in individual intervention. Nonetheless, the largest concept loss method is unrealistic in practice as the model does not have access to the ground truth concept values to determine the order of intervention. We leave closing this gap as a future work.

5.1 Ablation: Counter-intuitive aspect of the intervention

(a) Random.

(b) Concept uncertainty.

(c) Largest concept loss.

Figure 3: When all concepts are predicted correctly, intervention is expected to at least keep the task error as constant (Expected). Contrary to the expectation, however, rectifying the concept values by intervention increases the task error when following the current protocol (Current). By not intervening on the concept values when the related parts are invisible, intervention can decrease the task error consistently (Ours). Shaded regions are the standard deviations over 5 different random seeds.

It is observed in Figure 2a that the task error does not always decrease with more intervention; *i.e.*, see the largest concept loss method for which the error starts to increase after about twenty concept intervention counts. This result is unexpected and counter-intuitive since intervention is supposed to improve the prediction performance. To better understand, we set up an ablation experiment where we have the images for which all their concepts are correctly predicted (*i.e.*, 100% concept prediction accuracy); in this case, intervention is expected at least not to increase the task error ('Expected' in Figure 3). For those images, however, the task error keeps on increasing as more concepts get intervened, and when all concepts are intervened at the end, the prediction error reaches to more than five times as much as with no intervention ('Current' in Figure 3). This reveals that intervention, as opposed to how it is believed, can actually degrade the subsequent target prediction performance, questioning its reliability.

We realize that this happens due to the specific intervention protocol used in [1] to make the intervention more realistic. Since intervening on the concepts correctly is nearly impossible when the related part is invisible from the image, the authors assume that domain experts would consider the concepts to be false or non-existent (value of 0) in this case; for example, if the wing is invisible, concept 'wing color:black' changes to 0 at intervention. Thus, when $c_i^{\mathrm{GT}} = \hat{c}_i = 1$, *i.e.*, the model correctly predicts the concept value as 1, but the related part is not visible, intervention can rather increase the task error as it makes the predictions to be incorrect. However, we find that simply not intervening on those concepts, *i.e.*, not changing the predicted values when the related part is invisible, can consistently decrease the task error when all concepts are correctly predicted ('Ours' in Figure 3). This technique also prevents the task error from increasing in the largest concept loss method, and can actually make intervention more effective in general. (see Appendix E).

6 Fairness problem lying in majority voting

Since the concept labels in the CUB dataset are noisy, we use majority voting to increase the task accuracy and the intervention effectiveness. When training CBMs with noisy labels without majority voting, we observe that the task error is too high and intervention does not effectively reduce the error as seen in Figure 4. Despite its advantages, we find that majority voting can have a negative impact on the model fairness. As a concrete example, we observe that a majority of the images in 'black tern' class have black underparts color, but some minorities in this class have white underparts color (Figure 5a). After majority voting, it changes the ground-truth underparts color of the minorities as

(a) Random.   (b) Concept uncertainty.   (c) Largest concept loss.

Figure 4: Comparison of test-time intervention results with and without using majority voting (See Appendix B for the training details). **Left, Mid**: When we do not use majority voting, intervention does not decrease task error at all with random or concept uncertainty method. **Right**: Even with the largest concept loss method, intervention does not reduce the task error as much as when we use majority voting, and the error rather starts to increase after about 15 concepts intervened.

(a) Majorities and minorities.

(b) Prediction of the minority.

Figure 5: An example where majority voting can be harmful to the model fairness. **Left**: In 'black tern' class, a majority of the images have black underparts color, but some minorities have white underparts color. **Right**: At test time, if another minority comes in, the label prediction is correct only when the predicted concept value is the same as majority voted value.

black, and as a result, the model is trained to predict black concept value from minorities. When another minority image comes in at the test time, we observe that the target class prediction is biased. In other words, the image is classified correctly only when the predicted concept is identical to the majority-voted value (black) and it is not the case when the predicted value is the original minority value (white). (Figure 5b).

This phenomenon can threaten the model fairness significantly in practice. Suppose that we are given a dataset where each data point (x_i, c_i, y_i) consists of the image of the human face, binary concepts including white face color, and the job of the person. If we train the model with majority voting when more than 50% of people in 'physician' class have white face color, we can only classify the images with other face colors, *e.g.*, Asian physicians, when the model predicts the concept value as 'white'. In other words, the model thinks all physicians have white face color and does not take physicians from different races into account. To prevent these kinds of undesirable scenarios, we argue that future researchers should also take care of the model fairness rather than just focusing on the performance and adopting majority voting without much consideration. As an applicable approach, we suggest not to contain the concepts that may build a biased model, *e.g.*, gender or race, in the concept layer in CBMs.

7   Conclusion

In this work, we analyze CBMs in terms of the test-time intervention, which was missing in the previous works. First, we evaluate different intervention methods which show promising results in decreasing the target error with the same costs. Furthermore, we observe that existing intervention or pre-preprocessing protocols can make CBMs unreliable and unfair, and discuss the way we can remove or mitigate the problems. We hope these findings can help future researchers to build more interpretable and responsible models.

References

[1] Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In *ICML*, 2020.

[2] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[3] Michael I Jordan and Tom M Mitchell. Machine learning: Trends, perspectives, and prospects. *Science*, 349(6245):255–260, 2015.

[4] Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *ICML*, 2018.

[5] Amirata Ghorbani, James Wexler, James Y Zou, and Been Kim. Towards automatic concept-based explanations. In *NeurIPS*, 2019.

[6] David Alvarez Melis and Tommi Jaakkola. Towards robust interpretability with self-explaining neural networks. *NeurIPS*, 2018.

[7] Mohammad Taha Bahadori and David E Heckerman. Debiasing concept-based explanations with causal analysis. *arXiv preprint arXiv:2007.11500*, 2020.

[8] Yoshihide Sawada and Keigo Nakamura. Concept bottleneck model with additional unsupervised concepts. *arXiv preprint arXiv:2202.01459*, 2022.

[9] Mateo Espinosa Zarlenga, Pietro Barbiero, Gabriele Ciravegna, Giuseppe Marra, Francesco Giannini, Michelangelo Diligenti, Zohreh Shams, Frederic Precioso, Stefano Melacci, Adrian Weller, et al. Concept embedding models. *arXiv preprint arXiv:2209.09056*, 2022.

[10] Andrei Margeloiu, Matthew Ashman, Umang Bhatt, Yanzhi Chen, Mateja Jamnik, and Adrian Weller. Do concept bottleneck models learn as intended? *arXiv preprint arXiv:2105.04289*, 2021.

[11] Anita Mahinpei, Justin Clark, Isaac Lage, Finale Doshi-Velez, and Weiwei Pan. Promises and pitfalls of black-box concept learning models. *arXiv preprint arXiv:2106.13314*, 2021.

[12] Burr Settles. Active learning literature survey. *Computer Science Technical Report*, 2009.

[13] David D Lewis and Jason Catlett. Heterogeneous uncertainty sampling for supervised learning. In *Machine learning proceedings*. Elsevier, 1994.

[14] David D Lewis. A sequential algorithm for training text classifiers: Corrigendum and additional data. In *Acm Sigir Forum*, 1995.

[15] Ido Dagan and Sean P Engelson. Committee-based sampling for training probabilistic classifiers. In *Machine Learning Proceedings*, 1995.

[16] Aron Culotta and Andrew McCallum. Reducing labeling effort for structured prediction tasks. In *AAAI*, 2005.

[17] Tobias Scheffer, Christian Decomain, and Stefan Wrobel. Active hidden markov models for information extraction. In *International Symposium on Intelligent Data Analysis*, 2001.

[18] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pages 618–626, 2017.

[19] Solomon Kullback and Richard A Leibler. On information and sufficiency. *The annals of mathematical statistics*, 1951.

[20] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. 2011.

[21] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *CVPR*, 2016.

[22] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

A Different ways to train CBMs

Let $g : \mathbb{R}^d \to \mathbb{R}^k$ and $f : \mathbb{R}^k \to \mathcal{Y}$ be the concept predictor and the target predictor respectively. The original work [1] introduced 3 different ways to train the two networks, which we describe in this section. Here, we use the notation of N for the number of data points, σ for the sigmoid function, and l_c, l_y for the loss functions.

The first one is the independent model, where two networks g and f are trained separately from each other. Specifically, two networks are trained to minimize the following objectives respectively.

$$L_g = \frac{1}{N} \sum_{i=1}^{N} l_c(\sigma(g(x^{(i)})), c^{(i)}), \ L_f = \frac{1}{N} \sum_{i=1}^{N} l_y(f(c^{(i)}), y^{(i)}).$$

The second one is the sequential model, where we first train g and then train f after finishing training g. Specifically, they are trained to minimize the following objectives respectively.

$$L_g = \frac{1}{N} \sum_{i=1}^{N} l_c(\sigma(g(x^{(i)})), c^{(i)}), \ L_f = \frac{1}{N} \sum_{i=1}^{N} l_y(f(g(x^{(i)}), y^{(i)})$$

Note that f now takes predicted concept value $\hat{c} = g(x)$ as input rather than the ground-truth c.

The final one is the joint model, where we train g and f simultaneously to minimize the following single objective.

$$L_{gf} = \frac{1}{N} \sum_{i=1}^{N} \{\lambda l_c(\sigma(g(x^{(i)})), c^{(i)}) + l_y(f(g(x^{(i)}), y^{(i)}))\}$$

Here, hyperparmater λ determines the trade-off between l_c and l_y.

B Training details of when not using MV

For training the concept predictor g and the target predictor f when not using majority voting, we used the same architecture, Inceptionv3 pretrained on the Imagenet for g. For f, we used the 2-layer MLP whose hidden layer is of dimension 200 so that it can describe more complex functions. We searched the best hyperparameters for both g and f over the same sets of values as when using majority voting in [1]. Specifically, we tried initial learning rates of $[0.01, 0.001]$, constant learning rate and decaying the learning rate by 0.1 every $[10, 15, 20]$ epochs, and the weight decay of $[0.0004, 0.00004]$. After finding the optimal values of hyperparameters whose validation accuracy is the best, we trained the networks with the same values again over 5 different random seeds.

C Evaluation of other intervention methods based on the target class uncertainty

We define the maximum entropy and least confidence method as follows.

Maximum entropy To measure the expected uncertainty in the target class with respect to the i-th concept intervention, this method utilizes the maximum entropy [15]. Specifically, it first intervenes on the concept c_i with the largest value of $H(\hat{y}_{tti}^i)$ where $H(X) = \mathbb{E}[-\log p(X)]$ is the function measuring the entropy in the probability distribution.

Least confidence This method utilizes the least confidence [16] to measure the expected uncertainty in the target class with respect to the i-th concept intervention. Specifically, it first intervenes on the concept c_i with the smallest value of $(y_1^*)^i$, the largest class probability in $\hat{y}_{tti}^i$.

As seen in Figure 6, smallest margin method is slightly more effective than the others in the individual intervention, though the difference is not huge.

(a) Individual intervention.	(b) Group-wise intervention.

Figure 6: Results of intervention methods measuring the expected uncertainty in the target class with respect to the i-th concept intervention. All the methods work similarly, but smallest margin is the most effective one in the individual intervention.

D   Details about CBMs

Concept Bottleneck Models   Concept Bottleneck Models(CBMs) [1] are a class of interpretable deep neural networks which utilize high level concepts to predict the target label. Borrowing the notations from [1, 10], let the i-th data point be $(x^{(i)}, c^{(i)}, y^{(i)})$ where $x, c,$ and y each correspond to the input image, binary concepts, and the target label. Here, $x \in \mathbb{R}^d, c \in \{0,1\}^k, y \in \mathcal{Y}$ where d is the dimension of the input images, k is the number of concepts, and $\mathcal{Y}$ is the target space. Though predicting c and y can either be a classification or regression task, we only focused on the case when c and y are classification tasks in this paper following the dataset we used for the experiments. The model consists of the two networks $g : \mathbb{R}^d \to \mathbb{R}^k$, the concept predictor which predicts concepts from the input image, and $f : \mathbb{R}^k \to \mathcal{Y}$, the target predictor which predicts the target label from the concepts. At test time, we predict the target label using the two networks as $\hat{y} = f(g(x))$.

Test-time Intervention   Unlike other interpretable models, CBMs support test-time intervention so that domain experts can change the concept values at test time, which may help the model make correct target label predictions. The effectiveness of the intervention can be measured by how fast the task error decreases, in other words, the decrease in the task error with the same number of intervened concepts, where task error indicates the proportion of the misclassified images.

Pre-processing   To build CBMs with the CUB dataset, we follow the pre-processing of [1] and perform majority voting since the original concept labels are too noisy (see Section 4 for the details). After this process, we remove too sparse concepts whose value is present in less than 10 classes. The authors of [1] explain that including these sparse concepts in the concept layer makes it hard to predict their values as the positive training examples are too scarce. Since high concept error can further lead to an increase in the task error, they do not use these concepts when training the model.

E   Results of ablation study

Not only our simple technique introduced in Section 5.1 increases the reliability of the intervention, it can also make intervention more effective. As seen in Figure 7, task error decreases more with the same number of intervened concepts consistently in the 3 intervention methods. Note that in largest concept loss method, task error now keeps on decreasing and does not increase after 20 intervened concepts.

(a) Random. (b) Concept uncertainty. (c) Largest concept loss.

Figure 7: By not intervening on the concepts whose related parts are not visible, intervention is more effective consistently in all the methods.