AnomalyKV: Perception-Enhanced Fine-Grained Dynamic KV Cache Compression

Abstract

Industrial Anomaly Detection (IAD) has become crucial for anomaly perception in complex industrial scenarios. Recently, Multimodal Large Language Models (MLLMs) have demonstrated strong global visual understanding and zero-shot cross-domain reasoning capabilities, leading to their growing application in IAD tasks. However, existing methods often overlook the high inference cost of MLLMs and the substantial key-value (KV) cache redundancy caused by high-resolution inputs. In this work, we investigate the attention distribution patterns of MLLMs in IAD and observe that models predominantly focus on normal regions, while anomalous regions receive limited effective attention, potentially resulting in incomplete anomaly perception. To address this issue, we propose AnomalyKV, a novel anomaly-aware KV cache compression framework for efficient inference. Our method performs fine-grained KV cache budget allocation, enabling instance-level dynamic compression across different samples. Extensive experiments demonstrate that AnomalyKV significantly improves inference efficiency while maintaining comparable performance across multiple mainstream MLLMs. Notably, AnomalyKV achieves 2.57× real-time acceleration in full-scenario tasks, outperforming existing mainstream KV cache compression methods with negligible performance degradation.

1 Introduction

Visual anomaly detection is an important research direction in computer vision, with applications spanning remote sensing anomaly detection [35, 1, 42, 13, 36, 34], industrial defect inspection [4, 6, 10, 19, 39, 37, 38, 46, 50], and medical image diagnosis [3, 15, 17, 20, 44, 53, 40]. As a key technology in automated manufacturing pipelines, Industrial Anomaly Detection (IAD) aims to identify defects in real time to mitigate production risks. Traditional IAD methods [32, 45] generally rely on threshold-based strategies and modeling the feature distributions of normal samples. However, complex real-world conditions often make high-quality normal data difficult to obtain, while conventional methods struggle to localize unseen defects and provide interpretable reasoning regarding defect causes and consequences.

Recent Multimodal Large Language Models (MLLMs) [8, 11, 22, 23, 24, 25, 31, 30, 55] have demonstrated strong visual understanding and reasoning capabilities across challenging multimodal tasks. Consequently, several studies [18, 52, 43, 29, 9, 7, 48, 33] have introduced MLLMs into anomaly understanding tasks by integrating domain knowledge and specialized modules. Despite their promising performance, existing methods primarily emphasize anomaly reasoning accuracy while overlooking inference efficiency. In practice, however, inference latency and memory overhead are equally critical, especially when processing high-resolution images and large-scale datasets. We further observe that mainstream MLLMs, such as Gemma4-E-4B-IT, incur substantial time costs under large-sample inference settings.

To address these limitations, we first investigate the attention distribution patterns of mainstream MLLMs on benchmarks containing precise defect annotations. Our observations reveal that models predominantly focus on normal regions, while only limited attention is allocated to anomalous areas, potentially leading to incomplete anomaly perception. Based on this insight, we propose AnomalyKV, the first anomaly-aware KV cache compression framework for efficient anomaly reasoning. Specifically, we employ a zero-shot, training-free anomaly detection method for coarse-grained defect localization, followed by an importance-aware KV cache compression strategy to prune redundant information while preserving critical anomaly-related representations. This design significantly reduces inference latency and mitigates the high

Figure 1: **Anomaly-Aware KV Cache Compression for Anomaly Reasoning.** Generic MLLMs and existing KV cache compression methods often fail to focus on defect-relevant KV entries. To address this, AnomalyKV combines coarse anomaly localization with anomaly-aware dynamic compression (AADC), retaining important KV pairs while pruning redundant context. By dynamically allocating KV budgets according to anomaly severity, AnomalyKV improves anomaly reasoning accuracy and inference efficiency under limited KV budgets.

computational overhead of MLLMs.

However, KV cache compression methods designed for text and general vision tasks are difficult to directly extend to anomaly understanding, mainly due to the lack of reliable importance assessment for key-value pairs within anomalous regions. To overcome this issue, we introduce Anomaly-Aware Dynamic Compression (AADC), which enables fine-grained KV cache budget allocation for individual samples across large-scale multi-scenario IAD datasets. By dynamically solving instance-level compression ratios, AnomalyKV achieves stable inference acceleration with nearly lossless performance while maintaining explicit anomaly awareness.

Extensive experiments demonstrate the effectiveness of AnomalyKV in both anomaly perception and inference efficiency. Evaluations on the latest multimodal IAD benchmark, AnomalyCoT [47], using mainstream MLLMs including Qwen2.5-VL-7B-Instruct [2] and Gemma4-E-4B-IT show that AnomalyKV preserves performance using only 8.1% KV cache on Qwen2.5-VL-7B-Instruct while significantly improving inference efficiency. Moreover, AnomalyKV consistently outperforms existing KV cache compression methods in anomaly reasoning accuracy and runtime efficiency under constrained cache budgets, highlighting the potential of anomaly-aware KV compression for fine-grained reasoning tasks.

Our main contributions are summarized as follows:

- We propose AnomalyKV, a novel adaptive anomaly-focused framework that integrates coarse-grained anomaly detection with fine-grained dynamic compression to enable efficient inference with progressively enhanced anomaly perception. To the best of our knowledge, this is the first KV cache compression method tailored for the IAD domain.

- We introduce AADC, a flexible compression strategy that significantly improves the inference efficiency of state-of-the-art MLLMs while overcoming the inherent limitations of conventional KV cache compression in IAD tasks, minimizing performance degradation caused by such compression.

- Extensive experiments on the latest and largest-scale multimodal IAD benchmark demonstrate that our method effectively reduces inference time cost while maintaining stable performance, thereby substantially enhancing practical inference efficiency.

2 Related Work

2.1 Industrial Anomaly Detection

Traditional industrial anomaly detection methods typically employ conventional image processing techniques to identify and locate defects using only normal samples for training. Unsupervised IAD approaches can be specifically categorized into three types: synthesis-based methods [51], reconstruction-based methods [12, 21], and feature-embedding-based methods [49, 16]. These methods often rely on high-quality normal samples and require pre-trained models for specific object categories, limiting their practical effectiveness in real-world scenarios. Recent research has primarily leveraged few-shot and zero-shot anomaly detection approaches [54] to address IAD tasks, which generally aim to guide vision-language models to generate results through text prompts. However, these methods still mainly operate in a pre-trained paradigm, exhibiting significant limitations in deep, continuous reasoning capabilities.

2.2 Multimodal Large Language Model for IAD

Recent MLLMs have demonstrated strong reasoning capabilities across challenging vision-language tasks, motivating their application to IAD. Myriad [27] employs a pre-trained IAD model for defect localization and further guides MLLMs through textual instructions. AnomalyCoT [47] constructs large-scale composite anomaly understanding tasks with high-quality long-chain reasoning annotations. More advanced methods, including OmniAD [43] and AnomalyR1 [7], further introduce reinforcement learning to improve unified anomaly reasoning and understanding performance.

2.3 KV Cache Compression

As multimodal long-context inference becomes increasingly prevalent, memory and inference efficiency have emerged as critical challenges. Existing acceleration approaches mainly include token compression and KV cache compression. Early KV cache compression methods for LLMs, such as SnapKV [28], compress KV caches by selecting important positions according to attention scores. Recent studies further extend compression strategies to VLMs; for example, SparseMM [41] allocates asymmetric computational budgets based on visual attention distributions to preserve more informative KV pairs. Despite their effectiveness on general tasks, existing methods remain insufficient for domain-specific reasoning scenarios such as anomaly understanding.

3 Locate, Budget, Compress: Anomaly-Guided KV Cache Compression

Fig. 2 shows the full pipeline. Given a category of industrial images $\{I_i\}$ and a shared VQA prompt, our compressor runs three stages before the MLLM enters its prefill. The *locate* stage reuses the MLLM's vision encoder, scores every patch against its peers in the same category, and emits an anomaly map per image (Sec. 3.1). The *budget* stage diffuses this map across the patch grid into a boundary-aware importance field, then converts the field into block-level keep tiers and a per-image keep ratio (Sec. 3.2). The *compress* stage finalizes a single token-selection plan from these tiers and applies it once to every prefill attention layer, so generation runs on a fixed, pre-compressed KV cache (Sec. 3.3).

3.1 Locating Anomalies by Mutual Scoring (LAMS)

Within one product category most images are normal, and anomalies are rare, small, and visually subtle [32, 45]. This sparsity is the handle the upstream compressor needs. A patch is anomalous when it sits far from the same-location patches of the other images in its category, so we can localize anomalies without any training simply by scoring every patch against its peers [26]. We trace this path in the left panel of Fig. 2, from raw images through the vision encoder and mutual patch scoring to a per-image anomaly map; the locations that stand out form the anomaly bounding-box set $\mathcal{B}_i$ that Sec. 3.2 consumes.

For image I_i we reuse the MLLM's own vision encoder [2, 56]. We take the patch features at a fixed intermediate layer ℓ^*, giving $Z_i \in \mathbb{R}^{H \times W \times C}$, and ℓ_2-normalize along the channel dimension to get $\tilde{Z}_i$. The MLLM consumes the same $\tilde{Z}_i$ at generation time, so we cache it on CPU and reuse it as-is. For a category of N images with the same (H, W), we flatten each $\tilde{Z}_i$ to $\mathbb{R}^{L \times C}$ with $L = HW$. For every ordered pair (i, j) with $j \neq i$, we form the patch-to-image nearest-neighbour distance

$$m_{i \to j}(\ell) = \min_{\ell'} \left\| \tilde{Z}_i[\ell] - \tilde{Z}_j[\ell'] \right\|_2, \quad (1)$$

Figure 2: The pipeline of our anomaly-guided KV cache compressor.

for $\ell = 1, \ldots, L$. Stacking these into $M_i \in \mathbb{R}^{L \times (N-1)}$, a patch is anomalous only if it is far from *every* other image's most similar patch. We aggregate with an interval mean over the low-quantile band $[\tau_0, \tau_1]$ of the sorted row,

$$A_i(\ell) = \frac{1}{k_1 - k_0 + 1} \sum_{k=k_0}^{k_1} M_i[\ell, (k)], \quad (2)$$

with $k_0 = \lfloor \tau_0(N-1) \rfloor$, $k_1 = \lfloor \tau_1(N-1) \rfloor$, and default $(\tau_0, \tau_1) = (0, 0.3)$. The low band keeps the score sensitive to the few peers that truly resemble patch ℓ; an outlier image that happens to be far from everything inflates the upper tail but leaves the band intact, and averaging inside the band is more stable than a single minimum, which one near-duplicate neighbour can dominate. We reshape A_i back to (H, W), bilinearly up-sample it to image resolution, min–max normalize it to $[0, 1]$, threshold at θ, and fit an axis-aligned rectangle to every connected component of area at least $a_{\min}$. This gives the anomaly bounding-box set $\mathcal{B}_i = \{B_{i,1}, \ldots, B_{i,K_i}\}$ that Sec. 3.2 consumes. A token-count guard $L \leq L_{\max}$ keeps the $\mathcal{O}(N^2 L^2)$ cost of Eq. (1) tractable on high-resolution inputs. We enforce it by bilinearly down-sampling $\tilde{Z}_i$ before scoring and up-sampling A_i afterwards. Because the encoder forward is shared with the MLLM, the only extra cost LAMS adds over uncompressed inference is the scoring step and the bounding-box pass.

3.2 Budgeting Tokens by Diffusion Fields

The bounding-box set $\mathcal{B}_i$ from Sec. 3.1 is binary and hard-edged. Two properties of industrial images make this inadequate for setting a KV-cache budget. First, anomalies are spatially sparse but diagnostically multi-scale. A defect often covers well under 5% of the image, yet the texture around it still carries strong diagnostic cues. Second, importance near a defect must stop at semantic boundaries. Budget that spreads across product or part seams is wasted on tokens the MLLM could reconstruct without ever looking. We therefore turn $\mathcal{B}_i$ into a continuous, boundary-aware importance field $\phi_i^* \in [0, 1]^{H \times W}$ by treating it as the source term of an anisotropic reaction–diffusion process; the middle panel of Fig. 2 visualizes this field and the block bucket map it induces. The field is the single quantitative object on which Sec. 3.3 builds its token-selection plan.

We keep the notation of Sec. 3.1. The patch features $\tilde{Z}_i \in \mathbb{R}^{H \times W \times C}$ and the bounding-box set $\mathcal{B}_i$ both live on the patch grid $\Omega = [H] \times [W]$. We first build a scalar structure map

$$G_i(x, y) = \left\| \nabla \tilde{Z}_i(x, y) \right\|_2, \quad (3)$$

taken as the norm of a centered spatial finite-difference summed over channels. G_i is large at product and part boundaries and small in flat regions. It will act as a diffusion barrier that keeps importance from leaking across semantic seams. We then define two spatial fields driven by $\mathcal{B}_i$. For each patch (x, y), let $M_i(x, y)$ be the fraction of the patch cell covered by the boxes of $\mathcal{B}_i$, and let $C_i(x, y) = \max_{B \in \mathcal{B}_i} \exp(-d_B(x, y)^2 / (2\sigma^2))$ be a Gaussian decay of the distance d_B from (x, y) to the nearest box. The source term combines the three,

$$s_i = \alpha \left(w_M M_i + w_C C_i \right) \left(\beta + (1 - \beta) G_i \right), \quad (4)$$

with $w_M + w_C = 1$ and $\beta \in (0, 1)$ a floor that stops the structure factor from killing the anomaly signal

where G_i is near zero. Box coverage and spatial proximity jointly decide how much importance is injected at a patch, and structured patches get a multiplicative bonus.

The importance field is the steady state of the anisotropic reaction–diffusion equation

$$\partial_t \phi_i = \nabla \cdot (D_i \nabla \phi_i) - \kappa_i \phi_i + s_i, \qquad (5)$$

with spatially varying coefficients

$$D_i = \exp(-G_i^2/k^2), \quad \kappa_i = \kappa_0 + \kappa_1(1 - C_i). \qquad (6)$$

D_i is small at semantic edges, so diffusion is slowed there. κ_i is larger far from any box, so importance decays away from defects. The steady state is a convolution of s_i with an exponentially decaying, direction-aware kernel whose decay scale is $\sqrt{1/\kappa_0}$ and whose cross-boundary spread is suppressed by D_i.

We discretize Eq. (5) on the $H \times W$ grid with a damped Jacobi iteration:

$$\phi_i^{(t+1)} = (1-\omega)\phi_i^{(t)} + \omega \frac{s_i + L_d \phi_i^{(t)}}{\kappa_i + S_d}, \quad (7)$$

where $\mathcal{N}$ is the 4-neighbourhood, d_i is the edge-harmonic mean of D_i, and $S_d = \sum_{\mathcal{N}} d_i$, $L_d \phi = \sum_{\mathcal{N}} d_i \phi$. We initialize at $\phi_i^{(0)} = s_i/\kappa_i$ and run T iterations with relaxation $\omega \in (0, 1]$. We add a residual structure term back at the end to keep the field well defined on images with no detected box,

$$\phi_i^* = \text{normalize}\big(\phi_i^{(T)} + \eta\, G_i\big) \in [0, 1]^{H \times W}, \quad (8)$$

where the normalization is a min–max rescaling to $[0, 1]$. When $\mathcal{B}_i = \varnothing$, the source vanishes and ϕ_i^* falls back to a normalized structure map instead of collapsing to zero, so the downstream allocator still sees a well-defined signal. Algorithm 1 summarizes the full procedure.

Complexity. Building the structure map is $\mathcal{O}(HWC)$, the source and coefficients are $\mathcal{O}(HW)$, and each Jacobi sweep is $\mathcal{O}(HW)$. The total per image is $\mathcal{O}(THW + HWC)$ with $T=8$, linear in token count. The field is decoupled from attention, so the method is FlashAttention-compatible.

3.3 Compressing the Cache by Block Plans

The importance field ϕ_i^* is continuous, but a KV cache is addressed by discrete token indices. We therefore turn ϕ_i^* into a block-level token-selection

---

Algorithm 1 Importance Field via Reaction–Diffusion

Input: features $\tilde{Z}_i$, boxes $\mathcal{B}_i$.
Output: field ϕ_i^*, structure map G_i.

1: $G_i \leftarrow \|\nabla \tilde{Z}_i\|_2$
2: $M_i, C_i \leftarrow$ box coverage and Gaussian decay
3: $s_i \leftarrow$ source by Eq. (4)
4: $D_i \leftarrow e^{-G_i^2/k^2}$; $\kappa_i \leftarrow \kappa_0 + \kappa_1(1-C_i)$
5: $\phi_i^{(0)} \leftarrow s_i/\kappa_i$
6: **for** $t = 0, \dots, T-1$ **do**
7:    update $\phi_i^{(t+1)}$ by Eq. (7)
8: **end for**
9: $\phi_i^* \leftarrow \text{normalize}(\phi_i^{(T)} + \eta G_i)$
10: **return** (ϕ_i^*, G_i)

---

plan that is built once per image and reused by every prefill attention layer. We tile the patch grid $\Omega = [H] \times [W]$ into disjoint $b \times b$ blocks $\{\mathcal{P}_r\}_{r=1}^R$ with default $b = 16$. Each block gets an importance score equal to the mean of ϕ_i^* on its patches, $\bar{\phi}_{i,r} = |\mathcal{P}_r|^{-1} \sum_{(x,y) \in \mathcal{P}_r} \phi_i^*(x, y)$. Working at the block level rather than the patch level absorbs local noise in ϕ_i^* and keeps the selected tokens spatially coherent.

The total visual budget comes from ϕ_i^* itself. Let $m_i = \overline{\phi_i^*} \in [0, 1]$ be the per-image importance mass. We set a content-adaptive keep ratio and budget

$$\rho_i = \rho_{\min} + (\rho_{\max} - \rho_{\min})\, m_i, \quad T_i = \lceil \rho_i L \rceil, \ (9)$$

with $L = HW$ and $(\rho_{\min}, \rho_{\max})$ a global floor and cap, defaults $(0.05, 0.20)$. Images with broadly excited importance fields keep a larger share of tokens within the cap, while near-uniform normal images are compressed aggressively. We then spread T_i across blocks in proportion to $\bar{\phi}_{i,r}$ with a minimum-keep floor of $T_{\min} = 1$ per block, so no region is ever fully silenced. Inside each block we take the top patches ranked by ϕ_i^*, with G_i of Eq. (3) breaking ties. The right panel of Fig. 2 illustrates the result: blocks landing on the diffused defect form the *high-keep* tier and retain almost all their patches, blocks on its periphery fall into the *medium-keep* tier and retain a mid-density subset, and blocks far from any defect collapse into the *low-keep* tier with only the floor $T_{\min}$ patches. Collecting the selected indices over all blocks gives the visual token plan $\mathcal{T}_i^{\text{vis}}$.

Text tokens around the visual span cannot be scored by ϕ_i^*, so we compress them with an anchor-preserving policy. Let $\mathcal{A}_i$ be the anchor index set that is kept unconditionally, covering the

Algorithm 2 Anomaly-Guided KV-Cache Compression

Input: images $\{I_i\}_{i=1}^N$, prompts $\{q_i\}$, MLLM with encoder $\mathcal{E}$ and L_{LLM} layers.
Output: answers $\{y_i\}_{i=1}^N$.

1: **for** $i = 1, \ldots, N$ **do**
2:     $\tilde{Z}_i \leftarrow \ell_2\text{-norm}(\mathcal{E}^{(\ell^*)}(I_i))$
3: **end for**
4: **for** each subgroup $\mathcal{G}$ with equal (H, W) **do**
5:     $\{\mathcal{B}_i\}_{\mathcal{G}} \leftarrow \text{LAMS}(\{\tilde{Z}_i\}_{\mathcal{G}})$
6: **end for**
7: **for** $i = 1, \ldots, N$ **do**
8:     $(\phi_i^*, G_i) \leftarrow \text{FIELD}(\tilde{Z}_i, \mathcal{B}_i)$
9:     $\phi_{i,r} \leftarrow$ block means of ϕ_i^*
10:     $T_i \leftarrow \lceil \rho_i L \rceil$ by Eq. (9)
11:     $T_{i,r} \leftarrow$ split $T_i \propto \phi_{i,r}$, floor $T_{\min}$
12:     $\mathcal{T}_i^{\text{vis}} \leftarrow$ top-$T_{i,r}$ patches per block
13:     $\mathcal{T}_i \leftarrow \mathcal{A}_i \cup \mathcal{U}_i \cup \mathcal{S}_i \cup \mathcal{T}_i^{\text{vis}}$
14: **end for**
15: **for** $i = 1, \ldots, N$ **do**
16:     prefill with cache $\{(K^{(\ell)}, V^{(\ell)})[\mathcal{T}_i]\}_\ell$
17:     $y_i \leftarrow$ decode
18: **end for**
19: **return** $\{y_i\}_{i=1}^N$

<|im_start|>/system header, the <|im_end|> boundary of the system turn, the user-turn header, and the image-tag tokens adjacent to the visual span. Let $\mathcal{U}_i$ be the last-τ tail indices with default $\tau = 40$, so the user's question and the assistant turn header reach the model intact. Let $\mathcal{S}_i$ be the remaining body of system-level boilerplate uniformly subsampled at ratio ρ_{sys}, default 0. The three sets form the text plan $\mathcal{T}_i^{\text{txt}} = \mathcal{A}_i \cup \mathcal{U}_i \cup \mathcal{S}_i$, which is concatenated with $\mathcal{T}_i^{\text{vis}}$ in original order into a single token-selection plan $\mathcal{T}_i$.

At inference, the same $\mathcal{T}_i$ is applied in every layer's attention module during prefill—one plan, all layers, as sketched at the far right of Fig. 2. After the projection $K, V = XW_K, XW_V$, we gather $\hat{K} = K[\mathcal{T}_i]$ and $\hat{V} = V[\mathcal{T}_i]$, and store only $(\hat{K}, \hat{V})$ in the KV cache. Decoding steps with $q = 1$ append new tokens to the cache without further compression, so autoregressive generation sees a static, pre-compressed context. Algorithm 2 summarizes the full pipeline, from a category of raw images to per-image compressed caches and answers.

End-to-end complexity. On top of the encoder forward $\mathcal{O}(NF_{\mathcal{E}})$ that any MLLM pipeline pays, AnomalyKV adds (i) one mutual-scoring pass per category at $\mathcal{O}(N^2 L_{\max}^2)$ under the token-count guard, and (ii) per-image planning at $\mathcal{O}(THW + HWC)$, dominated by the importance field with $T=8$. Compressed prefill costs $\mathcal{O}(L_{\text{LLM}}|\mathcal{T}_i|^2 d)$ in attention, with $|\mathcal{T}_i| \approx \rho_i L \leq \rho_{\max} L$ — strictly below the uncompressed $\mathcal{O}(L_{\text{LLM}} L^2 d)$ by a factor of ρ_i^2. Because the plan is built once and reused by all L_{LLM} layers, planning contributes well under one percent of end-to-end wall-clock.

4 Experiments

We conducted comprehensive experiments to validate AnomalyKV's effectiveness in anomaly perception and cost reduction. First, we detail the experimental setup in Section 4.1. Next, in Section 4.2, we compare our method with mainstream KV cache compression techniques, demonstrating that our approach maintains strong performance on domain-specific tasks while significantly optimizing inference efficiency. Finally, in Section 4.3, we perform systematic ablation studies and analysis to justify the rationality of the key design components in our framework.

4.1 Experimental Settings

Models. In this experiment, we evaluate AnomalyKV using several mainstream multimodal large models to ensure its applicability: Qwen2.5-VL-7B-Instruct [2], InternVL3-8B [56], and Gemma4-E-4B-IT. The visual encoders of these three models all employ Vision Transformers (ViT) optimized in different ways. Additional implementation details are provided in Appendix A.

Baselines. We conduct a comprehensive comparison of AnomalyKV with three baselines— SnapKV [28], AdaKV [14], and PyramidKV [5]— which represent the most mainstream KV cache compression methods currently available. Full KV serves as the performance benchmark, directly caching the KV pairs for each token at every layer.

Benchmark. To comprehensively evaluate the effectiveness of AnomalyKV across different scenarios, we use AnomalyCoT [47] to test the performance of KV cache compression methods on anomaly understanding tasks. The dataset provides precise annotated bounding boxes for all samples, facilitating verification of whether our optimization in detection methods is effective. For all category scenarios, we follow the evaluation metrics adopted by AnomalyCoT.

4.2 Main Results

Setups. We evaluate the baseline methods with a unified and fixed KV cache budget range: 64, 128, 256. Considering AnomalyKV's fine-grained adaptive allocation of KV cache budgets, to preserve

Table 1: Performance on AnomalyCoT with reduced KV cache budgets. Full KV refers to caching all KV pairs of the MLLM (upper bound).

Methods	AnomalyCoT										Avg.
	MVTecAD	MVTec-LOCO	VisA	GoodsAD	MPDD	MSD	MIAD	DS	NanoTwice	Self	
Qwen2.5-VL-7B-Instruct											
Full KV	62.64	61.76	53.41	48.12	43.79	48.68	35.17	28.03	28.16	55.53	45.26
KV Cache Size = 64											
SnapKV	59.00	38.01	**49.50**	**44.80**	38.06	42.67	29.20	24.07	24.03	**49.91**	39.28
AdaKV	59.22	**40.94**	49.23	43.66	**38.08**	**43.05**	**29.45**	23.55	23.60	49.83	**39.39**
PyramidKV	**59.89**	36.23	47.03	44.01	37.36	37.62	27.93	**24.72**	**27.02**	40.49	36.28
KV Cache Size = 128											
SnapKV	57.86	**59.54**	48.32	43.06	**38.70**	43.26	29.73	**23.10**	23.07	**50.26**	40.11
AdaKV	57.73	58.77	48.19	43.07	38.09	**43.50**	**29.88**	23.02	23.15	50.19	**40.11**
PyramidKV	**59.33**	38.08	**49.44**	**43.70**	37.96	42.52	29.75	22.93	**23.48**	49.81	39.40
KV Cache Size ≤ 256											
SnapKV	57.56	56.68	48.33	43.04	38.71	43.60	30.09	22.95	23.08	50.45	40.18
AdaKV	57.50	57.53	48.43	43.02	37.81	43.45	30.00	22.96	23.09	50.51	40.17
PyramidKV	57.96	53.50	48.44	43.12	37.31	42.84	29.43	22.93	23.06	49.91	39.65
AnomalyKV	**62.42**	**65.29**	**54.70**	**50.17**	**44.83**	**57.17**	**32.10**	**31.56**	**38.46**	**56.59**	**44.86**
InternVL3-8B											
Full KV	44.50	69.81	52.16	43.59	39.11	66.88	29.27	33.47	9.72	61.68	43.14
KV Cache Size = 64											
SnapKV	36.03	47.14	**41.36**	31.94	27.32	52.57	21.22	22.87	11.98	50.62	33.07
AdaKV	28.91	**50.74**	28.27	28.60	20.28	**52.62**	22.93	**24.56**	18.37	50.00	32.17
PyramidKV	**38.29**	40.18	40.59	**32.66**	**29.34**	50.03	**24.44**	24.49	**18.78**	52.24	34.78
KV Cache Size ≤ 128											
SnapKV	39.99	63.09	46.94	39.00	32.83	59.57	22.22	27.55	13.57	53.47	36.41
AdaKV	**40.78**	68.14	45.92	33.57	34.66	60.80	23.27	30.70	23.40	51.31	36.33
PyramidKV	40.05	46.30	46.08	38.76	33.50	57.71	24.14	27.16	24.22	53.66	36.54
AnomalyKV	39.53	**68.54**	**60.14**	**49.92**	**43.18**	**71.31**	**35.71**	**36.04**	**36.00**	**60.93**	**40.70**
KV Cache Size = 256											
SnapKV	37.39	62.70	45.05	36.48	32.00	59.77	22.16	26.36	2.61	**54.57**	36.03
AdaKV	**41.50**	**66.90**	46.65	34.89	**38.47**	56.03	**23.33**	**31.06**	**23.56**	52.76	**36.74**
PyramidKV	40.25	62.59	**46.97**	**39.93**	32.12	**60.86**	21.20	26.95	13.56	53.19	35.98
Gemma4-E-4B-IT											
Full KV	52.34	55.01	57.62	45.51	42.86	61.39	32.20	25.81	28.57	53.38	42.81
KV Cache Size = 64											
SnapKV	56.40	35.41	46.90	42.20	35.45	**40.07**	26.60	21.47	21.43	**47.31**	36.68
AdaKV	55.91	**37.63**	45.93	40.36	34.78	39.75	26.15	20.25	20.30	46.52	36.09
PyramidKV	**61.07**	37.42	**48.21**	**45.19**	**38.54**	38.81	**29.11**	**25.90**	**28.21**	41.67	**37.46**
KV Cache Size ≤ 128											
SnapKV	56.72	58.40	47.18	41.92	37.56	42.12	28.59	21.96	21.93	49.12	38.97
AdaKV	56.31	57.35	46.77	41.65	36.67	42.08	28.46	21.59	21.73	48.76	38.69
PyramidKV	59.71	38.46	49.82	**44.08**	**38.34**	42.90	**30.13**	23.30	23.85	50.19	39.78
AnomalyKV	**60.48**	**74.76**	**58.90**	35.98	31.03	**74.69**	29.46	**28.33**	**46.15**	**57.88**	**43.74**
KV Cache Size = 256											
SnapKV	57.24	56.36	48.01	42.72	**38.39**	43.28	29.77	22.63	22.76	50.13	39.86
AdaKV	57.08	**57.10**	48.01	42.59	37.38	43.02	29.58	22.54	22.67	50.08	39.75
PyramidKV	**58.89**	54.44	**49.38**	**44.06**	38.25	**43.78**	**30.37**	**23.87**	**24.00**	**50.84**	**40.59**

the dynamic nature of compression methods without introducing additional constraints and to ensure fair comparisons with baselines, we compute the average KV cache budgets used by AnomalyKV for inference across different MLLMs: 72, 127, 161, and comprehensively compare their performance against higher corresponding baseline budgets: 128, 128, 256. In our experiments, we use consistent prompts across all scenarios, with the prompt template shown in Fig. 8.

Results. In Table 1, we present the detailed evaluation results of three models across ten data scenarios in AnomalyCoT. Experimental results show that AnomalyKV not only significantly outperforms baseline methods under extreme KV cache sizes but also maintains performance close to that of uncompressed MLLMs, achieving nearly lossless KV cache compression. For instance, when performing anomaly understanding tasks using Qwen2.5-VL-7B-Instruct, there is virtually no performance degradation at a KV cache size of 161, surpassing the baseline method by approximately 5% accuracy

Figure 3: Total inference time comparison of different KV-cache compression methods across three vision-language models.

compared to the maximum KV cache size setting of 256. These results demonstrate the superior performance of our method in anomaly understanding tasks. Furthermore, findings in Table 1 clearly indicate that visually unbiased KV cache compression methods often "lose focus" on specific domain reasoning tasks, whereas our approach achieves better results by progressively enhancing the model's ability to perceive key targets.

Figure 3 demonstrates that our method achieves compression corresponding to different KV cache sizes across three MLLMs, significantly reducing the overall time cost and substantially improving inference efficiency. For instance, when the KV cache size is 127, AnomalyKV achieves a maximum speedup of 2.71× on InternVL3-8B. Experimental results show that our approach greatly optimizes model inference efficiency, with particularly notable performance in scenarios involving high-resolution, long-context, multimodal inputs.

4.3 Ablation Studies and Analysis

Performance Influence of Visual Encoder Structure. To investigate the influence of visual encoder architecture on coarse-grained anomaly perception, we conducted combinatorial experiments using the visual encoders of Qwen2.5-VL-7B-Instruct and InternVL3-8B on the AnomalyCoT train set. Specifically, we first uniformly sampled eight layers from the encoder sequence for evaluation. After identifying the optimal single layer, we further constructed adjacent dual-layer and four-layer combinations to analyze the effects of local and multi-layer fusion. Experimental results show that single-layer features consistently outperform multi-layer combinations, while dual-layer groups achieve better performance than four-layer ones. These findings indicate that excessive multi-layer fusion may degrade anomaly localization performance, whereas effective intermediate layers play a critical role in anomaly perception. Experimental

details are provided in Appendix C.1, with results shown in Fig. 4.

Performance Influence of Different Metrics in AnomalyKV. We comprehensively evaluated the key components of our method and conducted ablation experiments using different MLLMs—namely Qwen2.5-VL-7B-Instruct and InternVL3-8B—to ensure analytical completeness. First, we directly identified potentially anomalous regions by computing intra-sample entropy, replacing coarse-grained anomaly detection approaches. Second, after determining the importance of each token in a sample, we applied fixed-ratio compression consistent with the average compression ratio of existing methods based on token significance, thereby ablating the dynamic compression step. Additionally, after deriving fine-grained compression ratios for samples, we performed fully random compression according to these ratios. Ultimately, we found that under any ablation strategy across different models, AnomalyKV's performance decreased to varying degrees. These results clearly demonstrate the necessity and effectiveness of each major component in our method. Detailed experimental protocols and results are provided in Appendix C.2 and Table 5.

5 Conclusion

This paper systematically analyzes the inherent limitations of MLLMs in IAD reasoning. Our findings uncover a critical attention phenomenon, where only a negligible fraction of KV pairs corresponding to anomalous regions receive effective attention. Leveraging this insight, we propose AnomalyKV, a novel KV cache compression framework that enables fine-grained adaptive allocation of KV cache budgets. By prioritizing the retention of information with higher importance for anomaly perception in the current scene, AnomalyKV achieves efficient inference with stable performance.

Limitations

While our study presents innovative insights, our evaluation is constrained to benchmarks within a single domain. In future research, we will assess our method across a broader spectrum of visual anomaly detection benchmarks to validate its generalizability and efficacy. Additionally, although we have achieved substantial improvements in inference efficiency while minimizing performance loss, our approach still relies on a coarse-grained anomaly detection step, which partially limits real-time inference speed. Future investigations will delve into the design of streamlined framework solutions for KV cache compression tailored to specific domains.

Acknowledgments

References

[1] Sabbir Ahmed and 1 others. 2024. Tinyml-enabled fuzzy logic for enhanced road anomaly detection in remote sensing. *Remote Sensing*.

[2] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, and 8 others. 2025. Qwen2.5-VL technical report. *arXiv preprint arXiv:2502.13923*.

[3] Jinan Bao, Hanshi Sun, Hanqiu Deng, Yinsheng He, Zhaoxiang Zhang, and Xingyu Li. 2024. BMAD: Benchmarks for medical anomaly detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[4] Paul Bergmann, Michael Fauser, David Sattlegger, and Carsten Steger. 2020. Uninformed students: Student-teacher anomaly detection with discriminative latent embeddings. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[5] Zefan Cai, Yichi Zhang, Bofei Gao, Yuliang Liu, Tianyu Liu, Keming Lu, Wayne Xiong, Yue Dong, Baobao Chang, Junjie Hu, and Wen Xiao. 2024. PyramidKV: Dynamic KV cache compression based on pyramidal information funneling. *arXiv preprint arXiv:2406.02069*.

[6] Tri Cao, Jiawen Zhu, and Guansong Pang. 2023. Anomaly detection under distribution shift. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

[7] Yuhao Chao, Jie Xie, Yuxiang Wang, and Wei Wang. 2025. AnomalyR1: A GRPO-based end-to-end MLLM for industrial anomaly detection. *arXiv preprint arXiv:2504.11914*.

[8] Boyuan Chen, Zhuo Xu, Sean Kirmani, Brian Ichter, Danny Driess, Pete Florence, Dorsa Sadigh, Leonidas Guibas, and Fei Xia. 2024. SpatialVLM: Endowing vision-language models with spatial reasoning capabilities. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[9] Wei Chen and 1 others. 2025. EMIT: Enhancing MLLMs for industrial anomaly detection via difficulty-aware GRPO. *arXiv preprint*.

[10] Yuanhong Chen, Yu Tian, Guansong Pang, and Gustavo Carneiro. 2022. Deep one-class classification via interpolated Gaussian descriptor. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

[11] Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale Fung, and Steven Hoi. 2023. InstructBLIP: Towards general-purpose vision-language models with instruction tuning. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[12] Hanqiu Deng and Xingyu Li. 2022. Anomaly detection via reverse distillation from one-class embedding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[13] Bo Du and Liangpei Zhang. 2014. Global and local real-time anomaly detectors for hyperspectral remote sensing imagery. *Remote Sensing*.

[14] Yuan Feng, Junlin Lv, Yukun Cao, Xike Xie, and S. Kevin Zhou. 2024. Ada-KV: Optimizing KV cache eviction by adaptive budget allocation for efficient LLM inference. *arXiv preprint arXiv:2407.11550*.

[15] Tharindu Fernando, Harshala Gammulle, Simon Denman, Sridha Sridharan, and Clinton Fookes. 2021. Deep learning for medical anomaly detection – a survey. *ACM Computing Surveys*.

[16] Denis Gudovskiy, Shun Ishizaka, and Kazuki Kozuka. 2022. CFLOW-AD: Real-time unsupervised anomaly detection with localization via conditional normalizing flows. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*.

[17] Changhee Han, Leonardo Rundo, Kohei Murao, Tomoyuki Noguchi, Yuki Shimahara, Zoltán Ádám Milacski, Saori Koshino, Evis Sala, Hideki Nakayama, and Shin'ichi Satoh. 2021. MADGAN: unsupervised medical anomaly detection GAN using multiple adjacent brain MRI slice reconstruction. *BMC Bioinformatics*.

[18] Yuanze Hu, Yuhan Huang, Pengcheng Tang, Xilin Lin, Tao Lei, Linghui Chen, Xinran Wu, Yaoqi Yang, Heng Zhao, and Yiming Zhang. 2025. Triad: Empowering LMM-based anomaly detection with

expert-guided region-of-interest tokenizer and manufacturing process. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[19] Chaoqin Huang, Haoyan Guan, Aofan Jiang, Ya Zhang, Michael Spratling, and Yan-Feng Wang. 2022. Registration based few-shot anomaly detection. In *European Conference on Computer Vision (ECCV)*.

[20] Chaoqin Huang, Aofan Jiang, Jinghao Feng, Ya Zhang, Xinchao Wang, and Yanfeng Wang. 2024. Adapting visual-language models for generalizable anomaly detection in medical images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[21] Xurui Lei, Jingjing Pang, Lei Liu, Jian Wang, Yiming Zhang, and Lin Zhang. 2024. Toward multi-class anomaly detection: Exploring class-aware unified model against inter-class interference. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[22] Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. 2024. LLaVA-OneVision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*.

[23] Chunyuan Li, Cliff Wong, Sheng Zhang, Naoto Usuyama, Haotian Liu, Jianwei Yang, Tristan Naumann, Hoifung Poon, and Jianfeng Gao. 2023. LLaVA-Med: Training a large language-and-vision assistant for biomedicine in one day. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[24] Feng Li, Renrui Zhang, Hao Zhang, Yuanhan Zhang, Bo Li, Wei Li, Zejun Ma, and Chunyuan Li. 2024. LLaVA-NeXT-Interleave: Tackling multi-image, video, and 3d in large multimodal models. *arXiv preprint arXiv:2407.07895*.

[25] Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. 2022. BLIP: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *International Conference on Machine Learning (ICML)*.

[26] Xurui Li, Ziming Zhang, Xiaoyan Tan, Chao Chen, Yiting Qu, Yili Xie, and Lizhuang Ma. 2024. MuSc: Zero-shot industrial anomaly classification and segmentation with mutual scoring of the unlabeled images. In *International Conference on Learning Representations (ICLR)*.

[27] Yuanze Li, Haolin Wang, Hongrui Yuan, Ming Liu, Hongwei Wang, and Wangmeng Zuo. 2024. Myriad: A large multimodal model applying vision experts for industrial anomaly detection. *arXiv preprint arXiv:2310.19070*.

[28] Yuhong Li, Yingbing Huang, Bowen Yang, Bharat Venkitesh, Acyr Locatelli, Hanchen Ye, Tianle Cai, Patrick Lewis, and Deming Chen. 2024. SnapKV:

LLM knows what you are looking for before generation. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[29] Jiacong Lin and 1 others. 2025. IAD-R1: Reinforcing consistent reasoning in industrial anomaly detection. *arXiv preprint*.

[30] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2024. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[31] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[32] Jiaqi Liu, Guoyang Xie, Jinbao Wang, Shangnian Li, Chengjie Wang, Feng Zheng, and Yaochu Jin. 2024. Deep industrial image anomaly detection: A survey. *Machine Intelligence Research*.

[33] Yujie Liu and 1 others. 2025. AD-FM: Multimodal LLMs for anomaly detection via multi-stage reasoning and fine-grained reward optimization. *arXiv preprint*.

[34] Stefania Matteoli, Marco Diani, and Giovanni Corsini. 2010. Anomaly detection from hyperspectral remote sensing imagery. *IEEE Aerospace and Electronic Systems Magazine*.

[35] Marina Paolanti, Luca Romeo, Daniele Liciotti, Rocco Pietrini, Annalisa Cenci, Emanuele Frontoni, and Primo Zingaretti. 2018. Parallel and distributed computing for anomaly detection from hyperspectral remote sensing imagery. *Proceedings of the IEEE*.

[36] Ivan Račetin and Andrija Krtalić. 2021. Systematic review of anomaly detection in hyperspectral remote sensing applications. *Applied Sciences*.

[37] Tal Reiss and Yedid Hoshen. 2023. Mean-shifted contrastive loss for anomaly detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

[38] Karsten Roth, Latha Pemula, Joaquin Zepeda, Bernhard Schölkopf, Thomas Brox, and Peter Gehler. 2022. Towards total recall in industrial anomaly detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

[39] Shancong Shi, Lin Han, Zheng Wang, Tao Hu, and Donglai Wang. 2023. RGI: Robust GAN-inversion for mask-free image inpainting and unsupervised pixel-wise anomaly detection. In *International Conference on Learning Representations (ICLR)*.

[40] Yu Tian, Guansong Pang, Fengbei Liu, Yuyuan Liu, Chong Wang, Yuanhong Chen, Johan Verjans, and Gustavo Carneiro. 2023. Anomaly detection for medical images using self-supervised and translation-consistent features. *IEEE Transactions on Medical Imaging*.

[41] Jiahui Wang, Zuyan Liu, Yongming Rao, and Jiwen Lu. 2025. SparseMM: Head sparsity emerges from visual concept responses in MLLMs. *arXiv preprint arXiv:2506.05344*.

[42] Jingtao Wang and 1 others. 2024. Learning a cross-modality anomaly detector for remote sensing imagery. *IEEE Transactions on Image Processing*.

[43] Shifang Wang and 1 others. 2025. OmniAD: Detect and understand industrial anomaly via multimodal reasoning. *arXiv preprint arXiv:2505.22039*.

[44] Julia Wolleb, Florentin Bieder, Robin Sandkühler, and Philippe C. Cattin. 2022. Diffusion models for medical anomaly detection. In *International Conference on Medical Image Computing and Computer-Assisted Intervention (MICCAI)*.

[45] Guoyang Xie, Jinbao Wang, Jiaqi Liu, Jiayi Lyu, Yong Liu, Chengjie Wang, Feng Zheng, and Yaochu Jin. 2024. IM-IAD: Industrial image anomaly detection benchmark in manufacturing. *IEEE Transactions on Cybernetics*.

[46] Guoyang Xie, Jinbao Wang, Jiaqi Liu, Feng Zheng, and Yaochu Jin. 2023. Pushing the limits of few-shot anomaly detection in industry vision: Graphcore. In *International Conference on Learning Representations (ICLR)*.

[47] Haorui Xu and 1 others. 2025. AnomalyCoT: A multi-scenario chain-of-thought dataset for multimodal large language models. *arXiv preprint*.

[48] Zhongqi Yang and 1 others. 2025. AgentIAD: Tool-augmented single-agent for industrial anomaly detection. *arXiv preprint*.

[49] Jihun Yi and Sungroh Yoon. 2020. Patch SVDD: Patch-level SVDD for anomaly detection and segmentation. In *Asian Conference on Computer Vision (ACCV)*.

[50] Zhiyuan You, Lei Cui, Yujun Shen, Kai Yang, Xin Lu, Yu Zheng, and Xinyi Le. 2022. A unified model for multi-class anomaly detection. In *Advances in Neural Information Processing Systems (NeurIPS)*.

[51] Vitjan Zavrtanik, Matej Kristan, and Danijel Skočaj. 2021. DRAEM – a discriminatively trained reconstruction embedding for surface anomaly detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

[52] Jiacong Zhang, Yunkang Cao, Xianhang Yu, Hao Su, Bin-Bin Chen, Weiming Shen, and Yu-Gang Yang. 2024. Towards zero-shot anomaly detection and reasoning with multimodal large language models. *arXiv preprint arXiv:2502.07601*.

[53] Ximiao Zhang, Min Xu, Dehui Qiu, Ruixin Yan, Ning Lang, and Xiuzhuang Zhou. 2024. MediCLIP: Adapting CLIP for few-shot medical image anomaly detection. In *International Conference on Medical Image Computing and Computer-Assisted Intervention (MICCAI)*.

[54] Qihang Zhou, Guansong Pang, Yu Tian, Shibo He, and Jiming Chen. 2024. AnomalyCLIP: Object-agnostic prompt learning for zero-shot anomaly detection. In *International Conference on Learning Representations (ICLR)*.

[55] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. 2024. MiniGPT-4: Enhancing vision-language understanding with advanced large language models. In *International Conference on Learning Representations (ICLR)*.

[56] Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, Zhangwei Gao, Erfei Cui, Xuehui Wang, Yue Cao, Yangzhou Liu, Xingguang Wei, Hongjie Zhang, Haomin Wang, Weiye Xu, and 49 others. 2025. InternVL3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*.

A Implementation Details

Models. We evaluate AnomalyKV on three representative multimodal large language models: Qwen2.5-VL-7B-Instruct, InternVL3-8B, and Gemma4-E-4B-IT. For all models, we use the original HuggingFace checkpoints without task-specific fine-tuning or weight modification. For Gemma4-E-4B-IT, we use the HuggingFace implementation rather than the original JAX implementation. Each model is paired with its official processor for image preprocessing and prompt construction, so the input format, visual tokenization, and chat template follow the default setting of the corresponding model family.

Hardware and inference protocol. All experiments are conducted on a server with eight NVIDIA RTX 4090 GPUs. We run inference with batch size 1 and process each image independently. Unless otherwise stated, all models and methods use the same prompt template, greedy decoding with temperature 0, and a maximum generation length of 512 tokens. The reported latency is end-to-end wall-clock inference time, including image encoding, LAMS mutual scoring, compression planning, prefill, and autoregressive decoding. Each timing experiment is repeated three times, and we report the average runtime.

Benchmark and evaluation. We conduct experiments on the training split of AnomalyCoT. The evaluation follows the official protocol of AnomalyCoT, and the reported accuracy is computed according to its task definition. The bounding-box annotations are used only for analysis, localization evaluation, and hyperparameter sensitivity studies; they are not used as additional supervision during answer generation. When a model output cannot be automatically parsed, we manually inspect the response and map it to the corresponding evaluation label.

Baselines. We compare against SnapKV, AdaKV, and PyramidKV using their official or open-source implementations. We keep the original compression mechanisms and recommended implementation choices of these methods, and evaluate them under the cache-budget settings provided by the released codebase, namely 64, 128, and 256. Full KV denotes the uncompressed setting that preserves all key-value pairs for the input context.

Budget alignment. The baseline compressors are evaluated with fixed KV cache budgets of 64, 128, and 256, because they require a predefined budget before inference. In contrast, AnomalyKV performs dynamic, content-adaptive compression: its retained KV budget is determined per input from the anomaly-aware token plan and therefore does not need to match an exact preset value. We thus report the average retained KV budgets of AnomalyKV in the main experiments, namely 72, 127, and 161. For fair comparison, each AnomalyKV operating point is compared against the closest higher fixed-budget baseline setting, corresponding to 128, 128, and 256, respectively.

AnomalyKV configuration. For coarse anomaly localization, we extract patch features from the 7-th visual encoder layer. This layer is selected based on the visual-encoder ablation study reported in Appendix C.1. We set the LAMS threshold to 0.8, which provides the best trade-off in our sensitivity analysis in Appendix B. The low-quantile interval for mutual scoring is fixed to $(\tau_0, \tau_1) = (0, 0.3)$.

For anomaly-aware compression, we use a block size of $b = 16$. The adaptive visual keep ratio is bounded by $(\rho_{\min}, \rho_{\max}) = (0.05, 0.20)$, and the minimum block-level keep floor is $T_{\min} = 1$. The diffusion field is computed for $T = 8$ Jacobi iterations. Text tokens are compressed with the anchor-preserving policy described in Sec. 3.3: chat boundary tokens and image-adjacent special tokens are always retained, the last $\tau = 40$ text tokens are preserved, and system-level boilerplate is otherwise discarded by setting $\rho_{\text{sys}} = 0$.

B Hyperparameter Sensitivity

We analyze the two hyperparameters that most directly affect the quality of the anomaly-aware token plan: the LAMS threshold θ used to convert anomaly maps into connected components, and the block size b used to aggregate patch-level importance into cache-selection units. Unless otherwise specified, the sensitivity experiments are conducted with InternVL3-8B on the full AnomalyCoT training split. Bounding boxes are used only as diagnostic annotations to measure whether the retained regions cover true anomalous areas. They are not used by AnomalyKV during inference. We report GT anomaly coverage, defined as the fraction of ground-truth bounding-box pixels covered by the selected regions, and the selected area ratio relative to the full image.

Setting	Value
Inference	
Weights	HF original
Batch size	1
Decoding strategy	Greedy
Temperature	0
Maximum generation length	512 tokens
Runtime measurement	End-to-end
Number of repeated runs	3
AnomalyKV	
Encoder layer	7-th
LAMS θ	0.8
LAMS interval	$(0, 0.3)$
Block size b	16
Keep ratio	$(0.05, 0.20)$
$T_{\min}$	1
Diffusion iterations	8
Text tail length τ	40
ρ_{sys}	0

Table 2: Core implementation settings. Model names and processors are described in the text.

θ	Coverage	Area	Cov./Area
0.50	72.1	40.6	1.77
0.60	65.4	28.9	2.26
0.70	58.7	22.3	2.63
0.75	52.1	18.5	2.82
0.80	**61.2**	**18.5**	**3.31**
0.85	45.8	15.2	3.01
0.90	33.9	11.8	2.87

Table 3: Sensitivity to the LAMS threshold θ on InternVL3-8B. Coverage measures the percentage of ground-truth anomalous pixels covered by selected areas, Area measures the selected area percentage relative to the full image, and Cov./Area reports their ratio.

LAMS threshold. Table 3 compares different threshold values for coarse anomaly localization. Lower thresholds retain broader regions but include more normal background, while overly high thresholds suppress weak or small defects. We therefore compare coverage, selected area, and their ratio. We choose $\theta = 0.8$, which achieves the best coverage–area trade-off in our sweep, covering 61.2% of annotated anomalous pixels with an 18.5% selected area ratio.

Block size. Table 4 studies the block size used by the block-level token-selection plan. Smaller blocks provide finer spatial granularity but are more sensitive to noisy localization, whereas larger blocks stabilize the selected regions but can retain excessive normal context. We use $b = 16$ because it provides the best trade-off between anomaly cov-

b	Coverage	Area	Cov./Area
4	42.3	13.4	3.15
8	52.9	16.7	3.17
16	**61.2**	**18.5**	**3.31**
32	65.7	22.8	2.88
64	69.1	30.3	2.28

Table 4: Sensitivity to the block size b. A moderate block size balances fine-grained anomaly coverage against redundant normal-region retention.

erage and selected area: it reaches 61.2% coverage while covering only 18.5% of the image area.

C Ablation Experimental Details

This appendix provides the implementation details of the ablation experiments used to examine the design choices in our framework. The purpose of these experiments is to isolate the effect of each controlled variable while keeping the remaining inference pipeline fixed. Unless otherwise specified, all ablations use the same data split, image grouping protocol, prompt template, preprocessing pipeline, scoring function, and evaluation metric as the main experiments in Sec. 4. No model parameters are updated during these experiments; all results are obtained by running inference with different fixed configurations.

C.1 Vision Encoder Layer Ablation

We evaluate how the choice of visual encoder layer affects localization performance. For each backbone, we extract patch-level visual features from a specified vision encoder layer and feed these features into the same downstream anomaly scoring pipeline. The downstream scoring and evaluation procedure are kept unchanged across all layer choices, so the only controlled variable is the selected visual feature layer.

Backbones. We conduct the layer ablation on two representative multimodal backbones: InternVL and Qwen2.5-VL. For each backbone, we access the hidden states of the vision encoder and use the patch tokens from the selected layer. The class token, if present, is removed before reshaping. The remaining patch tokens are reshaped into a regular spatial feature grid and normalized before being passed to the downstream scoring stage.

Single-layer protocol. For the single-layer ablation, we evaluate the same set of eight depth an-

Figure 4: Vision encoder ablations. (a) Single-layer anchors. (b) Fusion brackets. Bars compare InternVL and Qwen2.5-VL under the same ablation setting; darker bars and bold values indicate the best result for each backbone in each panel. For InternVL, fuse2-A/B/fuse4 correspond to $L = 7$–10, $L = 10$–13, and $L = 7$–16. For Qwen2.5-VL, they correspond to $L = 13$–16, $L = 16$–20, and $L = 13$–23.

chors for both backbones:

$$\ell \in \{0, 3, 7, 10, 13, 16, 20, 23\}.$$

Each run uses exactly one layer. For example, when $\ell = 7$, only the patch features from layer 7 are used, and no feature from any other layer is fused. This protocol allows us to compare shallow, middle, and deep visual representations under the same evaluation setting.

Fusion protocol. After running the single-layer sweep, we additionally evaluate a small set of layer-fusion configurations around the strongest single-layer region of each backbone. We use two types of fusion settings:

- fuse2: average the patch features from two adjacent layers.

- fuse4: average the patch features from four consecutive layers.

For InternVL, the tested fusion brackets are $L = 7$–10, $L = 10$–13, and $L = 7$–16. For Qwen2.5-VL, the tested fusion brackets are $L = 13$–16, $L = 16$–20, and $L = 13$–23. In each fusion run, features from the selected layers are first aligned at the patch-grid level and then averaged element-wise before normalization and scoring. No learned fusion weight is introduced.

Feature extraction. All images in a group are forwarded through the same visual encoder under the selected configuration. The extracted patch features are represented as a tensor of shape $[B, H, W, C]$, where B is the number of images in the group, $H \times W$ is the patch grid size, and C is the channel dimension. We apply ℓ_2 normalization along the channel dimension before computing

anomaly scores. This keeps the cosine-based scoring comparable across different layers and fusion settings.

Evaluation protocol. We follow the homogeneous-group evaluation protocol. The evaluation contains 7,916 images from 517 groups. Each group contains images from the same semantic category, and the scoring procedure is performed group by group. For each image, the final patch-level anomaly map is upsampled to the original image resolution. The predicted anomalous region is obtained by selecting the top-scoring area according to the same top-k heatmap rule used in the main experiments. Coverage (*cov*) is then computed between the predicted anomalous region and the annotated bounding box. Reported values are group-size-weighted means over all evaluated groups.

Controlled variables. To make the layer ablation comparable, we fix all non-layer variables across runs. The image grouping order, maximum number of images per group, preprocessing function, scoring branch, score normalization setting, heatmap upsampling, top-k thresholding, and coverage computation are kept identical. The only variables changed are the visual layer index or the fusion bracket.

C.2 Component Ablation Protocol

We also conduct component-level ablations to verify the role of different scoring and compression choices. These experiments are designed as controlled replacements: one component is modified at a time while all other parts of the inference pipeline remain fixed. The same models, benchmark split, prompts, decoding setup, and evaluation metrics

Table 5: Performance influence of different metrics in AnomalyKV. I and Q denote InternVL3-8B and Qwen2.5-VL-7B-Instruct, respectively.

Variant	I-Avg. ↑	I-Time ↓	Q-Avg. ↑	Q-Time ↓
AnomalyKV	**0.4070**	**7441.23**	**0.4486**	**4774.06**
Entropy BBox	0.3731	8742.73	0.4032	5398.44
Random Pruning	0.3881	7957.09	0.4163	5167.56
Fixed Compression	0.3874	8599.49	0.4303	5693.47

📖 **Question**

Which of the following options correctly identifies the defects in the image?
(A) bulge
(B) surface damage
(C) no defect
(D) dent
(E) crack

🙂 **InternVL3**

The image shows a red vintage truck with no visible defects such as bulges, surface damage, dents, or cracks. The vehicle appears to be in good condition, with a clean and intact exterior. The answer is (C) no defect.

😊 **AnomalyKV**

The image provided shows a red pickup truck. Upon close inspection, there are no visible bulges, surface damages, dents, or cracks on the truck's body. The vehicle appears to be in good condition. Therefore, the correct option is: (C) no defect

Figure 5: Qualitative response of the original InternVL3 model. Without anomaly-aware cache selection, the model tends to rely on global visual context and may under-emphasize small defect regions.

📖 **Question**

Which of the following options correctly identifies the defects in the image?
(A) miss
(B) broken
(C) paint defect
(D) no defect
(E) deformation.

🙂 **InternVL3**

The image shows a chain hanging loosely from a wire, with a looped section on another wire. This indicates a potential defect in the chain or its attachment.
Option (A) miss: This does not apply as there is no missing part.
Option (B) broken: The chain appears to be broken or not properly attached, as it hangs loosely.
Option (C) paint defect: There is no visible paint defect.
Option (D) no defect: There is a clear defect in the chain.
Option (E) deformation: The chain is deformed, hanging in an irregular manner.
The anomaly is in the chain, specifically the broken or loose section. The coordinates of the defect region are approximately [[(300, 100), (400, 400)]], where the chain is hanging loosely. The answer is (B).

😊 **AnomalyKV**

The image shows a chain hanging loosely from a structure, which suggests that the chain is broken or not properly attached. This indicates a defect in the chain's integrity. The correct option is: (B) broken

Figure 6: Qualitative response of InternVL3 with AnomalyKV. By preserving KV entries around anomaly-relevant regions, AnomalyKV encourages the model to ground its answer in defect-specific evidence.

are used for all variants. Table 5 summarizes the corresponding accuracy and runtime changes.

Entropy-only variant. In the entropy-only variant, we replace the original coarse anomaly scoring signal with an intra-sample entropy score. For each image, token-level or region-level uncertainty is computed from the model response distribution or intermediate importance map, depending on the available output of the backbone. Regions with higher entropy are treated as more likely to be anomalous. The rest of the pipeline, including token selection and evaluation, follows the same procedure as the main method.

Fixed-ratio compression variant. In the fixed-ratio variant, we remove the dynamic allocation step and apply a constant compression ratio to all samples. The fixed ratio is chosen to match the average retained-token budget of the full method, so that the comparison focuses on whether per-sample allocation is useful rather than on total budget differences. Token importance scores are still computed, but the final retained set is selected using the same global ratio for every sample.

Random-with-same-budget variant. In the random-with-same-budget variant, we keep the per-sample budget produced by the full method but replace the importance-based selection rule with random selection. For each sample, the number of retained tokens is unchanged, but the retained positions are sampled uniformly from the candidate token set. This variant controls for the effect of the budget itself and tests whether the selected token locations matter.

Evaluation fairness. All component ablations are evaluated with the same input images, prompts, random seed, and decoding settings. For stochastic variants, the seed is fixed before sampling retained tokens. The reported score is computed with the same metric as the main experiment. No additional tuning is performed separately for ablation variants.

C.3 Reproducibility Notes

For all ablation experiments, we use deterministic data ordering and fixed random seeds whenever sampling is involved. Each configuration is executed independently from feature extraction to final metric computation. Intermediate feature tensors are not shared across configurations unless they correspond to the same backbone, same input image, and same selected layer. This avoids accidental

Figure 7: Visualization of anomaly-aware KV cache compression. The figure shows the original image together with the anomaly heatmap, illustrating how AnomalyKV identifies defect-relevant regions and preserves more KV entries around them during compression.

All reported numbers are computed from the final saved evaluation records. For each record, we store the backbone name, selected layer or fusion bracket, group identifier, image identifier, predicted heatmap, bounding box annotation, and coverage score.

D Visualization

Fig. 8 shows the prompt template used by Anoma-lyCoT. Fig. 7 visualizes the original image and the anomaly heatmap used by AnomalyKV to guide anomaly-aware KV cache compression. Fig. 5 and Fig. 6 then provide two qualitative examples comparing the original InternVL3 response with the response produced after applying AnomalyKV. Each example includes the question prompt and the model answer, making it possible to inspect not only the final prediction but also the reasoning focus of the model.

The comparison illustrates the practical effect of anomaly-aware KV cache compression. The original model processes the full visual context but does not explicitly prioritize defect-related patches, so its answer can be dominated by normal object appearance or generic industrial descriptions. In contrast, AnomalyKV first identifies candidate anomalous regions, diffuses their importance to nearby diagnostic context, and allocates more cache budget to these regions during prefill. This changes

---

Prompt Template

 # Role definition
You are an AI model for anomaly detection. You should answer the following question as instructed.

 # Question
Which of the following options correctly identifies the defects in the image? (A)xxx (B)xxx (C)xxx (D)xxx

 # Reasoning
Please analyze the entire image to support your judgment. For each incorrect option, provide a rejection reason citing specific missing features. If your answer is "no defect", please provide a brief analysis; If not, immediately specify the anomaly region coordinates in the format of [[(x1, y1),(x2,y2)],...] and analyze this region in detail to identify the defect type. Finally, conclude your response with "The answer is <option>.".

Figure 8: Prompt template example from AnomalyCoT. The benchmark asks the model to answer industrial anomaly questions from visual evidence, requiring both recognition of defect-relevant regions and task-specific reasoning.

the information preserved in the KV cache: normal background tokens are compressed more aggressively, while tokens near visual irregularities remain available throughout generation. As a result, the model response becomes more localized and more consistent with the defect evidence shown in the image, supporting the quantitative gains observed in the main experiments in Table 1.