SHAPE DEFENSE

ABSTRACT

Humans rely heavily on shape information to recognize objects. Conversely, convolutional neural networks (CNNs) are biased more towards texture. This fact is perhaps the main reason why CNNs are susceptible to adversarial examples. Here, we explore how shape bias can be incorporated into CNNs to improve their robustness. Two algorithms are proposed, based on the observation that edges are invariant to moderate imperceptible perturbations. In the first one, a classifier is adversarially trained on images with the edge map as an additional channel. At inference time, the edge map is recomputed and concatenated to the image. In the second algorithm, a conditional GAN is trained to translate the edge maps, from clean and/or perturbed images, into clean images. The inference is done over the generated image corresponding to the input's edge map. A large number of experiments with more than 10 data sets demonstrate the effectiveness of the proposed algorithms against FGSM and ℓ_∞ PGD-40 attacks. Further, we show that edge information can a) benefit other adversarial training methods, b) be even more effective in conjunction with background subtraction, c) be used to defend against poisoning attacks, and d) make CNNs more robust against natural image corruptions such as motion blur, impulse noise, and JPEG compression, than CNNs trained solely on RGB images. From a broader perspective, our study suggests that CNNs do not adequately account for image structures and operations that are crucial for robustness. The code is available at: `https://github.com/[masked]`.

1   INTRODUCTION

Deep neural networks (LeCun et al., 2015) remain the state of the art across many areas and are employed in a wide range of applications. They also provide the leading model of biological neural networks, especially in visual processing (Kriegeskorte, 2015). Despite the unprecedented success, however, they can be easily fooled by adding carefully-crafted imperceptible noise to normal inputs (Szegedy et al., 2014; Goodfellow et al., 2015). This poses serious threats in using them in safety- and security-critical domains. Intensive efforts are ongoing to remedy this problem.

Our primary goal here is to learn *robust models* for visual recognition inspired by two observations. First, object shape remains largely invariant to imperceptible adversarial perturbations (Fig. 1). Shape is a sign of an object and plays a vital role in recognition (Biederman, 1987). We rely heavily on edges and object boundaries, whereas CNNs emphasize more on texture (Geirhos et al., 2018). Second, unlike CNNs, we recognize objects one at a time through attention and background subtraction (e.g., Itti & Koch (2001)). These may explain why adversarial examples are perplexing.

The convolution operation in CNNs is biased towards capturing texture since the number of pixels constituting texture far exceeds the number of pixels that fall on the object boundary. This in turn provides a big opportunity for adversarial image manipulation. Some attempts have been made to emphasize more on edges, for example by utilizing normalization layers (e.g., contrast and divisive normalization (Krizhevsky et al., 2012)). Such attempts, however, have not been fully investigated for adversarial defense. Overall, how shape and texture should be reconciled in CNNs continues to be an open question. Here we propose two solutions that can be easily implemented and integrated in existing defenses. We also investigate possible adaptive attacks against them. Extensive experiments across ten datasets, over which shape and texture have different relative importance, demonstrate the effectiveness of our solutions against strong attacks. Our first method performs adversarial training on edge-augmented inputs. The second method uses a conditional GAN (Isola et al., 2017) to translate edge maps to clean images, essentially finding a perturbation-invariant transformation. There is no need for adversarial training (and hence less computation) in this method. Further, and

Figure 1: Adversarial attacks against ResNet152 over the giant panda image using FGSM (Goodfellow et al., 2015), PGD-40 (Madry et al., 2017) (α=8/255), DeepFool (Moosavi-Dezfooli et al., 2016) and Carlini-Wagner (Carlini & Wagner, 2017) attacks. The second columns in panels show the difference ($\mathcal{L}_2$) between the original image (not shown) and the adversarial one (values shifted by 128 and clamped). The edge map (using Canny edge detector) remains almost intact at small perturbations. Notice that edges are better preserved for the PGD-40. See Appx. A for a more detailed version of this figure, and also the same using the Sobel method.

perhaps less surprising, we find that incorporating edges also makes CNNs more robust to natural images corruptions and backdoor attacks. The versatility and effectiveness of these approaches, without significant parameter tuning, is very promising. Ultimately, our study shows that shape is the key to build robust models and opens a new direction for future research in adversarial robustness.

2 RELATED WORK

Here, we provide a brief overview of the closely related research with an emphasis on adversarial defenses. For detailed comments on this topic, please refer to Akhtar & Mian (2018).

Adversarial attacks. The goal of the adversary is to craft an adversarial input $\tilde{x} \in \mathbb{R}^d$ by adding an imperceptible perturbation ϵ to the (legitimate) input $x \in \mathbb{R}^d$ (here in the range [0,1]), i.e., $\tilde{x} = x + \epsilon$. Here, we consider two attacks based on the ℓ_∞-norm of ϵ, the Fast Gradient Sign Method (FGSM) (Goodfellow et al., 2015), as well as the Projected Gradient Descent (PGD) method (Madry et al., 2017). Both white-box and black-box attacks in the untargeted condition are considered. Deep models are also susceptible to image transformations other than adversarial attacks (e.g., noise, blur), as is shown in Hendrycks & Dietterich (2019) and Azulay & Weiss (2018).

Adversarial defenses. Recently, there has been a surge of methods to mitigate the threat from adversarial attacks either by making models robust to perturbations or by detecting and rejecting malicious inputs. A popular defense is **adversarial training** in which a network is trained on adversarial examples (Szegedy et al., 2014; Goodfellow et al., 2015). In particular, adversarial training with a PGD adversary remains empirically robust to this day (Athalye et al., 2018). Drawbacks of adversarial training include impacting clean performance, being computationally expensive, and overfitting to the attacks it is trained on. Some defenses, such as Feature Squeezing (Xu et al., 2017), Feature Denoising (Xie et al., 2019), PixelDefend (Song et al., 2017), JPEG Compression (Dziugaite et al., 2016) and Input Transformation (Guo et al., 2017), attempt to **purify the maliciously perturbed images** by transforming them back towards the distribution seen during training. MagNet (Meng & Chen, 2017) trains a reformer network (one or multiple auto-encoders) to move the adversarial image closer to the manifold of legitimate images. Likewise, Defense-GAN (Samangouei et al., 2018) uses GANs (Goodfellow et al., 2014) to project samples onto the manifold of the generator before classifying them. A similar approach based on Variational AutoEncoders (VAE) is proposed in Li & Ji (2019). Unlike these works which are based on texture (and hence are fragile (Athalye et al., 2018)), our GAN-based defense is built upon edge maps. Some defenses are inspired by biology (e.g., Dapello et al. (2020), Li et al. (2019), Strisciuglio et al. (2020), Reddy et al. (2020)).

Shape *vs.* texture. Geirhos et al. (2018) discovered that CNNs routinely latch on to the object texture, whereas humans pay more attention to shape. When presented with stimuli with conflicting cues (e.g., a cat shape with elephant skin texture; Appx. A), human subjects correctly labeled them based on their shape. In sharp contrast, predictions made by CNNs were mostly based on the texture (See also Hermann & Kornblith (2019)). Similar results are also reported by Baker et al. (2018). Hermann et al. (2020) studied the factors that produce texture bias in CNNs and learned that data augmentation plays a significant role to mitigate texture bias. Xiao et al. (2019), in parallel to our work, have also proposed methods to utilize shape for adversarial defense. They perform classification on the edge map rather than the image itself. This is a baseline method against which we compare our algorithms. Similar to us, they also use GANs to purify the input image.

Algorithm 1 Edge-guided adversarial training (EAT) for T epochs, perturbation budget ϵ, and loss balance ratio α, over a dataset of size M for a network f_θ (performed in minibatches in practice). $\beta \in \{edge, img, imgedge\}$ indicates network type and *redetect_train* means edge redetection during training.

---

  for $t = 1 \ldots T$ **do**
    for $i = 1 \ldots M$ **do**
      // launch adversarial attack (here FGSM and PGD attacks)
      $\tilde{x}_i = \text{clip}(x_i + \epsilon\, sign(\nabla_x \ell(f_\theta(x_i), y_i)))$
      if $\beta ==$ *imgedge* & *redetect_train* **then**
        $\tilde{x}_i = \text{detect\_edge}(\tilde{x}_i)$ *// recompute and replace the edge map*
      end if
      $\ell = \alpha\, \ell(f_\theta(x_i), y_i) + (1-\alpha)\, \ell(f_\theta(\tilde{x}_i), y_i)$ *// here $\alpha = 0.5$*
      $\theta = \theta - \nabla_\theta \ell$ *// update model weights with some optimizer, e.g., Adam*
    end for
  end for

Algorithm 2 GAN-based shape defense (GSD)

// Training
    1. Create a dataset of images $X = \{x_i, y_i\}^{i=1\cdots N}$ including clean and/or perturbed images
    2. Extract edge maps (e_i) for all images in the dataset
    3. Train a conditional GAN $p_g(x|e)$ to map edge image e to clean image x *// here pix2pix*
    4. Train a classifier $p_c(y|x)$ to map generated image x to class label y
// Inference
    1. For input image x, clean or perturbed, first compute the edge image e
    2. Then, compute $p_c(y|x')$ where x' is the generated image corresponding to e

---

3 PROPOSED METHODS

Edge-guided Adversarial Training (EAT). The intuition here is that the edge map retains the structure in the image and helps disambiguate the classification (See Fig. 1). In its simplest form (Fig. 7(A) in Appx. A; Alg. 1), adversarial training is performed over the 2D (Gray+Edge) or 4D (RGB+Edge) input (i.e., number of channels; denoted as Img+Edge). In a slightly more complicated form (Fig. 7(B)), first, for each input (clean or adversarial), the old edge map is replaced with the newly extracted one. The edge map can be computed from the average of only image channels or all available channels (i.e., image plus edge). The latter can sometimes improve the results, since the old edge map (although perturbed; Fig. 10 and Appx. B) still contains unaltered shape structures. Then, adversarial training is performed over the new input. The reason behind adversarial training with redetected edges is to expose the network to possible image structure damage. The loss for training is a weighted combination of loss over clean images and loss over adversarial images. At inference time, first, the edge map is computed and then classification is done over the edge-augmented input. As a baseline model, we also consider first detecting the input's edge map and then feeding it to the model trained on the edges for classification. We refer to this model as Img2Edge.

GAN-based Shape Defense (GSD). Here, first, a conditional GAN is trained to map the edge image, from clean or adversarial images, to its corresponding clean image (Alg. 2). Any image translation method (here pix2pix by Isola et al. (2017) using this code[1]) can be employed for this purpose. Next, a CNN is trained over the generated images. At inference time, first, the edge map is computed and then classification is done over the generated image for this edge image. The intuition is that the edge map remains nearly the same over small perturbation budgets (See Appx. A). Notice that conditional GAN can also be trained on perturbed images (similar to Samangouei et al. (2018) and Li & Ji (2019) or edge-augmented perturbed images (similar to above).

4 EXPERIMENTS AND RESULTS

4.1 DATASETS AND MODELS

Experiments are spread across 10 datasets covering a variety of stimulus types. Sample images from datasets are given in Fig. 2. Models are trained with cross-entropy loss and Adam optimizer (Kingma

---

[1]https://github.com/mrzhu-cool/pix2pix-pytorch

& Ba, 2014) with a batch size of 100, for 20 epochs over MNIST and FashionMNIST, 30 over DogVsCat, and 10 over the remaining. Canny method (Canny, 1986) is used for edge detection over all datasets, except DogBreeds for which Sobel is used. Edge detection parameters are separately adjusted for each dataset. We did not carry out an exhaustive hyperparameter search, since we are interested in additional benefits edges may bring rather than training the best possible models.

The first two datasets include MNIST (LeCun et al., 1998) and FashionMNIST (Xiao et al., 2017). A CNN with 2 convolution, 2 pooling, and 2 fc layers is trained. Each of these datasets contains 60K training images (resolution 28×28) and 6K test images over 10 classes. The third dataset, DogVsCat[2] contains 18,085 training and 8,204 test images. Images in this dataset are of varying dimensions. They are resized here to 150×150 pixels to save computation. A CNN with 4 convolution, 4 pooling, and 2 fc layers is trained from scratch.

Over the remaining datasets, we finetune a pre-trained ResNet18 (He et al., 2016), trained over ImageNet (Deng et al., 2009), and normalize images using ImageNet mean and standard deviation.

Figure 2: Sample images from the datasets. Numbers in parentheses denote the number of classes.

The fourth dataset, CIFAR-10 (Krizhevsky, 2009), contains 50K training and 10K test images with a resolution of 32×32 which are resized here to 64×64 for better edge detection. The fifth dataset is DogBreeds (see footnote). It contains 1,421 training and 356 test images at resolution 224×224 over 16 classes. The sixth dataset is GTSRB (Stallkamp et al., 2012) and includes 39,209 and 1,2631 training and test images, respectively, over 43 classes (resolution 64×64 pixels). The seventh dataset, Icons-50, includes 6,975 training and 3,025 test images over 50 classes (Hendrycks & Dietterich, 2019). The original image size is 120×120 which is resized to 64×64. The eighth dataset, Sketch, contains 14K training and 6K test images over 250 classes. Images have size 1111×1111 and are resized to 64×64 in experiments (Eitz et al., 2012). The ninth and tenth datasets are derived from ImageNet. The Imagenette2-160 dataset[3] has 3,925 training and 9,469 test images (resolution 160×160) over 10 classes (*tench*, *English springer*, *cassette player*, *chain saw*, *church*, *French horn*, *garbage truck*, *gas pump*, *golf ball*, and *parachute*). The Tiny Imagenet dataset[4] has 100K training images (resolution 64 × 64) and 10K validation images (used here as the test set) over 200 classes.

For attacks, we use the implementation from `https://github.com/Harry24k/adversarial-attacks-pytorch`, except Boundary attack for which we use `https://github.com/bethgelab/foolbox`.

4.2 RESULTS

4.2.1 EDGE-GUIDED ADVERSARIAL TRAINING

Results over MNIST and CIFAR-10 are shown in Tables 1 and 2, respectively. In these experiments, edge maps are computed only from the gray-level image (in turn computed from the image channels). Please refer to Appx. B for results over the remaining datasets.

Over MNIST and FashionMNIST, robust models trained using edges outperform models trained on gray-level images (the last column). The naturally trained models, however, perform better using gray-level images than edge maps (Orig. model column). Adversarial training with augmented inputs improves the robustness significantly over both datasets, except the FGSM attack on Fashion-MNIST. Over CIFAR-10, incorporating the edges improves the robustness by a large margin against the PGD-40 attack. At $\epsilon = 32/255$, the performance of the robust model over clean and perturbed images is raised from (0.316, 0.056) to (0.776, 0.392). On average, the robust model shows 64% improvement over the RGB model (last column in Table 2). Results when using the Sobel edge detector instead of the Canny does not show a significant difference (Table 7 in Appx. B). Over the

---

[2]www.kaggle.com/c/dogs-vs-cats-redux-kernels-edition & www.kaggle.com/c/dog-breed-identification
[3]https://github.com/fastai/imagenette
[4]https://tiny-imagenet.herokuapp.com/

Table 1: Results (Top-1 acc) over MNIST. The best accuracy in each column is highlighted in **bold**. In *italics* are the results of the substitute attack. Epsilon values are over 255. We used the ℓ_∞ variants of FGSM and PGD. Img2Edge means applying the Edge model (first row) to the edge map of the image.

		Orig. model				Rob. model (8)		Rob. model (32)		Rob. model (64)		Average Rob. models
	ϵ	0/clean	8	32	64	0/clean	8	0/clean	32	0/clean	64	
FGSM	Edge	0.964	0.925	0.586	0.059	0.973	0.954	0.970	0.892	0.964	0.776	0.921
	Img2Edge	,,	**0.960**	**0.951**	**0.918**	,,	**0.971**	,,	**0.957**	,,	0.910	**0.957**
	Img	**0.973**	0.947	0.717	0.162	**0.976**	0.955	**0.977**	0.892	0.970	0.745	0.919
	Img+Edge	0.972	0.941	0.664	0.089	**0.976**	0.958	**0.977**	0.902	**0.972**	0.782	0.928
	Redetect	"	0.950	0.803	0.356	"	0.962 *(0.968)*	"	0.919 *(0.947)*	"	0.843 *(0.881)*	0.941
	Img + Redetected Edge					0.974	0.950	0.970	0.771	0.968	0.228	0.810
	Redetect					"	0.958 *(0.966)*	"	0.929 *(0.947)*	"	**0.922** *(0.925)*	0.953
PGD-40	Edge	0.964	0.923	0.345	0.000	0.971	0.949	0.973	0.887	0.955	0.739	0.912
	Img2Edge	,,	**0.961**	**0.955**	**0.934**	,,	**0.970**	,,	**0.958**	,,	0.927	**0.960**
	Img	**0.973**	0.944	0.537	0.008	0.977	0.957	**0.978**	0.873	0.963	0.658	0.901
	Img+Edge	0.972	0.938	0.446	0.001	**0.978**	0.953	0.975	0.879	0.965	0.743	0.915
	Redetect	"	0.950	0.741	0.116	"	0.960 *(0.967)*	"	0.913 *(0.948)*	"	0.804 *(0.908)*	0.932
	Img + Redetected Edge					0.975	0.949	0.973	0.649	**0.968**	0.000	0.752
	Redetect					"	0.958 *(0.967)*	"	0.945 *(0.958)*	"	**0.939** *(0.942)*	**0.960**

Table 2: Results over the CIFAR-10 dataset.

		Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
	ϵ	0/clean	8	32	0/clean	8	0/clean	32	
FGSM	Edge	0.490	0.060	0.015	0.535	0.323	0.382	0.199	0.360
	Img2Edge	,,	0.258	0.258	,,	0.270	,,	0.217	0.351
	Img	**0.887**	0.359	0.246	**0.869**	0.668	**0.855**	0.553	0.736
	Img + Edge	0.860	0.366	0.169	0.846	0.611	0.815	0.442	0.679
	Redetect	,,	**0.399**	**0.281**	,,	0.569 *(0.631)*	,,	0.417 *(0.546)*	0.662
	Img + Redetected Edge				0.846	0.530	0.832	0.337	0.636
	Redetect				,,	**0.702** *(0.753)*	,,	**0.569** *(0.678)*	**0.737**
PGD-40	Edge	0.490	0.071	0.000	0.537	0.315	0.142	0.119	0.278
	Img2Edge	,,	0.259	**0.253**	,,	0.274	,,	0.253	0.301
	Img	**0.887**	0.018	0.000	0.807	0.450	0.316	0.056	0.407
	Img + Edge	0.860	0.019	0.000	0.788	0.429	0.176	0.119	0.378
	Redetect	,,	**0.306**	0.093	,,	0.504 *(0.646)*	,,	0.150 *(0.170)*	0.404
	Img + Redetected Edge				**0.834**	0.155	**0.776**	0.006	0.443
	Redetect				,,	**0.661** *(0.767)*	,,	**0.392** *(0.700)*	**0.666**

TinyImageNet dataset, as in CIFAR-10, classification using edge maps is poor perhaps due to the background clutter. Nevertheless, incorporating edges improves the results. We expect even better results with more accurate edge detection algorithms (e.g., supervised deep edge detectors). Over these 4 datasets, the final model (i.e., adversarial training using image + redetected edge, and edge redetection at inference time) leads to the best accuracy. The improvement over the image is more pronounced at larger perturbations, in particular against the PGD-40 attack (as expected; Fig. 1).

Over the DogVsCat dataset, as in FashionMNIST, the model trained on the edge map is much more robust than the image-only model (Table 8 in Appx. B). Over the DogBreeds dataset, utilizing edges does not improve the results significantly (compared to the image model). The reason could be that texture is more important than shape in this fine-grained recognition task (Table 9 Appx. B). Over GTSRB, Icons-50, and Sketch datasets, *image+edge* model results in higher robustness than the *image-only* model, but leads to relatively less improvement compared to the *edge-only* model. Please see Tables 11, 13, and 15. Over the Imagenette2-160 dataset (Table 17), classification using images does better than edges since the texture is very important on this dataset.

Average results over 10 datasets is presented in Fig. 3 (left panel). Combining shape and texture (full model) leads to a substantial improvement in robustness over the texture alone (5.24% imp. against FGSM and 28.76% imp. against PGD-40). Also, *image+edge* model is slightly more robust than the *image-only* model. Computing the edge map from all image channels improves the results on some datasets (e.g., GTSRB and Sketch) but hurts on some others (e.g., CIFAR-10) as shown in Appx. B. The right two panels in Fig. 3 show a comparison of natural (Orig. model column in tables; solid lines) *vs.* adversarial training. Natural training with *image+edge* and *redetection* at inference time leads to enhanced robustness with little to no harm to standard accuracy. Despite the Edge model only being trained on edges from clean images, the Img2Edge model does better than other naturally-trained models against attacks. The best performance, however, belongs to models trained adversarially. Notice that our results set a new record on adversarial robustness on some of these datasets even without exhaustive parameter search[5].

---

[5]cf. Zhang et al. (2019); the best robust accuracy on CIFAR-10 against PGD attacks is under 60%.

Figure 3: Left) Average results of the EAT defense on all datasets (last cols. in tables). Middle and Right) Comparison of natural (Orig. model column; solid lines) *vs.* adversarial training averaged over all datasets.

Robustness against Carlini-Wagner (CW) and Boundary attacks. Performance of our method against l_2 CW attack on MNIST dataset is shown in Appx. J. To make experiments tractable, we set the number of attack iterations to 10. With even 10 iterations, the original Edge and Img models are severely degraded. Img2Edge and Img+(Edge Redetect) models, however, remain robust. Adversarial training with CW attack results in robust models in all cases.

Results against the decision-based Boundary attack (Brendel et al., 2017) are shown in Appx. K over MNIST and Fashion MNIST datasets. Edge, Img, and Img+Edge models perform close to zero over adversarial images. Img+(Edge Redetect) model remains robust since the Canny edge map does not change much after the attack, as is illustrated in Fig. 29.

Robustness against substitute model attacks. Following Papernot et al. (2016), we trained substitute models to mimic the robust models (with the same architecture but with RGB channels) using the cross-entropy loss over the logits of the two networks, for 5 epochs. The adversarial examples crafted for the substitute networks were then fed to the robust networks. Results are shown in *italics* in Tables 1, 2, 4 and 5 (performed only against the edge-redetect models). We find that this attack is not able to knock off the robust models. Surprisingly, it even improves the accuracy in some cases. Please refer to Appx. E for more details.

Robustness against adaptive attacks. So far we have been using the Canny edge detector which is non-differentiable. What if the adversary builds a differentiable edge detector to approximate the Canny edge detector and then utilizes it to craft adversarial examples? To address this, we build the following pipeline using the HED deep edge detector (Xie & Tu, 2015): Img $\longrightarrow$ HED $\longrightarrow$ Classifier^{HED}. A CNN classifier (as above) is trained over the HED edges on the Imagenette2-160 dataset (See Appx. L). Attacking this classifier with FGSM and PGD-5 ($\epsilon = 8/255$) fools the network completely. The original classifier (Img2Edge here) trained on Canny edge maps, however, is still robust to the attacks (i.e., Img$^{adv-HED}$ $\longrightarrow$ Canny $\longrightarrow$ Classifier^{Canny}) as shown in Table 29. Notice that the HED edge maps are continuous in the range [0,1] whereas Canny edge maps are binary, which may explain why it is easy to fool the HED classifier (See Fig. 30). Alternatively, the adversary may decide to train a CNN with the (*input, output*) pair as (*input image, Canny edge map*) and then train a classifier on top of it to craft adversarial examples. Since output of Canny is binary, the adversary has to devise a differential function to approximate a step function before feeding it to the edge map CNN classifier. Adversarial images generated this way, however, are unlikely to be effective since input image has to change in such a way that a pixel is reset in the Canny edge map which may not be possible without significant (perceptible) modification.

Analysis of parameter α. By setting $\alpha = 0$, the network will be exposed only to adversarial examples (Alg. 1), which is computationally more efficient. However, it results in lower accuracy and robustness compared to when $\alpha = 0.5$, which means exposing the network to both clean and adversarial images is important (See Table 19; Appx. D). Nevertheless, here again incorporating edges improves the robustness significantly compared to the image-only case.

Why is this method working? The main reason is that the edge map acts as a checksum, and the network learns (through adversarial training) to rely more on the redetected edges when other channels are misleading (See Table 23). This aligns with prior observations such as shortcut learning in CNNs (Geirhos et al., 2020). Also, our approach resembles adversarial patch or backdoor/trojan attacks where the goal is to fool a classifier by forcing it to rely on irrelevant cues. Conversely, here we use this trick to make a model more robust. Also, the Img2Edge model can purify the input before classifying it. Any adaptive attack against the EAT defense has to alter the edges which most likely will result in perceptible structural damages. See also Figs. 10 & 14 in Appx. A.

4.2.2 GAN-BASED SHAPE DEFENSE

We trained the pix2pix model for 10 epochs over MNIST and FashionMNIST, and for 100 epochs over CIFAR-10 and Icons-50 datasets. Sample generated images are shown in Fig. 18 (Appx. F). A CNN (same architecture as before) was trained for 10 epochs to classify the generated images. Results are shown in Fig. 4. The model trained over the images generated by pix2pix (solid lines in the figure) is compared to the model trained over the original clean training set (denoted by the dashed lines). Both models are tested over the clean and perturbed versions of the original test sets of the four datasets. Over MNIST and FashionMNIST datasets, GSD performs on par with the original model on clean test images. It is, however, much more robust than the original model against the attacks. When we trained the pix2pix over the edge maps from the perturbed images, the new CNN models became even more robust (stars in Fig. 4; top panels). We expect even better results with training over edge maps from both intact and perturbed images[6].

Figure 4: Results of GSD method.

Over CIFAR-10 and Icons-50 datasets, generated images are poor. Consequently, GSD underperforms the original model over the original clean images. Over the adversarial inputs, however, GSD wins, especially at high perturbation budgets and against the PGD-40 attack. With better edge detection and image generation methods (e.g., using perceptual loss), even better results are expected.

Why is this method working? The main reason is that cGAN learns a function f that is invariant to adversarial perturbations. Since the edge map is not completely invariant to (especially large) perturbations, one has to train the cGAN on the augmented dataset composed of clean and perturbed images. One advantage of this approach is it computational efficiency since there is no need for adversarial training. Any adaptive attack against this defense has to fool the cGAN which is perhaps not feasible since it will be noticed from the generated images (i.e., cGAN will fail to generate decent images). Compared to other adversarial defenses that utilize GANs (e.g., Samangouei et al. (2018); Li & Ji (2019)), our approach relies less on texture. It can be integrated with these defenses.

5 FAST & FREE ADVERSARIAL TRAINING WITH SHAPE DEFENSE

Here, we examine whether incorporating shape bias can empower other defenses, in particular, a) fast adversarial training by Wong et al. (2020), dubbed *FastAT*, and free adversarial training by Shafahi et al. (2019), dubbed *FreeAT*. Wong et al. trained robust models using a much weaker and cheaper adversary to lower the cost of adversarial training. They showed that adversarial training with the FGSM adversary is as effective as PGD-based training. The key idea in Shafahi et al. 's work is to simultaneously update both the model parameters and image perturbations in one backward pass, rather than using separate gradient computations at each update step. Please see also Appx. G.

The same CNN architectures as in Wong et al. are employed here. For FastAT, we trained three models over MNIST (for 10 epochs), FashionMNIST (for 3 epochs), and CIFAR-10 (for 10 epochs & *early-stopping*) datasets. For FreeAT, we trained models only over CIFAR-10 for 10 epochs.

Results are shown in Table 3. Using shape-based FastAT and over MNIST, robust accuracy against PGD-50 grows from 95.5% (image-only model) to 98.4% (our full model) at $\epsilon = 0.1$ and from 87.7% to 98.6% at $\epsilon = 0.3$, which are even higher than what is reported by Wong et al. (97.5% at $\epsilon = 0.1$ and 88.8% at $\epsilon = 0.3$). Over FashionMNIST, the improvement is even more pronounced (from 69.6% to 85.5% at $\epsilon = 0.1$ and from 0% to 82.3% at $\epsilon = 0.3$). Over clean images, our full model outperforms other models in most of the cases. Over the CIFAR-10 dataset, the shape-based extension of the defenses results in high accuracy over both clean and perturbed images (using PGD-

---

[6]Similarly, the edge map classifier used in the Img2Edge model in the previous section (EAT defense) can be trained on edge maps from both clean and adversarial examples to improve performance.

Table 3: Performance of edge-augmented *FastAT* and *FreeAT* adversarial defenses over clean and perturbed images (See Appx. G for extended algorithms). FastAT is trained with the FGSM adversary ($\epsilon = 0.1$ or $\epsilon = 0.3$) over MNIST and FashionMNIST datasets, and $\epsilon = 8/255$ over CIFAR-10). FreeAT is trained over CIFAR-10 with $\epsilon = 8/255$ and 8 minibatch replays. CIFAR-10 results are averaged over 3 runs (Appx. G). PGD attacks use 10 random restarts. The remaining settings and parameters are as in Wong et al. (2020).

	MNIST (FastAT)						Fashion MNIST (FastAT)						CIFAR-10 (FastAT)			CIFAR-10 (FreeAT)		
ϵ	0.1		0.3		Avg.		0.1		0.3		Avg.		8/255		Avg.	8/255		Avg.
	0	PGD-50	0	PGD-50	Acc.		0	PGD-50	0	PGD-50	Acc.		0	PGD-10	Acc.	0	PGD-10	Acc.
Edge	0.986	0.940	0.113	0.113	0.538		0.844	0.753	0.786	0.110	0.623		0.582	0.386	0.484	0.679	**0.678**	**0.678**
Img	0.991	0.955	0.985	0.877	0.952		0.835	0.696	0.641	0.000	0.543		0.767	0.381	0.574	0.774	0.449	0.612
Img + Edge	**0.988**	0.968	0.980	0.922	0.965		0.851	0.780	**0.834**	0.769	0.809		**0.874**	0.386	0.630	**0.782**	0.442	0.612
Redetect	,,	0.977	,,	0.966	0.978		,,	0.823	,,	0.778	0.822		,,	0.393	0.634	,,	0.448	0.615
Img + Red. Edge	0.986	0.087	**0.986**	0.000	0.515		**0.857**	0.262	0.817	0.000	0.484		0.866	0.074	0.470	0.777	0.451	0.614
Redetect	,,	**0.984**	,,	**0.986**	**0.986**		,,	**0.855**	,,	**0.823**	**0.838**		,,	**0.416**	**0.641**	,,	0.452	0.615

10 attack), compared to the image-only model. We expect similar improvements with the classic PGD adversarial training. Overall, our analyses in this section suggest that exploiting edges is not specific to the particular way we perform adversarial training (Algorithms 1&2), and be extended to other defense methods (e.g., TRADES algorithm by Zhang et al. (2019)).

6 BACKGROUND SUBTRACTION

Background subtraction (a.k.a foreground detection) is an important mechanism by which humans process scenes and recognize objects. It interacts with other mechanisms such as edge and boundary detection. How useful is it for adversarial robustness? In other words, how robust the model will be assuming that the attacker has only access to the foreground object? To find out, we perform an experiment over MNIST and FashionMNIST, for which it is easy to derive the foreground masks. We compare the Img and Edge models (from Section 4.2.1) over the original and noisy (digits placed on white noise background) data, with and without background subtraction and edge detection, against the FGSM attack. Results are shown in Fig. 5(A). First, both models perform poorly over noisy images with the Edge model doing better. Second, post background subtraction, models are much more robust. Third, applying the Edge model to the foreground region leads to almost perfect robustness over MNIST. Even without perfect edge detection, the Edge model does very well over FashionMNIST. This analysis provides an upper bound on the potential benefit from background subtraction on model robustness, assuming that foreground objects can be reliably detected.

7 HARNESSING BACKDOOR ATTACKS

Proposed mechanisms can also withstand invisible and visible backdoor attacks (Brown et al., 2017; Liu et al., 2017). Over MNIST, we planted an invisible C-like patch in half of the 8s and relabeled them as 9. We then trained the Img model on this new dataset. The Img model on a test set where all 8s are contaminated (with the patch), classifies almost all of them as 9 (top-left panel in Fig. 5.B). The Edge model, however, correctly classifies them as 8 since edge detection removes the pattern (top-right panel). Thanks to the edge detection, it is also not possible to train the Edge model on the poisoned dataset. A similar experiment on FashionMNIST, using a different patch, shows similar results (bottom panels in Fig. 5.B). In presence of visible patches, the model would not be affected if the correct region is identified (via background subtraction) during training or testing (Appx. I).

8 ROBUSTNESS AGAINST NATURAL IMAGE DISTORTIONS

Previous work has shown that ImageNet-trained CNNs generalize poorly over a wide range of image distortions (e.g., Azulay & Weiss (2018); Dodge & Karam (2017)). Our objective in this section is to study whether increasing shape bias improves robustness against common image distortions just as it did over adversarial examples. Following Hendrycks & Dietterich (2019), we systematically test how model accuracies degrade if images are corrupted by 15 different types of distortions including *brightness*, *contrast*, *defocus blur*, *elastic transform*, *fog*, *frost*, *Gaussian noise*, *glass blur*, *impulse noise*, *JPEG compression*, *motion blur*, *pixelatation*, *shot noise*, *snow*, and *zoom blur*, at 5 levels of severity. Fig. 19 (Appx. H) shows sample images along with their distortions.

We test the original models (trained naturally on clean training images) as well as the robust models (trained adversarially using Algorithm 1) over the corrupted versions of test sets on three datasets. Results are visualized in Fig. 6. See Appx. H for breakdown results on each dataset and distortion. Two conclusions are drawn. First, incorporating edge information in origi-

Figure 5: A) Background subtraction together with edge detection improves robustness (here against the FGSM attack). Noisy data is created by overlaying a digit over white noise (noise×(1-mask)+digit). B) Defending backdoor attacks. An almost invisible pattern (with intensity 10/255 of the digit intensity) is added to half of the samples from one class, which are then relabeled as another class. Notice that the Edge model is not confused over the edge maps (right panels) since edge detection removes the pattern. In case of a visible backdoor attack, background subtraction can help discard the irrelevant region. See Appx. I for more details.

nal models (and hence increasing shape bias) improves robustness against common image distortions (solid curves in Fig. 6; RGB+Egde > RGB or Edge). Improvement is more noticeable at larger distortions and over datasets with less background clutter (e.g., Icons-50). This is in alignment with Geirhos et al. (2018) where they showed ResNet-50 trained on the Stylized-ImageNet dataset performs better than the vanilla ResNet-50 on both clean and distorted images.

Second, adversarially-trained models (in particular those trained on Img + Edge) are more robust to image distortions compared to original models. In summary, incorporating edges and adversarial images leads to improved robustness against natural image distortions, *despite models not being trained on any of the distortions during training*. This in turn suggests that the proposed algorithms indeed rely more on shape than texture.

Figure 6: Classification accuracy over naturally distorted images.

9 DISCUSSION AND OUTLOOK

Two algorithms are proposed to use shape bias and background subtraction to strengthen CNNs and defend against adversarial attacks and backdoor attacks. To fool these defenses one has to perturb the image such that the new edge map is significantly different from the old one while preserving image shape and geometry, which does not seem to be trivial at low perturbation budgets. Even though we did not perform an exhaustive parameter search (model architecture, epochs, edge detection, cGAN training, etc.), our results are better than or on par with the state of the art in some cases (e.g., over MNIST and CIFAR datasets). The proposed mechanisms are computationally efficient and excel with higher resolution images and low background clutter. They are also more effective against stronger attacks than weaker ones since strong attacks perturb the image less while being more destructive (e.g., PGD *vs.* FGSM; Fig. 1). Shape defense can also be combined with other defenses to produce robust models without a significant slowdown.

Future work should assess shape defense against adversarial attacks such as e.g., gradient-free attacks, decision-based attacks, sparse attacks (e.g., the one pixel attack (Su et al., 2019)), attacks that perturb only the edge pixels, attacks that manipulate the image structure (Xiao et al., 2018), ad-hoc adaptive attacks, , and backdoor (Chen et al., 2017)), as well as other ℓ_p norms, and datasets. There might be also other ways to incorporate shape-bias in CNNs, such as 1) augmenting a dataset with edge maps or negative images, 2) overlaying texture from some objects onto some others as in Geirhos et al. (2018), and 3) designing normalization layers (Carandini & Heeger, 2012). Lastly, the interpretation of the shape defense, as in Zhang & Zhu (2019), is another research direction.

REFERENCES

Naveed Akhtar and Ajmal Mian. Threat of adversarial attacks on deep learning in computer vision: A survey. *IEEE Access*, 6:14410–14430, 2018.

Anish Athalye, Nicholas Carlini, and David A. Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. *CoRR*, abs/1802.00420, 2018.

Aharon Azulay and Yair Weiss. Why do deep convolutional networks generalize so poorly to small image transformations? *arXiv preprint arXiv:1805.12177*, 2018.

Nicholas Baker, Hongjing Lu, Gennady Erlikhman, and Philip J Kellman. Deep convolutional networks do not classify based on global object shape. *PLoS computational biology*, 14(12): e1006613, 2018.

Irving Biederman. Recognition-by-components: a theory of human image understanding. *Psychological review*, 94(2):115, 1987.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. *arXiv preprint arXiv:1712.04248*, 2017.

Tom B Brown, Dandelion Mané, Aurko Roy, Martín Abadi, and Justin Gilmer. Adversarial patch. *arXiv preprint arXiv:1712.09665*, 2017.

John Canny. A computational approach to edge detection. *IEEE Transactions on pattern analysis and machine intelligence*, (6):679–698, 1986.

Matteo Carandini and David J Heeger. Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, 13(1):51–62, 2012.

Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy*, pp. 39–57, 2017.

Xinyun Chen, Chang Liu, Bo Li, Kimberly Lu, and Dawn Song. Targeted backdoor attacks on deep learning systems using data poisoning. *arXiv preprint arXiv:1712.05526*, 2017.

Joel Dapello, Tiago Marques, Martin Schrimpf, Franziska Geiger, David D Cox, and James J DiCarlo. Simulating a primary visual cortex at the front of cnns improves robustness to image perturbations. *BioRxiv*, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Samuel Dodge and Lina Karam. A study and comparison of human and deep learning recognition performance under visual distortions. In *2017 26th international conference on computer communication and networks (ICCCN)*, pp. 1–7. IEEE, 2017.

Gintare Karolina Dziugaite, Zoubin Ghahramani, and Daniel Roy. A study of the effect of JPG compression on adversarial images. *CoRR*, abs/1608.00853, 2016.

Mathias Eitz, James Hays, and Marc Alexa. How do humans sketch objects? *ACM Trans. Graph. (Proc. SIGGRAPH)*, 31(4):44:1–44:10, 2012.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained cnns are biased towards texture; increasing shape bias improves accuracy and robustness. *arXiv preprint arXiv:1811.12231*, 2018.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *arXiv preprint arXiv:2004.07780*, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *Proc. ICLR*, 2015.

Chuan Guo, Mayank Rana, Moustapha Cissé, and Laurens van der Maaten. Countering adversarial images using input transformations. *CoRR*, abs/1711.00117, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Katherine Hermann, Ting Chen, and Simon Kornblith. The origins and prevalence of texture bias in convolutional neural networks. *Advances in Neural Information Processing Systems*, 33, 2020.

Katherine L Hermann and Simon Kornblith. Exploring the origins and prevalence of texture bias in convolutional neural networks. *arXiv preprint arXiv:1911.09071*, 2019.

Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1125–1134, 2017.

Laurent Itti and Christof Koch. Computational modelling of visual attention. *Nature reviews neuroscience*, 2(3):194–203, 2001.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2014.

Nikolaus Kriegeskorte. Deep neural networks: a new framework for modeling biological vision and brain information processing. *Annual review of vision science*, 1:417–446, 2015.

Alex Krizhevsky. Learning multiple layers of features from tiny images, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proc. IEEE*, 1998.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

Xiang Li and Shihao Ji. Defense-vae: A fast and accurate defense against adversarial attacks. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 191–207. Springer, 2019.

Zhe Li, Wieland Brendel, Edgar Walker, Erick Cobos, Taliah Muhammad, Jacob Reimer, Matthias Bethge, Fabian Sinz, Zachary Pitkow, and Andreas Tolias. Learning from brains how to regularize machines. In *Advances in Neural Information Processing Systems*, pp. 9529–9539, 2019.

Yingqi Liu, Shiqing Ma, Yousra Aafer, Wen-Chuan Lee, Juan Zhai, Weihang Wang, and Xiangyu Zhang. Trojaning attack on neural networks. 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *CoRR*, abs/1706.06083, 2017.

Dongyu Meng and Hao Chen. Magnet: A two-pronged defense against adversarial examples. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security, CCS 2017, Dallas, TX, USA, October 30 - November 03, 2017*, pp. 135–147, 2017. doi: 10.1145/3133956.3134057.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: A simple and accurate method to fool deep neural networks. In *Proc. CVPR*, pp. 2574–2582, 2016.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against deep learning systems using adversarial examples. *CoRR*, abs/1602.02697, 2016.

Manish Vuyyuru Reddy, Andrzej Banburski, Nishka Pant, and Tomaso Poggio. Biologically inspired mechanisms for adversarial robustness. *Advances in Neural Information Processing Systems*, 33, 2020.

Pouya Samangouei, Maya Kabkab, and Rama Chellappa. Defense-gan: Protecting classifiers against adversarial attacks using generative models. *arXiv preprint arXiv:1805.06605*, 2018.

Ali Shafahi, Mahyar Najibi, Mohammad Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *Advances in Neural Information Processing Systems*, pp. 3358–3369, 2019.

Yang Song, Taesup Kim, Sebastian Nowozin, Stefano Ermon, and Nate Kushman. Pixeldefend: Leveraging generative models to understand and defend against adversarial examples. *arXiv preprint arXiv:1710.10766*, 2017.

Johannes Stallkamp, Marc Schlipsing, Jan Salmen, and Christian Igel. Man vs. computer: Benchmarking machine learning algorithms for traffic sign recognition. *Neural networks*, 32:323–332, 2012.

Nicola Strisciuglio, Manuel Lopez-Antequera, and Nicolai Petkov. Enhanced robustness of convolutional networks with a push–pull inhibition layer. *Neural Computing and Applications*, pp. 1–15, 2020.

Jiawei Su, Danilo Vasconcellos Vargas, and Kouichi Sakurai. One pixel attack for fooling deep neural networks. *IEEE Transactions on Evolutionary Computation*, 23(5):828–841, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *In Proc. ICLR*, 2014.

Eric Wong, Leslie Rice, and J Zico Kolter. Fast is better than free: Revisiting adversarial training. *arXiv preprint arXiv:2001.03994*, 2020.

Chaowei Xiao, Jun-Yan Zhu, Bo Li, Warren He, Mingyan Liu, and Dawn Song. Spatially transformed adversarial examples. *arXiv preprint arXiv:1801.02612*, 2018.

Chaowei Xiao, Mingjie Sun, Haonan Qiu, Han Liu, Mingyan Liu, and Bo Li. Shape features improve general model robustness. 2019.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

Cihang Xie, Yuxin Wu, Laurens van der Maaten, Alan L Yuille, and Kaiming He. Feature denoising for improving adversarial robustness. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 501–509, 2019.

Saining Xie and Zhuowen Tu. Holistically-nested edge detection. In *IEEE International Conference on Computer Vision*, 2015.

Weilin Xu, David Evans, and Yanjun Qi. Feature squeezing: Detecting adversarial examples in deep neural networks. *CoRR*, abs/1704.01155, 2017.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P Xing, Laurent El Ghaoui, and Michael I Jordan. Theoretically principled trade-off between robustness and accuracy. *arXiv preprint arXiv:1901.08573*, 2019.

Tianyuan Zhang and Zhanxing Zhu. Interpreting adversarially trained convolutional neural networks. *arXiv preprint arXiv:1905.09797*, 2019.

A ILLUSTRATION OF SHAPE IMPORTANCE IN ADVERSARIAL ROBUSTNESS

Figure 7: Edge-guided adversarial training (EAT). In its simplest form, adversarial training is performed over the 2D (Gray+Edge) or 4D (RGB+Edge) input (i.e., number of channels; denoted as Img+Edge). In a slightly more complicated form (B), first for each input (clean or adversarial), the old edge map is replaced with the newly extracted one. The edge map can be computed from the average of only image channels or all available channels (i.e., image plus edge).

Figure 8: Adversarial attacks against ResNet152 over the giant panda image using 4 prominent attack types: FGSM (Goodfellow et al., 2015) and PGD-40 (Madry et al., 2017) (α=8/255) for different perturbation budgets $\epsilon \in \{8, 16, 32, 64\}$, as well as DeepFool (Moosavi-Dezfooli et al., 2016) and Carlini-Wagner (Carlini & Wagner, 2017). The second column in each panel shows the difference ($\mathcal{L}_2$) between the original image (not shown) and the adversarial one (values shifted by 128 and clamped). For DF and CW, values are magnified 20x and then shifted. The edge map (using the Canny edge detector) remains almost intact at small perturbations. Notice that edges are better preserved for the PGD-40 attack. See Appx. A for results using the Sobel method.

Figure 9: As is in Fig. 1 in the main text but using the Sobel edge detector. As it can be seen edge maps are almost invariant to adversarial perturbation.

Figure 10: Illustration of adversarial perturbation over the image as well as its edge map. The first row in each panel shows the clean or adversarial image (under the FGSM attack). The second row shows the perturbed edge map (i.e., the edge channel of the the 2D or 4D adversarial input). The third row shows the redetected edge map from the attacked gray or rgb image (i.e., calculated only from the image channels and excluding the edge map itself).

Figure 11: Samples images from Sketch and Icons-50 datasets, perturbed with FGSM $\epsilon = 8/255$, and their corresponding edge maps using Canny edge detection.

Figure 12: Top) Adversarial example generated for the giant panda image using the FGSM attack (Goodfellow et al., 2015). Bottom) Adversarial examples generated for AlexNet from Szegedy et al. (2014). (Left) is a correctly predicted sample, (center) difference between correct image, and image predicted incorrectly magnified by 10x (values shifted by 128 and clamped), (right) adversarial example (i.e., left image + middle image). Even though the left and right images appear visually the same to humans, the left images are correctly classified by a DNN classifier while the right images are misclassified as "ostrich, Struthio camelus". Notice that in all of these images the overall image structure and edges are preserved.

Figure 13: A) Classification of a standard ResNet-50 of (a) a texture image (elephant skin: only texture cues); (b) a normal image of a cat (with both shape and texture cues), and (c) an image with a texture-shape cue conflict, generated by style transfer between the first two images, B) Accuracy and example stimuli for five different experiments without cue conflict, and C) Sample images from the Stylized-ImageNet (SIN) dataset created by applying AdaIN style transfer to an ImageNet image (left). Figure compiled from Geirhos et al. (2018).

Figure 14: An example visual illusion simultaneously depicting a portrait of a young lady or an old lady. While fooling humans takes a lot of effort and special skills are needed, deep models are much easier to be fooled. In this example, the artist has carefully added features to make the portrait look like an old lady while the new additions will not negatively impact the look of the young lady too much. For example, the right eyebrow of the old lady (marked in red below) does not distort the ear of the young lady too much. See `https://medium.com/@jonathan_hui/adversarial-attacks-b58318bb497b` for more details.

Display Image	Shape-Object	Texture-Object	1st Choice	2nd Choice	3rd Choice	4th Choice	5th Choice
	Otter (0%)	Odometer (0.03%)	Can Opener (12.12%)	Electric Guitar (7.66%)	Hook (3.64%)	Remote Control (3.54%)	Corkscrew (3.53%)
	Ram (31.8%)	Bison (0.06%)	Ibex (46.51%)	Ram (31.8%)	Bighorn (18.1%)	Chesapeake Bay Retriever (1.09%)	Hyena (0.48%)
	Sturgeon (0.02%)	Honeycomb (0.48%)	Starfish (15.36%)	Banded Gecko (5.6%)	Electric Ray (5.57%)	Snail (5.56%)	Kite (4.52%)
	Bee (0.04%)	Velvet (6.97%)	Stole (29.94%)	Wool (10.24%)	Velvet (6.97%)	Bonnet (4.53%)	Poncho (4.2%)
	Bison (0.01%)	Stone Wall (8.72%)	Stone Wall (8.72%)	Parachute (7.9%)	Tile Roof (5.19%)	Stole (3.6%)	Kite (3.26%)
	Dugong (0.03%)	Gorilla (0%)	Bluetick (8.53%)	German Short-Haired Pointer (7.73%)	Egyptian Cat (6.19%)	Tabby (5.79%)	Kerry Blue Terrier (5.6%)
	Flamingo (0.83%)	Python (0.05%)	Limpkin (13.48%)	Hook (12.46%)	Corkscrew (6.33%)	Bustard (3.8%)	Ostrich (3.63%)
	Gorilla (0%)	Green Mamba (1.48%)	Strawberry (19.03%)	Custard Apple (16.42%)	Granny Smith (6.81%)	Bell Pepper (5.47%)	Knot (4.5%)
	Hyena (0.15%)	Cask (0.19%)	Triceratops (19.8%)	Mortarboard (3.2%)	Pedestal (2.4%)	Pencil Sharpener (2.02%)	Kite (1.78%)
	Lobster (0.02%)	Broom (0.83%)	Wool (18.69%)	Rocking Chair (4.8%)	Knot (4.67%)	Hamper (4.41%)	Stole (3.36%)

Figure 15: Classification results based on shape vs. texture. The left-most column shows the image presented to a model. The second column in each row names the object from which the shape was sampled. The third column names the object from which the textured silhouette was obtained. Probabilities assigned to the object name in columns 2 and 3 are shown as percents below the object label. The remaining five columns show the probabilities (as percents) produced by the network for its top five classifications, ordered left to right in terms of probability. Correct shape classifications in the top five are shaded in blue and correct texture classifications are shaded in orange. Figure from Baker et al. (2018).

B   ADDITIONAL RESULTS FOR THE EDGE-AUGMENTED DEFENSE

Results of the shape defense (Algorithm 1 in the main text) over eight datasets. Tables with (*) in their caption have contributed to Fig 3 in the main text. In some tables, results are computed when the edge map is computed from all image channels, i.e., a gray-level image is first computed by averaging the 4 image channels (Img + Edge map) and then a new edge map is derived.

Table 4: Results over the Fashion MNIST dataset (*)

ε	Orig. model				Rob. model (8)		Rob. model (32)		Rob. model (64)		Average Rob. models
	0/clean	8	32	64	0/clean	8	0/clean	32	0/clean	64	
FGSM											
Edge	0.775	0.714	0.497	0.089	0.776	0.740	0.766	**0.664**	0.748	**0.750**	**0.741**
Img2Edge	,,	**0.755**	**0.679**	**0.452**	,,	**0.762**	,,	**0.664**	,,	0.420	0.690
Img	0.798	0.670	0.288	0.027	**0.798**	0.722	0.764	0.584	**0.768**	0.505	0.690
Img+Edge	**0.809**	0.662	0.229	0.010	0.794	0.732	0.769	0.623	0.750	0.537	0.701
Redetect	"	0.691	0.326	0.053	"	0.739 (0.761)	"	0.616 (0.660)	,,	0.491 (0.496)	0.693
Img + Redetected Edge					0.789	0.719	**0.775**	0.539	0.762	0.045	0.605
Redetect					"	0.739 (0.753)	"	**0.664** (0.678)	"	0.611 (0.532)	0.721
PGD-40											
Edge	0.775	0.711	0.370	0.002	0.783	0.744	0.769	0.661	0.743	0.574	0.712
Img2Edge	,,	**0.757**	**0.683**	**0.380**	,,	**0.762**	,,	0.658	,,	0.374	0.681
Img	0.798	0.659	0.133	0.000	0.792	0.713	0.760	0.515	0.734	0.324	0.640
Img+Edge	**0.809**	0.647	0.100	0.000	0.794	0.726	0.765	0.608	0.744	0.568	0.701
Redetect	"	0.682	0.235	0.014	"	0.734 (0.760)	"	0.629 (0.666)	-	0.607 (0.426)	0.712
Img + Redetected Edge					**0.800**	0.717	**0.779**	0.393	**0.771**	0.002	0.577
Redetect					"	0.743 (0.766)	"	**0.694** (0.681)	"	**0.690** (0.504)	**0.746**

Table 5: Results over the TinyImageNet dataset (*)

ε	Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
	0/clean	8	32	0/clean	8	0/clean	32	
FGSM								
Edge	0.136	0.010	0.001	0.150	0.078	0.098	0.021	0.087
Img2Edge	,,	0.097	**0.096**	,,	0.094	,,	0.077	0.105
Img	**0.531**	0.166	0.074	**0.512**	0.297	**0.488**	0.168	**0.366**
Img + Edge	0.522	0.152	0.050	0.508	0.273	0.471	0.148	0.350
Redetect	,,	**0.171**	0.081	"	0.287 (0.356)	,,	0.162 (0.266)	0.357
Img + Redetected Edge				0.505	0.264	0.482	0.111	0.340
Redetect				"	**0.305** (0.371)	,,	**0.171** (0.296)	**0.366**
PGD-40								
Edge	0.136	0.007	0.000	0.148	0.077	0.039	0.014	0.069
Img2Edge	,,	**0.094**	**0.092**	,,	0.095	,,	0.033	0.079
Img	**0.531**	0.019	0.000	0.392	0.150	0.191	0.019	0.188
Img + Edge	0.522	0.008	0.000	0.402	0.131	0.157	0.003	0.173
Redetect	,,	0.074	0.009	,,	0.198 (0.353)	,,	0.019 (0.103)	0.194
Img + Redetected Edge				**0.425**	0.072	**0.328**	0.005	0.208
Redetect				"	**0.206** (0.380)	,,	**0.073** (0.279)	**0.258**

Table 6: Results on CIFAR-10 dataset [edge map computed from 4 channels]

	Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
ε	0/clean	8	32	0/clean	8	0/clean	32	
FGSM								
Img+Edge	0.860	0.366	0.169	0.846	0.611	0.815	0.442	0.679
Redetect	”	0.415	0.280	”	0.574	,,	0.416	0.663
Img + Redetected Edge				0.848	0.547	0.835	0.351	0.645
Redetect				”	0.696	”	0.553	0.733
PGD-40								
Img+Edge	0.860		0.000	0.789	0.431	0.179	0.135	0.384
Redetect	”		0.087	,,	0.501	,,	0.152	0.405
Img + Redetected Edge				0.837	0.164	0.767	0.010	0.444
Redetect				”	0.648	,,	0.352	0.651

Table 7: Results on CIFAR dataset using Sobel edge detection [edge map computed from 4 channels]

	Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
ε	0/clean	8	32	0/clean	8	0/clean	32	
FGSM								
Img+Edge	0.876	0.331	0.207	0.856	0.613	0.829	0.469	0.692
Redetect	,,	0.424	0.285	,,	0.645	,,	0.490	0.705
Img + Redetected Edge				0.858	0.580	0.842	0.411	0.673
Redetect				”	0.685	,,	0.558	0.736

Table 8: Results on DogVsCat dataset [edge map computed from 4 channels] (*)

	Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
ε	0/clean	8	32	0/clean	8	0/clean	32	
FGSM								
Edge	0.814	0.633	0.119	0.812	0.757	0.806	**0.999**	0.843
Img2Edge	,,	**0.755**	**0.584**	,,	**0.767**	,,	0.576	0.740
Img	**0.863**	0.007	0.051	0.777	0.430	**0.819**	0.985	0.753
Img+Edge	0.823	0.007	0.000	0.782	0.641	0.808	0.992	0.806
Redetect	”	0.043	0.002	”	0.666	”	0.986	0.810
Img + Redetected Edge				**0.829**	0.615	0.812	0.853	0.778
Redetect				”	0.763	”	0.998	**0.850**
PGD-40								
Edge	0.814	0.624	0.018	**0.820**	0.770	0.763	0.681	0.758
Img2Edge	,,	**0.760**	**0.568**	,,	**0.778**	,,	0.656	0.754
Img	**0.863**	0.000	0.000	0.769	0.384	0.500	0.500	0.538
Img+Edge	0.823	0.000	0.000	0.785	0.689	0.816	0.496	0.696
Redetect	”	0.006	0.000	,,	0.744	,,	0.500	0.711
Img + Redetected Edge				0.819	0.600	**0.817**	0.009	0.561
Redetect				”	0.760	,,	**0.972**	**0.842**

Table 9: Results on DogBreeds dataset using Sobel edge detection [edge map computed from 4 channels] (*)

	Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ	0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM								
Edge	0.750	0.006	0.031	0.506	0.101	0.413	0.073	0.273
Img2Edge	,,	0.236	**0.194**	,,	0.362	,,	0.241	0.380
Img	**0.899**	0.256	0.140	0.823	0.595	0.829	**0.449**	0.674
Img + Edge	0.896	0.225	0.098	**0.862**	0.534	0.820	0.385	0.650
Redetect	,,	**0.244**	0.171	,,	0.455	,,	0.292	0.607
Img + Redetected Edge				0.843	0.506	**0.874**	0.298	0.630
Redetect				,,	**0.618**	,,	0.419	**0.689**
PGD-40								
Edge	0.750	0.000	0.000	0.514	0.065	0.036	0.000	0.154
Img2Edge	,,	**0.250**	**0.207**	,,	0.301	,,	0.037	0.222
Img	**0.899**	0.000	0.000	0.795	0.286	0.596	0.025	0.425
Img + Edge	0.896	0.000	0.000	0.789	0.225	0.567	0.042	0.406
Redetect	,,	0.008	0.000	,,	0.396	,,	0.065	0.454
Img + Redetected Edge				**0.772**	0.028	**0.677**	0.000	0.369
Redetect				,,	**0.393**	,,	**0.149**	**0.498**

Table 10: Results on DogBreeds dataset using Sobel edge detection [edge map computed from 3 channels]

	Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ	0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM								
Img + Edge	0.888	0.177	0.073	0.882	0.455	0.812	0.261	0.602
Redetect	,,	0.258	0.110	,,	0.502	,,	0.275	0.618
Img + Redetected Edge				0.893	0.480	0.848	0.216	0.609
Redetect				,,	0.626	,,	0.388	0.689

Table 11: Results on GTSRB dataset [edge map computed from 4 channels] (*)

	Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ	0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM								
Edge	0.938	**0.683**	0.315	**0.947**	**0.863**	**0.946**	0.701	0.864
Img2Edge	,,	0.501	0.451	,,	0.516	,,	0.469	0.719
Img	**0.955**	0.464	0.322	0.902	0.607	0.896	0.562	0.742
Img + Edge	0.951	0.624	0.382	0.940	0.842	0.943	0.686	0.853
Redetect	"	0.592	**0.471**	"	0.743	"	0.626	0.813
Img + Redetected Edge				0.925	0.801	0.939	0.616	0.820
Redetect				"	0.844	"	**0.766**	**0.869**
PGD-40								
Edge	0.938	**0.618**	0.054	**0.950**	**0.861**	**0.937**	**0.598**	**0.836**
Img2Edge	,,	0.501	**0.459**	,,	0.506	,,	0.462	0.714
Img	**0.955**	0.189	0.033	0.855	0.495	0.736	0.246	0.583
Img + Edge	0.951	0.271	0.021	0.943	0.750	0.839	0.342	0.718
Redetect	,,	0.526	0.251	,,	0.774	,,	0.514	0.767
Img + Redetected Edge				0.929	0.505	0.893	0.134	0.615
Redetect				"	0.818	,,	0.557	0.799

Table 12: Results on GTSRB dataset [edge map computed from 3 channels]

	Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ	0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM								
Img + Edge	0.951	0.624	0.382	0.940	0.842	0.943	0.686	0.853
Redetect	,,	0.500	0.395	,,	0.558	,,	0.492	0.733
Img + Redetected Edge				0.889	0.699	0.891	0.549	0.757
Redetect				,,	0.610	,,	0.577	0.742

Table 13: Results on Icons-50 dataset [edge map computed from 4 channels] (*)

		Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ		0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM									
Edge		0.883	0.545	0.210	**0.904**	0.771	**0.889**	0.594	0.789
Img2Edge		,,	**0.713**	**0.690**	,,	0.746	,,	0.730	**0.817**
Img		**0.930**	0.495	0.433	0.772	0.789	0.836	0.720	0.779
Img + Edge		0.929	0.569	0.433	0.829	0.818	0.844	**0.745**	0.809
Redetect		,,	0.470	0.414	,,	0.730	,,	0.732	0.784
Img + Redetected Edge					0.841	**0.837**	0.849	0.688	0.804
Redetect					,,	0.817	,,	0.710	0.804
PGD-40									
Edge		0.883	0.423	0.000	**0.902**	0.769	**0.846**	0.404	0.730
Img2Edge		,,	**0.706**	**0.683**	,,	0.753	,,	**0.695**	**0.799**
Img		**0.930**	0.341	0.113	0.765	0.663	0.736	0.453	0.654
Img + Edge		0.929	0.320	0.011	0.800	0.678	0.785	0.366	0.657
Redetect		,,	0.416	0.248	,,	0.738	,,	0.660	0.746
Img + Redetected Edge					0.838	0.644	0.824	0.097	0.601
Redetect					”	**0.792**	,,	0.539	0.748

Table 14: Results on Icons-50 dataset [edge map computed from 3 channels]

		Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ		0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM									
Img+Edge		0.929	0.569	0.433	0.829	0.818	0.844	0.745	0.809
Redetect		,,	0.520	0.460	,,	0.737	,,	0.731	0.785
Img + Redetected Edge					0.831	0.788	0.870	0.725	0.804
Redetect					”	0.783	,,	0.765	0.812

Table 15: Results on Sketch dataset [edge map computed from 2 channels] (*)

		Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ		0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM									
Edge		0.479	0.167	**0.041**	0.502	0.343	**0.483**	**0.216**	**0.386**
Img2Edge		,,	**0.464**	0.014	,,	**0.494**	,,	0.022	0.375
Img		**0.532**	0.109	0.278	**0.530**	0.278	0.474	0.144	0.356
Gray + Edge		0.486	0.097	0.019	0.513	0.286	0.440	0.167	0.352
Redetect		,,	0.263	0.004	,,	0.355	,,	0.013	0.330
Img + Redetected Edge					0.497	0.180	0.420	0.071	0.292
Redetect					”	0.416	,,	0.162	0.374
PGD-40									
Edge		0.480	0.106	0.000	0.508	0.341	0.401	0.068	0.330
Img2Edge		,,	**0.471**	**0.127**	,,	**0.499**	,,	**0.214**	**0.405**
Img		**0.532**	0.028	0.000	**0.538**	0.260	0.018	0.000	0.204
Gray + Edge		0.486	0.034	0.000	0.500	0.279	0.026	0.000	0.201
Redetect		,,	0.277	0.024	,,	0.360	,,	0.004	0.223
Img + Redetected Edge					0.502	0.121	**0.448**	0.000	0.268
Redetect					”	0.423	,,	0.212	0.396

Table 16: Results on Sketch dataset [edge map computed from 1 channel]

		Orig. model			Rob. model (8)		Rob. model (32)		Average
ϵ		0/clean	8	32	0/clean	8	0/clean	32	Rob. models
FGSM									
Gray + Edge		0.486	0.097	0.019	0.513	0.286	0.440	0.167	0.352
Redetect		,,	0.213	0.005	,,	0.388	,,	0.022	0.341
Img + Redetected Edge					0.519	0.296	0.445	0.191	0.363
Redetect					,,	0.397	,,	0.020	0.345

Table 17: Results on Imagenette2-160 dataset [edge map computed from 4 channels] (*)

	Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
ϵ	0/clean	8	32	0/clean	8	0/clean	32	
FGSM								
Edge	0.780	0.101	0.436	0.781	0.520	0.664	0.245	0.553
Img2Edge	,,	0.599	**0.598**	,,	0.603	,,	0.578	0.656
Img	**0.969**	0.617	0.409	**0.959**	0.827	0.946	0.710	0.860
Img + Edge	0.959	0.613	0.373	0.951	0.801	0.935	0.643	0.832
Redetect	,,	**0.652**	0.471	,,	0.812	,,	0.687	0.846
Img + Redetected Edge				0.950	0.747	**0.949**	0.592	0.810
Redetect				,,	**0.834**	,,	**0.732**	**0.866**
PGD-40								
Edge	0.780	0.064	0.000	0.794	0.526	0.577	0.071	0.492
Img2Edge	,,	**0.601**	**0.577**	,,	0.610	,,	0.381	0.591
Img	**0.969**	0.052	0.005	0.918	0.599	0.808	0.221	0.636
Img + Edge	0.959	0.045	0.000	0.909	0.558	0.762	0.151	0.595
Redetect	"	0.445	0.069	"	0.743	"	0.305	0.680
Img + Redetected Edge				0.944	0.246	**0.883**	0.046	0.530
Redetect				"	**0.757**	"	**0.432**	**0.754**

Table 18: Results on Imagenette2-160 dataset [edge map computed from 3 channels]

	Orig. model			Rob. model (8)		Rob. model (32)		Average Rob. models
ϵ	0/clean	8	32	0/clean	8	0/clean	32	
FGSM								
Img + Edge	0.959	0.613	0.373	0.951	0.801	0.935	0.643	0.833
Redetect	,,	0.611	0.447	,,	0.802	,,	0.673	0.840
Img + Redetected Edge				0.952	0.767	0.949	0.596	0.816
Redetect				,,	0.832	,,	0.729	0.865

C   SUMMARY RESULTS OF USING EDGES FOR ADVERSARIAL DEFENSE

Figure 16: Comparison of natural (the Orig. column in the tables; solid curves) *vs.* adversarial training (blue dashed-dot curves). The accuracy at $\epsilon = 0$ (for adversarial training) is averaged over different robust models (three over MNIST and two over others; corresponding to clean columns in tables). Left column) Average over MNIST and Fashion MNIST datasets, Right column) Average over all datasets. Results show a clear advantage of using edges. Over MNIST and FashionMNIST, the model trained on edges alone leads to a trade-off between accuracy and robustness. Img+edge model does worse than the Image model but its performance is recovered after adversarial training. Img2Edge model wins over models using natural training. Please see also tables in the main text and Appx. B and the explanation in the main text. Overall, incorporating edge and image together and redetection at inference times leads to higher accuracy and robustness.

Figure 17: Breakdown of natural training (the Orig. row in Tables) over datasets.

D ANALYSIS OF PARAMETER α IN ALG. 1 (EAT DEFENSE)

Table 19: Results (Top-1 acc.) over MNIST corresponding to $\alpha = 0$ (i.e., adversarial training only on adversarial examples taking part in the loss function). See also Table 1 in the main text.

	Rob. model (8)		Rob. model (32)		Rob. model (64)		Average
ϵ	0/clean	8	0/clean	32	0/clean	64	Rob. models
FGSM							
Img+Edge	**0.963**	0.938	**0.959**	0.869	0.931	0.684	0.891
Redetect	"	0.943	,,	0.887	,,	0.727	0.902
Img + Redetected Edge	**0.963**	0.936	0.944	0.588	**0.937**	0.030	0.733
Redetect	"	**0.948**	,,	**0.911**	,,	**0.916**	**0.937**
PGD-40							
Img+Edge	**0.966**	0.940	**0.960**	0.859	0.928	0.607	0.877
Redetect	"	**0.946**	,,	0.883	,,	0.657	0.890
Img + Redetected Edge	0.963	0.933	0.947	0.469	**0.936**	0.000	0.708
Redetect	"	**0.946**	,,	**0.913**	,,	**0.915**	**0.937**

Table 20: Results (Top-1 acc.) over Fashion MNIST corresponding to $\alpha = 0$ (i.e., adversarial training only on adversarial examples taking part in the loss function). See also Table 4 in the main text.

	Rob. model (8)		Rob. model (32)		Rob. model (64)		Average
ϵ	0/clean	8	0/clean	32	0/clean	64	Rob. models
FGSM							
Img+Edge	0.756	0.701	0.732	0.619	0.683	0.487	0.663
Redetect	"	0.707	,,	0.635	,,	0.481	0.666
Img + Redetected Edge	**0.768**	0.705	**0.739**	0.481	**0.693**	0.040	0.571
Redetect	"	**0.727**	,,	**0.660**	,,	**0.635**	**0.704**
PGD-40							
Img+Edge	0.768	0.702	0.749	0.573	0.718	0.432	0.657
Redetect	"	0.714	,,	0.593	,,	0.510	0.675
Img + Redetected Edge	**0.778**	0.702	**0.762**	0.414	**0.750**	0.001	0.568
Redetect	"	**0.725**	,,	**0.632**	,,	**0.615**	**0.710**

E RESULTS OF THE SUBSTITUTE MODEL ATTACK

Table 21: Results of the substitute attack against the robust Img + Edge models (redetect and full model).

	MNIST			Fashion MNIST			CIFAR		TinyImgNet	
ϵ	8	32	64	8	32	64	8	32	8	32

FGSM

Img + edge model (redetect inference)

Substitute model on clean images	0.94	0.9365	0.9314	0.7515	0.7393	0.7311	0.8079	0.7766	0.008	0.008
Substitute model on adversarial images	0.8941	0.5858	0.0992	0.6484	0.3701	0.0967	0.2716	0.2049	0.004	0.003
Robust model on clean images	0.9761	0.9766	0.9722	0.7939	0.7692	0.75	0.8463	0.8463	0.508	0.471
Robust model on adversarial images	0.9623	0.9189	0.842	0.7391	0.6156	0.4908	0.5695	0.4186	0.287	0.161
Robust model on substitute adv. images	0.9678	0.9472	0.8813	0.7609	0.6604	0.4955	0.6307	0.5463	0.356	0.266

Img + redetected edge model (redetect inference)

Substitute model on clean images	0.9381	0.9335	0.9326	0.7513	0.7431	0.7388	0.8104	0.7966	0.008	0.008
Substitute model on adversarial images	0.89	0.5696	0.0989	0.6538	0.3663	0.08	0.2879	0.1988	0.004	0.002
Robust model on clean images	0.9742	0.9699	0.9681	0.7891	0.7746	0.7617	0.8456	0.8328	0.495	0.482
Robust model on adversarial images	0.9583	0.9283	0.9216	0.7392	0.664	0.6115	0.7032	0.5684	0.380	0.170
Robust model on substitute adv. images	0.9657	0.9469	0.9249	0.7529	0.6776	0.5318	0.7528	0.7528	0.371	0.296

PGD-40

Img + edge model (redetect inference)

Substitute model on clean images	0.9391	0.9344	0.9257	0.7531	0.7408	0.7303	0.756	0.194	0.008	0.006
Substitute model on adv. images	0.8906	0.4455	0.0196	0.6473	0.2745	0.0096	0.020	0.003	0.000	0.000
Robust model on clean images	0.9782	0.9751	0.9654	0.7938	0.7652	0.7442	0.788	0.179	0.395	0.157
Robust model on adv. images	0.9599	0.9132	0.8039	0.7336	0.6289	0.6068	0.504	0.152	0.242	0.018
Robust model on substitute adv. images	0.9667	0.9477	0.9079	0.7603	0.6656	0.4263	0.646	0.170	0.352	0.103

Img + redetected edge model (redetect inference)

Substitute model on clean images	0.9385	0.9363	0.9329	0.7503	0.7471	0.7415	0.804	0.730	0.008	0.008
Substitute model on adv. images	0.8888	0.4617	0.0211	0.6458	0.2687	0.01	0.016	0.000	0.000	0.000
Robust model on clean images	0.975	0.9732	0.9682	0.7998	0.7793	0.7715	0.834	0.766	0.425	0.328
Robust model on adv. images	0.9581	0.9449	0.9386	0.7435	0.6943	0.6902	0.662	0.375	0.206	0.074
Robust model on substitute adv. images	0.9665	0.9575	0.9417	0.7661	0.681	0.5037	0.767	0.700	0.380	0.279

Analysis of making either the image channel or the edge channel in models (i.e., making them zero). Over the original edge augmented model (Img+Edge), the image channel is more important since masking it hurts the model more (compared to the making the edge channel). Conversely, over the robust and robust redetect models, masking the edge channel hurts more. This indicates that robust models rely more on shape than texture. Models used here are adversarially trained against each attack. For example, Img+Edge Robust model is trained separately for $\epsilon = 8/255$. This is the same setup as in the main text and tables.

Table 22: Masking channels over MNIST dataset

	Img+Edge Model	Img+Edge Robust			Img+Edge Robust Redetect		
ϵ	0	8	32	64	8	32	64
FGSM							
Masking Img Channels	0.851	0.841	0.914	0.924	0.850	0.931	0.951
Masking Edge Channel	0.968	0.974	0.975	0.969	0.964	0.942	0.718
PGD							
Masking Img Channels	0.851	0.915	0.921	0.920	0.862	0.956	0.956
Masking Edge Channel	0.968	0.975	0.973	0.954	0.970	0.957	0.858

Table 23: Masking channels over Fashion MNIST dataset

	Img+Edge Model	Img+Edge Robust			Img+Edge Robust Redetect		
ϵ	0	8	32	64	8	32	64
FGSM							
Masking Img Channels	0.161	0.324	0.526	0.690	0.253	0.560	0.734
Masking Edge Channel	0.768	0.761	0.709	0.530	0.715	0.650	0.543
PGD							
Masking Img Channels	0.161	0.220	0.585	0.744	0.246	0.677	0.760
Masking Edge Channel	0.768	0.758	0.656	0.100	0.717	0.577	0.447

F   SAMPLE GENERATED IMAGES BY THE CONDITIONAL GAN IN GAN-BASED SHAPE DEFENSE (GSD)

Figure 18: Top) GSD with a classifier trained on images generated (by pix2pix) only from the edge maps of the clean images, Bottom) GSD with edge maps derived from adversarial examples. Columns from left to right: adversarial images by the FGSM attack, their edge maps, and generated images by pix2pix.

G SHAPE-BASED EXTENSIONS OF VANILLA PGD ADVERSARIAL TRAINING, FREE ADVERSARIAL TRAINING (FREEAT), AND FAST ADVERSARIAL TRAINING (FASTAT) ALGORITHMS

Algorithm 3 Shape-based PGD adversarial training for T epochs, given some radius ϵ, adversarial step size α and N PGD steps and a dataset of size M for a network f_θ. $\beta \in \{edge, img, imgedge\}$ indicates the net_type and *redetect_train* mean edge redetection during training.

---

for $t = 1 \ldots T$ **do**
    for $i = 1 \ldots M$ **do**
        // Perform PGD adversarial attack
        $\delta = 0$ *// or randomly initialized*
        for $j = 1 \ldots N$ **do**
            $\delta = \delta + \alpha \cdot \text{sign}(\nabla_\delta \ell(f_\theta(x_i + \delta), y_i))$
            $\delta = \max(\min(\delta, \epsilon), -\epsilon)$
        end for
        $\tilde{x}_i = x_i + \delta$
        if *redetect_train* & β == *imgedge* **then**
            $\tilde{x}_i = \text{detect\_edge}(\tilde{x}_i)$ *// recompute and replace the edge map*
        end if
        $\theta = \theta - \nabla_\theta \ell(f_\theta(\tilde{x}_i), y_i)$ *// Update model weights with some optimizer, e.g. SGD*
    end for
end for

Algorithm 4 Shape-based "Free" adversarial training for T epochs, given some radius ϵ, N minibatch replays, and a dataset of size M for a network f_θ. $\beta \in \{edge, img, imgedge\}$ indicates the net_type and *redetect_train* mean edge redetection during training.

$\delta = 0$
// Iterate T/N times to account for minibatch replays and run for T total epochs
for $t = 1 \ldots T/N$ **do**
    for $i = 1 \ldots M$ **do**
        // Perform simultaneous FGSM adversarial attack and model weight updates T times
        for $j = 1 \ldots N$ **do**
            $\tilde{x}_i = x_i + \delta$
            if *redetect_train* & β == *imgedge* **then**
                $\tilde{x}_i = \text{detect\_edge}(\tilde{x}_i)$ *// recompute and replace the edge map*
            end if
            // Compute gradients for perturbation and model weights simultaneously
            $\nabla_\delta, \nabla_\theta = \nabla \ell(f_\theta(\tilde{x}_i), y_i)$
            $\delta = \delta + \epsilon \cdot \text{sign}(\nabla_\delta)$
            $\delta = \max(\min(\delta, \epsilon), -\epsilon)$
            $\theta = \theta - \nabla_\theta$ *// Update model weights with some optimizer, e.g. SGD*
        end for
    end for
end for

Algorithm 5 Shape-based FGSM adversarial training for T epochs, given some radius ϵ, N PGD steps, step size α, and a dataset of size M for a network f_θ. $\beta \in \{edge, img, imgedge\}$ indicates the net_type and *redetect_train* mean edge redetection during training.

---

  for $t = 1 \ldots T$ **do**
    for $i = 1 \ldots M$ **do**
      // Perform FGSM adversarial attack
      $\delta = \text{Uniform}(-\epsilon, \epsilon)$
      $\delta = \delta + \alpha \cdot \text{sign}(\nabla_\delta \ell(f_\theta(x_i + \delta), y_i))$
      $\delta = \max(\min(\delta, \epsilon), -\epsilon)$
      $\tilde{x}_i = x_i + \delta$
      if *redetect_train* & $\beta == imgedge$ **then**
        $\tilde{x}_i = \text{detect\_edge}(\tilde{x}_i)$ *// recompute and replace the edge map*
      end if
      $\theta = \theta - \nabla_\theta \ell(f_\theta(\tilde{x}_i), y_i)$ *// Update model weights with some optimizer, e.g. SGD*
    end for
  end for

Table 24: Performance of the Fast Adversarial Training (FastAT) method over three runs.

Model	Run 1 Clean	Run 1 PGD-10	Run 1 Clean	Run 1 PGD-10	Run 1 Clean	Run 1 PGD-10	Average Clean	Average PGD-10
Edge	0.559	0.384	0.581	0.187	0.608	0.586	0.582	0.386
RGB	0.813	0.368	0.598	0.205	0.889	0.569	0.767	0.381
Img + Edge	0.863	0.590	0.882	0.334	0.878	0.878	**0.874**	0.386
Redetect	,,	0.593	,,	0.341	,,	0.245	,,	0.393
RGB + Redet. Edge	0.892	0.001	0.817	0.115	0.889	0.105	0.866	0.074
Redetect	,,	0.265	,,	0.656	,,	0.326	,,	**0.416**

Table 25: Performance of the Free Adversarial Training (FreeAT) method over three runs.

Model	Run 1 Clean	Run 1 PGD-10	Run 1 Clean	Run 1 PGD-10	Run 1 Clean	Run 1 PGD-10	Average Clean	Average PGD-10
Edge	0.674	0.672	0.704	0.702	0.660	0.659	0.679	**0.678**
RGB	0.783	0.450	0.768	0.450	0.772	0.447	0.774	0.449
Img + Edge	0.784	0.432	0.779	0.447	0.782	0.448	**0.782**	0.442
Redetect	,,	0.447	,,	0.448	,,	0.449	,,	0.448
RGB + Redet. Edge	0.776	0.451	0.776	0.454	0.780	0.447	0.777	0.451
Redetect	,,	0.452	,,	0.456	,,	0.448	,,	0.452

H PERFORMANCE OF THE MODELS AGAINST COMMON IMAGE CORRUPTIONS

Figure 19: Sample images alongside their corruptions with 5 severity levels.

Figure 20: Edges for images in Fig. 19.

Figure 21: Performance of models against natural image corruptions over the TinyImageNet dataset. Robust models are trained against FGSM attack.

Figure 22: Performance of models against natural image corruptions over the GTSRB dataset.

Figure 23: Performance of models against natural image corruptions over the Icons-50 dataset.

I   EFFECT OF BACKGROUND SUBTRACTION IN ADVERSARIAL DEFENSE

Figure 24: Examples of invisible (left) and visible (right) backdoor attacks (e.g., Brown et al. (2017)). Our proposed shape defense can easily bypass the invisible backdoor attack since edge detection removes the watermark. Our defense together with background subtraction (akin to gazing to a single object at a time) can also avoid visible backdoor attacks. See also the main text.

Figure 25: Application of the Img and Edge models over Original, noisy, and background-subtracted MNIST digits. Noisy data is created by overlaying a digit over white noise (noise×(1-mask)+digit). The FGSM attack is used here. We find that background subtraction together with edge detection improves robustness.

Figure 26: Application of the Img and Edge models over Original, noisy, and background-subtracted FashionMNIST data. Noisy data is created by overlaying an object over white noise (noise×(1-mask)+object). The FGSM attack is used here. We find that background subtraction together with edge detection improves robustness.

Figure 27: Similar to Fig. 5 in the main text with the difference that here the noise model is trained over the noisy data. Removing the perturbations on the image background (via background subtraction) improves the robustness.

Figure 28: Masking the FGSM attack perturbations (i.e., keeping the altered pixels on the image or edge only regions).

Table 26: Performance of the models (naturally trained and adversarially-trained) against the images with only the foreground being impacted/perturbed. Compared with the results in Table. 1, applying the models to the foreground regions improves the accuracy by a large margin.

	FGSM			PGD-40		
	$\epsilon = 8$	$\epsilon = 32$	$\epsilon = 64$	$\epsilon = 8$	$\epsilon = 32$	$\epsilon = 64$
Img (natural training)	0.9598	0.9021	0.7516	0.9598	0.8947	0.7042
Img (adversarial training)	0.9641	0.9237	0.8398	0.9636	0.9139	0.7868
Edge (natural training)	0.9553	0.9199	0.8323	0.9553	0.9213	0.8452
Edge (adversarial training)	0.9686	0.9468	0.9059	0.9686	0.9474	0.9057

J ROBUSTNESS AGAINST THE CW ATTACK OVER MNIST DATASET

Performance of the the EAT defense against the l_2 Carlini-Wagner attack (Carlini & Wagner, 2017) with the following parameters:

```
attack = CW(net, targeted=False, c=1e-4, kappa=0, iters=10, lr=0.001)
```

	Orig. model		Robust model		Average
	0/clean	adv.	0/clean	adv.	Rob. models
Edge	0.964	0.106	0.948	0.798	0.873
Img2Edge	,,	0.962	,,	0.949	**0.949**
Img	0.973	0.103	0.949	0.856	0.903
Img+Edge	0.972	0.097	0.945	0.845	0.895
Redetect	,,	0.971	,,	0.942	0.944
Img + Redetected Edge			0.947	0.819	0.883
Redetect			,,	0.946	0.946

K   ROBUSTNESS AGAINST BOUNDARY ATTACK

Performance of the the edge augmented model against the Boundary attack (Brendel et al., 2017) with the following parameters:

```
BoundaryAttack(init_attack=None, steps=25000, spherical_step=0.01,
               source_step=0.01, source_step_convergance=1e-07,
               step_adaptation=1.5, tensorboard=False,
               update_stats_every_k=10)
```

Table 27: Results over 500 images from the MNIST dataset

	Orig. model	
	0/clean	adv.
Edge	0.964	0.000
Img	0.973	0.003
Img+Edge	0.972	0.000
Redetect	,,	**0.945**

Table 28: Results over 500 images from the Fashion MNIST dataset

	Orig. model	
	0/clean	adv.
Edge	0.776	0.005
Img	0.798	0.018
Img+Edge	0.809	0.003
Redetect	,,	**0.747**

Figure 29: Sample images from the Boundary attack.

L   ROBUSTNESS AGAINST ADAPTIVE ATTACKS OVER IMAGENETTE2-160 DATASET

We use the PyTorch implementation[7] of the HED edge detector proposed by Xie & Tu (2015). Here, a classifier is first trained on top of the edge maps from the HED. Then, the entire pipeline (Img $\longrightarrow$ HED $\longrightarrow$ Classifier^{HED}) is attacked to generate an adversarial image. The performance of this classifier is measured on both clean and adversarial images. The adversarial image is also fed to the classifier trained on Canny edge maps (Img$^{adv-HED}$ $\longrightarrow$ Canny $\longrightarrow$ Classifier^{Canny}). Results are shown in Table below. As it can be seen, adversarial examples crafted for HED fail to completely fool the model trained on Canny edges (i.e., they do not transfer).

Table 29: Results over 500 images from the Imagenette2-160 dataset against the FGSM and PGD-5 ($\epsilon = 8/255$) attacks.

	Orig. model		
	0/clean	adv. (FGSM)	adv. (PGD-5)
Img2Edge (Img $\longrightarrow$ HED $\longrightarrow$ Classifier^{HED})	0.793	0.052	0.003
Img2Edge (Img$^{adv-HED}$ $\longrightarrow$ Canny $\longrightarrow$ Classifier^{Canny})	0.767	0.542	0.548

Figure 30: Two sample adversarial images (FGSM) along with their edge maps using HED and Canny edge detection methods.

---

[7]https://github.com/sniklaus/pytorch-hed