LEARNING INVARIANT FEATURES FOR ONLINE CONTINUAL LEARNING

ABSTRACT

It has been shown recently that learning only *discriminative features* that are sufficient to separate the classes in a task using a traditional learning method has a major shortcoming for continual learning (CL). This is because many features that are not learned may be necessary for distinguishing classes of some future tasks. When such a future task arrives, these features have to be learned by updating the network, which causes *catastrophic forgetting* (CF). A recent work on online CL showed that if the learning method can learn as many features as possible from each class, called *holistic representations*, CF can be significantly reduced to achieve a large performance gain. This paper argues that learning only holistic representations is still insufficient. The learned representations should also be *invariant* and those features that are present in the data but are irrelevant to the class (e.g., the background information) should be ignored for better generalization across tasks. This new condition further boosts the performance significantly. This paper proposes several strategies and a loss to learn *holistic and invariant representations* and evaluates their effectiveness in online CL. [1]

1 INTRODUCTION

A major challenge of continual learning (CL) is *catastrophic forgetting* (CF). CF means that the learning of a new task may modify the parameters learned from previous tasks causing their performance to degrade (McCloskey & Cohen, 1989). Existing techniques for dealing with CF have mainly focused on preventing changes to parameters learned in the past. For example, the *regularization-based* approach (Kirkpatrick et al., 2017) finds important parameters to previous tasks and uses a regularization to penalize updates to them in the new task learning. The *parameter isolation* approach (Serrà et al., 2018) masks out the past parameters during the new task learning. The *replay-based* approach (Rebuffi et al., 2017) saves a small amount of past data and uses them in training the new task to protect/adjust the previous task parameters. But a small amount of replay data is far from sufficient to overcome CF. From a more theoretical perspective, limited work has been done to study the necessary conditions for CL to overcome CF. Recently, Guo et al. (2022) argued that it is necessary to learn *holistic representations* of the data. This work proposes another condition, *invariance*, and argues that the learning of each task itself needs to be improved so that future tasks would not need to make major changes to old parameters.

It is well-known that supervised learning losses (e.g., cross-entropy) aim to learn only discriminative features that are sufficient to separate the classes in a task. This is problematic for CL due to two main reasons. (1) many features that are not learned may be necessary to distinguish classes of some future tasks. When such a future task comes, these features have to be learned, which may make significant changes to the existing parameters and cause CF. (2) even if the previous parameters can be protected (e.g., in the regularization-based approach), the classes in the new task still make the classification more challenging because each task focuses only on learning discriminative features for its own classes, which can cause *confusion* in classification when we need to classify all classes learned so far. We call this the ***biased representation learning*** problem. For example, task-1 learns to classify *black pig* and *dove*. The learner may only learn the color features (e.g., black and white) as they are sufficient to classify the two classes. However, task-2 learns rabbit and cow. Since cows and

---

[1]The code has been submitted in the supplemental material.

rabbits can be black or white. The color features learned from task-1 are no longer sufficient. Shape-based features may need to be learned, which can make major changes to the existing parameters and cause CF. If the shape-based features had been learned from task-1, when learning cow and rabbit, it will not need to update the parameters linked to the representation of pigs and doves as much, which will result in less CF (mitigating (1) above). Since there are now 4 classes to classify, it can be quite confusing. Some cows or rabbits may be classified as pigs or doves due to the same color. Some pigs may be classified as cows or rabbits due to shape-based features learned in task-2. However, if all features have been learned in task-1 and task-2, such wrong classifications will be reduced (dealing with (2)). Recently, Guo et al. (2022) proposed to learn *holistic representations* from the input data to cover as many characteristics of the input as possible. Their system OCM learns holistic representations in online CL by maximizing the mutual information (MI) between the input data and the learned feature representations to ensure that as much information in the input is reflected in the learned features. This results in a major performance gain in online CL.

This paper argues that learning *holistic representations* is still sub-optimal. CL should also ensure that the learned features are *invariant* for each class. Those features that are present in the input but are irrelevant to the class should be ignored for better generalization to future tasks. For example, to classify images of *apple* and *fish*, some green background and red color of apple may be learned, but these features are not invariant for apple. When new classes *cows* and *ladybird* need to be learned, the feature green (or red) is shared (see Figure 1(a)) and may cause high logit outputs to apple and cow (or ladybird). Then the learner has to modify the representations of apple to reduce its logit values, which causes CF. That is, variant features are unsuitable to establish decision boundaries. If the learner has learned shape and other invariant features for apple, the input of cow (or ladybird) will not activate the parameters linked to the apple representation. Then, in learning cow and ladybird, changes to the parameters that are important for apple will be limited, which is desirable for overcoming CF. Our goal in this paper is to learn *invariant* and *holistic* representations for each class. This additional *invariance* condition gives another boost to online CL performance.

Note that invariance is not critical for traditional single task or multitask learning due to the i.i.d assumption, but for CL, it is very important because each new task introduces new distributions and we want each class to be distinguishable against any past and future classes, which may have similar variant features that can confuse the model.

This paper works in the online *class-incremental learning* (CIL) setting.[2] It proposes a replay-based online CIL method called IFO (*I*nvariant *F*eature learning for *O*nline CL), which adds the invariance condition to holistic feature representation learning to also learn invariant features. We propose two ways to achieve invariance. The first is to construct a diverse set of environments and force the model to learn invariant features across the environments in the set. Two data augmentations are proposed to construct the set and a new loss to learn invariant representations is also designed. The second is to better utilize the data in the original dataset to learn invariant features across different natural environments. Based on OCM Guo et al. (2022), we further add the new data in learning and store more resized images to learn invariant class representations. Finally, we combine the methods into a single optimization goal. Theoretical justifications are also given. We verify the effectiveness of IFO in two online CL scenarios: traditional *disjoint task scenario* and *blurry task boundary scenario* (Koh et al., 2021). The results show the proposed IFO outperforms strong baselines by a large margin. Detailed analyses also show that IFO not only helps establish decision boundaries of classes within a task but also boundaries of classes across tasks.

2 RELATED WORK

Although many CL approaches have been proposed, little work has been done to study the necessary conditions for effective CL. The popular *replay* approach saves a small amount of past data and uses it to protect/adjust the previous knowledge in learning a new task (Rebuffi et al., 2017; Wu et al., 2019; Hou et al., 2019; Chaudhry et al., 2020; Zhao et al., 2021; Korycki & Krawczyk, 2021; Sokar et al., 2021; Yan et al., 2021; Wang et al., 2022a). *Pseudo-replay* generates replay samples (Shin et al., 2017; Hu et al., 2019). Using *regularizations* to penalize changes of important parameters to previous tasks is another approach (Kirkpatrick et al., 2017; Ritter et al., 2018; Ahn et al., 2019; Yu

---

[2]In the CIL setting, no task related information (e.g., task-id) is provided in testing. The other popular CL setting is *task-incremental learning* (TIL), which needs the task-id to be provided for each test instance.

et al., 2020; Zhang et al., 2020). The *parameter-isolation* approaches protect models of old tasks using masks with/without network expansion (Ostapenko et al., 2019; von Oswald et al., 2020; Li et al., 2019; Hung et al., 2019; Rajasegaran et al., 2020; Abati et al., 2020; Wortsman et al., 2020; Saha et al., 2021). Zhu et al. (2021) found that using data augmentations can learn more transferable features. Sokar et al. (2021) proposed a pseudo-replay method based on CVAE and assumes that CVAE contains good class discriminative features. That is very different from invariant features across environments that we focus on. So far, little work has been done on invariant features or necessary conditions for effective CL except (Guo et al., 2022) which we have discussed in Sec. 1.

In online CL, apart from OCM (Guo et al., 2022), there are many other approaches. They are primarily based on replay. For example, ER randomly samples the replay data (Chaudhry et al., 2020), MIR chooses replay samples whose losses increase most (Aljundi et al., 2019a), ASER uses the Shapley value theory (Shim et al., 2021), and GDumb produces the class balanced replay data (Prabhu et al., 2020). GSS diversifies the gradients of the replay data (Aljundi et al., 2019b). DER++ used knowledge distillation (Buzzega et al., 2020), SCR uses contrastive loss (Mai et al., 2021), and NCCL calibrates the network (Yin et al., 2021). Applications of online CL are also reported, e.g., segmentation (Yan et al., 2021) and object detection (Wang et al., 2021). Bang et al. (2021) propose the blurry online CL setting but only the data distribution shifts and no new classes appear in the setting. Bang et al. (2022) further study the online blurry data stream setting with corrupted labels. Our IFO is also a replay method but it focuses on learning invariant features.

Domain generalization (DG) is also related to our work. DG aims to learn a model with inputs from multiple given source domains having the same class labels and test with inputs from unseen target domains. Existing DG methods typically leverage data augmentations to expand the diversity of the source domains (Wang et al., 2020; Wu et al., 2020; Arjovsky et al., 2019; Rame et al., 2022). There are also works on a single domain. Yang et al. (2021) used a pre-trained domain augmenter to create novel stylized images. Yue et al. (2019) used auxiliary datasets to help create images. Our training data have no identified domains and we use no additional datasets. DG does not do CL.

3 PROBLEM FORMULATION

This paper uses two online CL settings. The first is the traditional *disjoint tasks* setting, where the system learns a set of tasks incrementally. Each task consists of several classes. After one task completes, a new task starts. The data for each task comes in a stream and the learner sees the data only once. In a replay method, when a small batch of data of the current task t is accumulated in the data stream $D_t^{new} = (X_t^{new}, Y_t^{new})$ (where X_t^{new} is a set of new samples and Y_t^{new} is its set of corresponding labels), a small batch of replay data $D_t^{buf} = (X_t^{buf}, Y_t^{buf})$ is sampled from the memory buffer $\mathcal{M}$ and used to jointly train in one iteration. The second setting is the *i-Blurry setting* (Koh et al., 2021), where the classes from a previous task may appear again later and new classes incremental appear (more details will be given in Sec. 5.2).

The model F consists of two parts: the feature extractor f_θ and the classifier σ_ϕ. f_θ extracts features from the input x to form a high-level representation and σ_ϕ and softmax operation map the representation to a prediction probability for each class.

Learning holistic representations. As discussed in Sec. 1, f_θ should learn *holistic feature representations* (Guo et al., 2022) but cross-entropy loss $\mathcal{L}_{ce}$ alone is unable to do that. Geirhos et al. (2020) also found that $\mathcal{L}_{ce}$ encourages models to stop learning once simple features suffice to minimize the loss. This means f_θ may learn simple discriminative features for the current distribution and ignore other semantic features present in the input data. OCM (Guo et al., 2022) tackles this problem by learning as many features as possible from the input X via maximizing the mutual information between the input X and the hidden representation $f_\theta(X)$ ($I(X; f_\theta(X))$) and the mutual information ($I(.)$) between the representation $f_\theta(X)$ and the label Y ($I(Y; f_\theta(X))$) to learn as many characteristics of the input as possible. OCM uses the InfoNCE loss (Poole et al., 2019) ($\mathcal{L}_{InfoNCE}$) to optimize $I(X; f_\theta(X))$ (i.e., $I(X_t^{new}; f_\theta(X_t^{new})) + I(X_t^{buf}; f_\theta(X_t^{buf}))$) for the replay-based method. Note that it maximizes $I(Y; f_\theta(X))$ by using only X_t^{buf} to calculate the cross-entropy loss as $I(Y; f_\theta(X))$ is maximized when Y follows the uniform distribution. X_t^{buf} is sampled from the class uniformly distributed data of all seen classes stored in the memory buffer. The loss for OCM is

$$\mathcal{L}_{OCM}(D_t^{buf}, D_t^{new}) = \mathcal{L}_{InfoNCE}(X_t^{new}, f_\theta(X_t^{new})) + \mathcal{L}_{InfoNCE}(X_t^{buf}, f_\theta(X_t^{buf})) + \mathcal{L}_{InfoNCE}(f_\theta(X_t^{buf}), f_\theta^{prev}(X_t^{buf}))$$

(1)

where the last term tries to prevent F from forgetting features of previous classes by maximizing the mutual information between the hidden representations of X_t^{buf} given by the current feature extractor f_θ and the feature extractor f_θ^{prev} before the current task, i.e., $I(f_\theta(X_t^{buf}); f_\theta^{prev}(X_t^{buf}))$. Then OCM uses the InfoNCE loss to estimate $I(f_\theta(X_t^{buf}); f_\theta^{prev}(X_t^{buf}))$.

Invariant features. As discussed in Sec. 1, in addition to learning holistic feature representations of the input data, this paper argues that the learned feature sshould also be invariant to each class. We give a more rigorous definition of the invariant class-related feature here.

Definition 1 A feature s is *invariant* for a class label $y \in Y$ if the following holds,

$$\mathbb{E}_{x \sim X_z}[\mathbb{I}(s \in x) \cdot |Corr(x, y)|] > \rho \quad \forall z \in Z \tag{2}$$

where X_z is the input variable under the environment z, Z is the set of all possible environments and not limited to the dataset D, $Corr$ is a function computing the correlation between the input x and its label y, $|\cdot|$ is the absolute value function and ρ is a constant. $\mathbb{I}(s \in x)$ is the indicator function that identifies if feature s exists in input x. Note that by environment z we not only mean the background of an object (e.g., forest as the background) but also the object in the input (e.g., a building showing different colors in rainy days and sunny days).

Learning holistic invariant representations. Combining the two concepts, our goal is to learn *holistic invariant representations* for each class, i.e., learning invariant features as many as possible, which help reduce CF and improve the generalization power of the model. In the following, we focus on proposing techniques to learn invariant features. We rely on the method in OCM to learn as many invariant features as possible to achieve holisticness.

4 OPTIMIZATION OBJECTIVE AND PROPOSED METHOD

The proposed optimization objective for holistic invariant representation learning is $\mathcal{L}_{holistic} = \mathcal{L}_{all} + \mathcal{L}_{invariant}$, where $\mathcal{L}_{all}$ aims to learn holistic features and $\mathcal{L}_{invariant}$ emphasizes invariance and suppresses non-invariant features. The proposed method focuses only on designing $\mathcal{L}_{invariant}$. We directly use the holistic representation loss of OCM, $\mathcal{L}_{OCM}(D_t^{buf}, D_t^{new})$, as $\mathcal{L}_{all}$.

To learn invariant features, the model should ignore features that have a positive relation with class y in some environments but not in other environments (Definition 1). That is, the model should learn features that have a positive correlation with each class regardless of the environments. Here we borrow an idea in (Jung et al., 2020) for causal inference. Jung et al. (2020) proposed to replace the *observational distribution* $P(Y_t^{new}|X_t^{new})$ with the interventional distribution $P(Y_t^{new}|do(X_t^{new}))$ in Empirical Risk Minimization, where $do(X)$ removes the environmental effects from the prediction of Y. Then the interventional Empirical Risk can be written as Wang et al. (2022b):

$$\hat{R}(D_t^{new}) = \mathbb{E}_{x \sim P(X_t^{new}), y \sim P(Y_t^{new}|do(X_t^{new}))} \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y))$$
$$= \sum_y \sum_x \sum_z \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(y|x, z) P(z) P(x) \tag{3}$$

where z is a sample from the ideal environment variable Z that includes all possible environments. For a replay-based method, the interventional empirical risk is $\hat{R}(D_t^{new}) + \hat{R}(D_t^{buf})$. However, directly optimizing the interventional empirical risk is hard as z is hard to observe or annotate. In the following, we use the interventional empirical risk (Eq. 3) to guide the design of our method.

4.1 CREATING MORE ENVIRONMENTS z FOR LEARN INVARIANT FEATURES

Different from domain generalization, CL does not provide a fixed number visually distinct domains/environments or any prior knowledge about the domains (e.g., the domains/environments where the objects to be classified reside in). To achieve a similar effect of different domains or environments, we propose two data augmentations for the input image x to create augmented images with different z's. The idea is to construct a diverse environment set $\mathbb{Z}$ so that the learner can ignore irrelevant (non-invariant) features to the class and emphasize the invariant ones.

(1). Color change. For an input image x, we first randomly reorder the RGB channels of the image to create an augmented image x'. Then, we sample a λ from the Beta distribution and create the

Figure 1: (a) is the illustration for the example in the Introduction and (b) is the illustration for the data augmentation Aug_{color} and (c) is the illustration for the data augmentation Aug_{plus}.

final version of the augmented image,

$$\hat{x} = \lambda \cdot x + (1 - \lambda) \cdot x' \tag{4}$$

We use this augmentation to create augmented images with different color environments (Fig. 1(b)). The labels of the augmented images do not change. We denote this augmentation as $Aug_{color}(x, s)$, where s means that we repeat the two steps s times to create s different augmented images.

(2). Adding more environments. For an input x of size d, we first resize x to $r_1 \cdot d$ where r_1 is the resize rate. We name this resized image as $resize(x, r_1 \cdot d)$. Then we randomly sample anther image x_2 from the batch $X_t^{buf} \bigcup X_t^{new}$ and replace the center part of x_2 with $resize(x, r_1 \cdot d)$. We denote the augmented image as $Aug_{plus}(x)$, whose original object is not changed dramatically with a reasonable choice of r_1. But the background change introduces features from image x_2 (see Fig. 1(c).

We use the two augmentations separately to create augmented images of x as $Aug(x) = Aug_{plus}(x) \bigcup Aug_{color}(x, s)$, and then calculate the cross-entropy loss of the union of the augmented images ($s + 1$ images) and the original image x (one image),

$$R(x, y) = \frac{\sum\limits_{x_i \in Aug(x) \bigcup \{x\}} \mathcal{L}_{ce}(x_i, y)}{s + 2} \tag{5}$$

However, optimizing the empirical risk in Eq. 5 directly can lead to two outcomes: (1) the model learns invariant features to reduce the loss and (2) the model remembers (or overfits) each augmented image's features, including irrelevant features, and outputs different representations for different augmented images to reduce the loss. To avoid (2), we force the representations of the augmented images to be near to each other (the second term in Eq. 6 below). The overall risk is turned into:

$$R(x, y) = \frac{\sum\limits_{x_i \in Aug(x) \bigcup \{x\}} \mathcal{L}_{ce}(x_i, y)}{s + 2} + \sum\limits_{x_i, x_j \in Aug(x) \bigcup \{x\}} \frac{dist(f_\theta(x_i), f_\theta(x_j))}{\frac{(s+2) \cdot (s+3)}{2}} \tag{6}$$

where x_i, x_j are images in $Aug(x) \bigcup \{x\}$ ($x_i \neq x_j$) and $dist(\cdot, \cdot)$ computes the distance between two representations. We use the cosine distance here. With the regularization of the second term, F should learn invariant features across different environments to reduce the loss in Eq. 6.

Theoretical justification: We construct an environment set $\mathbb{Z}$ and want the model to learn invariant features across different environments. However, as the number of constructed environments is limited, the model may memorize each environment and use environment-related features to reduce the loss. By optimizing the second term in Eq. 6, we force the representations of different augmented images of an original image to be very similar. Then the learner will learn little information about $\mathbb{Z}$ from the augmented images, which means $P(\mathbb{Z}|x) \approx P(\mathbb{Z})$, where $x \in Aug(x)$. Then we have

$$\hat{R}(x, y) = \sum\limits_y \sum\limits_x \sum\limits_z \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(y|x, z) P(z) P(x)$$

$$\approx \sum\limits_y \sum\limits_x \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(x, y) = \frac{\sum\limits_{x_i \in Aug(x) \bigcup \{x\}} \mathcal{L}_{ce}(x_i, y)}{s + 2} \tag{7}$$

So minimizing the risk in Eq. 6 is approximated by minimizing the ideal interventional empirical risk under the environments variable $\mathbb{Z}$. Note, the constructed $\mathbb{Z}$ is a subset of the ideal environment set Z. Increasing the diversity of samples in $\mathbb{Z}$ makes it closer to the ideal set Z.

4.2 Storing More Data for Learning More Invariant Features

Data augmentation can reduce the influence of environment partially but not completely. For example, Samoyed dog and Golden Retriever are dogs in different environments and it's hard to use the data augmentation to generate images of Samoyed dog when we only have the images of Golden Retriever. But training F with more diverse images of objects of a class makes the model find and focus on learning invariant features from the objects to form the invariant class representations. So our method also focuses on better utilizing the original data to learn invariant features across different natural environments. OCM (Guo et al., 2022) discards the new data batch D_t^{new} and uses only the buffer data batch D_t^{buf} (which also contains saved data from the new task t in the online CL setting) to calculate $\mathcal{L}_{ce}$ loss. That makes the model use less data to learn. We add D_t^{new} into our empirical risk loss as follows,

$$R(D_t^{new} \bigcup D_t^{buf}) = \sum_{x \in X_t^{buf}} \frac{R(x,y)}{N^{buf}} + \sum_{x \in X_t^{new}} \frac{R(x,y)}{N^{new}} \quad (8)$$

where N_t^{new} and N^{buf} are the batch sizes of D^{new} and D_t^{buf} respectively. Following (Ahn et al., 2021), to avoid the interference from the new data to the replayed data, for the second term in Eq. 8, we clip the logits of classes that do not appear in Y^{new} when calculating the cross-entropy loss.

Furthermore, due to the limited memory buffer size, only a small number of samples are stored. However, storing more samples makes the model learn more invariant features because more images also mean more diversity of the environments. Without increasing the memory size, we propose to store a fixed rate (storage rate) of resized images. Specifically, we use a quarter of the original memory space to store resized images. The size of a resized image is set as $r_2 \cdot d$ where r_2 is the resized rate and d is the size of the original image. When we sample data from the buffer, we resize the sampled resized images to their original size and mix them with other sampled images to construct $X_t^{buf} = \bigcup_{i=1}^{N^{buf}} resize(x_i, d)$, where x_i is an image sampled from the memory buffer. Also, training F with more diverse images helps the model learn richer features to form holistic and invariant representations.

In Appendix 1, we justify the introduction of more samples to enable F to learn better invariant feature representations and to make the risk in Eq. 8 better approximate the ideal objective in Eq. 3.

Finally, our $\mathcal{L}_{invariant}$ loss is

$$\mathcal{L}_{invariant}(D_t^{new}, D_t^{buf}) = \sum_{x \in \bigcup_{i=1}^{N^{buf}} resize(x_i, d_{ori})} \frac{R(x,y)}{N^{buf}} + \sum_{x \in X_t^{new}} \frac{R(x,y)}{N^{new}} \quad (9)$$

Then the joint optimization $\mathcal{L}_{joint}$ loss for learning task t is

$$\mathcal{L}_{joint}(D_t^{new}, D_t^{buf}) = \mathcal{L}_{OCM}(D_t^{new}, D_t^{buf}) + \mathcal{L}_{invariant}(D_t^{new}, D_t^{buf}) \quad (10)$$

where the first term learns holistic feature representations and the second term learns invariant features for each class to form its class representation.

5 Experiment Results

We evaluate the proposed IFO in two online CL scenarios. The first is the standard disjoint scenario, where F learns different tasks one after another. The other is the task boundary blurry scenario.

5.1 Disjoint Online Continual Learning Scenario

Datasets. In this scenario, we use five datasets. For the MNIST (LeCun et al., 1998) dataset, we split the original 10 classes into 5 different tasks, two classes per task. For the CIFAR10 (Krizhevsky & Hinton, 2009) dataset, we also split the original 10 classes into 5 different tasks with two classes per task. For the CIFAR100 (Krizhevsky & Hinton, 2009) dataset, we split the original 100 classes into 10 different tasks with 10 classes per task. For the TinyImagenet (Le & Yang, 2015) dataset, we split the original 200 classes into 100 different tasks with 2 classes per task for stress testing. For the ImageNet (Deng et al., 2009) dataset, we split the original 1000 classes int into 10 different tasks with 100 classes per task. Each task runs with only one epoch for online CL.

Baselines. See the 12 baselines in column 1 of Table 1. We run their official codes (Appendix 2).

Backbone, Optimizer, Buffer and Data Augmentation. We follow (Guo et al., 2022) and use ResNet-18 (not pre-trained) as the backbone for our method and baselines in the CIFAR10, CI-FAR100, TinyImageNet, and ImageNet settings. A fully-connected network with two hidden layers (400 ReLU units) is used as the backbone for MNIST. We use the Adam optimizer and set the learning rate as 1e-3 for all methods. Following (Guo et al., 2022), we set N^{new} and N^{buf} as 10 and 64 respectively for all methods and use the reservoir sampling for our method. For the buffer size B, we use $\frac{B}{4}$ to store resized images and $\frac{3B}{4}$ to store the original-sized images. As the numbers of resized images and stored original-sized images are similar, if the training iteration is an even number, we store resized images and otherwise we store original-sized images. For other baselines, only the original-sized images are stored. The whole memory size is the same for all methods. Following (Guo et al., 2022), the data augmentation methods *horizontal-flip*, *random-resized-crop* and *random-gray-scale* are applied to all methods to improve the performance (no drops). We set s in Eq. 6 as 5 and r_1 in Aug_{plus} as 0.75 and r_2 as 0.5. More details are in Appendix 2.

Table 1: Accuracy on the MNIST (5 tasks), CIFAR10 (5 tasks), CIFAR100 (10 tasks) and TinyImageNet (100 tasks) datasets with different memory buffer sizes B. All values are the averages of 15 runs. See the results on ImageNet in Figure 2(a).

Method	MNIST			CIFAR10			CIFAR100			TinyImageNet		
B	B=0.1k	B=0.5k	B=1k	B=0.2k	B=0.5k	B=1k	B=1k	B=2k	B=5k	B=2k	B=4k	B=10k
AGEM Chaudhry et al. (2018)	56.9±5.2	57.7±8.8	61.6±3.2	22.7±1.8	22.7±1.9	22.6±0.7	5.8±0.2	5.8±0.3	6.5±0.2	0.9±0.1	2.1±0.1	3.9±0.2
GSS Aljundi et al. (2019b)	70.4±1.5	80.7±5.8	87.5±5.9	26.9±1.2	30.7±1.3	40.1±1.4	11.1±0.2	13.3±0.5	17.4±0.1	3.3±0.5	10.0±0.2	10.5±0.2
ER Chaudhry et al. (2020)	78.7±0.4	88.0±0.2	90.3±0.1	29.7±1.0	35.2±0.3	44.3±0.4	11.7±0.3	15.0±0.9	14.4±0.9	5.6±0.5	10.1±0.7	11.7±0.2
MIR Aljundi et al. (2019a)	79.0±0.5	88.3±0.1	91.3±1.9	37.3±0.3	40.0±0.6	41.0±0.6	15.7±0.2	19.1±0.1	24.1±0.2	6.1±0.5	11.7±0.2	13.5±0.2
ASER Shim et al. (2021)	61.6±2.1	71.0±0.6	82.1±5.9	27.8±1.0	36.2±1.2	44.7±1.2	16.4±0.3	12.2±1.9	27.1±0.3	5.3±0.3	8.2±0.2	10.3±0.4
GDumb Prabhu et al. (2020)	81.2±0.5	91.0±0.2	94.5±0.1	35.9±1.1	50.7±0.7	63.5±0.5	14.1±0.2	20.1±0.2	36.0±0.5	12.6±0.1	12.7±0.3	15.7±0.2
SCR Mai et al. (2021)	86.2±0.5	92.8±0.3	94.6±0.1	47.2±1.7	58.2±0.5	64.1±1.2	26.5±0.2	31.6±0.5	36.5±0.2	10.6±1.1	17.2±0.1	20.4±1.1
DER++ Buzzega et al. (2020)	74.4±1.1	91.5±0.2	92.1±0.2	44.2±1.1	47.9±1.5	54.7±2.2	15.3±0.2	19.7±1.5	27.0±0.7	4.5±0.3	10.1±0.3	17.6±0.5
IL2A Zhu et al. (2021)	90.2±0.1	92.7±0.1	93.9±0.1	54.7±0.5	56.0±0.4	58.2±1.2	18.2±1.2	19.7±0.5	22.2±0.2	5.5±0.7	8.1±1.2	11.6±0.4
Co^{2}L Cha et al. (2021)	83.1±0.1	91.5±0.1	94.7±0.1	42.1±1.2	51.0±0.7	58.8±0.4	17.1±0.4	24.2±0.2	32.2±0.6	10.1±0.2	15.8±0.4	22.5±1.2
SSIL Ahn et al. (2021)	88.2±0.1	93.0±0.2	95.1±0.1	49.5±0.2	59.2±0.4	64.0±0.5	26.0±0.1	33.1±0.5	39.5±0.4	9.6±0.7	15.2±1.5	21.1±0.1
OCMGuo et al. (2022)	90.7±0.1	95.7±0.3	96.7±0.1	59.4±0.2	70.0±1.3	77.2±0.5	28.1±0.3	35.0±0.4	42.4±0.5	15.7±0.2	21.2±0.4	27.0±0.3
IFO	**92.7**±0.4	**96.1**±0.2	**97.0**±0.2	**65.0**±0.3	**73.5**±0.2	**78.5**±0.3	**38.5**±0.5	**45.5**±0.3	**49.4**±0.2	**20.5**±0.5	**27.2**±0.5	**34.6**±0.4

Accuracy results. We report the average accuracy of all seen tasks after learning of the final task in Table 1. We observe that our IFO outperforms all baselines by a large margin over the four different datasets. Our main baseline is OCM as we added the condition of invariance to its holistic representation learning. We can see that IFO is effective in boosting the performance of OCM significantly. IFO's performance is especially strong when the buffer size is small (e.g., 10 samples per class). The reason is that the baselines tend to overfit the buffer data and learn variant features when the buffer size is small. Our method mitigates this by emphasizing invariant features, which improves the generalization ability of the model. Another observation is that the improvement of our method does not decrease when the dataset becomes more complex (e.g., TinyImageNet). Because the learning of invariant features is a key advantage when the model meets more complex features.

For the hardest ImageNet dataset, due to the poor overall performance, we compare IFO with top-3 baselines (OCM, SSIL, and SCR). Figure 2(a) shows the average accuracy of all tasks seen so far after learning each task. IFO outperforms the three baselines in the whole learning process. Also, the average accuracy first arises and then drops. This is because the random-initialized model doesn't have enough features to solve the first task until the second task arrives. The later drop is due to CF.

Forgetting rate. We report the average forgetting rate Chaudhry et al. (2020) in Table 3 in Appendix 3. We observe that IFO gives less forgetting than OCM over the 4 datasets, especially on CIFAR10 and TinyImageNet. Also, IFO forgets the least except for GDumb and SCR on TinyImageNet. But the performance of the two methods are much poorer than that of IFO. For ImageNet, IFO also fares well (see Appendix 3)

Learning invariant and holistic representations. Zhu et al. (2021) observed that representations $f_\theta(x)$ with larger eigenvalues transfer better and suffer less forgetting. Guo et al. (2022) showed the number of eigenvectors with significant variances is a good indicator of holistic degree of the learned representations. We follow their experiment setting and plot the eigenvalues of the eigenvectors of the representations learned with ER, OCM and IFO from the first 50 classes of CIFAR-100 as a single supervised learning task (see Appendix 4). From Figure 4(a) in Appendix 4, we see that IFO and OCM have much more significant directions (eigenvectors) than the basic ER method (Chaudhry

Figure 2: (a) results in the disjoint setting using ImageNet. The buffer size is 10k. For (b) and (c), 'samples' of the x-axis means the number of new data samples that the model has seen and the unit is 1k. (b) results of the online i-Blurry setting using CIFAR100. The buffer size is 2k. (c) results of the online i-Blurry setting using TinyImageNet. The buffer size is 4k.

Table 2: Ablation accuracy - average of 5 runs. B is the memory buffer size.

Dataset	no Aug_{color}	no Aug_{plus}	no align	OCM+Mixup	OCM+CutMix	OCM+ClassAug	OCM+X^{new}	no new data	no resized image
CIFAR100 (B=2k)	41.8±0.4	44.0±0.6	44.6±0.2	33.2±0.5	36.3±0.3	39.5±0.4	37.4±0.5	42.0±0.2	44.0±0.6
TinyImageNet (B=2k)	18.0±0.3	19.5±0.1	20.0±0.3	14.4±0.2	16.0±0.5	17.7±0.2	23.0±0.5	18.5±0.6	19.9±0.4

et al., 2020), which shows that both IFO and OCM have learned more diverse/holistic representations. Our IFO method has a similar number of significant directions to that of OCM, but the eigenvalues of the eigenvectors of IFO and OCM are very different (see Appendix 4), which gives us an indirect evidence that IFO is able to emphasize more or less of some directions compared to OCM. Coupled with IFO's better result, we can conclude that IFO finds better features.

5.2 BLURRY ONLINE CONTINUAL LEARNING SCENARIO

In this scenario (Koh et al., 2021), the classes of the training data for a dataset is split into two parts, $N\%$ of the classes as the disjoint part and the rest of $100 - N\%$ of the classes as the blurry part. Each task consists of some disjoint classes (with all their data) and some blurry class samples. The disjoint classes of a task do not appear in any other task. The blurry classes data are sampled from the blurry part. Specifically, for a task, $100 - M\%$ of the samples are from some randomly selected dominant blurry classes (these classes will not be dominant classes in other tasks) and $M\%$ of the samples are from the other minor classes. This strategy of forming tasks is called *i-Blurry*.

We follow (Koh et al., 2021) and use the i-Blurry setup with $N = 50$ and $M = 10$ (i-Blurry-50-10) in our experiments on the CIFAR100 (5 tasks) and TinyImageNet (5 tasks) datasets. We compare their original system CLIB with our CLIB+INV (replacing CLIB's cross-entropy loss with our $\mathcal{L}_{invariant}$ loss in Eq. 9). Here we do not use the full IFO as our main contribution is the $\mathcal{L}_{invariant}$ loss and IFO has all components of OCM. Following CLIB, we use ResNet-34 and Adam optimizer with an initial learning rate of 0.0003 and CLIB's learning rate schedule for both systems. We list the details in Appendix 5. As CLIB is the only system designed for the 'i-Blurry' scenario that we are aware of (see Sec. 2), we only compare with CLIB to show that learning invariant features help.

Accuracy results Following (Koh et al., 2021), we measure any time inference and plot the accuracy-to-samples curve in Figure 2(b)&(c). The setting is as follows. After the model sees every 100 new samples, we test the model using the original test set of all classes in the CIFAR100 or TinyImageNet dataset and record the accuracy. The figures show that CLIB+INV clearly outperforms CLIB, especially after the model has seen some tasks, which indicates that effectively learning invariant class representations improves the overall generalization ability in incremental learning.

5.3 ABLATION STUDY AND ANALYSIS

Ablation study of the components in IFO. Table 2 shows the results without using Aug_{color} (no Aug_{color}), Aug_{plus} (no Aug_{plus}) or the second term of Eq. 6 (no align). The performances of these experiments drop, which shows the contribution of learning invariant features by using the proposed augmentations and loss. As IFO is basically OCM plus invariant feature learning, we also tried several other data augmentations and losses designed for better feature learning, Mixup (Zhang

Figure 3: (a) results of CIFAR100 with different s. (b) results of CIFAR100 with different storage rate. (c) results of CIFAR100 with different resize rates r_1 and r_2. We set B as 2k for all experiments. We put the experiments on TinyImageNet in Appendix 6 and the best parameters are the same.

et al., 2017) (OCM+Mixup), Cutmix Yun et al. (2019) (OCM+CutMix) and ClassAug (Zhu et al., 2021) (OCM+ClassAug). CutMix and ClassAug improve the performance of OCM but Mixup does not. However, the improvements of these augmentations and their losses are poorer than that of IFO. In the "OCM+X^{new}" experiment, we add the $\mathcal{L}_{ce}$ loss of the new data batch into OCM. The performance improves slightly as the model learns more invariant features from more data. In the "no new data" experiment, only D_t^{buf} in Eq. 9 is used. For the "no resized image" experiment, we do not store resized images. The performances of both experiments drop, which means that considering more training samples to learn invariant features is useful.

Influence of the hyperparameters in IFO. For s in Eq. 6, from Figure 3(a), we observe that the performance has a positive correlation with the number s as the model gradually focuses on invariant features rather than strongly depending on simple colors. We set s to 5 as it achieves the best performance with less compute. For the storage rate for resized images, we need to find a balance between storing more samples and avoiding huge information loss caused by the resizing operation. From Figure 3(b), we found that using a quarter of the memory space to store resized images achieves a good balance. For rate r_1 in the augmentation Aug_{plus}, we need to avoid introducing trivial features (r_1 is too high) and causing a huge information loss in the original image (r_1 is too low). For rate r_2 in Sec. 4.2, we have the same balancing issue with the storage rate (more saved samples vs information loss). Based on Figure 3(c), we set r_1 as 0.75 and r_2 as 0.5.

Influence of learning invariant features for continual learning (CL). To further investigate how learning invariant features helps the performance of CL methods, we measure three abilities of OCM and IFO: (1) the ability to establish decision boundaries between the classes within a new task by recording the accuracy performance of the new task. From Figure 6(a) in Appendix 7, we see that IFO's accuracy of the new task outperforms that of OCM as learning invariant class-related features makes the model improve its generalization power. (2) the ability to maintain the learned decision boundaries within a task by calculating the average task incremental accuracy of the previous tasks. Our method again outperforms OCM (Figure 6(b)) as IFO mitigates the overfitting problem of the limited buffer data. (3) the ability to establish class boundaries for across tasks. We measure this by considering only the logit of the true label of each test instance in a task and the logits of the classes from the other tasks when the model predicts the label of the test instance. IFO's performance is still better than that of OCM (Figure 6(c)) as our method reduces the variant features, which enables the model to project those class representations to different locations in the space, making the decision boundaries easier to establish. Also, from Figure 6, we can clearly see that improving the last ability is the biggest challenge for online CL. More details are given in Appendix 7.

6 CONCLUSION

Despite the fact that numerous techniques have been proposed to solve the class-incremental learning (CIL) problem, limited work has been done to study the necessary conditions for good CIL performance. Recent work in (Guo et al., 2022) proposes that it is neccesary to learn *holistic feature representations*, which improved the online CIL performance significantly. This paper further argued that it is also necessary to learn *invariant features* for each class, and proposed several methods to help learn invariant features in addition to learning holistic representations. Experimental results showed that the new condition gave another boost to the online CIL performance.

REFERENCES

Davide Abati, Jakub Tomczak, Tijmen Blankevoort, Simone Calderara, Rita Cucchiara, and Babak Ehteshami Bejnordi. Conditional channel gated networks for task-aware continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3931–3940, 2020.

Hongjoon Ahn, Sungmin Cha, Donggyu Lee, and Taesup Moon. Uncertainty-based continual learning with adaptive regularization. In *NeurIPS*, 2019.

Hongjoon Ahn, Jihwan Kwak, Subin Lim, Hyeonsu Bang, Hyojun Kim, and Taesup Moon. Ss-il: Separated softmax for incremental learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 844–853, 2021.

Rahaf Aljundi, Lucas Caccia, Eugene Belilovsky, Massimo Caccia, Min Lin, Laurent Charlin, and Tinne Tuytelaars. Online continual learning with maximally interfered retrieval. *arXiv preprint arXiv:1908.04742*, 2019a.

Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning. *Advances in neural information processing systems*, 32, 2019b.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Jihwan Bang, Heesu Kim, YoungJoon Yoo, Jung-Woo Ha, and Jonghyun Choi. Rainbow memory: Continual learning with a memory of diverse samples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8218–8227, 2021.

Jihwan Bang, Hyunseo Koh, Seulki Park, Hwanjun Song, Jung-Woo Ha, and Jonghyun Choi. Online continual learning on a contaminated data stream with blurry task boundaries. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9275–9284, 2022.

Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline. *arXiv preprint arXiv:2004.07211*, 2020.

Hyuntak Cha, Jaeho Lee, and Jinwoo Shin. Co2l: Contrastive continual learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9516–9525, 2021.

Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem. *arXiv preprint arXiv:1812.00420*, 2018.

Arslan Chaudhry, Naeemullah Khan, Puneet K Dokania, and Philip HS Torr. Continual learning in low-rank orthogonal subspaces. *arXiv preprint arXiv:2010.11635*, 2020.

Ekin D Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V Le. Autoaugment: Learning augmentation strategies from data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 113–123, 2019.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673, 2020.

Yiduo Guo, Bing Liu, and Dongyan Zhao. Online continual learning through mutual information maximization. In *International Conference on Machine Learning*, pp. 8109–8126. PMLR, 2022.

Saihui Hou, Xinyu Pan, Chen Change Loy, Zilei Wang, and Dahua Lin. Learning a unified classifier incrementally via rebalancing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 831–839, 2019.

Wenpeng Hu, Zhou Lin, Bing Liu, Chongyang Tao, Zhengwei Tao, Jinwen Ma, Dongyan Zhao, and Rui Yan. Overcoming catastrophic forgetting for continual learning via model adaptation. In *ICLR*, 2019.

Steven C. Y. Hung, Cheng-Hao Tu, Cheng-En Wu, Chien-Hung Chen, Yi-Ming Chan, and Chu-Song Chen. Compacting, picking and growing for unforgetting continual learning. In *NeurIPS*, 2019.

Yonghan Jung, Jin Tian, and Elias Bareinboim. Learning causal effects via weighted empirical risk minimization. *Advances in neural information processing systems*, 33:12697–12709, 2020.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, and Others. Overcoming catastrophic forgetting in neural networks. volume 114, pp. 3521–3526. National Acad Sciences, 2017.

Hyunseo Koh, Dahyun Kim, Jung-Woo Ha, and Jonghyun Choi. Online continual learning on class incremental blurry task configuration with anytime inference. *arXiv preprint arXiv:2110.10031*, 2021.

Łukasz Korycki and Bartosz Krawczyk. Class-incremental experience replay for continual learning under concept drift. *arXiv preprint arXiv:2104.11861*, 2021.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. *Technical Report TR-2009, University of Toronto, Toronto.*, 2009.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. *CS 231N*, 7:7, 2015.

Yann LeCun, Corinna Cortes, and Christopher JC Burges. The mnist database of handwritten digits. *http://yann.lecun.com/exdb/mnist/*, 1998.

Xilai Li, Yingbo Zhou, Tianfu Wu, Richard Socher, and Caiming Xiong. Learn to grow: A continual structure learning framework for overcoming catastrophic forgetting. In *ICML*, 2019.

Zheda Mai, Ruiwen Li, Hyunwoo Kim, and Scott Sanner. Supervised contrastive replay: Revisiting the nearest class mean classifier in online class-incremental continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, pp. 3589–3599, 2021.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning & motiv.*, volume 24. 1989.

Oleksiy Ostapenko, Mihai Puscas, Tassilo Klein, Patrick Jahnichen, and Moin Nabi. Learning to remember: A synaptic plasticity driven framework for continual learning. In *CVPR*, pp. 11321–11329, 2019.

Ben Poole, Sherjil Ozair, Aaron Van Den Oord, Alex Alemi, and George Tucker. On variational bounds of mutual information. In *International Conference on Machine Learning*, pp. 5171–5180. PMLR, 2019.

Ameya Prabhu, Philip HS Torr, and Puneet K Dokania. Gdumb: A simple approach that questions our progress in continual learning. In *EECV*, pp. 524–540, 2020.

Jathushan Rajasegaran, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Mubarak Shah. itaml: An incremental task-agnostic meta-learning approach. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13588–13597, 2020.

Alexandre Rame, Corentin Dancette, and Matthieu Cord. Fishr: Invariant gradient variances for out-of-distribution generalization. In *International Conference on Machine Learning*, pp. 18347–18377. PMLR, 2022.

Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H Lampert. icarl: Incremental classifier and representation learning. In *CVPR*, pp. 2001–2010, 2017.

Hippolyt Ritter, Aleksandar Botev, and David Barber. Online structured laplace approximations for overcoming catastrophic forgetting. In *NIPS*, pp. 3738–3748, 2018.

Gobinda Saha, Isha Garg, and Kaushik Roy. Gradient projection memory for continual learning. *arXiv preprint arXiv:2103.09762*, 2021.

Joan Serrà, Dídac Surís, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *ICML*, 2018.

Dongsub Shim, Zheda Mai, Jihwan Jeong, Scott Sanner, Hyunwoo Kim, and Jongseong Jang. Online class-incremental continual learning with adversarial shapley value. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 9630–9638, 2021.

Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In *NIPS*, pp. 2994–3003, 2017.

Ghada Sokar, Decebal Constantin Mocanu, and Mykola Pechenizkiy. Learning invariant representation for continual learning. *arXiv preprint arXiv:2101.06162*, 2021.

Johannes von Oswald, Christian Henning, João Sacramento, and Benjamin F Grewe. Continual learning with hypernetworks. *ICLR*, 2020.

Jianren Wang, Xin Wang, Yue Shang-Guan, and Abhinav Gupta. Wanderlust: Online continual object detection in the real world. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10829–10838, 2021.

Liyuan Wang, Xingxing Zhang, Kuo Yang, Longhui Yu, Chongxuan Li, Lanqing Hong, Shifeng Zhang, Zhenguo Li, Yi Zhong, and Jun Zhu. Memory replay with data compression for continual learning. In *ICLR-2022*, 2022a.

Tan Wang, Qianru Sun, Sugiri Pranata, Karlekar Jayashree, and Hanwang Zhang. Equivariance and invariance inductive bias for learning from insufficient data. *arXiv preprint arXiv:2207.12258*, 2022b.

Yufei Wang, Haoliang Li, and Alex C Kot. Heterogeneous domain generalization via domain mixup. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3622–3626. IEEE, 2020.

Mitchell Wortsman, Vivek Ramanujan, Rosanne Liu, Aniruddha Kembhavi, Mohammad Rastegari, Jason Yosinski, and Ali Farhadi. Supermasks in superposition. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *NeurIPS*, 2020.

Yuan Wu, Diana Inkpen, and Ahmed El-Roby. Dual mixup regularized learning for adversarial domain adaptation. In *European Conference on Computer Vision*, pp. 540–555. Springer, 2020.

Yue Wu, Yinpeng Chen, Lijuan Wang, Yuancheng Ye, Zicheng Liu, Yandong Guo, and Yun Fu. Large scale incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 374–382, 2019.

Shipeng Yan, Jiale Zhou, Jiangwei Xie, Songyang Zhang, and Xuming He. An em framework for online incremental learning of semantic segmentation. In *Proceedings of the 29th ACM International Conference on Multimedia*, pp. 3052–3060, 2021.

Fu-En Yang, Yuan-Chia Cheng, Zu-Yun Shiau, and Yu-Chiang Frank Wang. Adversarial teacher-student representation learning for domain generalization. *Advances in Neural Information Processing Systems*, 34:19448–19460, 2021.

Haiyan Yin, Ping Li, et al. Mitigating forgetting in online continual learning with neuron calibration. *Advances in Neural Information Processing Systems*, 34, 2021.

Lu Yu, Bartlomiej Twardowski, Xialei Liu, Luis Herranz, Kai Wang, Yongmei Cheng, Shangling Jui, and Joost van de Weijer. Semantic drift compensation for class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6982–6991, 2020.

Xiangyu Yue, Yang Zhang, Sicheng Zhao, Alberto Sangiovanni-Vincentelli, Kurt Keutzer, and Bo-qing Gong. Domain randomization and pyramid consistency: Simulation-to-real generalization without accessing target domain data. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 2100–2110, 2019.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 6023–6032, 2019.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

Junting Zhang, Jie Zhang, Shalin Ghosh, Dawei Li, Serafettin Tasci, Larry Heck, Heming Zhang, and C.-C. Jay Kuo. Class-incremental learning via deep model consolidation. In *CVPR*, 2020.

Hanbin Zhao, Hui Wang, Yongjian Fu, Fei Wu, and Xi Li. Memory efficient class-incremental learning for image classification. *IEEE Transactions on Neural Networks and Learning Systems*, 2021.

Fei Zhu, Zhen Cheng, Xu-Yao Zhang, and Cheng-lin Liu. Class-incremental learning via dual augmentation. *Advances in Neural Information Processing Systems*, 34:14306–14318, 2021.

A APPENDIX

A.1 *Theoretical justification* FOR SECTION 4.2

In the ideal case (data is sufficient and highly diverse), X can be observed in any environment z. That leads to $P(Z|X) \approx P(Z)$ (the independence of Z and X) and we have

$$\hat{R}(D_t^{new}) = \sum_{y \in Y_t^{new}} \sum_{x \in X_t^{new}} \sum_z \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(y|x, z) P(z) P(x)$$
$$\approx \sum_{y \in Y_t^{new}} \sum_{x \in X_t^{new}} \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(y, x) \tag{11}$$

where $\sum_y \sum_x \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(y, x)$ is the traditional cross-entropy loss. We also have $\hat{R}(X_t^{buf}, Y_t^{buf}) = \sum_{y \in Y_t^{buf}} \sum_{x \in X_t^{buf}} \mathcal{L}_{ce}(\sigma_\phi(f_\theta(x), y)) P(y, x)$. So adding X^{new} and resizing and storing more buffer data to construct X^{buf} makes the model have more samples from different environments to train. And that makes the risk in Eq. 8 better approximated to the ideal objective in Eq. 3.

A.2 THE DETAILS OF DISJOINT ONLINE CONTINUAL LEARNING SCENARIO

Due to the limitation of computational resources, we download the downsampled version of ImageNet ($3 \times 32 \times 32$) from the official website and conduct experiments on this dataset. We don't use the Aug_{color} in the MNIST setting. We set the alpha and the beta of the beta distribution in Aug_{color} as 1.

For AGEM, following the original paper, we use the SGD optimizer and set the learning rate as 0.1. We use the random method to update the buffer and to sample data.

For GSS, based on the original paper, we use the same optimizer and learning rate as above. The number of buffer batches randomly sampled from the memory to estimate the maximal gradients cosine similarity score is set to 10 and the randomly sampled buffer batch (X^{buffer}) size for calculating the score is 64.

For ASER, we use the mean value of Adversarial SV and Cooperative SV, and set the maximum number of samples per class for random sampling as 1.5. We allow 3 nearest neighbors for KNN-SV computation. We use the same SV-based methods for both Memory-Update and Memory-Retrieval as given in the original paper.

For MIR/ER, we use the Adam optimizer and we set the learning rate as 0.001 and fix the weight decay as 0.0001. We set the sub-sample size as 128.

For DER++, we use the Adam optimizer, set the learning rate as 0.001, fix the weight decay as 0.0001 and the value of alpha (α) as 0.1, and fix the beta (β) as 0.5.

For GDumb, we use the Adam optimizer, set the learning rate as 0.001 and fix the weight decay as 0.0001. We use the CutMix as the regularization to overcome over-fitting. we follow the official code and set the number of epochs for training the whole buffer data as 256 for MINIST, CIFAR10, and CIFAR100 datasets, and 32 for the TinyImagenet dataset. We set the gradient clip as 10.

For SCR, we use the Adam optimizer, set the learning rate as 0.001 and fix the weight decay as 0.0001. We set the temperature for contrastive loss as 0.07. We employ a linear layer with the size $[dim_h, 128]$ as the contrastive head. We follow the official code and use the horizontal-flip, random-resized crop, random-gray-scale,color-jitter as its data augmentations.

The official code of these systems can be found from the following locations.

The code of ER and MIR: `https://github.com/optimass/Maximally_Interfered_Retrieval`.
The code of ASER and SCR: `https://github.com/RaptorMai/online-continual-learning`.
The code of GDumb: `https://github.com/drimpossible/GDumb`.
The code of DER++: `https://github.com/aimagelab/mammoth`.
The code for AGEM: `https://github.com/facebookresearch/agem`.
The code for GSS: `https://github.com/rahafaljundi/Gradient-based-Sample-Selection`.
The code for Co^{2}L: `https://github.com/chaht01/Co2L`.
The code for IL2A: `https://github.com/Impression2805/IL2A`.
The code for SSIL: `https://github.com/hongjoon0805/SS-IL-Official`.
The code for OCM: `https://github.com/gydpku/OCM`.

A.3 THE FORGETTING RATE TABLE

Table 3: Average forgetting rate. All numbers are the averages of 15 runs. See the forgetting rates for the ImageNet dataset in the text below.

Method	MNIST			CIFAR10			CIFAR100			TinyImageNet		
B	B=0.1k	B=0.5k	B=1k	B=0.2k	B=0.5k	B=1k	B=1k	B=2k	B=5k	B=2k	B=4k	B=10k
AGEM Chaudhry et al. (2018)	32.5±5.9	30.1±4.2	32.0±2.9	36.1±3.8	43.2±4.3	48.1±3.4	43.3±0.2	45.7±0.3	43.9±0.2	73.9±0.2	78.9±0.2	74.1±0.3
GSS Aljundi et al. (2019b)	26.1±2.2	17.8±5.22	10.5±6.7	75.5±1.5	65.9±1.6	54.9±2.0	30.8±0.2	30.7±0.5	26.4±0.3	72.8±1.2	72.6±0.4	71.5±0.2
ER Chaudhry et al. (2020)	22.7±0.5	9.7±0.4	6.7±0.5	42.0±0.3	26.7±0.7	20.7±0.7	34.2±0.2	31.7±0.9	35.3±0.9	68.2±2.8	66.2±0.8	67.2±0.2
MIR Aljundi et al. (2019a)	22.3±0.5	9.0±0.5	5.7±0.9	40.0±1.6	25.9±0.7	24.5±0.5	24.5±0.3	21.4±0.3	21.0±0.1	61.1±3.2	60.9±0.3	59.5±0.3
ASER Shim et al. (2021)	33.8±1.1	24.8±0.5	13.8±0.4	71.1±1.8	59.1±1.5	50.4±1.5	25.0±0.2	12.2±1.9	13.2±0.1	65.7±0.7	64.2±0.2	62.2±0.1
GDumb Prabhu et al. (2020)	10.3±0.1	6.2±0.1	4.8±0.2	26.5±0.5	24.5±0.2	18.9±0.4	16.7±0.5	17.6±0.2	16.8±0.4	15.9±0.5	14.6±0.3	11.7±0.2
SCR Mai et al. (2021)	10.7±0.1	4.7±0.1	4.0±0.2	41.3±0.1	31.5±0.2	24.7±0.4	17.5±0.2	11.6±0.5	5.6±0.4	19.4±0.3	15.4±0.3	14.9±0.7
DER++ Buzzega et al. (2020)	25.0±0.3	7.3±0.3	6.6±1.2	30.1±0.8	31.8±2.5	18.7±3.4	43.4±0.2	44.0±1.9	25.8±3.5	67.2±1.7	63.6±0.3	55.2±0.7
IL2A Zhu et al. (2021)	8.7±0.1	7.2±0.1	4.1±0.1	36.0±0.2	32.1±0.4	29.1±0.4	24.6±0.6	12.5±0.7	20.0±0.5	65.5±0.7	60.1±0.5	57.6±1.1
Co^{2}L Cha et al. (2021)	14.7±0.2	7.1±0.1	3.1±0.1	32.0±0.1	21.0±0.3	16.9±0.2	16.9±0.4	16.6±0.6	9.9±0.7	60.5±0.5	52.5±0.9	42.5±0.8
SSIL Ahn et al. (2021)	11.3±0.1	2.7±0.1	2.8±0.1	36.0±0.7	29.6±0.4	13.5±0.4	40.1±0.5	33.9±1.2	21.7±0.8	44.4±0.7	36.6±0.7	29.0±0.7
OCM Guo et al. (2022)	4.7±0.1	1.8±0.1	1.3±0.1	23.0±0.2	14.0±0.7	12.0±1.1	12.2±0.3	8.5±0.3	4.5±0.3	23.5±1.9	21.0±0.3	18.6±0.5
IFO	4.2±0.1	1.0±0.2	1.1±0.1	16.3±0.3	8.1±0.1	2.0±0.7	11.9±0.5	8.3±0.4	4.3±0.2	22.5±0.3	18.6±0.5	13.5±0.8

From this forgetting table (Table 3), we observe an obvious drop in forgetting rate from OCM to IFO (our method). That means our method forgets less. In the ImageNet setting, the forgetting rates for the four top methods are: 11.47 (SCR), 12.1 (SSIL), 11.7 (OCM) and 10.9 (IFO). Our method suffers less forgetting.

A.4 THE RATE BETWEEN THE EIGENVALUE DISTRIBUTION OF IFO AND OCM

From Figure 4(a)&(b), we see that the main difference of the eigenvalue distributions of OCM and IFO is the different eigenvalues they learned in the first 15 eigenvectors. That means that the representation quality not only depends on the diversity of eigenvectors (holistic), but also on the different emphases (different eigenvalues) on the features for class representations.

Figure 4: In (a), we plot the Eigenvalue distribution of the learned representations by ER, OCM, and IFO using the CIFAR100 dataset.

A.5 MORE DETAILS OF I-BLURRY ONLINE CONTINUAL LEARNING SCENARIO

Following (Koh et al., 2021), we use the batch size of 16 and 3 updates per streamed sample for CIFAR100 and the batch size of 32 and 3 updates per streamed sample for TinyImageNet, and employ ResNet-34 for CIFAR100 and TinyImageNet. In the CIFAR100 setting, each task has 10 unique disjoint classes and 10 dominant blurry classes exclusively. The selection process of classes for each task is random. In the TinyImageNet setting, each task has 20 unique disjoint classes and 20 dominant blurry classes exclusively. AutoAugment (Cubuk et al., 2019) and CutMix (Yun et al., 2019) are also used as the data augmentations as in CLIB and CLIB+IFO. We use the same adaptive learning rate schedule (Koh et al., 2021) with $\gamma = 0.95$ and $m = 10$ for the two datasets. We use their official code `https://github.com/naver-ai/i-Blurry` to run the experiments.

A.6 ABLATION ANALYSIS IN THE TINYIMAGENET SETTING

Figure 5: (a) results of TinyImageNet with different s'. (b) results of TinyImageNet with different storage rates. (c) results of TinyImageNet with different resize rates r_1 and r_2. We set B as 2k for all experiments.

From Figure 5, we set s as 5 as it achieves the best performance with less compute. Also, we set the storage rate as 0.25 and r_1 as 0.75 and r_2 as 0.5.

A.7 ANALYSIS OF THE INFLUENCE OF LEARNING INVARIANT FEATURES

Figure 6: (a) the performance of learning new task. (b) the performance of maintaining learned decision boundaries. (c) the performance of establishing decision boundary between new classes and previous classes.

We conduct experiments on the CIFAR100 dataset (10 tasks) and the buffer size of 2k. From Figure 6, we observe that the performance of the first two abilities of OCM and IFO are non-decreasing and bigger than 70 at the end. But the performance of the last ability is decreasing and is smaller than 50 at the end (OCM (35.8) and IFO (46.36)). Also, we find that the average accuracy of OCM and IFO are 35.0 and 45.5 respectively in the Table 1. That means the main limitation of the performance of the current model is in establishing boundaries between classes from different tasks.