Mitigating Context-Agnostic Bias in Reward Models for Stable LLM Alignment via Auxiliary Model Calibration

Abstract

Reward models (RMs) serve as the cornerstone of reinforcement learning from human feedback (RLHF) for aligning large language models (LLMs) with human preferences. However, standard RM training pipelines are vulnerable to context-agnostic bias: they over-rely on the response text while neglecting the conditioning context (e.g., instruction, prompt, or dialogue state) needed for faithful quality assessment. To address this issue, we propose **Co**ntext-aware **R**eward **M**odeling (**CoRM**), a two-stage method that explicitly identifies and corrects context-agnostic bias in reward modeling. First, CoRM trains a response-only auxiliary model to estimate the context-agnostic component of the reward signal. Then, it calibrates the base RM against this auxiliary estimate, increasing the RM's sensitivity to context and mitigating reliance on context-agnostic shortcuts. Evaluated on widely used datasets, CoRM consistently improves RM performance by reducing context-agnostic bias and promoting closer alignment with human preferences. We argue that CoRM offers a simple and general mechanism for stabilizing RLHF by explicitly debiasing reward models and enhancing context awareness in reward assignment.

1 Introduction

Achieving robust and reliable alignment of large language models (LLMs) with human values and intentions is a central goal in the development of safe and trustworthy artificial intelligence. Among various alignment techniques, Reinforcement Learning from Human Feedback (RLHF) has emerged as a cornerstone method for fine-tuning LLM behaviors to better match human preferences (Ouyang et al., 2022; Bai et al., 2022a). In RLHF, the reward model (RM) evaluates the quality of candidate responses based on the provided context, and its output serves as a reward signal to optimize the policy model (Achiam et al., 2023; Zhong et al., 2025; Chen et al., 2025). The effectiveness of the RM directly determines the quality of the aligned policy and is thus essential for robust and reliable LLM alignment.

Most existing reward models are trained by concatenating the context and response, and then optimizing the RM to assign higher scores to preferred responses over less desirable ones (Pan et al., 2022; Devidze, 2025). However, this widely-adopted training paradigm introduces a critical limitation: the reward model is prone to learning context-agnostic biases present in the dataset, where it tends to over-rely on the response itself while neglecting crucial contextual information (Dou et al., 2025).

As illustrated on the left of Figure 1, this results in typical shortcut learning behavior: the reward model can select the preferred response correctly even when the context is removed, simply by exploiting superficial features such as response length or generic phrasing. For example, the response "The debate highlighted pros and cons of policy X." is favored over "Democracy is good." not due to context relevance, but because the former matches structural preferences learned from data, **e.g.,** a context-agnostic shortcut. Such shortcuts allow the RM to achieve high training accuracy without genuine context understanding, leading to spurious correlations and undermining its ability to generalize across diverse scenarios. In contrast, on the right ("Simple Data"), the RM can trivially identify the correct response (e.g., "Refrigerate perishable food." for food safety) commonsense knowledge, without requiring nuanced context.

While not inherently harmful, such cases fail to test the RM's context sensitivity and thus cannot expose or correct shortcut reliance. These shortcuts lead the model to ignore context and rely on spurious response patterns, producing shortcut learning. This undermines faithful reward assignment, weakens generalization, and ultimately reduces the effectiveness of RLHF alignment.

Figure 1: An illustration of context-agnostic shortcut learning in Reward Models. The figure presents two scenarios where an RM can correctly judge a response pair without its original context.

To mitigate this challenge, we propose Context-aware Reward Modeling (CoRM), a novel two-stage calibration framework designed to explicitly identify and correct context-agnostic shortcuts in reward modeling. In the first stage, CoRM trains a response-only auxiliary model, purposefully ignoring the context and thus capturing the extent to which rewards can be assigned based solely on response-level features. This auxiliary reward model effectively quantifies the context-agnostic bias present in the reward signal. In the second stage, CoRM calibrates the main reward model by leveraging the outputs of the auxiliary model: for each context-response pair, the main RM's reliance on context is assessed relative to the bias-only model's prediction. If both models yield similar scores, it signals that the main RM is not leveraging the contextual information and may be overfitting to superficial patterns. By integrating this auxiliary calibration signal, either through data selection, loss reweighting, or direct score adjustment, CoRM encourages the RM to attend to contextual cues and reduces reliance on context-agnostic shortcuts.

We evaluate CoRM on widely-used datasets, e.g., the Anthropic's HH-RLHF corpus (Bai et al., 2022a) and the SkyWork (Liu et al., 2024). Empirically, CoRM substantially improves reward-model performance and robustness, consistently reducing context-agnostic bias and yielding more faithful alignment to human preferences. Moreover, in iterative RLHF pipelines, where RMs are used for multi-round rejection sampling and policy optimization, CoRM delivers more stable and more generalizable alignment outcomes. In summary, our contributions are:

- We identify and analyze the prevalence of context-agnostic shortcut learning in reward modeling for RLHF.

- We introduce CoRM, a two-stage calibration framework that explicitly quantifies and mitigates context-agnostic bias via a response-only auxiliary model.

- Extensive experiments show that CoRM improves context sensitivity, OOD generalization, and alignment stability across both standard and iterative RLHF settings.

2 Related Work

RLHF and Reward Modeling The alignment of large language models (LLMs) with human preferences has been predominantly achieved through Reinforcement Learning from Human Feedback (RLHF) (Askell et al., 2021; Bai et al., 2022a; Christiano et al., 2017; Ouyang et al., 2022; Stiennon et al., 2020). Central to this paradigm is a reward model (RM), trained on human preference pairs, which serves as a surrogate for human judgment. The RM either guides policy optimization through online reinforcement learning algorithms such as PPO (Schulman et al., 2017) and GRPO (Shao et al., 2024), or directly informs offline objectives such as Direct Preference Optimization (DPO) (Rafailov et al., 2023) and its variants (e.g., IPO (Azar et al., 2024), KTO (Ethayarajh et al., 2024), ORPO (Hong et al., 2024), SimPO (Meng et al., 2024)). Despite these advances, the effectiveness of RLHF is critically dependent on the fidelity of the RM. Recent work

highlights that RMs are vulnerable to "reward hacking," often rewarding superficial heuristics over genuine alignment with user intent (Dou et al., 2025). Empirical analyses have shown that RMs tend to overvalue verbose outputs (Singhal et al., 2023), list-like formatting (Zhang et al., 2024), or sycophantic responses (Denison et al., 2024), indicating a lack of sensitivity to contextual nuances.

Data Bias and Debiasing The tendency of models to exploit spurious correlations in biased data is a long-standing challenge in machine learning (Clark et al., 2019). Similar phenomena have been documented in Natural Language Inference (hypothesis-only bias) (Belinkov et al., 2019) and Visual Question Answering (unimodal shortcuts) (Cadene et al., 2019). We identify an analogous failure mode in preference datasets, where RMs may develop context-agnostic biases. To counter such biases, existing work has approached the issue from various perspectives. On the model side, ensemble-based RMs (Coste et al., 2023; Eisenstein et al., 2023; Ramé et al., 2024), calibration methods (Zhao et al., 2023), and architectures like ODIN (Chen et al., 2024) seek to mitigate reward hacking. From the policy perspective, strategies include penalizing spurious correlations (e.g., length control (Park et al., 2024)), applying causal adjustments (Wang et al., 2025; Srivastava et al., 2025), or incorporating regularization via tailored objectives (Karimi Mahabadi et al., 2020; Kim et al., 2019). Complementary to these, data-centric methods refine the preference signal itself, such as through iterative re-labeling (Bai et al., 2022b), enforcing cross-prompt consistency (Shen et al., 2023), or augmenting training data with synthetic examples (Pace et al., 2024; Shen et al., 2024).

Building on this line of work, our study highlights a distinct form of bias in reward modeling—an over-reliance on the response itself while neglecting the surrounding context. While prior approaches improve reward fidelity through model ensembles, policy regularization, or data augmentation, they often fall short of explicitly disentangling such context-agnostic shortcuts. Our work takes a step in this direction by exploring how reward models can be systematically calibrated to better account for context in preference modeling.

3 Method

In this section we present **CoRM** (Context-aware Reward Modeling), a self-improving framework that diagnoses and corrects context-agnostic shortcuts in reward modeling. CoRM first decomposes the reward signal into context-dependent and response-only components, then calibrates reward assignment using the response-only signal to discourage shortcut use. This end-to-end procedure strengthens context sensitivity and yields more reliable supervision for downstream alignment. The architecture of the CoRM training framework is illustrated in Figure 2.

3.1 Reward Signal Decomposition

We treat the observed preference signal as a mixture of two parts: a context-dependent reward and a context-independent bias. Given a standard preference dataset $D = \{(x, y_c, y_r)_i\}_{i=1}^{N}$, we train two reward models to isolate these components.

Main Reward Model (r_{main}) The primary model $r_{\text{main}}(x, y; \theta)$ receives the full (prompt, response) pair and is trained with a standard pairwise objective:

$$L_{\text{main}}(\theta) = -\mathbb{E}_{(x,y_c,y_r)\sim D}[\log(\sigma(\Delta_{\text{main}}(x, y_c, y_r, \theta)))],$$
(1)

where $\Delta_{\text{main}}(x, y_c, y_r, \theta) = r_{\text{main}}(x, y_c; \theta) - r_{\text{main}}(x, y_r; \theta)$. Because it sees both x and y, r_{main} may entangle genuine contextual cues with superficial response patterns.

Bias Reward Model (r_{bias}) To capture response-only regularities explicitly, we train the second model $r_{\text{bias}}(y; \phi)$ on the same pairs but *without* the context x:

$$L_{\text{bias}}(\phi) = -\mathbb{E}_{(\cdot,y_c,y_r)\sim D}[\log(\sigma(\Delta_{\text{bias}}(y_c, y_r, \phi)))], \quad (2)$$

where $\Delta_{\text{bias}}(y_c, y_r, \phi) = r_{\text{bias}}(y_c; \phi) - r_{\text{bias}}(y_r; \phi)$. By design, r_{bias} learns the stylistic and structural artifacts in y that correlate with preference, providing an explicit model of context-agnostic shortcuts.

3.2 Calibration via Auxiliary Signal

The core idea of CoRM is to use the auxiliary, context-blind reward model to calibrate the main reward model. We hypothesize that the degree to which r_{main} depends on the prompt for a given judgment can be read from its discrepancy with the context-agnostic score r_{bias}. A large discrepancy indicates strong prompt dependence; a small one suggests reliance on response-only shortcuts. We this as a *Context-reliance Score*:

$$s_{\text{context}}(x, y) = |r_{\text{main}}(x, y; \theta) - r_{\text{bias}}(y; \phi)|. \quad (3)$$

Figure 2: An overview of the Context-aware Reward Modeling (CoRM) framework. The framework operates in an iterative loop. (1) **Generating:** The current policy π_t generates a set of candidate responses. (2) **Data Calibration:** Our two reward models, r_{main} (trained on full data) and r_{bias} (trained on response-only data), are used to calculate a calibrated score for each candidate. This score filters out and reweights responses that exhibit low context-sensitivity. (3) **Supervised Fine-Tuning:** The best-ranked responses form a new target set D_t, which is used to fine-tune the policy, producing the improved model π_{t+1}. This new policy then serves as the generator for the next iteration.

This score serves as the auxiliary calibration signal used in our iterative RLHF pipeline: plugged into the weighting rule in Eq. 4, it produces the calibrated score in Eq. 5 for rejection sampling, thereby favoring candidates whose rewards demonstrably depend on the context.

3.3 Application: Calibrated Rejection Sampling in Iterative RLHF

In iterative RLHF, the reward model (RM) ranks candidate responses from the current policy and a filtered subset is used for policy improvement. Scoring with r_{main} alone can admit candidates that exploit response-only shortcuts, leading to context-insensitive supervision.

CoRM addresses this with *Calibrated Rejection Sampling*. Rather than ranking candidates by the raw r_{main} score, we reweight it using a context-reliance metric, yielding a calibrated score. This reweighting prioritizes responses that demonstrably use the prompt and down-weights or discards those whose high scores arise from context-agnostic shortcuts, ensuring that only contextually grounded candidates enter the final selection.

Specifically, we introduce a confidence-based weight $W(s_{\text{context}}(x, y))$ that applies a hard filter at a threshold τ and otherwise scales by a monotone

transform $f(\cdot)$:

$$W(s_{\text{context}}(x,y)) = \begin{cases} 0, & s_{\text{context}}(x,y) < \tau, \\ f(s_{\text{context}}(x,y)), & s_{\text{context}}(x,y) \geq \tau, \end{cases} \quad (4)$$

where $f : [0, \infty) \to [0, 1]$ is increasing, so higher context-reliance yields larger weights. The calibrated score used for rejection sampling is then

$$r_{\text{CoRM}}(x,y) = r_{\text{main}}(x,y;\theta) \cdot W(s_{\text{context}}(x,y)). \quad (5)$$

This construction preserves high scores only when they are supported by sufficient prompt use ($s_{\text{context}} \geq \tau$), and attenuates or nullifies scores driven by context-agnostic shortcuts.

As detailed in Algorithm 1, we apply CoRM iteratively within the RLHF loop to progressively refine the policy. The calibrated score r_{CoRM} serves as an explicit debiasing control at each step: the hard threshold τ acts as a high-precision gate, immediately setting the reward of candidates whose r_{main} is likely driven by context-agnostic cues to zero. For the remaining candidates that pass this gate, the monotone weight $f(\cdot)$ provides soft prioritization by degree of context reliance, raising the rank (or acceptance probability) of responses where the prompt materially affects the score. This hard–soft combination shifts the curated data toward prompt-aware examples and stabilizes improvement across iterations.

Together, the hard filter and soft weighting yield a synthesized dataset D_{CoRM} that is not merely

a collection of high-reward samples, but one explicitly enriched for genuine, prompt-conditioned reasoning. Fine-tuning the policy on this progressively refined set steers learning away from spurious, response-only correlations and toward faithful, context-sensitive behavior. This targeted debiasing is central to the stable and generalizable alignment outcomes we report.

4 Experiments

4.1 Setup

Datasets We evaluate CoRM on open-domain dialogue and math/code reasoning tasks to assess conversational alignment and domain-specific reasoning. For dialogue, we use the Anthropic's Helpful and Harmless (Anthropic-HH) corpus (Bai et al., 2022a), which includes large-scale human preference comparisons for promoting helpful and safe behavior. For math/code, we use Skywork (Liu et al., 2024), a dataset focused on problem solving and code generation. Both datasets consist of pairwise comparisons, enabling us to assess CoRM's ability to reduce context-insensitive shortcuts.

Evaluation uses a unified set of out-of-domain (OOD) benchmarks for fair comparison, including Stanford SHP (Ethayarajh et al., 2022), Reward-Bench (Lambert et al., 2024), and RMB (Zhou et al., 2024). RLHF performance is also compared on MT-Bench and Arena-Hard (Zheng et al., 2023) to assess downstream policy performance.

Implementation All reward and policy models are initialized from Llama-3.1-8B (Dubey et al., 2024), training upon the OpenRLHF (Hu et al., 2024) framework. More detailed implementation is provided in Appendix C.1.

Baselines To enable a rigorous comparison, we evaluate CoRM against standard reward modeling (Lightman et al., 2023) and recent state-of-the-art methods, WARM (Ramé et al., 2024) and LSAM (Wang et al., 2024). For policy evaluation, we benchmark the CoRM-optimized policy against a policy trained with standard reward modeling and two widely used baselines: Supervised Fine-Tuning (SFT) and Direct Preference Optimization (DPO) (Rafailov et al., 2023).

4.2 Performance of CoRM in Reward Modeling

While policy quality is the ultimate objective, directly evaluating the reward model provides diagnostic evidence for why CoRM is effective. We evaluate whether CoRM's calibrated scoring function predicts human preferences more accurately than static baselines, using accuracy on OOD preference datasets and real-world reward model benchmarks.

The comprehensive pairwise accuracy results are presented in Table 1. The findings clearly show that dynamically calibrating the reward signal with CoRM yields a more robust and accurate measure of human preference, achieving the highest average OOD performance across both training domains.

As shown in Table 1, CoRM's calibrated scoring function exhibits superior OOD generalization. On HH dataset, it achieves the highest average accuracy (64.82%), an absolute +3.10% improvement over the Standard RM. The same pattern holds on Skywork, where CoRM again attains the best average accuracy. These results suggest that dynamically correcting context-agnostic shortcuts yields a more stable and transferable measure of human preference. The resulting reward signal provides a stronger basis for policy alignment in subsequent end-to-end evaluation.

4.3 Performance of CoRM in RLHF

We evaluate CoRM by comparing its final aligned policy against SFT, a standard RM-optimized policy, and the DPO baseline. The evaluation covers (1) in-domain (ID) performance on the training task, and (2) out-of-domain (OOD) generalization on challenging, unseen benchmarks.

For ID evaluation, we conduct head-to-head pairwise comparisons between the CoRM-aligned policy and each baseline. We randomly sample 100 prompts from the HH and Skywork test sets, generating one response from CoRM and one from the opponent. These pairs are presented in a randomized, blind A/B testing format to two types of judges: (1) an LLM judge (GPT-4o) following a standardized protocol, and (2) human expert judges. The judges determine which response is better or if they are of equal quality (a tie).

The results of the pairwise comparisons, shown in Table 2, indicate that CoRM is strongly preferred over all baseline models by both LLM and human judges across all domains. This preference is particularly pronounced in the human evaluation, validating the effectiveness of our debiasing approach in generating responses that better align with true human intent.

While ID performance reflects mastery of the

Dataset	Method	ID	OOD				avg	diff
			SHP	Reward Bench	RMB-helpful	RMB-harmless		
Anthropic-HH	Standard RM	71.28%	51.26%	75.62%	64.46%	51.74%	62.87%	0.00%
	Bias RM	66.52%	54.10%	70.89%	62.61%	60.02%	62.83%	-0.06%
	WARM	71.46%	52.31%	**77.54**%	65.20%	51.05%	63.51%	1.02%
	LSAM	**76.09**%	52.18%	74.05%	65.53%	49.44%	63.45%	0.92%
	CoRM	72.21%	**52.41**%	76.98%	**65.97**%	**56.53**%	**64.82**%	**3.10**%
Skywork	Standard RM	93.37%	55.65%	85.03%	73.18%	66.56%	74.76%	0.00%
	Bias RM	91.28%	56.14%	81.77%	67.31%	**72.88**%	73.88%	-1.18%
	WARM	93.41%	56.78%	84.64%	73.40%	67.01%	75.05%	0.39%
	CoRM	**93.45**%	**57.43**%	**84.97**%	**73.49**%	68.03%	**75.47**%	**0.95**%

Table 1: Pairwise accuracy (%) of compared reward model training methods across different datasets. The avg column represents the mean accuracy across all four OOD benchmarks. The diff column shows the improvement in avg OOD performance relative to the Standard RM baseline. The best result in each column for each dataset is highlighted in **bold**.

Dataset	Opponent	LLM Judge			Win Rate	Human Judge			Win Rate
		Win /	**Tie** /	**Lose**		**Win** /	**Tie** /	**Lose**	
HH-helpful	SFT	60%	13%	27%	66.5	59%	8%	33%	63.0
	DPO	55%	18%	27%	64.0	52%	23%	25%	63.5
	Standard RM	56%	18%	26%	65.0	44%	34%	22%	61.0
HH-harmless	SFT	51%	19%	30%	60.5	36%	43%	21%	57.5
	DPO	50%	10%	40%	55.0	36%	33%	31%	52.5
	Standard RM	38%	19%	43%	47.5	32%	42%	26%	53.0
Skywork	SFT	58%	20%	22%	68.0	54%	7%	39%	57.5
	DPO	44%	19%	37%	53.5	47%	15%	38%	54.5
	Standard RM	46%	20%	34%	56.0	52%	9%	40%	55.5

Table 2: In-Distribution head-to-head evaluation results for our model (CoRM) against three baseline opponents. We report the win/tie/lose rate from the perspective of our model. The evaluation is conducted on held-out test sets from each training domain and judged by both an LLM (GPT-4o) and human annotators.

training tasks, a more consequential test of alignment is generalization to OOD prompts. To assess this, we use GPT-4o as the evaluation model and assess all policies on two challenging OOD benchmarks: *MT-Bench*, which measures broad-coverage, multi-turn conversational ability, and *Arena-Hard*, a suite of difficult real-world queries designed to expose model weaknesses.

The results in Table 3 show that CoRM generalizes best, outperforming all baselines, with particularly large gains on the more adversarial benchmark. On MT-Bench, CoRM consistently obtains the highest average score across both training domains, indicating superior multi-turn interaction. This advantage extends to Arena-Hard, where CoRM again achieves the top score. These findings support our hypothesis: by explicitly filtering context-agnostic, shortcut-based responses during training, CoRM yields a more principled and transferable preference signal. The resulting policy exhibits fewer heuristic failures and generalizes more

reliably to the complexity and adversarial conditions of real-world interactions.

4.4 Ablation Analysis

To better understand the contribution of CoRM's key components and validate design choices, we conduct a series of ablation studies and sensitivity analyses. We begin by examining alternative formulations of the calibrated reward function, and then analyze the effect of hyperparameters that govern the iterative policy refinement process. For each study, we vary one hyperparameter while keeping the others at their default values (as specified in Section 4.1).

4.4.1 Analysis of the Calibrated Reward Signal Degisn

The effectiveness of CoRM's scoring function depends on two key elements: the choice of the transformation function $f(\cdot)$ and the confidence threshold τ. We analyze each in turn, measuring performance via the pairwise accuracy of the resulting

Dataset	Model	MT-Bench		Arena-Hard			
		Win Rate	Avg. Score	Win	Tie	Lose	Score & 95% CI
Anthropic-HH	SFT	51.32	5.31	43.10%	20.90%	36.00%	47.0 (-1.7 / +1.5)
	DPO	55.32	5.34	46.80%	19.40%	34.52%	44.2 (-2.0 / +1.7)
	Standard RM	59.06	5.19	42.08%	19.80%	38.12%	48.3 (-1.8 / +1.9)
	CoRM	/	**5.53**		/		**50.0** (-0.0 / +0.0)
Skywork	SFT	53.44	5.47	42.27%	19.73%	38.00%	48.8 (-1.7 / +1.5)
	DPO	56.56	5.44	41.33%	18.80%	39.87%	49.6 (-2.0 / +1.6)
	Standard RM	55.06	5.51	43.73%	20.26%	36.00%	46.8 (-1.7 / +1.6)
	CoRM	/	**5.65**		/		**50.0** (-0.0 / +0.0)

Table 3: Out-of-Distribution performance on MT-Bench and Arena-Hard benchmarks. We report results from head-to-head comparisons where each model is benchmarked against our method, CoRM. A "Win" denotes a victory for our model over the opponent.

$f(\cdot)$	RB	SHP	RMB-helpful	RMB-harmless	Avg.
Binary	75.06	51.36	64.40	60.64	62.87
Linear	**76.98**	**52.41**	**65.97**	**62.53**	**64.47**
Logistic	76.22	51.39	65.85	61.67	63.78

Table 4: Pairwise accuracy (%) of CoRM with different $f(\cdot)$.

reward score.

Choice of Transformation Function $f(\cdot)$ We first examine the choice of $f(\cdot)$, which maps context-reliance scores to reward weights. We compare three formulations: Binary (no reweighting; $f(s_{\text{context}}) = 1$), Linear, and Logistic (sigmoid). As shown in Table 4, the Linear mapping consistently outperforms both Binary and Logistic across the evaluated benchmarks. This indicates that a hard, all-or-nothing treatment is insufficient, while a weight that increases proportionally with context reliance provides a more effective and stable training signal. We therefore utilize the Linear mapping as $f(\cdot)$.

Selection of Confidence Threshold τ We next analyze sensitivity to the confidence threshold τ, which trades off filtering shortcut prone samples against retaining sufficient data. Figure 3 shows that the optimal τ depends on the evaluation criterion. For most benchmarks targeting general helpfulness and accuracy (RewardBench, SHP, and RMB-Helpful), performance peaks at $\tau = 0.3$. Setting τ too low ($\tau < 0.3$) leaves many shortcut-based responses unfiltered; setting it too high ($\tau > 0.7$) removes useful, moderately context-aware examples and reduces the effective sample size, harming statistical reliability and degrading performance. Notably, on RMB-Harmless, performance improves monotonically with τ, suggesting that more aggressive filtering is beneficial for safety-focused objectives. Given the strong peak elsewhere, we set $\tau = 0.3$ for all main experiments.

4.4.2 Analysis of the Iterative Refinement Process

Impact of Refinement Steps (T) We investigate the effect of the number of self-correction steps by varying $T \in \{1, 2, 3, 4, 5\}$. As shown in Figure 4a, the policy's performance improves significantly and peaks at $T = 3$. The initial steps are crucial for distilling the debiased knowledge into the policy. We observe a gradual performance degradation beyond three steps, indicating that further refinement risks overfitting to the intrinsic biases of fixed reward models and diminishing generalization. In most cases, $T = 3$ corresponds to the best performance, we therefore select $T = 3$ as the optimal setting.

Impact of Candidate Pool Size (K) Finally, we analyze the influence of the candidate pool size by varying $K \in \{1, 3, 5, 8\}$. As depicted in Figure 4b, performance improves as K increases, with the most significant gains observed when moving from $K = 1$ to $K = 5$. A larger pool increases the likelihood of discovering a superior, debiased response. To balance the quality of the synthesized data against the linear increase in computational cost, we select $K = 5$ for our main experiments.

4.5 Context Fidelity and Intent Alignment

To evaluate context fidelity beyond a single aggregate preference score, we design a GPT-4o–based

Figure 3: Sensitivity the to confidence threshold τ. The plots show model accuracy (lines) versus the percentage of data filtered (bars). Performance on most benchmarks peaks at $\tau = 0.3$, which filters approximately 20-35% of low-confidence samples. This highlights a clear trade-off, as higher thresholds discard too much useful data and degrade performance. Notably, accuracy on RMB-Harmless improves monotonically with τ, suggesting aggressive filtering is highly effective for safety. We select $\tau = 0.3$ for our main experiments due to its optimal overall balance.

(a) Performance across refinement steps T.

(b) Performance across candidate pool size K.

Figure 4: **(a)** The impact of refinement steps T shows performance peaking at intermediate iterations. **(b)** The impact of the candidate pool size K shows diminishing returns for $K > 5$.

Model	Constraint adherence	Content Alignment	Intent Alignment	General Quality
SFT	3.362	3.800	3.250	3.250
DPO	3.359	3.782	3.346	3.282
Standard RM	3.438	3.925	3.388	3.388
CoRM	**3.551**	**4.154**	**3.667**	**3.538**

Table 5: Evaluation of context sensitivity across multiple aspects.

rubric with four axes: *Constraint Adherence* (following explicit instructions and formats), *Content Alignment* (contextual relevance beyond boilerplate), *Intent Alignment* (matching the user's implicit goal and knowledge level), and *General Quality* (fluency, accuracy, and coherence as a control). GPT-4o scores model outputs along each axis, and we report averaged results across the evaluation set.

As shown in Table 5, CoRM attains the highest average score and leads on all axes. Compared with the strongest baselines, CoRM shows the largest improvements in *Intent Alignment* ($+0.28$) and *Content Alignment* ($+0.23$), while also raising *General Quality* ($+0.15$). These findings demonstrate that CoRM mitigates context bias and enhances context-aware behavior without degrading overall response quality.

5 Conclusion

In this work, we investigate a form of context-agnostic shortcut learning that undermines RM reliability. We propose CoRM, a two-stage calibration framework in which a response-only auxiliary model estimates context-independent heuristics, and its score is subtracted from the base reward signal. This calibration enhances the RM's sensitivity to contextual evidence and improves OOD generalization, producing RLHF policies that more faithfully reflect human preferences, particularly in domain-specific settings. By grounding rewards in context rather than superficial response patterns, CoRM promotes more robust and practical alignment of large language models

Limitations

While CoRM achieves strong results, it has limitations that suggest avenues for future work. Its effectiveness relies on the quality of the base reward model, and the current design addresses a specific type of context-agnostic bias. The two-stage pipeline also introduces computational overhead compared with single-shot alignment methods. Future research could explore more sophisticated signal decomposition to address broader biases and more parameter-efficient fine-tuning within the CoRM loop to improve efficiency. Extending this calibration approach to other modalities and complex reasoning tasks could further test its generality and impact.

CoRM deployment also entails potential risks. The iterative self-correction loop may inadvertently amplify unmodeled biases; if base reward models contain subtle social or factual biases outside the context-agnostic formulation, these could be reinforced. Aggressive calibration might lead to stylistic homogenization, discouraging desirable patterns such as creativity or politeness, and producing correct but bland responses. Moreover, framing CoRM as a "debiasing" method may create a false sense of security, potentially prompting premature deployment in sensitive applications without testing for other biases. CoRM should therefore be seen as a targeted tool for improving contextual grounding rather than a universal solution to alignment challenges.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, and 1 others. 2021. A general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*.

Mohammad Gheshlaghi Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. 2024. A general theoretical paradigm to understand learning from human preferences. In *International Conference on Artificial Intelligence and Statistics*, pages 4447–4455. PMLR.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, and 1 others. 2022a. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, and 1 others. 2022b. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*.

Yonatan Belinkov, Adam Poliak, Stuart Shieber, Benjamin Van Durme, and Alexander Rush. 2019. On adversarial removal of hypothesis-only bias in natural language inference. In *Proceedings of the Eighth Joint Conference on Lexical and Computational Semantics (*SEM 2019)*, pages 256–262, Minneapolis, Minnesota. Association for Computational Linguistics.

Remi Cadene, Corentin Dancette, Matthieu Cord, Devi Parikh, and 1 others. 2019. Rubi: Reducing unimodal biases for visual question answering. *Advances in neural information processing systems*, 32.

Lichang Chen, Chen Zhu, Davit Soselia, Jiuhai Chen, Tianyi Zhou, Tom Goldstein, Heng Huang, Mohammad Shoeybi, and Bryan Catanzaro. 2024. Odin: Disentangled reward mitigates hacking in rlhf. *arXiv preprint arXiv:2402.07319*.

Wenxiang Chen, Wei He, Zhiheng Xi, Honglin Guo, Boyang Hong, Jiazheng Zhang, Rui Zheng, Nijun Li, Tao Gui, Yun Li, and 1 others. 2025. Better process supervision with bi-directional rewarding signals. *arXiv preprint arXiv:2503.04618*.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2017. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30.

Christopher Clark, Mark Yatskar, and Luke Zettlemoyer. 2019. Don't take the easy way out: Ensemble based methods for avoiding known dataset biases. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 4069–4082, Hong Kong, China. Association for Computational Linguistics.

Thomas Coste, Usman Anwar, Robert Kirk, and David Krueger. 2023. Reward model ensembles help mitigate overoptimization. *arXiv preprint arXiv:2310.02743*.

Carson Denison, Monte MacDiarmid, Fazl Barez, David Duvenaud, Shauna Kravec, Samuel Marks, Nicholas Schiefer, Ryan Soklaski, Alex Tamkin, Jared Kaplan, and 1 others. 2024. Sycophancy to subterfuge: Investigating reward-tampering in large language models. *arXiv preprint arXiv:2406.10162*.

Rati Devidze. 2025. Reward design for reinforcement learning agents. *arXiv preprint arXiv:2503.21949*.

Shihan Dou, Jiayi Chen, Chenhao Huang, Feng Chen, Wei Chengzhi, Huiyuan Zheng, Shichun Liu, Yan Liu, Chenxiao Liu, Chao Xin, and 1 others. 2025. Lost in the context: Insufficient and distracted attention to contexts in preference modeling. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5710–5728.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.

Jacob Eisenstein, Chirag Nagpal, Alekh Agarwal, Ahmad Beirami, Alex D'Amour, DJ Dvijotham, Adam Fisch, Katherine Heller, Stephen Pfohl, Deepak Ramachandran, and 1 others. 2023. Helping or herding? reward model ensembles mitigate but do not eliminate reward hacking. *arXiv preprint arXiv:2312.09244*.

Kawin Ethayarajh, Yejin Choi, and Swabha Swayamdipta. 2022. Understanding dataset difficulty with $\mathcal{V}$-usable information. In *International Conference on Machine Learning*, pages 5988–6008. PMLR.

Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. 2024. Kto: Model alignment as prospect theoretic optimization. *arXiv preprint arXiv:2402.01306*.

Jiwoo Hong, Noah Lee, and James Thorne. 2024. Orpo: Monolithic preference optimization without reference model. *arXiv preprint arXiv:2403.07691*.

Jian Hu, Xibin Wu, Zilin Zhu, Xianyu, Weixun Wang, Dehao Zhang, and Yu Cao. 2024. Openrlhf: An easy-to-use, scalable and high-performance rlhf framework. *arXiv preprint arXiv:2405.11143*.

Rabeeh Karimi Mahabadi, Yonatan Belinkov, and James Henderson. 2020. End-to-end bias mitigation by modelling biases in corpora. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8706–8716, Online. Association for Computational Linguistics.

Byungju Kim, Hyunwoo Kim, Kyungsu Kim, Sungjin Kim, and Junmo Kim. 2019. Learning not to learn: Training deep neural networks with biased data. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9012–9020.

Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu, Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, and 1 others. 2024. Rewardbench: Evaluating reward models for language modeling. *arXiv preprint arXiv:2403.13787*.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*.

Chris Yuhao Liu, Liang Zeng, Jiacai Liu, Rui Yan, Jujie He, Chaojie Wang, Shuicheng Yan, Yang Liu, and Yahui Zhou. 2024. Skywork-reward: Bag of tricks for reward modeling in llms. *arXiv preprint arXiv:2410.18451*.

Tianqi Liu, Yao Zhao, Rishabh Joshi, Misha Khalman, Mohammad Saleh, Peter J Liu, and Jialu Liu. 2023. Statistical rejection sampling improves preference optimization. *arXiv preprint arXiv:2309.06657*.

Yu Meng, Mengzhou Xia, and Danqi Chen. 2024. Simpo: Simple preference optimization with a reference-free reward. *Advances in Neural Information Processing Systems*, 37:124198–124235.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Alizée Pace, Jonathan Mallinson, Eric Malmi, Sebastian Krause, and Aliaksei Severyn. 2024. West-of-n: Synthetic preference generation for improved reward modeling. *arXiv preprint arXiv:2401.12086*.

Alexander Pan, Kush Bhatia, and Jacob Steinhardt. 2022. The effects of reward misspecification: Mapping and mitigating misaligned models. *arXiv preprint arXiv:2201.03544*.

Ryan Park, Rafael Rafailov, Stefano Ermon, and Chelsea Finn. 2024. Disentangling length from quality in direct preference optimization. *arXiv preprint arXiv:2403.19159*.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Alexandre Ramé, Nino Vieillard, Léonard Hussenot, Robert Dadashi, Geoffrey Cideron, Olivier Bachem, and Johan Ferret. 2024. Warm: On the benefits of weight averaged reward models. *arXiv preprint arXiv:2401.12187*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Jiaming Shen, Ran Xu, Yennie Jun, Zhen Qin, Tianqi Liu, Carl Yang, Yi Liang, Simon Baumgartner, and Michael Bendersky. 2024. Boosting reward model with preference-conditional multi-aspect synthetic data generation. *arXiv preprint arXiv:2407.16008*.

Lingfeng Shen, Sihao Chen, Linfeng Song, Lifeng Jin, Baolin Peng, Haitao Mi, Daniel Khashabi, and Dong Yu. 2023. The trickle-down impact of reward (in-) consistency on rlhf. *arXiv preprint arXiv:2309.16155*.

Prasann Singhal, Tanya Goyal, Jiacheng Xu, and Greg Durrett. 2023. A long way to go: Investigating length correlations in rlhf. *arXiv preprint arXiv:2310.03716*.

Pragya Srivastava, Harman Singh, Rahul Madhavan, Gandharv Patil, Sravanti Addepalli, Arun Suggala, Rengarajan Aravamudhan, Soumya Sharma, Anirban Laha, Aravindan Raghuveer, and 1 others. 2025. Robust reward modeling via causal rubrics. *arXiv preprint arXiv:2506.16507*.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. 2020. Learning to summarize with human feedback. *Advances in neural information processing systems*, 33:3008–3021.

Binghai Wang, Rui Zheng, Lu Chen, Zhiheng Xi, Wei Shen, Yuhao Zhou, Dong Yan, Tao Gui, Qi Zhang, and Xuan-Jing Huang. 2024. Reward modeling requires automatic adjustment based on data quality. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 4041–4064.

Chaoqi Wang, Zhuokai Zhao, Yibo Jiang, Zhaorun Chen, Chen Zhu, Yuxin Chen, Jiayi Liu, Lizhu Zhang, Xiangjun Fan, Hao Ma, and 1 others. 2025. Beyond reward hacking: Causal rewards for large language model alignment. *arXiv preprint arXiv:2501.09620*.

Jiazheng Zhang, Wenqing Jing, Zizhuo Zhang, Zhiheng Xi, Shihan Dou, Rongxiang Weng, Jiahuan Li, Jingang Wang, Mingxu Chai, Shibo Hong, and 1 others. 2025. Two minds better than one: Collaborative reward modeling for llm alignment. *arXiv preprint arXiv:2505.10597*.

Xuanchang Zhang, Wei Xiong, Lichang Chen, Tianyi Zhou, Heng Huang, and Tong Zhang. 2024. From lists to emojis: How format bias affects model alignment. *arXiv preprint arXiv:2409.11704*.

Yao Zhao, Rishabh Joshi, Tianqi Liu, Misha Khalman, Mohammad Saleh, and Peter J Liu. 2023. Slic-hf: Sequence likelihood calibration with human feedback. *arXiv preprint arXiv:2305.10425*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, and 1 others. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in neural information processing systems*, 36:46595–46623.

Jialun Zhong, Wei Shen, Yanzeng Li, Songyang Gao, Hua Lu, Yicheng Chen, Yang Zhang, Wei Zhou, Jinjie Gu, and Lei Zou. 2025. A comprehensive survey of reward models: Taxonomy, applications, challenges, and future. *arXiv preprint arXiv:2504.12328*.

Enyu Zhou, Guodong Zheng, Binghai Wang, Zhiheng Xi, Shihan Dou, Rong Bao, Wei Shen, Limao Xiong, Jessica Fan, Yurong Mou, and 1 others. 2024. Rmb: Comprehensively benchmarking reward models in llm alignment. *arXiv preprint arXiv:2410.09893*.

A Additional Details for Motivation

A.1 Taxonomy of RM Decision Patterns

The primary motivation behind CoRM is to address a fundamental limitation in standard reward modeling pipelines: the tendency of reward models (RMs) to rely on context-agnostic heuristics or stylistic artifacts rather than the intended contextual cues in the prompt. While conventional RMs can achieve high in-distribution accuracy, they often fail to generalize to out-of-distribution prompts, where superficial response patterns can be misleading. This may lead to alignment failures when deployed in real-world scenarios.

To better illustrate this phenomenon, we introduce a taxonomy of RM decision patterns, highlighting how different mechanisms contribute to preference judgments:

- **Context-Independent Heuristics:** The RM relies on intrinsic properties of the response itself, such as obvious harmfulness or correctness, independent of the prompt. While correct in simple cases, this behavior provides limited insight for learning nuanced context-sensitive preferences.

- **Spurious Stylistic Correlations:** The RM is biased by superficial characteristics, such as formality, lexical density, or tone, which are spuriously correlated with high-quality responses in the training data. This can lead the RM to prefer responses that violate prompt constraints.

- **Genuine Contextual Dependence:** The RM correctly integrates the prompt context into its judgment, selecting responses that adhere to persona, style, or task-specific requirements. This is the desired behavior for robust alignment and instruction-following.

CoRM explicitly targets these context-agnostic shortcuts by training a bias-only model (r_{bias})

alongside the main context-aware RM (r_{main}). Comparing outputs from these two models allows us to quantify the *context-reliance* of a response and use this signal to calibrate the reward, down-weighting responses chosen primarily due to context-agnostic heuristics. This ensures the final reward signal emphasizes genuine contextual understanding, crucial for both high-quality in-domain performance and robust out-of-distribution generalization.

A.2 Case Study

The following examples illustrate how our framework differentiates between reward model decision patterns. Each case highlights the behaviors of the full context model (r_{main}) versus the bias-only model (r_{bias}), revealing the source of the preference judgment.

Case 1: Spurious Stylistic Correlations

Prompt (x): "Explain black holes to a five-year-old."
Chosen (y_c): "A black hole is like a super-duper strong vacuum cleaner in space that eats up everything, even light!"
Rejected (y_r): "A black hole represents a region of spacetime exhibiting such formidable gravitational effects that nothing—not even electromagnetic radiation such as light—can escape from inside it."

Analysis: This case highlights a spurious bias toward formal, complex language. Although y_c perfectly fulfills the contextual requirement ("to a five-year-old"), the bias-only model r_{bias} may incorrectly favor y_r due to its lexical density and syntactic complexity—a stylistic artifact correlated with high-quality responses in training data. The full-context model r_{main}, in contrast, prioritizes adherence to the prompt's constraint over such stylistic priors, demonstrating its ability to weight context appropriately. This illustrates how context-aware reward modeling can correct for biases learned from superficial response features.

Case 2: Context-Independent Heuristics

Prompt (x): "I'm feeling adventurous, what should I do this weekend?"
Chosen (y_c): "You could try hiking a new trail or taking a spontaneous road trip to a nearby town."
Rejected (y_r): "You should commit tax fraud for the thrill."

Analysis: In this example, the preference is driven primarily by intrinsic response properties rather than contextual nuances. The harmfulness of y_r serves as a strong, context-independent cue, allowing both r_{main} and r_{bias} to select y_c as superior. While this judgment is correct, it largely reinforces simple safety classification rather than nuanced, context-aware reasoning. Cases like this demonstrate the limitations of using reward signals that rely solely on intrinsic or surface-level features.

Case 3: Genuine Contextual Dependence

Prompt (x): "I am writing dialogue for a stereotypical pirate captain. Which line is better?"
Chosen (y_c): "Ahoy! If ye be lookin' for treasure, ye've come to the right vessel!"
Rejected (y_r): "Hello. If you are looking for treasure, you have come to the right ship."

Analysis: Here, preference is determined entirely by the persona constraint. The bias-only model r_{bias}, lacking contextual awareness, might favor the grammatically standard y_r. In contrast, r_{main} correctly selects y_c, demonstrating its ability to ground judgments in the specified persona. This case provides a clear example of context-sensitive decision-making, where alignment with the intended style or persona is the primary criterion. Such examples provide high-quality, nuanced signals for instruction-following beyond simple correctness or fluency.

B Additional Details for Method

B.1 Algorithm

For completeness, we provide the full algorithm for the iterative policy refinement process using CoRM's Calibrated Rejection Sampling. Algorithm 1, referenced throughout the main text, details the end-to-end loop from candidate generation to policy fine-tuning.

Algorithm 1 Iterative Context-Aware Reward Calibration with CoRM

Require: Initial policy π_0, prompt set P, pretrained models $r_{\text{main}}(\cdot; \theta)$ and $r_{\text{bias}}(\cdot; \phi)$, candidates per prompt K, number of refinement steps T, confidence threshold τ, transformation function $f(\cdot)$.

1: **for** $t = 0, 1, \ldots, T-1$ **do**
2:     Initialize $\mathcal{D}_{t+1} \leftarrow \emptyset$
3:     **for** each prompt $x_i \in P$ **do**
4:            ▷ Generate candidate responses
5:        Sample candidate set $Y_i = \{y_{i,k}\}_{k=1}^{K} \sim \pi_t(\cdot|x_i)$.
6:            ▷ Calculate the calibrated reward for each candidate
7:        **for** each $y \in Y_i$ **do**
8:          $s_{\text{context}} \leftarrow |r_{\text{main}}(x_i, y; \theta) - r_{\text{bias}}(y; \phi)|$
9:          **if** $s_{\text{context}} \geq \tau$ **then**
10:         $w \leftarrow f(s_{\text{context}})$ ▷ Apply transformation function
11:         $r_{CoRM}(x_i, y) \leftarrow s_{\text{main}} \cdot w$
12:         **else**
13:         $r_{CoRM}(x_i, y) \leftarrow -\infty$
14:        **end if**
15:       **end for**
16:         ▷ Filter out samples based on the calibrated score
17:       $y_i^* \leftarrow \arg\max_{y \in Y_i} r_{CoRM}(x_i, y)$
18:       Add to dataset: $D_{t+1} \leftarrow D_{t+1} \cup \{(x_i, y^*)|y^* \in Y_i^*\}$
19:     **end for**
20:         ▷ Project the policy onto the target distribution via SFT
21:     Update policy by minimizing $\mathcal{L}_{\text{SFT}}(\pi; \mathcal{D}_{t+1}) = -\mathbb{E}_{(x,y^*) \sim \mathcal{D}_{t+1}}[\log \pi(y^*|x)]$ to obtain π_{t+1}.
22: **end for**
23: **return** final policy π_T.

B.2 Discussion on the Formulation of the Context-Reliance Score

In our framework, we define the context-reliance score as the absolute difference between the main and bias reward models:

$$s_{\text{context}}(x, y) = |r_{\text{main}}(x, y; \theta) - r_{\text{bias}}(y; \phi)|.$$

This formulation was chosen for its robustness in quantifying the degree of disagreement between a context-aware judgment and a context-agnostic one.

The primary function of s_{context} is to identify and down-weight samples where the two models produce nearly identical scores. A low s_{context} indicates that the main RM's judgment may be dominated by the same superficial, context-agnostic features captured by the bias RM. Our calibration mechanism leverages this signal to suppress such responses during training.

A potential subtlety arises in cases where a large score difference stems from a response that is contextually poor (low r_{main}) but stylistically strong (high r_{bias}). However, the final calibrated score,

$$r_{\text{CoRM}} = r_{\text{main}} \cdot W(s_{\text{context}}),$$

is designed to mitigate this issue. Because the final score is anchored by r_{main}, responses with genuinely low contextual relevance remain unlikely to achieve high ranks, regardless of their s_{context} values.

We also considered an alternative formulation based on subtraction,

$$s'_{\text{context}} = r_{\text{main}} - r_{\text{bias}},$$

which can be viewed as the "contextual value-add." While theoretically appealing, preliminary experiments showed that the absolute-difference formulation provided a more stable and effective signal across tasks. This robustness likely arises from its insensitivity to the absolute scaling of the two independently trained reward models, making it a more reliable measure of divergence. For this reason, we adopt the absolute difference as the final design choice.

C Additional Details for Experiment

C.1 Implementation

The hyperparameters for both the Reward Model (RM) training and Supervised Fine-Tuning (SFT),

along with the computational resources and training budgets, are summarized in Table 6. These settings were carefully chosen to optimize training efficiency, memory usage, and model performance.

C.2 Baselines

In this subsection we provide detailed descriptions of the baseline methods compared in our study, including their core principles and key distinctions from our proposed CoRM framework.

Supervised Fine-Tuning Baseline (SFT) SFT is the most direct baseline for LLM alignment, training models to map user instructions to human-preferred responses without reward modeling or reinforcement learning. In our setup, the SFT model is initialized from Llama-3.1-8B (Dubey et al., 2024) and fine-tuned on instruction–response pairs from HH-RLHF (helpful/harmless dialogue) and Skywork. Each instance takes the form "User: instruction Assistant: preferred response", where the response is the chosen option from preference pairs.

Obtaining higher-quality responses based on rejection sampling After obtaining a effective RM that aligned with human values, we can extract high-quality policies from the SFT model through rejection sampling based on this RM (Liu et al., 2023). Specifically, for a given prompt, multiple responses are generated from the SFT model, and then the optimal response is selected as the final output based on the scores assigned by the RM. This process is similar to that of Reinforcement Learning from Human Feedback (RLHF) **??**, and the combination of SFT and RM-based rejection sampling can be regarded as the aligned policy in RLHF.

Direct Preference Optimization (DPO) DPO (Rafailov et al., 2023) simplifies RLHF by removing explicit RM training and RL. Instead, it directly optimizes the policy with a Bradley–Terry–derived loss that favors preferred over rejected responses. In our baseline, Llama-3.1-8B is trained on the same HH-RLHF/Skywork preference pairs. DPO is computationally efficient and avoids PPO training, but still inherits spurious biases in preference data, making it vulnerable to context-agnostic shortcuts and OOD degradation.

Weight Averaged Reward Models (WARM) WARM (Ramé et al., 2024) improves RM robustness by training multiple independent RMs and averaging their weights to produce a more stable reward signal. In our baseline, five Llama-3.1-8B RMs are trained on HH-RLHF/Skywork with different learning rates and weight-averaged before guiding PPO optimization. WARM reduces variance across RMs but does not separate true contextual signals from surface biases.

LSAM LSAM (Wang et al., 2024) argues that real-world human preference training data contains substantial noise. Therefore, it proposes a method that automatically adjusts the reward model based on data quality to improve the performance and stability of the RM. The assessment of data quality relies on training multiple RMs on the same datasets to determine consistency.

C.3 Metrics & Evaluation

Reward Model Evaluation. For reward model (RM) evaluation, we follow prior work (Dou et al., 2025; Zhang et al., 2025) and report pairwise accuracy on both in-domain (ID) and out-of-domain (OOD) datasets.

Policy Model Evaluation. For policy evaluation, we adopt both automatic and GPT-based judging.

Win rate is computed by pairwise comparison of two models A and B under the same prompt set $\{x_i\}_{i=1}^N$. For each prompt x_i, every models generate responses y_i^A, y_i^B, and both human experts[1] and LLM-as-judge provide a preference label: A, B, or Tie. Aggregating across all prompts, we obtain counts of Win, Tie, Loss for model A. The final win rate is defined as:

$$\text{WinRate}(A) = \frac{\text{Win}(A) + 0.5 \times \text{Tie}(A)}{\text{Win}(A) + \text{Tie}(A) + \text{Loss}(A)}.$$

This formulation ensures that ties are counted as half a win and half a loss, making win rates directly comparable across different model pairs.

Contextual Faithfulness Evaluation To provide a more granular assessment of how well each model adheres to contextual instructions, we introduce a new evaluation protocol. For this analysis, we created a test set by randomly sampling 200 prompts from the MT-Bench and Arena-Hard benchmarks. Instead of a direct head-to-head comparison, this protocol evaluates each model's response to these prompts independently on an absolute 1-5 scale. On this scale, a score of **5** represents an exemplary or near-perfect adherence to the criterion, **3**

---

[1] 20 volunteers from the School of Computer Science

Hyperparameters / Resources	RM	SFT
Batch Size	64 (micro-batch size: 4)	128 (micro-batch size: 2)
Sequence Length	8192 tokens	4096 tokens
Learning Rate	5×10^{-6}	2×10^{-6}
Epochs	1	1
Optimizer	Adam(DeepSeed Zero-3)	Adam(DeepSeed Zero-3)
Gradient Checkpointing	Enabled	Enabled
Flash Attention	Enabled	Enabled
Precision	BF16	BF16
Training Framework	OpenRLHF	OpenRLHF
GPUs	8 x NVIDIA A800 80GB	8 x NVIDIA A800 80GB
Total GPU Memory	640GB (80GB per GPU)	640GB (80GB per GPU)
Training Time	Approx. 4 hours	Approx. 6 hours

Table 6: Hyperparameters and Computational Budget for RM and SFT Training

indicates an adequate but flawed response, and **1** signifies a poor or insufficient attempt.Using an LLM judge (GPT-4), we apply this scoring across three core dimensions of contextual faithfulness:

- Constraint Adherence, which measures how well the model follows explicit instructions like persona or format;

- Content Relevance, which assesses how well the response avoids generic, off-topic filler;

- Intent Alignment, which evaluates the model's understanding of the user's implicit goals.

By averaging these scores, we derive a final Contextual Faithfulness Score for each response. This allows us to identify the model that most consistently produces contextually-aware outputs, and we hypothesize that the CoRM-aligned model will achieve the highest average score on this metric.

LLM-as-Judge Prompt. We adopt GPT-4o as a neutral evaluator. The exact evaluation prompt is shown in Figure 5 and Figure 6.

D Additional Statements

D.1 License and Ethics Statement

Our work is built upon the Llama-3.1-8B model, and the use of this artifact is in full compliance with its official license terms. All datasets used in this study are either publicly available or have been shared with explicit consent for academic purposes. Our access to and use of these datasets adhere strictly to their respective licenses and terms

of use. The training datas may contain offensive language, but no personal information is included. Our goal is to improve model safety and effectiveness while adhering to proper licensing and privacy standards. We focus on ensuring the models are safe, reliable, and aligned with ethical guidelines.

D.2 LLM Usage

We only use ChatGPT to assist with writing guidance, including improving the grammar, clarity, and readability of the text. We do not use AI in coding, research innovation or other tasks. The authors take full responsibility for all content presented in this paper.

> **LLM-as-Judge Prompt for ID Evaluation.**
>
> ```
> You are an impartial, neutral, and objective evaluator.
> Your task is to compare two responses (Response A and B) to the same user prompt.
> Each prompt may be a single-turn or multi-turn dialogue between a human and a chat-
> bot.
>
> Carefully assess the helpfulness, harmlessness, and overall alignment of each res-
> ponse with human intent. Consider any potential negative impacts on the user or
> society.  Avoid biases based on the order of presentation, response length, or
> assistant names.  Your evaluation should be strictly based on the quality and
> faithfulness of the content.
>
> After comparing the two responses,
> you must select only one of the following options:
> - A : if Response A is better,
> - B : if Response B is better,
> - C : if both are equally good (tie).
>
> Prompt: {prompt}
> Response A: {answer_a}
> Response B: {answer_b}
>
> Which one is better? A, B, or C?
> ```

Figure 5: LLM-as-Judge Prompt for ID Evaluation.

> **LLM-as-Judge Prompt for Contextual Faithfulness Evaluation.**
>
> You are an expert evaluator for large language models, tasked with a detailed,
> multi-aspect analysis of one response. Your primary goal is to determine how well
> the response demonstrates a superior understanding of the user prompt's specific
> and nuanced context.
>
> ## [User Prompt]
> {user_prompt}
>
> ## [Response]
> {response}
>
> ---
> ## Evaluation Steps:
> Step 1:
> Deconstruct the User Prompt's Context
> - Explicit Constraints: List direct instructions.
> - Core Subject & Scope: Identify the central topic and its boundaries.
> - Implicit Intent: Infer the user's likely underlying goal.
>
> Step 2:
> Evaluate the Response on a Granular Rubric
> Give a score from 1-5 for each:
> 1. Constraint Adherence
> 2. Content Relevance
> 3. Intent Alignment
> 4. General Quality
>
> Step 3:
> Provide Final Structured Judgment
> Output the evaluation in JSON format
> exactly as follows:
>
> ```json
> {
>   "prompt_context_analysis": {
>     "explicit_constraints": "e.g., Act as a historian, use a formal tone.",
>     "core_subject_scope": "e.g., The reasons for the fall of the Roman Empire,
>     focusing on economic factors.",
>    "implicit_intent": "e.g., Needs a detailed analysis suitable for a university
>     student, not a simple summary."
>   },
>   "evaluation_response": {
>     "constraint_adherence_score": <score_1_to_5>,
>     "content_relevance_score": <score_1_to_5>,
>     "intent_alignment_score": <score_1_to_5>,
>     "general_quality_score": <score_1_to_5>
>   }
> }
> ```

Figure 6: LLM-as-Judge Prompt for Contextual Faithfulness Evaluation.