A Data-efficient Neural ODE Framework for Optimal Control of Soft Manipulators

Abstract: This paper introduces a novel approach for modelling continuous forward kinematic models of soft continuum robots by employing Augmented Neural ODE (ANODE), a cutting-edge family of deep neural network models. To the best of our knowledge, this is the first application of ANODE in modelling soft continuum robots. Our methodology achieves exceptional sample efficiency, training the continuous forward kinematic model using only 25 scattered data points. By leveraging ANODE, we enhance the adaptability and robustness of the learned model, enabling accurate prediction and control of soft continuum robot motion in diverse and previously unseen scenarios. Additionally, we design and implement a fully parallel Model Predictive Path Integral (MPPI)-based controller running on a GPU, which efficiently manages a non-convex objective function. Through a set of experiments, we showed that the proposed framework (ANODE+MPPI) significantly outperforms state-of-the-art learning based methods such as FNN and RNN in unseen-before scenarios and marginally outperforms them in seen-before scenarios.

Keywords: Soft robots, Non-parametric modelling

1 Introduction

Soft robots are composed of compliant materials such as silicone, rubber, or elastomers, which allows them to conform to surfaces and objects while maintaining a level of physical robustness unavailable to their rigid counterparts. This level of compliance makes them suitable for a broad range of applications, including medical procedures, search and rescue operations, and exploration [1]. However, the design and control of soft continuum robots present significant challenges. This is due to the inherent non-linearities and high DOF required to accurately capture the structural deformations that realize these compliant behaviours, which in turn makes it challenging to control the robot's motion. Several methodologies have been proposed to model soft robot controllers, broadly classified into two categories: model-based and data-driven [2].

Model-based approaches rely on mathematical models to represent the dynamics of the robot and use this model to design controllers. Various methodologies have been proposed in this category, including polynomial curvature fitting [3], reduced-order finite element models [4], and lumped parameter models [5, 6]. A comprehensive review of physics-based models for soft robots can be found in [7]. These models have limitations, as they are based on assumptions that may not hold in all conditions and may only be able to accurately describe the behaviour of the robot under a subset of conditions. Furthermore, these methods can be computationally expensive and may not fully capture the nonlinear behaviour exhibited by the robot. Additionally, physics-based models' error tends to increase together with the model inaccuracies, e.g., fabrication inaccuracies.

Learning-based approaches for soft robot modelling and control utilize collected data to develop models and controllers, either with or without relying on mathematical models. The learning-based models tend to be insensitive to physics-based modelling assumptions and fabrication inaccuracies, especially if training is accomplished on the physical robot arm. These approaches aim to learn kinematic or dynamics models directly [8, 9, 10, 11] or employ model-based/model-free Reinforce-

Figure 1: 25 scattered data points are employed within the demonstration space for acquiring knowledge about a continuous forward kinematic model (left). Subsequently, this trained model serves as the foundation for a fully parallel controller capable of managing a non-convex objective function executed on a GPU (right).

ment Learning (RL) techniques to learn control policies [12, 13]. While data-driven approaches have the potential to overcome the limitations of model-based methods, they also face inherent drawbacks. First, they require a substantial amount of training data, which can be challenging to acquire for real robots and may compromise their structural integrity as demonstrated in [14], [15] and [16], where 12000, 7000, and 4096 sample points were utilized. Second, the ability to generalize knowledge is limited, leading to poor performance in new or unseen situations [17]. Lastly, data-driven approaches lack interpretability and physical insight, making it challenging to understand decision-making processes and the underlying physical principles of soft robot behaviour [12].

In this paper, we introduce a novel framework for modelling and controlling soft robots. We address the limitations of existing data-driven methods and proposed a solution that is extensively tested on a real soft robot in different scenarios. Our key contributions are as follows:

1. We propose a novel approach to developing continuous forward kinematic models for soft continuum robots by employing Augmented Neural ODE (ANODE), a state-of-the-art family of deep neural network models. To the best of our knowledge, this is the first time that ANODE has been applied to modelling soft continuum robots. Our methodology achieves exceptional sample efficiency, training the continuous forward kinematic model using only 25 real robot demonstrations.

2. Utilizing the trained model as a basis, we developed a fully parallel Model Predictive Path Integral (MPPI) controller running on a GPU, capable of efficiently managing a non-convex objective function. This controller harnesses the power of parallel processing to optimize trajectory planning and control for the soft continuum robot. By leveraging the capabilities of the trained model, our controller enables the robot to navigate previously unseen trajectories within the feasible kinematic space. In comparison to state-of-the-art data-driven approaches such as feed-forward neural network (FNN) and recurrent neural network (RNN), our framework (FK model and controller combination) demonstrates superior performance in terms of trajectory tracking error while trained on significantly fewer data.

This paper is organized as follows: the methodology of the proposed approach is outlined in Section 2. To evaluate the effectiveness of the proposed framework, a series of experiments are conducted in Section 3, and the results are discussed. An ablation and comparison study with existing approaches will be presented in Section 4. Finally, the conclusion and future work are summarized in Section 5.

2   Methodology

This section will provide a comprehensive overview of the key steps involved in our approach. We will start by discussing the process of generating the training dataset, explaining how we collect the necessary data to train our model. Next, we will focus on learning the differential kinematics of the robot, highlighting the techniques and methodologies employed in this process. Finally, we will describe the development of a controller based on the learned model, explaining how it enables the robot to execute precise and controlled movements.

2.1 Training Dataset

The robot utilized in this study is a multi-backbone robot, as depicted in Figure 1 (left). It consists of a central flexible backbone made of a compression spring and four parallel flexible rods encased around it. By manipulating the rods (pulling/pushing), the shape of the robot can be altered. More details about the robot prototype are presented in the supplementary material. The modelling and controlling of such robots present significant challenges, including the complexity of the coupling between actuation inputs, difficulties in modelling friction between the rods and spacers, particularly when the robot is bent, and the challenge of determining model parameters and the mechanical characteristics of the backbones.

In this paper, we intend to utilize a limited dataset to model the behavior of the robot. The dataset was generated by an experienced operator who performed a series of demonstrations using the robot. The operator manipulated the lengths of the rods to move the tip in various directions. The demonstrations were conducted with the rods being pulled/pushed up to 3mm. The feasible kinematic space and demonstration space are depicted in Figure 1. As it is shown, the demonstration space is significantly smaller compared to the feasible kinematic space. The robot inputs, $u_t \in \mathbb{R}^3$, and the corresponding Cartesian coordinates of the robot tip, $x_t \in \mathbb{R}^3$, were recorded at a rate of 15 Hz to generate the training dataset, i.e., $\mathcal{D} = \{x_t^k, u_t^k\}_{k=1}^N$. The position of the robot was estimated using an RGB camera, as discussed in Section 3. It is noteworthy that generating this dataset was efficient and took less than 10 minutes, and our dataset contains N=9100 samples. Only 25 points randomly selected from this dataset will be used to model the robot in the next section, while the remaining data was utilized to train other state-of-the-art machine learning algorithms for comparison.

2.2 Learning Differential Kinematics of the Robot

We assume that the robot's behavior can be modeled by a series of nonlinear differential equations:

$$\dot{x}(t) = f(x(t), u(t)),$$
$$f : \mathbb{R}^3 \times \mathbb{R}^3 \to \mathbb{R}^3 \tag{1}$$

with the initial conditions specified as follows:

$$x(t_0) = x(0),$$
$$u(t_0) = u(0). \tag{2}$$

It is assumed that a closed-form expression for the function f does not exist. One can use two consecutive states and an action to train a multilayer perceptron (MLP) ($\{x_t, u_t\} \to x_{t+1}$) or a Recurrent neural network (RNN) like nonlinear auto-regressive network with exogenous inputs (NARX). MLPs and NARX models work well on the range of training data but they may struggle with extrapolation, especially if the data lies outside the range of the training data. Additionally, MLPs and NARX models, which typically operate in a discrete-time fashion, may produce predictions that exhibit discontinuities between time steps, leading to less smooth or less physically plausible extrapolations [18].

To overcome these limitations, and to develop a continuous and smooth data-efficient neural network to approximate the robot's model, we formulated the problem as an Augmented Neural ODE (ANODE) [19] which models the continuous kinematics of the system and can naturally extend predictions beyond the observed data and time span [18]. In order to prevent trajectories from intersecting, we expand the learning and solution space of the ODE from $\mathbb{R}^3 \times \mathbb{R}^3 \to \mathbb{R}^3$ to $\mathbb{R}^3 \times \mathbb{R}^{3+p} \to \mathbb{R}^{3+p}$. By concatenating a vector of zeros ($0_{p \times 1}$) to each data point, we solve the ODE in this augmented space. This augmentation leads to a smoother learned function f, resulting in simpler flows that can be computed by the ODE solver in fewer steps. Additionally, it allows the ODE flow to lift points into the extra dimensions, effectively preventing trajectory intersections. This continuous-time formulation allows the model to capture the underlying dynamics and make reasonable extrapolations based on the learned ODEs [19]. With the objective in mind, we proceed to discretize the robot model described in (1) and transform it into a boundary value problem:

$$x^+ = f_\theta(x(t), u(t)), \tag{3}$$

based on the following boundary conditions:

$$
\begin{aligned}
\boldsymbol{x}_0 &= \boldsymbol{x}(t_0), \ \boldsymbol{u}_0 = \boldsymbol{u}(t_k), \\
\boldsymbol{x}_k &= \boldsymbol{x}(t_k), \ \boldsymbol{u}_k = \boldsymbol{u}(t_k),
\end{aligned}
\tag{4}
$$

considering the neural network f_θ as an approximation of the function f, we can determine the solution of $\boldsymbol{x}(t_k)$ if we have prior knowledge of f_θ:

$$
\boldsymbol{x}(t_k) = \boldsymbol{x}(t_{k-1}) + \int_{t_{k-1}}^{t_k} f_\theta(x(t), u(t)) dt,
\tag{5}
$$

thus, conventional numerical ODE solvers like the Euler or Runge-Kutta algorithms can be utilized to estimate the value of $\boldsymbol{x}(t_k)$:

$$
\hat{\boldsymbol{x}}(t_k) = \text{ODESolver}(f_\theta, \boldsymbol{x}(t_{k-1}), (t_{k-1}, t_k)).
\tag{6}
$$

However, in cases where f_θ is imprecise or remains unknown, it becomes possible to assess the error in estimating the boundary values:

$$
\ell = \|\hat{\boldsymbol{x}}(t_k) - \boldsymbol{x}(t_k)\|.
\tag{7}
$$

To update this model, f_θ, we adopt a random selection approach, where only 25 points are chosen from the generated dataset. At each training step, a single point from the dataset is selected. The loss function is estimated using equations (3-7). This error is utilized in a supervised learning manner, and the model is trained using the adjoint sensitivity method [20] to ensure memory efficiency. It is important to note that, based on equation (4), the control inputs remain constant, denoted as $\boldsymbol{u}_0 = \boldsymbol{u}_k$, during each training step. To enhance learning efficiency, we have disregarded the dynamics of the control inputs (i.e., $\dot{\boldsymbol{u}} = 0$) and focused solely on learning the input-output dynamics. Details of training and network architecture are presented in our supplementary material.

2.3 Controller Architecture

In this section, we present a robot control methodology that utilizes the trained model, f_θ, to steer the robot towards arbitrary trajectories in accordance with non-convex cost objectives. The proposed approach is a derivative-free, sampling-based Model Predictive Control (MPC) technique, known as the Model Predictive Path Integral (MPPI) controller, which is capable of handling nonlinear dynamics and non-convex cost objectives [21].

First, a Jacobian matrix, denoted as $\mathbf{J}$, is defined through the utilization of the trained model, f_θ, which maps the velocity of the robot's end-effector to the corresponding velocities in the configuration space:

$$
\dot{\boldsymbol{x}} = \mathbf{J}\dot{\boldsymbol{u}},
\tag{8}
$$

where $\mathbf{J}$ is a 3×3 matrix, $\boldsymbol{x} \in \mathbb{R}^3$ and $\boldsymbol{u} \in \mathbb{R}^3$ represent the robot's end-effector Cartesian coordinates and the input space, respectively. In this work, we employ a numerical estimate of the Jacobian using finite difference method and batch sampling from the trained model. Now, using (8), a discrete-time stochastic dynamical system can be obtained:

$$
\boldsymbol{x}_{t+1} = \boldsymbol{x}_t + \mathbf{J}(\dot{\boldsymbol{u}}_t + \delta\dot{\boldsymbol{u}}_t)
\tag{9}
$$

where $\delta\dot{\boldsymbol{u}}_t$ is the control input update which represents by a zero-mean Gaussian noise vector with a variance of $\Sigma_{\boldsymbol{u}}$ ($\delta\boldsymbol{u}_t \sim \mathcal{N}(\boldsymbol{0}, \Sigma_{\boldsymbol{u}})$). Using (9), the control problem can be formulated as a stochastic optimal control problem. Given a finite time-horizon, $t \in \{0, 1, 2, ..., T-1\}$, the objective of the controller is to determine an optimal control sequence, $u = (\boldsymbol{u}_0, \boldsymbol{u}_1, ..., \boldsymbol{u}_{T-1}) \in \mathbb{R}^{m \times T}$, that minimizes the expected cost-to-go, $S(\tau)$, across all possible system trajectories, $\tau = \{\boldsymbol{x}_0, \boldsymbol{u}_0, \boldsymbol{x}_1, ..., \boldsymbol{u}_{T-1}, \boldsymbol{x}_T\}$, with respect to (9), by taking into account the state-dependent cost function, $S(\tau) \in \mathbb{R}$:

$$
J = \min_{\boldsymbol{u}} \mathbb{E}\left[\phi(\boldsymbol{x}_T) + \sum_{t=0}^{T-1}\left(q(\boldsymbol{x}_t) + \frac{1}{2}\boldsymbol{u}_t^T\mathbf{R}\boldsymbol{u}_t \right) \right],
\tag{10}
$$

where $\phi(\boldsymbol{x}_T)$ is the terminal cost, $q(\boldsymbol{x}_t)$ represents running cost and $\mathbf{R} \in \mathbb{R}^{m \times m}$ denotes a positive definite control weight matrix. In order to solve this optimization problem, we adopt an iterative

update law, as derived in reference [21], for the implementation of the Model Predictive Path Integral (MPPI) algorithm. This algorithm iteratively updates the control sequence for a predefined time horizon, utilizing a successive approximation approach:

$$\boldsymbol{u}_t \leftarrow \boldsymbol{u}_t + \frac{\sum_{k=1}^{K} exp\left(-(1/\lambda)\tilde{S}(\tau_{t,k})\right)\delta\boldsymbol{u}_{t,k}}{\sum_{k=1}^{K} exp\left(-(1/\lambda)\tilde{S}(\tau_{t,k})\right)}, \tag{11}$$

where K represents the number of samples, $\tilde{S}(\tau_{t,k}) = \phi(\boldsymbol{x}_T) + \sum_{t=0}^{T-1} \tilde{q}(\boldsymbol{x}_t, \boldsymbol{u}_t, \delta\boldsymbol{u}_t)$ is a cost-to-go of the k^{th} sample, and $\lambda \in \mathbb{R}^+$ is a hyperparameter called inverse temperature. The cost-to-go function serves as a critical component in guiding the robot's decision-making process, incorporating multiple objectives such as tracking a reference trajectory, obstacle avoidance, and considering affordance. By evaluating the future costs associated with different control inputs, the cost-to-go function allows the robot to anticipate the consequences of its actions. It considers the desired trajectory as a reference, aiming to minimize the deviation from this path while accounting for the presence of obstacles. Furthermore, the cost-to-go function can take into account the concept of affordance which encode the relationships between actions, objects, and their resulting effects [22], so that enables the robot to assess its capabilities and exploit the available opportunities for safe and efficient navigation.

By considering these aspects within the cost-to-go function, MPPI facilitates the generation of control policies that effectively balance trajectory tracking, obstacle avoidance, and the utilization of affordance to optimize the robot's performance in complex environments. The architecture of the proposed controller is depicted in Figure 1 (right). In the next section, a set of experiments has been designed and conducted to assess the performance, robustness, and safety of the proposed method.

Figure 2: Experiment setup.

3 Experiments

Here, a series of experiments were conducted to assess the effectiveness of the proposed approach across various scenarios. Figure 2 shows the experimental arrangement employed in our study, comprising a flexible and expandable soft manipulator, a Logitech RGB camera positioned within the robot's workspace, and a user interface for recording, initiating, and terminating the experiments. To enable the camera to detect the position of the robot's tip, an ArUco marker [23, 24] is affixed to the tip of the robot, providing feedback to the control loop. Details of the robot, the hyper parameters, the controller configuration, and the network structure can be found in the supplementary material.

3.1 Experiment Design

A series of experiments have been conducted to assess the effectiveness of the proposed framework:

- **Static Target Tracking:** ten different targets are pre-defined within the robot's workspace. The objective is for the robot to reach these targets with minimal positional error.

- **Trajectory Tracking:** the robot is set to track various trajectories in both 2D and 3D space, which include: **i)** a square on the X-Y plane with sides measuring 0.06 m; **ii)** A circular shape in the XY plane with a radius measuring 0.03 meters; **iii)** A triangle with all sides measuring 0.06 meters; **iv)** An eight-shaped curve defined by the equations $x = a\cos\left(\frac{2t\pi}{T}\right)$ and $y = \frac{b}{2}\sin\left(\frac{4t\pi}{T}\right)$, where $a = 0.03$, $b = 0.05$, $T = 100$ seconds, and t ranges from 0 to 120 seconds; **v)** A helical trajectory is executed along the Z-axis, characterized by a radius of 0.03 m and a pitch of 0.02 m. To assess the tracking's repeatability and accuracy, three trials are conducted for each trajectory.

- **Obstacle Avoidance:** In this task, the robot is set to track a helix trajectory characterized by a radius of 0.03 m and a pitch of 0.02 m which is near the border of its feasible kinematic space.

Figure 3: Trajectory tracking results: the robot is set to track diverse trajectories in both two-dimensional (2D) and three-dimensional (3D) space. The solid-red and the dashed-black lines represent the actual and desired trajectories, respectively.

The objective of this task is to show how safely the robot is tracking the desired trajectory while avoiding obstacles without being unstable.

• **Box Opening and Test Tube Manipulation:** To showcase a potential application of the robot and the controller's adeptness at incorporating affordance in object manipulation during environmental interactions, we have designed a demanding teleoperation task consists of two sub-tasks: opening the box and picking and placing the test tubes into the box. In this task, the operator's objective is to maneuver the robot to open the lid of a wooden box, taking into consideration that the robot lacks the strength to counteract the force of gravity and fully extend the lid. This challenging scenario serves as a compelling demonstration of the controller's ability to effectively utilize affordance while navigating the complexities of object manipulation in real-world environments. Once the lid is opened, the operator should pick tubes from the racks and place them into the box.

3.2 Results and Discussions

In the context of static target tracking, the robot's performance is assessed based on three metrics: steady-state error (SSE), standard deviation (σ), and settling time (ST). The obtained results are showcased in Table 1. It is noteworthy that the position error remains

Table 1: Static Target Tracking Results

	SSE (mm)	σ (mm)	ST (sec)
$\tilde{x}$	0.82	0.68	5.72
$\tilde{y}$	0.71	0.58	4.21
$\tilde{z}$	0.37	0.32	3.82
$\tilde{X}$	**0.63**	**0.52**	**4.58**

below the threshold of 1 mm. Additionally, the consistently low standard deviation reveals a stable error pattern observed throughout all experiments.

In trajectory tracking experiments, the evaluation of the robot's performance involves the calculation and presentation of the root mean squared error (RMSE) and standard deviation (σ) of the error across five distinct trials. These metrics, along with a visual depiction in Figure 3, provide a comparative analysis between the robot's actual tip trajectory and the desired trajectory. Notably, the robot successfully tracks various shapes, including square, limacon, rose, helix, and square helix, with a maximum RMSE of 3.2×10^{-3} m. Results are summarised in Table 2.

Representative results depicted in Figure 4 showcase the effectiveness of the MPPI algorithm in achieving obstacle avoidance while simultaneously maintaining stable tracking of the desired trajectories. In our implementation, the running cost is the sum of the individual cost terms including a term for tracking a reference trajectory, a term for avoiding obstacles, and a term for penalizing jerky motions (details are presented in the supplementary material). The

Table 2: Trajectory Tracking Results

	RMSE (mm)			σ (mm)		
	$\tilde{x}$	$\tilde{y}$	$\tilde{z}$	$\tilde{x}$	$\tilde{y}$	$\tilde{z}$
Square	2.40	2.60	2.50	1.40	1.50	1.30
Circle	2.80	3.20	3.10	0.51	1.50	1.50
Triangle	1.10	1.10	1.60	0.90	0.90	1.50
Eight	2.00	2.10	2.50	0.50	0.50	1.50
Helix	1.10	1.10	1.80	0.52	1.50	0.61

running cost plays a vital role in guiding the robot's behavior by influencing the control actions to minimize deviations and ensure a safe and efficient path. By incorporating the position of the obstacles into the running cost, the robot can effectively evaluate the consequences of its actions and make decisions that prioritize obstacle avoidance and trajectory tracking. This approach enables the robot to dynamically adjust its control inputs based on real-time feedback, resulting in reliable and robust performance even in complex scenarios.

Figure 4: Representative results of obstacle avoidance experiments. Blue dots represent the obstacles, solid-red and dashed-black lines are the actual and reference trajectories, respectively.

Figure 5: This set of snapshots illustrates the box opening and test tube manipulation task. In this particular task, the operator's objective is to guide the robot in opening the lid of the box and subsequently picking and placing the tubes into the designated racks.

In the Box Opening and Test Tube Manipulation task, the robot operates in a unidirectional teleoperation mode, where the designed controller enables it to track targets specified by an operator through keyboard input. The complexity of this task arises primarily from the absence of direct force feedback, the disparity in kinematics between control interfaces and the robot, the delayed response time, and the lag between the operator's commands and the robot's actions. To address these challenges, we incorporate a set of affordance terms into the running cost of the controllers (details are provided in supplementary material). These affordance terms can be selectively activated or deactivated by the operator to limit the motion of the robot along one direction deemed suitable to accomplish the task (i.e, x, y, or z), depending on the task phase. The versatility of MPPI, which can handle non-convex running costs, allows us to effectively utilize these affordance terms for a more intuitive and context-aware interaction between the operator, the robot, and the environment, enabling more effective and efficient teleoperation. Results are presented in the supplementary multimedia file and Figure 5 shows a set of snapshots of this task. The results of this task provide insights into the capabilities of the robot and the effectiveness of the controller in incorporating affordance for object manipulation in real-world environments.

4 Ablation and Comparison Study

In this section, we conduct an ablation study to thoroughly compare the performance of the proposed ANODE-based forward kinematics model with Feedforward Neural Network (FNN) and Recurrent Neural Network (RNN) based models in four distinct scenarios. We assess the performance of the models in open-loop and closed-loop trajectory tracking scenarios for both unseen-before and seen-before scenarios, providing a comprehensive analysis of their strengths and limitations. In the open-loop scenarios, we opted to exclude the MPPI controller and instead utilized a simplified approach. Specifically, we employed the equation ($\dot{\mathbf{u}} = \mathbf{J}^+\dot{\mathbf{x}}$), where $\mathbf{J}^+$ represents the pseudo-inverse of the Jacobian and $\dot{\mathbf{x}}$ is the reference trajectory. By implementing this modified strategy, we aimed to observe the system's response without the influence of the MPPI controller, focusing solely on the FK models. In the seen-before scenario, the robot was tasked with tracking an eight-trajectory in X-Y plane within the demonstration space. Conversely, in the unseen-before scenario, the robot was challenged to track a 3D eight-trajectory spanning the entire feasible kinematic space. These distinct scenarios were designed to assess the robot's ability to adapt and generalize its knowledge across different dimensions and spatial configurations. By evaluating its performance in both seen and unseen trajectories, we gain valuable insights into the framework's capacity to handle novel situations and extrapolate its learned behaviors to unfamiliar scenarios (details of the reference trajectories are presented in supplementary material).

Furthermore, by comparing ANODE's performance with the traditional MLP and RNN models, we aim to highlight the unique advantages of the ANODE model in capturing the underlying dynamics and temporal dependencies inherent in soft robot forward kinematics pre-

Figure 6: Results of the ablation study: the dashed-black lines, the solid-red and solid-blue lines correspond to the reference, closed-loop and open-loop actual trajectories, respectively.

diction. The FNN is constructed with multilayer perceptrons (MLP) to map the input u_t to the output x_t. On the other hand, the RNN adopts a NARX architecture, which takes the current state (x_t, u_t) as input and predicts the subsequent state x_{t+1}. Both the FNN and RNN models are trained using the dataset $\mathcal{D}$ generated in accordance with the methodology described in Section 2, employing mean square error as their respective loss functions.

To ensure a fair and equitable comparison, we maintained consistent network sizes across all methods. We trained three distinct FK models and integrated them within the identical control loop framework depicted in Figure 1 (right). To evaluate and contrast their respective performances, we computed the RMSE and standard deviation (σ) of errors across five trials, summarizing the outcomes in Table 3. Representative outcomes are visually depicted in Figure 6,

Table 3: Ablation and comparison results of trajectory tracking scenarios; -O/-C tokens refer to open-loop and closed-loop results, respectively.

		RMSE (mm)			σ (mm)		
		$\tilde{x}$	$\tilde{y}$	$\tilde{z}$	$\tilde{x}$	$\tilde{y}$	$\tilde{z}$
seen	MLP-C	0.531	0.548	0.570	0.531	0.548	0.869
	MLP-O	0.572	0.563	0.702	0.557	0.543	0.494
	RNN-C	0.542	0.537	5.100	0.541	0.537	0.498
	RNN-O	0.576	0.546	5.000	0.544	0.540	0.419
	ANODE-C	**0.105**	**0.127**	**0.116**	**0.105**	**0.127**	**0.116**
	ANODE-O	**0.198**	**0.177**	**0.122**	**0.198**	**0.177**	**0.121**
unseen	MLP-RNN-(C/O)	-	-	-	-	-	-
	ANODE-C	**0.256**	**0.164**	**0.157**	**0.256**	**0.164**	**0.157**
	ANODE-O	**5.600**	**3.100**	**4.900**	**4.700**	**1.800**	**2.900**

providing further insights into the trajectory-tracking capabilities of each model. As depicted in this figure, all the models demonstrated proficiency in successfully accomplishing the seen-before scenario. Notably, among the tested methods, the ANODE(both open/closed loop versions) showcased superior performance, outperforming the other models in accurately accomplishing the task. In the unseen-before scenario, ANODE stood out as the only model capable of effectively generalizing its knowledge and successfully accomplishing the task. On the other hand, the MLP and RNN models encountered difficulties, leading to the robot becoming uncontrollable. The results showed that the proposed method outperformed alternative approaches significantly in unseen-before scenarios and performed slightly better in seen-before scenarios.

5   Conclusion and Limitations

This paper introduced a new method for modelling the continuous forward kinematic models of soft continuum robots using ANODE. The proposed method only required 25 scattered data points. Additionally, we developed a parallel MPPI-based controller running on a GPU, which effectively handles a non-convex objective function. This design enhances the adaptability and robustness of the learned model, enabling accurate prediction and control of soft continuum robot motion in various new scenarios. Through extensive experimentation, ablation, and comparison studies, our proposed framework (ANODE+MPPI) exhibits superior performance over learning-based approaches like FNN and RNN in unseen-before scenarios. It also slightly outperforms them in seen-before settings. While these results are promising, there are some challenges and limitations. The soft robot manipulator being studied has a limited input space comprising three variables. However, when applied to more complex robotic systems characterized by higher dimensions, the Neural ODEs encounters certain limitations. Specifically, the computational costs associated with training Neural ODEs become more challenging. This is attributed to the time-consuming nature of the forward pass, which necessitates the numerical integration of an ODE. Additionally, the proposed methodology assumes the presence of continuous dynamics within the robot, rendering it less suitable for effectively modelling soft robots that exhibit sudden changes, instabilities, or discontinuities in their behaviour.

References

[1] C. Lee, M. Kim, Y. J. Kim, N. Hong, S. Ryu, H. J. Kim, and S. Kim. Soft robot review. *International Journal of Control, Automation and Systems*, 15(1):3–15, Feb 2017.

[2] G. Mengaldo, F. Renda, S. L. Brunton, M. Bächer, M. Calisti, C. Duriez, G. S. Chirikjian, and C. Laschi. A concise guide to modelling the physics of embodied intelligence in soft robotics. *Nature Reviews Physics*, 4(9):595–610, Sept. 2022.

[3] C. Della Santina and D. Rus. Control oriented modeling of soft robots: the polynomial curvature case. *IEEE Robotics and Automation Letters*, 5(2):290–298, 2019.

[4] R. K. Katzschmann, M. Thieffry, O. Goury, A. Kruszewski, T.-M. Guerra, C. Duriez, and D. Rus. Dynamically closed-loop controlled soft robotic arm using a reduced order finite element model with state observer. In *2019 2nd IEEE international conference on soft robotics (RoboSoft)*, pages 717–724. IEEE, 2019.

[5] C. Della Santina, R. K. Katzschmann, A. Biechi, and D. Rus. Dynamic control of soft robots interacting with the environment. In *2018 IEEE International Conference on Soft Robotics (RoboSoft)*, pages 46–53. IEEE, 2018.

[6] C. Della Santina, R. K. Katzschmann, A. Bicchi, and D. Rus. Model-based dynamic feedback control of a planar soft robot: trajectory tracking and interaction with the environment. *The International Journal of Robotics Research*, 39(4):490–513, 2020.

[7] C. Armanini, C. Messer, A. T. Mathew, F. Boyer, C. Duriez, and F. Renda. Soft robots modeling: a literature unwinding, 2021.

[8] B. Thamo, F. Alambeigi, K. Dhaliwal, and M. Khadem. A hybrid dual jacobian approach for autonomous control of concentric tube robots in unknown constrained environments. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 2809–2815, 2021. doi:10.1109/IROS51168.2021.9636085.

[9] J. M. Bern, Y. Schnider, P. Banzet, N. Kumar, and S. Coros. Soft robot control with a learned differentiable model. In *2020 3rd IEEE International Conference on Soft Robotics (RoboSoft)*, pages 417–423. IEEE, 2020.

[10] T. G. Thuruthel, E. Falotico, F. Renda, and C. Laschi. Learning dynamic models for open loop predictive control of soft robotic manipulators. *Bioinspiration & biomimetics*, 12(6):066003, 2017.

[11] D. Bruder, C. D. Remy, and R. Vasudevan. Nonlinear system identification of soft robot dynamics using koopman operator theory. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 6244–6250. IEEE, 2019.

[12] R. Morimoto, S. Nishikawa, R. Niiyama, and Y. Kuniyoshi. Model-free reinforcement learning with ensemble for a soft continuum robot arm. In *2021 IEEE 4th International Conference on Soft Robotics (RoboSoft)*, pages 141–148. IEEE, 2021.

[13] D. Büchler, S. Guist, R. Calandra, V. Berenz, B. Schölkopf, and J. Peters. Learning to play table tennis from scratch using muscular robots. *IEEE Transactions on Robotics*, 2022.

[14] T. G. Thuruthel, E. Falotico, F. Renda, and C. Laschi. Model-based reinforcement learning for closed-loop dynamic control of soft robotic manipulators. *IEEE Transactions on Robotics*, 35 (1):124–134, 2018.

[15] T. George Thuruthel, F. Renda, and F. Iida. First-order dynamic modeling and control of soft robots. *Frontiers in Robotics and AI*, 7:95, 2020.

[16] G. Fang, Y. Tian, Z.-X. Yang, J. M. Geraedts, and C. C. Wang. Efficient jacobian-based inverse kinematics with sim-to-real transfer of soft robots by learning. *IEEE/ASME Transactions on Mechatronics*, 2022.

[17] W. Xu, J. Chen, H. Y. Lau, and H. Ren. Data-driven methods towards learning the highly nonlinear inverse kinematics of tendon-driven surgical manipulators. *The International Journal of Medical Robotics and Computer Assisted Surgery*, 13(3):e1774, 2017.

[18] R. T. Chen, Y. Rubanova, J. Bettencourt, and D. K. Duvenaud. Neural ordinary differential equations. *Advances in neural information processing systems*, 31, 2018.

[19] E. Dupont, A. Doucet, and Y. W. Teh. Augmented neural odes. *Advances in neural information processing systems*, 32, 2019.

[20] L. S. Pontryagin. *Mathematical theory of optimal processes*. CRC press, 1987.

[21] G. Williams, A. Aldrich, and E. A. Theodorou. Model predictive path integral control: From theory to parallel computation. *Journal of Guidance, Control, and Dynamics*, 40(2):344–357, 2017.

[22] L. Montesano, M. Lopes, A. Bernardino, and J. Santos-Victor. Learning object affordances: from sensory–motor coordination to imitation. *IEEE Transactions on Robotics*, 24(1):15–26, 2008.

[23] S. Garrido-Jurado, R. M. noz Salinas, F. Madrid-Cuevas, and M. Marín-Jiménez. Automatic generation and detection of highly reliable fiducial markers under occlusion. *Pattern Recognition*, 47(6):2280 – 2292, 2014. ISSN 0031-3203. doi:http://dx.doi.org/10.1016/j.patcog.2014.01.005. URL http://www.sciencedirect.com/science/article/pii/S0031320314000235.

[24] S. Garrido-Jurado, R. M. noz Salinas, F. Madrid-Cuevas, and R. Medina-Carnicer. Generation of fiducial marker dictionaries using mixed integer linear programming. *Pattern Recognition*, 51:481 – 491, 2016. ISSN 0031-3203. doi:http://dx.doi.org/10.1016/j.patcog.2015.09.023. URL http://www.sciencedirect.com/science/article/pii/S0031320315003544.