iPTR: Learning a representation for Interactive program translation retrieval

Abstract

Program translation contributes to many real world scenarios, such as porting codebases written in an obsolete or deprecated language to a modern one or re-implementing existing projects in one's preferred programming language. Existing data-driven approaches either require large amounts of training data or neglect significant characteristics of programs. In this paper, we present iPTR for interactive code translation retrieval from Big Code. iPTR uses a novel code representation technique that encodes structural characteristics of a program and a predictive transformation technique to transform the representation into the target programming language. The transformed representation is used for code retrieval from Big Code. With our succinct representation, the user can easily update and correct the returned results to improve the retrieval process. Our experiments show that iPTR outperforms supervised baselines in terms of program accuracy.

1 Introduction

Numerous programs are being developed and released online. To port codebases written in obsolete or deprecated languages to a modern one (Lachaux et al., 2020), or to further study, reproduce and apply them on various platforms, these programs require corresponding versions in different languages. In cases when developers do not make the translation efforts themselves, third-party users have to manually translate the software to their needed language, which is time consuming and error prone because they have to be the expert in both languages. Also, hard-wired cross-language compilers still require heavy human intervention for adaptation and are limited between some specified types of programming. In this paper, we discuss the potentials of data-driven methods that exploit existing big code resources to support code translation. The abundance of open source programs on the internet provides opportunities for new applications, such as workflow generation (Derakhshan et al., 2020), data preparation (Yan & He, 2020), and transformation retrieval (Yan & He, 2018). Code translation is another application that is gaining attention (Lachaux et al., 2020).

Data-driven program translation. Inspired by natural language translation, one line of approaches trains a translation model from large amounts of code data either in a supervised (Nguyen et al., 2013; 2015; Chen et al., 2018) or weakly-supervised fashion (Lachaux et al., 2020). Supervised approaches require a *parallel dataset* to train the translation model. In parallel datasets, programs in different languages are considered to be "semantically aligned". Obtaining the parallel datasets in programming languages is hard because the translations have to be handwritten most of the time. Besides massive human efforts, it is also a tricky problem to extract general textual features that apply to every programming language. A recent weakly-supervised method (Lachaux et al., 2020) pretrains the translation model on the task of denoising randomly corrupted programs and optimizes the model through back-translation. However, this method still relies on high-quality training data. Further, all these approaches directly reuse NLP approaches that neglect the special features of programming languages. Another potential approach is to use a retrieval system to obtain translation candidates directly from Big Code, which refers to well-maintained program repositories. However, existing code retrieval systems, such as Sourcerer (Linstead et al., 2009), lack the proper capabilities for code-to-code search and cross-language code retrieval. These methods ask users to give feedback on several preset metrics and questions (Wang et al., 2014; Dietrich et al., 2013; Martie et al., 2015; Sivaraman et al., 2019). None of these methods is tailored to cross-language retrieval.

In this paper, we propose an interactive program translation retrieval system IPTR based on a novel and generalizable code representation that retains important code properties. The representation not only encodes textual features but structural features that can be generalized across all imperative programming languages. We further propose a query transformation model based on autoencoders to transform the input program representation to a representation that has properties of the target language. Due to the succinct form of our code representation, IPTR can adapt the original query based on user annotations. This methodology can compete with existing statistical translation models that require a large amount of training data. In short, we make the **following main contributions**:

- We propose IPTR, an interactive cross-language code retrieval system with a program feature representation that additionally encodes code structure properties.
- We further propose a novel query transformation model that learns a refined code representation in the target language before using it for retrieval. This model can be trained in an unsupervised way but also improved through active learning.
- Based on our succinct code representation, we propose a user feedback mechanism that enables IPTR to successively improve its results.

2 SYSTEM OVERVIEW

We propose IPTR, an interactive cross language code retrieval system that supports program translation on multiple programming languages.

Problem Definition. Given a piece of source program P_s written in language L_s, a selected target language L_t, and a large program repository $D_p = \{P_1, P_2, ..., P_n\}$, the goal is to find the best possible translation P_t of P_s in L_t from D_p. The problem is to design an effective program feature representation that generalizes to many languages and can be updated through user feedback.

Our solution: IPTR The workflow of IPTR is shown in Figure 1. IPTR first constructs a succinct but informative feature representation for input programs (Section 3.1). Since the target is to identify a similar program in the target language, IPTR then applies a query transformation model (QTM) to transform this representation into an estimated feature representation of the translation (Section 3). The transformation model is trained in an unsupervised manner but can also be updated dynamically through active learning (Section 3.2.2). Finally, this new representation will be used as a query to retrieve the program that has similar features from the database. In addition, as an interactive system, IPTR allows the user to give feedback on the retrieved translation (Section 4). The user can either accept the result or make corrections. Based on our structured and informative feature representation, IPTR can easily and quickly adapt the query based on raw user corrections. Then with the new query, it may identify a more appropriate translation candidate in the second retrieval attempt.

Figure 1: IPTR overview

3 PROGRAM REPRESENTATION

To retrieve a promising program translation from a large code database, IPTR needs an effective and efficient query. Directly retrieving based on raw code is impractical. In contrast to existing methods that generate queries based on either keywords (Linstead et al., 2009) or preset metrics and questions (Martie et al., 2015), IPTR generates a feature representation that effectively combines structural properties of the program and textual features. It further uses a query transformation model (QTM) to generate features in the target language.

3.1 BASIC ENCODING OF PROGRAM STRUCTURE AND TEXT

Due to the special and non-trival structure of programming languages compared to natural languages, we take both structural and textual features into consideration. The structural features of a program can be represented by its syntax tree where each tree node denotes a code construct. The

Figure 2: Program representation

tree can be either a concrete syntax tree (CST) or an abstract syntax tree (AST) (Alon et al., 2018; 2019; Chen et al., 2018). A CST depicts nodes with complete structural information, such as all the tokens in the code while the AST is more abstract and only displays structural or content-related details. For more details on CSTs and ASTs, we provide examples in the Appendix A.2.

As the CST is quite verbose and the AST does not generalize to multiple languages, we fall back on the low-level CST as a basis, and take the philosophy of AST as an inspiration to construct a unified abstract representation. Specifically, IPTR first simplifies the CST by removing semantically repetitive nodes such as `equalityExpression` and `==` and intermediate nodes and generates a more simplified but still informative syntax tree. As shown in Figure 2, a piece of Javascript code is first converted into a simplified syntax tree (details of simplifying CST are shown in Appendix A.2). Inspired by prior work (Alon et al., 2018), IPTR further simplifies it by extracting a set of one-dimensional paths that connect the program elements of the two-dimensional tree. Our method abstracts these paths by only keeping the three nodes that enclose the most critical information on a path: for each pair of leaf-nodes in the CST, IPTR keeps the nodes with their values and the root node of the statement. It drops all other intermediate nodes on this path. The extracted abstract paths of the JavaScript Program example are also shown in Figure 2. By simply matching nodes with similar names from different languages, IPTR can classify these paths into different types and generalize them to multiple programming languages. Thus, the structural feature of a program can be succinctly represented by the different types of paths $p_1, p_2, ..., p_j$ it contains.

To additionally incorporate textual features, IPTR treats extracted paths as plain text and keeps all the text tokens $t_1, t_2, ..., t_k$ appearing in each extracted path to generate text features. Finally, we can use these tokens (textual features) together with different types of paths (structural features) illustrated above as feature elements of programs. For each input program, we generate a feature vector consisting of the feature element frequencies in that program. Let f be the occurrence frequency of feature elements, then the final feature representation will be $[f_{e_1}, f_{e_2}, ..., f_{e_n}] = [f_{p_1}, f_{p_2}, ..., f_{p_{n_p}}, f_{t_1}, f_{t_2}, ..., f_{t_{n_t}}]$. These elements can also be used as index keys to filter the database, and by calculating the similarity of feature vectors IPTR can retrieve the most similar program in target language, which is the translation candidate.

3.2 QUERY TRANSFORMATION MODEL

We can directly use the feature vector described in Section 3.1 as a query to retrieve translation candidate. However, the feature vector will still fail to accommodate some cross languages hurdles. For example, C# supports `goto` statement while its Java translation has to use `break` or `continue` with label instead of `goto`. In this case, IPTR cannot directly use the features of C# program to retrieve its Java translation. The result can be improved if the retrieval can be conducted based on the features of the translation. While translation of a complete program is our original problem and hard to solve, we propose a query transformation model (QTM) that solves a smaller problem. QTM transforms the original query (feature vector of the input program) into an optimized query (estimated feature vector of the translation). While the estimated feature vector is not a full program it is a better estimate for finding the correct program in the database.

3.2.1 MODEL DESCRIPTION

As shown on the left of Figure 3, in the online phase, to translate from language L_s to language L_t, IPTR extracts the features as F_s of a program from source language L_s and feeds it into the QTM. In the QTM, a one layer encoder (red in Figure 3) maps the original feature vector to a low dimensional latent space and produces a shorter hidden vector H. Then H is reconstructed to the estimated translation feature vector F_t by a one layer decoder (yellow in Figure 3). F_t will be used as query to retrieve potential translation in target language L_t.

Since there is no available training data for QTM, we leverage an unsupervised method - autoencoder (AE) to train the encoder and the decoder. An AE is an encoder-decoder that aims to reproduce its input. That is, it encodes the input to a hidden vector, then reconstructs the input from this hidden vector. In IPTR, we exploit this property to learn the weights of the encoders and decoders separately. As shown on the right of Figure 3, in the offline phase, for each programming language L_i in the database IPTR trains a separate AE_i on all programs that are written in this language. Thus it obtains a pair of $Encoder_i$ and $Decoder_i$ for each programming language. For the actual translation task, we combine the

Figure 3: Query transformation model (QTM)

appropriate encoder and decoders depending on the source and target language of a translation task. We can see in the QTM in Figure 3, it selects the encoder $Encoder_s$ of the source language L_s from AE_s, which is trained in offline phase, to transform F_s into the hidden layer representation. And it picks the trained decoder $Decoder_t$ of the target language L_t from AE_t to estimate the F_t. This way, we can build a pretrained model with an encoder that learns significant information from the feature vector of the input program and an decoder that can generate features of its translation.

3.2.2 Sampling Strategies for Active Learning

To make the QTM more suitable for specific real-world code data, we also design an active learning mechanism to enable the user to fine-tune the mixed encoder model. As shown in Figure 1, during each translation retrieval, the most useful programs are selected with a sampling strategy for user labeling. IPTR will ask the user to give the correct translation as its label. We propose an aggregation of four sampling strategies to approximate measure the informativeness of the given program:

1. **Coverage sampling.** It picks all programs that cover more than half of the possible feature elements. A program that contains more different feature elements may reveal more information.
2. **Rarity sampling.** Rarity sampling considers programs with rare feature elements, i.e. programs that contain features that appear in at most $\epsilon\%$ of the database programs.
3. **Uncertainty sampling.** Uncertainty sampling picks retrieved programs with low certainty, i.e., lower similarity score than 75%.
4. **Random sampling.** It randomly selects a program for labeling (Zhu et al., 2007).

After running the above four sampling strategies for an input program, IPTR employs query-by-committee method to aggregate the results. The final decision is made by selecting program data where the largest disagreement occurs among those sampling strategies.The level of disagreement of a program x can be measured by vote entropy VE (Dagan & Engelson, 1995):

$$VE(x) = -\frac{V(x)}{N_s}\log\frac{V(x)}{N_s} - \frac{N_s - V(x)}{N_s}\log\frac{N_s - V(x)}{N_s} \tag{1}$$

$V(x)$ is the number of sampling strategies that select/vote x as valuable sample. N_s is the number of sampling strategies, which equals 5 in our case. Programs with higher vote entropy are returned as samples. After a task was successfully completed a new label can be stored for the QTM at hand.

4 Query Adaption based on User Feedback

IPTR can also adapt a query based on user's feedback on returned results to improve the query. Existing interactive code retrieval methods ask the user to give feedback on the preset metrics and questions (Nie et al., 2016; Sivaraman et al., 2019). On contrary, IPTR directly leverages user's corrections to the retrieved results as feedback circumventing the efforts needed to pose the right questions. The simplest form of using the user corrections is to just use the feature vector of the corrected program. However, we also can make use of the fact that user corrections lead to manually curated features. To reflect this in out feature representaion, we extend it with a weighting scheme. As shown in Figure 4, we obtain a new feature representation R, where each element consists of a feature ele-

ment f_{e_i} and its weight w_i. The initial weights are uniform. After the user makes corrections to the result, IPTR featurizes the correction the same way and compares it with the original code to generate the weights. We classify corrections into three categories and the weights are tuned accordingly:

- **Emphasize.** If the correction increases feature element f_{e_i} that already exists in R, the weight of f_{e_i} will be increased.
- **Add.** If the correction adds feature element f_{e_i} that does not exist in R, f_{e_i} and its initial weight w_i will be added into R.
- **Delete.** If the correction decreases feature element f_{e_i} in R, its weight w_i will also be decreased.

Then the feature representation is updated and used for a new round of retrieval. When calculating the similarity between query and instance in database, we consider an instance is better if it has higher similarity in features with high weights.

Figure 4: User feedback mechanism

5 EXPERIMENTS

In this section, we first compare different variations of IPTR with existing work from data-driven program translation and code search. We further evaluate IPTR's performance for different languages and discuss the user feedback. All our experiments are conducted on a PC with an Intel Xeon E5-2650 v2 2.60GHz CPU and an NVIDIA Tesla K40m GPU.

Dataset. Datasets with ground truth are generally scarce. We run our experiments on the parallel dataset used in previous work with ground truth on Java to C# translations (Nguyen et al., 2013; 2015; Chen et al., 2018) and the dataset GeekforGeeks provided by Lachaux et al. (2020). The former was built based on several authoritative open source projects, such as Lucene, ANTLR, and JGit, which have both official Java and C# versions that have been correctly aligned to 39.797 matched methods. The latter gathered and aligned 698 coding problems and their solutions in several programming languages. We train the AEs of QTM on a database generated from the Public Git Archive (PGA) - a database with more than 260,000 top bookmarked Git repositories (web, b). We cleaned the dataset beforehand by gradually removing duplicates at file level, and files that cannot be successfully parsed due to format, errors, version compatibility or other issues. Finally, we obtain a dataset with the size of 260GB. We split all the files into methods or functions.

Metric. To measure effectiveness, we use *program accuracy* as proposed by prior work (Nguyen et al., 2015; Chen et al., 2018). Each time, we pick one program from the dataset and try to retrieve its translation from the database. *Program accuracy* is the percentage of the retrieved translations that are exactly the same as the ground truth in the dataset. Note that, it is an underestimation of the true accuracy based on semantic equivalence. That is, program and its translation should have the same functionality, but minor differences, such as variable names and writing habits, can be tolerated. Since we use a parallel dataset for evaluation, we can directly use the ground truth.

5.1 COMPARISON WITH BASELINES

We compare IPTR with four program translation baselines (**1pSMT** (Nguyen et al., 2013), **mppSMT** (Nguyen et al., 2015), **Tree2tree** (Chen et al., 2018), **TransCoder** (Lachaux et al., 2020)), which use a translation model to generate the results. The supervised baselines use 90% matched method pairs as training data to predict the translations for the rest of programs. We used the openly available implementation of **Tree2tree**. For TransCoder, we follow their method to pre-train the cross-language model on the Public Git Archive dataset (30GB of Java and C# data). For the program translation baselines 1pSMT, mmpSMT and Tree2tree, we report the results from their work on the same dataset as their code and configurations are not available. Finally, we report the results of two code search baselines **Sourcerer** (Linstead et al., 2009) and **CodeHow** (Lv et al., 2015)).

We generate different versions of IPTR with variations in interaction and feature representation:

- **Interative versions**: We discuss three different interactive versions of IPTR. All of which use the same feature representation and the QTM module. IPTR$_{AL+FB}$ is the full fledges interactive

Table 1: Comparison of different methods on program accuracy (PA) and supervision extent

Genre	Method	Description	PA	Supervision Extent
Data-driven program translation	1pSMT	Phrase-based SMT	24.1%	fully supervised
	mmpSMT	multi-phase phrase-based SMT	41.7%	
	Tree2tree	tree-to-tree neural networks	70.1%	
	TransCoder	weakly-supervised neural translation	49.9%	weakly supervised
Code search system	Sourcerer	Lucene-based code search, free-text queries	13.5%	-
	CodeHow	free-text queries	13.5%	
Variations of IPTR	PTR		71.1%	no labels (directly retrieve translation with input)
	PTR$_{\text{WORD2VEC}}$	word2vec as queries	67.7%	
	PTR$_{\text{CODE2VEC}}$	code2vec as queries	63.4%	
	PTR+QTM		78.6%	
	IPTR$_{\text{AL}}$		87.1%	80 labels for QTM
	IPTR$_{\text{FB}}$		79.3%	At most 1 correction per task
	IPTR$_{\text{AL+FB}}$	the full system	**89.6%**	combination of IPTR$_{\text{AL}}$ and IPTR$_{\text{FB}}$

    system with active learning for QTM and user feedback as described in Table 1. IPTR$_{\text{AL}}$ and IPTR$_{\text{FB}}$ only use the active learning component or the user feedback component, respectively.

- **Representions**: PTR refers to the basic program translation retrieval module with the feature vector of input program as query (Section 3.1). PTR+QTM uses the QTM module without active learning on top of PTR. We further analyze PTR$_{\text{WORD2VEC}}$ and PTR$_{\text{CODE2VEC}}$ as two feature representations variations of PTR based on **Code2vec** (Alon et al., 2019) and **Word2vec** (Mikolov et al., 2013), respectively.

Table 1 shows the results and the degree of supervision. We observe that holistic IPTR with at most one user correction per task and optimized QTM outperforms all the baselines. The improvement in program accuracy is ranges from 19.5% to 65.5%. As expected, the code search baselines perform poorly because they are designed for retrieval with more accurate and detailed input than raw program code. The results of partial components of IPTR are also encouraging. PTR and PTR+QTM, which do not leverage any supervision, outperform the **Tree2tree**, which shows the effectiveness of our program feature representation and translation retrieval methodology. Leveraging the QTM successfully improves the result by 7.5% showing that generating features in the target language is more promising than using features of the source language. If the QTM is trained by active learning, the accuracy can increase by 8.5% (IPTR$_{\text{AL}}$). The table also shows that the Word2vec and Code2vec variants of PTR cannot outperform PTR with our proposed feature representation based on structural features. Word2vec is designed for natural languages so that it can not capture the special features of programming languages. Although Code2vec is designed specifically to represent code, their model can only be trained within a same programming language, which makes it less suitable for cross-language similarity comparisons.

We further explored the supervision impact on IPTR. In this experiment, we let the user give at most one correction to each retrieved task. Without optimizing the QTM, IPTR$_{\text{FB}}$ slightly improves on PTR+QTM. The same improvement rate can be observed when comparing IPTR$_{\text{AL+FB}}$ to IPTR$_{\text{AL}}$, suggesting that AL and FB have independent influence on the results. Compared to the fully supervised methods 1pSMT, mmpSMT and Tree2tree, IPTR leverages very limited human supervision to achieve better results. In the first retrieval round, the user does not make correction to any wrong results, IPTR achieves 87.1% accuracy with only 80 labels for QTM. Also the reproduced weakly supervised approach TransCoder does not achieve better results than IPTR. Although some of the performance loss can be contributed to the fact that our training data is not as large as they report in their paper, we also observed that their model often generates invalid translations with regard to grammar. For example, it often mistakes the input type of a function for different languages. This phenomenon is also acknowledged in their own paper and can be attributed to the fact that only textual features have been used. IPTR avoids this problem by reusing existing code.

Table 2: Comparing program accuracy with Transcoder on GeeksforGeeks dataset

	C++-Java	C++-Python	Java-C++	Java-Python	Python-C++	Python-Java
Transcoder	3.1%	6.7%	24.7%	3.7%	4.9%	0.8%
PTR	69.2%	65.3%	70.9%	59.3%	55.4%	54.2%
PTR+QTM	76.6%	74.2%	78.1%	68.1%	59.2%	59.6%
IPTR$_{AL}$	87.2%	79.5%	84.8%	72.5%	66.2%	68.8%
IPTR$_{FB}$	75.9%	71.3%	76.5%	64.2%	59.5%	63.3%
IPTR$_{AL+FB}$	84.8%	83.0%	90.5%	77.5%	67.8%	68.1%

5.2 COMPARISON ON MULTIPLE PROGRAMMING LANGUAGES

We further compare IPTR and the state-of-the-art method Transcoder on the GeeksforGeeks benchmark provided by Lachaux et al. (2020). It contains groundtruth for Java, Python, and C++. Table 2 shows that the program accuracy of IPTR is significantly higher than Transcoder on their own datasets as also reported in their own paper. This is because of two reasons: (1) Our targets are different - Transcoder outputs machine-generated translations while IPTR directly retrieves existing programs as translation candidates, which makes IPTR always output syntactically correct programs. (2) Transcoder generally treats programming languages as plain text and aims to generate semantically similar programs. It does not encode the non-trival syntactical features of programming languages in their model. Thus, it has difficulties in generating results exactly the same as the ground truth. This experiment shows that IPTR is generalizable for multiple languages including dynamic languages, such as Python. Further it shows that it is easier to find translation candidates for grammatically similar programming languages, such as C++ and Java compared to Python as a high-level dynamic language.

5.3 INFLUENCE OF USER CORRECTIONS

In Table 1, we showed the influence of a single user correction on the result. We further investigate the number of user corrections required in order to retrieve the correct translations. We simulate users with the ground truth in our parallel dataset and for each returned result we fix the first different line between true result and returned result.

Figure 5 shows the number of required user corrections to obtain the correct result for all 5.134 translation tasks that failed in the first retrieval round and the improvement in the overall accuracy. We observe that in most cases, IPTR only requires a single user correction to successfully complete the

Figure 5: Required amount of user feedback

translation task. About 98% of the failed retrieval tasks can succeed after 10 user corrections. Considering the average length of an input programs is 168 lines, we can conclude that with small amounts of user feedback the accuracy of IPTR can be significantly improved. Note that, we might even achieve better results if we do not restrict the users to fix the first difference each time. A real user might fix more significant errors that improve the success rate of the retrieval task. The average response time of IPTR to each user feedback is **9.4ms** using an efficient index structure.

6 RELATED WORK

Data-Driven program translation. Existing research mainly focus on building a translation model. Nguyen et al. (2013) directly applied the phrase-based statistical machine translation (SMT) model on the lexemes of source code to translate Java code to C#. In their follow-up work, they develop a multi-phase, phrase-based SMT method that infers and applies both structure and API mapping rules (Nguyen et al., 2015). But they are limited to languages that are similar on either structural or textual level, such as Java/C#. Chen et al. (2018) binarize the code tree using left-Child right-sibling and translate code by an LSTM-based encoder-decoder model. However, all these approaches require a large parallel dataset for training. In contrast to them, a recent work also proposes a weakly-supervised system TransCoder (Lachaux et al., 2020). They first train a cross language model for

programming languages through predicting randomly masked words task, then acquire a pre-trained translation model from denoising randomly corrupted program task. Finally they improve this model through back translation. Although they do not need parallel translation data, this transfer learning method highly relies on the similarity of the data for pre-trained. And this approach is originally designed for natural language processing, which makes it produce results neglecting the features of programming languages. Our code retrieval system can support program translation without parallel dataset and violating the strict grammar rules of programming languages, which is a non-trivial problem in all the above methods.

Interactive program retrieval. In addition to the Sourcerer (Linstead et al., 2009) and StackOverflow search engines that were discussed in the introduction, there are some other work incorporating user interaction. Wang et al. (2014) refine query based on user's feedback on each result and reorder the rest ranking list. Nie et al. (2016) extract relevant feedback from StackOverflow for the initial query and reformulate it using Rocchio expansion. Dietrich et al. (2013) utilize a novel form of association rule mining to learn a set of query transformation rules from user feedback and use them to improve the efficacy of future queries. Martie et al. (2015) propose CodeExchange that uses the previous results to formulate the query so that user can find new results based on the previous characteristics. Sivaraman et al. (2019) propose an active learning system ALICE to iteratively refine a query based on positive or negative labels. All these approaches are designed for the monolanguage setting and their queries are in natural language. IPTR performs cross language retrieval and directly uses raw code as input. Moreover, their method asks the user to feedback on the preset metrics and questions so that the result improvement largely depends on the subjective design from the developer. Due to the different understandings of different users, the feedback cannot be evaluated fairly and uniformly. IPTR directly uses user's corrections to the retrieved results as feedback and integrates an active learning based query transformation model to refine the query.

Program representation. By constructing program representations, one can enable the application of data processing to a wide range of programming-language tasks including program translation and code search. Kamiya et al. (2002) and Allamanis et al. (2016) treat a program as natural language and use the sequence of tokens as representation to detect code clones and summarize code. Allamanis et al. (2018) present a Gated Graph Neural Network in which program elements are represented by graph nodes and their semantic relations are edges in the graph to predict variable name and select correct variable. These methods rely on semantic knowledge, which requires more expert analysis and is not generalizable as the semantic analyses need to be implemented differently for every language. A recent approach uses paths in program's abstract syntax trees (AST) as code representation to predict program properties such as names or expression types (Alon et al., 2018). And they further leverage a tree-based neural network to encode these paths and generate more abstract representations (Alon et al., 2019). Yin et al. employ neural networks to express source code edits (Yin et al., 2019). However, these methods are not designed for translation retrieval. Some of them are too simple to effectively represent program's features (Kamiya et al., 2002; Allamanis et al., 2016). Others are too abstract for users to understand intuitively, which makes it impossible to easily interact with users (Allamanis et al., 2018; Alon et al., 2018; 2019; Yin et al., 2019). The program representation we use as query is more structured. It is not only informative for translation retrieval but also succinct for user interaction.

7   CONCLUSION

We presented IPTR, a novel interactive translation retrieval system that can support program translation. Different from traditional data-driven methods that train a translation model, IPTR directly searches for the most suitable translation candidate in existing code database. We propose a program representation based on a query transformation model that can learn a succinct but informative feature vector to retrieve the translation of an input raw program. IPTR can easily adapt the representation to user corrections for interactive retrieval improvements. Our experiments show that IPTR outperforms existing solutions in terms of effectiveness and requires no training data.

Future work. One important direction is to design a convenient user interface that allows user to make relevant corrections to translation suggestions and enable the system to converge faster to the desired result. Another possible direction to explore is other forms of user interaction that do not require the user to provide corrections in the target language.

REFERENCES

Antlr. website, a. https://www.antlr.org/ [Online; accessed 15-May-2020].

Public git archive. website, b. https://github.com/src-d/datasets/tree/master/PublicGitArchive [Online; accessed 15-May-2020].

Miltiadis Allamanis, Hao Peng, and Charles A. Sutton. A convolutional attention network for extreme summarization of source code. In *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, volume 48 of *JMLR Workshop and Conference Proceedings*, pp. 2091–2100. JMLR.org, 2016.

Miltiadis Allamanis, Marc Brockschmidt, and Mahmoud Khademi. Learning to represent programs with graphs. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018.

Uri Alon, Meital Zilberstein, Omer Levy, and Eran Yahav. A general path-based representation for predicting program properties. In *Proceedings of the 39th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2018, Philadelphia, PA, USA, June 18-22, 2018*, pp. 404–419. ACM, 2018.

Uri Alon, Meital Zilberstein, Omer Levy, and Eran Yahav. code2vec: learning distributed representations of code. *Proc. ACM Program. Lang.*, 3(POPL):40:1–40:29, 2019.

Xinyun Chen, Chang Liu, and Dawn Song. Tree-to-tree neural networks for program translation. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Workshop Track Proceedings*. OpenReview.net, 2018.

Ido Dagan and Sean P. Engelson. Committee-based sampling for training probabilistic classifiers. In *Machine Learning, Proceedings of the Twelfth International Conference on Machine Learning, Tahoe City, California, USA, July 9-12, 1995*, pp. 150–157. Morgan Kaufmann, 1995.

Behrouz Derakhshan, Alireza Rezaei Mahdiraji, Ziawasch Abedjan, Tilmann Rabl, and Volker Markl. Optimizing machine learning workloads in collaborative environments. In *Proceedings of the 2020 International Conference on Management of Data, SIGMOD Conference 2020, online conference [Portland, OR, USA], June 14-19, 2020*, pp. 1701–1716. ACM, 2020.

Timothy Dietrich, Jane Cleland-Huang, and Yonghee Shin. Learning effective query transformations for enhanced requirements trace retrieval. In *2013 28th IEEE/ACM International Conference on Automated Software Engineering, ASE 2013, Silicon Valley, CA, USA, November 11-15, 2013*, pp. 586–591. IEEE, 2013.

Toshihiro Kamiya, Shinji Kusumoto, and Katsuro Inoue. Ccfinder: A multilinguistic token-based code clone detection system for large scale source code. *IEEE Trans. Software Eng.*, 28(7):654–670, 2002.

Marie-Anne Lachaux, Baptiste Rozière, Lowik Chanussot, and Guillaume Lample. Unsupervised translation of programming languages. *CoRR*, abs/2006.03511, 2020.

Erik Linstead, Sushil Krishna Bajracharya, Trung Chi Ngo, Paul Rigor, Cristina Videira Lopes, and Pierre Baldi. Sourcerer: mining and searching internet-scale software repositories. *Data Min. Knowl. Discov.*, 18(2):300–336, 2009.

Fei Lv, Hongyu Zhang, Jian-Guang Lou, Shaowei Wang, Dongmei Zhang, and Jianjun Zhao. Codehow: Effective code search based on API understanding and extended boolean model (E). In *30th IEEE/ACM International Conference on Automated Software Engineering, ASE 2015, Lincoln, NE, USA, November 9-13, 2015*, pp. 260–270. IEEE Computer Society, 2015.

Lee Martie, Thomas D. LaToza, and André van der Hoek. Codeexchange: Supporting reformulation of internet-scale code queries in context (T). In *30th IEEE/ACM International Conference on Automated Software Engineering, ASE 2015, Lincoln, NE, USA, November 9-13, 2015*, pp. 24–35. IEEE Computer Society, 2015.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. In *1st International Conference on Learning Representations, ICLR 2013, Scottsdale, Arizona, USA, May 2-4, 2013, Workshop Track Proceedings*, 2013.

Anh Tuan Nguyen, Tung Thanh Nguyen, and Tien N. Nguyen. Lexical statistical machine translation for language migration. In *Joint Meeting of the European Software Engineering Conference and the ACM SIGSOFT Symposium on the Foundations of Software Engineering, ESEC/FSE'13, Saint Petersburg, Russian Federation, August 18-26, 2013*, pp. 651–654. ACM, 2013.

Anh Tuan Nguyen, Tung Thanh Nguyen, and Tien N. Nguyen. Divide-and-conquer approach for multi-phase statistical migration for source code (T). In *30th IEEE/ACM International Conference on Automated Software Engineering, ASE 2015, Lincoln, NE, USA, November 9-13, 2015*, pp. 585–596. IEEE Computer Society, 2015.

Liming Nie, He Jiang, Zhilei Ren, Zeyi Sun, and Xiaochen Li. Query expansion based on crowd knowledge for code search. *IEEE Trans. Serv. Comput.*, 9(5):771–783, 2016.

Aishwarya Sivaraman, Tianyi Zhang, Guy Van den Broeck, and Miryung Kim. Active inductive logic programming for code search. In *Proceedings of the 41st International Conference on Software Engineering, ICSE 2019, Montreal, QC, Canada, May 25-31, 2019*, pp. 292–303. IEEE / ACM, 2019.

Shaowei Wang, David Lo, and Lingxiao Jiang. Active code search: incorporating user feedback to improve code search relevance. In *ACM/IEEE International Conference on Automated Software Engineering, ASE '14, Vasteras, Sweden - September 15 - 19, 2014*, pp. 677–682. ACM, 2014.

Cong Yan and Yeye He. Synthesizing type-detection logic for rich semantic data types using open-source code. In *Proceedings of the 2018 International Conference on Management of Data, SIGMOD Conference 2018, Houston, TX, USA, June 10-15, 2018*, pp. 35–50. ACM, 2018.

Cong Yan and Yeye He. Auto-suggest: Learning-to-recommend data preparation steps using data science notebooks. In *Proceedings of the 2020 International Conference on Management of Data, SIGMOD Conference 2020, online conference [Portland, OR, USA], June 14-19, 2020*, pp. 1539–1554. ACM, 2020.

Pengcheng Yin, Graham Neubig, Miltiadis Allamanis, Marc Brockschmidt, and Alexander L. Gaunt. Learning to represent edits. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Xingquan Zhu, Peng Zhang, Xiaodong Lin, and Yong Shi. Active learning from data streams. In *Proceedings of the 7th IEEE International Conference on Data Mining (ICDM 2007), October 28-31, 2007, Omaha, Nebraska, USA*, pp. 757–762, 2007.

A APPENDIX

In this section we lay out details on syntax trees and their general properties.

A.1 CST AND AST

Figure 6: CST and AST of a simple JavaScript program

Figure 7: Generating simplified syntax tree

The structure of a program can be described by a syntax tree where each tree node denotes a construct occurring in the code, e.g., if_stmt in Python denotes an if construct. The tree can be either a comprehensive CST or a more abstract AST. CST is a tree representation of the grammar (rules of how the program should be written). It represents the source program exactly in parsed form. In other words, it defines the way programs look like to the programmer. There is an example in Figure 6. The CST of the simple JavaScript program is verbose with all the detail information about parsing the code. It keeps all the tokens in the program and their types, such as literal and identifier. And it reveals all the grammar rules, such as equalityExpression: singleExpression == singleExpression. On contrary, AST is a tree representation of the abstract syntactic structure of source code. Each node of the tree denotes a construct occurring in the source code. The syntax is "abstract" in the sense that it does not represent every detail appearing in the real syntax, but rather just the structural or content-related details. It defines the way the programs look like to the evaluator/compiler. As shown in Figure 6, the AST directly shows the equal structure without any detail information. It discards the intermediate structural information that would not contribute to semantics.

A.2 GENERATING SIMPLIFIED SYNTAX TREE.

IPTR first employs a left-to-right parser, such as ANTLR web (a), to parse the source code and generate the original CST. Figure 7 shows the CST of a raw JavaScript program. However, as shown in Figure 7, the original JavaScript code is simple while its CST is comparably intricate with all the details preserved. The large amount of nodes and branches will raise the computation complexity while having little contribution to the representation. For example, the node type ifStatement already specifically indicates the existence of an IF expression. Therefore its parent node type statement is not necessary as it does not reveal more information. On a syntax tree, all the nodes are already enclosed by their parent node. Thus, nodes of parentheses are not needed to reveal enclosure relationships. Further, node == is not necessary when node type equalityExpression already explains the content. Thus, IPTR follows two rules to prune the CST: (1) Node types that

only have one child node are discarded, unless this child node represents specific content in the source code (Italics in Figure 7). For example, `statement` and `singleExpression` are discarded, while `identifier` and `literal` are retained. (2) If the parent node of a terminal node has more than one child node, this terminal node is removed. This is the case for symbols, such as `(` and `==`. The pruned tree in Figure 7 is much simpler than the original CST and retains all major structural features.