Video Prediction with Variational Temporal Hierarchies

Abstract

Deep learning has shown promise for accurately predicting high-dimensional video sequences. Existing video prediction models succeeded in generating sharp but often short video sequences. Toward improving long-term video prediction, we study hierarchical latent variable models with levels that process at different time scales. To gain insights into the representations of such models, we study the information stored at each level of the hierarchy via the KL divergence, predictive entropy, datasets of varying speed, and generative distributions. Our analysis confirms that faster changing details are generally captured by lower levels, while slower changing facts are remembered by higher levels. On synthetic datasets where common methods fail after 25 frames, we show that temporally abstract latent variable models can make accurate predictions for up to 200 frames.

1 Introduction

Deep learning has enabled predicting video sequences from large datasets (Chiappa et al., 2017; Oh et al., 2015; Vondrick et al., 2016). For high-dimensional inputs such as video, there likely exists a more compact representation of the scene that facilitates long term prediction. Instead of learning dynamics in pixel space, latent dynamics models predict ahead in a more compact feature space (Doerr et al., 2018; Buesing et al., 2018; Karl et al., 2016; Hafner et al., 2019). This has the added benefit of increased computational efficiency and a lower memory footprint, allowing to predict thousands of sequences in parallel using a large batch size.

A lot of work in deep learning has focused on spatial abstraction, following the advent of convolutional networks (LeCun et al., 1989), such as the Variational Ladder Autoencoder (Zhao et al., 2017) that learns a hierarchy of features in images using networks of different capacities, along with playing an important role in the realm of video

Figure 1: Mean SSIM over a test set of 100 sequences of open-loop prediction with Moving MNIST. All 3-level latent dynamics models, with temporal abstraction factors 2, 4, 6, and 8, have the same number of model parameters.

prediction models (Castrejón et al., 2019). Recent sequential models have incorporated temporal abstraction for learning dependencies in temporally distant observations (Koutník et al., 2014; Chung et al., 2016). Kim et al. (2019) proposed Variational Temporal Abstraction (VTA), in which they explored one level of temporal abstraction above the latent states, the transition of which was modeled using a Bernoulli random variable. In this paper, we intend to work in a more controlled setup than VTA for a qualitative and quantitative analysis of temporally abstract latent variable models.

In this paper, we study the benefits of temporal abstraction using a hierarchical latent dynamics model, trained using a variational objective. Each level in the hierarchy of this model temporally abstracts the level below by an adjustable factor. This model can perform long-horizon video prediction of 200 frames, while predicting accurate low-level information for a 6 times longer duration than the baseline model. We study the information stored at different levels of the hierarchy via KL divergence, predictive entropy, datasets of varying speeds, and generative distributions. In our experiments we show that this amounts to object location and identities for the Moving MNIST dataset, and the wall or floor patterns for the GQN mazes dataset (Eslami et al., 2018), stored at different levels.

Figure 2: Long horizon open-loop video prediction for the GQN mazes dataset (Eslami et al., 2018) using our 2-level TALD model with temporal abstraction factor of 6. RSSM does not use temporal abstraction and thus starts to forget wall and floor patterns after 40 frames, while TALD maintains this global information over 200 frames.

Our key contributions are summarized as follows:

- **Temporal Abstract Latent Dynamics (TALD)** We introduce a simple model with different clock speeds at every level to study the properties of variational hierarchical dynamics.
- **Accurate long-term predictions** Our form of temporal abstraction substantially improves for how long the model can accurately predict video frames into the future.
- **Adaptation to sequence speed** We demonstrate that our model automatically adapts the amount of information processed at each level to the speed of the video sequence.
- **Separation of information** We visualize the content represented at each level of the hierarchy to find location information in lower levels and object identity in higher levels.

2 RELATED WORK

Generative video models A variety of methods have successfully approached video prediction using large datasets (Chiappa et al., 2017; Oh et al., 2015; Vondrick et al., 2016; Babaeizadeh et al., 2017; Gemici et al., 2017; Ha & Schmidhuber, 2018). Denton & Fergus (2018) proposed a stochastic video generation model with a learned prior that transitions in time, and is conditioned on past observations.

Latent dynamics models Latent dynamics models have evolved from latent space models that had access to low-dimensional features (Deisenroth & Rasmussen, 2011; Higuera et al., 2018), to models that can build a compact representation of visual scenes and facilitate video prediction purely in the latent space (Doerr et al., 2018; Buesing et al., 2018; Karl et al., 2016). The Variational RNN (Chung et al., 2015) uses an auto-regressive state transition that takes inputs from observations, making it computationally expensive to be used as an imagination module. Hafner et al. (2019) proposed a latent dynamics model, which is a combination of deterministic and stochastic states, that enables the model to deterministically remember all previous states and filter that information to obtain a distribution over the current state.

Hierarchical latent variables Zhao et al. (2017) proposed the Variational Ladder Autoencoder (VLAE) that uses networks of different capacities at different levels of the hierarchy, encouraging the model to store high-level image features at the top level, and simple features at the bottom. Other recently proposed hierarchical models use a purely bottom-up inference approach with no interaction between the inference and generative models (Kingma & Welling, 2014; Rezende & Mohamed, 2015; Rezende et al., 2014). In contrast, Sønderby et al. (2016, LVAE) and Vahdat & Kautz (2020, NVAE) proposed to use a combination of bottom-up and top-down inference procedures, sharing parameters between the inference and generative distributions during the top-down pass. We incorporate this conditional structure in our model design as well.

Temporal abstraction Identifying complex dependencies between temporally distant observations is a challenging task and has inspired a variety of fundamental work in recurrent models (Koutník et al., 2014; Chung et al., 2016). However, relatively few works have demonstrated modeling long-term dependencies using temporally abstract latent dynamics models (Wichers et al., 2018; Jaderberg et al., 2018). Recently, Kim et al. (2019) introduced Variational Temporal Abstraction (VTA) to learn temporally abstract latent spaces. They explored one level of temporal abstraction above the

Figure 3: Temporally Abstract Latent Dynamics (TALD). Left is the structure of our recurrent model, in which each latent state s_t^l in the second level abstracts two latent states in the first level. The solid arrows represent the generative model, while both solid and broken arrows comprise the inference model. On the right, we illustrate the internal components of the state variable, which comprises a deterministic state h_t and a stochastic state z_t. The deterministic state processes all contextual information and passes it to the stochastic state to be used for either generation or inference.

latent states, the transition of which was modeled using a Bernoulli random variable, that chose between 'copy' or 'update' steps. Inspired by this work, we aim to gain a deeper understanding of such temporally-abstract latent dynamics models. We perform our analysis on a model that is simplified to using fixed time scales for every level. Moreover, the lower level is a continuing chain in our model, whereas VTA resets transitions at a lower level when transitioning at a higher level.

3 TEMPORALLY ABSTRACT LATENT DYNAMICS

Long video sequences contain both information that is local to a few frames as well as global information that is shared among many frames. Traditional video prediction models that predict ahead at the frame rate of the video can struggle to retain information long enough to learn such long-term dependencies. We introduce Temporally Abstract Latent Dynamics (TALD) to learn long-term correlations of videos. Our model predicts ahead on multiple time scales to learn dependencies at different temporal levels, as visualized in Figure 3. We build our work upon the recurrent state-space model (RSSM; Hafner et al., 2019), the details of which can be found in Appendix A.

TALD consists of a hierarchy of recurrent latent variables, where each level transitions at a different clock speed. We slow down the transitions exponentially as we go up in the hierarchy, i.e. every level being slower than the level below by a factor of k. We denote a set of active timesteps for every level $l \in [1, L]$ as those steps in time where the state transition generates a new latent state,

$$\text{Active timesteps:} \qquad \mathcal{T}_l \doteq \{t \in [1, T] \mid t \bmod k^{l-1} = 1\}. \qquad (1)$$

At each level, we condition every window of k latent states on a single latent variable in the level above. This can also be thought of as a hierarchy of latent variables where each level has the same clock speed, but performs a state transition every k^{l-1} timesteps and copies the same state variable otherwise, so that $\forall t \notin \mathcal{T}_l$:

$$\text{Inactive states:} \qquad s_t^l \doteq s_{\max_\tau \{\tau \in \mathcal{T}_l \mid \tau \leq t\}}^l. \qquad (2)$$

Joint distribution We can factorize the joint distribution of a sequence of observations and (active) latents at every level into two terms: (1) a decoder term conditioned on the latent states in the lowest level, and (2) state transitions at all levels conditioned on the latent state of the last active timestep at the current level and the level above,

$$p(x_{1:T}, s_{1:T}^{1:L}) \doteq \left(\prod_{t=1}^T p(x_t \mid s_t^1) \right) \left(\prod_{l=1}^L \prod_{t \in \mathcal{T}_l} p(s_t^l \mid s_{t-1}^l, s_t^{l+1}) \right). \qquad (3)$$

Inference For inference, TALD embeds observed frames using a CNN. A hierarchical recurrent network then summarizes the input embeddings, for which each (active) latent state at a level l receives embeddings from k^{l-1} observation frames (dashed lines in Figure 3). The latent state at the previous timestep at the current level, and the state belief at the level above also condition the posterior belief (solid lines in Figure 3). The input embeddings combined with this top-down and temporal context together condition the posterior belief q_t^l over the latent state.

Generation The prior transition p_t^l is computed by conditioning over the latent state at the previous timestep at the current level, and the state belief at the level above (solid lines in Figure 3).

Decoding Finally, the state beliefs at the bottom-most level are decoded using a transposed CNN to provide a training signal. To summarize, we utilize the following components in our model, $\forall\, l \in [1, L], t \in \mathcal{T}_l$,

$$
\begin{aligned}
&\text{Encoder:} && e_t^l = e(x_{t:t+k^{l-1}-1}) \\
&\text{Posterior transition } q_t^l: && q(s_t^l \mid s_{t-1}^l, s_t^{l+1}, e_t^l) \\
&\text{Prior transition } p_t^l: && p(s_t^l \mid s_{t-1}^l, s_t^{l+1}) \\
&\text{Decoder:} && p(x_t \mid s_t^1).
\end{aligned}
\tag{4}
$$

Training objective Since we cannot compute the likelihood of the training data under the model in closed form, we use the ELBO as our training objective. This training objective optimizes a reconstruction loss at the lowest level, and a KL regularizer at every level in the hierarchy summed across active timesteps,

$$
\max_{e,h,q,p} \sum_{t=1}^{T} \mathrm{E}_{q_t^1}[\ln p(x_t \mid s_t^1)] - \sum_{l=1}^{L} \sum_{t \in T_l} \mathrm{KL}[q_t^l \parallel p_t^l].
\tag{5}
$$

The KL regularizer at each level limits the amount of information that filters through the encoder and stays in the posterior at that level. This encourages the model to utilize the state transitions and context from the level above as much as possible. Since the number of active timesteps decreases as we go higher in the hierarchy, the number of KL terms per level decreases as well. Hence it is easier for the model to push global information high up in the hierarchy and pay lesser KL penalty, instead of transitioning those bits with an identity transformation at a lower level.

Stochastic and Deterministic Path As illustrated in Figure 3 (right), we split the state s_t^l into stochastic (z_t^l) and deterministic (h_t^l) parts (Hafner et al., 2019). The deterministic state is computed using the top-down and temporal context, which then conditions the stochastic state at that level.

The stochastic states follow a diagonal Gaussian, with mean and variance predicted by a neural network. We use a GRU (Cho et al., 2014) per level to update the deterministic state at every active timestep. All components in Equation 4 are trained jointly by optimizing Equation 5 using stochastic backpropagation with reparameterized sampling. Please refer to Appendix B for architectures details.

4 EXPERIMENTS

We aim to evaluate temporally-abstract latent dynamics models at modeling long-term dependencies in video. Moreover, we aim to understand how they separate information into different levels of the hierarchy. To investigate these questions, we train TALD described in Section 3, the temporally-abstract VTA model (Kim et al., 2019), the RSSM model without temporal abstraction (Hafner et al., 2019), and the image-space video prediction model SVG-LP (Denton & Fergus, 2018) on three datasets of varying complexity. We consider the well-

Table 1: KL divergence (in bits) between the posterior and prior at different levels of the hierarchy (summed in time). We observe that the amount of information at the (lowest) level 1 decreases as the model gets deeper.

TALD	LEVEL 1	LEVEL 2	LEVEL 3	LEVEL 4
4 LEVELS	572.89	59.44	3.84	1.76e−4
3 LEVELS	529.04	65.33	9.07	-
2 LEVELS	561.79	56.52	-	-
1 LEVEL	635.51	-	-	-

established Moving MINST dataset (Srivastava et al., 2015), the KTH Action dataset (Schuldt et al., 2004), and the GQN mazes dataset (Eslami et al., 2018). We evaluate open-loop video predictions on these datasets. In Section 4.4, we investigate how the amount of information stored at different levels of a temporal hierarchy adapts to changes in sequence speed. In Section 4.5, we visualize the information stored at different levels by resetting individual levels of the hierarchy.

We trained all our models using sequences of length 100. We used convolutional frame encoders and decoders, with architectures very similar to the DCGAN (Radford et al., 2016) discriminator and generator, respectively. Our implementations made use of TensorFlow Probability (Dillon et al., 2017) and CuDNN, and used the Adam optimizer (Kingma & Ba, 2014) for training. The training time for a 3-level TALD model with temporal abstraction 6 amounted to around 24 hours for 100 epochs on a single NVIDIA TITAN Xp GPU. Refer to Appendix C for hyperparameters and experimental setup.

Figure 4: Long-horizon open-loop prediction for Moving MNIST. (L for levels, F for abstraction factor.) We illustrate samples from our TALD model with 3 levels and temporal abstraction factors: 6 (3L-F6), and 1 (3L-F1) (i.e. no temporal abstraction). We compare those with samples from the RSSM and SVG-LP baselines. We observe that TALD, with abstraction factor 6, is able to maintain accurate long-term dependencies in the form of object identities for 900 frames into the future.

4.1 MOVING MNIST DATASET

The Moving MNIST dataset consists of two digits moving in a square with velocities sampled in the range of 2 to 6 pixels per frame. We trained different versions of TALD with 3 levels in the hierarchy and temporal abstraction factors 1, 2, 4, 6 and 8, all of which use the same number of model parameters. We compare samples of long-horizon open-loop video predictions of 900 frames with RSSM and SVG-LP in Figure 4. All samples were conditioned using posterior beliefs inferred after observing 36 context frames.

We observe that SVG typically forgets object identity within 50 timesteps, while TALD with abstraction factor 6 maintains digit identity over 900 timesteps. RSSM clearly outperforms SVG, however starts to forget object identities after 250 time frames. TALD with abstraction factor 1 (i.e. no temporal abstraction) also starts to forget object identity after around 250 frames. With regards to the object positions, TALD with abstraction factor 6 predicts accurate digit positions until around 90 steps, and predicts a plausible sequence thereafter. RSSM and TALD without temporal abstraction predict the correct location of digits for at least as long as TALD with temporal abstraction. However, SVG starts to lose track of positions much sooner. We also note that our predictions are a bit blurry compared to those generated by SVG. Please refer to Appendix D for more experimental results.

We report the KL divergence value per level (summed over active time steps) for our TALD models in Table 1. Each value was obtained after training over sequences of length 100, for 200 epochs. The 2 and 3-level models were trained with a temporal abstraction factor of 6, and the 4-level model with a factor of 4 (to fit into memory). Figure 1 compares the Structural Similarity index (SSIM) for different versions of TALD with RSSM and SVG-LP. We note that SSIM decreases at a lower rate for models with higher temporal abstractions. As a baseline, we compute SSIM between ground truths and random sequences from the training set. It is interesting to note that quality of video predictions from TALD stay better than random for a 6 times longer duration than SVG.

Figure 5: Quantitative comparison between our temporally abstract latent dynamics model (TALD) and baselines over open-loop video prediction of 300 frames for the KTH Action dataset.

Figure 6: Open-loop video prediction for the KTH Action dataset. While TALD predicts accurately for 50 time frames, we observe jumpy transitions in VTA, where in this example the person disappears after the 17th frame. SVG predicts accurately for 18 frames, but starts to forget the task thereafter, as the person in the video starts to move in the opposite direction.

4.2 KTH ACTION DATASET

We trained a 3-level TALD model with temporal abstraction factor 6 for the KTH Action dataset. In Figure 5, we report the Structural Similarity index (SSIM; higher is better), Peak Signal-to-Noise Ratio (PSNR; higher is better), and Learned Perceptual Image Patch Similarity (LPIPS; lower is better) (Zhang et al., 2018), of TALD compared to SVG-LP, RSSM, and VTA. We also illustrate open-loop video predictions in Figure 6, conditioned using 36 context frames. While TALD predicts plausible frames for 50 timesteps, we observe jumpy transitions with VTA, probably because of breaks in the transition chain at the lower level. We also observe that SVG predicts accurately for 18 frames, while switching to a different task thereafter. We also note that SVG uses the DCGAN architecture for MNIST and the much larger VGG for KTH, whereas TALD works well even with the smaller DCGAN encoder/decoder.

4.3 GQN 3D MAZES DATASET

We trained a 2-level TALD model with temporal abstraction factor 6, and compared it with RSSM and VTA, on the GQN mazes dataset. Figure 2 shows open-loop video prediction samples, conditioned using 36 context frames. We observe that while our model can maintain global information of wall and floor colors for 200 frames, RSSM starts to forget the same after ∼50 frames. Even though the open-loop predictions from TALD differ from ground truth in terms of camera viewpoints, the model does not forget the wall and floor patterns. Please refer to Appendix D for more experimental results.

4.4 ADAPTING TO SEQUENCE SPEED

In order to understand how our model adapts to changing temporal correlations in the dataset, we trained our model with slower and faster versions of moving MNIST, with speeds varied by factors of 3. For this experiment, our model consisted of 3 levels in the hierarchy, with each level temporally abstracting the level below by a factor of 6.

Figure 8 shows the KL divergence summed across the active timesteps at every level in the hierarchy. We observe that there is a correlation between the KL divergence at every level and the speed at which the digits move. There is more information at level 1 when the digits move faster, and consequently lesser information at the levels above it. Also, even though the KL divergence at level 3 is small, it still follows the same trend as the other two levels. It is also important to note that the KL divergence between the prior and the posterior is only an upper bound on the information stored by the encoder in a posterior belief state.

Figure 8: KL divergence at each level of the TALD model (3 levels, temporal abstraction factor 6), trained on slower/faster versions of Moving MNIST. Observe that the KL term at higher levels decreases with an increase in the speed of the digits, suggesting less global information being pushed up in the hierarchy.

Ground truth sequence

Conditioned sample using all levels

Conditioned samples setting level-3 to prior

$t = 0 \quad 1 \quad 2 \quad 3 \quad 4 \quad 5 \quad 10 \quad 15 \quad 20 \quad 25 \quad 30 \quad 35 \quad 40 \quad 45 \quad 50$

Figure 7: Visualizing the information stored at the higher level of our 3-level model with temporal abstraction factor 2, using the GQN mazes dataset. We computed a posterior belief at each level using 8 observation frames, and set one of the levels to the prior (by not feeding it with observations), which were then used to condition open-loop predictions. Changing wall textures show that they are stored at the highest level.

4.5 RESETTING INDIVIDUAL LEVELS

We visualize the information stored at a certain level by replacing the posterior belief at one level with the prior belief, i.e. all but one level receive observations (Zhao et al., 2017). Conditioned on those posterior beliefs, we sample open-loop video predictions using the trained prior model, which should show variations in the attributes learned at that level. We expect our model to store global information high up in the hierarchy, allowing the model to perform fewer transitions over that information, making it easier to pay less cost in the form of KL divergence during training.

Figure 7 shows video predictions with different levels reset to the prior for the GQN mazes dataset. With a 3-level model and temporal abstraction factor 2, we observe that when level 3 was not fed with observations, the conditioned open-loop predictions started with the correct viewpoint, but differed w.r.t. wall and floor colors. This suggests that those characteristics were stored in the higher level of the hierarchy.

Figure 9 shows video predictions with different levels reset to the prior for the Moving MNIST dataset. The 3-level model with temporal abstraction factor 6 obtained a separation of information in the bottom two levels, while the posterior at the third level nearly collapsed to the prior. When level 1 was not fed with observations, we observe that the conditioned open-loop predictions maintained the same digit identity, but showed variations w.r.t. digit positions. On the other hand, when level 2 was not fed with observations, the samples maintained the same digit positions but produced digits with different identities in every sample. This suggests that lower level stored digit positions, high frequency details which changed frequently in time, while the level above it stored the digit identities, i.e. long-term information. We also observed that, when resetting level 2 to the prior, the digits start to differ in position sooner (∼60 frames) than when all levels receive observations (∼80 frames). This suggests that this level does have some information about digit positions, and that there is still mixing of information between different levels of the hierarchy.

(a) GQN mazes

(b) Moving MNIST

Figure 10: Entropy of the prior during open-loop video generation at different levels of TALD (3 levels, temporal abstraction 2). (a) With GQN mazes, constant entropy at level 3 (stored wall and floor patterns). (b) With Moving MNIST, constant entropy at level 2 (stored digit identities), and level 3 (suffered posterior collapse).

Figure 9: Visualizing the information stored at different levels of TALD with 3-levels and temporal abstraction factor 6, for Moving MNIST. We computed a posterior belief at each level using 36 observation frames, while setting one of the levels to the prior (by not feeding it with observations), which were then used to condition open-loop predictions.

Predictive entropy   To corroborate our understanding of the latent representations, we observe the entropy of the prior distribution as it varies over time during open-loop video generation in Figure 10. With GQN mazes, the entropy at the top level remained relatively constant as the model remained certain about the high-level details. With Moving MNIST, the top two levels showed a relatively constant entropy, with level 2 storing the digit identities and level 3 suffering from posterior collapse.

5   DISCUSSION

In this work, we presented a hierarchical latent dynamics model with temporal abstraction (TALD), where each level in the hierarchy temporally abstracted the level below by an adjustable factor.

- We evaluated long-horizon open-loop predictions using our model, and observed that TALD was able to predict far into the future while accurately maintaining global information.

- We also observed that the amount of information at the higher levels decreased as the speed of the sequence was increased.

- We analyzed the separation of information at different levels of the hierarchy, by generating open-loop video predictions with different levels reset to the prior. With Moving MNIST, the bottom level in the hierarchy stored high frequency details (digit positions) and the level above stored more global information (digit identities). With the GQN mazes dataset, TALD stored wall and floor patterns at the top level in the hierarchy.

Temporally abstract models are an intuitive approach to obtaining high-level representations of complex datasets and environments. We hope that our work can refuel interest in temporally abstract latent dynamics models and motivate the development of effective deep learning systems for high-dimensional data more generally.

REFERENCES

Mohammad Babaeizadeh, Chelsea Finn, Dumitru Erhan, Roy H. Campbell, and Sergey Levine. Stochastic variational video prediction. *CoRR*, abs/1710.11252, 2017. URL http://arxiv.org/abs/1710.11252.

Lars Buesing, Theophane Weber, Sébastien Racanière, S. M. Ali Eslami, Danilo Jimenez Rezende, David P. Reichert, Fabio Viola, Frederic Besse, Karol Gregor, Demis Hassabis, and Daan Wierstra. Learning and querying fast generative models for reinforcement learning. *CoRR*, abs/1802.03006, 2018. URL http://arxiv.org/abs/1802.03006.

Lluís Castrejón, Nicolas Ballas, and Aaron C. Courville. Improved conditional vrnns for video prediction. *CoRR*, abs/1904.12165, 2019. URL http://arxiv.org/abs/1904.12165.

Silvia Chiappa, Sébastien Racanière, Daan Wierstra, and Shakir Mohamed. Recurrent environment simulators. *CoRR*, abs/1704.02254, 2017. URL http://arxiv.org/abs/1704.02254.

Kyunghyun Cho, Bart van Merrienboer, Çaglar Gülçehre, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder-decoder for statistical machine translation. *CoRR*, abs/1406.1078, 2014. URL http://arxiv.org/abs/1406.1078.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron C. Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. *CoRR*, abs/1506.02216, 2015. URL http://arxiv.org/abs/1506.02216.

Junyoung Chung, Sungjin Ahn, and Yoshua Bengio. Hierarchical multiscale recurrent neural networks. *CoRR*, abs/1609.01704, 2016. URL http://arxiv.org/abs/1609.01704.

Marc Deisenroth and Carl E Rasmussen. Pilco: A model-based and data-efficient approach to policy search. In *Proceedings of the 28th International Conference on machine learning (ICML-11)*, pp. 465–472, 2011.

Emily Denton and Rob Fergus. Stochastic video generation with a learned prior. *CoRR*, abs/1802.07687, 2018. URL http://arxiv.org/abs/1802.07687.

Joshua V Dillon, Ian Langmore, Dustin Tran, Eugene Brevdo, Srinivas Vasudevan, Dave Moore, Brian Patton, Alex Alemi, Matt Hoffman, and Rif A Saurous. Tensorflow distributions. *arXiv preprint arXiv:1711.10604*, 2017.

Andreas Doerr, Christian Daniel, Martin Schiegg, Duy Nguyen-Tuong, Stefan Schaal, Marc Toussaint, and Sebastian Trimpe. Probabilistic recurrent state-space models. *arXiv preprint arXiv:1801.10395*, 2018.

SM Ali Eslami, Danilo Jimenez Rezende, Frederic Besse, Fabio Viola, Ari S Morcos, Marta Garnelo, Avraham Ruderman, Andrei A Rusu, Ivo Danihelka, Karol Gregor, et al. Neural scene representation and rendering. *Science*, 360(6394):1204–1210, 2018.

Mevlana Gemici, Chia-Chun Hung, Adam Santoro, Greg Wayne, Shakir Mohamed, Danilo Jimenez Rezende, David Amos, and Timothy P. Lillicrap. Generative temporal models with memory. *CoRR*, abs/1702.04649, 2017. URL http://arxiv.org/abs/1702.04649.

David Ha and Jürgen Schmidhuber. World models. *CoRR*, abs/1803.10122, 2018. URL http://arxiv.org/abs/1803.10122.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, pp. 2555–2565, 2019.

Juan Camilo Gamboa Higuera, David Meger, and Gregory Dudek. Synthesizing neural network controllers with probabilistic model based reinforcement learning. *arXiv preprint arXiv:1803.02291*, 2018.

Max Jaderberg, Wojciech M. Czarnecki, Iain Dunning, Luke Marris, Guy Lever, Antonio García Castañeda, Charles Beattie, Neil C. Rabinowitz, Ari S. Morcos, Avraham Ruderman, Nicolas Sonnerat, Tim Green, Louise Deason, Joel Z. Leibo, David Silver, Demis Hassabis, Koray Kavukcuoglu, and Thore Graepel. Human-level performance in first-person multiplayer games with population-based deep reinforcement learning. *CoRR*, abs/1807.01281, 2018. URL http://arxiv.org/abs/1807.01281.

Maximilian Karl, Maximilian Soelch, Justin Bayer, and Patrick Van der Smagt. Deep variational bayes filters: Unsupervised learning of state space models from raw data. *arXiv preprint arXiv:1605.06432*, 2016.

Taesup Kim, Sungjin Ahn, and Yoshua Bengio. Variational temporal abstraction. In *Advances in Neural Information Processing Systems*, pp. 11566–11575, 2019.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2014. URL http://arxiv.org/abs/1412.6980.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Diederik P Kingma and Max Welling. Auto-Encoding Variational Bayes. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2014.

Jan Koutník, Klaus Greff, Faustino J. Gomez, and Jürgen Schmidhuber. A clockwork RNN. *CoRR*, abs/1402.3511, 2014. URL http://arxiv.org/abs/1402.3511.

Yann LeCun, Bernhard Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne Hubbard, and Lawrence D Jackel. Backpropagation applied to handwritten zip code recognition. *Neural computation*, 1(4):541–551, 1989.

Junhyuk Oh, Xiaoxiao Guo, Honglak Lee, Richard L Lewis, and Satinder Singh. Action-conditional video prediction using deep networks in atari games. In *Advances in Neural Information Processing Systems*, pp. 2863–2871, 2015.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL http://arxiv.org/abs/1511.06434.

Danilo Jimenez Rezende and Shakir Mohamed. Variational inference with normalizing flows. *arXiv preprint arXiv:1505.05770*, 2015.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

C. Schuldt, I. Laptev, and B. Caputo. Recognizing human actions: a local svm approach. In *Proceedings of the 17th International Conference on Pattern Recognition, 2004. ICPR 2004.*, volume 3, pp. 32–36 Vol.3, 2004.

Casper Kaae Sønderby, Tapani Raiko, Lars Maaløe, Søren Kaae Sønderby, and Ole Winther. Ladder variational autoencoders. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, pp. 3745–3753, USA, 2016. Curran Associates Inc. ISBN 978-1-5108-3881-9. URL http://dl.acm.org/citation.cfm?id=3157382.3157516.

Nitish Srivastava, Elman Mansimov, and Ruslan Salakhutdinov. Unsupervised learning of video representations using lstms. *CoRR*, abs/1502.04681, 2015. URL http://arxiv.org/abs/1502.04681.

Arash Vahdat and Jan Kautz. Nvae: A deep hierarchical variational autoencoder, 2020.

Carl Vondrick, Hamed Pirsiavash, and Antonio Torralba. Generating videos with scene dynamics. In *Advances In Neural Information Processing Systems*, 2016.

Nevan Wichers, Ruben Villegas, Dumitru Erhan, and Honglak Lee. Hierarchical long-term video prediction without supervision. *CoRR*, abs/1806.04768, 2018. URL http://arxiv.org/abs/1806.04768.

R. Zhang, P. Isola, A. A. Efros, E. Shechtman, and O. Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 586–595, 2018.

Shengjia Zhao, Jiaming Song, and Stefano Ermon. Learning hierarchical features from generative models. *CoRR*, abs/1702.08396, 2017. URL http://arxiv.org/abs/1702.08396.