Constant Rate Scheduling: A General Framework for Optimizing Diffusion Noise Schedule via Distributional Change

Abstract

We propose a general framework for optimizing noise schedules in diffusion models, applicable to both training and sampling. Our method enforces a constant rate of change in the probability distribution of diffused data throughout the diffusion process, where the rate of change is quantified using a user-defined discrepancy measure. We introduce three such measures, which can be flexibly selected or combined depending on the domain and model architecture. While our framework is inspired by theoretical insights, we do not aim to provide a complete theoretical justification of how distributional change affects sample quality. Instead, we focus on establishing a general-purpose scheduling framework and validating its empirical effectiveness. Through extensive experiments, we demonstrate that our approach consistently improves the performance of both pixel-space and latent-space diffusion models, across various datasets, samplers, and a wide range of number of function evaluations from 5 to 250. In particular, when applied to both training and sampling schedules, our method achieves a state-of-the-art FID score of 2.03 on LSUN Horse 256×256, without compromising mode coverage.

1 Introduction

Diffusion models are a class of probabilistic generative models that have attracted significant attention due to their ability to generate high-quality samples across a variety of domains, including image generation (Saharia et al., 2022b; Nichol et al., 2022b; Podell et al., 2024a), image super-resolution (Saharia et al., 2023; Doi et al., 2024), video synthesis (Ho et al., 2022b;a), and audio generation (Kong et al., 2021; Popov et al., 2021).

Diffusion models were originally introduced in Sohl-Dickstein et al. (2015), and denoising diffusion probabilistic models (DDPMs) (Ho et al., 2020) demonstrated that diffusion models can achieve state-of-the-art performance in image generation. A typical diffusion model consists of two Markovian processes: a forward process and a reverse process. The forward process gradually adds Gaussian noise to the input data, transforming its distribution toward a Gaussian. The reverse process aims to reconstruct data from Gaussian noise by tracing the forward process in the reverse direction.

The noise levels applied at each step of these processes are treated as hyperparameters and are collectively referred to as the noise schedule. The noise schedule has a critical impact on both the quality and efficiency of training and sampling. Importantly, the schedules used during training and sampling do not have to be identical, and recent studies have shown that using different schedules for training and sampling can improve performance (Karras et al., 2022; Kingma & Gao, 2023). However, designing effective noise schedules remains a non-trivial and largely empirical process.

In this work, we propose a general framework for optimizing both training and sampling schedules by enforcing a constant rate of change in the probability distribution of diffused data throughout the diffusion process. We refer to this framework as constant rate scheduling (CRS). Since the reverse process is expected to accurately trace the forward process, the key motivation is to determine noise schedules that can enhance the traceability of the forward process .

Figure 1: Toy example of diffused data distributions with three data points in one-dimensional data space. Probability distributions barely change when $\alpha \lesssim 0.6$, and we can rapidly change noise level. Three modes corresponding to data points emerge when $0.6 \lesssim \alpha \lesssim 0.97$, and noise level should be changed slowly for mode coverage. Three modes become distinct when $\alpha \gtrsim 0.97$, requiring careful control of noise level for sample fidelity.

Figure 1 presents a toy example of diffused data distributions with three data points in one-dimensional data space (see Appendix A for details). Here, α represents the decay rate of data at each step of the diffusion process. In this example, the diffusion process can be divided into three regions: 1) where distributions barely change and noise can be decreased rapidly ($\alpha \lesssim 0.6$), 2) where modes corresponding to each data point emerge and require fine control of noise to avoid mode dropping ($0.6 \lesssim \alpha \lesssim 0.97$), and 3) where mode peaks become sharp and noise must be reduced gradually for better fidelity ($\alpha \gtrsim 0.97$). This example illustrates that the distributional dynamics of the diffusion process are highly non-uniform. We hypothesize that the probability-distributional change represents the traceability of the diffusion process, and controlling the rate of distributional change can improve the quality and stability of the generative process.

CRS offers a unified and flexible framework for designing noise schedules, with the following key properties: 1) it supports both training and sampling schedules, 2) it allows the use of arbitrary discrepancy measures to quantify distributional change, enabling domain-specific tailoring and independent schedules for training and sampling, and 3) many existing schedules can be viewed as special cases of CRS under different discrepancy measures.

Our contributions are summarized as follows:

1. We propose a general framework for optimizing noise schedules in diffusion models by enforcing a constant rate of distributional change throughout the diffusion process. Our framework supports both training and sampling schedules and allows the use of any user-specified discrepancy measure.

2. We introduce three practical discrepancy measures for quantifying distributional change, each capturing different aspects of the diffusion process. These measures can be flexibly selected or combined, depending on the domain or model type (e.g., pixel-space or latent-space diffusion models).

3. While theoretically motivated, this work does not aim to provide a full formal analysis of the link between distributional change and sample quality. Instead, we focus on empirically validating the effectiveness of CRS across diverse experimental settings. Through extensive experiments, we demonstrate that CRS consistently improves the performance of both pixel-space and latent-space diffusion models across various datasets, samplers, and numbers of function evaluations (NFEs), ranging from 5 to 250.

The remainder of this paper is organized as follows: Sec. 2 reviews related work. Sec. 3 briefly introduces DDPMs. Sec. 4 presents our proposed framework. Sec. 5 provides the experimental results. Sec. 6 discusses limitations, and Sec. 7 concludes the paper.

2 Related work

The performance of generative models is typically evaluated along three axes: sampling speed, fidelity, and mode coverage. Diffusion models are known to excel in terms of fidelity and mode coverage, but suffer from slow sampling speed due to the iterative nature of the reverse process (Xiao et al., 2022). To address this limitation, a wide range of acceleration strategies have been proposed. These approaches can be broadly categorized into five groups:

Conditional generation: This strategy improves sampling speed by reducing sample diversity through conditioning (e.g., class labels or text prompts) (Dhariwal & Nichol, 2021; Ho & Salimans, 2021; Rombach et al., 2022; Saharia et al., 2022a; Nichol et al., 2022a; Podell et al., 2024b), which guides the model to generate specific outputs and avoid unnecessary exploration.

Dimensionality reduction: Latent diffusion models (LDMs) (Rombach et al., 2022) employ pre-trained autoencoders to compress data representations, allowing the diffusion process to operate in a lower-dimensional latent space. This improves both training and sampling efficiency.

Samplers: These methods improve the update rule of diffused data for the reverse process. Denoising diffusion implicit models (DDIMs) (Song et al., 2021a) introduce a non-Markovian process to generalize DDPMs and propose a deterministic sampler. In continuous-time diffusion models, the forward and reverse processes are formulated as stochastic differential equations (SDEs) and ordinary differential equations (ODEs) (Song et al., 2021b). Numerous studies have developed efficient solvers tailored to these formulations (Jolicoeur-Martineau et al., 2021; Liu et al., 2022; Lu et al., 2022a;b; Zhang & Chen, 2023; Zhao et al., 2023; Zheng et al., 2023b; Zhou et al., 2024).

Noise schedules: The choice of noise schedule significantly affects training and sampling efficiency. Early schedules, such as linear (Ho et al., 2020) and cosine (Nichol & Dhariwal, 2021), were chosen heuristically. More recently, principled approaches for optimizing sampling schedules have been proposed (Chen et al., 2024; Sabour et al., 2024; Williams et al., 2024; Park et al., 2025). Among them, Align Your Steps (AYS) (Sabour et al., 2024) determines a noise schedule to minimize the discretization errors measured using Kullback-Leibler divergence. One of the discrepancy measures in our approach can be interpreted as a simplified variant of Kullback-Leibler divergence upper bound (KLUB) introduced in AYS, and thus CRS generalizes AYS and related methods as special cases.

In contrast, elucidating diffusion models (EDMs) (Karras et al., 2022) and variational diffusion models++ (VDM++) (Kingma & Gao, 2023) have proposed optimization of the training schedule. These works also highlight that using different schedules for training and sampling can improve performance. However, most prior work has focused predominantly on sampling schedules, and optimization of training schedules remains relatively underexplored. CRS is designed to optimize both schedules within a unified framework, supporting the use of arbitrary and even composite discrepancy measures. This flexibility allows practitioners to adapt scheduling strategies based on empirical behavior and task-specific requirements.

Distillation: Distillation-based approaches are another major direction for fast sampling (Luhman & Luhman, 2021; Salimans & Ho, 2022; Song et al., 2023; Yin et al., 2024b;a; Frankel et al., 2025). These methods compress multi-step diffusion into fewer steps. CRS is orthogonal to this line of work and can provide better teacher models for distillation, as it can improve training schedules.

3 Background

We briefly introduce DDPMs (Feller, 2015).

In the forward process, Gaussian noise is gradually added to the data through a sequence of timesteps, transforming the data distribution into an isotropic Gaussian. This process is typically modeled as a Markov

chain that starts from a data sample $\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0)$:

$$q(\boldsymbol{x}_{0:T}) = \left(\prod_{t=1}^{T} q(\boldsymbol{x}_t | \boldsymbol{x}_{t-1}) \right) q(\boldsymbol{x}_0), \quad \text{where} \quad q(\boldsymbol{x}_t | \boldsymbol{x}_{t-1}) = \mathcal{N}(\boldsymbol{x}_t; \beta_t \boldsymbol{x}_{t-1}, \delta_t^2 \boldsymbol{I}). \tag{1}$$

Here, T denotes the number of timesteps, β_t is a decay factor controlling the signal strength, δ_t represents the added noise level, and $q(\boldsymbol{x}_0)$ is the data distribution.

It is straightforward to show that $q(\boldsymbol{x}_t | \boldsymbol{x}_0)$ takes the following form:

$$q(\boldsymbol{x}_t | \boldsymbol{x}_0) = \mathcal{N}(\boldsymbol{x}_t; \alpha_t \boldsymbol{x}_0, \sigma_t^2 \boldsymbol{I}) \tag{2}$$

where the coefficients satisfy the recursive relations: $\alpha_t = \beta_t \alpha_{t-1}$ and $\sigma_t^2 = \delta_t^2 + \beta_t^2 \sigma_{t-1}^2$. This formulation allows sampling of $\boldsymbol{x}_t$ from $\boldsymbol{x}_0$ in a single step. In this work, we parameterize the forward process using (α_t, σ_t) instead of (β_t, δ_t), and adopt a variance-preserving formulation in which both $\alpha_t^2 + \sigma_t^2 = 1$ and $\beta_t^2 + \delta_t^2 = 1$ hold. The sequence $\{\alpha_t\}_{t=0}^{T}$ defines the noise schedule, which controls how rapidly the signal component of the data decays during diffusion. Our goal is to optimize this noise schedule to enable more effective and efficient training and sampling in diffusion models.

In the reverse process, data samples are generated from Gaussian noise by tracing the forward process in the reverse direction. This process is also modeled as a Markov chain and is defined as:

$$p_\theta(\boldsymbol{x}_{0:T}) = \left(\prod_{t=1}^{T} p_\theta(\boldsymbol{x}_{t-1} | \boldsymbol{x}_t) \right) p(\boldsymbol{x}_T), \quad \text{where} \quad p(\boldsymbol{x}_T) = \mathcal{N}(\boldsymbol{x}_T; \boldsymbol{0}, \boldsymbol{I}). \tag{3}$$

Here, θ denotes the learnable parameters of the diffusion model. In the limit of $T \to \infty$, the reverse transitions can be well approximated by the Gaussian distributions (Feller, 2015):

$$p_\theta(\boldsymbol{x}_{t-1} | \boldsymbol{x}_t) = \mathcal{N}(\boldsymbol{x}_{t-1}; \boldsymbol{\mu}_\theta(\boldsymbol{x}_t, t), \nu_t^2 \boldsymbol{I}). \tag{4}$$

DDPMs employ a noise prediction model $\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}_t, t)$, which predicts the noise added at timestep t. The predicted mean $\boldsymbol{\mu}_\theta(\boldsymbol{x}, t)$ is given by:

$$\boldsymbol{\mu}_\theta(\boldsymbol{x}, t) = \frac{1}{\beta_t} \left(\boldsymbol{x}_t - \frac{\delta_t^2}{\sigma_t} \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, t) \right). \tag{5}$$

The noise prediction model is trained by maximizing a simplified version of the variational lower bound, which yields a practical and stable learning objective.

4 General Approach for Optimizing Noise Schedule

We explain our motivation and present CRS.

4.1 Motivation

As stated in Sec. 3, when T is sufficiently large, it is a good approximation to assume that the reverse transitions $p_\theta(\boldsymbol{x}_{t-1} | \boldsymbol{x}_t)$ follow a Gaussian distribution, as expressed in Eq. (4). This implies that the distributional change between adjacent timesteps must be small enough to be well approximated by a Gaussian distribution. In diffusion models, sample quality depends on how faithfully the reverse process can trace the forward process. Large distributional changes can lead to poor approximation, resulting in artifacts or mode dropping. This observation motivates us to minimize the maximum distributional change during the diffusion process, in order to maintain the validity of Eq. (4) throughout the trajectory.

The importance of controlling distributional change can also be understood from the perspective of noise conditional score networks (NCSNs) (Song & Ermon, 2019; 2020; Song et al., 2021b), which are the conceptual predecessors of diffusion models. According to the manifold hypothesis, natural data typically lie on a

low-dimensional manifold embedded in high-dimensional space. This leads to two main challenges when generating samples using only the score function $\nabla_{\boldsymbol{x}} \log q(\boldsymbol{x})$ from a randomly initialized point $\boldsymbol{x}_{\text{rnd}}$ (Song & Ermon, 2019): first, $\boldsymbol{x}_{\text{rnd}}$ is likely to fall in regions where $q(\boldsymbol{x}_{\text{rnd}}) \ll 1$, making it difficult to estimate accurate gradients; second, even if the score is correctly estimated, it tends to be small in such regions, leading to slow mixing.

To address these challenges, NCSNs interpolate between the data distribution and a Gaussian distribution, whose support spans the entire space. If the distributional change between adjacent steps is kept small during this interpolation, each reverse step is likely to remain within regions of high probability density. This improves the reliability of local updates and enhances overall sample quality.

These theoretical motivations form the basis for our proposed framework: to design noise schedules that ensure a constant rate of change in the distribution of the diffused data across timesteps.

4.2 Constant Rate Scheduling

As described above, our goal is to optimize noise schedules by minimizing the maximum distributional change between adjacent timesteps in the diffusion process. Let $D(t, t + \Delta t)$ denote a discrepancy measure between the distributions of diffused data $q(\boldsymbol{x}_t)$ and $q(\boldsymbol{x}_{t+\Delta t})$. Our criterion can be formulated as:

$$\operatorname*{argmin}_{\alpha(t)} \left(\max_t D(t, t + \Delta t) \right). \tag{6}$$

This optimization problem has a straightforward solution as follows:

$$D(t, t + \Delta t) = \frac{D(t, t + \Delta t) - D(t, t)}{\Delta t} \Delta t \simeq \left. \frac{\partial D(t, t')}{\partial t'} \right|_{t'=t} \Delta t = \text{const.}, \tag{7}$$

where we used $D(t, t) = 0$.

To explicitly reflect the dependence on the noise schedule, we rewrite $D(t, t')$ as $\tilde{D}(\alpha(t), \alpha(t')) \equiv \tilde{D}(\alpha, \alpha')$, where $\alpha(t)$ is the noise schedule to be optimized. This leads to:

$$D(t, t + \Delta t) \simeq \left. \frac{\partial D(t, t')}{\partial t'} \right|_{t'=t} \Delta t = v(\alpha) \frac{d\alpha(t)}{dt} \Delta t = \text{const.}, \tag{8}$$

where $v(\alpha)$ represents the rate of change in the probability distribution of the diffused data.

Therefore, the noise schedule must satisfy $\frac{d\alpha(t)}{dt} \propto v(\alpha)^{-1}$. The proportionality constant is computed from the boundary conditions $\alpha(0) = \alpha_{\max}$ and $\alpha(1) = \alpha_{\min}$, yielding:

$$-\frac{d\alpha(t)}{dt} = Cv(\alpha)^{-\xi}, \quad \text{where} \quad C = \int_{\alpha_{\min}}^{\alpha_{\max}} v(\alpha)^{\xi} d\alpha, \tag{9}$$

where we introduce a hyperparameter $\xi > 0$ to control the dependence of $\alpha(t)$ on $v(\alpha)$. Larger values of ξ allocate more timesteps to regions where $v(\alpha)$ is large, i.e., where the distribution changes rapidly.

The noise schedule optimization using CRS consists of the following steps:

1. Choose a discrepancy measure to quantify distributional change.

2. Compute $v(\alpha)$ using the selected discrepancy measure.

3. Solve Eq. (9) to obtain $\alpha(t)$.

4. Apply the resulting schedule as follows:
   - For training, use $\alpha(t)$ directly.
   - For sampling, discretize the schedule uniformly in time: $\{\alpha(t/T)|t = 0, 1, ..., T\}$ where T is the number of sampling steps.

We propose three discrepancy measure for computing $v(\alpha)$, which are detailed in Section 4.3.

Similar to NCSNs inspired by simulated annealing (Kirkpatrick et al., 1983), our formulation draws additional motivation from the adiabatic theorem (Morita & Nishimori, 2008) in quantum annealing (Kadowaki & Nishimori, 1998). Quantum annealing solves combinatorial optimization problems by interpolating between a target cost function and an initial one that has a trivial optimum. The optimization starts from the known optimum of the initial function and aims to trace the instantaneous optimums along the interpolation path. It is crucial to accurately trace the optimum of the instantaneous cost function, and the adiabatic theorem provides the traceability of the optimum at each step. Let $\alpha(t)$ be the weight of the target cost function and $1 - \alpha(t)$ be the weight of the initial cost function. In this setting, the inverse traceability is expressed in the form of $\frac{d\alpha(t)}{dt} v(\alpha)$, which takes the same form as Eq. (8). Prior work has shown that minimizing the maximum value of this inverse traceability yields the optimal $\alpha(t)$ (Roland & Cerf, 2002), that ensures consistent traceability throughout the interpolation. In CRS, we regard the rate of probability-distributional change as the inverse traceability and minimize its maximum value to derive an optimal noise schedule.

4.3 Discrepancy Measures

Any discrepancy measure is applicable to CRS. We introduce three discrepancy measures.

4.3.1 Discrepancy measure based on FID

FID is a widely used metric for evaluating sample fidelity in the field of image generation. It computes the Fréchet distance (Heusel et al., 2017) between the feature distributions of real and generated images under a Gaussian assumption, where the features are extracted using the Inception-V3 network (Szegedy et al., 2016) trained on ImageNet classification.

When used as a discrepancy measure in our framework, $v(\alpha)$ tends to take large values in the region where sample fidelity significantly degrades (i.e., $\alpha \simeq 1$). As a result, CRS allocates more timesteps to this region, thereby improving sample fidelity.

However, a limitation of the FID-based measure is that it fails to accurately capture distributional changes in high-noise regions ($\alpha \simeq 0$), since the feature extractor is not trained on heavily diffused images and may not provide meaningful representations in that regime. Therefore, while the FID-based measure is effective for capturing fidelity-related changes in low-noise regions, it may benefit from being complemented by other discrepancy measures that can better capture high-noise dynamics.

Once the forward process is defined, $v(\alpha)$ can be computed by simulating the forward diffusion using the training dataset (see Algorithm 1 in Appendix C.1). Since this procedure is independent of model parameters, it only needs to be executed once prior to training the diffusion model.

The computation time of $v(\alpha)$ is proportional to the number of training images, which may be prohibitively expensive for large-scale training datasets. To address the scalability issue for large-scale datasets, we introduce a practical alternative in Sec. 5.6.

We refer to $v(\alpha)$ computed using FID as $v_{\text{FID}}(\alpha)$.

4.3.2 Discrepancy measure based on data prediction

We introduce a discrepancy measure that leverages a trained diffusion model as follows:

$$v_x(\alpha) = \sqrt{\left. \frac{\partial \overline{D_x^2}(\alpha, \alpha')}{\partial \alpha'} \right|_{\alpha' = \alpha}}, \quad \text{where} \quad \overline{D_x^2}(\alpha, \alpha') = \mathbb{E}_{\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'} \sim q(\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'})} \left[\| \boldsymbol{x}_\theta(\boldsymbol{x}_\alpha, \alpha) - \boldsymbol{x}_\theta(\boldsymbol{x}_{\alpha'}, \alpha') \|_2^2 \right]. \quad (10)$$

Here, $q(\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'})$ is the joint distribution of diffused data at different noise levels, and $\boldsymbol{x}_\theta(\boldsymbol{x}, \alpha)$ denotes the data prediction, which is related to the noise prediction $\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)$ via $\boldsymbol{x} = \alpha \boldsymbol{x}_\theta(\boldsymbol{x}, \alpha) + \sigma \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)$.

This measure is designed to allocate more computational resources to regions where the data prediction changes rapidly with respect to α. As shown in Appendix B, $v_x(\alpha)$ can be interpreted as a simplified variant

of KLUB, introduced in AYS. Importantly, $v_x(\alpha)$ can be used not only to determine the sampling schedule after training, but also to adaptively optimize the training schedule during learning.

We further interpret $v_x(\alpha)$ as measuring the probability-distributional change of the diffused data. According to prior work (Ambrogioni, 2024), the data prediction $\boldsymbol{x}_\theta(\boldsymbol{x}, \alpha)$ can be viewed as a weighted average over training data points $\boldsymbol{x}_0$, where the weighting depends on the noise level α. When $\alpha = 0$, the weights are approximately uniform across the dataset. As $\alpha \to 1$, only a few data points contribute significantly, indicating sharper and more specific representations. The change in these implicit weights reflects how sample trajectories diverge as noise decreases, and thus $v_x(\alpha)$ provides a proxy for the rate of distributional change.

The pseudocode for optimizing training and sampling schedules is provided in Appendix C.2. For sampling schedule optimization, the computation time of $v_x(\alpha)$ is negligible compared to the overall training time. In contrast, training schedule optimization requires updating $\overline{D_x^2}(\alpha, \alpha')$ during training as the model parameters evolve, which increases the total training time by approximately 20–30%. However, our experiments show that the schedule typically stabilizes early in training. Therefore, fixing the schedule after a few epochs or reducing the update frequency of $\overline{D_x^2}(\alpha, \alpha')$ may mitigate the computational cost without compromising performance. Developing a more efficient implementation remains an important direction for future work.

4.3.3 Discrepancy measure based on noise prediction

In the experiments presented in Sec. 5, we trained the noise prediction model. In this setting, it is also effective to use the noise predictions themselves to quantify distributional change, leading to the following definition:

$$v_\varepsilon(\alpha) = \sqrt{\left. \frac{\partial \overline{D_\varepsilon^2}(\alpha, \alpha')}{\partial \alpha'} \right|_{\alpha' = \alpha}}, \quad \text{where} \quad \overline{D_\varepsilon^2}(\alpha, \alpha') = \mathbb{E}_{\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'} \sim q(\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'})} \left[\|\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}_\alpha, \alpha) - \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}_{\alpha'}, \alpha')\|_2^2 \right]. \quad (11)$$

We refer to CRS using $v_{\text{FID}}(\alpha)$, $v_x(\alpha)$, and $v_\varepsilon(\alpha)$ as CRS-v_{FID}, CRS-v_x, and CRS-v_ε, respectively, depending on the choice of discrepancy measure used to compute $v(\alpha)$.

4.4 Combining Multiple Discrepancy Measures

Each discrepancy measure has its own strengths and weaknesses. For example, CRS-v_{FID} effectively captures distributional changes relevant to sample fidelity, but fails to represent changes accurately in high-noise regions ($\alpha \simeq 0$), as the feature extractor is not trained on diffused images. On the other hand, CRS-v_x captures distributional change even in high-noise regions, but it is not necessarily optimal for improving sample fidelity. Therefore, it is considered effective to complementarily combining multiple discrepancy measures for optimizing noise schedules.

We introduce the following strategy for combining multiple discrepancy measures:

$$v(\alpha) = \sum_{m=1}^{M} w_m \tilde{v}_m(\alpha), \quad \text{where} \quad \tilde{v}_m(\alpha) = \frac{1}{C_m} v_m(\alpha)^{\xi_m} \quad \text{and} \quad C_m = \int_{\alpha_{\min}}^{\alpha_{\max}} v_m(\alpha)^{\xi_m}. \quad (12)$$

where M is the number of discrepancy measures, $v_m(\alpha)$ is the rate of change computed using the m-th measure, w_m is its corresponding weight (satisfying $\sum_{m=1}^{M} w_m = 1$), and ξ_m controls the emphasis on $v_m(\alpha)$. Since the value ranges of different discrepancy measures can vary significantly, we normalize each $v_m(\alpha)$ as in Eq. (12) before combining them.

This formulation also enables conventional noise schedules to be interpreted and incorporated within the CRS framework. By converting a given noise schedule $\alpha(t)$ into its corresponding form of $v(\alpha)$, we can treat it as an implicit discrepancy measure. For example, if $\alpha(t) = \cos\left(\frac{\pi t}{2}\right)$, then:

$$v(\alpha) \propto -\left(\frac{d\alpha(t)}{dt} \right)^{-1} \propto \sin^{-1}\left(\frac{\pi t}{2} \right) = \frac{1}{\sqrt{1 - \alpha^2}}. \quad (13)$$

This observation implies that any noise schedule can be viewed as the optimization result of CRS with an associated (possibly implicit) discrepancy measure, thus providing a unified perspective on the design of noise schedules.

While combining multiple discrepancy measures increases the flexibility of CRS, it also introduces additional hyperparameters. In our experiments, we found that tuning these hyperparameters is required only when optimizing sampling schedules in pixel-space diffusion models. In all other cases—training schedules for both pixel-space and latent-space models, and sampling schedules for latent-space models—CRS-v_x with $\xi = 1$ consistently performed well and can serve as a default setting.

5 Experiments

We experimentally demonstrate that CRS broadly improves the performance of diffusion models.

5.1 Experimental Settings

Below, we provide a brief overview of the components and settings used in our experiments.

Dataset: We use six image datasets: LSUN (Church, Bedroom, Horse) (Yu et al., 2016), ImageNet (Deng et al., 2009), FFHQ (Karras et al., 2019), and CIFAR10 (Krizhevsky, 2009). LSUN and FFHQ are used for unconditional image generation, while ImageNet and CIFAR10 are used for class-conditional image generation.

Noise Prediction Model: We adopt the U-Net architecture introduced in the ablated diffusion model (ADM) (Dhariwal & Nichol, 2021) as the noise prediction model. Hyperparameter settings are listed in Table 8 (Appendix E).

Training Schedule: We compare four training noise schedules: linear (Ho et al., 2020), shifted cosine (Hoogeboom et al., 2023), the adaptive schedule proposed in VDM++ (Kingma & Gao, 2023), and our proposed CRS.

Loss Function: Except for the adaptive schedule in VDM++, we use the simplified loss function from DDPMs:

$$L = \frac{1}{2}\mathbb{E}_{\boldsymbol{x}_0\sim\mathcal{D},t\sim\mathcal{U}(0,1),\boldsymbol{\varepsilon}\sim\mathcal{N}(\mathbf{0},\boldsymbol{I})}\left[\left\|\boldsymbol{\varepsilon}_\theta(\boldsymbol{x},\alpha(t)) - \boldsymbol{\varepsilon}\right\|_2^2\right], \tag{14}$$

where $\boldsymbol{x} = \alpha(t)\boldsymbol{x}_0 + \sqrt{1 - \alpha(t)^2}\boldsymbol{\varepsilon}$, $\mathcal{D}$ denotes the training dataset, and $\alpha(t)$ is the training schedule.

When using the adaptive schedule from VDM++, the following loss function is used:

$$L = \frac{1}{2}\mathbb{E}_{\boldsymbol{x}_0\sim\mathcal{D},\lambda\sim p(\lambda),\boldsymbol{\varepsilon}\sim\mathcal{N}(\mathbf{0},\boldsymbol{I})}\left[\frac{\omega(\lambda)}{p(\lambda)}\left\|\boldsymbol{\varepsilon}_\theta\left(\boldsymbol{x},\sqrt{\mathrm{sigmoid}(\lambda)}\right) - \boldsymbol{\varepsilon}\right\|_2^2\right], \tag{15}$$

where $\lambda = \log\left(\frac{\alpha^2}{\sigma^2}\right)$ is the log signal-to-noise ratio (log-SNR), $\omega(\lambda)$ is the weighting function, and $p(\lambda) = -\frac{d\lambda}{dt}$ denotes the noise schedule. We adopt the EDM monotonic function as $\omega(\lambda)$, and update $p(\lambda)$ at each iteration to approximately satisfy:

$$p(\lambda) \propto \mathbb{E}_{\boldsymbol{x}_0\sim\mathcal{D},\boldsymbol{\varepsilon}\sim\mathcal{N}(\mathbf{0},\boldsymbol{I})}\left[\omega(\lambda)\left\|\boldsymbol{\varepsilon}_\theta\left(\boldsymbol{x},\sqrt{\mathrm{sigmoid}(\lambda)}\right) - \boldsymbol{\varepsilon}\right\|_2^2\right]. \tag{16}$$

Sampling Schedule: We evaluate four sampling schedules: linear, shifted cosine, EDM (Karras et al., 2022), and CRS. For pixel-space diffusion models, we additionally evaluate CRS-$v_x + v_{\mathrm{FID}}$, which combines $v_x(\alpha)$ and $v_{\mathrm{FID}}(\alpha)$ to leverage their complementary strengths, as discussed in Sec. 5.5. Following prior work (Karras et al., 2022; Kingma & Gao, 2023), we allow training and sampling schedules to differ. We thus evaluate all combinations of training and sampling schedules. Details of the conventional schedules are summarized in Table 11 (Appendix E).

Sampling Methods: To assess the generality across samplers, we employ two stochastic samplers and three deterministic samplers. The stochastic samplers include Stochastic DDIM ($\eta = 1$) (Song et al., 2021a)

and SDE-DPM-Solver++(2M) (Lu et al., 2022b). The deterministic samplers include DDIM (Song et al., 2021a), DPM-Solver++(2M) (Lu et al., 2022b), and pseudo numerical methods (PNDM) (Liu et al., 2022). At low NFE regimes, we also evaluate improved PNDM (iPNDM) (Zhang & Chen, 2023) and the unified predictor-corrector framework (UniPC) (Zhao et al., 2023).

Evaluation Metrics: We use four evaluation metrics: FID (Heusel et al., 2017), spatial FID (sFID) (Nash et al., 2021), and improved precision and recall (Sajjadi et al., 2018; Kynkäänniemi et al., 2019). FID, sFID, and precision measure sample fidelity, while recall quantifies mode coverage.

5.2 Results on Pixel-Space Diffusion Models

We trained continuous-time diffusion models on LSUN Horse 256×256 and LSUN Bedroom 256×256 for unconditional image generation. Detailed experimental results are provided in Appendix F.1.

LSUN Horse 256×256: The evaluation results are summarized in Table 1. Rows shaded in gray represent results obtained under different training schedules. Although sample fidelity and mode coverage are generally considered to be in a trade-off relationship, CRS-v_x achieved the highest scores across all evaluation metrics. This indicates that CRS-v_x does not merely balance fidelity and diversity but leads to an overall improvement in sample quality.

The unshaded rows represent the dependence on sampling schedules. CRS-v_x + v_{FID} outperformed all baselines across all metrics, indicating a fundamental improvement in generation quality (see Appendix D for the hyperparameter tuning details). Notably, our model achieved an FID score of 2.03, surpassing the previous state-of-the-art score of 2.11 reported in Kumari et al. (2022).

LSUN Bedroom 256×256: We further validated the effectiveness of CRS in low-NFE regimes by comparing it with strong baselines reported in GITS (Chen et al., 2024). We trained continuous-time diffusion models with CRS-v_x used for optimizing the training schedule. Table 2 lists the results. At NFE = 5 and NFE = 10, the best FID scores were achieved by using CRS-v_x and CRS-v_x + v_{FID} for optimizing training and sampling schedules, respectively.

As shown in Table 15 in Appendix F.1, we also tuned the ρ parameter in the EDM sampling schedule. Even with the optimal ρ setting, CRS-v_x + v_{FID} consistently outperformed EDM.

5.3 Results on Latent-Space Diffusion Models

We trained latent-space diffusion models using the pre-trained VQ-4 autoencoder from LDMs (Rombach et al., 2022). LSUN Church and LSUN Bedroom were used for unconditional image generation, and ImageNet was used for class-conditional image generation. All images were resized to 256×256 and encoded into 64×64 latent representations. Here, we present the evaluation results on LSUN Church 256×256. Detailed results are provided in Appendix F.2.

LSUN Church 256×256: Table 3 summarizes the results. Rows shaded in gray show the effect of different training schedules, where CRS-v_x achieved the best performance on all metrics except sFID. Unshaded rows show the dependence on the sampling schedule, and again, CRS-v_x achieved the best performance on all metrics except precision.

These results indicate that CRS is also effective in latent-space diffusion models. Although CRS-v_x performs best in most settings, we observe that depending on the sampler and NFEs, CRS-v_ε can be preferable for sampling.

5.4 Comparison with AYS Using a Pretrained EDM Model

Since $v_x(\alpha)$ is closely related to the KLUB introduced in AYS, we additionally compare CRS with AYS on FFHQ 64×64 using the pretrained model provided by EDMs (Karras et al., 2022).

It is important to note that EDM adopts a variance-exploding formulation, whereas all of our previous experiments have been conducted under the variance-preserving setting. However, CRS can still be applied

Table 1: Performance of pixel-space diffusion models on LSUN Horse 256×256 with NFE = 250, using SDE-DPM-Solver++(2M) as the sampler. Gray-shaded rows indicate variations in the training schedule, while unshaded rows correspond to different sampling schedules. Bold values highlight the best performance for each metric under varying training or sampling schedules.

Training schedule	Sampling schedule	Metrics			
		FID ↓	sFID ↓	Precision ↑	Recall ↑
Linear	Linear	2.90	6.82	0.66	**0.56**
Shifted cosine		2.95	6.43	**0.67**	**0.56**
VDM++		3.82	7.40	0.66	0.54
CRS-v_ε		2.91	6.56	0.66	**0.56**
CRS-v_x		**2.73**	**6.40**	**0.67**	**0.56**
CRS-v_x	Linear	2.73	6.40	0.67	**0.56**
	Shifted cosine	3.13	7.09	0.67	0.54
	EDM	2.09	6.16	**0.69**	**0.56**
	CRS-v_ε	2.87	6.71	0.66	0.56
	CRS-v_x	5.46	8.34	0.62	0.52
	CRS-$v_x + v_{\mathrm{FID}}$	**2.03**	**6.06**	**0.69**	**0.56**

Table 2: FID scores for LSUN Bedroom 256×256 in pixel-space diffusion models under low NFE conditions. Our results are compared with prior work from Chen et al. (2024). Bold entries indicate the best FID achieved at each NFE setting.

Model	Sampler	Sampling schedule	NFE = 5	NFE = 10
EDM	UniPC (Zhao et al., 2023)	EDM	23.34	5.75
	AMED-Solver (Zhou et al., 2024)		–	5.38
	iPNDM (Zhang & Chen, 2023)	GITS (Chen et al., 2024)	15.85	5.28
Ours	DPM-Solver++(2M)	EDM	23.72	4.73
		CRS-$v_x + v_{\mathrm{FID}}$	**14.02**	4.88
	UniPC	EDM	82.52	4.94
		CRS-$v_x + v_{\mathrm{FID}}$	21.42	**3.30**

to variance-exploding processes by converting between α and the EDM noise level σ_{EDM} via the log-SNR, as shown below:

$$\log \mathrm{SNR} = \log\left(\frac{\alpha^2}{1-\alpha^2}\right) = \log\left(\frac{1}{\sigma_{\mathrm{EDM}}^2}\right) \quad \Rightarrow \quad \alpha = \frac{1}{\sqrt{1+\sigma_{\mathrm{EDM}}^2}}. \tag{17}$$

The results are presented in Table 4. CRS-$v_x + v_{\mathrm{FID}}$ consistently outperforms AYS across all NFE settings, demonstrating the effectiveness of CRS even in the variance-exploding regime. Detailed results using the pretrained EDM model are provided in Appendix F.3

5.5 Comparison of Noise Schedules

Figure 2 shows examples of CRS-based noise schedules in pixel-space diffusion models, computed using different discrepancy measures. For CRS-$v_x + v_{\mathrm{FID}}$, the hyperparameters were set to $w_x = w_{\mathrm{FID}} = 0.5$ and $\xi_x = \xi_{\mathrm{FID}} = 1.0$.

Since $v_{\mathrm{FID}}(\alpha)$ tends to be large in regions where sample fidelity degrades (i.e., near $\alpha \simeq 1$), CRS-v_{FID} allocates more timesteps to these regions. In contrast, CRS-v_x allocates more timesteps to regions with smaller α. This is due to the formulation of the data prediction $\boldsymbol{x}_\theta(\boldsymbol{x}, \alpha) = \frac{\boldsymbol{x} - \sigma\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)}{\alpha}$, where α appears in the denominator, making the data prediction more sensitive to small changes in α when α is small. Thus, CRS-v_{FID} and CRS-v_x exhibit complementary behaviors, and combining both yields an effective and balanced sampling schedule.

Furthermore, we observed that the noise schedule derived from CRS-v_ε can be approximately reproduced by appropriately tuning the hyperparameters of CRS-$v_x + v_{\mathrm{FID}}$. Therefore, in practice, $v_x(\alpha)$ and $v_{\mathrm{FID}}(\alpha)$ serve as the two principal components for constructing robust sampling schedules.

Table 3: Performance of latent-space diffusion models on LSUN Church 256×256 with NFE = 30, using DPM-Solver++(2M) as the sampler. Gray-shaded rows indicate variations in the training schedule, while unshaded rows correspond to different sampling schedules. Bold values highlight the best performance for each metric under varying training or sampling schedules.

Training schedule	Sampling schedule	Metrics			
		FID ↓	sFID ↓	Precision ↑	Recall ↑
Linear	Linear	3.82	10.28	**0.60**	0.58
VDM++		4.00	**10.07**	0.58	**0.59**
CRS-v_{FID}		3.78	10.51	**0.60**	0.58
CRS-v_ε		3.87	10.30	**0.60**	**0.59**
CRS-v_x		**3.69**	10.23	**0.60**	**0.59**
CRS-v_x	Linear	3.69	10.23	**0.60**	0.59
	EDM	4.31	11.31	**0.60**	0.56
	CRS-v_{FID}	3.98	9.61	0.58	**0.60**
	CRS-v_ε	3.63	9.91	0.59	**0.60**
	CRS-v_x	**3.59**	**9.51**	0.59	**0.60**

Table 4: FID scores on FFHQ 64×64 evaluated using the pretrained model provided by EDM (Karras et al., 2022). Bold values indicate the best performance at each NFE. Results for AYS are taken from the original paper (Sabour et al., 2024).

Sampler	Noise Schedule	NFE = 10	NFE = 20	NFE = 50
DPM-Solver++(2M)	AYS (Sabour et al., 2024)	5.43	3.29	2.62
	CRS-$v_x + v_{\mathrm{FID}}$	**4.70**	**2.87**	**2.52**

Table 5: Evaluation of CRS-$v_x + v_{\cos}$ as a practical alternative to CRS-$v_x + v_{\mathrm{FID}}$ for sampling in pixel-space diffusion models on LSUN Bedroom 256×256. Despite not requiring the computation of $v_{\mathrm{FID}}(\alpha)$, CRS-$v_x + v_{\cos}$ achieves similar FID scores.

Sampler	Sampling Schedule	NFE = 5	NFE = 10
DPM-Solver++(2M)	CRS-$v_x + v_{\mathrm{FID}}$	14.02	4.88
	CRS-$v_x + v_{\cos}$	14.10	4.46
UniPC	CRS-$v_x + v_{\mathrm{FID}}$	21.42	3.30
	CRS-$v_x + v_{\cos}$	20.77	3.30

Figure 3 illustrates CRS-based noise schedules for latent-space diffusion models. The optimized schedules differ notably between pixel-space and latent-space models. In latent-space diffusion, fewer timesteps are allocated to the region where $\alpha \simeq 1$. This difference can be attributed to the nature of latent-space diffusion models: perceptual expression is largely reconstructed by the autoencoder, and the autoencoder is robust to minor deviations in the generated latent variables. Consequently, precise control near $\alpha \simeq 1$ is less critical. In contrast, pixel-space models directly generate the final image, so the schedule must allocate sufficient timesteps near $\alpha \simeq 1$ to preserve high-fidelity details.

Because all discrepancy measures result in similar noise schedules for latent-space models, we did not evaluate combinations of multiple discrepancy measures.

5.6 A Practical Alternative to FID-Based Scheduling

In pixel-space diffusion models, CRS-$v_x + v_{\mathrm{FID}}$ consistently achieves the best performance as a sampling schedule. However, for large-scale training datasets, computing $v_{\mathrm{FID}}(\alpha)$ becomes prohibitively expensive.

As shown in the previous subsection, CRS-v_{FID} allocates a large number of timesteps to regions near $\alpha \simeq 1$, resulting in a schedule shape similar to that of the cosine schedule. Motivated by this observation, we evaluate a lightweight alternative: CRS-$v_x + v_{\cos}$, which combines CRS-v_x with the cosine schedule (see Eq. 13 for $v(\alpha)$ of the cosine schedule).

Figure 2: Noise schedules computed using different discrepancy measures on LSUN Horse 256×256 in the pixel-space diffusion model.

Figure 3: Noise schedules computed using different discrepancy measures on LSUN Church 256×256 in the latent-space diffusion model.

Table 5 compares the FID scores of CRS-$v_x + v_{\text{FID}}$ and CRS-$v_x + v_{\cos}$ on LSUN Bedroom 256×256. In all settings, CRS-$v_x + v_{\cos}$ achieves FID scores comparable to CRS-$v_x + v_{\text{FID}}$, demonstrating that CRS-$v_x + v_{\cos}$ is a practical and effective alternative when $v_{\text{FID}}(\alpha)$ is costly to compute.

6 Limitations

This paper focuses on developing CRS and empirically validating its effectiveness under fundamental experimental settings. While the results are promising, there are several directions for future work to further enhance the generality and applicability of CRS: 1) a complete formal analysis of the relationship between distributional change and sample quality, 2) validation across a wider range of generation tasks and conditions, 3) empirical validation on large-scale datasets and high-resolution inputs, and 4) extension to domains beyond image generation.

Although $v_{\text{FID}}(\alpha)$ has proven effective as a discrepancy measure for designing sampling schedules in pixel-space diffusion models, it is inherently tailored to image generation due to its reliance on vision-specific feature extractors such as Inception-V3. Therefore, when applying CRS to other modalities (e.g., text, audio, graphs), it may be necessary to develop new discrepancy measures that better reflect the characteristics and inductive biases of the target domain.

7 Conclusion

We proposed a general framework called CRS for optimizing noise schedules in diffusion models. CRS enforces a constant rate of distributional change throughout the diffusion process and provides a unified perspective for designing both training and sampling schedules. Our framework supports arbitrary user-specified discrepancy measures, and we introduced three practical options that capture different aspects of the distributional dynamics.

Through extensive experiments, we demonstrated that CRS consistently improves the performance of both pixel-space and latent-space diffusion models across various datasets, samplers, and NFEs ranging from 5 to 250. In particular, for sampling in pixel-space diffusion models, CRS-$v_x + v_{\text{FID}}$ with tuned hyperparameters achieved the best results. In all other settings, CRS-v_x with $\xi = 1$ performed consistently well and is recommended as a default configuration due to its simplicity and robustness.

Although this study has limitations, as discussed in Sec. 6—including the lack of a complete theoretical analysis and the need for further validation in other domains—we believe that CRS provides a solid and extensible foundation for future research on schedule optimization in diffusion models. We hope that this work encourages broader exploration of discrepancy-based scheduling, and that future research will further generalize CRS and extend its applicability beyond image generation.

References

Luca Ambrogioni. The statistical thermodynamics of generative diffusion models: Phase transitions, symmetry breaking and critical instability. *arXiv preprint arXiv:2310.17467*, 2024.

Defang Chen, Zhenyu Zhou, Can Wang, Chunhua Shen, and Siwei Lyu. On the trajectory regularity of ODE-based diffusion sampling. In *Forty-first International Conference on Machine Learning*, 2024.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

Prafulla Dhariwal and Alexander Nichol. Diffusion models beat gans on image synthesis. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 8780–8794. Curran Associates, Inc., 2021.

Kenji Doi, Shuntaro Okada, Ryota Yoshihashi, and Hirokatsu Kataoka. Real-srgd: Enhancing real-world image super-resolution with classifier-free guided diffusion. In *Proceedings of the Asian Conference on Computer Vision (ACCV)*, pp. 3739–3755, December 2024.

William Feller. *RETRACTED CHAPTER: On the Theory of Stochastic Processes, with Particular Reference to Applications*, pp. 769–798. Springer International Publishing, Cham, 2015. ISBN 978-3-319-16859-3. doi: 10.1007/978-3-319-16859-3_42.

Eric Frankel, Sitan Chen, Jerry Li, Pang Wei Koh, Lillian J. Ratliff, and Sewoong Oh. S4s: Solving for a diffusion model solver. *arXiv preprint arXiv:2502.17423*, 2025.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. In *NeurIPS 2021 Workshop on Deep Generative Models and Downstream Applications*, 2021.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 6840–6851. Curran Associates, Inc., 2020.

Jonathan Ho, William Chan, Chitwan Saharia, Jay Whang, Ruiqi Gao, Alexey Gritsenko, Diederik P. Kingma, Ben Poole, Mohammad Norouzi, David J. Fleet, and Tim Salimans. Imagen video: High definition video generation with diffusion models. *arXiv preprint arXiv:2210.02303*, 2022a.

Jonathan Ho, Tim Salimans, Alexey Gritsenko, William Chan, Mohammad Norouzi, and David J Fleet. Video diffusion models. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 8633–8646. Curran Associates, Inc., 2022b.

Emiel Hoogeboom, Jonathan Heek, and Tim Salimans. Simple diffusion: End-to-end diffusion for high resolution images. *arXiv preprint arXiv:2301.11093*, 2023.

Alexia Jolicoeur-Martineau, Ke Li, Rémi Piché-Taillefer, Tal Kachman, and Ioannis Mitliagkas. Gotta go fast when generating data with score-based models. *arXiv preprint arXiv:2105.14080*, 2021.

Tadashi Kadowaki and Hidetoshi Nishimori. Quantum annealing in the transverse ising model. *Phys. Rev. E*, 58:5355–5363, Nov 1998. doi: 10.1103/PhysRevE.58.5355.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4396–4405, 2019. doi: 10.1109/CVPR.2019.00453.

Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022.

Diederik P Kingma and Ruiqi Gao. Understanding diffusion objectives as the ELBO with simple data augmentation. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. Optimization by simulated annealing. *Science*, 220(4598): 671–680, 1983. doi: 10.1126/science.220.4598.671.

Zhifeng Kong, Wei Ping, Jiaji Huang, Kexin Zhao, and Bryan Catanzaro. Diffwave: A versatile diffusion model for audio synthesis. In *International Conference on Learning Representations*, 2021.

Alex Krizhevsky. Learning multiple layers of features from tiny images, 2009.

Nupur Kumari, Richard Zhang, Eli Shechtman, and Jun-Yan Zhu. Ensembling off-the-shelf models for gan training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10651–10662, June 2022.

Tuomas Kynkäänniemi, Tero Karras, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Improved precision and recall metric for assessing generative models. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Luping Liu, Yi Ren, Zhijie Lin, and Zhou Zhao. Pseudo numerical methods for diffusion models on manifolds. In *International Conference on Learning Representations*, 2022.

Cheng Lu, Yuhao Zhou, Fan Bao, Jianfei Chen, Chongxuan Li, and Jun Zhu. DPM-solver: A fast ODE solver for diffusion probabilistic model sampling in around 10 steps. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022a.

Cheng Lu, Yuhao Zhou, Fan Bao, Jianfei Chen, Chongxuan Li, and Jun Zhu. DPM-Solver++: Fast solver for guided sampling of diffusion probabilistic models. *arXiv preprint arXiv:2211.01095*, 2022b.

Eric Luhman and Troy Luhman. Knowledge distillation in iterative generative models for improved sampling speed. *arXiv preprint arXiv:2101.02388*, 2021.

Satoshi Morita and Hidetoshi Nishimori. Mathematical foundation of quantum annealing. *Journal of Mathematical Physics*, 49(12):125210, 12 2008. ISSN 0022-2488. doi: 10.1063/1.2995837.

Charlie Nash, Jacob Menick, Sander Dieleman, and Peter W. Battaglia. Generating images with sparse representations. *arXiv preprint arXiv:2103.03841*, 2021.

Alexander Quinn Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 8162–8171. PMLR, 18–24 Jul 2021.

Alexander Quinn Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob Mcgrew, Ilya Sutskever, and Mark Chen. GLIDE: Towards photorealistic image generation and editing with text-guided diffusion models. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 16784–16804. PMLR, 17–23 Jul 2022a.

Alexander Quinn Nichol, Prafulla Dhariwal, Aditya Ramesh, Pranav Shyam, Pamela Mishkin, Bob Mcgrew, Ilya Sutskever, and Mark Chen. GLIDE: Towards photorealistic image generation and editing with text-guided diffusion models. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 16784–16804. PMLR, 17–23 Jul 2022b.

Yong-Hyun Park, Chieh-Hsin Lai, Satoshi Hayakawa, Yuhta Takida, and Yuki Mitsufuji. Jump your steps: Optimizing sampling schedule of discrete diffusion models. In *The Thirteenth International Conference on Learning Representations*, 2025.

Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. SDXL: Improving latent diffusion models for high-resolution image synthesis. In *The Twelfth International Conference on Learning Representations*, 2024a.

Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. SDXL: Improving latent diffusion models for high-resolution image synthesis. In *The Twelfth International Conference on Learning Representations*, 2024b. URL `https://openreview.net/forum?id=di52zR8xgf`.

Vadim Popov, Ivan Vovk, Vladimir Gogoryan, Tasnima Sadekova, and Mikhail Kudinov. Grad-tts: A diffusion probabilistic model for text-to-speech. *arXiv preprint arXiv:2105.06337*, 2021.

Jérémie Roland and Nicolas J. Cerf. Quantum search by local adiabatic evolution. *Phys. Rev. A*, 65:042308, Mar 2002. doi: 10.1103/PhysRevA.65.042308. URL `https://link.aps.org/doi/10.1103/PhysRevA.65.042308`.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10684–10695, June 2022.

Amirmojtaba Sabour, Sanja Fidler, and Karsten Kreis. Align your steps: Optimizing sampling schedules in diffusion models. In *Forty-first International Conference on Machine Learning*, 2024.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Raphael Gontijo-Lopes, Burcu Karagol Ayan, Tim Salimans, Jonathan Ho, David J. Fleet, and Mohammad Norouzi. Photorealistic text-to-image diffusion models with deep language understanding. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022a.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, Jonathan Ho, David J Fleet, and Mohammad Norouzi. Photorealistic text-to-image diffusion models with deep language understanding. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 36479–36494. Curran Associates, Inc., 2022b.

Chitwan Saharia, Jonathan Ho, William Chan, Tim Salimans, David J. Fleet, and Mohammad Norouzi. Image super-resolution via iterative refinement. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(4):4713–4726, 2023. doi: 10.1109/TPAMI.2022.3204461.

Mehdi S. M. Sajjadi, Olivier Bachem, Mario Lucic, Olivier Bousquet, and Sylvain Gelly. Assessing generative models via precision and recall. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Tim Salimans and Jonathan Ho. Progressive distillation for fast sampling of diffusion models. In *International Conference on Learning Representations*, 2022.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 2256–2265, Lille, France, 07–09 Jul 2015. PMLR.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *International Conference on Learning Representations*, 2021a.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Yang Song and Stefano Ermon. Improved techniques for training score-based generative models. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 12438–12448. Curran Associates, Inc., 2020.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2021b.

Yang Song, Prafulla Dhariwal, Mark Chen, and Ilya Sutskever. Consistency models. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 32211–32252. PMLR, 23–29 Jul 2023.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2818–2826, 2016. doi: 10.1109/CVPR.2016.308.

Christopher Williams, Andrew Campbell, Arnaud Doucet, and Saifuddin Syed. Score-optimal diffusion schedules. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Zhisheng Xiao, Karsten Kreis, and Arash Vahdat. Tackling the generative learning trilemma with denoising diffusion GANs. In *International Conference on Learning Representations*, 2022.

Tianwei Yin, Michaël Gharbi, Taesung Park, Richard Zhang, Eli Shechtman, Fredo Durand, and William T. Freeman. Improved distribution matching distillation for fast image synthesis. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024a.

Tianwei Yin, Michaël Gharbi, Richard Zhang, Eli Shechtman, Frédo Durand, William T. Freeman, and Taesung Park. One-step diffusion with distribution matching distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 6613–6623, June 2024b.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2016.

Qinsheng Zhang and Yongxin Chen. Fast sampling of diffusion models with exponential integrator. In *The Eleventh International Conference on Learning Representations*, 2023.

Wenliang Zhao, Lujia Bai, Yongming Rao, Jie Zhou, and Jiwen Lu. UniPC: A unified predictor-corrector framework for fast sampling of diffusion models. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

Kaiwen Zheng, Cheng Lu, Jianfei Chen, and Jun Zhu. DPM-solver-v3: Improved diffusion ODE solver with empirical model statistics. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023a.

Kaiwen Zheng, Cheng Lu, Jianfei Chen, and Jun Zhu. DPM-solver-v3: Improved diffusion ODE solver with empirical model statistics. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023b.

Zhenyu Zhou, Defang Chen, Can Wang, and Chun Chen. Fast ode-based sampling for diffusion models in around 5 steps. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7777–7786, June 2024.

A   Probability Distribution of Diffused Data

We derive the probability distribution of the diffused data used in the toy example (Fig. 1).

The distribution of the diffused data is given by:

$$q(\boldsymbol{x}_\alpha) = \int q(\boldsymbol{x}_\alpha|\boldsymbol{x}_0)q(\boldsymbol{x}_0)d\boldsymbol{x}_0, \tag{18}$$

$$q(\boldsymbol{x}_\alpha|\boldsymbol{x}_0) = \mathcal{N}(\boldsymbol{x}_\alpha; \alpha\boldsymbol{x}_0, \sigma^2\boldsymbol{I}), \tag{19}$$

where $q(\boldsymbol{x}_0)$ is the probability distribution of the target dataset.

We approximate $q(\boldsymbol{x}_0)$ by the empirical distribution:

$$q(\boldsymbol{x}_0) = \frac{1}{N} \sum_{n=1}^{N} \delta(\boldsymbol{x}_0 - \boldsymbol{x}_0^n), \tag{20}$$

where N is the number of data samples, $\boldsymbol{x}_0^n$ is the n-th sample, and δ denotes the Dirac delta function. Substituting Eq. (20) into Eq. (18) yields:

$$q(\boldsymbol{x}_\alpha) = \frac{1}{N} \sum_{n=1}^{N} \mathcal{N}(\boldsymbol{x}_\alpha; \alpha\boldsymbol{x}_0^n, \sigma^2\boldsymbol{I}). \tag{21}$$

This derivation uses the following formula of Dirac's delta function:

$$\int f(\boldsymbol{x})\delta(\boldsymbol{x} - \boldsymbol{y})d\boldsymbol{x} = f(\boldsymbol{y}). \tag{22}$$

The resulting probability distribution is a Gaussian mixture distribution. We used Eq. (21) in the toy example.

B   Derivation of Discrepancy Measure Based on Data Prediction from KLUB

We show that $v_x(\alpha)$ can be derived as a simplified variant of the KLUB introduced in AYS.

B.1   KLUB in Variance-Preserving Process

The forward SDE in continuous-time diffusion models (Song et al., 2021b) is defined as:

$$d\boldsymbol{x} = f(t)\boldsymbol{x}dt + g(t)d\boldsymbol{\omega}, \tag{23}$$

where $f(t)\boldsymbol{x}$ is the drift coefficient, $g(t)$ is the diffusion coefficient, and $\boldsymbol{\omega}$ is the standard Wiener process. The corresponding reverse SDE is given by:

$$d\boldsymbol{x} = \left[f(t)\boldsymbol{x} - g(t)^2 \nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x}) \right] dt + g(t)d\boldsymbol{\omega}. \tag{24}$$

To approximate the score $\nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x})$, we train a noise prediction model $\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)$:

$$\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha) \simeq -\sigma \nabla_{\boldsymbol{x}} \log p_t(\boldsymbol{x}). \tag{25}$$

The data prediction $\boldsymbol{x}_\theta(\boldsymbol{x}, \alpha)$ is related to the noise prediction via:

$$\boldsymbol{x} = \alpha \boldsymbol{x}_\theta(\boldsymbol{x}, \alpha) + \sigma \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha). \tag{26}$$

By substituting Eq. (25) into Eq. (24) and using Eq. (26), the reverse SDE can be rewritten as

$$d\boldsymbol{x} = \boldsymbol{f}(\boldsymbol{x}, t)dt + g(t)d\boldsymbol{\omega}, \tag{27}$$

$$\boldsymbol{f}(\boldsymbol{x}, t) = \left(f(t) + \frac{1}{\sigma(t)^2} g(t)^2 \right) \boldsymbol{x} - \frac{\alpha(t)}{\sigma(t)^2} g(t)^2 \boldsymbol{x}_\theta(\boldsymbol{x}, \alpha(t)). \tag{28}$$

Stochastic DDIM numerically solves this reverse SDE. It exactly integrates the linear term and approximates the remaining term, introducing discretization error (Lu et al., 2022a;b). According to Sabour et al. (2024), in the interval $[t_{i-1}, t_i]$, Stochastic DDIM solves the discretized SDE:

$$d\boldsymbol{x} = \boldsymbol{f}'(\boldsymbol{x}, t)dt + g(t)d\boldsymbol{\omega}, \tag{29}$$

$$\boldsymbol{f}'(\boldsymbol{x}, t) = \left(f(t) + \frac{1}{\sigma(t)^2} g(t)^2 \right) \boldsymbol{x} - \frac{\alpha(t)}{\sigma(t)^2} g(t)^2 \boldsymbol{x}_\theta(\boldsymbol{x}_{t_i}, \alpha(t_i)). \tag{30}$$

Furthermore, the KLUB between probability distributions of $\boldsymbol{x}_{t_{i-1}}$ obtained by solving the true reverse SDE and the descretized one is introduced as

$$\text{KLUB}(t_{i-1}, t_t) = \frac{1}{2} \int_{t_{i-1}}^{t_i} \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0) \\ \boldsymbol{x}_t \sim q(\boldsymbol{x}_t | \boldsymbol{x}_0) \\ \boldsymbol{x}_{t_i} \sim q(\boldsymbol{x}_{t_i} | \boldsymbol{x}_t)}} \left[\frac{\|\boldsymbol{f}(\boldsymbol{x}_t, t) - \boldsymbol{f}'(\boldsymbol{x}_t, t)\|_2^2}{g(t)^2} \right] dt, \tag{31}$$

$$= \frac{1}{2} \int_{t_{i-1}}^{t_i} \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0) \\ \boldsymbol{x}_t \sim q(\boldsymbol{x}_t | \boldsymbol{x}_0) \\ \boldsymbol{x}_{t_i} \sim q(\boldsymbol{x}_{t_i} | \boldsymbol{x}_t)}} \left[\frac{\alpha(t)^2}{\sigma(t)^4} g(t)^2 \|\boldsymbol{x}_\theta(\boldsymbol{x}_t, \alpha(t)) - \boldsymbol{x}_\theta(\boldsymbol{x}_{t_i}, \alpha(t_i))\|_2^2 \right] dt. \tag{32}$$

In the variance-preserving setting, the diffusion coefficient satisfies:

$$\frac{1}{2} g(t)^2 = -\frac{\dot{\alpha}}{\alpha}. \tag{33}$$

Substituting Eq. (33) into Eq. (32) gives:

$$\text{KLUB}(t_{i-1}, t_i) = -\int_{t_{i-1}}^{t_i} dt \dot{\alpha}(t) \frac{\alpha(t)}{\sigma(t)^4} \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0) \\ \boldsymbol{x}_t \sim q(\boldsymbol{x}_t | \boldsymbol{x}_0) \\ \boldsymbol{x}_{t_i} \sim q(\boldsymbol{x}_{t_i} | \boldsymbol{x}_t)}} \left[\|\boldsymbol{x}_\theta(\boldsymbol{x}_t, \alpha(t)) - \boldsymbol{x}_\theta(\boldsymbol{x}_{t_i}, \alpha(t_i))\|_2^2 \right]. \tag{34}$$

B.2   KLUB as Discrepancy Measure of CRS

To apply KLUB within the CRS framework, we reinterpret it as a discrepancy measure over adjacent steps in the diffusion process. Because the KLUB is introduced to evaluate the discretization error when solving the reverse SDE, it is reasonable to regard the KLUB as the traceability measure of the diffusion process.

We approximate the integral in the KLUB using Simpson's rule as follows:

$$\text{KLUB}(t, t + \Delta t) = \frac{\dot{\alpha}(t)\alpha(t)}{2\sigma(t)^4} \overline{\mathcal{D}_x^2}(t, t + \Delta t)\Delta t, \tag{35}$$

$$\overline{\mathcal{D}_x^2}(t, t') = \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0) \\ \boldsymbol{x}_t \sim q(\boldsymbol{x}_t | \boldsymbol{x}_0) \\ \boldsymbol{x}_{t'} \sim q(\boldsymbol{x}_{t'} | \boldsymbol{x}_t)}} \left[\|\boldsymbol{x}_\theta(\boldsymbol{x}_t, \alpha(t)) - \boldsymbol{x}(\boldsymbol{x}_{t'}, \alpha(t'))\|_2^2 \right]. \tag{36}$$

Then, to treat $\overline{\mathcal{D}_x^2}(t, t')$ as a function of α rather than t, we introduce $\overline{D_x^2}(\alpha(t), \alpha(t')) = \overline{\mathcal{D}_x^2}(t, t')$:

$$\overline{D_x^2}(\alpha, \alpha') = \mathbb{E}_{\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'} \sim q(\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'})} \left[\|\boldsymbol{x}_\theta(\boldsymbol{x}_\alpha, \alpha) - \boldsymbol{x}_\theta(\boldsymbol{x}_{\alpha'}, \alpha')\|_2^2 \right], \tag{37}$$

Here, $q(\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'})$ is given by

$$q(\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'}) = \int q(\boldsymbol{x}_{\alpha'}|\boldsymbol{x}_\alpha)q(\boldsymbol{x}_\alpha|\boldsymbol{x}_0)q(\boldsymbol{x}_0)d\boldsymbol{x}_0, \tag{38}$$

$$q(\boldsymbol{x}_\alpha|\boldsymbol{x}_0) = \mathcal{N}(\boldsymbol{x}_\alpha; \alpha\boldsymbol{x}_0, \sigma^2\boldsymbol{I}), \tag{39}$$

$$q(\boldsymbol{x}_{\alpha'}|\boldsymbol{x}_\alpha) = \mathcal{N}(\boldsymbol{x}_{\alpha'}; \beta\boldsymbol{x}_\alpha, \delta^2\boldsymbol{I}), \tag{40}$$

where $\beta = \frac{\alpha'}{\alpha}$, $\sigma = \sqrt{1 - \alpha^2}$, and $\delta = \sqrt{1 - \beta^2}$. Using $\overline{D_x^2}(\alpha, \alpha')$, we can rewrite $\mathrm{KLUB}(t, t + \Delta t)$ as

$$\mathrm{KLUB}(t, t + \Delta t) = \frac{\dot{\alpha}\alpha}{2\sigma^4}\overline{D_x^2}(\alpha, \alpha + \Delta\alpha)\Delta t, \tag{41}$$

$$= \frac{\dot{\alpha}\alpha}{2\sigma^4}\frac{\overline{D_x^2}(\alpha, \alpha + \Delta\alpha) - \overline{D_x^2}(\alpha, \alpha)}{\Delta\alpha}\frac{\Delta\alpha}{\Delta t}(\Delta t)^2, \tag{42}$$

$$\simeq \left\{\frac{d\alpha}{dt}\cdot\frac{\sqrt{\alpha}}{\sqrt{2\sigma^2}}\sqrt{\left.\frac{\partial\overline{D_x^2}(\alpha, \alpha')}{\partial\alpha'}\right|_{\alpha'=\alpha}}\Delta t\right\}^2. \tag{43}$$

We use $\overline{D_x^2}(\alpha, \alpha) = 0$ in the second equality. Finally, by adopting $\sqrt{\mathrm{KLUB}(t, t')}$ as the discrepancy measure $D(t, t')$ in CRS, we obtain the following equation:

$$D(t, t + \Delta t) = \sqrt{\mathrm{KLUB}(t, t + \Delta t)} = -\frac{d\alpha}{dt}\cdot\underbrace{\frac{\sqrt{\alpha}}{\sqrt{2\sigma^2}}\sqrt{\left.\frac{\partial\overline{D_x^2}(\alpha, \alpha')}{\partial\alpha'}\right|_{\alpha'=\alpha}}}_{v_{\mathrm{KLUB}}(\alpha)}\Delta t. \tag{44}$$

which corresponds to the general form of CRS in Eq. (8). We can interpret $v_x(\alpha)$ as a simplified variant of $v_{\mathrm{KLUB}}(\alpha)$, in which the multiplicative weighting term $\frac{\sqrt{\alpha}}{\sqrt{2\sigma^2}}$ is omitted.

Although it is possible to optimize the noise schedule using $v_{\mathrm{KLUB}}(\alpha)$ directly, this can lead to undesirable behavior, as the weighting term $\frac{\sqrt{\alpha}}{\sqrt{2\sigma^2}}$ grows very large when $\alpha \simeq 1$ (i.e., $\sigma \simeq 0$), which can overwhelm the influence of $\overline{D_x^2}(\alpha, \alpha')$. Since $\overline{D_x^2}(\alpha, \alpha')$ can be interpreted as capturing the distributional change between diffused data distributions (as discussed in Section 4.3), the simplified variant $v_x(\alpha)$ is more aligned with the objective of CRS.

C   Implementation of CRS

We describe how to compute $v(\alpha)$ using each discrepancy measure.

C.1   Discrepancy Measure Based on FID

Algorithm 1 presents the pseudocode for computing $v_{\mathrm{FID}}(\alpha)$. Once the forward process is defined, $v(\alpha)$ can be computed by simulating the forward diffusion using the training dataset. Since this procedure is independent of model parameters, it only needs to be executed once prior to training the diffusion model.

It is important to note that, in latent-space diffusion models, the probability-distributional change must be measured in the latent space embedded by the autoencoder, as the Gaussian approximation in Eq. (4) applies to the diffusion process defined in the latent space. Therefore, for latent-space models, we trained a ResNet-50 (He et al., 2016) classifier on ImageNet in the autoencoder's latent space and use it as the feature extractor ϕ.

To compute $v(\alpha)$, we discretize the range of α using a one-dimensional grid $\{\alpha_t\}_{t=0,\ldots,T}$ and approximate the continuous function via linear interpolation. In our experiments, we define the discretized grid of α values as:

$$\alpha_t = 1 - \left(\frac{t}{T}\right)^p, \tag{45}$$

Algorithm 1 $v(\alpha)$ on basis of FID

Require: training dataset $\{\boldsymbol{x}^{(n)}\}_{n=0,\ldots,N-1}$, timesteps T, noise levels $\{\alpha_t\}_{t=0,\ldots,T}$, feature model $\boldsymbol{\phi}$
Ensure: LinearInterp1d($\{\alpha_t\}_{t=0,\ldots,T}, \{v_t\}_{t=0,\ldots,T}$)
 1: # Compute feature vectors of diffused data
 2: **for** $n = 0$ to $N - 1$ **do**
 3:     $\boldsymbol{x}_0^{(n)} \leftarrow \boldsymbol{x}^{(n)}$
 4:     **if** is_latent_space **then**
 5:         $\boldsymbol{x}_0^{(n)} \leftarrow$ autoencoder($\boldsymbol{x}_0^{(n)}$)
 6:     **end if**
 7:
 8:     # Simulate the forward process
 9:     **for** $t = 1$ to T **do**
10:         $\beta_t \leftarrow \frac{\alpha_t}{\alpha_{t-1}}$
11:         $\delta_t \leftarrow \sqrt{1 - \beta_t^2}$
12:         $\boldsymbol{x}_t^{(n)} \leftarrow \beta_t \boldsymbol{x}_{t-1}^{(n)} + \delta_t \mathcal{N}(\boldsymbol{0}, \boldsymbol{I})$
13:     **end for**
14: **end for**
15:
16: # Compute statistics of feature vectors
17: $\boldsymbol{\mu}_t \leftarrow \text{mean}(\{\boldsymbol{x}_t^{(n)}\}_{n=0,\ldots,N-1}), \ \forall t \in \{0,\ldots,T\}$
18: $\boldsymbol{\Sigma}_t \leftarrow \text{cov}(\{\boldsymbol{x}_t^{(n)}\}_{n=0,\ldots,N-1}), \ \forall t \in \{0,\ldots,T\}$
19:
20: # Compute $v(\alpha)$ based on FID
21: **for** $t = 0$ to $T - 1$ **do**
22:     $v_t \leftarrow \dfrac{\text{FID}(\boldsymbol{\mu}_t, \boldsymbol{\Sigma}_t, \boldsymbol{\mu}_{t+1}, \boldsymbol{\Sigma}_{t+1})}{\alpha_t - \alpha_{t+1}}$
23: **end for**
24: $v_T \leftarrow v_{T-1}$

---

where $T = 1000$. For pixel-space diffusion models, where $v(\alpha)$ exhibits sharp variation near $\alpha \simeq 1$, we set $p = 2$ to allocate more evaluation points in that region. For latent-space models, where $v(\alpha)$ is more uniformly distributed, we use $p = 1$.

The computational cost of $v(\alpha)$ is proportional to the number of training images. For the pixel-space diffusion process on LSUN Horse 256×256 with 2M images, the computation takes approximately 35 hours using eight A100 GPUs. For the latent-space process on ImageNet 256×256 with 1.28M images, it takes about 12 hours using eight A100 GPUs. To address the scalability issue for large-scale datasets, we introduce a practical alternative in Sec. 5.6.

C.2 Discrepancy Measure Based on Data Prediction

Algorithm 2 presents the pseudocode for computing $v_x(\alpha)$ using a trained diffusion model. As in the case of $v_{\text{FID}}(\alpha)$, this involves simulating the forward process on the training data and measuring changes in the predicted data across adjacent timesteps. A common configuration of hyperparameters ($T = 10^3, S = 10^4, \alpha_s = 1, \alpha_e = 10^{-4}$) was used in our experiments.

The computation time for obtaining $v_x(\alpha)$ is negligible compared with the training time of the diffusion model. It takes approximately 5.5 hours using eight H100 GPUs in pixel-space diffusion models. In latent-space diffusion models, it takes approximately 1.5 hours using eight A100 GPUs.

Algorithm 3 shows how $v_x(\alpha)$ can be used to adaptively optimize the training schedule. Since the data prediction is expressed as $\boldsymbol{x}_\theta(\boldsymbol{x}, \alpha) = \frac{\boldsymbol{x} - \sigma \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)}{\alpha}$, $v_x(\alpha)$ can become numerically unstable as $\alpha \to 0$. To prevent this, we restrict evaluation to the range $\alpha_{\text{th}} \le \alpha \le \alpha_{\text{max}}$ and fix $v_x(\alpha) = v_x(\alpha_{\text{th}})$ for $\alpha < \alpha_{\text{th}}$.

Algorithm 2 $v_x(\alpha)$ for optimizing sampling schedule.

Require: training dataset $\{\boldsymbol{x}^{(n)}\}_{n=0,\ldots,N-1}$, trained diffusion model $\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)$, number of timesteps T, number of samples for mean S, range of α (α_s, α_e)
Ensure: $\mathrm{LinearInterp1d}\big(\{\alpha_t\}_{t=0,\ldots,T}, \{v_t\}_{t=0,\ldots,T}\big)$

1:   # Evaluate $\mathbb{E}_{\boldsymbol{x}_\alpha, \boldsymbol{x}_{\alpha'}}\left[\|\boldsymbol{x}_\theta(\boldsymbol{x}_\alpha, \alpha) - \boldsymbol{x}_\theta(\boldsymbol{x}_{\alpha'}, \alpha')\|_2^2\right]$

2:   $\overline{D_t^2} \leftarrow 0, \;\; \forall t \in \{0, 1, \ldots, T\}$

3:   $\Delta\alpha \leftarrow \dfrac{1}{T}\left(\alpha_s - \alpha_e\right)$

4:   **for** n **in** $\mathrm{randperm}(N)[:S]$ **do**

5:      $\boldsymbol{x}_0 \leftarrow \boldsymbol{x}^{(n)}$

6:      **if** model operates in latent space **then**

7:          $\boldsymbol{x}_0 \leftarrow \mathrm{autoencoder}(\boldsymbol{x}_0)$

8:      **end if**

9:      $\boldsymbol{y}_0 \leftarrow \boldsymbol{x}_0$

10:

11:      # Simulate the forward process

12:      **for** $t = 1$ to T **do**

13:          $\alpha_t \leftarrow \alpha_s - \Delta\alpha\, t, \quad \sigma_t \leftarrow \sqrt{1 - \alpha_t^2}$

14:          $\beta_t \leftarrow \dfrac{\alpha_t}{\alpha_{t-1}}, \quad \delta_t \leftarrow \sqrt{1 - \beta_t^2}$

15:          $\boldsymbol{x}_t \leftarrow \beta_t \boldsymbol{x}_{t-1} + \delta_t\, \mathcal{N}(\boldsymbol{0}, \boldsymbol{I})$

16:          $\boldsymbol{y}_t \leftarrow \dfrac{1}{\alpha_t}(\boldsymbol{x}_t - \sigma_t\, \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}_t, \alpha_t))$

17:          $\overline{D_t^2} \leftarrow \overline{D_t^2} + \dfrac{1}{S}\|\boldsymbol{y}_t - \boldsymbol{y}_{t-1}\|_2^2$

18:      **end for**

19: **end for**

20:

21: # Compute $v(\alpha)$ using $\overline{D_t^2}$

22: **for** $t = 1$ to T **do**

23:      $v_t \leftarrow \sqrt{\dfrac{1}{\Delta\alpha}\overline{D_t^2}}$

24: **end for**

25: $v_0 \leftarrow v_1$

Similar to VDM++ (Kingma & Gao, 2023), we divide the range of α into B uniform bins and estimate $\overline{D_x^2}$ for each bin using an exponential moving average (EMA). We use a shared configuration across experiments: $B = 100$, $e = 0.995$, $\alpha_{\max} = 1$, $\alpha_{\min} = 0$, $\alpha_{\mathrm{th}} = 0.01$, $\Delta\alpha = 10^{-3}$, and $\xi = 1.0$. The initial schedule is set to linear: $\alpha(t) = \alpha_{\max} - (\alpha_{\max} - \alpha_{\min}) \cdot \frac{t}{T}$. Although not explicitly included in the pseudocode, the update of $\overline{D_b^2}$ starts after 1000 iterations, and the noise schedule $\alpha(t)$ is updated every 100 iterations.

While this adaptive scheme slightly increases training time (by 20–30% compared to fixed schedules; see Table 10 in Appendix E), we find that the schedule stabilizes early: for example, on LSUN Horse 256×256, $v_x(\alpha)$ changes very little after 10 epochs. Thus, fixing the schedule after a few epochs or reducing the frequency of $\overline{D_x^2}$ updates may mitigate the cost without degrading performance. Developing a more efficient implementation remains an important direction for future work.

D   Hyperparameter Tuning for Combining Multiple Discrepancy Measures

CRS-$v_x + v_{\mathrm{FID}}$ achieves the best performance for sampling in pixel-space diffusion models. CRS-$v_x + v_{\mathrm{FID}}$ involves four hyperparameters: w_x, w_{FID}, ξ_x, and ξ_{FID}. The effects of these hyperparameters on the resulting noise schedules are illustrated in Figs. 4, 5, and 6. Increasing either w_{FID} or ξ_{FID} amplifies the influence of $v_{\mathrm{FID}}(\alpha)$, resulting in more timesteps being allocated to the region where $\alpha \simeq 1$ (see Figs. 4 and 5).

Algorithm 3 Adaptive optimization of training schedule using $v_x(\alpha)$.

Require: training dataset $\{\boldsymbol{x}^{(n)}\}_{n=0,\ldots,N}$, initial noise schedule $\alpha(t)$, number of bins B, decay rate of EMA e, range of α ($\alpha_{\max}, \alpha_{\min}$), derivative step $\Delta\alpha$, minimum value for evaluating $v(\alpha)$ α_{th}, hyperparameter of CRS ξ

Ensure: noise prediction model $\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \alpha)$

1: $\alpha_b \leftarrow \alpha_{\text{th}} + (\alpha_{\max} - \alpha_{\text{th}}) \dfrac{b}{B}, \quad \forall b \in \{0, \ldots, B\}$

2: $\overline{D_b^2} \leftarrow 10^{-6}, \quad \forall b \in \{0, \ldots, B-1\}$

3: **for** n **in** randperm(N) **do**

4:      # Compute loss for training diffusion models

5:      $\boldsymbol{x}_0 \leftarrow \boldsymbol{x}^{(n)}, \quad t \sim \mathcal{U}(0,1), \quad \boldsymbol{\varepsilon} \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{I})$

6:      $\alpha \leftarrow \alpha(t), \quad \sigma \leftarrow \sqrt{1 - \alpha^2}$

7:      $\boldsymbol{\varepsilon}_\alpha \leftarrow \boldsymbol{\varepsilon}_\theta(\alpha\boldsymbol{x}_0 + \sigma\boldsymbol{\varepsilon}, \alpha)$

8:      $loss \leftarrow \dfrac{1}{2} \|\boldsymbol{\varepsilon}_\alpha - \boldsymbol{\varepsilon}\|_2^2$

9:

10:      # Evaluate $\overline{D_b^2}$ using EMA (without gradient)

11:      **if** $\alpha \geq \alpha_{\text{th}}$ **then**

12:          $\alpha' \leftarrow \alpha - \Delta\alpha, \quad \sigma' \leftarrow \sqrt{1 - \alpha'^2}, \quad \beta' \leftarrow \dfrac{\alpha'}{\alpha}, \quad \delta' \leftarrow \sqrt{1 - \beta'^2}$

13:          $\boldsymbol{x}_{\alpha'} \leftarrow \beta'\boldsymbol{x}_\alpha + \delta'\mathcal{N}(\boldsymbol{0}, \boldsymbol{I})$

14:          $\boldsymbol{\varepsilon}_{\alpha'} \leftarrow \boldsymbol{\varepsilon}_\theta(\boldsymbol{x}_{\alpha'}, \alpha')$

15:          $\boldsymbol{y}_\alpha \leftarrow \dfrac{1}{\alpha}(\boldsymbol{x}_\alpha - \sigma\boldsymbol{\varepsilon}_\alpha), \quad \boldsymbol{y}_{\alpha'} \leftarrow \dfrac{1}{\alpha'}(\boldsymbol{x}_{\alpha'} - \sigma'\boldsymbol{\varepsilon}_{\alpha'})$

16:          $b \leftarrow \min\left(\left\lfloor \dfrac{\alpha - \alpha_{\text{th}}}{\alpha_{\max} - \alpha_{\text{th}}} B \right\rfloor, B - 1\right)$

17:          $\overline{D_b^2} \leftarrow e\overline{D_b^2} + (1 - e)\|\boldsymbol{y}_\alpha - \boldsymbol{y}_{\alpha'}\|_2^2$

18:          $v_b \leftarrow \sqrt{\dfrac{1}{\Delta\alpha} \overline{D_b^2}}$

19:      **end if**

20:

21:      # Update training schedule $\alpha(t)$

22:      $\mathcal{X} \leftarrow \{\alpha_{\min}, \alpha_0, \alpha_1, \ldots, \alpha_B\}$

23:      $\mathcal{Y} \leftarrow \{v_0, v_0, v_1, \ldots, v_{B-1}, v_{B-1}\}$

24:      $v(\alpha) \leftarrow$ LinearInterp1d($\mathcal{X}, \mathcal{Y}$)

25:      **Update noise schedule $\alpha(t)$ by solving Eq. (9)**

26:

27:      # Update model parameters θ

28:      **loss.backward()**

29:      **optimizer.step()**

30: **end for**

Conversely, increasing either w_x or ξ_x strengthens the contribution of $v_x(\alpha)$, leading to more timesteps being assigned to the region where $\alpha \simeq 0$ (see Figs. 4 and 6).

We tuned these hyperparameters in two steps. First, we fixed $\xi_x = \xi_{\text{FID}} = 1$ and searched for appropriate values of w_x and w_{FID} under the constraint $w_x + w_{\text{FID}} = 1$. Then, we fixed the weights and adjusted ξ_x and ξ_{FID}. Although further iterations between tuning weights and exponents are possible, we found that just one iteration per step was typically sufficient to outperform conventional noise schedules.

The detailed tuning results on LSUN Horse 256×256 are presented in Table 6. In the first step, adjusting w_x and w_{FID} led to substantial changes in FID at both NFE = 250 and NFE = 50. In the second step, tuning ξ_x and ξ_{FID} had little impact at NFE = 250, but resulted in a significant FID improvement at NFE = 50. This suggests that hyperparameter sensitivity increases as the NFEs decrease.

Table 6: Detailed results of hyperparameter tuning for CRS-$v_x + v_{\text{FID}}$ on LSUN Horse 256×256 in pixel-space diffusion model. DPM-Solver++(2M) was used as sampler. To reduce computational cost, FID scores were calculated using 10K samples.

NFE	Tuning step	w_{FID}	x_x	ξ_{FID}	ξ_x	FID (10K)
250	1st	0.9	0.1	1.0	1.0	3.78
		0.7	0.3			**3.70**
		0.5	0.5			**3.70**
		0.3	0.7			3.73
		0.1	0.9			3.76
	2nd	0.7	0.3	0.5	0.5	3.77
					1.0	4.30
					1.2	3.75
					1.4	3.94
				1.0	0.5	3.76
					1.0	3.70
					1.2	**3.69**
					1.4	3.78
				1.2	0.5	3.82
					1.0	**3.69**
					1.2	3.78
					1.4	3.77
				1.4	0.5	3.83
					1.0	3.78
					1.2	3.77
					1.4	3.77
50	1st	0.9	0.1	1.0	1.0	6.13
		0.7	0.3			4.42
		0.5	0.5			**4.38**
		0.3	0.7			4.78
		0.1	0.9			7.03
	2nd	0.5	0.5	0.5	0.5	7.42
					1.0	7.44
					1.2	7.48
					1.4	7.79
				1.0	0.5	4.85
					1.0	4.38
					1.2	4.32
					1.4	4.27
				1.2	0.5	4.57
					1.0	4.09
					1.2	3.96
					1.4	3.93
				1.4	0.5	4.51
					1.0	3.95
					1.2	3.85
					1.4	**3.82**

Figure 4: Effect of the weights w_x and w_{FID} on the noise schedule generated by CRS-$v_x + v_{\text{FID}}$, with fixed exponents $\xi_x = \xi_{\text{FID}} = 1$.

Figure 5: Effect of the exponent ξ_{FID} on the noise schedule generated by CRS-$v_x + v_{\text{FID}}$, with fixed weights $w_x = w_{\text{FID}} = 0.5$.

Figure 6: Effect of the exponent ξ_x on the noise schedule generated by CRS-$v_x + v_{\text{FID}}$, with fixed weights $w_x = w_{\text{FID}} = 0.5$.

The final hyperparameter settings used in our experiments are summarized in Table 7. The resulting noise schedules $\alpha(t)$ for CRS-$v_x + v_{\text{FID}}$ are visualized in Figs. 7, 8, 9, 10, 11, and 12.

E   Implementation Details

E.1   U-Net Architecture

The hyperparameters of the U-Net model are listed in Table 8. For latent-space diffusion models, we use the same settings as those for ImageNet 64×64 in ADM (Dhariwal & Nichol, 2021). For pixel-space diffusion models, we adopt the same settings as those for LSUN 256×256 in ADM.

E.2   Training Hyperparameters

The training hyperparameters are summarized in Table 9. We save ten checkpoints for each model. FID scores are computed using 10K samples for all checkpoints, and we report the results from the checkpoint with the best FID.

The training times for each model configuration are provided in Table 10. When using CRS to optimize the training schedule, training time increases by 20–30% compared to conventional noise schedules, due to the overhead of computing $v_x(\alpha)$ during training. In practice, however, we observe that the noise schedule stabilizes early; for example, on LSUN Horse 256×256, $v_x(\alpha)$ shows minimal change beyond 10 epochs. This suggests that freezing the schedule after a small number of epochs or reducing the frequency of $\overline{D_x^2}$ updates

Table 7: Hyperparameter settings used for CRS-$v_x + v_{\text{FID}}$ in our experiments on LSUN Horse 256×256, LSUN Bedroom 256×256, FFHQ 64×64, and CIFAR10 32×32.

Dataset	Sampler	NFE	w_{FID}	w_x	ξ_{FID}	ξ_x
LSUN Horse 256×256	SDE-DPM-Solver++(2M)	250	0.9	0.1	1.4	1.0
		50	0.7	0.3	1.4	1.2
	PNDM	250	0.9	0.1	1.0	0.5
		50	0.5	0.5	1.2	0.5
	DPM-Solver++(2M)	250	0.7	0.3	1.0	1.2
		50	0.5	0.5	1.4	1.4
LSUN Bedroom 256×256	DPM-Solver++(2M)	10	0.5	0.5	1.0	1.0
		5	0.5	0.5	1.0	1.2
	UniPC	10	0.5	0.5	1.0	1.5
		5	0.3	0.7	1.0	1.0
FFHQ 64×64	DPM-Solver++(2M)	50	0.5	0.5	1.6	1.4
		20	0.5	0.5	1.6	1.4
		10	0.5	0.5	1.6	1.5
	iPNDM	50	0.5	0.5	1.2	1.5
		20	0.5	0.5	1.4	1.4
		10	0.5	0.5	1.5	1.4
CIFAR10 32×32	DPM-Solver++(2M)	50	0.5	0.5	1.6	1.0
		20	0.5	0.5	1.8	2.4
		10	0.5	0.5	1.6	3.0
	iPNDM	50	0.7	0.3	1.6	1.2
		20	0.5	0.5	1.6	1.6
		10	0.5	0.5	1.6	3.2

Table 8: Hyperparameters of UNet model.

	Latent-space diffusion models	Pixel-space diffusion models
Resolution	64 × 64	256 × 256
Number of parameters	296M	552M
Channels	192	256
Depth	3	2
Channels multiple	1,2,3,4	1,1,2,2,4,4
Heads channels	64	64
Attention resolution	32,16,8	32,16,8
BigGAN up/downsample	True	True
Dropout	0.1	0.1

Table 9: Hyperparameters for training diffusion models. Same configuration was used for training latent-space and pixel-space diffusion models.

Item	Value
EMA decay	0.9999
Optimizer	Adam
β_1	0.9
β_2	0.999
Learning rate	1e-4
Batch size	32 × 8

Figure 7: Noise schedules generated by CRS-$v_x + v_{\mathrm{FID}}$ for LSUN Horse 256×256, used with SDE-DPM-Solver++(2M) during sampling.

Figure 8: Noise schedules generated by CRS-$v_x + v_{\mathrm{FID}}$ for LSUN Horse 256×256, used with PNDM during sampling.

Figure 9: Noise schedules generated by CRS-$v_x + v_{\mathrm{FID}}$ for LSUN Horse 256×256, used with DPM-Solver++(2M) during sampling.

Figure 10: Noise schedules generated by CRS-$v_x + v_{\mathrm{FID}}$ for LSUN Bedroom 256×256, used with DPM-Solver++(2M) during sampling.

Figure 11: Noise schedules generated by CRS-$v_x + v_{\mathrm{FID}}$ for LSUN Bedroom 256×256, used with UniPC during sampling.

Figure 12: Noise schedules generated by CRS-$v_x + v_{\mathrm{FID}}$ for FFHQ 64×64, used with DPM-Solver++(2M) during sampling.

Table 10: Training time of diffusion models.

Diffusion type	Dataset	GPUs	Epochs	Training schedule	Training time
Latent space	LSUN Church	A100 × 8	1000	Linear
VDM++
CRS-v_{FID}	85 hours
				CRS-v_ε
CRS-v_x	105 hours
	LSUN Bedroom	A100 × 8	100	CRS-v_{FID}	190 hours
				CRS-v_ε
CRS-v_x	245 hours
	ImageNet	A100 × 8	500	Linear
VDM++
CRS-v_{FID}	430 hours
				CRS-v_ε
CRS-v_x	525 hours
Pixel space	LSUN Horse	H100 × 8	50	Linear
Shifted cosine
VDM++	170 hours
				CRS-v_ε
CRS-v_x	215 hours
	LSUN Bedroom	H100 × 8	50	CRS-v_x	325 hours

can mitigate training overhead without degrading performance. Developing a more efficient implementation remains an important direction for future work.

E.3 Noise Schedules for Training and Sampling

The conventional noise schedules used in this study are summarized in Table 11.

F Detailed Experimental Results

We provide detailed experimental results to confirm the effectiveness of CRS for optimizing both training and sampling schedules.

F.1 Results on Pixel-Space Diffusion Models

LSUN Horse 256×256: The results showing the dependence on training and sampling schedules at NFE = 250 are presented in Table 12. To assess the generality across samplers, we evaluated three different ones: SDE-DPM-Solver++(2M), PNDM, and DPM-Solver++(2M). As shown in the gray-shaded rows, using CRS-v_x for training consistently improved multiple evaluation metrics, including FID, regardless of the sampler used.

Table 13 presents the effect of different sampling schedules at NFE = 250 and NFE = 50. When using SDE-DPM-Solver++(2M), CRS-$v_x + v_{\mathrm{FID}}$ improved all four metrics at NFE = 250, achieving a new state-of-the-art FID score. With PNDM and DPM-Solver++(2M), differences among sampling schedules were minor at NFE = 250; however, at NFE = 50, performance became more sensitive to the sampling schedule. In this low-NFE regime, CRS-$v_x + v_{\mathrm{FID}}$ achieved the best FID score.

LSUN Bedroom 256×256: Since only FID scores are reported in the main text (Table 2), we include sFID, precision, and recall in Table 14 for reference.

Table 15 compares the FID scores of CRS-$v_x + v_{\mathrm{FID}}$ and EDM sampling under various values of the hyperparameter ρ. While the default setting for EDM uses $\rho = 7$, tuning ρ can further improve its performance. However, even with the optimal ρ, EDM sampling did not outperform CRS-$v_x + v_{\mathrm{FID}}$ in terms of FID.

Table 11: Conventional noise schedules evaluated in this study. T_s denotes number of timesteps for sampling.

Name	Phase	Noise schedule
Linear	Training	$\alpha_{\text{linear}}(t) = \text{LinearInterp1d}\left(\left\{\frac{i}{T}\right\}_{i=0,\dots,T}, \{\alpha_i\}_{i=0,\dots,T}\right),$
$\alpha_0 = 1,$
$\alpha_{1 \leq i \leq T} = \sqrt{1 - \tilde{\beta}_i}\alpha_{i-1},$
$\tilde{\beta}_i = \tilde{\beta}_{\min} + \frac{\tilde{\beta}_{\max} - \tilde{\beta}_{\min}}{T-1}(i-1),$
$T = 1000, \tilde{\beta}_{\min} = 10^{-4}, \tilde{\beta}_{\max} = 0.02.$
	Sampling	$\left\{\alpha_{\text{linear}}\left(\frac{t}{T_s}\right) \middle| t = 0, \dots, T_s\right\}$
Shifted cosine	Training	$\alpha_{\text{shifted}}(t) = \sqrt{\text{sigmoid}(\lambda(t))},$
$\lambda(t) = -2\log\tan\left(\frac{\pi t}{2}\right) + 2\log\left(\frac{64}{d}\right),$
where d is resolution in diffusion process.
	Sampling	$\left\{\tilde{\alpha}_{\text{shifted}}\left(\frac{t}{T_s}\right) \middle| t = 0, \dots, T_s\right\},$
$\tilde{\alpha}_{\text{shifted}}(t) = \alpha_{\min} + (\alpha_{\max} - \alpha_{\min})\alpha_{\text{shifted}}(t),$
$\alpha_{\min} = 0.01, \alpha_{\max} = 1.0.$
VDM++	Training	$p(\lambda) \propto \mathbb{E}_{\boldsymbol{x}_0 \sim \mathcal{D}, \boldsymbol{\varepsilon} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{I})}\left[\omega(\lambda)\left\|\boldsymbol{\varepsilon}_\theta(\boldsymbol{x}, \tilde{\alpha}(\lambda)) - \boldsymbol{\varepsilon}\right\|_2^2\right],$
$\omega(\lambda) = \begin{cases} \max_{\lambda} \tilde{\omega}(\lambda), & \lambda < \operatorname{argmax}_{\lambda} \tilde{\omega}(\lambda) \\ \tilde{\omega}(\lambda), & \lambda \geq \operatorname{argmax}_{\lambda} \tilde{\omega}(\lambda), \end{cases}$
$\tilde{\omega}(\lambda) = \mathcal{N}(\lambda; \lambda_\mu, \lambda_\sigma^2)(e^{-\lambda} + c^2),$
$\mu_\lambda = 2.4, \sigma_\lambda = 2.4, c = 0.5.$
	Sampling	Only for training.
EDM	Training	Not evaluated in this study.
	Sampling	$\alpha_0 = 1, \alpha_{t \geq 1} = \alpha_{\text{EDM}}\left(\frac{t}{T_s}\right),$
$\alpha_{\text{EDM}}(t) = \sqrt{\text{sigmoid}(\lambda(t))},$
$\lambda(t) = -2\log\sigma(t),$
$\sigma(t) = \left\{\sigma_{\max}^{\frac{1}{\rho}} + \left(\sigma_{\min}^{\frac{1}{\rho}} - \sigma_{\max}^{\frac{1}{\rho}}\right)(1-t)\right\}^\rho,$
$\sigma_{\max} = 80, \sigma_{\min} = 0.002, \rho = 7.$

F.2 Results on Latent-Space Diffusion Models

LSUN Church 256×256: The results showing the dependence on training and sampling schedules at NFE = 30, using stochastic and deterministic samplers, are summarized in Tables 16 and 17, respectively. To evaluate generality across samplers, we tested five different ones: Stochastic DDIM, SDE-DPM-Solver++(2M), DDIM, PNDM, and DPM-Solver++(2M). As shown in the gray-shaded rows, CRS-v_x consistently improved FID scores across all samplers except for SDE-DPM-Solver++(2M).

The effects of different sampling schedules are shown separately for stochastic and deterministic samplers in Tables 18 and 19, respectively. CRS-v_x or CRS-v_ε achieved the best FID scores in all cases except when using SDE-DPM-Solver++(2M) at NFE = 20. In most cases, multiple evaluation metrics—including sFID, precision, and recall—were simultaneously improved.

LSUN Bedroom 256×256: The results showing the dependence on sampling schedules using stochastic and deterministic samplers are presented in Tables 20 and 21, respectively. The training schedule was fixed to CRS-v_x. CRS achieved the best FID scores in all cases, except when using SDE-DPM-Solver++(2M) at NFE = 30 and NFE = 20. In most cases, multiple evaluation metrics were simultaneously improved.

FID scores evaluated at small NFE settings are listed in Table 22. Compared to the results reported in DPM-Solver-v3 (Zheng et al., 2023a), better FID scores are consistently achieved by using CRS to optimize both training and sampling schedules across all NFE values. As with other evaluations in this paper, we set $\xi = 1$ by default for CRS-v_x and CRS-v_ε, except at NFE = 5, where ξ was manually tuned to further improve performance. A comprehensive set of evaluation metrics, including FID, sFID, precision, and recall, is reported in Table 23. CRS-based noise schedules consistently outperform the linear schedule across all metrics, except for recall at NFE = 20.

ImageNet 256×256: We demonstrated the effectiveness of CRS in class-conditional image generation on ImageNet. The results showing the dependence on training and sampling schedules at NFE = 30, using both stochastic and deterministic samplers, are summarized in Tables 24 and 25, respectively. As shown in the gray-shaded rows, CRS-v_{FID} achieved the best performance for training schedule optimization, while CRS-v_x, which consistently performed well on other datasets, was the second-best. This result may be attributed to the fact that the feature extractor used in FID computation is pre-trained on ImageNet, which may advantage CRS-v_{FID} in this specific setting.

The impact of different sampling schedules using stochastic and deterministic samplers is shown in Tables 26 and 27, respectively. Here, the training schedule was fixed to CRS-v_x, which outperformed conventional noise schedules by a significant margin on ImageNet and delivered strong results across a wide range of datasets. CRS achieved the best FID scores in all cases, except when using PNDM at NFE = 20 and DPM-Solver++(2M) at NFE = 30. In most settings, CRS-based schedules also led to improvements in other evaluation metrics, including sFID, precision, and recall.

F.3 Results on Pretrained EDM

FFHQ 64×64: Evaluation results are presented in Table 28. When using DPM-Solver++(2M), CRS-$v_x + v_{\mathrm{FID}}$ outperforms both EDM and AYS. Further improvements in FID are observed when using iPNDM, where CRS-$v_x + v_{\mathrm{FID}}$ continues to outperform EDM across all tested NFE settings.

CIFAR10 32×32: Evaluation results for class-conditional image generation are shown in Table 29. CRS-$v_x + v_{\mathrm{FID}}$ consistently outperforms EDM across all NFEs, and significant performance gains are observed at small NFEs.

G Generated Samples

Generated samples are shown in the following figures:

- LSUN Horse 256×256 in the pixel-space diffusion model: Figs. 13 and 14.
- LSUN Bedroom 256×256 in the pixel-space diffusion model: Figs. 15 and 16.

- LSUN Church 256×256 in the latent-space diffusion model: Fig. 17.

- LSUN Bedroom 256×256 in the latent-space diffusion model: Fig. 18.

- ImageNet 256×256 in the latent-space diffusion model: Fig. 19.

All models are trained using CRS-v_x for the training schedule optimization.

Table 12: Performance of pixel-space diffusion models on LSUN Horse 256×256 at NFE = 250, evaluated under various training and sampling schedules. To assess generality across samplers, we used three different samplers: SDE-DPM-Solver++(2M), PNDM, and DPM-Solver++(2M). Gray-shaded rows indicate results for different training schedules (with fixed sampling), while unshaded rows show results for different sampling schedules (with fixed training). Bold values indicate the best performance for each metric. Note that "cosine" refers to the shifted cosine schedule.

Sampler	Training schedule	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
SDE-DPM-Solver++(2M)	Linear	Linear	2.90	6.82	0.66	**0.56**
	Cosine		2.95	6.43	**0.67**	**0.56**
	VDM++		3.82	7.40	0.66	0.54
	CRS-v_ε		2.91	6.56	0.66	**0.56**
	CRS-v_x		**2.73**	**6.40**	**0.67**	**0.56**
	CRS-v_x	Linear	2.73	6.40	0.67	**0.56**
		Cosine	3.13	7.09	0.67	0.54
		EDM	2.09	6.16	**0.69**	**0.56**
		CRS-v_ε	2.87	6.71	0.66	0.56
		CRS-v_x	5.46	8.34	0.62	0.52
		CRS-$v_x + v_{\text{FID}}$	**2.03**	**6.06**	**0.69**	**0.56**
PNDM	Linear	Linear	4.06	6.23	0.57	**0.61**
	Cosine		2.36	5.59	0.63	0.60
	VDM++		70.18	36.78	0.20	0.53
	CRS-v_{FID}		8.20	7.92	0.51	0.60
	CRS-v_x		**2.09**	**5.43**	**0.65**	0.58
	CRS-v_x	Linear	**2.09**	**5.43**	0.65	**0.58**
		Cosine	2.19	5.59	**0.67**	0.57
		EDM	2.35	5.85	**0.67**	0.56
		CRS-v_ε	2.11	5.58	0.66	**0.58**
		CRS-v_x	2.50	5.94	0.64	**0.58**
		CRS-$v_x + v_{\text{FID}}$	2.12	5.50	**0.67**	0.57
DPM-Solver++(2M)	Linear	Linear	3.17	5.98	0.60	**0.61**
	Cosine		2.31	5.63	0.63	0.60
	VDM++		47.63	29.77	0.26	0.56
	CRS-v_ε		7.12	7.45	0.54	0.60
	CRS-v_x		**2.08**	**5.47**	**0.65**	0.59
	CRS-v_x	Linear	**2.08**	**5.47**	0.65	**0.59**
		Cosine	2.18	5.72	0.66	0.58
		EDM	2.35	5.85	**0.67**	0.56
		CRS-v_x	2.12	5.65	0.66	0.58
		CRS-v_ε	2.87	6.15	0.63	0.58
		CRS-$v_x + v_{\text{FID}}$	2.19	5.56	**0.67**	0.57

Table 13: Performance of pixel-space diffusion models on LSUN Horse 256×256 under different sampling schedules. Training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
SDE-DPM-Solver++(2M)	250	Linear	2.73	6.40	0.67	0.56
		Shifted cosine	3.13	7.09	0.67	0.54
		EDM	2.09	6.16	0.69	0.56
		CRS-v_ε	2.87	6.71	0.66	0.56
		CRS-v_x	5.46	8.34	0.62	0.52
		CRS-$v_x + v_{\mathrm{FID}}$	**2.03**	**6.06**	**0.69**	**0.56**
	50	Linear	7.54	9.73	0.59	0.48
		Shifted cosine	11.37	12.46	0.53	0.43
		EDM	**2.75**	**6.91**	**0.68**	**0.55**
		CRS-v_ε	6.08	8.75	0.61	0.50
		CRS-v_x	12.99	12.59	0.50	0.41
		CRS-$v_x + v_{\mathrm{FID}}$	3.84	8.16	0.67	0.52
PNDM	250	Linear	**2.09**	**5.43**	0.65	**0.58**
		Shifted cosine	2.19	5.59	**0.67**	0.57
		EDM	2.35	5.85	**0.67**	0.56
		CRS-v_ε	2.11	5.58	0.66	**0.58**
		CRS-v_x	2.50	5.94	0.64	**0.58**
		CRS-$v_x + v_{\mathrm{FID}}$	2.12	5.50	**0.67**	0.57
	50	Linear	2.50	5.76	0.62	**0.59**
		Shifted cosine	3.92	6.77	0.60	0.57
		EDM	2.36	5.87	**0.67**	0.56
		CRS-v_ε	2.46	5.97	0.64	0.58
		CRS-v_x	6.03	7.32	0.57	0.56
		CRS-$v_x + v_{\mathrm{FID}}$	**2.04**	**5.60**	0.66	0.58
DPM-Solver++(2M)	250	Linear	**2.08**	**5.47**	0.65	**0.59**
		Shifted Cosine	2.18	5.72	0.66	0.58
		EDM	2.35	5.85	**0.67**	0.56
		CRS-v_ε	2.12	5.65	0.66	0.58
		CRS-v_x	2.87	6.15	0.63	0.58
		CRS-$v_x + v_{\mathrm{FID}}$	2.19	5.56	**0.67**	0.57
	50	Linear	3.17	5.98	0.60	**0.59**
		Shifted cosine	5.27	7.12	0.57	0.56
		EDM	2.43	**5.87**	**0.67**	0.56
		CRS-v_ε	3.10	6.18	0.62	0.58
		CRS-v_x	7.44	7.83	0.55	0.55
		CRS-$v_x + v_{\mathrm{FID}}$	**2.26**	5.90	0.66	0.57

Table 14: Evaluation results on LSUN Bedroom 256×256 in pixel-space diffusion model. CRS-v_x was used for optimizing training schedule.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
DPM-Solver++(2M)	10	EDM	**4.73**	**7.75**	**0.53**	0.51
		CRS-$v_x + v_{\text{FID}}$	4.88	8.67	0.49	**0.52**
	5	EDM	23.72	19.24	0.20	0.28
		CRS-$v_x + v_{\text{FID}}$	**14.02**	**17.49**	**0.28**	**0.41**
UniPC	10	EDM	4.94	8.20	0.53	0.40
		CRS-$v_x + v_{\text{FID}}$	**3.30**	**6.60**	**0.55**	**0.53**
	5	EDM	82.52	33.35	0.06	0.08
		CRS-$v_x + v_{\text{FID}}$	**21.42**	**11.26**	**0.21**	**0.44**

Table 15: Comparison of FID scores for CRS-$v_x + v_{\text{FID}}$ and EDM sampling on LSUN Bedroom 256×256 in the pixel-space diffusion model. Performance of EDM is reported under various values of the hyperparameter ρ. Even with the optimal ρ, EDM does not outperform CRS-$v_x + v_{\text{FID}}$.

Sampler	Sampling schedule	NFE = 5	NFE = 10
DPM-Solver++(2M)	EDM: $\rho = 1$	190.32	102.10
	EDM: $\rho = 3$	30.24	13.12
	EDM: $\rho = 5$	22.97	7.92
	EDM: $\rho = 7$	23.72	**4.73**
	CRS-$v_x + v_{\text{FID}}$	**14.02**	4.88
UniPC	EDM: $\rho = 1$	178.24	90.30
	EDM: $\rho = 3$	23.45	4.43
	EDM: $\rho = 5$	55.06	3.96
	EDM: $\rho = 7$	82.52	4.94
	CRS-$v_x + v_{\text{FID}}$	**21.42**	**3.30**

Table 16: Performance of latent-space diffusion models on LSUN Church 256×256 at NFE = 30, evaluated under various training and sampling schedules using stochastic samplers. Two samplers were used: Stochastic DDIM and SDE-DPM-Solver++(2M). Gray-shaded rows indicate variations in training schedules (with fixed sampling), while unshaded rows show variations in sampling schedules (with fixed training). Bold values indicate the best result for each evaluation metric.

Sampler	Training schedule	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
Stochastic DDIM	Linear	Linear	10.73	18.31	0.57	0.33
	VDM++		11.05	17.33	0.56	**0.35**
	CRS-v_{FID}		10.85	18.77	0.57	0.34
	CRS-v_ε		10.43	17.81	0.57	0.34
	CRS-v_x		**9.82**	**16.39**	**0.58**	0.34
	CRS-v_x	Linear	9.82	16.39	0.58	0.34
		EDM	21.73	29.33	0.43	0.22
		CRS-v_{FID}	7.36	13.04	0.60	0.39
		CRS-v_ε	7.53	13.73	0.61	0.38
		CRS-v_x	**6.77**	**12.57**	**0.63**	**0.40**
SDE-DPM-Solver++(2M)	Linear	Linear	3.49	10.19	0.63	**0.57**
	VDM++		**3.33**	**9.79**	0.63	**0.57**
	CRS-v_{FID}		3.50	10.69	0.63	**0.57**
	CRS-v_ε		3.57	10.26	**0.64**	0.56
	CRS-v_x		3.38	10.09	**0.64**	0.55
	CRS-v_x	Linear	3.38	10.09	**0.64**	0.55
		EDM	4.20	11.69	0.63	0.54
		CRS-v_{FID}	3.61	9.51	0.61	0.57
		CRS-v_ε	**3.19**	9.56	0.62	**0.59**
		CRS-v_x	3.20	**9.14**	0.62	0.58

Table 17: Performance of latent-space diffusion models on LSUN Church 256×256 at NFE = 30, evaluated under various training and sampling schedules using deterministic samplers. Three samplers were used: DDIM, PNDM, and DPM-Solver++(2M). Gray-shaded rows indicate variations in training schedules (with fixed sampling), while unshaded rows show variations in sampling schedules (with fixed training). Bold values indicate the best result for each evaluation metric.

Sampler	Training schedule	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
DDIM	Linear	Linear	6.18	13.16	**0.59**	0.51
	VDM++		6.50	12.67	0.56	**0.54**
	CRS-v_{FID}		6.06	13.69	**0.59**	0.51
	CRS-v_ε		6.05	12.49	0.58	0.50
	CRS-v_x		**5.67**	**12.33**	**0.59**	0.51
	CRS-v_x	Linear	5.67	12.33	**0.59**	0.51
		EDM	9.15	16.86	0.56	0.44
		CRS-v_{FID}	5.35	**10.70**	0.57	0.53
		CRS-v_ε	4.95	11.01	**0.59**	0.53
		CRS-v_x	**4.81**	10.79	**0.59**	**0.55**
PNDM	Linear	Linear	3.74	10.48	0.60	0.58
	VDM++		3.88	**10.20**	0.59	**0.59**
	CRS-v_{FID}		3.59	10.61	**0.61**	**0.59**
	CRS-v_ε		3.71	10.36	0.60	**0.59**
	CRS-v_x		**3.56**	10.37	**0.61**	0.58
	CRS-v_x	Linear	3.56	10.37	**0.61**	0.58
		EDM	3.88	10.76	0.60	0.57
		CRS-v_{FID}	3.59	**9.69**	0.59	**0.61**
		CRS-v_ε	**3.48**	9.79	0.59	0.59
		CRS-v_x	3.62	10.15	0.59	**0.61**
DPM-Solver++(2M)	Linear	Linear	3.82	10.28	**0.60**	0.58
	VDM++		4.00	**10.07**	0.58	**0.59**
	CRS-v_{FID}		3.78	10.51	**0.60**	0.58
	CRS-v_ε		3.87	10.30	**0.60**	**0.59**
	CRS-v_x		**3.69**	10.23	**0.60**	**0.59**
	CRS-v_x	Linear	3.69	10.23	**0.60**	0.59
		EDM	4.31	11.31	**0.60**	0.56
		CRS-v_{FID}	3.98	9.61	0.58	**0.60**
		CRS-v_ε	3.63	9.91	0.59	**0.60**
		CRS-v_x	**3.59**	**9.51**	0.59	**0.60**

Table 18: Performance of latent-space diffusion models on LSUN Church 256×256 using stochastic samplers, evaluated under different sampling schedules. The training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
Stochastic DDIM	50	Linear	6.23	11.94	**0.65**	0.43
		EDM	10.05	17.14	0.60	0.34
		CRS-v_{FID}	5.17	**10.49**	**0.65**	0.44
		CRS-v_ε	5.26	10.94	**0.65**	0.44
		CRS-v_x	**4.82**	11.91	0.62	**0.51**
	30	Linear	9.82	16.39	0.58	0.34
		EDM	21.73	29.33	0.43	0.22
		CRS-v_{FID}	7.36	13.04	0.60	0.39
		CRS-v_ε	7.53	13.73	0.61	0.38
		CRS-v_x	**6.77**	**12.57**	**0.63**	**0.40**
	20	Linear	18.24	25.36	0.45	0.24
		EDM	48.46	52.53	0.25	0.11
		CRS-v_{FID}	12.42	18.38	0.51	0.29
		CRS-v_ε	12.53	19.27	0.52	0.29
		CRS-v_x	**10.66**	**16.54**	**0.55**	**0.32**
SDE-DPM-Solver++(2M)	50	Linear	3.42	10.58	0.63	0.57
		EDM	3.57	10.93	**0.64**	0.57
		CRS-v_{FID}	3.32	**9.19**	0.62	0.58
		CRS-v_ε	3.14	9.65	0.63	0.58
		CRS-v_x	**3.09**	9.34	0.63	**0.59**
	30	Linear	3.38	10.09	**0.64**	0.55
		EDM	4.20	11.69	0.63	0.54
		CRS-v_{FID}	3.61	9.51	0.61	0.57
		CRS-v_ε	**3.19**	9.56	0.62	**0.59**
		CRS-v_x	3.20	**9.14**	0.62	0.58
	20	Linear	**3.55**	10.37	**0.63**	0.56
		EDM	5.92	13.79	0.62	0.52
		CRS-v_{FID}	4.39	**9.33**	**0.63**	0.48
		CRS-v_ε	3.58	9.93	0.61	**0.57**
		CRS-v_x	3.57	9.55	0.62	0.56

Table 19: Performance of latent-space diffusion models on LSUN Church 256×256 using deterministic samplers, evaluated under different sampling schedules. The training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics FID ↓	sFID ↓	Precision ↑	Recall ↑
DDIM	50	Linear	4.52	11.03	**0.60**	0.54
		EDM	5.95	13.37	0.59	0.50
		CRS-v_{FID}	4.28	**10.07**	0.59	0.56
		CRS-v_ε	4.17	10.66	**0.60**	0.56
		CRS-v_x	**4.01**	10.10	**0.60**	**0.57**
	30	Linear	5.67	12.33	**0.59**	0.51
		EDM	9.15	16.86	0.56	0.44
		CRS-v_{FID}	5.35	**10.70**	0.57	0.53
		CRS-v_ε	4.95	11.01	**0.59**	0.53
		CRS-v_x	**4.81**	10.79	**0.59**	**0.55**
	20	Linear	7.85	14.66	0.56	0.47
		EDM	15.74	22.86	0.48	0.34
		CRS-v_{FID}	7.47	12.74	0.54	0.48
		CRS-v_ε	6.49	12.55	0.56	0.49
		CRS-v_x	**6.09**	**11.72**	**0.57**	**0.50**
PNDM	50	Linear	3.52	10.42	**0.61**	0.58
		EDM	3.71	10.59	0.60	0.57
		CRS-v_{FID}	3.49	9.95	0.60	**0.61**
		CRS-v_ε	**3.48**	10.18	0.60	0.59
		CRS-v_x	**3.48**	**9.92**	0.60	0.60
	30	Linear	3.56	10.37	**0.61**	0.58
		EDM	3.88	10.76	0.60	0.57
		CRS-v_{FID}	3.59	**9.69**	0.59	**0.61**
		CRS-v_ε	**3.48**	9.79	0.59	0.59
		CRS-v_x	3.62	10.15	0.59	**0.61**
	20	Linear	3.74	10.24	0.60	0.59
		EDM	4.57	11.49	0.59	0.56
		CRS-v_{FID}	4.06	**9.54**	0.57	**0.61**
		CRS-v_ε	**3.64**	9.98	0.59	**0.61**
		CRS-v_x	3.86	**9.54**	**0.62**	0.52
DPM-Solver++(2M)	50	Linear	3.62	10.44	**0.61**	0.58
		EDM	3.90	10.85	0.60	0.56
		CRS-v_{FID}	3.59	9.68	0.59	**0.60**
		CRS-v_ε	3.46	9.82	0.60	0.59
		CRS-v_x	**3.43**	**9.45**	0.60	0.59
	30	Linear	3.69	10.23	**0.60**	0.59
		EDM	4.31	11.31	**0.60**	0.56
		CRS-v_{FID}	3.98	9.61	0.58	**0.60**
		CRS-v_ε	3.63	9.91	0.59	**0.60**
		CRS-v_x	**3.59**	**9.51**	0.59	**0.60**
	20	Linear	3.92	10.03	**0.59**	0.59
		EDM	5.25	12.19	**0.59**	0.55
		CRS-v_{FID}	4.95	9.92	0.56	0.58
		CRS-v_ε	**3.89**	9.73	0.58	**0.60**
		CRS-v_x	4.00	**9.44**	0.58	0.59

Table 20: Performance of latent-space diffusion models on LSUN Bedroom 256×256 using stochastic samplers, evaluated under different sampling schedules. The training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
Stochastic DDIM	50	Linear	3.95	8.98	0.56	0.48
		EDM	7.43	16.05	0.54	0.38
		CRS-v_{FID}	3.09	**7.17**	0.57	**0.50**
		CRS-v_ε	3.25	7.81	0.57	0.49
		CRS-v_x	**3.08**	7.20	**0.58**	**0.50**
	30	Linear	7.28	15.70	0.53	0.38
		EDM	17.03	33.60	0.40	0.26
		CRS-v_{FID}	5.17	10.62	**0.57**	0.43
		CRS-v_ε	5.58	12.33	0.56	0.42
		CRS-v_x	**4.78**	**9.85**	0.55	**0.45**
	20	Linear	14.53	29.25	0.42	0.28
		EDM	38.01	68.62	0.21	0.13
		CRS-v_{FID}	9.18	16.67	0.50	0.35
		CRS-v_ε	9.70	19.40	0.49	0.34
		CRS-v_x	**8.11**	**15.96**	**0.51**	**0.36**
SDE-DPM-Solver++(2M)	50	Linear	2.47	6.44	0.57	0.54
		EDM	2.48	6.32	0.57	0.54
		CRS-v_{FID}	**2.21**	5.87	0.57	0.54
		CRS-v_ε	2.22	5.76	0.57	**0.55**
		CRS-v_x	2.23	**5.67**	0.57	0.54
	30	Linear	**2.45**	6.70	0.56	**0.55**
		EDM	2.90	7.41	**0.57**	0.52
		CRS-v_{FID}	2.46	6.19	**0.57**	0.54
		CRS-v_ε	2.50	5.93	**0.57**	0.53
		CRS-v_x	2.48	**5.73**	0.56	0.54
	20	Linear	**2.78**	6.79	0.56	**0.53**
		EDM	4.00	9.57	0.55	0.50
		CRS-v_{FID}	3.19	6.70	0.55	**0.53**
		CRS-v_ε	2.87	**6.22**	**0.57**	**0.53**
		CRS-v_x	3.07	6.34	0.56	0.52

Table 21: Performance of latent-space diffusion models on LSUN Bedroom 256×256 using deterministic samplers, evaluated under different sampling schedules. The training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
DDIM	50	Linear	3.02	6.59	0.53	0.54
		EDM	4.17	7.64	0.52	0.51
		CRS-v_{FID}	2.66	6.03	**0.54**	**0.55**
		CRS-v_ε	2.71	6.03	**0.54**	**0.55**
		CRS-v_x	**2.62**	**5.86**	**0.54**	**0.55**
	30	Linear	3.76	7.50	0.53	0.51
		EDM	6.81	9.98	0.47	0.46
		CRS-v_{FID}	3.23	6.61	0.53	**0.53**
		CRS-v_ε	3.22	6.65	0.53	**0.53**
		CRS-v_x	**3.10**	**6.43**	0.54	**0.53**
	20	Linear	5.38	9.27	0.49	0.48
		EDM	12.57	14.55	0.38	0.40
		CRS-v_{FID}	4.39	7.86	**0.51**	0.49
		CRS-v_ε	4.28	7.97	**0.51**	0.49
		CRS-v_x	**4.10**	**7.54**	**0.51**	**0.51**
PNDM	50	Linear	2.51	6.02	**0.54**	0.56
		EDM	2.64	6.16	0.53	**0.57**
		CRS-v_{FID}	2.50	5.66	**0.54**	**0.57**
		CRS-v_ε	**2.44**	5.73	**0.54**	**0.57**
		CRS-v_x	2.45	**5.61**	**0.54**	0.56
	30	Linear	2.57	6.03	**0.54**	0.56
		EDM	2.93	6.45	0.52	**0.57**
		CRS-v_{FID}	2.64	5.59	0.53	**0.57**
		CRS-v_ε	**2.48**	5.58	**0.54**	0.56
		CRS-v_x	2.65	**5.53**	**0.54**	**0.57**
	20	Linear	2.77	6.13	0.53	**0.57**
		EDM	3.76	7.25	0.52	0.54
		CRS-v_{FID}	3.02	5.66	0.52	**0.57**
		CRS-v_ε	**2.71**	**5.53**	0.54	0.56
		CRS-v_x	3.63	6.23	**0.61**	**0.57**
DPM-Solver++(2M)	50	Linear	2.59	6.15	**0.54**	0.56
		EDM	2.86	6.44	0.52	**0.57**
		CRS-v_{FID}	2.46	5.63	**0.54**	0.56
		CRS-v_ε	2.46	5.63	**0.54**	0.56
		CRS-v_x	**2.37**	**5.42**	**0.54**	0.56
	30	Linear	2.68	6.18	**0.54**	**0.56**
		EDM	3.40	7.09	0.51	**0.56**
		CRS-v_{FID}	**2.60**	5.63	**0.54**	**0.56**
		CRS-v_ε	**2.60**	5.53	**0.54**	**0.56**
		CRS-v_x	2.63	**5.45**	**0.54**	0.55
	20	Linear	2.89	6.24	0.53	**0.56**
		EDM	4.14	8.07	0.52	0.53
		CRS-v_{FID}	3.03	5.81	0.52	**0.56**
		CRS-v_ε	**2.88**	**5.59**	0.53	**0.56**
		CRS-v_x	3.00	5.63	**0.54**	0.55

Table 22: FID scores on LSUN Bedroom 256×256 in latent-space diffusion models at small NFE settings. Bold values indicate the best FID score at each NFE. Results for rows other than "Ours" are taken from Zheng et al. (2023a).

Model	Sampler	Sampling schedule	FID ↓ NFE = 5	NFE = 10	NFE = 20
LDM	DPM-Solver++	Linear	18.59	3.63	3.16
	UniPC		12.24	3.56	3.07
	DPM-Solver-v3 Zheng et al. (2023a)		7.54	3.16	3.05
Ours	iPNDM	Linear	10.81	3.71	2.64
		CRS-v_ε	7.88	**3.12**	**2.48**
		CRS-v_x	8.07	3.45	2.50
		CRS-v_ε: $\xi = 1.4$	7.64	–	–
		CRS-v_x: $\xi = 2.2$	**6.96**	–	–

Table 23: Detailed evaluation results on LSUN Bedroom 256×256 in latent-space diffusion models at small NFE settings. Bold values indicate the best sampling schedule for each metric.

Sampler	NFE	Sampling schedule	Metrics FID ↓	sFID ↓	Precision ↑	Recall ↑
iPNDM	20	Linear	2.64	6.15	0.53	**0.57**
		CRS-v_ε	**2.48**	5.48	0.54	0.56
		CRS-v_x	2.50	**5.41**	**0.55**	0.56
	10	Linear	3.71	6.88	0.52	0.54
		CRS-v_ε	**3.12**	**5.69**	0.52	**0.56**
		CRS-v_x	3.45	6.15	**0.54**	0.53
	5	Linear	10.81	13.82	0.42	0.49
		CRS-v_ε	7.88	9.84	**0.45**	0.50
		CRS-v_x	8.07	10.43	**0.45**	0.48
		CRS-v_ε: $\xi = 1.4$	7.64	9.23	**0.45**	**0.52**
		CRS-v_x: $\xi = 2.2$	**6.96**	**8.65**	**0.45**	0.49

Table 24: Performance of latent-space diffusion models on ImageNet 256×256 at NFE = 30, evaluated under various training and sampling schedules using stochastic samplers. Two samplers were used: Stochastic DDIM and SDE-DPM-Solver++(2M). Gray-shaded rows indicate variations in training schedules (with fixed sampling), while unshaded rows show variations in sampling schedules (with fixed training). Bold values indicate the best result for each evaluation metric.

Sampler	Training schedule	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
Stochastic DDIM	Linear	Linear	27.31	21.39	0.46	0.55
	VDM++		29.00	**17.67**	0.46	**0.57**
	CRS-v_{FID}		**25.50**	21.41	**0.48**	0.56
	CRS-v_ε		26.97	20.71	0.47	0.56
	CRS-v_x		25.83	19.92	0.47	**0.57**
	CRS-v_x	Linear	25.83	19.92	0.47	0.57
		EDM	49.72	50.08	0.31	0.51
		CRS-v_{FID}	20.85	13.01	0.52	0.56
		CRS-v_ε	20.43	13.14	0.53	0.58
		CRS-v_x	**17.88**	**10.14**	**0.55**	**0.59**
SDE-DPM-Solver++(2M)	Linear	Linear	11.12	5.68	**0.62**	0.62
	VDM++		29.00	17.67	0.46	0.57
	CRS-v_{FID}		**10.22**	5.81	**0.62**	**0.64**
	CRS-v_ε		11.18	5.84	**0.62**	0.63
	CRS-v_x		10.25	**5.64**	**0.62**	**0.64**
	CRS-v_x	Linear	10.25	5.64	0.62	**0.64**
		EDM	11.52	6.13	0.60	**0.64**
		CRS-v_{FID}	10.49	5.39	**0.63**	0.63
		CRS-v_ε	**10.24**	**5.22**	**0.63**	0.63
		CRS-v_x	10.56	5.32	**0.63**	0.63

Table 25: Performance of latent-space diffusion models on ImageNet 256×256 at NFE = 30, evaluated under various training and sampling schedules using deterministic samplers. Three samplers were used: DDIM, PNDM, and DPM-Solver++(2M). Gray-shaded rows indicate variations in training schedules (with fixed sampling), while unshaded rows show variations in sampling schedules (with fixed training). Bold values indicate the best result for each evaluation metric.

Sampler	Training schedule	Sampling schedule	Metrics FID ↓	sFID ↓	Precision ↑	Recall ↑
DDIM	Linear	Linear	17.33	6.79	0.55	0.62
	VDM++		19.53	**5.97**	0.54	**0.64**
	CRS-v_{FID}		**15.52**	6.95	**0.56**	0.63
	CRS-v_{ε}		17.02	6.94	0.55	0.63
	CRS-v_{x}		16.28	6.27	**0.56**	**0.64**
	CRS-v_{x}	Linear	16.28	6.27	0.56	**0.64**
		EDM	22.17	9.22	0.49	0.62
		CRS-v_{FID}	15.51	6.72	0.56	0.63
		CRS-v_{ε}	**15.26**	5.79	**0.57**	**0.64**
		CRS-v_{x}	15.28	**5.67**	**0.57**	**0.64**
PNDM	Linear	Linear	13.21	5.35	**0.59**	0.65
	VDM++		16.01	6.31	0.57	**0.66**
	CRS-v_{FID}		**11.42**	**5.31**	**0.59**	**0.66**
	CRS-v_{ε}		12.69	5.45	**0.59**	0.65
	CRS-v_{x}		12.29	5.38	**0.59**	**0.66**
	CRS-v_{x}	Linear	12.29	5.38	**0.59**	**0.66**
		EDM	12.86	5.62	0.58	**0.66**
		CRS-v_{FID}	**12.18**	**5.21**	**0.59**	0.65
		CRS-v_{ε}	12.57	5.24	**0.59**	**0.66**
		CRS-v_{x}	12.65	5.38	**0.59**	**0.66**
DPM-Solver++(2M)	Linear	Linear	13.87	5.41	**0.59**	0.64
	VDM++		16.97	6.45	0.56	**0.66**
	CRS-v_{FID}		**12.09**	**5.40**	**0.59**	0.65
	CRS-v_{ε}		13.41	5.54	0.58	0.65
	CRS-v_{x}		12.92	5.46	**0.59**	**0.66**
	CRS-v_{x}	Linear	**12.92**	5.46	**0.59**	**0.66**
		EDM	13.67	5.79	0.58	**0.66**
		CRS-v_{FID}	13.02	5.19	**0.59**	0.65
		CRS-v_{ε}	13.02	5.17	**0.59**	0.65
		CRS-v_{x}	13.33	**5.13**	**0.59**	0.65

Table 26: Performance of latent-space diffusion models on ImageNet 256×256 using stochastic samplers, evaluated under different sampling schedules. The training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
Stochastic DDIM	50	Linear	15.61	8.97	0.57	0.60
		EDM	25.66	19.17	0.46	0.57
		CRS-v_{FID}	13.67	6.86	**0.60**	0.60
		CRS-v_ε	13.44	7.56	0.59	**0.61**
		CRS-v_x	**13.05**	**6.45**	**0.60**	**0.61**
	30	Linear	25.83	19.92	0.47	0.57
		EDM	49.72	50.08	0.31	0.51
		CRS-v_{FID}	20.85	13.01	0.52	0.56
		CRS-v_ε	20.43	13.14	0.53	0.58
		CRS-v_x	**17.88**	**10.14**	**0.55**	**0.59**
	20	Linear	44.15	42.96	0.34	0.53
		EDM	78.05	99.25	0.20	0.44
		CRS-v_{FID}	30.28	24.26	0.44	0.54
		CRS-v_ε	31.86	26.34	0.43	0.55
		CRS-v_x	**27.20**	**20.09**	**0.47**	**0.56**
SDE-DPM-DPM-Solver++(2M)	50	Linear	9.96	5.62	0.63	**0.64**
		EDM	9.72	5.35	0.63	**0.64**
		CRS-v_{FID}	10.26	5.43	0.63	0.63
		CRS-v_ε	**9.68**	5.33	0.63	**0.64**
		CRS-v_x	10.11	**5.32**	0.63	**0.64**
	30	Linear	10.25	5.64	0.62	**0.64**
		EDM	11.52	6.13	0.60	**0.64**
		CRS-v_{FID}	10.49	5.39	**0.63**	0.63
		CRS-v_ε	**10.24**	**5.22**	**0.63**	0.63
		CRS-v_x	10.56	5.32	**0.63**	0.63
	20	Linear	11.47	5.81	0.61	**0.63**
		EDM	16.26	9.38	0.55	**0.63**
		CRS-v_{FID}	11.10	5.50	**0.63**	0.62
		CRS-v_ε	**10.83**	5.36	0.62	**0.63**
		CRS-v_x	11.64	**5.26**	**0.63**	0.62

Table 27: Performance of latent-space diffusion models on ImageNet 256×256 using deterministic samplers, evaluated under different sampling schedules. The training schedule was fixed to CRS-v_x. Bold values indicate the best sampling schedule for each evaluation metric.

Sampler	NFE	Sampling schedule	Metrics			
			FID ↓	sFID ↓	Precision ↑	Recall ↑
DDIM	50	Linear	13.91	5.37	0.58	**0.65**
		EDM	16.25	6.24	0.55	**0.65**
		CRS-v_{FID}	**13.45**	5.36	0.58	0.64
		CRS-v_ε	13.64	5.20	0.58	**0.65**
		CRS-v_x	13.75	**5.12**	**0.59**	**0.65**
	30	Linear	16.28	6.27	0.56	**0.64**
		EDM	22.17	9.22	0.49	0.62
		CRS-v_{FID}	15.51	6.72	0.56	0.63
		CRS-v_ε	**15.26**	5.79	**0.57**	**0.64**
		CRS-v_x	15.28	**5.67**	**0.57**	**0.64**
	20	Linear	20.49	8.82	0.51	0.62
		EDM	33.08	15.78	0.40	0.60
		CRS-v_{FID}	18.43	7.52	0.54	**0.63**
		CRS-v_ε	18.30	7.57	0.54	**0.63**
		CRS-v_x	**18.16**	**7.05**	**0.55**	0.62
PNDM	50	Linear	12.10	5.32	0.59	**0.66**
		EDM	12.53	5.49	0.59	**0.66**
		CRS-v_{FID}	**11.86**	**5.20**	0.59	0.65
		CRS-v_ε	12.35	5.28	0.59	**0.66**
		CRS-v_x	12.44	5.28	0.59	**0.66**
	30	Linear	12.29	5.38	**0.59**	**0.66**
		EDM	12.86	5.62	0.58	**0.66**
		CRS-v_{FID}	**12.18**	**5.21**	**0.59**	0.65
		CRS-v_ε	12.57	5.24	**0.59**	**0.66**
		CRS-v_x	12.65	5.38	**0.59**	**0.66**
	20	Linear	**12.83**	5.52	**0.59**	**0.66**
		EDM	13.99	5.99	0.58	**0.66**
		CRS-v_{FID}	12.97	5.38	0.58	**0.66**
		CRS-v_ε	12.92	**5.30**	**0.59**	0.65
		CRS-v_x	13.63	6.10	0.57	**0.66**
DPM-Solver++(2M)	50	Linear	12.42	5.41	0.59	**0.66**
		EDM	12.90	5.57	0.59	**0.66**
		CRS-v_{FID}	**12.27**	**5.15**	0.59	0.65
		CRS-v_ε	12.64	5.23	0.59	**0.66**
		CRS-v_x	12.75	5.21	0.59	0.65
	30	Linear	**12.92**	5.46	**0.59**	**0.66**
		EDM	13.67	5.79	0.58	**0.66**
		CRS-v_{FID}	13.02	5.19	**0.59**	0.65
		CRS-v_ε	13.02	5.17	**0.59**	0.65
		CRS-v_x	13.33	**5.13**	**0.59**	0.65
	20	Linear	13.71	5.45	0.58	0.65
		EDM	15.31	6.23	0.57	**0.66**
		CRS-v_{FID}	14.10	5.25	**0.59**	0.65
		CRS-v_ε	**13.70**	5.13	**0.59**	0.65
		CRS-v_x	14.16	**5.09**	**0.59**	0.64

Table 28: Evaluation results on FFHQ 64×64 using the pretrained model provided in EDM. Bold values indicate the best sampling schedule for each combination of sampler and NFE. FID scores for AYS are taken from Sabour et al. (2024).

Sampler	Sampling schedule	FID ↓		
		NFE = 10	NFE = 20	NFE = 50
DPM-Solver++(2M)	EDM	5.57	3.02	2.58
	AYS	5.43	3.29	2.62
	CRS-$v_x + v_{\text{FID}}$	**4.70**	**2.87**	**2.52**
iPNDM	EDM	4.60	2.62	2.49
	CRS-$v_x + v_{\text{FID}}$	**3.87**	**2.53**	**2.44**

Table 29: Evaluation results on CIFAR10 32×32 for class-conditional image generation using the pretrained model provided in EDM. Bold values indicate the best sampling schedule for each combination of sampler and NFE.

Sampler	Sampling schedule	FID ↓		
		NFE = 10	NFE = 20	NFE = 50
DPM-Solver++(2M)	EDM	4.12	2.20	1.94
	CRS-$v_x + v_{\text{FID}}$	**3.03**	**2.07**	**1.89**
iPNDM	EDM	2.51	1.93	1.89
	CRS-$v_x + v_{\text{FID}}$	**2.33**	**1.92**	1.89

Figure 13: Generated samples of LSUN Horse 256×256 using a pixel-space diffusion model at NFE = 250 (FID = 2.03). The training and sampling schedules were optimized using CRS-v_x and CRS-$v_x + v_{\text{FID}}$, respectively. SDE-DPM-Solver++(2M) was used as the sampler.

Figure 14: Generated samples of LSUN Horse 256×256 using a pixel-space diffusion model at NFE = 50 (FID = 2.04). The training and sampling schedules were optimized using CRS-v_x and CRS-$v_x + v_{\text{FID}}$, respectively. PNDM was used as the sampler.

Figure 15: Generated samples of LSUN Bedroom 256×256 using a pixel-space diffusion model at NFE = 10 (FID = 3.30). The training and sampling schedules were optimized using CRS-v_x and CRS-$v_x + v_{\text{FID}}$, respectively. UniPC was used as the sampler.

Figure 16: Generated samples of LSUN Bedroom 256×256 using a pixel-space diffusion model at NFE = 5 (FID = 14.02). The training and sampling schedules were optimized using CRS-v_x and CRS-$v_x + v_{\text{FID}}$, respectively. DPM-Solver++(2M) was used as the sampler.

Figure 17: Generated samples of LSUN Church 256×256 using a latent-space diffusion model at NFE = 20 (FID = 3.89). The training and sampling schedules were optimized using CRS-v_x and CRS-v_ε, respectively. DPM-Solver++(2M) was used as the sampler.

Figure 18: Generated samples of LSUN Bedroom 256×256 using a latent-space diffusion model at NFE = 20 (FID = 2.71). The training and sampling schedules were optimized using CRS-v_x and CRS-v_ε, respectively. PNDM was used as the sampler.

Figure 19: Generated samples of ImageNet 256×256 using a latent-space diffusion model at NFE = 20 with class condition (FID = 10.83). Six classes were randomly selected, and each row corresponds to one class. The training and sampling schedules were optimized using CRS-v_x and CRS-v_ε, respectively. SDE-DPM-Solver++(2M) was used as the sampler.