TOUCAN: Synthesizing 1.5M Tool-Agentic Data from Real-World MCP Environments

Abstract

Large Language Model (LLM) agents are rapidly emerging as powerful systems for automating tasks across domains. Yet progress in the open-source community is constrained by the lack of high quality permissively licensed tool-agentic training data. Existing datasets are limited in diversity, realism, and complexity, particularly regarding multi-tool and multi-turn interactions. To address this gap, we introduce TOUCAN , which contains 1.5 million trajectories synthesized from nearly 500 real-world Model Context Protocols (MCPs). Unlike prior work, TOUCAN leverages authentic MCP environments to generate diverse, realistic, and challenging tasks with trajectories involving real tool execution. Our pipeline first produces a broad spectrum of tool-use queries using five distinct models, applies model-based quality filtering, and then generates agentic trajectories with three teacher models using two agentic frameworks. Rigorous rule-based and model-based validation ensures high-quality outputs. We also introduce three extensions to further diversify tasks and simulate multi-turn conversations. Models fine-tuned on TOUCAN outperform larger closed-source counterparts on the BFCL V3 benchmark and establish a new Pareto optimum on MCP-Universe Bench.

1 Introduction

Large language models (LLMs) have become integral to AI applications, with LLM agents emerging as powerful systems for automating complex tasks across diverse domains (Li et al., 2024). There is growing excitement about the potential of LLM agents to unlock new levels of automation across industries (Ferrag et al., 2025; Bousetouane, 2025). These agents handle multi-step workflows that require discovering the right tools from potentially large toolsets, calling them correctly with appropriate parameters, handle tool failures gracefully, and synthesizing results into accurate, context-aware

responses (Xu et al., 2025a). Recent advancements, such as the Model Context Protocol (MCP) (Anthropic, 2025), have streamlined tool integration by providing standardized interfaces, enabling seamless connections between LLMs and real-world environments and simplifying the process for agents to discover, invoke, and execute external tools.

Despite these advancements, progress in the open-source community is constrained by the lack of high-quality, permissively licensed **tool-agentic data** for training more capable agentic LLMs. An instance of tool-agentic data comprises a task-trajectory pair, where trajectories capture sequences of planning, tool calls, tool responses, and the final model response. While previous efforts (Qin et al., 2023; Liu et al., 2024, 2025a; Prabhakar et al., 2025) have introduced datasets covering various tool-calling scenarios, they suffer from several limitations: restricted tool diversity, lack of authentic tool responses, focus on single-turn conversations between users and models, or insufficient scale, all of which constrain effective training of agentic capabilities. There is an urgent need for comprehensive, high-quality datasets that capture the full spectrum of tool-agentic interactions observed in production environments.

In this work, we bridge this gap by introducing TOUCAN, the largest publicly available tool-agentic dataset to date, comprising 1.5 million trajectories synthesized from nearly 500 real-world MCP servers. Unlike prior approaches that rely on simulated or limited toolsets, TOUCAN leverages authentic MCP environments with more than 2,000 tools to generate diverse, realistic, and challenging tasks spanning parallel and multi-step tool calls, as well as multi-turn conversations. Our pipeline begins by producing a broad spectrum of tool-use tasks using five distinct models with MCP server specifications, followed by model-based quality filtering to ensure relevance and difficulty. We then generate agentic trajectories with

three teacher models, incorporating rigorous rule-based and model-based checks for high-quality outputs, including verification of tool execution and response accuracy. Our pipeline also integrates extensions to generate additional tasks targeting edge case scenarios, interactive conversations, and multi-turn dialogues.

Our experiments demonstrate the effectiveness of TOUCAN in enhancing LLM agentic capabilities. Models fine-tuned on TOUCAN surpass closed-source counterparts on the BFCL V3 benchmark (Patil et al., 2025), achieving superior performance in function calling accuracy across single-turn and multi-turn scenarios. Furthermore, they show substantial improvements on τ-Bench (Yao et al., 2024) and τ^2-Bench (Barres et al., 2025), with gains in tool selection, execution fidelity, and multi-turn reasoning under dynamic user interactions. On the recent MCP-Universe benchmark (Luo et al., 2025), which evaluates LLMs on 231 realistic tasks using 11 real-world MCP servers, TOUCAN-tuned models achieve state-of-the-art performance within their parameter class, outperforming leading models of comparable size. In summary, the contributions of our work are:

- **TOUCAN Dataset**. The largest open-source tool-agent dataset, covering parallel and multi-step tool calls, multi-turn dialogues, and edge-cases.
- **TOUCAN Pipeline**. A pipeline that leverages any MCP specifications to generate diverse tool-agent trajectories, supports tool execution through MCP servers, and can be seamlessly extended to new tools via the MCP standard.
- **TOUCAN Checkpoints**. Experiments demonstrate that models fine-tuned on TOUCAN mixtures surpass closed-source counterparts on the BFCL V3 and MCP-Universe benchmarks.

2 Related Work

The past: Tool-calling datasets and benchmarks for LLMs. Early tool-calling datasets enabled LLMs to interact with tools like REST APIs and ML functions. The Gorilla project (Patil et al., 2023) demonstrated that fine-tuning on such data enhances tool-use over vanilla models, introducing the BFCL benchmark (Patil et al., 2025) as a standard. ToolAlpaca (Tang et al., 2023) offered cost-effective synthetic data with lower quality, while ToolLLM (Qin et al., 2023) expanded to 16,000+ APIs across domains. API Pack (Guo et al., 2025a) added cross-language diversity (Python,

Java, C++), and API Blend (Basu et al., 2024) optimized dataset mixtures for robustness, laying the foundation for tool-agent advancements. More recently, APIGen has focused on domain diversification, contributing a training dataset covering 21 domains (Liu et al., 2024).

The present: Tool-calling benchmarks and datasets for LLM-agents. Recent research has shifted toward training LLM agents for effective tool use, exemplified by models like Kimi-K2 (Team et al., 2025b) and GLM-4.5 (Team et al., 2025a), with performance assessed via benchmarks such as BFCL (Patil et al., 2025), τ-Bench (Yao et al., 2024), and ACEBench (Chen et al., 2025). BFCL covers diverse scenarios including parallel, multi-step, and multi-turn tool use, while τ-Bench focuses on realistic user-agent-tool interactions. ACEBench enhances evaluation by addressing edge cases and including a subset for tool-agent trajectories. Despite these advances, open-source training data for tool-agent trajectories remains limited. Existing datasets (interstellarninja; Liu et al., 2025a; Prabhakar et al., 2025; Nathawani et al., 2025) either lack dataset curation transparency, are small in size, simulate tool responses via LLMs, or focus on VLMs rather than LLMs (Gao et al., 2025b). Table 16 in the appendix compares existing tool-agentic datasets for LLMs with TOUCAN, which, at 1.5 million trajectories, offers the largest dataset, featuring extensive multi-turn dialogues, all tool-use scenarios, critical edge cases, and authentic tool responses from real-world environments.

The future: MCP benchmarks and datasets. As concurrent work, recent MCP benchmarks (Gao et al., 2025a; Wang et al., 2025; Luo et al., 2025; Team, 2025a; Guo et al., 2025b; Yin et al., 2025; Liu et al., 2025b; Yan et al., 2025; Team, 2025b) aim to rigorously assess LLMs in tool-use settings beyond simple correctness. For instance, MCP-Radar (Gao et al., 2025a) employs a five-dimensional evaluation including accuracy, tool selection efficiency, resource usage, parameter construction, and execution speed across software engineering, math, and problem-solving tasks with 300 queries and 42 MCP servers. Similarly, MCP-Bench (Wang et al., 2025) evaluates multi-step reasoning over 28 MCP servers and 250 tools, while MCP-Universe (Luo et al., 2025) focuses on execution-based metrics in six real-world domains. These advancements underscore the need for comprehensive training datasets to support the development of robust, open-source LLM agents.

Figure 1: The TOUCAN construction pipeline: A systematic five-stage process from MCP server onboarding through trajectory filtering, with three extensions for enhancing data diversity and realism.

3 TOUCAN: Scaling Tool-Agentic Data with Real World MCPs

3.1 TOUCAN Generation Pipeline

TOUCAN is a comprehensive dataset comprising over 1.5 million tool-agent trajectories constructed using real-world tools from MCP servers. Each instance in our dataset contains a task description, a complete agent trajectory with its associated tools, quality and classification annotations, as well as comprehensive metadata. Appendix A provides a detailed schema description and demonstration samples. The construction of TOUCAN follows a systematic five-stage pipeline: MCP server onboarding, task synthesis, task filtering, trajectory generation, and trajectory filtering. Additionally, we implement three extension mechanisms to further enhance data diversity and realism. Figure 1 illustrates the complete construction pipeline. We detail each stage below.

Figure 2: MCP servers filtering process.

Stage 1: MCP Server Onboarding. To generate questions from diverse environments, the initial step involves onboarding as many high-quality MCP servers as possible. We sourced MCP server specification files from GitHub and Smithery [1], a platform and registry for MCP servers that encapsulate modular execution environments. Each MCP server is accompanied by a structured JSON document detailing metadata about the server with a machine-readable definition of the tools it provides. From an initial crawl yielding approximately 2,800 MCP servers, we applied two key filtering criteria: (1) retaining only remote MCP servers accessible via streamable HTTP to ensure compatibility with trajectory generation, and (2) excluding servers requiring third-party credentials (e.g., API keys) for tool invocation to maintain accessibility and reproducibility. This process reduced the dataset to 30.6% (871 servers). As a final step, we generated a small subset of test questions to evaluate each tool within the MCP servers, subsequently filtering out servers with problematic tools that returned error messages or failed to function correctly. This rigorous curation process resulted in a refined set of 495 high-quality MCP servers spanning diverse domains and functionalities. Figure 2 depicts the number of MCP servers retained at each filtering stage. Figure 3 demonstrates the domain distribution of the final server collection across diverse categories. The domain distribution is annotated by LLMs, the prompts can be found in Appendix D.1.

Stage 2: Task Synthesis. The next step focuses on synthesizing high-quality tasks that involve complex tool calling over MCP servers. Each task comprises a question and the desired tools required from the MCP servers. The key challenge is ensuring that tasks are challenging, realistic, and cover edge cases. Therefore, we design diverse sampling strategies based on MCP server usage number from Smithery and server functionalities. To avoid potential bias from individual models, we uti-

[1]https://smithery.ai/

Figure 3: MCP servers distribution by domain, covering a wide range of categories. Values in parentheses indicate the number of servers belonging to each category.

lized five open-source LLMs (`Mistral-Small`, `DevStral-Small`, `GPT-OSS`, `Kimi-K2`, and `Qwen3-32B`) as task generators to construct synthetic tasks (see the prompts in Appendix D.2). We apply the following three strategies to synthesize tasks, where the maximum number of tools is set to $N = 3$ in our experiments:

Single Server: For a given MCP server, we synthesize tasks requiring the use of 1 to N tools, ensuring a balanced selection distribution guided by server usage statistics to reflect real-world applicability.

Multi-Server: Leveraging LLM-based domain annotations derived from MCP metadata, we first sample N MCP servers from either the same or different categories. We then prompt LLMs to conduct a server analysis, outlining potential workflows that integrate tools across these servers, targeting two to N specific tools, and subsequently generating tasks that leverage functionalities from multiple servers.

Featured Server: Based on the original MCP file metadata, we manually selected 25 representative MCP servers from various domains, with the complete list available in Appendix B.1. In this approach, we provide all MCP server metadata within the context, specify an expected number of tools, and allow the LLM to freely explore combinations, devise realistic scenarios, select the necessary tools, and create comprehensive tasks.

Stage 3: Task Filtering. To ensure the quality of synthesized tasks, this stage involves annotating tasks across six dimensions and filter out subopti-

mal instances. We employed the `Kimi-K2` model as the annotator, which was selected for its optimal balance between correlation with human annotations and cost efficiency. The correlation statistics are detailed in Appendix C.1, and the prompt template is provided in Appendix D.4. Each dimension is rated on a 1-5 Likert scale. The detailed evaluation metrics are as follows:

- *Tool Selection Difficulty:* Judges the difficulty of selecting the required tools from provided tools.
- *Tool Selection Uniqueness:* Assesses the uniqueness of the selected tool combination relative to the available tools, and whether viable alternatives could also solve the task.
- *Question Quality:* The task's overall quality, reflected by its clarity, specificity, and effectiveness.
- *Scenario Realism:* Evaluates the authenticity and realism of the task scenario.
- *Verifiable:* Evaluates how easily the final model answer can be verified given the question.
- *Stability:* Evaluates whether tool outputs remain consistent over time, across geolocation, and under stochastic variation.

Stage 4: Trajectory Generation. This step involves collecting trajectories including tool calls, tool responses, and reasoning steps in agentic environments given tasks synthesized and filtered from the previous steps. To ensure diversity, we employed three LLMs from different families (`GPT-OSS-120B`, `Kimi-K2`, and `Qwen3-32B`) in combination with two agent frameworks (`Qwen-agent` and `OpenAI-agent`) to produce high-quality agentic trajectories. The models are deployed remotely and accessed by the agent frameworks via streamable HTTP.

Stage 5: Rule&LLM-Based Post-Filtering. The trajectory filtering process combines rule-based verifiers with LLM-driven annotations to ensure high quality. Rule-based heuristics exclude trajectories that fail to start the agent or connect successfully with remote MCP servers, do not contain tool calls, exhibit failures in all tool responses, or contain local file system paths. We also validate whether the trajectory uses the required tools specified by the task in the correct sequence, and report both the *desired tool use percentage* (coverage of required tools) and *order correctness* (adherence to expected sequence) metrics. We then employ `GPT-OSS-120B` as a judge to annotate each trajectory in terms of completeness and con-

Figure 4: The figures above illustrate the TOUCAN dataset analysis. Subfigure (a) and (b) provide statistics on the number of servers and required tools per instance, highlighting TOUCAN 's comprehensive coverage of multi-server and multi-tool tasks. Subfigures (c) and (d) reveal that most tasks include more tools in the context than the targeted tools, underscoring the non-trivial tool selection challenges. Subfigure (e) displays the length of user messages in tokens. Subfigures (f) and (h) demonstrate the multi-turn nature of the tasks, characterized by extended and diverse interactions among users, agents, and tools. Subfigure (g) demonstrates that TOUCAN encompasses both single and parallel tool calls, which enhance the dataset's versatility in capturing diverse agent-tool interaction patterns.

ciseness. The annotation prompt is provided in Appendix D.5, with metric definitions as follows:

- *Completeness:* Judges whether the assistant fulfills the user's request end-to-end.
- *Conciseness:* Judges whether the task is solved with the minimum necessary steps and verbosity.

This dual-stage filtering approach ensures that only high-quality, concise, and executable trajectories are retained in the final dataset.

3.2 TOUCAN Extensions

While the core pipeline generates high-quality trajectories, these are single-turn interactions between user and agent without follow-ups, which limits their practical applicability to real-world scenarios. In addition, since all available tools are contextually relevant, tool selection becomes trivial for LLMs, resulting in relatively low difficulty. To address these limitations and enhance the dataset's versatility, we apply three distinct procedures post-core pipeline (Steps 1 to 5) to generate new instances targeting specific objectives.

Ext.1: Irrelevance. To reduce hallucination, it is critical to train models to reject unanswerable queries or seek alternative solutions when desired tools are unavailable. To achieve this, we systematically generate queries unsolvable with the current toolset (Ext1 in Figure 1) by shuffling MCP server metadata across instances and repeating the task generation step.

Ext.2: Persona-based Diversification. We implement persona-based diversification (Ext2 in Fig-

ure 1) to create varied task versions. This involves two strategies: one enhances diversity by introducing new contexts and personas, while the other increases task complexity through additional constraints, all while utilizing the same target tools. This diversification process produces tasks similar yet distinct from those in the core pipeline. The prompts are detailed in Appendix D.3.

Ext.3: Multi-Turn. Recognizing that real-world user-agent-tool interactions seldom conform to single-turn conversations (Yao et al., 2024), we introduce a self-simulation pipeline to generate multi-turn dialogues using the trajectory generation model. This is achieved through two methods: (1) splitting complex tasks requiring multi-tool coordination into sequential sub-questions, and (2) extending existing conversations by providing LLMs with context to formulate follow-up queries.

Finally, we repeat the core pipeline from steps 2 to 5 to build full trajectories with new tasks. For irrelevant tasks (Ext.1), we tighten trajectory filters to retain only instances with zero tool calls. Together, these data extensions yield a more realistic and robust TOUCAN dataset that covers all relevant tool-use scenarios and user question styles.

3.3 Data Analysis

This section analyzes the generated TOU-CAN dataset from statistical analysis and LLM-based quality assessment.

Statistical Analysis of TOUCAN . We conduct comprehensive statistical analysis of MCP servers

Figure 5: TOUCAN Subset Statistics.

Figure 6: TOUCAN Quality Statistics.

and data instances. The top MCP servers used in TOUCAN and tool statistics within each MCP servers are presented in Appendix B.2. Figure 4 provides a comprehensive analysis of the TOU-CAN dataset. We observe that TOUCAN provides comprehensive coverage of multi-server and multi-tool tasks, and includes multi-turn conversations among users, agents, and tools. Additionally, most tasks contain more tools in the context than the required target tools, indicating non-trivial tool selection requirements. Figure 5 presents the subset statistics of TOUCAN across different trajectory generator LLMs and data partitions. We also provide embedding visualization of TOUCAN using UMAP projection in Appendix B.3, demonstrating the wide domain coverage of TOUCAN.

Quality Assessment of TOUCAN. Figure 6

presents a statistical analysis conducted by an LLM-as-a-judge on TOUCAN. From the task perspective (labels in ■), we observe that the majority of tasks exhibit exceptionally high question quality and scenario realism, indicating robust task design and alignment with real-world applications. Additionally, the dataset features a mixed difficulty range, encompassing both simple and challenging tasks. From the response perspective (label in ■), we find that trajectory quality is satisfactory, with most scores at or above 3 (medium) across both completeness and conciseness metrics.

4 Experiments

In this section, we demonstrate the performance of TOUCAN by comparing the fine-tuned models' performance against existing model baselines across several widely used agentic benchmarks.

4.1 Experiment Setup

Model Setup. We perform supervised fine-tuning on different model families including `Qwen2.5-{7,14,32}B-Instruct` (Team, 2024) and `Llama3.1-{8,70}B-Instruct` (Dubey et al., 2024) to demonstrate the efficacy of TOUCAN across models of varying sizes. Detailed fine-tuning parameters are provided in Appendix C.2. We benchmark the performance of our fine-tuned models against models of comparable or larger scales, including `DeepSeek-V3` (DeepSeek-AI et al., 2025), `Qwen2.5-72B-Instruct`, `Qwen3-235B-A22B`, `Qwen3-32B` (Yang et al., 2025), and closed-source OpenAI models such as o3-mini, GPT-4.1, and GPT-4.5-Preview.

TOUCAN Setup. Given the large volume of the dataset, we follow the strategy of (Xu et al., 2025b) by sampling from a high-quality subset of TOUCAN. This subset was selected based on the following criteria: question quality and scenario realism scores of 5, response completeness and conciseness scores of at least 4, and desired tool use percentage of 1.0 (indicating that trajectories fully utilize all required tools from the task). We performed necessary data re-balancing to ensure the dataset remains representative across different categories. The resulting SFT dataset comprises 28.3K instances from the original pipeline, 40K instances from Ext.1 (Irrelevance), 15.8K instances from Ext.2 (Diversify), and 35.2K instances from Ext.3 (Multi-Turn), totaling 119.3K instances.

Table 1: Performance of TOUCAN-tuned models and baselines on BFCL-V3. TOUCAN remarkably improves baseline performance through SFT and enables smaller models to outperform larger models across different aspects.

Model	Overall	Single Turn		Multi Turn	Hallucination	
		Non-live (AST)	*Live (AST)*		*Relevance*	*Irrelevance*
DeepSeek-V3	64.71%	88.54%	77.34%	29.87%	**83.33%**	76.49%
Qwen2.5-72B-Instruct	64.37%	87.56%	78.68%	29.38%	72.22%	77.41%
Qwen3-235B-A22B	67.94%	87.90%	77.03%	40.12%	**83.33%**	76.32%
Qwen3-32B	69.25%	**88.90%**	77.83%	43.12%	72.22%	75.79%
o3-Mini	64.61%	86.15%	79.08%	28.75%	72.22%	82.96%
GPT-4.1	68.69%	85.42%	**79.92%**	40.50%	77.78%	**85.95%**
GPT-4.5-Preview	70.32%	86.12%	79.34%	45.38%	66.67%	83.64%
Qwen2.5-7B-Instruct	55.10%	84.19%	72.32%	12.88%	72.22%	67.93%
with TOUCAN	58.26% +3.16%	78.52%	74.50%	22.62%	66.67%	75.18%
Qwen2.5-14B-Instruct	57.69%	83.38%	73.70%	19.75%	**83.33%**	68.46%
with TOUCAN	65.09% +7.40%	85.42%	76.01%	35.25%	72.22%	75.96%
Qwen2.5-32B-Instruct	61.73%	85.58%	76.01%	26.38%	72.22%	72.68%
with TOUCAN	**70.45%** +8.72%	87.12%	78.90%	**46.50%**	77.78%	78.10%
Llama-3.1-8B-Instruct	26.23%	47.96%	33.63%	6.38%	94.44%	5.26%
with TOUCAN	58.46% +32.23%	83.44%	70.68%	24.88%	77.78%	64.85%
Llama-3.3-70B-Instruct	53.03%	85.23%	62.86%	16.38%	100.00%	48.50%
with TOUCAN	66.20% +13.17%	85.79%	73.48%	42.25%	77.78%	68.22%

Table 2: τ-Bench and τ^2-Bench results for models fine-tuned on TOUCAN compared to their respective baselines. Improvements are observed across most evaluation scenarios.

Model	τ-bench			τ^2-bench			
	Avg.	*Airline*	*Retail*	*Avg.*	*Airline*	*Retail*	*Telecom*
Qwen2.5-7B-Instruct	15.03%	8.75%	21.30%	16.08%	14.00%	17.54%	16.70%
with TOUCAN	22.48% +7.45%	15.50%	29.46%	17.77% +1.69%	20.00%	22.80%	10.50%
Qwen2.5-14B-Instruct	30.85%	17.25%	44.46%	24.46%	12.00%	41.20%	20.18%
with TOUCAN	35.24% +4.39%	22.00%	48.48%	30.43% +5.97%	22.00%	49.10%	20.18%
Qwen2.5-32B-Instruct	38.76%	26.00%	51.52%	29.40%	18.00%	49.10%	21.11%
with TOUCAN	42.33% +3.57%	29.00%	55.65%	31.60% +2.20%	22.00%	52.60%	20.20%

Benchmarks. We assess the performance of TOUCAN across several key tool-agentic benchmarks, including BFCL V3 (Patil et al., 2025), τ-Bench (Yao et al., 2024), τ^2-Bench (Barres et al., 2025), and MCP-Universe (Luo et al., 2025). All evaluations are conducted on an 8 × H100 server. For BFCL-V3, we use the official evaluation setup. For τ-Bench and τ^2-Bench, we employ GPT-4o as user simulators. For MCP-Universe, we configure the local evaluation environment as specified in the benchmark documentation.

4.2 Experimental Results

TOUCAN Effectively Increases Agentic Tool-Calling Performance. Tables 1 and 2 present the experimental results of models fine-tuned on TOUCAN across BFCL V3, τ-Bench, and τ^2-Bench, respectively. Models fine-tuned with TOUCAN show performance improvements compared to baseline models without fine-tuning across almost all aspects of these three benchmarks, indicating that TOUCAN effectively enhances the agentic and tool-calling capabilities of models. Additionally, on BFCL V3, models fine-tuned on TOUCAN outperform larger frontier LLMs including DeepSeek-V3 and GPT-4.5-Preview in average scores and achieve top performance in the *multi-turn* subset. This demonstrates the effectiveness of TOUCAN and validates our pipeline design.

Figure 7: This figure compares the performance of TOUCAN-tuned models with other open-source models on MCP-Universe (Luo et al., 2025). Model sizes increase from left to right. Bars with darker colors represent task success rate (full task completion), while lighter colors represent average evaluation scores considering partial task completion. TOUCAN-tuned models are shown with black borders. TOUCAN-tuned models outperform other models of similar sizes across most tasks.

Figure 8: Model Performance vs Size on MCP-Universe Benchmark. We report overall task success rate (OSR). Our models achieve a new Pareto optimum, outperforming leading models.

TOUCAN Enhances Models' Performance on Using Real-World MCP Servers. Figure 7 demonstrates a performance comparison between TOUCAN-tuned models and other open-source models of similar or larger sizes across six domains: Location Navigation, Repository Management, Financial Analysis, 3D Design, Browser Automation, and Web Search. We note that most MCP servers included in the benchmark are intentionally excluded from our data synthesis pipeline to ensure clean evaluation and minimize data contamination (see Appendix B.4 for a detailed analysis). Nevertheless, models fine-tuned on TOUCAN exhibit substantial performance gains over strong baselines on these challenging tasks, suggesting that exposure

to diverse tools improves generalization in agentic settings. Notably, our 32B model achieves the highest scores in 3D Design and strong performance in Financial Analysis, outperforming larger frontier open models like `Qwen2.5-72B-Instruct`, `GLM-4.5-Air` (106B), and `DeepSeek-V3` (671B). Figure 8 plots model performance versus model size on MCP-Universe benchmark. TOUCAN-tuned models establish a new Pareto optimum, indicating that TOUCAN can achieve superior performance-efficiency trade-offs in agentic tasks.

More Analysis. We include further ablation analysis on TOUCAN extensions, tool number scaling, dataset size scaling, fine-tuning comparisons between TOUCAN and other baseline datasets, the importance of trajectory annotation and filtering, and data mixture recipes in Appendix C.4–C.10.

5 Conclusion and Future Work

This paper introduces TOUCAN, a tool-agentic dataset containing 1.5M trajectories for training large language model (LLM) agents. We present a comprehensive data generation pipeline and demonstrate that models fine-tuned on TOUCAN consistently outperform strong baselines on benchmarks such as BFCL-V3 and MCP-Universe. By enabling scalable and realistic tool-use synthesis, TOUCAN provides a foundation for studying and improving agentic LLM behavior, and we hope it will facilitate further research on building more capable and reliable tool-using agents.

Limitations

This paper presents TOUCAN, a dataset and data generation pipeline for research on large language model (LLM) tool use. The proposed dataset and synthesis pipeline are constructed from publicly available sources, and automated filtering is applied to reduce the risk of exposing sensitive information. As the collected tool-use scenarios reflect the environments available at the time of data generation, the dataset may inherit temporal limitations and evolving assumptions about tool interfaces and diversity. While improved tool-calling capabilities can enable beneficial applications such as automation and decision support, they may also amplify risks if deployed without appropriate safeguards. We therefore emphasize that models trained using this dataset should be evaluated and deployed responsibly.

References

Anthropic. 2025. Introducing the model context protocol. https://www.anthropic.com/news/model-context-protocol. Accessed: 2025-08-18.

Victor Barres, Honghua Dong, Soham Ray, Xujie Si, and Karthik Narasimhan. 2025. τ^2-bench: Evaluating conversational agents in a dual-control environment. *Preprint*, arXiv:2506.07982.

Kinjal Basu, Ibrahim Abdelaziz, Subhajit Chaudhury, Soham Dan, Maxwell Crouse, Asim Munawar, Sadhana Kumaravel, Vinod Muthusamy, Pavan Kapanipathi, and Luis A. Lastras. 2024. Api-blend: A comprehensive corpora for training and benchmarking api llms. *Preprint*, arXiv:2402.15491.

Fouad Bousetouane. 2025. Agentic systems: A guide to transforming industries with vertical ai agents. *Preprint*, arXiv:2501.00881.

Chen Chen, Xinlong Hao, Weiwen Liu, Xu Huang, Xingshan Zeng, Shuai Yu, Dexun Li, Shuai Wang, Weinan Gan, Yuefeng Huang, Wulong Liu, Xinzhi Wang, Defu Lian, Baoqun Yin, Yasheng Wang, and Wu Liu. 2025. ACEBench: Who Wins the Match Point in Tool Usage? *arXiv preprint*. ArXiv:2501.12851 [cs].

DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, and 181 others. 2025. Deepseek-v3 technical report. *Preprint*, arXiv:2412.19437.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony S. Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, and 510 others. 2024. The llama 3 herd of models.

Mohamed Amine Ferrag, Norbert Tihanyi, and Merouane Debbah. 2025. From llm reasoning to autonomous ai agents: A comprehensive review. *Preprint*, arXiv:2504.19678.

Xuanqi Gao, Siyi Xie, Juan Zhai, Shqing Ma, and Chao Shen. 2025a. Mcp-radar: A multi-dimensional benchmark for evaluating tool use capabilities in large language models. *Preprint*, arXiv:2505.16700.

Zhi Gao, Bofei Zhang, Pengxiang Li, Xiaojian Ma, Tao Yuan, Yue Fan, Yuwei Wu, Yunde Jia, Song-Chun Zhu, and Qing Li. 2025b. Multi-modal agent tuning: Building a vlm-driven agent for efficient tool usage. *Preprint*, arXiv:2412.15606.

Zhen Guo, Adriana Meza Soria, Wei Sun, Yikang Shen, and Rameswar Panda. 2025a. Api pack: A massive multi-programming language dataset for api call generation. *Preprint*, arXiv:2402.09615.

Zikang Guo, Benfeng Xu, Chiwei Zhu, Wentao Hong, Xiaorui Wang, and Zhendong Mao. 2025b. Mcp-agentbench: Evaluating real-world language agent performance with mcp-mediated tools. *Preprint*, arXiv:2509.09734.

Teknium interstellarninja. Hermes function calling dataset v1.

Xinyi Li, Sai Wang, Siqi Zeng, Yu Wu, and Yi Yang. 2024. A survey on llm-based multi-agent systems: workflow, infrastructure, and challenges. *Vicinagearth*, 1(1):9.

Weiwen Liu, Xu Huang, Xingshan Zeng, Xinlong Hao, Shuai Yu, Dexun Li, Shuai Wang, Weinan Gan, Zhengying Liu, Yuanqing Yu, Zezhong Wang, Yuxian Wang, Wu Ning, Yutai Hou, Bin Wang, Chuhan Wu, Xinzhi Wang, Yong Liu, Yasheng Wang, and 8 others. 2025a. Toolace: Winning the points of llm function calling. *Preprint*, arXiv:2409.00920.

Zhiwei Liu, Jielin Qiu, Shiyu Wang, Jianguo Zhang, Zuxin Liu, Roshan Ram, Haolin Chen, Weiran Yao, Shelby Heinecke, Silvio Savarese, Huan Wang, and Caiming Xiong. 2025b. Mcpeval: Automatic mcp-based deep evaluation for ai agent models. *Preprint*, arXiv:2507.12806.

Zuxin Liu, Thai Hoang, Jianguo Zhang, Ming Zhu, Tian Lan, Shirley Kokane, Juntao Tan, Weiran Yao, Zhiwei Liu, Yihao Feng, Rithesh Murthy, Liangwei Yang, Silvio Savarese, Juan Carlos Niebles, Huan Wang, Shelby Heinecke, and Caiming Xiong. 2024. Apigen: Automated pipeline for generating verifiable and diverse function-calling datasets. *Preprint*, arXiv:2406.18518.

Ziyang Luo, Zhiqi Shen, Wenzhuo Yang, Zirui Zhao, Prathyusha Jwalapuram, Amrita Saha, Doyen Sahoo, Silvio Savarese, Caiming Xiong, and Junnan Li. 2025. Mcp-universe: Benchmarking large language models with real-world model context protocol servers. *Preprint*, arXiv:2508.14704.

Leland McInnes and John Healy. 2018. Umap: Uniform manifold approximation and projection for dimension reduction. *ArXiv*, abs/1802.03426.

Dhruv Nathawani, Igor Gitman, Somshubra Majumdar, Evelina Bakhturina, Ameya Sunil Mahabaleshwarkar, , Jian Zhang, and Jane Polak Scowcroft. 2025. Nemotron-Post-Training-Dataset-v1.

Shishir G. Patil, Huanzhi Mao, Charlie Cheng-Jie Ji, Fanjia Yan, Vishnu Suresh, Ion Stoica, and Joseph E. Gonzalez. 2025. The berkeley function calling leaderboard (bfcl): From tool use to agentic evaluation of large language models. In *Forty-second International Conference on Machine Learning*.

Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. 2023. Gorilla: Large language model connected with massive apis. *Preprint*, arXiv:2305.15334.

Akshara Prabhakar, Zuxin Liu, Ming Zhu, Jianguo Zhang, Tulika Awalgaonkar, Shiyu Wang, Zhiwei Liu, Haolin Chen, Thai Hoang, Juan Carlos Niebles, Shelby Heinecke, Weiran Yao, Huan Wang, Silvio Savarese, and Caiming Xiong. 2025. Apigenmt: Agentic pipeline for multi-turn data generation via simulated agent-human interplay. *Preprint*, arXiv:2504.03601.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2023. Toolllm: Facilitating large language models to master 16000+ real-world apis. *Preprint*, arXiv:2307.16789.

Donghao Ren, Fred Hohman, and Dominik Moritz. 2025. A scalable approach to clustering embedding projections. *Preprint*, arXiv:2504.07285.

Qiaoyu Tang, Ziliang Deng, Hongyu Lin, Xianpei Han, Qiao Liang, Boxi Cao, and Le Sun. 2023. ToolAlpaca: Generalized Tool Learning for Language Models with 3000 Simulated Cases. *arXiv preprint*. ArXiv:2306.05301 [cs].

5 Team, Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, Kedong Wang, Lucen Zhong, Mingdao Liu, Rui Lu, Shulin Cao, Xiaohan Zhang, Xuancheng Huang, Yao Wei, and 152 others. 2025a. Glm-4.5: Agentic, reasoning, and coding (arc) foundation models. *Preprint*, arXiv:2508.06471.

Kimi Team, Yifan Bai, Yiping Bao, Guanduo Chen, Jiahao Chen, Ningxin Chen, Ruijue Chen, Yanru Chen, Yuankun Chen, Yutian Chen, Zhuofu Chen, Jialei Cui, Hao Ding, Mengnan Dong, Angang Du, Chenzhuang Du, Dikang Du, Yulun Du, Yu Fan, and 150 others. 2025b. Kimi k2: Open agentic intelligence. *Preprint*, arXiv:2507.20534.

Qwen Team. 2024. Qwen2.5: A party of foundation models.

The MCPMark Team. 2025a. Mcpmark: Stress-testing comprehensive mcp use. https://github.com/eval-sys/mcpmark.

The Scale Research Team. 2025b. Actions, not words: Mcp-atlas raises the bar for agentic evaluation. https://scale.com/blog/mcp-atlas. Accessed: YYYY-MM-DD.

Zhenting Wang, Qi Chang, Hemani Patel, Shashank Biju, Cheng-En Wu, Quan Liu, Aolin Ding, Alireza Rezazadeh, Ankit Shah, Yujia Bao, and Eugene Siow. 2025. Mcp-bench: Benchmarking tool-using llm agents with complex real-world tasks via mcp servers. *Preprint*, arXiv:2508.20453.

Weikai Xu, Chengrui Huang, Shen Gao, and Shuo Shang. 2025a. Llm-based agents for tool learning: A survey. *Data Science and Engineering*.

Zhangchen Xu, Yang Liu, Yueqin Yin, Mingyuan Zhou, and Radha Poovendran. 2025b. Kodcode: A diverse, challenging, and verifiable synthetic dataset for coding. *ArXiv*, abs/2503.02951.

Yunhe Yan, Shihe Wang, Jiajun Du, Yexuan Yang, Yuxuan Shan, Qichen Qiu, Xianqing Jia, Xinge Wang, Xin Yuan, Xu Han, Mao Qin, Yinxiao Chen, Chen Peng, Shangguang Wang, and Mengwei Xu. 2025. Mcpworld: A unified benchmarking testbed for api, gui, and hybrid computer use agents. *Preprint*, arXiv:2506.07672.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. 2024. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *Preprint*, arXiv:2406.12045.

Ming Yin, Dinghan Shen, Silei Xu, Jianbing Han, Sixun Dong, Mian Zhang, Yebowen Hu, Shujian Liu, Simin Ma, Song Wang, and 1 others. 2025. Livemcp-101: Stress testing and diagnosing mcp-enabled agents on challenging queries. *arXiv preprint arXiv:2508.15760*.

A Dataset Schema and Examples

An instance of TOUCAN contains the following columns:

- **uuid:** Unique sample identifier.

- **subset:** Annotation specifying which pipeline was used to generate the trajectory. Options: (1) *single-turn-original:* only the core processing (Stage 1 to 5) described in Section 3 are applied, (2) *irrelevant:* a server shuffle process applied on top of the *single-turn-original* pipeline, (3) *single-turn-diversify:* a question diversification process applied on top of the *single-turn-original* pipeline, and (4) *multi-turn:* a multi-turn extension of the *single-turn-original* and *single-turn-diversify* subsets.

- **messages:** The trajectory formatted with the chat template from the original LLM-agent used for generation. The system prompt includes the associated list of tools.

- **question:** The user task crafted to generate the trajectory.

- **target_tools:** The MCP tools used as seeds for question generation.

- **question_quality_assessment:** Task evaluation by an LLM-as-judge, covering quality, difficulty, realism, and uniqueness.

- **response_quality_assessment:** Response evaluation by an LLM-as-judge, covering completeness and conciseness.

- **message_num_rounds:** Total number of messages, including turns of all types.

- **metadata:** Original MCP server data collected and used as seed for generation, as well as respective LLM annotations.

This is the structure of an instance in TOUCAN :

```
breaklines,
 breakanywhere]
{json}
    {
      "uuid": "3ac8fdcc-b9b5-50d2-a840
    -947a42b558d2",
      "subset": "single-turn-original",
      "messages": "[{...long JSON string
     of messages...}]",
```

```
    "question": "I'm reviewing my
company's policy document that needs
 quarterly updates for compliance
purposes. I need to first understand
 its current structure with all
sections and subsections, then
update every occurrence of 'Q3 2024'
 to 'Q1 2025' throughout the
document, and finally add
explanatory footnotes to the last 3
sections that reference our new
regulatory guidance document
published last month. Can you help
me accomplish these updates
systematically?",
    "target_tools": "
get_document_outline,
search_and_replace,
add_footnote_to_document",
    "
question_quality_assessment_kimik2w4a16
": {
    "tool_selection_difficulty": { "
reasoning": "...", "score": 3 },
    "tool_selection_uniqueness": { "
reasoning": "...", "score": 3 },
    "question_quality": { "reasoning
": "...", "score": 4 },
    "scenario_realism": { "reasoning
": "...", "score": 5 },
    "verifiable": { "reasoning":
"...", "score": 4 },
    "stability": { "reasoning":
"...", "score": 5 },
    "overall_score": 4.0
  },
  "
response_quality_assessment_oss120b":
 {
    "completeness": { "reasoning":
"...", "score": 2 },
    "conciseness": { "reasoning":
"...", "score": 3 },
    "overall_score": 2.5,
    "desired_tools_used_percentage":
 0.3333,
    "order_correctness": false
  },
  "messages_num_rounds": 9,
  "metadata": "{...long metadata
JSON string...}"
 }
```

Below, we present a TOUCAN trajectory, chat template tokens from the model generator and emojis have been removed, and some sections (e.g., tool list, tool output, assistant response) have been abbreviated to improve readability.

```
breaklines,
 breakanywhere]
{json}
[
  {
    "role": "system",
    "content": "{... contains the list
  of tools ... }"
  },
  {
```

```
      "role": "user",
      "content": "Can you explain what ENS
      (Ethereum Name Service) represents
      in the context of a transaction and
      why a name like 'blockscout.eth'
      might appear instead of a raw
      address?"
    },
    {
      "role": "assistant",
      "content": "I'll explain what ENS (
      Ethereum Name Service) represents,
      and show you how it resolves a name
      like 'blockscout.eth' into its
      actual Ethereum address."
    },
    {
      "role": "assistant",
      "content": "",
      "function_call": {
        "name": "blockscout-mcp-server-
      __unlock_blockchain_analysis__",
        "arguments": "{}"
      }
    },
    {
      "role": "function",
      "content": "{... long tool output
      ...}"
    },
    {
      "role": "assistant",
      "content": "Now, let me resolve '
      blockscout.eth' to show the actual
      address it represents."
    },
    {
      "role": "assistant",
      "content": "",
      "function_call": {
        "name": "blockscout-mcp-server-
      get_address_by_ens_name",
        "arguments": "{\"name\": \"
      blockscout.eth\"}"
      }
    },
    {
      "role": "function",
      "name": "blockscout-mcp-server-
      get_address_by_ens_name",
      "content": "{\n  \"data\": {\n    \"
      resolved_address\": \"0
      x441e1e47a6Fa2DBfD3cd9b54291E9AB3a58D7975
      \"\n  },\n  \"data_description\":
      null,\n  \"notes\": null,\n  \"
      instructions\": null,\n  \"
      pagination\": null\n}"
    },
    {
      "role": "assistant",
      "content": "{... parsed assistant
      response ...}"
    },
    {
      "role": "user",
      "content": "Based on that
      explanation, could you look up the
      ENS name 'blockscout.eth' and
      provide the Ethereum address it
      resolves to?"
```

```
    },
    {
      "role": "assistant",
      "content": "I already resolved that
      for you in my previous response!
      When I called the ENS lookup tool,
      \"blockscout.eth\"' resolved to the
      Ethereum address:\n\n'0
      x441e1e47a6Fa2DBfD3cd9b54291E9AB3a58D7975
      '"
    }
  ]
```

In the previous trajectory example, we abbreviated the assistant's parsed response for readability. The full response is shown below.

```
1 ## What ENS (Ethereum Name Service)
      Represents in Transactions
2
3 ENS stands for **Ethereum Name Service**,
      and it functions much like "DNS for
      Ethereum addresses." It allows
      users to register human-readable
      names (like "blockscout.eth") that
      map to complex hexadecimal
      blockchain addresses.
4
5 ### Key Points About ENS:
6
7 1. **Human-Readable Names for Complex
      Addresses**
8    - Instead of displaying '0
      x441e1e47a6Fa2DBfD3cd9b54291E9AB3a58D7975
      ' (which is the raw address for
      blockscout.eth), interfaces show the
      friendly "blockscout.eth"
9    - This reduces errors from copy/
      pasting long hex addresses
10
11 2. **Reverse Resolution**
12   - When you see "blockscout.eth" in
      transaction data, wallet labels, or
      block explorers, it means:
13     - ENS has been configured with this
      name
14     - The system has performed a
      reverse lookup to find the name
      associated with the address
15
16 3. **Self-Sovereign Identity**
17   - ENS names are owned and controlled
      by users through smart contracts
18   - They can be transferred, updated,
      or associated with additional
      metadata (social profiles, avatars,
      etc.)
19
20 ### Why "blockscout.eth" Appears Instead
      of Raw Address:
21
22 - **User Experience**: "blockscout.eth"
      is immediately recognizable and
      memorable
23 - **Trust Verification**: Users can
      verify they're interacting with the
      legitimate Blockscout entity rather
      than a random address
24 - **Branding**: Organizations use ENS
      names for consistent branding across
```

DeFi protocols and wallet interfaces
25 - **Error Prevention**: Reduces costly mistakes when users verify transaction recipients
26
27 Every time you see an ENS name like "blockscout.eth" in a transaction, the underlying system has actually resolved this to the precise blockchain address `0x441e1e47a6Fa2DBfD3cd9b54291E9AB3a58D7975`-the ENS simply provides a human-friendly layer on top of the raw cryptographic identity.

Below example demonstrated an error recovery of TOUCAN. In this example, the assistant attempts to invoke a math evaluation tool multiple times with incorrect function syntax (*exp*, *e*), receives execution errors from the tool, and then recovers by reformulating the expression using a numeric approximation of *e* to successfully complete the calculation.

```json
breaklines,
breakanywhere]
{json}
[
  {
    "role": "system",
    "content": "{... contains the list of tools ... }"
  },
  {
    "role": "user",
    "content": "Calculate the company's revenue in year\u202f5 using the exponential model Revenue\u202f=\u202f10,000\u202f\u00d7\u202fe^(0.15\u202f\u00d7\u202fyear). Show your work and give the numerical result."
  },
  {
    "role": "assistant",
    "content": "I'll calculate the company's revenue in year 5 using the exponential growth model you provided. Let me evaluate this expression."
  },
  {
    "role": "assistant",
    "content": "",
    "function_call": {
        "name": "expression-evaluation-server-eval",
        "arguments": "{\"expression\": \"10000 * exp(0.15 * 5)\"}"
    }
  },
  {
    "role": "function",
    "content": "handler returned an error: unknown name exp (1:9)\n | 10000 * exp(0.15 * 5)\n | ........^",
    "name": "expression-evaluation-server-eval"
  },
  {
    "role": "assistant",
    "content": "Let me try with the proper function name:"
  },
  {
    "role": "assistant",
    "content": "",
    "function_call": {
        "name": "expression-evaluation-server-eval",
        "arguments": "{\"expression\": \"10000 * e^(0.15 * 5)\"}"
    }
  },
  {
    "role": "function",
    "content": "handler returned an error: unknown name e (1:9)\n | 10000 * e^(0.15 * 5)\n | ........^",
    "name": "expression-evaluation-server-eval"
  },
  {
    "role": "assistant",
    "content": "Let me calculate this step by step, using the fact that e \u2248 2.718281828:"
  },
  {
    "role": "assistant",
    "content": "",
    "function_call": {
        "name": "expression-evaluation-server-eval",
        "arguments": "{\"expression\": \"10000 * 2.718281828^(0.15 * 5)\"}"
    }
  },
  {
    "role": "function",
    "content": "10000 * 2.718281828^(0.15 * 5) = 21170.00016344546",
    "name": "expression-evaluation-server-eval"
  },
  {
    "role": "assistant",
    "content": "## Solution\n\n**Given Model:** Revenue = 10,000 \u00d7 e^(0.15 \u00d7 year)\n\n**For Year 5:**\n1. **Calculate the exponent:** 0.15 \u00d7 5 = 0.75\n2. **Calculate e^0.75:** e^0.75 \u2248 2.117\n3. **Calculate final revenue:** 10,000 \u00d7 2.117 = **$21,170.00**\n\n**Numerical Result:** The company's revenue in year 5 is **$21,170** (rounded to the nearest dollar).\n\nNote: This represents approximately 111.7% growth over the starting revenue of $10,000, demonstrating the power of exponential growth at 15% per year compounded continuously."
  },
]
```

B More on Dataset Analysis

B.1 Featured Servers in TOUCAN

Table 3 demonstrates featured servers of TOUCAN. We note that these featured servers span a wide range of domains, making combinations possible for complex tool use tasks.

B.2 More on MCP Server Analysis in TOUCAN

Figure 11 shows the distribution of the most frequently used MCP servers in our dataset, highlighting the diversity of servers and domains covered in TOUCAN. Figure 10 shows the distribution of tool counts across the 495 MCP servers employed by TOUCAN , revealing that most servers expose only a limited number of tools, with the majority containing fewer than 10 tools.

Figure 10: Tools Number distribution across MCP servers

Figure 9: Pearson correlation between annotator and LLM-as-a-Judge evaluations across different models.

B.3 Emedding Visualization

Figure 12 presents embedding visualization via Embedding Atlas (Ren et al., 2025) using the `Xenova/multilingual-e5-small` embedding model with UMAP projection (McInnes and Healy, 2018). The visualization demonstrates that TOUCAN covers a wide range of topics. In addition, the proposed TOUCAN extensions (e.g., diversification) effectively increase the overall dataset coverage.

B.4 Domain Coverage Comparison between TOUCAN and MCP Universe

In what follows, we compare the MCP server names included in TOUCAN with those used for constructing MCP Universe. The results are summarized in Table 4. Our analysis shows that four MCP Universe domains are completely out-of-distribution (OOD) with respect to TOUCAN, indicating that our fine-tuned models demonstrate strong generalization performance on domains that were never seen during training.

C More on Experiments

C.1 LLM Annotation

Figure 9 shows the Pearson correlation between human annotations and LLM-as-a-judge evaluations across different models on 50 randomly sampled instances. We observe that `GPT-4.1` and `Kimi-K2` achieve the highest correlation with human judgments. Notably, the Pearson correlation between the two human annotators is only 0.5028, indicating moderate inter-annotator agreement, especially on inherently subjective aspects such as tool selection uniqueness and scenario realism. This suggests that the relatively low model-human correlation is partly due to annotation subjectivity rather than model unreliability. Considering cost efficiency and maintaining an end-to-end open-source pipeline, we deploy `Kimi-K2` locally as the annotator. Our annotation prompt is available in Appendix D.4.

C.2 Fine-Tuning Hyper-Parameters

We fine-tune models with TOUCAN using a super computing cluster, which is outfitted with NVIDIA H100 GPUs. The fine-tuning hyper-parameters can be found in Table 5.

Table 3: Featured Server Information

Server Name	Repository Name	Domain	Tools Count
OKX Server	esshka/okx-mcp	Cryptocurrency & Blockchain	2
AI Research Assistant - Semantic Scholar	Access via Smithery [2]	Web Search & Research	10
Book Search Server	Access via Smithery [3]	Web Search & Research	1
PubMed MCP Server	JackKuo666/PubMed-MCP-Server	Web Search & Research	4
Flux ImageGen Server	falahgs/flux-imagegen-mcp-server	AI/ML Tools	3
Pokémcp	NaveenBandarage/poke-mcp	Data Analysis & Processing	4
Hotel Booking Server	jinkoso/jinko-mcp	E-commerce	6
Cloudflare Playwright	cloudflare/playwright-mcp	Browser Automation	24
Time MCP Server	yokingma/time-mcp	Time & Calendar	6
Exa Search	exa-labs/exa-mcp-server	Web Search & Research	8
Weather Forecast Server	iremaltunay55/deneme	Weather	5
Advanced Calculator Server	alan5543/calculator-mcp	Data Analysis & Processing	17
Dictionary Server	ceydasimsekk/dictionarymcp	Others	1
Airbnb Search and Listing Details Server	AkekaratP/mcp-server-airbnb	Web Search & Research	2
Code Runner MCP Server	formulahendry/mcp-server-code-runner	Development Tools	1
Movie Recommender	iremert/movie-recommender-mcp	Content Creation	1
United States Weather	smithery-ai/mcp-servers	Weather	6
Context7	upstash/context7-mcp	Development Tools	2
Think Tool Server	PhillipRt/think-mcp-server	Memory Management	1
OpenAPI MCP Server	janwilmake/openapi-mcp-server	API Integration	2
Film Information Server	zehranurugurr/film_mcp	Content Creation	1
Trends Hub	baranwang/mcp-trends-hub	News & Media	21
ClinicalTrials MCP Server	JackKuo666/ClinicalTrials-MCP-Server	Health & Fitness	7
Drawing Tool for AI Assistants	flrngel/mcp-painter	Content Creation	4
LeetCode	jinzcdev/leetcode-mcp-server	Development Tools	9

Figure 11: Distribution of the most frequently occurring MCP servers in the TOUCAN dataset.

C.3 Ablation Studies on Data Extensions

To validate our extension designs, we perform ablation analysis on the Qwen2.5-14B-Instruct model, where we fine-tune on progressively extended versions of TOUCAN, allowing us to isolate the contributions of each extension described in Section 3.2. The experimental results are shown in Table 6. We observe that all components contribute to improved scores.

C.4 Ablation Studies on Tool Scaling

In this experiment, we create five subsets of TOUCAN datasets, each doubling the number of tools relative to the previous one. The number of tools preserved in the dataset ranges from

Figure 12: This figure is the visualization of 50K random-sampled TOUCAN instances via Embedding Atlas (Ren et al., 2025).

Table 4: In-distribution (ID) and out-of-distribution (OOD) domain coverage of TOUCAN relative to MCP Universe.

Benchmark	Benchmark Domain	TOUCAN
MCP Universe	Location Navigation	OOD
	Repository Management	OOD
	Financial Analysis	ID
	3D Design	OOD
	Browser Automation	ID
	Web Searching	OOD

Table 5: This table shows the hyper-parameters for supervised fine-tuning.

Hyper-parameter	Value
Tool-Call Template	Hermes
Learning Rate	2×10^{-5}
Number of Epochs	2
Number of Devices	8 or 64
Per-device Batch Size	1
Gradient Accumulation Steps	8 (8 GPUs) or 1 (64 GPUs)
Effective Batch Size	64
Optimizer	Adamw
Deepspeed	zero3
Max Sequence Length	32768

100 to 1,600, while the total number of trajectories is kept constant at 20,000. We fine tuned `Qwen2.5-32B-Instruct` on these subsets, and evaluate the resulting models on BFCL V3 and τ-Bench. Table 7 shows the results of this experiment. We observe a consistent upward trend in overall performance as tool diversity increases, indicating that a larger and more diverse tool set leads to better generalization rather than redundant learning.

C.5 Ablation Studies on Large Datasets

We conduct an ablation experiment to investigate the relevance of TOUCAN 's large size for the research community. Specifically, we cre-

ated two training datasets: TOUCAN -Full (including 1.5M trajectories), and TOUCAN -SFT (as detailed in Section 4.1). We fine-tuned `Qwen2.5-14B-Instruct` with each training dataset. Table 8 shows the evaluation results for BFCL V3. Overall, TOUCAN -Full slightly outperforms the SFT subset, and shows a remarkable improvement in the multi-turn setting. Our results also show that the model fine-tuned on the full dataset achieves a lower score on the Irrelevance setting, which suggests that the carefully rebalanced TOUCAN -SFT is more effective at reducing

Table 6: Ablation of TOUCAN Extensions on BFCL V3 Benchmark.

	Overall	Single Turn		Multi Turn	Hallucination	
		Non-live (AST)	*Live (AST)*		*Relevance*	*Irrelevance*
Qwen2.5-14B-Instruct	57.69	83.38%	73.70%	19.75%	83.33%	68.46%
+ Single Turn	60.16%	87.50%	66.86%	34.38%	72.22%	46.88%
+ Irrelevance	64.74%	88.46%	77.25%	30.38%	72.22%	77.85%
+ Diversify	64.56%	86.06%	76.90%	32.50%	72.22%	75.45%
+ Multi-Turn	65.09%	85.42%	76.01%	35.25%	72.22%	75.96%

Table 7: Ablation on Tool Diversity on BFCL V3 and τ-Bench.

	BFCL-V3						τ-Bench	
Model Variant	Overall	Single Turn		Multi Turn	Hallucination		Airline @1	Retail @1
		Non-live (AST)	*Live (AST)*		*Relevance*	*Irrelevance*		
Qwen2.5-32B-Instruct-Toucan-100Tools-20K	60.38%	87.58%	64.82%	36.00%	**88.89**%	46.66%	28.50%	47.39%
Qwen2.5-32B-Instruct-Toucan-200Tools-20K	60.90%	86.56%	65.44%	37.00%	**88.89**%	49.50%	27.50%	50.43%
Qwen2.5-32B-Instruct-Toucan-400Tools-20K	61.99%	87.48%	65.08%	40.00%	83.33%	49.00%	28.50%	48.48%
Qwen2.5-32B-Instruct-Toucan-800Tools-20K	61.73%	**87.31**%	64.73%	**40.38**%	83.33%	45.98%	29.25%	50.54%
Qwen2.5-32B-Instruct-Toucan-1600Tools-20K	**62.26%**	86.27%	**67.57%**	39.38%	83.33%	**52.08%**	**29.75%**	**52.06%**

hallucinations.

C.6 Ablation Studies on Data Scaling

We perform a data-scale ablation by randomly sampling subsets of 20K, 40K, 60K, 80K, and 100K trajectories from TOUCAN-SFT (see Section 4.1). We then fine-tune Qwen2.5-32B-Instruct on each subset and compare the results against training on the full dataset. We evaluated the results on the BFCL-V3 benchmark. Table 9 shows the results of this experiment. Overall, the models show a consistent performance gain as the data scale increases, with especially strong improvements in the multi-turn setting. We also observe diminishing returns and near-saturation beyond approximately 80K trajectories. This behavior mirrors common scaling trends in instruction tuning and suggests that our rebalanced subset already provides an effective cost-performance sweet spot.

C.7 Ablation Studies with Comparable Tool-calling Dataset

We perform a controlled experiment to compare TOUCAN with Nemotron-SFT (tool subset) under a similar data scale (see Table 16) and using the same model, Qwen2.5-14B-Instruct, as baseline. While the overall score of Nemotron-SFT achieves a comparable performance to TOUCAN on BFCL V3, our dataset shows substantially stronger performance on other tool-agentic benchmarks, especially τ-Bench and τ^2-bench. These benchmarks better reflect multi-tool reasoning and cross-domain generalization. Table 10 and Table 11 respectively report the results obtained.

C.8 Controlled Comparisons under Matched Training Budgets

To further isolate the contribution of data quality from data scale, we conducted additional controlled comparisons against ToolACE (Liu et al., 2025a) and Hermes Function-Calling (interstellarninja) under matched training budgets using Qwen2.5-14B-Instruct as the base model. We matched TOUCAN against ToolACE at 11K samples and against Hermes Function-Calling at 7K samples, with identical learning rate and epoch settings. As reported in Table 12, TOUCAN consistently outperforms both baselines in overall BFCL score at matched scale. The most pronounced advantage lies in multi-turn performance, where TOUCAN (11K) achieves 34.50% versus ToolACE's 14.37%, and TOUCAN (7K) achieves 30.37% versus Hermes's 7.50%. This confirms that the gains from TOUCAN stem primarily from data quality and composition—particularly the multi-turn agentic trajectories generated via real MCP execution—rather than from scale alone.

C.9 Ablation on the Importance of Trajectory Annotation and Filtering

We conducted an ablation study comparing datasets with and without the filtering step (Stage 5) of our generation pipeline. We report results in Table 13. We observed that the overall performance on BFCL V3, as well as the multi-turn and irrelevance setting benefit from filtering, which confirms the value of including an automated process to filter-out low-quality samples in data generation pipelines.

Table 8: BFCL-V3 Results for TOUCAN Full and SFT datasets.

| Dataset | Overall | Single Turn | | Multi Turn | Hallucination | |
		Non-live (AST)	Live (AST)		Relevance	Irrelevance
Qwen2.5-14B-Instruct	57.69%	83.38%	73.70%	19.75%	83.33%	68.46%
with Toucan-SFT	**65.09%**	**85.42%**	**76.01%**	35.25%	72.22%	**75.96%**
with Toucan-Full	**65.17%**	84.90%	74.63%	**39.13%**	**83.33%**	68.71%

Table 9: Ablation on SFT Data Scale on BFCL V3 and τ-Bench.

| | BFCL-V3 | | | | | | τ-Bench | |
| Model Variant | Overall | Single Turn | | Multi Turn | Hallucination | | | |
		Non-live (AST)	Live (AST)		Relevance	Irrelevance	Airline @1	Retail @1
Qwen2.5-32B-Instruct	61.73%	85.58%	76.01%	26.38%	72.22%	72.68%	26.00%	51.52%
Toucan-SFT-20K	68.21%	88.52%	74.99%	42.50%	83.33%	74.73%	27.75%	47.50%
Toucan-SFT-40K	68.82%	86.77%	77.30%	43.50%	77.78%	76.62%	28.50%	53.37%
Toucan-SFT-60K	68.55%	86.71%	77.08%	43.12%	83.33%	75.87%	28.25%	56.30%
Toucan-SFT-80K	69.62%	87.02%	77.65%	45.25%	77.78%	77.23%	30.00%	58.26%
Toucan-SFT-100K	69.83%	86.44%	78.76%	45.25%	77.78%	77.91%	28.00%	56.66%
Toucan-SFT-119K	**70.45%**	**87.12%**	**78.90%**	**46.50%**	77.78%	**78.10%**	29.00%	55.65%

Table 10: Comparison between Nemotron-SFT (tool subset) and TOUCAN on BFCL-V3.

| Model | Overall | Single Turn | | Multi Turn | Hallucination | |
		Non-live (AST)	Live (AST)		Relevance	Irrelevance
Qwen2.5-14B *with* TOUCAN	65.09%	85.42%	76.01%	35.25%	72.22%	75.96%
Qwen2.5-14B *with* Nemotron-SFT(tools)	65.64%	85.02%	81.83%	30.00%	66.67%	85.45%

Table 11: Comparison between Nemotron-SFT (tool subset) and TOUCAN on τ- and τ^2-Bench.

| Model | τ-bench | | | τ^2-bench | | | |
	Avg.	Airline	Retail	Avg.	Airline	Retail	Telecom
Qwen2.5-14B *with* TOUCAN	35.24%	22.00%	48.48%	30.43%	22.00%	49.10%	20.18%
Qwen2.5-14B *with* Nemotron-SFT(tools)	24.38%	18.00%	30.76%	20.23%	16.00%	36.80%	7.90%

Table 12: Comparison between TOUCAN and prior datasets (ToolACE, Hermes Function-Calling) on BFCL-V3 under matched training budgets.

| Model | Overall | Single Turn | | Multi Turn | Hallucination | | |
		Non-live (AST)	Live (AST)		Relevance	Irrelevance	
Qwen2.5-14B-Instruct (baseline)	57.69%	83.38%	73.70%	19.75%	83.33%	68.46%	
Qwen2.5-14B *with* TOUCAN (11K)	65.33%	86.23%	76.41%	34.50%	72.22%	77.51%	*
Qwen2.5-14B *with* ToolACE (11K)	60.08%	87.96%	76.99%	14.37%	61.11%	87.18%	
Qwen2.5-14B *with* TOUCAN (7K)	63.51%	85.77%	75.70%	30.37%	72.22%	76.83%	
Qwen2.5-14B *with* Hermes FC (7K)	48.11%	87.94%	60.06%	7.50%	88.89%	34.18%	

Table 13: Ablation on Stage 5 on BFCL-V3 Benchmark.

| Model | Overall | Single Turn | | Multi Turn | Hallucination | |
		Non-live (AST)	Live (AST)		Relevance	Irrelevance
Qwen2.5-14B-Instruct (FC)	57.69%	83.38%	73.70%	19.75%	83.33%	68.46%
TOUCAN *without* Filtering (4 stages)	62.60%	**86.83%**	72.01%	32.25%	77.78%	67.01%
TOUCAN *with* Filtering (5 stages)	**65.09%**	85.42%	**76.01%**	**35.25%**	72.22%	**75.96%**

Table 14: Ablation on data mixture proportions. Mix1, Mix2, and Mix3 contain 10K, 20K, and 40K multi-turn samples respectively, with all other categories scaled proportionally to maintain the same relative composition.

Model	Overall	Single Turn		Multi Turn	Hallucination	
		Non-live (AST)	*Live (AST)*		*Relevance*	*Irrelevance*
Qwen2.5-7B-Instruct (baseline)	—	84.19%	72.32%	12.88%	72.22%	67.93%
Qwen2.5-7B *with* TOUCAN Mix1 (10K MT)	57.35%	80.00%	74.59%	19.12%	72.22%	72.85%
Qwen2.5-7B *with* TOUCAN Mix2 (20K MT)	58.56%	80.23%	74.68%	22.00%	72.22%	74.90%
Qwen2.5-7B *with* TOUCAN Mix3 (40K MT)	59.33%	79.27%	75.08%	24.50%	77.78%	74.69%

C.10 Ablation on Data Mixture Proportions

We vary the proportion of multi-turn data across three mixtures containing 10K, 20K, and 40K multi-turn samples, with other categories scaled proportionally. As shown in Table 14, increasing multi-turn data consistently improves multi-turn performance with modest gains in overall score. Across all mixtures, TOUCAN yields substantial gains over the base model, indicating that improvements are robust to mixture choice rather than tied to a specific configuration.

D Prompts

D.1 MCP Server Annotation Prompt

Below is the prompt for annotating MCP server categories.

```
1  ## Task
2  Generate **Server Labels** to categorize
      the provided MCP Server based on
      its description and available tools.
3
4  ## Objective
5  Analyze the provided MCP Server's
      description and available tools,
      then assign appropriate category
      labels that best describe its
      primary functionality and use cases.
6
7  ## Guidelines
8
9  ### Label Selection
10 - Analyze the MCP Server's core
      functionality and purpose
11 - Consider the types of tools it
      provides and the problems it solves
12 - Select labels that accurately
      represent the server's primary use
      cases
13 - Choose from predefined categories when
       applicable, but also consider
      custom labels for unique
      functionality
14
15 ### Predefined Categories
16 Choose from these established categories
       when appropriate:
17 - **Web Search & Research**: Tools for
      searching the web, gathering
      information, academic research
18 - **Browser Automation**: Web scraping,
      automated browsing, page interaction
19 - **Memory Management**: Data storage,
      retrieval, knowledge bases, note-
      taking
20 - **Operating System**: File operations,
       system commands, process management
21 - **Data Analysis & Processing**:
      Analytics, data transformation,
      statistical analysis
22 - **Cryptocurrency & Blockchain**:
      Trading, wallet management, DeFi,
      blockchain interaction
23 - **Daily Productivity**: Task
      management, scheduling, personal
      organization
24 - **File Management**: File operations,
      document handling, storage
      management
25 - **Database Operations**: Data querying,
       database management, SQL operations
26 - **API Integration**: Third-party
      service integration, webhook
      handling
27 - **Communication Tools**: Messaging,
      email, notifications, social
      interaction
28 - **Development Tools**: Code analysis,
      debugging, version control, CI/CD
29 - **Security & Authentication**:
      Password management, encryption,
      access control
30 - **Cloud Services**: Cloud platform
      integration, serverless functions
31 - **AI/ML Tools**: Machine learning,
      model interaction, AI-powered
      features
32 - **Content Creation**: Writing, editing,
       media generation, publishing
33 - **Social Media**: Social platform
      integration, posting, analytics
34 - **Financial Services**: Banking,
      payments, financial data, accounting
35 - **E-commerce**: Shopping, product
      management, order processing
36 - **Gaming**: Game-related tools,
      entertainment, interactive features
37 - **Education**: Learning tools, course
      management, educational content
38 - **Health & Fitness**: Health
      monitoring, fitness tracking,
      medical tools
39 - **Travel & Maps**: Location services,
      travel planning, navigation
40 - **News & Media**: News aggregation,
      media consumption, journalism tools
```

1398 41 - **Weather**: Weather data, forecasting, climate information
1399
1400 42 - **Time & Calendar**: Scheduling, time management, calendar integration
1401
1402 43
1403 44 ### Custom Labels
1404 45 - If the server doesn't fit well into predefined categories, create a custom label
1405
1406
1407 46 - Custom labels should be descriptive and specific to the server's unique functionality
1408
1409
1410 47 - Use clear, concise terminology that would be useful for clustering and organization
1411
1412
1413 48
1414 49 ### Output Requirements
1415 50 - **Primary Label**: The main category that best describes the server (from predefined list or custom)
1416
1417
1418 51 - **Secondary Labels**: Additional relevant categories (0-2 labels)
1419
1420 52 - **Custom Label**: A free-form descriptive label if the server has unique functionality not covered by predefined categories
1421
1422
1423
1424
1425 53
1426 54 ## MCP Server Description
1427 55 {MCP_SERVER_NAME}: { MCP_SERVER_DESCRIPTION}

1428 56
1429 57 Available Tools:
1430 58 {TOOL_LIST}
1431 59
1432 60 ## Output
1433 61 Provide your response in the following XML format:
1434
1435 62
1436 63 <response>
1437 64   <analysis>
1438 65   <!-- Briefly analyze the MCP Server'
1439   s core functionality and the types
1440   of problems it solves based on its
1441   description and available tools. -->
1442 66   </analysis>
1443 67   <reasoning>
1444 68   <!-- Brief explanation of why these
1445   labels were chosen and how they
1446   represent the server's functionality
1447   -->
1448 69   </reasoning>
1449 70   <primary_label>
1450 71   <!-- The main category that best
1451   describes this server's primary
1452   functionality -->
1453 72   </primary_label>
1454 73   <secondary_labels>
1455 74   <!-- Additional relevant categories
1456   (0-2 labels), separated by commas if
1457   multiple -->
1458 75   </secondary_labels>
1459 76   <custom_label>
1460 77   <!-- A free-form descriptive label
1461   if the server has unique
1462   functionality not covered by
1463   predefined categories. Leave empty
1464   if not needed. -->
1465 78   </custom_label>
1466 79 </response>

D.2   Task Generation Prompt

Below is an example of a task generation prompt for the single-server task synthesis. The prompt generates a question targeting **one tool**.

1 ## Task
2 Generate a **Tool Use Question** based on the provided MCP Server and its tool descriptions.
3
4 ## Objective
5 Analyze the provided MCP Server and its available tools, then create a realistic user question that would naturally require the use of one of these tools to solve.
6
7 ## Guidelines
8
9 ### Question Realism
10 - Create questions that represent real-world scenarios where users would need to interact with the MCP Server's tools
11 - The question should sound natural and authentic, as if asked by someone genuinely needing to accomplish a task
12 - Consider common use cases, problems, or workflows that would require the functionality provided by the MCP Server's tools
13
14 ### Tool Selection
15 - Focus on **ONE specific tool** from the MCP Server that would be most appropriate to answer the question
16 - Choose tools based on the core functionality they provide and how they would solve real user problems
17 - Consider each tool's description and purpose when crafting the question
18
19 ### Question Complexity
20 - Create questions that are clear and specific enough to warrant tool usage
21 - Avoid overly simple questions that could be answered without tools
22 - Include relevant context or constraints that make the tool usage necessary
23 - Do not contain the exact tool name in the question
24
25 ### Output Format
26 Your response should include:
27 1. **Tool Analysis**: Briefly analyze the MCP Server's available tools and their main functionalities.
28 2. **Target Tool**: The specific tool name from the MCP Server that should be used to answer this question.
29 3. **Question**: A clear, realistic user question that requires tool usage.
30
31 ## MCP Server Description
32 {MCP_SERVER_NAME}: { MCP_SERVER_DESCRIPTION}

```
34 Available Tools:
35 {TOOL_LIST}
36
37 ## Output
38 Provide your response in the following
       XML format:
39
40 <response>
41   <server_analysis>
42     <!-- Briefly analyze the MCP Server'
       s available tools and their main
       functionalities. -->
43   </server_analysis>
44   <target_tool>
45     <!-- The specific tool name from the
        MCP Server that should be used to
       answer this question. -->
46   </target_tool>
47   <question>
48     <!-- A clear, realistic user
       question that requires tool usage.
       -->
49   </question>
50 </response>
```

Below is an example of a task generation prompt for the single-server task synthesis. The prompt generates a question targeting **multiple tools**.

```
1 ## Task
2 Generate a **Tool Use Question** based
     on the provided MCP Server and its
     tool descriptions.
3
4 ## Objective
5 Analyze the provided MCP Server and its
     available tools, then create a
     realistic user question that would
     naturally require the use of **{
     NUM_TOOLS} tools** from this MCP
     Server to solve completely.
6
7 ## Guidelines
8
9 ### Question Realism
10 - Create questions that represent real-
      world scenarios where users would
      need to interact with the MCP Server'
      s tools
11 - The question should sound natural and
      authentic, as if asked by someone
      genuinely needing to accomplish a
      task
12 - Consider common use cases, problems,
      or workflows that would require the
      functionality provided by the MCP
      Server's tools
13
14 ### Tool Selection
15 - Focus on **{NUM_TOOLS} tools** from
      the MCP Server that would work
      together to answer the question
16 - The question should require a sequence
       or combination of tool calls to
      solve completely
17 - Choose tools based on how they
      complement each other and create a
      logical workflow
18 - Consider each tool's description and
      purpose when crafting the question
      that requires multiple steps
19
20 ### Question Complexity
21 - Create questions that are complex
      enough to warrant using {NUM_TOOLS}
      tools
22 - The question should have multiple
      components or require several steps
      to solve
23 - Include relevant context or
      constraints that make the multi-tool
      usage necessary
24 - Do not contain the exact tool names in
       the question
25 - Ensure the question cannot be
      reasonably answered with just a
      single tool
26
27 ### Output Format
28 Your response should include:
29 1. **Tool Analysis**: Briefly analyze
      the MCP Server's available tools and
      their main functionalities.
30 2. **Target Tools**: The specific tool
      names from the MCP Server that
      should be used together to answer
      this question, in the order they
      would likely be called.
31 3. **Question**: A clear, realistic user
      question that requires multiple
      tool usage.
32
33 ## MCP Server Description
34 {MCP_SERVER_NAME}: {
      MCP_SERVER_DESCRIPTION}
35
36 Available Tools:
37 {TOOL_LIST}
38
39 ## Output
40 Ensure your question requires exactly {
      NUM_TOOLS} tools to solve completely.
       Provide your response in the
      following XML format:
41
42 <response>
43   <server_analysis>
44     <!-- Briefly analyze the MCP Server'
      s available tools and their main
      functionalities. -->
45   </server_analysis>
46   <target_tools>
47     <!-- The specific tool names from
      the MCP Server that should be used
      together to answer this question,
      listed in order. e.g., <tool>
      create_twitter_post</tool> <tool>
      get_last_tweet</tool> -->
48   </target_tools>
49   <question>
50     <!-- A clear, realistic user
      question that requires multiple tool
       usage. -->
51   </question>
52 </response>
```

Below is an example of a task generation prompt for the multi-server task synthesis.

Task

Generate a **Multi-Server Tool Use Question** based on the provided MCP Servers and their tool descriptions.

Objective

Analyze the provided MCP Servers and their available tools, then create a realistic user question that would naturally require the use of **{NUM_TOOLS} tools from at least 2 different MCP servers** to solve completely.

Guidelines

Question Realism

- Create questions that represent real-world scenarios where users would need to interact with tools from multiple MCP Servers
- The question should sound natural and authentic, as if asked by someone genuinely needing to accomplish a complex task
- Consider workflows that span across different services/domains that would require multiple servers
- Think about how different MCP servers complement each other in real-world use cases

Server and Tool Selection

- Use tools from **at least 2 different MCP servers** to answer the question
- Select **{NUM_TOOLS} tools total** that work together across multiple servers
- The question should require a sequence or combination of tool calls from different servers to solve completely
- Choose tools based on how they complement each other across different services/domains
- Consider each tool's description and purpose when crafting the cross-server workflow
- Ensure tools from different servers create a logical, interconnected workflow

Question Complexity

- Create questions that are complex enough to warrant using {NUM_TOOLS} tools across multiple servers
- The question should have multiple components or require several steps that span different services
- Include relevant context or constraints that make the multi-server tool usage necessary
- Do not contain the exact tool names or server names in the question
- Ensure the question cannot be reasonably answered with tools from just a single server
- Create scenarios that naturally require different types of services working together

Cross-Server Integration

- Think about how different servers' capabilities can be combined
- Consider data flow between different services (e.g., retrieving data from one service to use in another)
- Create realistic scenarios where multiple services need to work together
- Focus on complementary functionalities across different domains

Output Format

Your response should include:
1. **Server Analysis**: Briefly analyze all MCP Servers and their available tools, focusing on how they can work together.
2. **Cross-Server Workflow**: Describe the workflow showing how tools from different servers will be used together.
3. **Target Tools**: The specific tool names from different MCP Servers that should be used together, in the order they would likely be called, with their server names.
4. **Question**: A clear, realistic user question that requires multi-server tool usage.

Available MCP Servers

{SERVER_DESCRIPTIONS}

Output

Ensure your question requires exactly {NUM_TOOLS} tools from at least 2 different servers to solve completely. Provide your response in the following XML format:

```
<response>
  <server_analysis>
    <!-- Briefly analyze all MCP Servers
    and their available tools, focusing
    on how they can work together
    across different domains/services.
    -->
  </server_analysis>
  <cross_server_workflow>
    <!-- Describe the workflow showing
    how tools from different servers
    will be used together to solve the
    question. -->
  </cross_server_workflow>
  <target_tools>
    <!-- The specific tool names from
    different MCP Servers that should be
    used together, listed in order with
    their server names. e.g., <tool
    server="Server1">search_posts</tool>
    <tool server="Server2">send_email</
    tool> -->
  </target_tools>
  <question>
    <!-- A clear, realistic user
    question that requires multi-server
```

```
            tool usage spanning different
            services/domains. -->
63      </question>
64 </response>
```

Below is an example of a task generation prompt for the task synthesis for featured servers.

```
1  ## Task
2  Generate a **Multi-Server Tool Use
       Question** based on featured MCP
       Servers and their tool descriptions.
3
4  ## Objective
5  Brainstorm a compelling real-world
       scenario, then analyze the provided
       featured MCP Servers and their
       available tools to create a
       realistic user question that would
       naturally require the use of **{
       NUM_TOOLS} tools from at least 2
       different MCP servers** to solve
       completely.
6
7  ## Guidelines
8
9  ### Scenario Brainstorming
10 - Think of realistic, specific scenarios
        where someone would need to use {
       NUM_TOOLS} different tools across
       multiple servers to accomplish a
       meaningful task
11 - Consider diverse real-world contexts
       such as:
12    - Content creators managing their
       online presence across different
       platforms
13    - Researchers gathering and analyzing
       information from multiple sources
14    - Developers building and deploying
       applications using different
       services
15    - Business professionals managing
       projects and communications across
       platforms
16    - Students working on complex
       assignments requiring multiple tools
17    - Entrepreneurs launching new ventures
        using various services
18 - The scenario should be detailed and
       authentic, representing genuine use
       cases that span multiple services
19
20 ### Question Realism
21 - Create questions that represent real-
       world scenarios where users would
       genuinely need tools from multiple
       MCP servers
22 - The question should sound natural and
       authentic, as if asked by someone
       with a specific goal
23 - Include relevant context, constraints,
        and details that make the question
       engaging
24 - Consider workflows that require
       multiple complementary tools working
        together across different services
25 - Think about how different servers
       support each other in real-world use
        cases
```

```
26
27 ### Server and Tool Selection
28 - Use tools from **at least 2 different
       MCP servers** to answer the question
29 - Select **{NUM_TOOLS} tools total**
       that work together across multiple
       servers
30 - The question should require a sequence
        or combination of tool calls from
       different servers to solve
       completely
31 - Choose tools based on how they
       complement each other across
       different services/domains
32 - Consider each tool's description and
       purpose when crafting the cross-
       server workflow
33 - Ensure tools from different servers
       create a logical, interconnected
       workflow
34
35 ### Question Complexity
36 - Create questions that are complex
       enough to warrant using {NUM_TOOLS}
       tools across multiple servers
37 - The question should have multiple
       components or require several steps
       that span different services
38 - Include relevant context or
       constraints that make the multi-
       server tool usage necessary
39 - Do not contain the exact tool names or
        server names in the question
40 - Ensure the question cannot be
       reasonably answered with tools from
       just a single server
41 - Create scenarios that naturally
       require different types of services
       working together
42
43 ### Cross-Server Integration
44 - Think about how different servers'
       capabilities can be combined
45 - Consider data flow between different
       services (e.g., retrieving data from
        one service to use in another)
46 - Create realistic scenarios where
       multiple services need to work
       together
47 - Focus on complementary functionalities
        across different domains
48
49 ### Output Format
50 Your response should include:
51 1. **Server Analysis**: Briefly analyze
       the featured MCP Servers and their
       available tools, focusing on how
       they can work together.
52 2. **Cross-Server Workflow**: Describe
       the workflow showing how tools from
       different servers will be used
       together.
53 3. **Target Tools**: The specific tool
       names from different MCP Servers
       that should be used together, in the
        order they would likely be called,
       with their server names.
54 4. **Question**: A clear, realistic user
        question that requires multi-server
        tool usage.
```

```
55
56 ## Available Featured MCP Servers
57
58 {FEATURED_SERVER_DESCRIPTIONS}
59
60 ## Output
61 Ensure your question requires exactly {
       NUM_TOOLS} tools from at least 2
       different servers to solve
       completely. Provide your response in
        the following XML format:
62
63 <response>
64   <server_analysis>
65     <!-- Briefly analyze the featured
       MCP Servers and their available
       tools, focusing on how they can work
        together across different domains/
       services. -->
66   </server_analysis>
67   <cross_server_workflow>
68     <!-- Describe the workflow showing
       how tools from different servers
       will be used together to solve the
       question. -->
69   </cross_server_workflow>
70   <target_tools>
71     <!-- The specific tool names from
       different MCP Servers that should be
        used together, listed in order with
        their server names. e.g., <tool
       server="Server1">search_posts</tool>
        <tool server="Server2">send_email</
       tool> -->
72   </target_tools>
73   <question>
74     <!-- A clear, realistic user
       question that requires multi-server
       tool usage spanning different
       services/domains. -->
75   </question>
76 </response>
```

D.3 Task Diversification Prompt

The following prompt aims to add diversity to the given task by introducing new contexts and personas.

```
1 ## Task
2 Generate **augmented variations** of a
       given question that maintain the
       same target tool(s) usage and
       complexity level but apply them
       across different contexts and
       scenarios.
3
4 ## Objective
5 Take an existing question and its
       associated target tool(s), then
       create multiple variations that:
6 - Use the same target tool(s) to achieve
        the core goal
7 - Maintain the exact same tool usage
       order and final outcome
8 - Apply the question to completely
       different contexts, scenarios, or
       domains
9 - Keep the same level of complexity and
       constraints as the original
10 - Demonstrate how the same tool usage
       pattern applies across diverse real-
       world scenarios
11
12 ## Guidelines
13 - Translate the question to distinctly
       different domains, user personas, or
        situational contexts while
       preserving its original complexity
       level.
14 - Keep the tool usage sequence and final
        outcome identical across all
       variations.
15 - Ensure each variation feels like a
       realistic scenario in its new
       context and remains solvable with
       the same tool operations.
16 - Ensure the question does not contain
       any tool names or explicit
       references to the target tools.
17
18 ## Input Format
19 **Original Question**: {
       ORIGINAL_QUESTION}
20 **Target Tools**: {TARGET_TOOLS}
21 **Tool Descriptions**: {
       TOOL_DESCRIPTIONS}
22
23 ## Output Requirements
24 Generate **{VARIATIONS_COUNT} augmented
       variations** of the original
       question. Each variation should:
25 1. Maintain the same core goal that
       requires the target tool(s)
26 2. Use the exact same tool(s) in the
       same order with the same final
       outcome
27 3. Apply to a completely different
       context, scenario, or domain
28 4. Keep the same complexity level and
       constraints as the original
29 5. Feel like a natural, real-world
       scenario from a different setting
30 6. Be meaningfully different from the
       original and other variations in
       terms of context only
31 7. Avoid including any explicit mentions,
        hints, or references to the target
       tool names within the question text
32
33 ## Output
34 Provide your response in the following
       XML format:
35
36 <response>
37   <analysis>
38     <!-- Briefly analyze the original
       question and target tool(s) to
       understand the core goal, tool usage
        pattern, complexity level, and
       expected outcome, then identify how
       this can be applied across different
       domains while maintaining
       operational consistency -->
39   </analysis>
40   <variations>
41     <!-- Generate {VARIATIONS_COUNT}
       variations, each with <variation_X>,
```

```
          <context>, and <question> tags -->
42      <variation_1>
43        <context>
44          <!-- Brief description of the
            new domain/scenario introduced -->
45        </context>
46        <question>
47          <!-- The augmented question that
            maintains the same target tool(s)
            usage order, complexity, and outcome
            but in a different context -->
48        </question>
49      </variation_1>
50      <!-- Continue with variation_2,
          variation_3, etc. as needed based on
          number of variations -->
51    </variations>
52  </response>
```

The prompt below is designed to enhance task complexity through the introduction of additional constraints.

```
1  ## Task
2  Generate **augmented variations** of a
     given question that maintain the
     same target tool(s) usage and
     context but significantly increase
     the complexity and constraints
     required to solve the problem.
3
4  ## Objective
5  Take an existing question and its
     associated target tool(s), then
     create multiple sophisticated
     variations that:
6  - Use the same target tool(s) to achieve
     the core goal while navigating
     additional complexity layers
7  - Maintain the same general context and
     domain as the original question
8  - Increase multi-dimensional complexity
     through realistic constraints,
     competing requirements, stakeholder
     considerations, and interconnected
     dependencies
9  - Embed the tool usage within larger,
     more complex workflows that require
     strategic thinking and coordination
10 - Demonstrate how the same core tool
     usage applies under vastly different
     complexity levels
11
12 ## Guidelines
13 - Introduce realistic constraints such
     as resource limits, compliance
     requirements, tight timelines, or
     stakeholder conflicts
14 - Embed the same tool usage inside a
     broader workflow that requires
     coordination across teams or systems
15 - Escalate demands (performance,
     scalability, risk management)
     without changing the original domain
     or context
16 - Ensure each variation targets a
     different primary complexity angle (
     organizational, technical, strategic)
     while preserving tool relevance
17 - Ensure the question does not contain
```

```
     any tool names or explicit
     references to the target tools.
18
19 ## Input Format
20 **Original Question**: {
     ORIGINAL_QUESTION}
21 **Target Tools**: {TARGET_TOOLS}
22 **Tool Descriptions**: {
     TOOL_DESCRIPTIONS}
23
24 ## Output Requirements
25 Generate **{VARIATIONS_COUNT}
     strategically augmented variations**
     of the original question. Each
     variation should:
26 1. Maintain the same core goal that
     requires the target tool(s) while
     adding multiple complexity layers
27 2. Keep the same general context and
     domain as the original question
28 3. Introduce different but
     interconnected constraints and
     competing requirements
29 4. Feel like natural, high-stakes, real-
     world scenarios that professionals
     encounter
30 5. Be meaningfully different from the
     original and other variations in
     terms of complexity
31 6. Include specific details that make
     the constraints and requirements
     concrete and actionable
32 7. **Transform step-wise questions**: If
     the original question contains
     explicit steps, convert it to a goal-
     oriented format while maintaining
     the same tool usage requirements
33 8. Avoid including any explicit mentions,
     hints, or references to the target
     tool names within the question text
34
35 ## Output
36 Provide your response in the following
     XML format:
37
38 <response>
39   <analysis>
40     <!-- Analyze the original question
        and target tool(s) to understand the
        core goal, current complexity level,
        and identify multiple complexity
        dimensions that can be naturally
        introduced while maintaining tool
        relevance and solution feasibility
        -->
41   </analysis>
42   <variations>
43     <!-- Generate {VARIATIONS_COUNT}
        variations, each with <variation_X>,
        <constraints>, and <question> tags
        -->
44     <variation_1>
45       <constraints>
46         <!-- Specific organizational,
          stakeholder, or coordination
          constraints that add realistic
          complexity -->
47       </constraints>
48       <question>
49         <!-- The complex,
```

```
           organizationally-focused question
           that maintains the same target tool(
           s) usage within a more sophisticated
            workflow -->
50          </question>
51       </variation_1>
52       <!-- Continue with variation_2,
         variation_3, etc. as needed based on
         number of variations -->
53     </variations>
54 </response>
```

D.4   Task Quality Annotation Prompt

```
1  ## Task
2  Conduct a **Question Quality Assessment
   ** of a tool use question across six
   key dimensions to ensure it meets
   high standards for realistic tool
   usage scenarios.
3
4  ## Objective
5  Analyze the provided tool use question
   and assess its quality across six
   primary dimensions:
6  1. **Tool Selection Difficulty** - How
   challenging it is to determine which
    tools to use giving all available
   tools
7  2. **Tool Selection Uniqueness** - How
   unique and necessary the selected
   tools are for this specific task
   giving all available tools
8  3. **Question Quality** - Overall
   clarity, specificity, and
   effectiveness
9  4. **Scenario Realism** - How authentic
   and believable the scenario is
10 5. **Verifiable** - How easy it is to
   verify the correctness of the final
   model answer
11 6. **Stability** - How stable the answer
    will be when requested under
   different time and geolocation
12
13 ## Assessment Criteria
14
15 ### 1. Tool Selection Difficulty
16 **What to Evaluate**: How difficult it
   would be for a user to determine
   which specific tools are needed to
   solve this question.
17
18 **Rating Guidelines**:
19 - **very easy**: Question explicitly
   mentions tool names or makes tool
   selection obvious
20 - **easy**: Tool selection is
   straightforward with clear
   indicators
21 - **medium**: Requires some reasoning
   but tool needs are fairly apparent
22 - **hard**: Requires careful analysis to
    determine appropriate tools
23 - **very hard**: Requires extensive
   expertise and deep reasoning to
   identify the correct tools
24
25 ### 2. Tool Selection Uniqueness
```

```
26 **What to Evaluate**: How unique and
   necessary the selected tools are for
    accomplishing this specific task,
   and whether the task can only be
   completed with these tools in the
   specified sequence.
27
28 **Rating Guidelines**:
29 - **not unique**: Many alternative tool
   combinations could accomplish the
   same task equally well
30 - **somewhat unique**: Some alternative
   approaches exist, but selected tools
    offer advantages
31 - **moderately unique**: Selected tools
   are well-suited, with limited
   alternative approaches
32 - **quite unique**: Selected tools are
   particularly well-matched to the
   task requirements
33 - **highly unique**: Task can only be
   accomplished effectively with these
   specific tools in this sequence
34
35 ### 3. Question Quality
36 **What to Evaluate**: Overall quality,
   clarity, and effectiveness of the
   question as a realistic user query.
37
38 **Rating Guidelines**:
39 - **very poor**: Unclear, ambiguous, or
   poorly constructed question
40 - **poor**: Some clarity issues, missing
    important context
41 - **average**: Clear and understandable,
    but could be more specific or
   engaging
42 - **good**: Well-constructed, clear,
   specific, and realistic
43 - **excellent**: Exceptionally clear,
   detailed, engaging, and
   professionally written
44
45 ### 4. Scenario Realism
46 **What to Evaluate**: How authentic,
   believable, and true-to-life the
   described scenario is.
47
48 **Rating Guidelines**:
49 - **unrealistic**: Artificial, contrived,
    or implausible scenario
50 - **somewhat unrealistic**: Some
   realistic elements but feels forced
   or unlikely
51 - **moderately realistic**: Believable
   scenario with minor authenticity
   issues
52 - **realistic**: Authentic scenario that
    represents genuine use cases
53 - **highly realistic**: Completely
   natural, authentic scenario
   indistinguishable from real user
   needs
54
55 ### 5. Verifiable
56 **What to Evaluate**: How easy it is to
   verify the correctness of the final
   model answer.
57
58 **Rating Guidelines**:
```

59 - **hard to verify**: Fully free-form answer that requires extensive human judgment
60 - **somewhat hard**: Mostly subjective answer with some verifiable elements
61 - **moderately verifiable**: Short sentence that can be verified by LLM comparison
62 - **mostly verifiable**: Answer with clear, objective components and some subjective elements
63 - **easy to verify**: Answer can be verified by simple rules, exact matches, or clear success criteria
64
65 ### 6. Stability (1-5 Scale)
66 **What to Evaluate**: How stable and consistent the answer will be when the question is asked under different environmental conditions and system contexts. Consider factors like temporal dependency, geographical variations, operating system differences, network environments, and software version variations.
67
68 **Rating Guidelines**:
69 - **highly unstable**: Answer changes significantly across different conditions (real-time data, location-specific, system-dependent)
70 - **somewhat unstable**: Answer may vary moderately based on environmental or system factors
71 - **moderately stable**: Answer mostly consistent with minor variations due to context
72 - **mostly stable**: Answer remains largely consistent across different conditions
73 - **highly stable**: Answer is completely independent of environmental and system factors
74
75 ## Question Analysis
76
77 ### All Available Tools```
78 {ALL_SERVER_AND_TOOL_INFORMATION}
79 ```
80
81 ### Question Content
82 ```
83 {QUESTION_CONTENT}
84 ```
85
86 ### Intended Tool for This Question
87 ```
88 {INTENDED_TOOL}
89 ```
90
91 ## Output Requirements
92
93 Provide analysis with detailed reasoning BEFORE scores for each of the six metrics.
94
95 ## Output
96 Provide your response in the following XML format:

97
98 `<response>`
99   `<tool_selection_difficulty>`
100   `<reasoning>`
101   `<!-- Detailed explanation including ambiguity level, domain knowledge required, and alternative solutions giving all available tools -->`
102   `</reasoning>`
103   `<rating><!-- Rating: very easy, easy, medium, hard, very hard --></rating>`
104   `</tool_selection_difficulty>`
105
106   `<tool_selection_uniqueness>`
107   `<reasoning>`
108   `<!-- Detailed explanation of tool necessity, sequential dependencies, and alternative tool viability giving all available tools -->`
109   `</reasoning>`
110   `<rating><!-- Rating: not unique, somewhat unique, moderately unique, quite unique, highly unique --></rating>`
111   `</tool_selection_uniqueness>`
112
113   `<question_quality>`
114   `<reasoning>`
115   `<!-- Detailed explanation covering linguistic quality, information architecture, and actionability -->`
116   `</reasoning>`
117   `<rating><!-- Rating: very poor, poor, average, good, excellent --></rating>`
118   `</question_quality>`
119
120   `<scenario_realism>`
121   `<reasoning>`
122   `<!-- Detailed explanation of industry authenticity, workflow accuracy, and stakeholder behavior -->`
123   `</reasoning>`
124   `<rating><!-- Rating: unrealistic, somewhat unrealistic, moderately realistic, realistic, highly realistic --></rating>`
125   `</scenario_realism>`
126
127   `<verifiable>`
128   `<reasoning>`
129   `<!-- Detailed explanation of answer format, objective criteria, and ground truth availability -->`
130   `</reasoning>`
131   `<rating><!-- Rating: hard to verify, somewhat hard, moderately verifiable, mostly verifiable, easy to verify --></rating>`
132   `</verifiable>`
133
134   `<stability>`
135   `<reasoning>`
136   `<!-- Detailed explanation of temporal/geographical/system dependencies and environmental factors -->`

```
137      </reasoning>
138      <rating><!-- Rating: highly unstable,
         somewhat unstable, moderately
         stable, mostly stable, highly stable
         --></rating>
139    </stability>
140 </response>
```

D.5 Trajectory Annotation Prompt

```
1  ## Task
2  Conduct a **Response Quality Assessment
      ** of a tool-use conversation across
      two LLM-scored dimensions, with a
      third dimension computed
      automatically outside the LLM.
3
4  ## Objective
5  Analyze the provided conversation and
      assess its response quality across
      two primary dimensions scored by the
      LLM, while reserving an additional
      tool-call accuracy dimension for
      automated scoring:
6  1. Completeness - Whether the assistant
      fully accomplished the user's
      request end-to-end
7  2. Conciseness - Whether the assistant
      solved the task using the minimum
      necessary steps and verbosity
8
9  ## Assessment Criteria
10
11 ### 1. Completeness
12 **What to Evaluate**: Did the assistant
      fully satisfy the user's goal given
      the conversation context? Consider
      whether the assistant:
13 - Executed all required steps end-to-end
      (including saving/exporting/
      downloading where applicable)
14 - Provided the final deliverable or a
      working alternative when blocked (e.
      g., tool failure with a usable
      fallback)
15 - Included essential confirmations,
      paths, or instructions to achieve
      the outcome
16 - Avoided missing key requirements or
      leaving the user with unresolved
      gaps
17
18 **Rating Guidelines**:
19 - very incomplete: Major requirements
      missing; no usable outcome
20 - incomplete: Some key requirements
      missing; outcome is not directly
      usable
21 - partially complete: Core steps
      attempted; outcome usable only with
      user effort or missing minor
      requirements
22 - mostly complete: Meets most
      requirements; small omissions or
      minor issues remain
23 - fully complete: All requirements met
      with a usable outcome delivered
24
25 ### 2. Conciseness
26 **What to Evaluate**: Did the assistant
```

```
      achieve the goal with minimal
      redundancy and steps? Consider
      whether the assistant:
27 - Avoided repetitive or unnecessary
      explanations/tool calls
28 - Used the minimal set of steps/tools to
      complete the task
29 - Kept language concise while preserving
      clarity
30
31 **Rating Guidelines**:
32 - very redundant: Excessive repetition
      or unnecessary steps/tool calls
33 - redundant: Noticeable verbosity or
      extra steps beyond what's needed
34 - average: Reasonably concise with minor
      extraneous content
35 - concise: Efficient and to the point
      with minimal overhead
36 - very concise: Maximally efficient
      while clear and complete
37
38 ## Response Analysis
39
40 ### Question Content
41 ```
42 {QUESTION_CONTENT}
43 ```
44
45 ### Intended Tool for This Question
46 ```
47 {INTENDED_TOOL}
48 ```
49
50 ### Conversation History
51 ```
52 {CONVERSATION_HISTORY}
53 ```
54
55 ## Output Requirements
56 - Provide detailed reasoning BEFORE
      ratings for Completeness and
      Conciseness
57 - Do NOT score Tool Call Accuracy;
      include placeholders only
58
59 ## Output
60 Provide your response in the following
      XML format:
61
62 <response>
63   <completeness>
64     <reasoning>
65       <!-- Evaluate if the assistant
      delivered an end-to-end usable
      outcome, addressed all requirements,
      handled tool failures with
      alternatives, and provided necessary
      confirmations/paths. -->
66     </reasoning>
67     <rating><!-- Rating: very incomplete,
      incomplete, partially complete,
      mostly complete, fully complete --></
      rating>
68   </completeness>
69
70   <conciseness>
71     <reasoning>
72       <!-- Evaluate if the assistant
      minimized redundant steps/
```

```
2637        explanations, avoided unnecessary
2638        tool calls, and kept messaging
2639        efficient while clear. -->
2640   73    </reasoning>
2641   74    <rating><!-- Rating: very redundant,
2642         redundant, average, concise, very
2643        concise --></rating>
2644   75    </conciseness>
2645   76 </response>
```

E   Cost and Accessibility

All models used to build TOUCAN (data generation and annotation) are open-source and can be deployed efficiently using vLLM servers, which substantially reduce inference cost. Our data generation pipeline demonstrates that producing high-quality, end-to-end synthetic data is feasible without relying on proprietary models. In this section, we provide additional guidance on reproducing our results and extending TOUCAN to new MCP servers, considering both standard and resource-constrained computational settings. Table 15 lists the models used to build TOUCAN and their corresponding GPU requirements, along with a set of open-source, resource-efficient alternative models that are fully compatible with the TOUCAN tool-trajectory generation pipeline. These alternative options, when combined with manual review and/or lightweight verification tools, could produce data of comparable quality and difficulty to TOUCAN .

F   More on Related Works

Table 16 compares TOUCANwith open-source tool-agentic datasets.

Table 15: Approximate (H100) GPU requirements for the models used at each pipeline stage, as well as lightweight open-source alternatives. GPU requirements are provided for full precision inference, quantized versions of these models would further reduce resource requirements.

Stage	LLM Used	Approx. GPUs (vLLM, BF16)	Alternative (Smaller LLM)	Approx. GPUs (vLLM, BF16)	Notes
Task Synthesis	`Mistral-Small-3.2-24B-Instruct-2506`	1	N/A	N/A	Already efficient; runs on single GPU.
	`DevStral-Small-2505`	1	N/A	N/A	Already efficient; runs on single GPU.
	`GPT-OSS-120B`	4	`GPT-OSS-20B`	1	Suitable trade-off between performance and compute.
	`Kimi-K2-Instruct`	2	–	–	MoE with ∼32B active parameters (≈1T total).
	`Qwen3-32B-Instruct`	1	`Qwen2.5-7B-Instruct`	1	Lighter variant preserving coherence for synthesis.
Task Filtering	`Kimi-K2-Instruct`	32	`GPT-OSS-20B`	1	Best performing open model for filtering.
Trajectory Generation	`GPT-OSS-120B`	4	`GPT-OSS-20B`	1	Strong performance-compute balance in same agent framework.
	`Kimi-K2-Instruct`	32	–	–	Efficient, coherent model for synthesis tasks.
	`Qwen3-32B-Instruct`	1	`Qwen2.5-7B-Instruct`	1	Lighter model preserving coherence in trajectory generation.
Trajectory Filtering	`GPT-OSS-120B`	4	`GPT-OSS-20B`	1	Suitable performance—compute compromise for long trajectories.

Table 16: TOUCAN comparison to open-source tool-agentic datasets. Comparison comprises total trajectories, tool calling scenarios ([S]ingle, [P]arallel, [M]ulti[S]tep) including no-tool-use edge case (irrelevance[IR]), number of multi-turn conversations, and other details about data generation. Note − indicates information not publicly available.

Dataset	Trajectories	Tool-Call Scenarios	Multi Turn	Tool Specs	Tool Response
APIGent-MT-5K (Prabhakar et al., 2025)	5,000	S P MS IR	5,000	From τ-Bench	Executed
ToolACE (Liu et al., 2025a)	11,300	S P MS IR	509	Synthetic	Simulated
Hermes Function-Calling V1 (interstellarninja)	11,570	S P MS IR	1,890	Synthetic	Executed
Nemotron (Tools) (Nathawani et al., 2025)	310,051	S P MS –	199,610	–	–
TOUCAN (This Work)	1,527,259	S P MS IR	567,262	Real	Executed