GL-DISEN: GLOBAL-LOCAL DISENTANGLEMENT FOR UNSUPERVISED LEARNING OF GRAPH-LEVEL REPRESENTATIONS

ABSTRACT

Graph-level representation learning plays a crucial role in a variety of tasks such as molecular property prediction and community analysis. Currently, several models based on mutual information maximization have shown strong performance on the task of unsupervised graph representation learning. In this paper, instead, we consider a *disentanglement* approach to learn graph-level representations in the unsupervised setting. Our work is the first to study disentanglement learning for graph-level representations. Our key observation is that the formation of many real-world graphs is a complex process with *global* and *local* generative factors. We hypothesize that disentangled representations which capture these global and local generative factors into independent latent units can be highly beneficial. Specifically, for graph-level representation learning, our disentanglement approach can alleviate distraction due to local variations of individual nodes or individual local neighbourhoods. We propose a VAE based learning algorithm to disentangle the global graph-level information, which is common across the entire graph, and local patch-level information, which varies across individual patches (the local subgraphs centered around the nodes). Through extensive experiments and analysis, we show that our method achieves the state-of-the-art performance on the task of unsupervised graph representation learning.

1 INTRODUCTION

Graph structured data has been very useful in representing a variety of data types including social networks (Newman & Girvan, 2004), protein-protein interactions Krogan et al. (2006), scene graphs (Krishna et al., 2016), customer purchasing patterns (Bhatia et al., 2016) and many more. Graph Neural Networks (GNNs) have recently become the prominent approach for representing graph structured data (Li et al., 2016; Gilmer et al., 2017; Kipf & Welling, 2017; Velickovic et al., 2018; Xu et al., 2019). GNNs are capable of representing graphs in a permutation invariant manner, enabling information propagation among neighbours and mapping graphs to low dimensional spaces.

In this work, we focus on graph-level representation learning. Graph-level representation learning is crucial for tasks like molecular property identification (Duvenaud et al., 2015) and community classification based on the patterns of discussion threads (Yanardag & Vishwanathan, 2015), and they are useful for applications such as drug discovery and recommendation systems. Availability of task specific labels plays a significant role in graph representation learning as much as its role in other domains such as images, text and speech. However, due to many specialized fields which graphs are utilized (e.g., biological sciences, quantum mechanics), collecting labels has become very expensive as it needs expert knowledge (Sun et al., 2020). Therefore, unsupervised learning of graph representation is crucial.

Recent state-of-the-art unsupervised graph representation learning methods (Sun et al., 2020; Hassani & Khasahmadi, 2020) are based on Infomax principle by Linsker (1988). These methods learn the graph representation by maximizing the mutual information between the representation of the entire graph and the representations of individual *patches* of the graph. Here we follow (Velickovic et al., 2019; Sun et al., 2020) and define patches as local subgraphs centered around a node. This

approach allows the graph level representation to capture the globally relevant information from the patch representations (Sun et al., 2020).

Global-local disentanglement. We propose a novel approach for graph-level representation learning. Our observation is that many graphs are generated using multiple heterogeneous factors, with different factors providing different information. Specifically, the formation of many real-world graphs is driven by graph-level factors and node/patch-level factors. For example, an online discussion thread can be represented as a graph where nodes represent users who have participated in the discussion thread, and edges represent interaction between the users in the thread (Yanardag & Vishwanathan, 2015). Graph-level representation of such communication graphs can be used to classify the sub-community (e.g. subreddits on Reddit) of that discussion thread. However, the formation of these communication graphs is driven by global graph-level factors (e.g., the topic of the discussion-thread) and local node-level factors (e.g., characteristics of individual users engaging in on-line discussion). The graph is formed with a complex process involving complicated interactions between global graph-level factors and local node/patch-level factors.

It has been discussed in the literature that disentangling these generative factors can benefit many tasks in different domains (Bengio et al., 2013; Ridgeway, 2016). This is because disentanglement enables to separate out explanatory generative factors which cause variations in data and facilitates selection of only those factors which are well suited for the downstream task. Importantly, removing the irrelevant factors from the prediction process increases the robustness of models (Ma et al., 2019).

Based on the above discussion, we hypothesize that graph representation learning that disentangles the graph-level and node/patch-level factors can be useful for many graph analysis tasks. In particular, the disentangled graph-level representation can be powerful for graph-level inference. Therefore, in this work, we propose GL-Disen: a global graph level - local node/patch level disentanglement method for graph level representation learning.

Disentanglement learning is a novel direction for GNNs, and it has not been studied for either graph level representations learning or for unsupervised settings. The only existing work has focused on disentangling the factors which forms each neighbourhood, based on supervision from downstream node classification tasks (Ma et al., 2019; Liu et al., 2020).

To summarize, our contributions are:

- We propose GL-Disen: a novel global graph-level and local node/patch-level disentangling model. To the best of our knowledge, this is the first work of applying unsupervised disentangled learning for graph level representation learning.
- We conduct extensive experiments to verify that our model learns meaningful disentangled global and local representations for graphs. The disentangled global representation achieves outstanding performance in graph classification.

2 RELATED WORK

Here we review the most relevant work. Reviews of kernel base methods and disentangled learning are in Appendix.

The most recent family of graph embedding methods are based on contrastive learning. Main idea is to train an encoder model to make it learn the contrast in between a representation which captures the structural and statistic information provided by original data and a negative sample. InfoGraph by Sun et al. (2020) was the first graph level embedding model which utilized contrastive learning and this method was inspired by Infomax principle based Deep Graph Infomax (Velickovic et al., 2019). It draws negative samples from other graphs and sum pooling is used as the readout function. Multi-view contrastive learning method by Hassani & Khasahmadi (2020) enhances InfoGraph by introducing multi-view based data augmentation mechanism which uses contrastive learning to maximize mutual information among multiple structural views of the input graph. On the other hand, Graph Contrastive Coding (Qiu et al., 2020) utilizes contrastive learning for learning universal graph embeddings which can be transferred to multiple downstream tasks. Infomax principle based and contrastive learning based methods have produced the best performance for graph embedding models so far.

3 GL-DISEN METHODOLOGY

3.1 GRAPH GENERATION PROCESS

We follow the general framework of (Higgins et al., 2017). However, our specific disentanglement method is quite different, as will be discussed. Let $\mathbb{D} = \{\mathbb{G}, G_f, L_f\}$ be the set that consists of graphs and their ground truth generative factors for global and local level. Each graph $G = (V, A)$, contains a set of nodes V and A is the adjacency matrix. G_f and L_f represent two sets of generative factors: G_f contains global factors $\mathbf{g_f} \subset G_f$ common for the entire graph and $\mathbf{l_f} \subset L_f$ represents local factors which can differ from local patch to patch. In our model, $\mathbf{g_f}$ and $\mathbf{l_f}$ are conditionally independent given G, where $p(\mathbf{g_f}, \mathbf{l_f}|G) = p(\mathbf{g_f}|G) \cdot p(\mathbf{l_f}|G)$. We assume that the graph G is generated using a true world generator which uses the ground truth generative factors: $p(G|\mathbf{g_f}, \mathbf{l_f}) = Gen(\mathbf{g_f}, \mathbf{l_f})$.

3.2 GLOBAL GRAPH LEVEL AND LOCAL PATCH LEVEL DISENTANGLEMENT

Our goal is to develop an unsupervised deep graph generative model which can learn the joint distribution of graph G, the set of generative factors $\mathbf{Z}$, using only the samples from $\mathbb{G}$. This should be learnt in a way that the set of latent generative factors can generate the observed graph G, such that $p(G|\mathbf{Z}) \approx p(G|\mathbf{g_f}, \mathbf{l_f}) = Gen(\mathbf{g_f}, \mathbf{l_f})$. A suitable approach to fulfill this objective is to maximize the marginal log-likelihood for the observed graph G over the whole distribution of latent factors $\mathbf{Z}$.

$$\max_\theta \mathbb{E}_{p_\theta(\mathbf{Z})}[\log p_\theta(G|\mathbf{Z})] \tag{1}$$

For an observed graph G, the inferred posterior probability distribution of the latent factors $\mathbf{Z}$ can be described as $q_\phi(\mathbf{Z}|G)$. However, the graph generation process we described in Section 3.1 assumes two independent sets of generative factors representing global and local level information relevant for a graph. Therefore we consider a model where the latent factor set $\mathbf{Z}$ can be divided into two independent latent factor sets as $\mathbf{Z} = (\mathbf{Z}_g, \mathbf{Z}_l)$. $\mathbf{Z}_g$ represents the latent factors which capture the global generative factors of G and $\mathbf{Z}_l$ captures the local counterpart. Therefore we can rewrite our inferred posterior distribution as follows:

$$q_\phi(\mathbf{Z}|G) = q_\phi(\mathbf{Z}_g, \mathbf{Z}_l|G) = q_\phi(\mathbf{Z}_g|G)q_\phi(\mathbf{Z}_l|G) \tag{2}$$

We discuss in detail the two posteriors: $q_\phi(\mathbf{Z}_g|G)$ and $q_\phi(\mathbf{Z}_l|G)$. The graph G consists of $|V|$ number of nodes. In a graph data structure, each node is not isolated. They are connected with its neighbours and propagates information. Therefore, we use the term *patch* to indicate the local neighbourhood centered at each node where the node interacts with. Therefore, $q_\phi(\mathbf{Z}_g|G)$ and $q_\phi(\mathbf{Z}_l|G)$ are the posterior distributions of all these $|V|$ patches. However, if we consider the global latent posterior, it is common for all $|V|$ patches, as the graph G was originally generated with $\mathbf{g_f}$ common for all V. Hence, we propose to use a single latent $\mathbf{z}_g$ to capture the global generative factors common for all patches. In particular, we use $q_\phi(\mathbf{z}_g|G)$ to model this single posterior. On the other hand, the factors which contribute to generate each patch can vary significantly. Therefore in this model we assume the local latent factors are independent [1]. Therefore, we update Eq. 2 as:

$$q_\phi(\mathbf{Z}|G) = q_\phi(\mathbf{z}_g, \mathbf{Z}_l|G) = q_\phi(\mathbf{z}_g|G) \prod_{i=1}^{|V|} q_\phi(\mathbf{z}_l(i)|G) \tag{3}$$

Here $\mathbf{z}_l(i)$ is the latent factor that captures the local generative factors for a patch centered at node i. Now, our objective is to make sure the latent factors sampled from global and local latent posterior distributions can capture the global and local generative factors $\mathbf{g}_f$ and $\mathbf{l}_f$ respectively in a disentangled manner. Note that, we aim to only disentangle global latent factors from local latent factors in this work. This is because, since the intention of the global latent $\mathbf{z}_g$ is to capture all the global factors for graph level representation, entanglement among individual factors in either global latent or local latent is not being focused. Thus, this is different from (Higgins et al., 2017). To

---

[1]In the evaluation we assess the validity of this assumption.

enforce the disentangling nature between these two latent factors, first, we try to match each of them to their respective priors $p(\mathbf{z}_g)$ and $p(\mathbf{z}_l)$ separately. We select unit Gaussians ($\mathcal{N}(0, 1)$) as priors. This leads to following constrained optimization problem (Higgins et al., 2017).

$$
\begin{aligned}
\max_{\theta,\phi} \quad & \mathbb{E}_{G \sim \mathbb{G}}\Big[\mathbb{E}_{q_\phi(\mathbf{z}_g, \mathbf{Z}_l|G)}[\log p_\theta(G|\mathbf{z}_g, \mathbf{Z}_l)]\Big] \\
\text{s.t.} \quad & KL(q_\phi(\mathbf{z}_g|G) \parallel p(\mathbf{z}_g)) < \epsilon \\
& KL(q_\phi(\mathbf{Z}_l|G) \parallel p(\mathbf{Z}_l)) < \eta
\end{aligned}
\tag{4}
$$

where ϵ and η are strengths of each constraint. Following (Higgins et al., 2017), Eq. 4 can be written to obtain the variational evidence lower bound (ELBO) of a Graph Variational Autoencoder (GVAE) (Here we call this as GVAE because our input is a graph) with two separate latent representations with additional coefficients as follows:

$$
\begin{aligned}
\mathcal{F}(\theta, \phi, \alpha, \gamma; G, \mathbf{z}_g, \mathbf{Z}_l) \geq \, & \mathcal{L}(\theta, \phi; G, \mathbf{z}_g, \mathbf{Z}_l, \alpha, \gamma) \\
= \, & \mathbb{E}_{q_\phi(\mathbf{z}_g, \mathbf{Z}_l|G)}[\log p_\theta(G|\mathbf{z}_g, \mathbf{Z}_l)] \\
& - \alpha \, KL(q_\phi(\mathbf{z}_g|G) \parallel p(\mathbf{z}_g)) \\
& - \gamma \, KL(q_\phi(\mathbf{Z}_l|G) \parallel p(\mathbf{Z}_l))
\end{aligned}
\tag{5}
$$

Based on Eq.3 we can expand the KL divergence term $KL(q_\phi(\mathbf{Z}_l|G) \parallel p(\mathbf{Z}_l))$ and rewrite our objective function for a single graph G as:

$$
\begin{aligned}
\mathcal{L}(\theta, \phi; G, \mathbf{z}_g, \mathbf{Z}_l, \alpha, \gamma) = \, & \mathbb{E}_{q_\phi(\mathbf{z}_g, \mathbf{Z}_l|G)}[\log p_\theta(G|\mathbf{z}_g, \mathbf{Z}_l)] \\
& - \alpha \, KL(q_\phi(\mathbf{z}_g|G)|p(\mathbf{z}_g)) \\
& - \gamma \sum_{i=1}^{|V|} KL(q_\phi(\mathbf{z}_l(i)|G) \parallel p(\mathbf{z}_l(i)))
\end{aligned}
\tag{6}
$$

The training process maximizes this lower bound for all the graphs in a minibatch $\mathbb{G}_b$ from the full dataset $\mathbb{G}$:

$$
\mathcal{L}_{\theta,\phi}(\mathbb{G}_b) = \frac{1}{|\mathbb{G}_b|} \sum_{r=1}^{|\mathbb{G}_b|} \mathcal{L}(\theta, \phi; G, \mathbf{z}_g, \mathbf{Z}_l, \alpha, \gamma)
\tag{7}
$$

3.3 GL-Disen architecture in detail

Figure 1 depicts the proposed GL-Disen model. This is a variation of GVAE where we utilize a N-layer GNN as the encoder. n^{th} layer of a GNN can be defined in general as

$$
\mathbf{h}_v^{(n)} = \text{COMBINE}^{(n)}\left(\mathbf{h}_v^{(n-1)}, \text{AGGREGATE}^{(n)}\left(\left\{\left(\mathbf{h}_v^{(n-1)}, \mathbf{h}_u^{(n-1)}, e_{vu}\right) : u \in \mathcal{N}(v)\right\}\right)\right)
\tag{8}
$$

where $\mathbf{h}_v^{(n)}$ is the feature vector of a patch centered at node $v \in V$ at the n^{th} layer after propagating information from its neighbours $u \in \mathcal{N}(v)$. $\mathbf{e}_{vu}$ is the feature vector of the edge between u and v where $(v, u) \in A$. $\mathbf{h}_v^{(0)}$ is often initialized with node features. We use the term GNN to indicate any network which use layers described in Eq. 8.

Then we utilize two separate sets of GNN layers to produce parameters for posterior distributions for global and local level factors. Let $\mathbf{H}^N = \{\mathbf{h}_v^{(N)}\}_{i=1}^{|V|}$ be the output of GNN after N layers. $\boldsymbol{\mu}_g = \text{GNN}_{\boldsymbol{\mu}_g}(\mathbf{H}^N, A)$ and $\log \boldsymbol{\sigma}_g = \text{GNN}_{\boldsymbol{\sigma}_g}(\mathbf{H}^N, A)$ is used to generate parameters for the Gaussian posterior distributions for global level latent factors; $q_\phi(\mathbf{z}_g(i)|G) = \mathcal{N}(\boldsymbol{\mu}_g(i), diag(\boldsymbol{\sigma}_g(i))), \, \forall i \in \{1 \ldots |V|\}$. Same way we obtain parameters for the local level latent posterior distributions; $q_\phi(\mathbf{z}_l(i)|G) = \mathcal{N}(\boldsymbol{\mu}_l(i), diag(\boldsymbol{\sigma}_l(i))), \, \forall i \in \{1 \ldots |V|\}$, where

Figure 1: GL-Disen architecture: Given an input graph G, we first send it through a GNN to obtain individual global and local latent posterior distributions (Ex: $q(\mathbf{z}_g(1)|G), q(\mathbf{z}_l(1)|G)$) for each patch. Then all individual global posterior distributions $q(\mathbf{z}_g(i)|G)$ are sent through ACCUM process to accumulate into a single posterior $q(\mathbf{z}_g|G)$ for the global latent, using the procedure defined in Eq.9. Sampled local latent factors from their respective local posteriors are combined with the global latent $\mathbf{z}_g$, and this becomes the input to the decoder to reconstruct the graph as per Eq.10. Overall model is trained by maximizing the objective function in Eq.6.

$\boldsymbol{\mu}_l = \text{GNN}_{\boldsymbol{\mu}_l}(\mathbf{H}^N, A)$ and $log\ \boldsymbol{\sigma}_l = \text{GNN}_{\boldsymbol{\sigma}_l}(\mathbf{H}^N, A)$. By utilizing GNN layers for this purpose, GL-Disen allows each patch centered at a node v to disentangle and propagate only the disentangled information to obtain a better posterior distribution for each type of latent.

After obtaining posterior distributions for both global and local latents ($q_\phi(\mathbf{z}_l(i)|G)$ and $q_\phi(\mathbf{z}_l(i)|G), \forall i \in \{1 \ldots |V|\}$), we utilize the accumulation step proposed by Bouchacourt et al. (2018): We model the the single posterior distribution $q_\phi(\mathbf{z}_g|G)$ as the product of posteriors $q_\phi(\mathbf{z}_g(i)|G), \forall i \in \{1 \ldots |V|\}$. Then, the distribution parameters of $q_\phi(\mathbf{z}_g|G)$ are calculated as follows (Bouchacourt et al., 2018):

$$\boldsymbol{\sigma}_g^{-1} = \sum_{i=1}^{|V|} \boldsymbol{\sigma}_g^{-1}(i), \quad \boldsymbol{\mu}_g^T \boldsymbol{\sigma}_g^{-1} = \sum_{i=1}^{|V|} \boldsymbol{\mu}_g(i)^T \boldsymbol{\sigma}_g^{-1}(i) \tag{9}$$

Then global and local latent generative factors are sampled from their respective posterior distributions ($\mathbf{z}_g \sim q_\phi(\mathbf{z}_g|G)$ and $\mathbf{z}_l(i) \sim q_\phi(\mathbf{z}_l(i)|G), \forall i \in \{1 \ldots |V|\}$) and sent through a decoder for reconstructing the graph G. Note that the global latent factor $\mathbf{z}_g$ is only sampled once for the entire graph using $q_\phi(\mathbf{z}_g|G)$. We select a simple 2-layer feed-forward neural network with non-linear activations as our decoder $\mathbf{D}$ for the experiments.

A graph reconstruction can be done via both node reconstruction or adjacency matrix reconstruction. Hence we can rewrite the log-likelihood of generating G (first term of Eq. 6) as the combination of generating V and A as follows:

$$\mathbb{E}_{q_\phi(\mathbf{z}_g, \mathbf{Z}_l|G)}[\log p_\theta(G|\mathbf{z}_g, \mathbf{Z}_l)] = \mathbb{E}_{q_\phi(\mathbf{z}_g, \mathbf{Z}_l|V, A)} \sum_{i=1}^{|V|} \log p_\theta(V_i|\mathbf{z}_g, \mathbf{z}_l(i))$$

$$+ \mathbb{E}_{q_\phi(\mathbf{z}_g, \mathbf{Z}_l|V, A)} \sum_{i=1}^{|V|} \sum_{j=1}^{|V|} \log p_\theta(A_{ij}|\mathbf{z}_g, \mathbf{z}_l(i), \mathbf{z}_l(j)) \tag{10}$$

After training GL-Disen in an unsupervised manner, we utilize the latent global $\mathbf{z}_g \sim q_\phi(\mathbf{z}_g|G)$ as the representation which summarizes graph G in downstream tasks such as graph classification.

4 EXPERIMENTS

Here we discuss our main experiment and analysis results. Additional experiments and analysis are discussed in the Appendix.

4.1 QUANTITATIVE ANALYSIS ON GRAPH CLASSIFICATION

Firstly, we evaluate the effectiveness of learnt disentangled graph level representations from our GL-Disen model on downstream graph classification task.

4.1.1 BASELINES

We compare our proposed GL-Disen model with two categories of unsupervised graph level representation learning methods in the existing literature. First set is kernel based methods. Kernel category consists of 7 models ; Random Walk (RW) (Gärtner et al., 2003), Shortest Path (SP) (Borgwardt & Kriegel, 2005), Graphlet Kernel (GK) (Shervashidze et al., 2009), Weisfeiler-Lehman Subtree kernel (WL) (Shervashidze et al., 2011), Deep Graph Kernels (DGK) (Yanardag & Vishwanathan, 2015), Multi-Scale Laplacian (MLG) (Kondor & Pan, 2016) and most recent Graph Convolutional Kernel Network (GCKN) (Chen et al., 2020). We only compare with GCKN walk kernel method as it is the closest feature aggregation for GNNs. Next category is the most related to GL-Disen, unsupervised non-kernel based methods. These set of methods do not employ exhaustive feature selection (Ex: enumerating through paths or sub-trees) or hand-crafted filters like kernel based methods and only use node features and adjacency matrix on GNNs to propagate information and learn graph representations. We compare with all existing work to the best of our knowledge. It contains 6 models; node2vec (Grover & Leskovec, 2016), sub2vec (Adhikari et al., 2018), graph2vec (Narayanan et al., 2017), InfoGraph (Sun et al., 2020), CMV (Hassani & Khasahmadi, 2020) and GCC (Qiu et al., 2020). We use the same evaluation procedure followed by existing work (Yanardag & Vishwanathan, 2015; Sun et al., 2020; Hassani & Khasahmadi, 2020) for a fair comparison. 10-fold cross validation accuracy is used to report the performance and the mean accuracy and standard variation of 5 repeated runs is used as the final result. Complete details of our experiment setup is included at the Appendix.

4.1.2 RESULTS

Table 1: Mean 10-fold cross validation accuracy on graph classification. Results in **bold** indicate the best accuracy for each category. Underlined results show the second best performances.

DATASET	MUTAG	PTC-MR	IMDB-BIN	IMDB-MUL	RED-BIN	RED-MUL-5K
# Graphs	188	344	1000	1500	2000	4999
Avg. Nodes	17.93	14.29	19.77	13.0	429.63	508.52
Avg. Edges	19.79	14.69	96.53	65.94	497.75	594.87
# Classes	2	2	2	3	2	5
Kernel Methods						
RW	83.7 ± 1.5	57.9 ± 1.3	50.7 ± 0.3	34.7 ± 0.2	—	—
SP	85.2 ± 2.4	58.2 ± 2.4	55.6 ± 0.2	38.0 ± 0.3	64.1 ± 0.1	39.6 ± 0.2
GK	81.7 ± 2.1	57.3 ± 1.4	65.9 ± 1.0	43.9 ± 0.4	$\underline{77.3 \pm 0.2}$	41.0 ± 0.2
WL	80.7 ± 3.0	58.0 ± 0.5	72.3 ± 3.4	$\underline{47.0 \pm 0.5}$	68.8 ± 0.4	$\mathbf{46.1 \pm 0.2}$
DGK	87.4 ± 2.7	60.1 ± 2.6	$\underline{67.0 \pm 0.6}$	44.6 ± 0.5	$\mathbf{78.0 \pm 0.4}$	$\underline{41.3 \pm 0.2}$
MLG	$\underline{87.9 \pm 1.6}$	$\underline{63.3 \pm 1.5}$	66.6 ± 0.3	41.2 ± 0.0	—	—
GCKN-walk	$\mathbf{92.8 \pm 6.1}$	$\mathbf{65.9 \pm 2.0}$	$\mathbf{75.9 \pm 3.7}$	$\mathbf{53.4 \pm 4.7}$	—	—
Non-Kernal Methods						
node2vec	72.6 ± 10.2	58.6 ± 8.0	—	—	—	-
sub2vec	61.1 ± 15.8	60.0 ± 6.4	55.3 ± 1.5	36.7 ± 0.8	71.5 ± 0.4	36.7 ± 0.4
graph2vec	83.2 ± 9.6	60.2 ± 6.9	71.1 ± 0.5	50.4 ± 0.9	75.8 ± 1.0	47.9 ± 0.3
InfoGraph	89.0 ± 1.1	61.7 ± 1.4	73.0 ± 0.9	49.7 ± 0.5	82.5 ± 1.4	53.5 ± 1.0
CMV	$\underline{89.7 \pm 1.1}$	$\underline{62.5 \pm 1.7}$	$\underline{74.2 \pm 0.7}$	$\underline{51.2 \pm 0.5}$	84.5 ± 0.6	—
GCC	—	—	72.0	49.4	$\underline{89.8}$	$\underline{53.7}$
GL-Disen(ours)	$\mathbf{90.7 \pm 0.6}$	$\mathbf{67.9 \pm 0.8}$	$\mathbf{74.7 \pm 0.6}$	$\mathbf{52.1 \pm 0.4}$	$\mathbf{90.9 \pm 0.3}$	$\mathbf{54.9 \pm 0.1}$

Performance comparison of GL-Disen with state-of-the-art unsupervised graph representation learning models are reported in Table 1. We used 6 commonly used datasets; MUTAG, PTC-MR, IMDB-BINARY, IMDB-MULTI, REDDIT-BINARY and REDDIT-MULTI. Table 1 contains the statistics of these datasets, refer to Appendix for complete details. For existing work, we report results from previous papers. Our global graph level and local patch level disentanglement based GL-Disen model has been able to surpass all latest GNN based unsupervised methods. It is important to mention that, although CMV uses additional diffusion matrix to expand the neighbourhood information propagation and GCC pretrains its models with larger datasets, our GL-Disen which only uses adjacency matrix without any pretraining has been able to surpass them. This shows the effectiveness of disentangling and removing irrelevant factors for downstream tasks. When considering kernel based method category, GCKN reports superior performance to ours in 3 datasets although our results are very comparable to them.

4.2 QUALITATIVE ANALYSIS ON GL-DISEN

In order to qualitatively evaluate GL-Disen, we focus on two main aspects. First is whether GL-Disen actually have the ability to disentangle global and local level factors into independent representations. Second is whether disentangling global factors actually beneficial for downstream global level tasks over local factors and entangled representations. We try to answer some questions in the following sections to verify these two aspects.

4.2.1 ARE THE LEARNT GLOBAL AND LOCAL LATENT FACTORS BY GL-DISEN DISENTANGLED?

To answer this question, we measure the similarity and dependence between global $\mathbf{z}_g$ and local $\mathbf{z}_l$ latent representations for a given graph G. Following Ma et al. (2019) we use correlation metric and calculate correlation between disentangled global latent representation and local latent representations for two sample graphs from MUTAG (Kriege & Mutzel, 2012) dataset and visualize in Figure 2. Following UDR_s (Duan et al., 2020), we use Spearman's correlation to calculate the similarity/correlation matrix. Entry (i, j) of the correlation matrix indicate the absolute correlation value between $\mathbf{z}_g(i)$ and $\mathbf{z}_l(j)$. Note that, only for analysing purposes we sample $\mathbf{z}_g(i) \sim q_\phi(\mathbf{z}_g(i)|G)$. The diagonal of the correlation matrix shows the correlation between global latent and local latent learnt by GL-Disen for each patch of the graph. We can observe that the correlation values in diagonal is very low, closed to 0.0. This shows that the global and local latent representations output by GL-Disen is capable of likely capturing mutually exclusive information showing its disentangling ability.

(a) Sample Graph 1   (b) Sample Graph 2

Figure 2: Disentanglement of learnt global and local latent factors by GL-Disen via absolute values of correlation between those two representations for two sample graphs from MUTAG. Very low correlation shows the capability of DG-Disen in learning mutually exclusive information between its global and local latent factors. Best viewed in colour.

4.2.2 ARE THE INFERRED GLOBAL LATENTS CORRESPOND TO THE FIXED GLOBAL GENERATIVE FACTORS OF THE GRAPH?

Previous section verified GL-Disen's ability in disentangled learning. However, next we need to verify our assumption that the global latent factors extracted from each patch should be similar to each-other than their local counterparts. Since there are multiple global generative factors contribute for the graph generation and the information propagation is different from patch to patch, we cannot assume that the extracted global factors to be exactly the same. But they should be more similar than extracted local latent factors. We evaluate this using the Mean Absolute Pairwise Difference (MAPD) measure used by Higgins et al. (2017) for the disentanglement metric proposed in $\beta-$VAE. MAPD matrix for global latents is calculated as $\text{MAPD}_g(i,j) = \text{MEAN}(\left|\mathbf{z}_g(i) - \mathbf{z}_g(j)\right|)$ and $\text{MAPD}_l(i,j) = \text{MEAN}(\left|\mathbf{z}_l(i) - \mathbf{z}_l(j)\right|)$ used for local latents. We average over all the dimensions of the latent.

(a) Sample Graph 1   (b) Sample Graph 2

Figure 3: MAPD among global latent factors (Left of each sample) and local latent factors (Right) for two graphs from MUTAG. These matrices clearly show that the inter-patch latent representation difference for produced global latent factors is very low compared to local latent factors. This indicates the global factor representations disentangled by GL-Disen is indeed shared among the entire graph, unlike local factors which are local to certain patches.

Figure 3 shows that the produced global level latent representations are similar to each other for the entire graph compared to local level representations. Following the argument of Higgins et al. (2017), if the representations are disentangled meaningfully, i.e. independent and interpretable, then, there can only be small variances in the inferred latents that correspond to the *fixed* generative factors.

Under our model, the global factors for a given graph are fixed, therefore, we examine the variance of the inferred latents $\mathbf{z}_g(i), \forall i \in \{1 \dots |V|\}$ for a given graph (and we show that indeed these $\mathbf{z}_g(i)$ which correspond to the fixed global factors of the given graph has small variance). This justifies our implementation to produce single $\mathbf{z}_g$ from $\{\mathbf{z}_g(i)\}_{i=1}^{|V|}$ in Figure 1.

Also from the inter-patch local latent representation similarity, we can observe that a graph consists of several independent patches where the intra-patch local level latent similarity is very low. This finding supports our decision to model local latent factors as independent variables.

5 CONCLUSIONS

We introduced a disentanglement learning based approach for unsupervised graph level representation learning. Our assumption was that disentangling global level information shared among the entire graph, from local level information which are unique for patches, is beneficial for graph level tasks as it removes irrelevant information which can act as noise. We proposed VAE based GL-Disen for this purpose. From both quantitative and qualitative empirical results, we showcased the validity of our assumption and the effectiveness of our model. We achieve new state-of-the-art performance for unsupervised graph representation learning task.

REFERENCES

Bijaya Adhikari, Yao Zhang, Naren Ramakrishnan, and B. Aditya Prakash. Sub2vec: Feature learning for subgraphs. In *Advances in Knowledge Discovery and Data Mining - 22nd Pacific-Asia*

Conference, PAKDD 2018, Melbourne, VIC, Australia, June 3-6, 2018, Proceedings, Part II, pp. 170–182, 2018. doi: 10.1007/978-3-319-93037-4_14. URL `https://doi.org/10.1007/978-3-319-93037-4_14`.

P. Baldi and K. Hornik. Neural networks and principal component analysis: Learning from examples without local minima. *Neural Networks*, 2:53–58, 1989.

Yoshua Bengio, Aaron C. Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE Trans. Pattern Anal. Do. Intell.*, 35(8):1798–1828, 2013. doi: 10.1109/TPAMI.2013.50. URL `https://doi.org/10.1109/TPAMI.2013.50`.

K. Bhatia, K. Dahiya, H. Jain, A. Mittal, Y. Prabhu, and M. Varma. The extreme classification repository: Multi-label datasets and code, 2016. URL `http://manikvarma.org/downloads/XC/XMLRepository.html`.

K. M. Borgwardt and H. P. Kriegel. Shortest-path kernels on graphs. In *Fifth IEEE International Conference on Data Mining (ICDM'05)*, pp. 8 pp.–, 2005.

Diane Bouchacourt, Ryota Tomioka, and Sebastian Nowozin. Multi-level variational autoencoder: Learning disentangled representations from grouped observations. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pp. 2095–2102, 2018. URL `https://www.aaai.org/ocs/index.php/AAAI/AAAI18/paper/view/16521`.

Christopher Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in β-vae. 04 2018.

Chih-Chung Chang and Chih-Jen Lin. LIBSVM: A library for support vector machines. *ACM Trans. Intell. Syst. Technol.*, 2(3):27:1–27:27, 2011. doi: 10.1145/1961189.1961199. URL `https://doi.org/10.1145/1961189.1961199`.

Dexiong Chen, Laurent Jacob, and Julien Mairal. Convolutional kernel networks for graph-structured data. *CoRR*, abs/2003.05189, 2020. URL `https://arxiv.org/abs/2003.05189`.

Tian Qi Chen, Xuechen Li, Roger B. Grosse, and David Duvenaud. Isolating sources of disentanglement in variational autoencoders. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, 3-8 December 2018, Montr 'e al, Canada*, pp. 2615–2625, 2018. URL `http://papers.nips.cc/paper/7527-isolating-sources-of-disentanglement-in-variational-autoencoders`.

Guillaume Desjardins, Aaron C. Courville, and Yoshua Bengio. Disentangling factors of variation via generative entangling. *CoRR*, abs / 1210.5474, 2012. URL `http://arxiv.org/abs/1210.5474`.

Sunny Duan, Loic Matthey, Andre Saraiva, Nick Watters, Christopher Burgess, Alexander Lerchner, and Irina Higgins. Unsupervised model selection for variational disentangled representation learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020. URL `https://openreview.net/forum?id=SyxL2TNtvr`.

David K Duvenaud, Dougal Maclaurin, Jorge Iparraguirre, Rafael Bombarell, Timothy Hirzel, Alan Aspuru-Guzik, and Ryan P Adams. Convolutional networks on graphs for learning molecular fingerprints. In C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 28*, pp. 2224–2232. Curran Associates, Inc., 2015. URL `http://papers.nips.cc/paper/5954-convolutional-networks-on-graphs-for-learning-molecular-fingerprints.pdf`.

Matthias Fey and Jan Eric Lenssen. Fast graph representation learning with pytorch geometric. *CoRR*, abs/1903.02428, 2019. URL `http://arxiv.org/abs/1903.02428`.

Thomas Gärtner, Peter A. Flach, and Stefan Wrobel. On graph kernels: Hardness results and efficient alternatives. In *Computational Learning Theory and Kernel Machines, 16th Annual Conference on Computational Learning Theory and 7th Kernel Workshop, COLT/Kernel 2003, Washington, DC, USA, August 24-27, 2003, Proceedings*, pp. 129–143, 2003. doi: 10.1007/978-3-540-45167-9_11. URL `https://doi.org/10.1007/978-3-540-45167-9_11`.

Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural message passing for quantum chemistry. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, pp. 1263–1272, 2017. URL `http://proceedings.mlr.press/v70/gilmer17a.html`.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2010, Chia Laguna Resort, Sardinia, Italy, May 13-15, 2010*, pp. 249–256, 2010. URL `http://proceedings.mlr.press/v9/glorot10a.html`.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, San Francisco, CA, USA, August 13-17, 2016*, pp. 855–864, 2016. doi: 10.1145/2939672.2939754. URL `https://doi.org/10.1145/2939672.2939754`.

Kaveh Hassani and Amir Hosein Khasahmadi. Contrastive multi-view representation learning on graphs. In *Proceedings of International Conference on Machine Learning*, pp. 3451–3461. 2020.

Irina Higgins, Lo ” i c Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017. URL `https://openreview.net/forum?id=Sy2fzU9gl`.

Geoffrey E. Hinton and Richard S. Zemel. Autoencoders, minimum description length and helmholtz free energy. In *Advances in Neural Information Processing Systems 6, [7th NIPS Conference, Denver, Colorado, USA, 1993]*, pp. 3–10, 1993. URL `http://papers.nips.cc/paper/798-autoencoders-minimum-description-length-and-helmholtz-free-energy`.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsm ”a ssan, Stockholm, Sweden, July 10-15, 2018*, pp. 2654–2663, 2018. URL `http://proceedings.mlr.press/v80/kim18b.html`.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL `http://arxiv.org/abs/1412.6980`.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL `http://arxiv.org/abs/1312.6114`.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017. URL `https://openreview.net/forum?id=SJU4ayYgl`.

Risi Kondor and Horace Pan. The multiscale laplacian graph kernel. In *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 2982–2990, 2016. URL `http://papers.nips.cc/paper/6135-the-multiscale-laplacian-graph-kernel`.

Nils M. Kriege and Petra Mutzel. Subgraph matching kernels for attributed graphs. In *Proceedings of the 29th International Conference on Machine Learning, ICML 2012, Edinburgh, Scotland, UK, June 26 - July 1, 2012*, 2012. URL http://icml.cc/2012/papers/542.pdf.

Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, Michael Bernstein, and Li Fei-Fei. Visual genome: Connecting language and vision using crowdsourced dense image annotations. 2016. URL https://arxiv.org/abs/1602.07332.

Nevan Krogan, Gerard Cagney, Haiyuan Yu, Gouqing Zhong, Xinghua Guo, Alexandr Ignatchenko, Joyce Li, Shuye Pu, Nira Datta, Aaron Tikuisis, Thanuja Punna, José Peregrín-Alvarez, Michael Shales, Xin Zhang, Mike Davey, Mark Robinson, Alberto Paccanaro, James Bray, Anthony Sheung, and Jack Greenblatt. Global landscape of protein complexes in the yeast saccharomyces cerevisiae. *Nature*, 440:637–43, 04 2006. doi: 10.1038/nature04670.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*, 2018. URL https://openreview.net/forum?id=H1kG7GZAW.

Yujia Li, Daniel Tarlow, Marc Brockschmidt, and Richard S. Zemel. Gated graph sequence neural networks. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL http://arxiv.org/abs/1511.05493.

Ralph Linsker. Self-organization in a perceptual network. *computer*, 21(3):105–117, 1988. doi: 10.1109/2.36. URL https://doi.org/10.1109/2.36.

Yanbei Liu, Xiao Wang, Shu Wu, and Zhitao Xiao. Independence promoted graph disentangled networks. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 4916–4923, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/5929.

Jianxin Ma, Peng Cui, Kun Kuang, Xin Wang, and Wenwu Zhu. Disentangled graph convolutional networks. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, pp. 4212–4221, 2019. URL http://proceedings.mlr.press/v97/ma19a.html.

Annamalai Narayanan, Mahinthan Chandramohan, Rajasekar Venkatesan, Lihui Chen, Yang Liu, and Shantanu Jaiswal. graph2vec: Learning distributed representations of graphs. *CoRR*, abs/1707.05005, 2017. URL http://arxiv.org/abs/1707.05005.

M. E. J. Newman and M. Girvan. Finding and evaluating community structure in networks. *Phys. Rev. E*, 69:026113, Feb 2004. doi: 10.1103/PhysRevE.69.026113. URL https://link.aps.org/doi/10.1103/PhysRevE.69.026113.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Jiezhong Qiu, Qibin Chen, Yuxiao Dong, Jing Zhang, Hongxia Yang, Ming Ding, Kuansan Wang, and Jie Tang. Gcc: Graph contrastive coding for graph neural network pre-training. *arXiv preprint arXiv:2006.09963*, 2020.

Karl Ridgeway. A survey of inductive biases for factorial representation-learning. *CoRR*, abs/1612.05299, 2016. URL http://arxiv.org/abs/1612.05299.

Nino Shervashidze, S. V. N. Vishwanathan, Tobias Petri, Kurt Mehlhorn, and Karsten M. Borgwardt. Efficient graphlet kernels for large graph comparison. In *Proceedings of the Twelfth International Conference on Artificial Intelligence and Statistics, AISTATS 2009, Clearwater Beach, Florida, USA, April 16-18, 2009*, pp. 488–495, 2009. URL http://proceedings.mlr.press/v5/shervashidze09a.html.

Nino Shervashidze, Pascal Schweitzer, Erik Jan van Leeuwen, Kurt Mehlhorn, and Karsten M. Borgwardt. Weisfeiler-lehman graph kernels. *J. Mach. Learn. Res.*, 12:2539–2561, 2011. URL `http://dl.acm.org/citation.cfm?id=2078187`.

Fan-Yun Sun, Jordan Hoffmann, Vikas Verma, and Jian Tang. Infograph: Unsupervised and semi-supervised graph-level representation learning via mutual information maximization. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020. URL `https://openreview.net/forum?id=r1lfF2NYvH`.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Li 'o, and Yoshua Bengio. Graph attention networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*, 2018. URL `https://openreview.net/forum?id=rJXMpikCZ`.

Petar Velickovic, William Fedus, William L. Hamilton, Pietro Liò, Yoshua Bengio, and R. Devon Hjelm. Deep graph infomax. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*, 2019. URL `https://openreview.net/forum?id=rklz9iAcKQ`.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*, 2019. URL `https://openreview.net/forum?id=ryGs6iA5Km`.

Pinar Yanardag and S. V. N. Vishwanathan. Deep graph kernels. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, Sydney, NSW, Australia, August 10-13, 2015*, pp. 1365–1374, 2015. doi: 10.1145/2783258.2783417. URL `https://doi.org/10.1145/2783258.2783417`.

A   RELATED WORK

A.1   UNSUPERVISED GRAPH LEVEL REPRESENTATION LEARNING

Kernel Methods   Graph kernels are widely used for representing graph structured data over decades. Main idea of graph kernels is to first find out best sub-structures which the graphs can be divided into and then enumerate and count the occurrences of these sub-structures to represent them as a high dimentional feature vector. Most common substructures are walks (Gärtner et al., 2003), shortest paths (Borgwardt & Kriegel, 2005), subtrees (Shervashidze et al., 2011), or graphlets (Shervashidze et al., 2009). Then the graph kernels are defined to calculate pairwise substructure similarity between two given graphs. Earlier graph kernels decoupled the process for kernel based data representations and task based model training into two parts. Therefore unlike GNNs, kernels can neither produce task dependent features, nor can train end to end. However kernels have more expressive power and regularize properly than GNNs. More recent kernel based models like GCKN (Chen et al., 2020) have tried to combine the best of both kernal and GNN worlds by extending convolution kernel networks. However, still these kernel based methods rely on enumeration of the substructure occurrences in graphs, where they gain better expressive power at the cost of efficiency. Kernel based methods which use walk kernels are the most similar to GNN as GNN also uses walks for information propagation.

Other Methods   Another set of methods were proposed inspired by the word2vec skip-gram model from natural language processing to encode neighbourhood information to a vectorized representation and consider it as the graph embedding. First model was node2vec (Grover & Leskovec, 2016) and sub2vec (Adhikari et al., 2018) uses random walks to identify each node's neighbourhood and encode that to a latent vector to represent each node or sub-graph respectively. graph2vec (Narayanan et al., 2017) uses Weisfeiler-Lehman kernel (Shervashidze et al., 2011) to calculate non-linear substructures opposed to linear sub-structures from sub2vec to vectorize full graphs. However these methods are completely dependent of neighbourhood information and unable to utilize node features.

A.2   DISENTANGLED REPRESENTATION LEARNING

Autoencoder (Baldi & Hornik, 1989; Hinton & Zemel, 1993) based approaches has proven to be one of the most effective methods in representation leaning (Bengio et al., 2013) which provides compact and meaningful representations without any supervision. These learnt latent representations can be utilized for downstream tasks such as classification or clustering. Variational Autoencoders (Kingma & Welling, 2014) further enhance these capabilities by supporting variational inference. Disentangled learning (Desjardins et al., 2012) is focused on learning the model to assign different factors used for object composition to different dimension of the latent representation. VAEs were proven to be capable of disentangling the latent features after regularizing its objective function (Higgins et al., 2017; Burgess et al., 2018). Later more variations of VAE (Chen et al., 2018; Kim & Mnih, 2018; Kumar et al., 2018) have been proposed for better disentangled learning.

Another line of disentangled learning was proposed based on grouped observations by Bouchacourt et al. (2018) which makes the models learn the semantics of provided grouping. These methods aim at disentangling content (group) and style (individual element) level information where the content is common for the entire group while style is independent for each element in a group. Group level acts as weak supervision where the disentanglement is only learnt based on the fact that all element belong to the same group without actually knowing the group label. They propose a multi-layer VAE (ML-VAE) to achieve this and they show the effectiveness of their method based on its generalizability to unseen groups and controllability over latent space.

Inspired by this work, we propose to apply natural grouping among nodes (as they belong to the same graph via edges) to disentangle global graph level factors from local factors.

A.3   DISENTANGLED REPRESENTATION LEARNING FOR GNN

In this section, we discuss disentangled representation learning for GNN. We refer the reader to the Appendix for a review of general disentangled representation learning.

Disentangled learning is a very novel direction for graph representation learning domain as only very few work are currently available. DisenGCN (Ma et al., 2019) was the first method proposed to disentangle the node representation which dynamically extracts each factor caused for each neighbour to form an edge with current node. IPGDN (Liu et al., 2020) proposes another disentangled node representation which focuses not only on disentangling factors which relates the node with its neighbours, but also on making those factors as independent as possible. Both of these methods are guided by the supervision of downstream node classification tasks.

Compared to these two methods, we follow a different level of disentanglement in an unsupervised manner. Our GL-Disen focuses on disentangling global level factors common for the entire graph from local level factors specific to patches. We do not aim at disentangling individual factors in each level. DisenGCN and IPGDN can be identified as disentangling individual factors in local level as they factorize the neighbourhood.

B   Pseudo code of our proposed GL-Disen

Algorithm 1 GL-Disen Algorithm

1: **for** Each epoch **do**
2:     Sample a minibatch of graphs $\mathbb{G}_b$
3:     **for** $G \in \mathbb{G}_b$ **do**
4:         **procedure** Encoder(G)
5:             Encode $G \in (V, A)$ into $q(\mathbf{z}_g(i)|G; \phi)$, $q(\mathbf{z}_l(i)|G; \phi)$, $\forall i \in \{1 \dots |V|\}$
6:         **end procedure**
7:         Accumulate $q(\mathbf{z}_g(i)|G; \phi)$, $\forall i \in \{1 \dots |V|\}$
8:         Obtain a single global level latent posterior $q_\phi(\mathbf{z}_g|G)$ ▷ Eq. 9
9:         **procedure** Decoder$(q_\phi(\mathbf{z}_g|G), q(\mathbf{z}_l(i)|G; \phi)$, $\forall i \in \{1 \dots |V|\})$
10:            Sample a single global latent factor $\mathbf{z}_g \sim q_\phi(\mathbf{z}_g|G)$ for the entire G
11:            Sample individual local latent factors for each substructure i
12:            **for** $i \in \{1 \dots |V|\}$ **do**
13:                $\mathbf{z}_l(i) \sim q_\phi(\mathbf{z}_l(i)|G)$
14:            **end for**
15:            Decode $\mathbf{z}_g$ and $\{\mathbf{z}_l(i)\}_{i=1}^{|V|}$ to reconstruct the graph G using $p(G|\mathbf{z}_g, \{\mathbf{z}_l(i)\}_{i=1}^{|V|})$
16:        **end procedure**
17:    **end for**
18:    Update θ, ϕ by taking a gradient step of $\mathcal{L}_{\theta,\phi}(\mathbb{G}_b), \nabla_{\theta,\phi}\mathcal{L}(\mathbb{G}_b, \theta, \phi)$ ▷ Eq. 7
19: **end for**

B.1   Evaluation Datasets

We select six commonly used graph classification benchmark datasets as follows: MUTAG (Kriege & Mutzel, 2012) dataset contains mutagenic aromatic and heteroaromatic nitro compounds while PTC dataset (Kriege & Mutzel, 2012) consists of chemical compounds reported for carcinogenicity of rats. Apart from these bioinformatics datasets, next we evaluate on four social network datasets (Yanardag & Vishwanathan, 2015) namely IMDB-BINARY, IMDB-MULTI, REDDIT-BINARY and REDDIT-MULTI-5K. IMDB datasets contain information about movies where the nodes are actors/actresses and they are connected by edges if they have acted in the same movie. IMDB-BINARY contains two genres of movies: Action and Romance. Multi-class version of IMDB dataset contains movies from Comedy, Romance and Sci-Fi genres. Reddit datasets were created using threads in different subreddits. Nodes in each graph are users who responded to that particular thread and edges are formed when one user respond to another user's comment. REDDIT-BINARY dataset labels each graph as question/answer-based community or a discussion-based community and REDDIT-MULTI-5K labels graphs into 5 labels according to their subreddit namely, *worldnews, videos, AdviceAnimals, aww* and *mildlyinteresting*. Table 1 contains statistics of all these datasets.

C   EXPERIMENT SETUP

We use the same evaluation procedure followed by existing work (Yanardag & Vishwanathan, 2015; Sun et al., 2020; Hassani & Khasahmadi, 2020) for a fair comparison. 10-fold cross validation accuracy is used to report the performance and the mean accuracy and standard variation of 5 repeated runs is used as the final result. Mean Squared Error and Binary Cross Entropy losses are used to calculate node and adjacency matrix reconstruction errors. After GL-Disen model is trained in unsupervised manner, the classification accuracies are calculated using LIBSVM (Chang & Lin, 2011) which the C parameter was selected from $\{1, 10^1, 10^2, 10^3, 10^4\}$ using cross-validation from the training folds of data.

Following InfoGraph (Sun et al., 2020), Graph Isomorphism Network (GIN) (Xu et al., 2019) is used as the GNN encoder in GL-Disen. We initialize GL-Disen model using Xavier initialization (Glorot & Bengio, 2010) and train the model using Adam optimizer (Kingma & Ba, 2015). Initial learning rate, number of GNN layers and batch size were set to 0.001, 2 and 128 respectively. Number of training epochs and hidden dimension were chosen from $\{20, 30, 40, 50\}, \{32, 128, 512\}$. Refer to the Appendix for the selected hyper-parameter sets for each dataset.

Model implementations and data loading were done using Pytorch (Paszke et al., 2017) and Pytorch Geometric (Fey & Lenssen, 2019) for all our experiments.

D   ADDITIONAL ANALYSIS TO PROVIDE MORE EVIDENCE THAT $\mathbf{z}_g$ CAPTURES GLOBAL LEVEL INFORMATION

Table 1 shows that GL-Disen is able to surpass all existing GNN based unsupervised methods for graph classification. However, it is important to compare the performance of disentangled global representation against disentangled local representations as well as entangled representations to verify that the most crucial information for downstream global level tasks (Ex: graph classification) are indeed captured by global latent representation $\mathbf{z}_g$.

For this, the first experiment we conducted was to separately evaluate how the downstream graph classification accuracy gets effected when using disentangled latent global representations, disentangled latent local representations and entangled latent representations. We used the same configurations as the original GL-Disen where $\mathbf{z}_g$ was sent to the SVM. We use the same accumulation function mention in Eq.9 to obtain the single posterior distribution and sample a representation for both disentangled latent local and entangled latent before feeding them to SVM. For obtaining entangled representations, we use a vanilla VAE.

Next, we examine whether local factors are completely irrelevant for global level tasks. To analyse this, we feed a linear combination of latent global representation and latent local representation to the SVM classifier. This experiment was conducted using the best pre-trained models according to Section C. We set a gating hyper-parameter λ to determine the contribution comes from latent local representation. We use the following function to obtain the final graph representation $\mathbf{z}_g$ to be sent to the SVM. We use the same accumulation function mention in Eq.9 for obtaining a single posterior distribution to sample $\mathbf{z}_l$ from.

$$\hat{\mathbf{z}}_g = \lambda \, \mathbf{z}_l + (1 - \lambda) \, \mathbf{z}_g \tag{11}$$

Figure 4 visualizes the impact of local latent factors $\mathbf{z}_l$ and entangled latent factors (latent representation from vanilla VAE) against global latent factors $\mathbf{z}_g$ for graph classification task. Each dotted line indicates the accuracy value obtained when each of these latent representations are individually sent to SVM for graph classification. We can observe that global latent representation has achieved the best individual performance surpassing local only and entangled. GL-Disen local only performance has been very close to entangled performance obtained from VAE. We believe this is because, although global information are included in VAE'S latent representation (in an entangled manner), each observation is treated in an IID manner. Hence those global information might be getting suppressed in order to give space for latent factors which enhances reconstruction ability of the model. Solid blue line shows how the graph classification accuracy changes with increasing λ. We observe when the λ is increasing (more contribution coming from local latent representation),

Figure 4: Comparison of the impact of other latent representations for graph classification task against global only $\mathbf{z}_g$ representation. (best viewed in colour)

the classification performance drops. Therefore we can conclude that the global latent $\mathbf{z}_g$ achieves the best performance. And there is no gain in incorporating disentangled local latent $\mathbf{z}_l$ except some random variations.

E ABLATION STUDY

E.1 IMPACT OF THE DIMENSIONAL RATIO BETWEEN GLOBAL AND LOCAL LATENT REPRESENTATIONS

In this study we analyse the impact of the amount of information we allocate for global latent $\mathbf{z}_g$ and local latent $\mathbf{z}_l(i)$ on the downstream task. For an example, if the ratio is 3:1, that means we allocate 3 times more dimentionality to $\mathbf{z}_g$ than $\mathbf{z}_l(i)$. The we input for the decoder also, we maintain this ratio.

Global Local Ratio	Accuracy $\pm$ S.D. %
3:1	86.5 ± 0.8
1:1	90.7 ± 0.6
1:3	88.7 ± 0.6
0:1	87.7 ± 0.7

We can observe that the performance drops when most of the information comes from global latent as the reconstruction error increases by being unable to reconstruct the graph in the decoder. When there is no dimension for global, that is the vanilla VAE where all information is entangled and considered local. Experiments were conducted on MUTAG dataset. This shows that allowing equal amount of information is the beneficial for our model.

E.2 IMPACT OF USING DEGREE FEATURES

Social network datasets (IMDB, REDDIT) we are using do not have input node features. Therefore existing work has taken two approaches to provide synthetic node features. First is using a constant vector and the second is to use node's degree count as a feature. Following table shows the performances of GL-Disen when different types of synthetic features are used.

Synthetic feature	IMDB-BINARY	IMDB-MULTI	REDDIT-BINARY	REDDIT-MULTI-5K
Constant	72.5 ± 0.3	48.3 ± 0.3	90.9 ± 0.3	54.9 ± 0.1
Out degree count	74.7 ± 0.6	52.1 ± 0.4	85.5 ± 0.4	52.4 ± 0.2

We can observe that, only IMDB benefits from degree features while Reddit achieves best performance when constant feature is used.

E.3 IMPACT OF HIDDEN SIZE

Following table shows how hidden size effect the performance.

Hidden size	MUTAG	PTC-MR	IMDB-BIN	IMDB-MUL	REDD-BIN	RED-MUL-5K
32	90.5 ± 0.3	63.7 ± 1.3	71.9 ± 0.6	49.9 ± 0.1	90.9 ± 0.3	54.9 ± 0.1
128	90.7 ± 0.6	65.9 ± 1.2	72.7 ± 0.4	51.7 ± 0.5	90.2 ± 0.2	52.4 ± 0.2
512	89.8 ± 0.8	67.9 ± 0.8	74.7 ± 0.6	52.1 ± 0.4	89.3 ± 0.2	51.6 ± 0.2

E.4 SELECTED FINAL SET OF HYPER-PARAMETERS

Following has the final set of hyper-parameters we selected for reported results. We observed that reconstructing only node features was beneficial for MUTAG and PTC as they had node features. For other datasets, we only reconstructed adjacency matrices.

Hidden size	MUTAG	PTC-MR	IMDB-BIN	IMDB-MULTI	RED-BIN	RED-MULTI-5K
α	1e-6	1e-9	1e+3	10	1e+4	1e+4
γ	1e-6	1e-9	1e+3	10	1e+4	1e+4
C	10	10	1e+4	1	1e+3	1e+3
# epochs	20	30	40	30	50	50
Hidden size	128	512	512	512	32	32
Degree	No	No	Yes	Yes	No	No
Reconstruction	Node	Node	Adj	Adj	Adj	Adj

F MORE SAMPLE PLOTS FOR DISENTANGLEMENT ANALYSIS

F.1 SAMPLES FOR DISENTANGLEMENT BETWEEN GLOBAL AND LOCAL LATENT FACTORS SAMPLES FROM LEARNT POSTERIOR DISTRIBUTIONS BY GL-DISEN

Figure 5 provides more examples to showcase the ability of our proposed GL-Disen model's capability of producing mutually exclusive information for its global and local latents. This shows that GL-Disen actually can disentangle two latent factors.

F.2 SAMPLES FOR SHOWING THE SIMILARITY OF GLOBAL LATENT FACTORS ACROSS THE GRAPH COMPARED TO LOCAL LATENT FACTORS

In this section, we provide more qualitative proof that the latent factors our GL-Disen model maps as global are indeed globally common across the graph. Figure 6 and Figure 7 compares the pairwise similarity of global latent factors and local latent factors separately in two matrices for multiple different graphs from MUTAG dataset. We can see that compared to local level inter-node latent representation similarity, global level similarity is very high as the Mean Absolute pairwise difference is low.

Figure 5: Correlation matrices to show the dependence among global and local latent factors. Very low correlation close to 0.0 shows that these is very less correlation between these two factors. These sample graphs from MUTAG dataset showcase the capability of GL-Disen in producing mutually exclusive information for its global and local latent factors.

(a) Sample Graph 1

(b) Sample Graph 2

(c) Sample Graph 3

Figure 6: Part 1 : Mean Absolute Pairwise Difference among global latent factors and local latent factors for two graphs from MUTAG. These matrices clearly show that the inter-node latent representation difference for produced global latent factors is very low compared to local latent factors. This indicates the global factor representations disentangled by GL-Disen is indeed shared among the entire graph, unlike local factors which are local to certain nodes groups.

Figure 7: Part 2 : Mean Absolute Pairwise Difference among global latent factors and local latent factors for two graphs from MUTAG. These matrices clearly show that the inter-node latent representation difference for produced global latent factors is very low compared to local latent factors. This indicates the global factor representations disentangled by GL-Disen is indeed shared among the entire graph, unlike local factors which are local to certain nodes groups.