Improving Generalization in Meta-RL with Imaginary Tasks from Latent Dynamics Mixture

Abstract

The generalization ability of most meta-reinforcement learning (meta-RL) methods is largely limited to test tasks that are sampled from the same distribution as training tasks. To overcome the limit, we propose Latent Dynamics Mixture (LDM) that trains a reinforcement learning agent with imaginary tasks generated from mixtures of learned latent dynamics. By training a policy on mixture tasks along with original training tasks, LDM allows the agent to prepare for unseen test tasks and prevents the agent from overfitting the training tasks. LDM significantly outperforms standard meta-RL methods in test returns on gridworld navigation and MuJoCo tasks with strictly disjoint training and test task distributions.

1 Introduction

Overfitting and lack of generalization ability have been raised as the most critical problems of deep reinforcement learning (RL) [5, 8, 29, 32, 36, 45, 50]. Numbers of meta-reinforcement learning (meta-RL) methods have proposed solutions to the problems by training a policy that easily adapts to unseen but similar tasks. Meta-RL trains an agent in multiple sample tasks to construct an inductive bias over the shared structure across tasks. Most meta-RL works evaluate their agents on test tasks that are sampled from the same distribution used to sample training tasks. Therefore, the vulnerability of meta-RL to test-time distribution shift is hardly revealed [25, 28, 29].

One major category of meta-RL is gradient-based meta-RL that learns an initialization of a model such that few steps of policy gradient are sufficient to attain good performance in a new task [9, 34, 37, 38, 53]. Most of these methods require many rollouts for adaptation during a test that may be costly in real environments. Moreover, the networks are composed of feedforward networks that make online adaptation difficult.

Another major category of meta-RL is context-based meta-RL that tries to learn the tasks' structures by utilizing a recurrent or a memory-augmented model [6, 13, 22, 24, 31, 33, 47, 54]. These methods encode the experience collected into a context (or latent belief and model[1]) at each timestep. The policy conditioned on the context is trained to maximize the return. These methods have difficulties generalizing to unseen out-of-distribution (OOD) tasks mainly because of two reasons. (1) The process of encoding an unseen task dynamics into a context is not well generalized. (2) Even if the context for the unseen task is well encoded, the policy that has never been trained conditioned on the unseen context cannot interpret the context to output optimal actions.

We propose Latent Dynamics Mixture (LDM), a novel meta-RL method that overcomes the aforementioned limits and generalizes to strictly unseen test tasks without any additional test-time training. LDM is based on variational Bayes-adaptive meta-RL that meta-learns approximate inference on a

---

[1]We use the terms context, latent belief and latent model interchangeably.

| (a) $\mathcal{M}_{\text{train}}$ | (b) $\mathcal{M}_{\text{test}}$ | (c) Mean returns achieved at the N-th episode for each task. |

Figure 1: Gridworld example for the problem setup. **(a)** Training MDPs $\mathcal{M}_{\text{train}}$: a goal is located at one of the 18 shaded states. During training, the agent has to navigate to discover the unknown goal position randomly sampled at the beginning of each task. **(b)** Test MDPs $\mathcal{M}_{\text{test}}$: a test goal is located at one of the 27 shaded states disjoint to the set of training goals in **(a)**. The agent does not have access to the tasks in $\mathcal{M}_{\text{test}}$ during training. The solid lines and dashed lines represent examples of optimal paths with and without the knowledge of the true goals, respectively. $\circ$ and $\times$ symbols represent the initial state and the hidden goal state, respectively.

latent belief distribution over multiple reward and transition dynamics [54]. We generate imaginary tasks using mixtures of training tasks' meta-learned latent beliefs. By providing the agent with imaginary tasks during training, the agent can train its context encoder and policy given the context for unseen tasks that may appear during a test. Since LDM prepares for the test during training, it does not require additional updates during testing.

For example, let there be four types of training tasks, each of which must move east, north, west, and south. By mixing the two tasks of moving east and north, we may create a new task of moving northeast. By mixing the training tasks in different weights, we may create a set of tasks that covers the entire direction of $360°$.

We evaluate LDM and other meta-RL methods on the gridworld navigation tasks and MuJoCo meta-RL tasks, where we completely separate training task distribution and test task distribution. We show that LDM, without any prior knowledge on the test task distribution during training, achieves superior test returns compared to other meta-RL methods.

2 Problem Setup

Our work is motivated by the meta-learning setting of variBAD [54], therefore we follow most of the problem setup and notations except for a key difference that the test and training task distributions are strictly disjoint in our setup. A Markov decision process (MDP) $M = (\mathcal{S}, \mathcal{A}, R, T, T_0, \gamma, H)$ consists of a set of states $\mathcal{S}$, a set of actions $\mathcal{A}$, a reward function $R(r_{t+1}|s_t, a_t, s_{t+1})$, a transition function $T(s_{t+1}|s_t, a_t)$, an initial state distribution $T_0(s_0)$, a discount factor γ and a time horizon H.

During meta-training, a task (or a batch of tasks) is sampled following $p(M)$ over the set of MDPs $\mathcal{M}$ at every iteration. Each MDP $M_i = (\mathcal{S}, \mathcal{A}, R_i, T_i, T_0, \gamma, H)$ has individual reward function R_i (e.g., goal location) and transition function T_i (e.g., amount of friction), while sharing some general structures. We assume that the agent does not have access to the task index i, which determines the MDP. At meta-test, standard meta-RL methods evaluate agents on tasks sampled from the same distribution p that has been used for training. To evaluate the generalization ability of agents in environments unseen during training, we split $\mathcal{M}$ into two strictly disjoint training and test sets of MDPs, i.e., $\mathcal{M} = \mathcal{M}_{\text{train}} \cup \mathcal{M}_{\text{test}}$ and $\mathcal{M}_{\text{train}} \cap \mathcal{M}_{\text{test}} = \emptyset$. The agent does not have prior information about $\mathcal{M}_{\text{test}}$ and cannot interact in $\mathcal{M}_{\text{test}}$ during training.

Since the MDP is initially unknown, the best the agent can do is to update its belief $b_t(R, T)$ about the environment according to its experience $\tau_{:t} = \{s_0, a_0, r_1, s_1, a_1, r_2, \ldots, s_t\}$. According to the Bayesian RL formulation, the agent's belief about the reward and transition dynamics at timestep t can be formalized as a posterior over the MDP given the agent's trajectory, $b_t(R, T) = p(R, T|\tau_{:t})$. By augmenting the belief to the state, a Bayes-Adaptive MDP (BAMDP) can be constructed [7]. The agent's goal in a BAMDP is to maximize the expected return while exploring the environment by minimizing the uncertainty about the initially unknown MDP.

The inference and the posterior update problem in a BAMDP can be solved by combining meta-learning and approximate variational inference. An inference model encodes a low-dimensional

Figure 2: Imaginary task generation from latent dynamics mixture. We train n normal workers and a mixture worker in parallel. Each normal worker $W^{(i)}$ trains a shared policy network and a latent dynamics network on its sampled MDP $M^{(i)} \in \mathcal{M}_{\text{train}}$. A mixture model $\hat{m}_t$ is generated as a weighted sum of normal workers' latent models. We feed this mixture belief to the latent dynamics network's learned decoder to generate a new reward $\hat{r}_t$ and construct an imaginary task $\hat{M}$.

stochastic latent variable m to represent the posterior belief over the MDPs. The reward and transition dynamics can be formulated as shared functions across MDPs: $R(r_{t+1}|s_t, a_t, s_{t+1}; m)$ and $T(s_{t+1}|s_t, a_t; m)$. Then the problem of computing the posterior $p(R, T|\tau_{:t})$ becomes inferring the posterior $p(m|\tau_{:t})$ over m. By conditioning the policy on the posterior $p(m|\tau_{:t})$, an approximately Bayes-optimal policy can be obtained [54].

Refer to Figure 1 for the gridworld navigation example that is the same as the example used in variBAD except for the increased number of cells and that the task set $\mathcal{M}$ is divided into disjoint $\mathcal{M}_{\text{train}}$ and $\mathcal{M}_{\text{test}}$. A Bayes-optimal policy of an agent for a task in $\mathcal{M}_{\text{train}}$ first assigns a uniform prior to the goal states of $\mathcal{M}_{\text{train}}$ (Figure 1a) and then explores these states until it discovers a goal state as the dashed path in Figure 1a. If this agent, trained to solve the tasks in $\mathcal{M}_{\text{train}}$ only, is put in to solve a task in $\mathcal{M}_{\text{test}}$ without any prior knowledge (Figure 1b), the best policy an agent can take first is to maintain its initial belief learned in $\mathcal{M}_{\text{train}}$ and explore the goal states of $\mathcal{M}_{\text{train}}$. Once the agent realizes that there are no goal states in $\mathcal{M}_{\text{train}}$, it could start exploring the states that are not visited (i.e., $\mathcal{M} - \mathcal{M}_{\text{train}}$), and discover an unseen goal state in $\mathcal{M}_{\text{test}}$. However, it is unlikely that the agent trained only in $\mathcal{M}_{\text{train}}$ will encode the beliefs for unseen tasks accurately and explore the goal states of $\mathcal{M}_{\text{test}}$ efficiently without any prior knowledge or test-time adaptation.

3 Latent Dynamics Mixture

Our work aims to train an agent that is prepared for unseen test tasks (as in Figure 1b). We provide the agent during training with imaginary tasks generated by mixtures of training tasks' latent beliefs. By training the agent on the imaginary tasks, the agent learns to encode beliefs and to produce optimal policy given the beliefs for tasks not only in $\mathcal{M}_{\text{train}}$ but also for more general tasks that may appear during test.

Refer to Figure 2 for the entire process. We train n normal workers $W^{(1)}, \dots, W^{(n)}$ and a mixture worker $\hat{W}$ in parallel. For the convenience of explanation, we first focus on the case with only one mixture worker. At the beginning of every iteration, we sample n MDPs $M^{(1)}, \dots, M^{(n)}$ from $\mathcal{M}_{\text{train}}$ and assign each MDP $M^{(i)}$ to each normal worker $W^{(i)}$. All normal and mixture workers share a single policy network and a single latent dynamics network. Normal workers train a policy network and a latent dynamics network using true rewards from the environment. A mixture worker trains the policy network with imaginary rewards from the learned decoder's output given mixture beliefs.

3.1 Policy Network

Any type of recurrent network that can encode the past trajectory into a belief state b_t is sufficient for the policy network. We use an RL^2 [6] type of policy network (Figure 2). Each normal worker $W^{(i)}$

trains a recurrent Encoder-p (parameterized by ϕ_p) and a feedforward policy network (parameterized by ψ) to maximize the return for its assigned MDP $M^{(i)}$. A mixture worker trains the same policy network to maximize the return in an imaginary task $\hat{M}$ where the imaginary reward $\hat{r}_t$ is from the decoder given the mixture belief $\hat{m}_t$. Any online RL algorithm can be used to train the policy network. We use A2C for the gridworld and PPO [35] for MuJoCo tasks to optimize ϕ_p and ψ end-to-end.

3.2 Latent Dynamics Network

We use the same network structure and training methods of VAE introduced in variBAD [54] for our latent dynamics network (Figure 2). The only difference is that the policy network and the latent dynamics network do not share an encoder. Therefore Encoder-v (parameterized by ϕ_v) of the latent dynamics network does not need to encode the context necessary for the policy but only needs to encode the MDP dynamics into a low-dimensional stochastic latent model m. The latent dynamics network is not involved in the action selection of normal workers. We store trajectories from $\mathcal{M}_{\text{train}}$ in a buffer and use samples from the buffer to train the latent dynamics network offline. Each normal worker trains the latent dynamics network to decode the entire trajectory, including the future, to allow inference about unseen future transitions. In this work, we focus on MDPs where only reward dynamics varies [9, 10, 12, 13, 17, 25] and only train the reward decoder (parameterized by θ_R) as in [54]. The parameters ϕ_v and θ_R are optimized end-to-end to maximize the ELBO [19] using a reparameterization trick.

3.3 Imaginary Task Generation from Latent Dynamics Mixture

While training the policy network of the normal workers $W^{(1)}, \dots, W^{(n)}$ in parallel, we generate an imaginary latent model $\hat{m}_t$ as a randomly weighted sum of the latent models $m_t^{(1)}, \dots, m_t^{(n)}$ of the normal workers.

$$\hat{m}_t = \sum_{i=1}^{n} \alpha^{(i)} m_t^{(i)} \quad \text{and} \quad \alpha^{(1)}, \dots, \alpha^{(n)} \sim \beta \cdot \text{Dirichlet}(1, \dots, 1) - \frac{\beta - 1}{n}. \quad (1)$$

$\alpha^{(i)}$'s are the random mixture weights for each latent model. At the beginning of every iteration when the normal workers are assigned to new MDPs, we also sample new mixture weights fixed for that iteration. There are many distributions suitable for sampling mixture weights, and we use the Dirichlet distribution in Equation 1. β is a hyperparameter that controls the mixture's degree of extrapolation. The sum of mixture weights equals 1 regardless of the hyperparameter β. If $\beta = 1$, all $\alpha^{(i)}$'s are bounded between 0 and 1. Then the mixture model becomes a convex combination of the training models. If $\beta > 1$, the resulting mixture model may express extrapolated dynamics of training tasks. We find $\beta = 1.0$ suits best for most of our experiments among $\{0.5, 1.0, 1.5, 2.0, 2.5\}$ that we tried. Refer to Appendix B for environments where β larger than 1 can be effective.

A mixture worker interacts with an MDP sampled from $\mathcal{M}_{\text{train}}$, but we replace the environment reward with the imaginary reward $\hat{r}_t$ from the latent dynamics network's learned decoder. The decoder generates an imaginary reward $\hat{r}_t$ given the mixture model $\hat{m}_t$ and true states to construct a mixture task $\hat{M}$. A mixture worker trains the policy network to maximize the return for the imaginary task $\hat{M}$. We expect the imaginary task $\hat{M}$ to share some common structures with the training tasks because the mixture task is generated using the decoder that is trained to fit the training tasks' reward dynamics. On the other hand, the decoder can generate unseen rewards because we feed the decoder unseen mixture beliefs. Note that the mixture worker only trains the policy network but not the decoder with imaginary dynamics of $\hat{M}$.

Dropout of state and action input for the decoder As the latent dynamics network is trained for the tasks in $\mathcal{M}_{\text{train}}$, we find that the decoder easily overfits the state and action observations, ignoring the latent model m. Returning to the gridworld example, if we train the decoder with the tasks in $\mathcal{M}_{\text{train}}$ (Figure 1a), and feed the decoder one of the goal states in $\mathcal{M}_{\text{test}}$, the decoder refers to the next state input s_{i+1} only and always returns zero rewards regardless of the latent model m (Figure 4a). We apply dropout of rate p_{drop} to all inputs of decoder except the latent model m. It forces the decoder to refer to the latent model when predicting the reward and generate general mixture tasks. Refer to Appendix D for empirical analysis on the dropout rate.

Training the decoder with a single-step regression loss is generally less complex than training the policy network with a multi-step policy gradient loss. Therefore the decoder can be stably trained even with input dropout, generalizing better than the meta-trained policy. Refer to Appendix E for empirical results on the test-time generalization ability of the latent dynamics network.

3.4 Implementation Details

Multiple episodes of the same task in one iteration Following the setting of variBAD [54], we define an iteration as a sequence of N episodes of the same task and train the agent to act Bayes-optimally within the N rollout episodes (i.e., $H^+ = N \times H$ steps). After every N episodes (or H^+ steps), new tasks are sampled from $\mathcal{M}_{\text{train}}$ for the normal workers, and new mixture weights are sampled for the mixture worker. Then we can compare our method to other meta-RL methods that are designed to maximize the return after rollouts of many episodes.

Multiple mixture workers We may train more than one mixture worker at the same time by sampling different sets of mixture weights for each mixture worker. Increasing the ratio of mixture workers to normal workers may help the agent generalize to unseen tasks faster, but the normal workers may require more iterations to learn the optimal policies in $\mathcal{M}_{\text{train}}$. We train $n = 14$ normal workers and $\hat{n} = 2$ mixture workers in parallel unless otherwise stated. Refer to Appendix C for empirical analysis on the ratio of workers.

4 Related Work

4.1 Meta-Reinforcement Learning

Although context-based methods require a large amount of data for meta-training, they can learn within the task and make online adaptation. RL^2 [6] is the most simple, yet effective context-based model-free meta-RL method that utilizes a recurrent network to encode the experience into a policy. PEARL [33] integrates an off-policy meta-RL method with online probabilistic filtering of latent task variables to achieve high meta-training efficiency. MAML [9] learns an initialization such that a few steps of policy gradient is enough for the agent to adapt to a new test task. E-MAML and ProMP [34, 38] extends MAML by proposing exploration strategies for collecting rollouts for adaptation.

4.2 Bayesian Reinforcement Learning

Bayesian RL quantifies the uncertainty or the posterior belief over the MDPs using past experience. Conditioning on the environment's uncertainty, a Bayes-optimal policy can set the optimal balance between exploration and exploitation to maximize the return during training [1, 11, 18, 27]. In a Bayes-adaptive MDP (BAMDP), where the agent augments the state space of MDP with its belief, it is almost impossible to find the optimal policy due to the unknown parameterization and the intractable belief update. VariBAD [54] proposes an approximate but tractable solution that combines meta-learning and approximate variational inference. However, it is restricted to the setting where the training and test task distributions are almost the same. Furthermore, the learned latent model is only used as additional information for the policy. LDM uses the learned latent model more actively by creating mixture tasks to train the policy for more general test tasks out of training task distribution.

4.3 Curriculum, Goal and Task Generation

The idea of generating new tasks for RL is not new. Florensa et al. [10] proposes generative adversarial training to generate goals. Gupta et al. [12] proposes an automatic task design process based on mutual information. SimOpt [3] learns the randomization of simulation parameters based on a few real-world rollouts. POET and enhanced POET [43, 44] generate the terrain for a 2D walker given access to the environment parameters when generating a new task. Dream to Control [14] solves a long-horizon task using a latent-imagination. BIRD [52] learns from imaginary trajectories by maximizing the mutual information between imaginary and real trajectories. Chandak et al. [2] trains an agent to forecast the future tasks in non-stationary MDPs. Most of these works require prior knowledge or control of the environment parameters, or the pool of the generated tasks is restricted to the training task distribution.

4.4 Data-augmentation for Reinforcement Learning

Many image augmentation techniques such as random convolution, l2-regularization, dropout, batch normalization and noise injection are shown to improve the generalization of RL [5, 16, 21, 23, 48]. Mixreg [42] that applies the idea of mix-up [51] in RL, generates new training data as a convex interpolation of input observation and output reward. LDM can be thought of as a data-augmentation method in a way that it generates a mixture task using the data from training tasks. However, LDM generates a new task in the latent space with the latent model that fully encodes an MDP's dynamics. Instead of the pre-defined augmentation techniques with heuristics, we generate mixture tasks using the learned decoder, which contains the shared structure of the MDPs.

4.5 Out-of-distribution Meta-Reinforcement Learning

Some recent works aim to generalize RL to OOD tasks [8]. MIER [29] relabels past trajectories in a buffer during a test to generate synthetic train data suited for the test MDP. FLAP [30] learns a shared linear representation of the policy. To adapt to a new task FLAP only needs to predict a set of linear weights for fast adaptation. MetaGenRL [20] meta-learns an RL objective to train a randomly initialized policy on a test task. Most of these methods require experience from the test for additional training or updates for the network. AdMRL [25] performs adversarial virtual training with varying rewards. AdMRL assumes known reward space and parameterization, while LDM meta-learns.

5 Experiments

We evaluate LDM and other meta-RL methods on the gridworld example (Figure 1) and three MuJoCo meta-RL tasks [40]. We slightly modify the standard MuJoCo tasks by splitting the task space $\mathcal{M}$ into disjoint $\mathcal{M}_{\text{train}}$ and $\mathcal{M}_{\text{test}}$. We use RL^2 [6] and variBAD [54] as baselines representing context-based meta-RL methods. We use E-MAML [38] and ProMP [34] as baselines representing gradient-based meta-RL methods. We implement RL^2-based Mixreg [42] to evaluate the difference between generating mixture tasks in the latent space and the observation space.

All methods are trained on tasks sampled from $\mathcal{M}_{\text{train}}$ uniformly at random, except for the oracle methods that are trained on tasks in the entire task set $\mathcal{M} = \mathcal{M}_{\text{train}} \cup \mathcal{M}_{\text{test}}$. Note that the oracle performance is only for reference and can not be achieved by any non-oracle methods theoretically. Non-oracle methods without prior knowledge on $\mathcal{M}_{\text{test}}$ require additional exploration during testing to infer the changes from $\mathcal{M}_{\text{train}}$, whereas the oracle agent can exploit the knowledge of the test distribution. In the gridworld example, the oracle agent can search for goals in $\mathcal{M}_{\text{test}}$ before navigating the outermost goal states of $\mathcal{M}_{\text{train}}$. Therefore the main focus should be on the relative improvement of LDM compared to non-oracle methods, bridging the gap between the oracle and the non-oracle methods. We report a mean of 4 random seeds and apply a moving average of window size 5 for all results. Shaded areas indicate standard deviations for all plots. Refer to Appendix A for the details of implementations and hyperparameters. The supplementary file contains our reference implementation of LDM.

5.1 Gridworld Navigation

Experimental setup   We use the gridworld navigation task introduced in Figure 1. The agent is allowed 5 actions: up, down, left, right, and stay. The agent receives a reward 1 for reaching or staying at the hidden goal and receives a reward -0.1 for all other transitions. Each episode lasts for $H = 30$ steps. All baselines are given $N = 4$ rollout episodes for a fixed task except for ProMP and E-MAML that are given $N = 20$ rollouts. Such choice of N follows from the reference implementations of the baselines. The time horizon has been carefully set so that the agent can not visit all states within the first episode but can visit them within two episodes. If a rollout is over, the agent is reset to the origin. The optimal policy is to search for the hidden goal and stay at the goal or return to the goal as quickly as possible. After N episodes ($H^+ = N \times H$ steps), a new task is sampled from $\mathcal{M}_{\text{train}}$ uniformly at random. The reward decoder requires only the latent model and the next state as input for this task. We apply dropout with the rate $p_{\text{drop}} = 0.7$ to the next state input of the reward decoder. Refer to Appendix D for the results with different dropout rates.

Figure 3: Results for the gridworld task evaluated at the N-th episode in terms of the mean returns in $\mathcal{M}_{\text{train}}$ and $\mathcal{M}_{\text{test}}$, and the number of tasks in $\mathcal{M}_{\text{test}}$ in which the agent fails to reach the goal.

Figure 4: Examples of mixture tasks generated by LDM. **First row**: Mixture weights ($\alpha^{(i)}$) multiplied to the latent models ($m_{H+}^{(i)}$) at the end of each training task (Equation 1). When the same training tasks are sampled multiple times, we plot the sum of weights. **Second row** (reward map): decoder output for each next state conditioned on the mixture weights from the first row. A cross mark denotes the state with the maximum mixture reward.

Results   Except for ProMP and E-MAML that use feedforward network, all the baseline methods achieve the same optimal performance in $\mathcal{M}_{\text{train}}$ at the N-th episode (Figure 3). However, our method outperforms the non-oracle baselines in $\mathcal{M}_{\text{test}}$. Out of the 27 tasks in $\mathcal{M}_{\text{test}}$, our agent succeeds to visit the goals in 19 tasks on average. There is only one goal state in $\mathcal{M}_{\text{test}}$ that all four seeds of LDM fail to reach (Figure 1c). Although LDM still does not reach 8 test goals on average, considering that there is no prior information on the test distribution and that the optimal policy for $\mathcal{M}_{\text{train}}$ does not visit most of the states in $\mathcal{M}_{\text{test}}$, the improvement of LDM over RL[2] and variBAD is significant. RL[2] achieves a high test return initially, but as the policy overfits the training tasks, its test return decays. VariBAD achieves high returns in $\mathcal{M}_{\text{train}}$, but fails to generalize in most of the tasks in $\mathcal{M}_{\text{test}}$. Mixreg performs better than RL[2], but does not match LDM.

Refer to Figure 6a for example of LDM behavior for a task in $\mathcal{M}_{\text{test}}$ that was introduced in Figure 1a. The agent searches for a goal in $\mathcal{M}_{\text{train}}$ first. Once it explores all the goal states in $\mathcal{M}_{\text{train}}$, it starts to search for the goals in $\mathcal{M}_{\text{test}}$. From the second episode, the agent directly heads to the goal based on the context made from the first episode. Note that the initial prior is nonzero even for the goals in $\mathcal{M}_{\text{test}}$ due to the dropout applied to the decoder's state input.

Tasks generated by LDM   We present an empirical analysis in Figure 4 to verify that LDM indeed generates meaningful new tasks that are helpful in solving the test tasks. Without prior knowledge or interaction with $\mathcal{M}_{\text{test}}$, it is impossible to create exactly the same reward maps of $\mathcal{M}_{\text{test}}$. But the reward maps in Figure 4c,d,e are sufficient to induce exploration toward the goal states of $\mathcal{M}_{\text{test}}$. Due to the dropout applied to the next state input of the decoder, the decoder assigns high rewards to some goals that belong to $\mathcal{M}_{\text{test}}$. Note that the decoder does not generalize without dropout therefore assigns high rewards only to training goals (Figure 4a).

Figure 5: Mean returns at the N-th episodes in $\mathcal{M}_{\text{eval}}$ of three MuJoCo tasks.

Table 1: Set of training, test and evaluation tasks of Mujoco tasks. $k \in \{0, 1, 2, 3\}$.

	Ant-direction θ	Ant-goal r	θ	Half-cheetah-velocity v
$\mathcal{M}_{\text{train}}$	$90° \times k$	$[0.0, 1.0) \cup [2.5, 3.0)$	$[0°, 360°)$	$[0.0, 0.5) \cup [3.0, 3.5)$
$\mathcal{M}_{\text{test}}$	$90° \times k + 45°$	$[1.0, 2.5)$	$[0°, 360°)$	$[0.5, 3.0)$
$\mathcal{M}_{\text{eval}}$	$90° \times k + 45°$	1.75	$90° \times k$	$\{0.75, 1.25, 1.75, 2.25, 2.75\}$

5.2 MuJoCo

Experimental setup We evaluate our agent and baselines on three standard MuJoCo domains (Ant-direction, Ant-goal, and Half-cheetah-velocity) to verify how effective LDM is for continuous control tasks. We evaluate the agents on a fixed set of evaluation tasks $\mathcal{M}_{\text{eval}} \subset \mathcal{M}_{\text{test}}$ for each domain to ensure the test result is not affected by the sampling of evaluation tasks (Table 1). ProMP and E-MAML are given $N = 20$ rollout episodes per task, and all other methods are given $N = 2$. $H = 200$ steps for each episode of all MuJoCo tasks. For MuJoCo tasks we report the results of PEARL [33] for $N = 3$. Because PEARL uses an off-policy RL algorithm, the performance converges with much less training data. We report the converged asymptotic performance of PEARL after 5 million steps of environment interaction. We set LDM's $p_{\text{drop}} = 0.5$ for all MuJoCo tasks.

Ant-direction We construct the Ant-direction task based on the example discussed in the introduction. θ denotes the angle of the target direction from the origin. A major component of the reward is the dot product of the target direction and the agent's velocity.

Ant-goal We construct the Ant-goal task similar to the gridworld task, where the agent has to reach the unknown goal position. The training task distribution $\mathcal{M}_{\text{train}}$ (shaded region of Figure 6c) is continuous, unlike the gridworld and Ant-direction tasks. r and θ denote the radius and angle of the goal from the origin, respectively. A major component of the reward is the negative value of the taxicab distance between the agent and the goal. We set $\beta = 2$ because LDM with $\beta = 1$ generates goals near the origin mostly due to the symmetry of training tasks. Refer to Appendix B for a detailed analysis regarding the choice of β. One may argue that the training and test tasks are not disjoint because the agent passes through the goal states of $\mathcal{M}_{\text{test}}$ momentarily while learning to solve $\mathcal{M}_{\text{train}}$. However, the task inference with the unseen rewards from $\mathcal{M}_{\text{test}}$, and the policy to stay at the goal state of $\mathcal{M}_{\text{test}}$ until the end of the time horizon cannot be learned during training.

Half-cheetah-velocity We train the Half-cheetah agent to match the target velocity sampled from the two distributions at extremes and test for target velocities in between. This task is relatively easier than the previous Ant tasks due to the reduced dimension of the task space. Therefore we train more mixture workers than the other tasks, training $n = 12$ normal workers and $\hat{n} = 4$ mixture workers in parallel. Refer to Appendix C for additional results with different numbers of mixture workers. The target velocity is v, where the velocity is measured as a change of position per second (or 20 environment steps). A major component of the reward is the negative value of the difference between the target velocity and the agent's velocity. Similar to Ant-Goal, although the test velocities in $\mathcal{M}_{\text{test}}$ are achieved momentarily in the process of reaching a target velocity in $[3.0, 3.5)$, the agent does not learn to maintain the target velocities in $\mathcal{M}_{\text{test}}$ during training.

(a) Sample trajectory of LDM for 4 rollout episodes. The red shade denotes decoder output for each state conditioned on the online context.

(b) Ant-drection, 4 trajectories from $\mathcal{M}_{\text{eval}}$.

(c) Ant-goal, 4 trajectories from $\mathcal{M}_{\text{eval}}$.

(d) Half-cheetah-velocity, 5 trajectories from $\mathcal{M}_{\text{eval}}$.

Figure 6: Example trajectories of the agents in $\mathcal{M}_{\text{eval}}$. We illustrate the behavior at the N-th episode as colored paths. The targets of $\mathcal{M}_{\text{eval}}$ are indicated as dashed lines or cross marks

Results Refer to Figure 5 for the test returns in $\mathcal{M}_{\text{eval}}$. LDM outperforms the non-oracle baselines at the N-th episode. VariBAD oracle achieves the best test return for all MuJoCo tests, revealing the strength of variBAD's task inference ability for tasks seen during training. However, the non-oracle variBAD has difficulty generalizing to $\mathcal{M}_{\text{test}}$. The performance of Mixreg is lower than that of RL^2, which reveals the limitation of mixing in complex observation space. In all MuJoCo tasks, the agent can infer the true task dynamics using the reward at every timestep, even at the first step of an episode. Therefore gradient-based methods with feedforward networks also make progress, unlike the gridworld task. Because PEARL is designed to collect data for the first two episodes, it achieves low returns before the N-th episode. Even after accumulating context, the policy of PEARL is not prepared for the unseen contexts in Ant-direction and Half-cheetah-velocity. Refer to Appendix F for additional experimental results on the test returns at the first rollout episode and the training returns.

Because LDM is not trained in $\mathcal{M}_{\text{test}}$, it can not solve the target tasks optimally from the beginning of each task in the Ant-direction and Ant-goal tasks, unlike variBAD Oracle (Figure 6b and 6c). However, LDM reaches the target direction or goal close enough after a sufficiently small amount of exploration, unlike RL^2. For the Half-cheetah-velocity task, LDM generates well-separated policies compared to RL^2 (Figure 6d). Refer to Appendix F for returns and trajectories on training tasks.

6 Conclusion

We propose Latent Dynamics Mixture to improve the generalization ability of meta-RL by training policy with generated imaginary tasks. LDM generates imaginary mixture tasks that can generalize to unseen test tasks without additional test-time training. Our method outperforms baseline meta-RL methods in experiments with strictly disjoint training and test task distributions, even reaching the oracle performance in some tasks. Because the latent dynamics network is independent of the policy network, we expect LDM to make orthogonal contributions when combined with not only RL^2 but most of the meta-RL methods.

We believe that our work can be a starting point for many interesting future works. For example, instead of a heuristic weight-sampling for generating the mixture, we may incorporate OOD generation techniques in the latent space. Another extension is to train the latent dynamics network to decode not only the reward but also the state transition dynamics. Then we can generate a purely imaginary task without additional environment interaction.

References

[1] A. R. Cassandra, L. P. Kaelbling, and M. L. Littman. Acting optimally in partially observable stochastic domains. In *National Conference on Artificial Intelligence*, 1994.

[2] Y. Chandak, G. Theocharous, S. Shankar, M. White, S. Mahadevan, and P. Thomas. Optimizing for the future in non-stationary mdps. In *International Conference on Machine Learning, (ICML)*, pages 119:1414–1425, 2020.

[3] Y. Chebotar, A. Handa, V. Makoviychuk, M. Macklin, J. Issac, N. D. Ratliff, and D. Fox. Closing the sim-to-real loop: Adapting simulation randomization with real world experience. In *International Conference on Robotics and Automation, (ICRA)*, pages 8973–8979, 2019.

[4] B. Chen, W. Deng, and H. Shen. Virtual class enhanced discriminative embedding learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 31:1942–1952, 2018.

[5] K. Cobbe, O. Klimov, C. Hesse, T. Kim, and J. Schulman. Quantifying generalization in reinforcement learning. In *International Conference on Machine Learning, (ICML)*, pages 97:1282–1289, 2019.

[6] Y. Duan, J. Schulman, X. Chen, P. L. Bartlett, I. Sutskever, and P. Abbeel. RL^2: Fast reinforcement learning via slow reinforcement learning. *arXiv preprint arXiv: 1611.02779*, 2016.

[7] M. O. Duff. *Optimal Learning: Computational Procedures for Bayes-adaptive Markov Decision Processes*. University of Massachusetts at Amherst, 2002.

[8] R. Fakoor, P. Chaudhari, S. Soatto, and A. J. Smola. Meta-q-learning. In *International Conference on Learning Representations, (ICLR)*, 2020.

[9] C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning, (ICML)*, pages 70:1126–1135, 2017.

[10] C. Florensa, D. Held, X. Geng, and P. Abbeel. Automatic goal generation for reinforcement learning agents. In *International Conference on Machine Learning (ICML)*, pages 80:1515–1528, 2018.

[11] M. Ghavamzadeh, S. Mannor, J. Pineau, and A. Tamar. Bayesian reinforcement learning: A survey. *Found. Trends Mach. Learn.*, pages 8(5–6):359–483, 2015.

[12] A. Gupta, B. Eysenbach, C. Finn, and S. Levine. Unsupervised meta-learning for reinforcement learning. *arXiv preprint arXiv: 1806.04640*, 2018.

[13] A. Gupta, R. Mendonca, Y. Liu, P. Abbeel, and S. Levine. Meta-reinforcement learning of structured exploration strategies. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 31:5302–5311, 2018.

[14] D. Hafner, T. P. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations, (ICLR)*, 2020.

[15] J. Humplik, A. Galashov, L. Hasenclever, P. A. Ortega, Y. W. Teh, and N. Heess. Meta reinforcement learning as task inference. *arXiv preprint arXiv: 1905.06424*, 2019.

[16] M. Igl, K. Ciosek, Y. Li, S. Tschiatschek, C. Zhang, S. Devlin, and K. Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. In *Neural Information Processing Systems (NeurIPS)*, pages 32:13978–13990, 2019.

[17] A. Jabri, K. Hsu, B. Eysenbach, A. Gupta, S. Levine, and C. Finn. Unsupervised curricula for visual meta-reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, 2019.

[18] L. P. Kaelbling, M. L. Littman, and A. R. Cassandra. Planning and acting in partially observable stochastic domains. *Artificial Intelligence*, 101:99–134, 1998.

[19] D. P. Kingma and M. Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations (ICLR)*, 2014.

[20] L. Kirsch, S. van Steenkiste, and J. Schmidhuber. Improving generalization in meta reinforcement learning using learned objectives. In *International Conference on Learning Representations, (ICLR)*, 2020.

[21] M. Laskin, K. Lee, A. Stooke, L. Pinto, P. Abbeel, and A. Srinivas. Reinforcement learning with augmented data. In *Neural Information Processing Systems (NeurIPS)*, 2020.

[22] A. X. Lee, A. Nagabandi, P. Abbeel, and S. Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[23] K. Lee, K. Lee, J. Shin, and H. Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. In *International Conference on Learning Representations, (ICLR)*, 2020.

[24] K. Lee, Y. Seo, S. Lee, H. Lee, and J. Shin. Context-aware dynamics model for generalization in model-based reinforcement learning. In *International Conference on Machine Learning, (ICML)*, pages 119:5757–5766, 2020.

[25] Z. Lin, G. Thomas, G. Yang, and T. Ma. Model-based adversarial meta-reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 33:10161–10173, 2020.

[26] S. Liu, A. J. Davison, and E. Johns. Self-supervised generalisation with meta auxiliary learning. In *Neural Information Processing Systems (NeurIPS)*, pages 1679–1689, 2019.

[27] J. J. Martin. *Bayesian Decision Problems and Markov Chains*. Wiley, 1967.

[28] B. Mehta, T. Deleu, S. C. Raparthy, C. J. Pal, and L. Paull. Curriculum in gradient-based meta-reinforcement learning. *arXiv preprint arXiv:2002.07956*, 2020.

[29] R. Mendonca, X. Geng, C. Finn, and S. Levine. Meta-reinforcement learning robust to distributional shift via model identification and experience relabeling. *arXiv preprint arXiv: 2006.07178*, 2020.

[30] M. Peng, B. Zhu, and J. Jiao. Linear representation meta-reinforcement learning for instant adaptation. *arXiv preprint arXiv: 2101.04750*, 2021.

[31] R. Raileanu, M. Goldstein, A. Szlam, and R. Fergus. Fast adaptation to new environments via policy-dynamics value functions. In *International Conference on Machine Learning, (ICML)*, pages 119:7920–7931, 2020.

[32] A. Rajeswaran, K. Lowrey, E. Todorov, and S. M. Kakade. Towards generalization and simplicity in continuous control. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 30:6550–6561, 2017.

[33] K. Rakelly, A. Zhou, C. Finn, S. Levine, and D. Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *International Conference on Machine Learning, (ICML)*, pages 97:5331–5340, 2019.

[34] J. Rothfuss, D. Lee, I. Clavera, T. Asfour, and P. Abbeel. Promp: Proximal meta-policy search. In *International Conference on Learning Representations, (ICLR)*, 2019.

[35] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv: 1707.06347*, 2017.

[36] X. Song, Y. Jiang, S. Tu, Y. Du, and B. Neyshabur. Observational overfitting in reinforcement learning. In *International Conference on Learning Representations, (ICLR)*, 2020.

[37] Y. Song, A. Mavalankar, W. Sun, and S. Gao. Provably efficient model-based policy adaptation. In *International Conference on Machine Learning (ICML)*, pages 119:9088–9098, 2020.

[38] B. C. Stadie, G. Yang, R. Houthooft, X. Chen, Y. Duan, Y. Wu, P. Abbeel, and I. Sutskever. The importance of sampling in meta-reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 31:9280–9290, 2018.

[39] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *International Conference on Intelligent Robots and Systems (IROS)*, pages 23–30, 2017.

[40] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *International Conference on Intelligent Robots and Systems (IROS)*, pages 5026–5033, 2012.

[41] J. X. Wang, Z. Kurth-Nelson, D. Tirumala, H. Soyer, J. Z. Leibo, R. Munos, C. Blundell, D. Kumaran, and M. Botvinick. Learning to reinforcement learn. In *Annual Meeting of the Cognitive Science Community (CogSci)*, 2016.

[42] K. Wang, B. Kang, J. Shao, and J. Feng. Improving generalization in reinforcement learning with mixture regularization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[43] R. Wang, J. Lehman, J. Clune, and K. O. Stanley. Paired open-ended trailblazer (POET): endlessly generating increasingly complex and diverse learning environments and their solutions. *arXiv preprint arXiv: 1901.01753*, 2019.

[44] R. Wang, J. Lehman, A. Rawal, J. Zhi, Y. Li, J. Clune, and K. Stanley. Enhanced poet: Open-ended reinforcement learning through unbounded invention of learning challenges and their solutions. In *International Conference on Machine Learning, (ICML)*, pages 119:9940–9951, 2020.

[45] S. Whiteson, B. Tanner, M. E. Taylor, and P. Stone. Protecting against evaluation overfitting in empirical reinforcement learning. In *IEEE Symposium on Adaptive Dynamic Programming and Reinforcement Learning (ADPRL)*, pages 120–127, 2011.

[46] A. Xie, J. Harrison, and C. Finn. Deep reinforcement learning amidst lifelong non-stationarity. *arXiv preprint arXiv: 2006.10701*, 2020.

[47] J. Yang, B. K. Petersen, H. Zha, and D. Faissol. Single episode policy transfer in reinforcement learning. In *International Conference on Learning Representations, (ICLR)*, 2020.

[48] D. Yarats, I. Kostrikov, and R. Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *International Conference on Learning Representations, (ICLR)*, 2021.

[49] M. Yin, G. Tucker, M. Zhou, S. Levine, and C. Finn. Meta-learning without memorization. In *International Conference on Learning Representations, (ICLR)*, 2020.

[50] C. Zhang, O. Vinyals, R. Munos, and S. Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv: 1804.06893*, 2018.

[51] H. Zhang, M. Cissé, Y. N. Dauphin, and D. Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations, (ICLR)*, 2018.

[52] G. Zhu, M. Zhang, H. Lee, and C. Zhang. Bridging imagination and reality for model-based deep reinforcement learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[53] L. M. Zintgraf, K. Shiarlis, V. Kurin, K. Hofmann, and S. Whiteson. Fast context adaptation via meta-learning. In *International Conference on Machine Learning, (ICML)*, pages 97:7693–7702, 2019.

[54] L. M. Zintgraf, K. Shiarlis, M. Igl, S. Schulze, Y. Gal, K. Hofmann, and S. Whiteson. Varibad: A very good method for bayes-adaptive deep RL via meta-learning. In *International Conference on Learning Representations, (ICLR)*, 2020.