Proximal Learning With Opponent-Learning Awareness

Abstract

Learning With Opponent-Learning Awareness (LOLA) (Foerster et al. [2018a]) is a
multi-agent reinforcement learning algorithm that typically learns reciprocity-based
cooperation in partially competitive environments. However, LOLA often fails
to learn such behaviour on more complex policy spaces parameterized by neural
networks, partly because the update rule is sensitive to the policy parameterization.
This problem is especially pronounced in the opponent modeling setting, where
the opponent's policy is unknown and must be inferred from observations; in such
settings, LOLA is ill-specified because behaviourally equivalent opponent policies
can result in non-equivalent updates. To address this shortcoming, we reinterpret
LOLA as approximating a proximal operator, and then derive a new algorithm,
Proximal LOLA (POLA), which uses the proximal formulation directly. Unlike
LOLA, the POLA updates are parameterization invariant, in the sense that when the
proximal objective has a unique optimum, behaviourally equivalent policies result
in behaviourally equivalent updates. We then present practical approximations
to the ideal POLA update. We evaluate these approximations in several partially
competitive environments with function approximation and opponent modeling,
empirically demonstrating POLA achieves reciprocity-based cooperation more
reliably than LOLA.

1 Introduction

As autonomous learning agents become more integrated into society, it is increasingly important to
ensure these agents' interactions produce socially beneficial outcomes. One step in this direction is
ensuring agents are able to navigate social dilemmas [Dawes, 1980]. Foerster et al. [2018a] showed
that simple applications of independent RL (reinforcement learning) to social dilemmas usually result
in suboptimal outcomes from a social welfare perspective. To address this, they introduce *Learning
With Opponent-Learning Awareness* (LOLA), which actively shapes the learning step of other agents.
LOLA with tabular policies learns *tit-for-tat* (TFT), i.e. reciprocity-based cooperation, in the iterated
prisoner's dilemma (IPD), a 2-agent social dilemma.

However, for the same IPD setting, we show that LOLA with policies parameterized by neural
networks often converges to the Pareto suboptimal equilibria of unconditional defection. This shows
that the learning outcome for LOLA is highly dependent on *policy parameterization*, one factor that
makes LOLA difficult to scale to higher dimensional settings. This problem is especially pronounced
in the *opponent modeling* setting, where the opponent's policy is *unknown* and must be inferred
from observations; in such settings, LOLA is ill-specified because behaviourally equivalent opponent
policies can result in non-equivalent updates and hence learning outcomes.

To address these issues, we build on ideas from proximal algorithms [Parikh and Boyd, 2014],
reinterpreting LOLA as an approximation of a proximal operator, and then devise a new algorithm,

Figure 1: In the IPD (Section 4.1), we initialize two neural networks using the same architecture with different weights that produce the same policy, and plot the probability of cooperation in 4 states (DD, DC, CD, CC) after a single update of LOLA and *outer POLA* (Section 3.3). Left: using LOLA; comparing circles to crosses, the different policy parameterizations result in very different updated policies despite the same starting policies and hyperparameters. Right: using *outer POLA*; the two updated policies are much more similar.

Proximal LOLA (POLA), which uses this proximal formulation directly. POLA replaces the gradient updates in LOLA with proximal operators based on a *proximity penalty* in policy space, which makes POLA invariant to policy parameterization. When the proximal objective has a unique optimum, behaviourally equivalent policies result in behaviourally equivalent updates.

Solving for the exact POLA update is usually intractable, so we also provide practical algorithms that rely on approximate versions of the POLA update. We show empirically that our algorithms learn reciprocity-based cooperation with significantly higher probability than LOLA in several settings with *function approximation* and also provide results on the combination of opponent modeling and function approximation.

Figure 1 illustrates our core idea: LOLA is sensitive to policy parameterization, whereas POLA is not. We compare the same policy parameterized by two different sets of weights in the same neural network architecture in the IPD, showing that our approximation to the POLA update is largely parameterization independent, while the LOLA update varies depending on parameterization.

For reproducibility, our code is available at this anonymous repo: `https://anonymous.4open. science/r/pola-B8DF/`.

2 Background

2.1 Reinforcement Learning

We consider the standard fully-observable reinforcement learning and Markov Game formulation:

An N-agent fully observable Markov Game $\mathcal{M}$ is defined as the tuple $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{T}, \mathcal{R}, \gamma \rangle$, where $\mathcal{S}$ is the state space, $\mathcal{A} = \{A_1, ..., A_N\}$ is a set of action spaces, where $\mathcal{A}_i$ for $i \in \{1, ..., N\}$ denotes the action space for agent i, $\mathcal{T} : \mathcal{S} \times \mathcal{A}_1 \times ... \times \mathcal{A}_N \to \mathcal{P}(\mathcal{S})$ is a transition function mapping from states and actions to a probability distribution over next states, $\mathcal{R} = \{\mathcal{R}_1, ..., \mathcal{R}_N\}$ is a set of reward functions, where $\mathcal{R}_i : \mathcal{S} \times \mathcal{A}_1 \times ... \times \mathcal{A}_N \to \mathbb{R}$ denotes the reward function for agent i, and $\gamma \in \mathbb{R}$ is a discount factor. Each agent acts according to a policy $\pi_{\theta^i} : \mathcal{S} \to \mathcal{P}(\mathcal{A}_i)$, with parameters θ^i.

Let $\boldsymbol{\theta}$ be the concatenation of each of the individual θ^i (so for $N = 2, \boldsymbol{\theta} = \{\theta^1, \theta^2\}$) and $\pi_{\boldsymbol{\theta}}$ be the concatenation of each of the individual π_{θ^i}. Each agent's objective is to maximize its discounted expected return: $J^i(\pi_{\boldsymbol{\theta}}) = \mathbb{E}_{s \sim P(\mathcal{S}), \mathbf{a} \sim \pi_{\boldsymbol{\theta}}} \left[\sum_{t=0}^{T} \gamma^t r_t^i \right]$ where $\mathbf{a} \sim \pi_{\boldsymbol{\theta}}$ is a joint action $\mathbf{a} = \{a_1, ..., a_N\} \in \mathcal{A}_1 \times ... \times \mathcal{A}_n$ drawn from the policies $\pi_{\boldsymbol{\theta}}$ given the current state $s \in \mathcal{S}$, $P(\mathcal{S})$ is the probability distribution over states given the current policies and transition function, r_t^i denotes the reward achieved by agent i at time step t as defined by the reward function $\mathcal{R}_i$ and $T \in \mathbb{N}$ is the total time horizon or episode length. Throughout this paper, we assume all states are visited with non-zero probability. This is true in practice with stochastic policies, which we use throughout our experiments.

Let $L^i(\pi_{\boldsymbol{\theta}}) = -J^i(\pi_{\boldsymbol{\theta}})$. Each agent's objective is equivalently formulated as minimizing $L^i(\pi_{\boldsymbol{\theta}})$. We use this as it better aligns with standard optimization frameworks. Throughout this paper, we

consider the $N = 2$ case, and for ease of exposition, consider updates from the perspective of agent 1. Updates for agent 2 follow the same structure, but with agents 1 and 2 swapped.

2.2 Reciprocity-Based Cooperation

Reciprocity-based cooperation refers to cooperation *iff* others cooperate. Unlike unconditional cooperation, this encourages other self-interested learning agents to cooperate. One well-known example is the *tit-for-tat* (TFT) strategy in the IPD [Axelrod and Hamilton, 1981]. At each time step in the IPD, agents cooperate (C) or defect (D). Defecting always provides a higher individual reward compared to cooperating for the given time step, but both agents are better off when both cooperate than when both defect. The game is played repeatedly with a low probability of termination at each time step, which is modeled by the discount factor γ in RL. TFT agents begin by cooperating, then cooperate *iff* the opponent cooperated at the previous time step. Against a TFT agent, the best strategy for a self-interested agent is to cooperate at every time step. Other examples of reciprocity-based cooperation include contributing to a common good when others contribute, or reciprocating by collecting only resources that do not harm others (such as in Section 4.3). Crucially, *unconditional cooperation*, for example in the single step prisoner's dilemma or against defecting opponents in the IPD, is usually a *dominated strategy* and thus not a desired learning outcome.

2.3 Learning with Opponent-Learning Awareness (LOLA)

LOLA [Foerster et al., 2018a] introduces *opponent shaping* via a gradient based approach. Instead of optimizing for $L^1(\pi_{\theta^1}, \pi_{\theta^2})$, i.e. the loss for agent 1 given the policy parameters (θ^1, θ^2), agent 1 optimizes for $L^1(\pi_{\theta^1}, \pi_{\theta^2 - \Delta\theta^2(\theta^1)})$, the loss for agent 1 after agent 2 updates its policy with one naive learning (NL) gradient step $\Delta\theta^2(\theta^1) = \eta\nabla_{\theta^2}L^2(\pi_{\theta^1}, \pi_{\theta^2})$, where η is the opponent's learning rate. Importantly, $\Delta\theta^2$ is treated as a function of θ^1, and LOLA differentiates through the update $\Delta\theta^2(\theta^1)$ when agent 1 optimizes for $L^1(\pi_{\theta^1}, \pi_{\theta^2})$. Appendix A.1 provides more detail, including a pseudo-algorithm for LOLA. Foerster et al. [2018a] also provide a policy gradient formulation for use with environment rollouts when the loss cannot be calculated exactly, and use opponent modeling to avoid needing access to the opponent's policy parameters.

In the IPD with tabular policies, LOLA agents learn a TFT strategy, with high probability cooperating when the other agent cooperates and defecting when the other defects [Foerster et al., 2018a]. Thus, LOLA showed that self-interested reinforcement learning agents can learn policies that lead to socially optimal outcomes in the IPD.

2.4 Proximal Point Method

Following Parikh and Boyd [2014], define the proximal operator $\text{prox}_{\lambda f} : \mathbb{R}^n \to \mathbb{R}^n$ of a closed proper convex function f as:

$$\text{prox}_{\lambda f}(v) = \arg\min_x \left(f(x) + \frac{1}{2\lambda}||x - v||_2^2 \right)$$

where $||\cdot||_2$ is the Euclidean (L2) norm and λ is a hyperparameter. If f is differentiable, its first-order approximation near v is:

$$\hat{f}_v^{(1)}(x) = f(v) + \nabla f(v)^T(x - v)$$

The proximal operator of the first-order approximation is:

$$\text{prox}_{\hat{f}_v^{(1)}}(v) = \arg\min_x \left(f(v) + \nabla f(v)^T(x - v) + \frac{1}{2\lambda}||x - v||_2^2 \right) = v - \lambda\nabla f(v)$$

which is a standard gradient step on the original function $f(v)$ with step size λ.

The proximal point method starts with an iterate x_0, then for each time step $t \in \{1, 2, ...\}$, calculates a new iterate $x_t = \text{prox}_{\lambda f}(x_{t-1})$. Gradient descent is equivalent to using the proximal point method with a first-order approximation of f.

3 Proximal LOLA (POLA)

In this section, we first explore how LOLA is sensitive to different types of changes in policy parameterization (Section 3.1). To design a method invariant to all such changes, we introduce an idealized version of POLA (Section 3.2). Lastly, we present approximations that form the basis of practical algorithms (Sections 3.3, 3.4).

3.1 Sensitivity to Policy Parameterization

LOLA is sensitive to policy parameterization, as it is defined in terms of (Euclidean) gradients, which are not invariant to smooth transformations of the parameters. Parameterization affects not only the convergence rate, but also which equilibrium is reached. We start with a simple toy example to illustrate this phenomenon. Consider the case of tabular policies with one time step of memory for the IPD. There are five possible states: DD (both agents last defected), DC (agent 1 defected while agent 2 cooperated), CD (agent 1 cooperated, agent 2 defected), CC (both agents last cooperated), and the starting state. For each agent $i \in \{1, 2\}$, $\theta^i \in \mathbb{R}^5$ parameterizes a tabular policy over these 5 states, so that $\pi_{\theta^i}(s) = \text{sigmoid}(\theta^i)[s]$, where $v[s]$ denotes the element of vector v corresponding to state s. We apply the transformation $\mathbf{Q}^i \theta^i$ where:

$$\mathbf{Q}^1 = \begin{pmatrix} 1 & 0 & -2 & 0 & 0 \\ 0 & 1 & -2 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & -2 & 1 & 0 \\ 0 & 0 & -2 & 0 & 1 \end{pmatrix}, \mathbf{Q}^2 = \begin{pmatrix} 1 & -2 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & -2 & 1 & 0 & 0 \\ 0 & -2 & 0 & 1 & 0 \\ 0 & -2 & 0 & 0 & 1 \end{pmatrix}$$

Thus, agent i's policy is now $\pi_{\mathbf{Q}^i \theta^i}(s) = \text{sigmoid}(\mathbf{Q}^i \theta^i)[s]$.

Definition 3.1. For policies $\pi_{\theta^{ia}}, \pi_{\theta^{ib}}$, we say $\pi_{\theta^{ia}} = \pi_{\theta^{ib}}$ when for all $s \in \mathcal{S}$, $\pi_{\theta^{ia}}(s) = \pi_{\theta^{ib}}(s)$.

The transformation matrices $\mathbf{Q}^1, \mathbf{Q}^2$ are non-singular and represent changes of basis. For any policy π_{θ^i}, there exists some $\theta^{i\prime}$ such that $\pi_{\mathbf{Q}^i \theta^{i\prime}} = \pi_{\theta^i}$. Despite this, LOLA fails to learn TFT in this transformed policy space (Figure 3). We also observe this issue when comparing tabular LOLA to LOLA with policies parameterized by neural networks in Figure 3; changes in policy representation materially affect LOLA. Relatedly, LOLA is sensitive to different policy parameterizations with the same policy representation, as Figure 1 (left) shows. In the next subsection, we propose an algorithm that addresses these issues.

3.2 Ideal POLA

We first formalize the desired invariance property. We then introduce an idealized (but impractical) version of POLA, and show that it achieves the desired invariance property.

Definition 3.2. An update rule $u : \mathbb{R}^n \times \mathbb{R}^m \to \mathbb{R}^n$ that updates policy parameters $\theta^1 \in \mathbb{R}^n$ using auxiliary information $\theta^2 \in \mathbb{R}^m$ is invariant to policy parameterization when for any $\theta^{1a} \in \mathbb{R}^n, \theta^{1b} \in \mathbb{R}^n, \theta^{2a} \in \mathbb{R}^m, \theta^{2b} \in \mathbb{R}^m$ such that $\pi_{\theta^{1a}} = \pi_{\theta^{1b}}$ and $\pi_{\theta^{2a}} = \pi_{\theta^{2b}}$, $\pi_{u(\theta^{1a}, \theta^{2a})} = \pi_{u(\theta^{1b}, \theta^{2b})}$. In short, if the original policies were the same, so are the new policies (but not necessarily the new policy parameters).

To achieve invariance to policy parameterization, we introduce our new Proximal LOLA (POLA) algorithm. Similarly to PPO [Schulman et al., 2017], each player adjusts their policy to increase the probability of highly rewarded states while penalizing the distance moved in policy space. Crucially, each player also assumes the other player updates their parameters through such a proximal update. More formally, at each policy update, agent 1 solves for the following $\theta^{1\prime}$:

$$\theta^{1\prime}(\theta^1, \theta^2) = \underset{\theta^{1\prime\prime}}{\arg\min} \left(L^1(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime}(\theta^{1\prime\prime}, \theta^2)}) + \beta_{\text{out}} D(\pi_{\theta^1} || \pi_{\theta^{1\prime\prime}}) \right) \tag{1}$$

where $D(\pi_{\theta^i} || \pi_{\theta^{i\prime\prime}})$ is shorthand for a general divergence defined on policies; specific choices are given in subsequent sections. For $\theta^{2\prime}$ in Equation 1, we choose the following proximal update:

$$\theta^{2\prime}(\theta^{1\prime\prime}, \theta^2) = \underset{\theta^{2\prime\prime}}{\arg\min} \left(L^2(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime\prime}}) + \beta_{\text{in}} D(\pi_{\theta^2} || \pi_{\theta^{2\prime\prime}}) \right) \tag{2}$$

For the above equations to be well defined, the $\arg\min$ must be unique; we assume this in all our theoretical analysis. If different parameters can produce the same policy, or multiple different policies have the same total divergence and loss, then the $\arg\min$ is non-unique. However, non-unique solutions is not an issue in practice, as our algorithms approximate $\arg\min$ operations with multiple gradient updates.

Algorithm 1 Outer POLA 2-agent formulation: update for agent 1

Input: Policy parameters θ^1, θ^2, proximal step size α_1, learning rate η, penalty strength β_{out}
Make copy: $\theta^{1\prime\prime} \leftarrow \theta^1$
repeat
$\quad \theta^{2\prime\prime} \leftarrow \theta^2 - \eta \nabla_{\theta^2} L^2(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^2})$
$\quad \theta^{1\prime\prime} \leftarrow \theta^{1\prime\prime} - \alpha_1 \nabla_{\theta^{1\prime\prime}} (L^1(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime\prime}}) + \beta_{\text{out}}(\mathbb{E}_{s \sim U(\mathcal{S})}[D_{KL}(\pi_{\theta^1}(s) || \pi_{\theta^{1\prime\prime}}(s))]))$
until $\theta^{1\prime\prime}$ has converged to a fixed point
Output: $\theta^{1\prime\prime}$

Theorem 3.3. *The POLA update rule $u(\theta^1, \theta^2) = \theta^{1\prime}(\theta^1, \theta^2)$, where $\theta^{1\prime}$ is defined based on Equations 1 and 2, is invariant to policy parameterization.*

The proof is in Appendix A.2. In short, this follows from the fact that all terms in the $\arg\min$ in Equations 1 and 2 are functions of policies, and not directly dependent on policy parameters.

This invariance also is a major advantage in opponent modeling settings, where agents cannot directly access the policy parameters of other agents, and must infer policies from observations. LOLA is ill-specified in such settings; the LOLA update varies depending on the assumed parameterization of opponents' policies. Conversely, POLA updates are invariant to policy parameterization, so any parameterization can be chosen for the opponent model.

To clarify the relation between LOLA and POLA, LOLA is a version of POLA that uses first-order approximations to all objectives and an L2 penalty on policy parameters rather than a divergence over policies. This follows from gradient descent being equivalent to the proximal point method with first order approximations (Section 2.4); we provide a full proof in Appendix A.3.

Exactly solving Equations 1 and 2 is usually intractable, so in Sections 3.3 and 3.4, we formulate practical algorithms that approximate the POLA update.

3.3 Outer POLA

To approximate *ideal POLA*, we use a first order approximation on agent 2's objective, which is equivalent to agent 2 taking a gradient step (see Theorem A.3 for details). That is, instead of finding $\theta^{2\prime}$ via Equation 2, we use $\theta^{2\prime} = \theta^2 - \Delta\theta^2$. Agent 1 thus solves for:

$$\theta^{1\prime}(\theta^1, \theta^2) = \underset{\theta^{1\prime\prime}}{\arg\min} \left(L^1(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^2 - \Delta\theta^2(\theta^{1\prime\prime})}) + \beta_{\text{out}} D(\pi_{\theta^1} || \pi_{\theta^{1\prime\prime}}) \right) \tag{3}$$

Solving the $\arg\min$ above exactly is usually intractable. For a practical algorithm, we differentiate through agent 2's gradient steps with unrolling, like in LOLA, and repeatedly iterate with gradient steps on agent 1's proximal objective until a fixed point is found; Algorithm 1 shows pseudo-code. We choose $D(\pi_{\theta^1} || \pi_{\theta^{1\prime\prime}}) = \mathbb{E}_{s \sim U(\mathcal{S})}[D_{KL}(\pi_{\theta^1}(s) || \pi_{\theta^{1\prime\prime}}(s))]$, where $U(\mathcal{S})$ denotes a uniform distribution over states, as this is most analogous to an L2 distance on tabular policies, and we only test *outer POLA* on settings where tabular policies can be used.

3.4 POLA-DiCE

Outer POLA assumes we can calculate the exact loss, but often we need to estimate the loss with samples from environment rollouts. For these cases, we introduce a policy gradient version of POLA adapted to work with DiCE [Foerster et al., 2018b]. DiCE is a sample-based estimator that makes it easy to estimate higher order derivatives using backprop. More details about DiCE and its combination with LOLA are in the Appendix (A.4, A.5) and in Foerster et al. [2018b].

POLA-DiCE approximates the $\arg\min$ in *ideal POLA* (Equations 1 and 2) with a fixed number of gradient steps on the proximal objectives, where steps on the outer objective (1) differentiate through the unrolled steps on the inner objective (2). We choose $D(\pi_{\theta^i} || \pi_{\theta^{i\prime\prime}}) = \mathbb{E}_{s \sim \mathcal{S}}[D_{KL}(\pi_{\theta^i}(s) || \pi_{\theta^{i\prime\prime}}(s))]$, and approximate the expectation under the true state visitation with an average over states visited during rollouts. $s_{\leq T}^{\text{ref}}$ denotes the states from a set of rollouts with T time steps: $s_{\leq T}^{\text{ref}} \triangleq \{s_t : t \in \{1, ..., T\}\}$, where s_t is the state at time step t. $D(\pi_{\theta^i}, \pi_{\theta^{i\prime\prime}} | s_{\leq T}^{\text{ref}}) \triangleq \frac{1}{|s_{\leq T}^{\text{ref}}|} \sum_{s \in s_{\leq T}^{\text{ref}}} [D_{KL}(\pi_{\theta^i}(s) || \pi_{\theta^{i\prime\prime}}(s))]$ denotes our sample based approximation

194 to $\mathbb{E}_{s \sim \mathcal{S}}[D_{KL}(\pi_{\theta^i}(s)||\pi_{\theta^{i\prime\prime}}(s))]$. As in LOLA-DiCE, rollouts are done in a simulator, and used in
195 the DiCE loss $\mathcal{L}^i_{\boxdot(\pi_{\theta^1}, \pi_{\theta^2})}$. For our experiments, we assume full knowledge of transition dynamics,
196 but in principle an environment model could be used instead. Algorithm 2 provides pseudo-code for
197 POLA-DiCE.

Algorithm 2 POLA-DiCE 2-agent formulation: update for agent 1

Input: Policy parameters θ^1, θ^2, learning rates α_1, α_2, penalty hyperparameters $\beta_{\text{in}}, \beta_{\text{out}}$, number of outer steps M and inner steps K
Initialize: $\theta^{1\prime\prime} \leftarrow \theta^1$
for m in $1...M$ **do**
    Initialize: $\theta^{2\prime\prime} \leftarrow \theta^2$
    for k in $1...K$ **do**
        Rollout trajectories using policies $(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime\prime}})$. If $k = 1$, save states $s^{\text{in}}_{\leq T}$ from the trajectories
        $\theta^{2\prime\prime} \leftarrow \theta^{2\prime\prime} - \alpha_2 \nabla_{\theta^{2\prime\prime}} (\mathcal{L}^2_{\boxdot(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime\prime}})} + \beta_{\text{in}} D(\pi_{\theta^2}, \pi_{\theta^{2\prime\prime}}|s^{\text{in}}_{\leq T}))$
    end for
    Rollout trajectories using policies $(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime\prime}})$. If $m = 1$, save states $s^{\text{out}}_{\leq T}$ from the trajectories
    $\theta^{1\prime\prime} \leftarrow \theta^{1\prime\prime} - \alpha_1 \nabla_{\theta^{1\prime\prime}} (\mathcal{L}^1_{\boxdot(\pi_{\theta^{1\prime\prime}}, \pi_{\theta^{2\prime\prime}})} + \beta_{\text{out}} D(\pi_{\theta^1}, \pi_{\theta^{1\prime\prime}}|s^{\text{out}}_{\leq T}))$
end for
Output: $\theta^{1\prime\prime}$

---

198 For sufficiently large inner steps K and outer steps M, and sufficiently small learning rates, POLA-
199 DICE iterates until a fixed point is found. Unfortunately, iterating to convergence often requires a
200 very large amount of rollouts and memory. When $M = 1$ and $\beta_{\text{in}} = 0$, POLA-DiCE is equivalent to
201 LOLA-DiCE [Foerster et al., 2018b].

202 Without opponent modeling, LOLA-DiCE and POLA-DiCE directly access the other agent's policy
203 parameters, using those in simulator rollouts for policy updates. In the opponent modeling (OM)
204 setting, agents can only access actions taken by the other agent, from real environment rollouts. For
205 policy updates, agents must use learned policy models in simulator rollouts. We learn policy models
206 by treating observed actions as targets in a supervised classification setting, as in behaviour cloning
207 [Ross et al., 2011]. Figure 2 illustrates the process at each time step; we keep policy models from
208 previous iterations and update incrementally on newly observed actions.

Figure 2: Illustration of the training process at each time step for LOLA-DiCE and POLA-DiCE. Without opponent modeling, each agent directly uses the other agent's policy parameters in simulator rollouts for policy updates. With opponent modeling, each agent first learns a policy model of the opponent based on observed actions from real environment rollouts. Agents then use the learned models in simulator rollouts for policy updates. We assume known dynamics, so no environment model needs to be learned for simulator rollouts.

4 Experiments

210 To investigate how useful our approximations to *ideal POLA* are, we run experiments to answer the
211 following questions: 1) Does *outer POLA* learn reciprocity-based cooperation more consistently than
212 LOLA, across a variety of policy parameterizations, in the IPD with one-step memory (Section 4.1)?
213 2) Does POLA-DiCE learn reciprocity-based cooperation more consistently than LOLA-DiCE in
214 settings that require function approximation and rollouts (IPD with full history (Section 4.2) and coin
215 game (Section 4.3))? If so, do these results still hold when using opponent modeling?

In all settings, during training, agents interact with each other only. To provide a fair comparison in terms of sample efficiency between LOLA-DiCE and POLA-DiCE in Sections 4.2 and 4.3, we plot results based on the number of rollouts used for policy updates. Rollouts used for opponent modeling are inherent to the change in problem setting, so we do not count those in our comparison.

4.1 One-Step Memory IPD

With one-step memory, the observations are the actions by both agents at the previous time step. In this setting, we can use the exact loss in gradient updates (see Appendix B.1.1 for details).

To investigate behaviour across settings that vary the difficulty of learning reciprocity-based coopera­tion, we introduce a *cooperation factor* f, which determines the reward for cooperating relative to defecting. At each time step, let c be the number of agents who cooperated. Each agent's reward is $c * f/2 - \mathbb{1}[\text{agent contributed}]$. This is a specific instance of the *contribution game* from Barbosa et al. [2020], with two agents. $1 < f < 2$ satisfies the dilemma characteristics of the IPD outlined in Section 2.2. For more details on the problem setup, see Appendices B.1.2 and B.1.3.

Figure 3 compares LOLA and *outer POLA* (Section 3.3) using various f and policy parameterizations. To evaluate whether agents learn reciprocity-based cooperation, we test how often agents *find TFT*. *Finding TFT* is a qualitative concept, as it is unclear when a stochastic policy becomes sufficiently close to TFT. We consider agents cooperating with each other with high probability, achieving average reward $> 80\%$ of the socially optimal, but both cooperating with probability < 0.65 if the opponent last defected, to have *found TFT*. We reproduce Foerster et al. [2018a]'s result that naive learning converges to unconditional defection, while LOLA using tabular policies finds TFT (see Appendix B.1.4 for details). However, changes in policy parameterization greatly hinder LOLA's ability to find TFT. In contrast, *outer POLA* finds TFT even with function approximation, and finds TFT significantly more often than LOLA in the pre-conditioned setting described in Section 3.1.

Figure 3: Comparison of LOLA and *outer POLA* in the one-step memory IPD with various f, plotting the % of 20 runs that *find TFT*. NN denotes policies parameterized by neural networks. Pre-condition denotes the setting in Section 3.1. Given hyperparameter tuning, tabular LOLA always finds TFT (for $f > 1$), whereas LOLA with function approximation fails on lower f. In the pre-conditioned setting, LOLA completely fails to find TFT. In contrast, *outer POLA* finds TFT regardless of whether the policy is tabular or a neural network. *Outer POLA* retains most of its performance in the pre-conditioned setting, demonstrating some limits of its approximation to *ideal POLA*. As sanity checks, naive learning ($\eta = 0$) always fails to find TFT, and all algorithms always defect for $f < 1$.

Qualitatively, Figure 1 shows that in the IPD with one-step memory, $f = 1.33$, and neural network parameterized policies, *outer POLA* closely approximates the invariance provided by *ideal POLA*.

4.2 Full History IPD

Next, we relax the assumption that agents are limited to one-step memory and instead consider policies that condition on the entire history. This makes using function approximation and rollouts necessary. We parameterize policies using GRUs [Cho et al., 2014] and test whether POLA-DiCE still learns reciprocity-based cooperation within this much larger policy space. We use the IPD reward structure in Foerster et al. [2018a], where both agents cooperating each get -1 and both agents defecting each get -2 at each step. For more details, see Appendix B.2.

Figure 4 shows results in this setting. Two LOLA agents both learn to always defect, whereas POLA agents achieve higher reward via reciprocity-based cooperation; POLA agents defect with high probability if the opponent always defects. Even opponent modeling works well with POLA; POLA agents behave similarly using opponent modeling instead of accessing policy parameters directly.

Figure 4: Comparison of LOLA-DiCE and POLA-DiCE on the IPD with GRU parameterized policies that condition on the full action history. Left: POLA-DiCE agents learn to cooperate with each other with high probability, achieving close to the socially optimal reward (always cooperate), whereas LOLA agents defect against each other. Right: we test the learned policies against a hard-coded rule that always defects. POLA-DiCE agents defect against such an opponent with high probability, showing POLA agents cooperate only when the other agent reciprocates. POLA-OM (POLA-DiCE with opponent modeling) agents show similar behaviour to POLA-DiCE agents. All results are averaged over 10 random seeds with 95% confidence intervals shown.

4.3 Coin Game

To investigate the scalability of POLA-DiCE under higher dimensional observations and function approximation, we test LOLA-DiCE and POLA-DiCE in the coin game setting from Foerster et al. [2018a]. The coin game consists of a 3x3 grid in which two agents, red and blue, move around and collect coins. There is always one coin, coloured either red or blue, which spawns with the other colour after being collected. Collecting any coin grants a reward of 1; collecting a coin with colour different from the collecting agent gives the other agent -2 reward. The coin game embeds a temporally extended social dilemma; if agents defect by trying to pick up all coins, both agents get 0 total reward in expectation, whereas if agents cooperate by only picking up coins of their own colour, they achieve positive expected total reward. Appendix B.3 provides more detail. We again parameterize the agents' policies with GRUs [Cho et al., 2014].

Figure 5 shows that POLA-DiCE agents learn to cooperate with higher probability than LOLA-DiCE agents,[1] picking up a larger proportion of their own coins, and again do not naively cooperate. POLA-DiCE agents with opponent modeling often behave the same as POLA-DiCE agents, but sometimes the noise from opponent modeling results in them failing to learn to encourage cooperation.

Figure 5: Comparison of LOLA-DiCE and POLA-DiCE on the coin game. Left: number of coins collected where the coin's colour matched the agent's colour, divided by the total number of coins collected. POLA agents cooperate more than LOLA agents, collecting a larger proportion of their own coloured coins. Middle: average score for the agents against each other. Right: we test the learned policies against a hard-coded rule that always *defects* by taking the shortest path to the coin regardless of colour. POLA agents learn to defect, achieving scores close to the optimal of 0 against such an opponent, again showing POLA agents cooperate based on reciprocity. POLA-OM (POLA-DiCE with opponent modeling) agents behaved the same as POLA-DiCE agents 6 out of 10 times; other times the noise from opponent modeling resulted in them failing to learn to encourage cooperation. All results are averaged over 10 random seeds with 95% confidence intervals shown.

---

[1]See Appendix B.3 for why the LOLA results cannot be directly compared with Foerster et al. [2018a]

5 Related Work

POLA-DiCE (Section 3.4) can alternatively be motivated as replacing the policy gradient update inherent in LOLA-DiCE with a proximal-style update like that of TRPO [Schulman et al., 2015a] or the adaptive KL-penalty version of PPO [Schulman et al., 2017].

There are other extensions to LOLA that address problems orthogonal to policy parameterization sensitivity. In concurrent work, Willi et al. [2022] highlight that LOLA is inconsistent in self-play; the update each player assumes the opponent makes is different from their actual update. They propose COLA, learning update rules $\Delta\theta^1$ and $\Delta\theta^2$ that are consistent with each other. However, their notion of consistency is gradient-based and thus not invariant to policy parameterization, whereas POLA is not consistent. SOS [Letcher et al., 2018], which combines the advantages of LOLA and LookAhead [Zhang and Lesser, 2010], is also not invariant to policy parameterization.

Al-Shedivat et al. [2018] formulate a meta-RL framework with a policy gradient theorem, and apply PPO as their optimization algorithm; this is one instance of combining proximal style operators with reinforcement learning style policy gradients for optimization with higher order gradients. However, they focus on adaptation rather than explicitly modeling and shaping opponent behaviour.

MATRL [Wen et al., 2021] sets up a metagame between the original policies and new policies calculated with independent TRPO updates for each agent, solving for a Nash equilibrium in the metagame at each step. MATRL finds a best response without actively shaping its opponents' learning, so is compared to LookAhead [Zhang and Lesser, 2010] instead of LOLA.

M-FOS [Lu et al., 2022] sets up a metagame where each meta-step is a full environment rollout, and the meta-reward at each step is the cumulative discounted return of the rollout. They use model-free optimization methods to learn meta-policies that shape the opponent's behaviour over meta-steps. We do not compare against it as it is concurrent work without published code at the time of writing.

Badjatiya et al. [2021] introduce *status-quo loss*, in which agents imagine the current situation being repeated for several steps; combined with the usual RL objective, this leads to cooperation in social dilemmas. However, their method learns to defect in the one-step memory IPD in the states DC and CD, and thus does not learn reciprocity-based cooperation.

Zhao et al. [2021] provide a detailed numerical analysis of the function approximation setting for two-player zero-sum Markov Games. Fiez et al. [2021] considers a proximal method for minimax optimization. In contrast to both, we consider the general-sum setting.

6 Limitations

Outer POLA and POLA-DiCE approximate *ideal POLA*, so are not completely invariant to policy parameterization; Figures 1 and 3 show how close the approximation is in the one-step memory IPD. POLA introduces additional hyperparameters compared to LOLA (e.g. β_{out} and number of outer steps for POLA-DiCE). POLA usually requires many rollouts for each update; future work could explore ways to mitigate this. For example, in Appendix A.8 we formulate a version of POLA-DiCE closer to PPO [Schulman et al., 2017], that repeatedly trains on samples for improved sample efficiency.

7 Conclusion and Future Work

Motivated by making LOLA invariant to policy parameterization, we introduced POLA. Empirically, we demonstrated that practical approximations to POLA learn reciprocity-based cooperation significantly more often than LOLA in several social dilemma settings.

Future work could explore and test: policy parameterization invariant versions of LOLA extensions like COLA [Willi et al., 2022] and SOS [Letcher et al., 2018]; POLA formulations with improved sample efficiency (e.g. Appendix A.8); an n-agent version of POLA; POLA formulations with adaptive penalty parameters $\beta_{\text{in}}, \beta_{\text{out}}$; connections to Mirror Learning [Kuba et al., 2022]; adapting approximations to proximal point methods such as the extra-gradient method [Mokhtari et al., 2020] to work with POLA.

We are excited and hopeful that this work opens the door to scaling LOLA and related algorithms to practical settings that require function approximation and opponent modeling.

References

Maruan Al-Shedivat, Trapit Bansal, Yura Burda, Ilya Sutskever, Igor Mordatch, and Pieter Abbeel. Continuous adaptation via meta-learning in nonstationary and competitive environments. In *International Conference on Learning Representations*, 2018.

Robert Axelrod and William Donald Hamilton. The evolution of cooperation. *science*, 211(4489): 1390–1396, 1981.

Pinkesh Badjatiya, Mausoom Sarkar, Nikaash Puri, Jayakumar Subramanian, Abhishek Sinha, Siddharth Singh, and Balaji Krishnamurthy. Status-quo policy gradient in multi-agent reinforcement learning. *arXiv preprint arXiv:2111.11692*, 2021.

João Vitor Barbosa, Anna H Reali Costa, Francisco S Melo, Jaime S Sichman, and Francisco C Santos. Emergence of cooperation in n-person dilemmas through actor-critic reinforcement learning. 2020.

Kyunghyun Cho, Bart Van Merriënboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-decoder approaches. *arXiv preprint arXiv:1409.1259*, 2014.

Robyn M Dawes. Social dilemmas. *Annual review of psychology*, 31(1):169–193, 1980.

Gregory Farquhar, Shimon Whiteson, and Jakob Foerster. Loaded dice: trading off bias and variance in any-order score function estimators for reinforcement learning. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pages 8151–8162, 2019.

Tanner Fiez, Chi Jin, Praneeth Netrapalli, and Lillian J Ratliff. Minimax optimization with smooth algorithmic adversaries. *arXiv preprint arXiv:2106.01488*, 2021.

Jakob Foerster, Richard Y Chen, Maruan Al-Shedivat, Shimon Whiteson, Pieter Abbeel, and Igor Mordatch. Learning with opponent-learning awareness. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pages 122–130. International Foundation for Autonomous Agents and Multiagent Systems, 2018a.

Jakob Foerster, Gregory Farquhar, Maruan Al-Shedivat, Tim Rocktäschel, Eric Xing, and Shimon Whiteson. Dice: The infinitely differentiable monte carlo estimator. In *International Conference on Machine Learning*, pages 1529–1538. PMLR, 2018b.

Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *In Proc. 19th International Conference on Machine Learning*. Citeseer, 2002.

Jakub Grudzien Kuba, Christian Schroeder de Witt, and Jakob Foerster. Mirror learning: A unifying framework of policy optimisation. *arXiv preprint arXiv:2201.02373*, 2022.

Alistair Letcher, Jakob Foerster, David Balduzzi, Tim Rocktäschel, and Shimon Whiteson. Stable opponent shaping in differentiable games. *arXiv preprint arXiv:1811.08469*, 2018.

Chris Lu, Timon Willi, Christian Schroeder de Witt, and Jakob Foerster. Model-free opponent shaping. *arXiv preprint arXiv:2205.01447*, 2022.

Aryan Mokhtari, Asuman Ozdaglar, and Sarath Pattathil. A unified analysis of extra-gradient and optimistic gradient methods for saddle point problems: Proximal point approach. In *International Conference on Artificial Intelligence and Statistics*, pages 1497–1507. PMLR, 2020.

Neal Parikh and Stephen Boyd. Proximal algorithms. *Foundations and Trends in optimization*, 1(3): 127–239, 2014.

Stéphane Ross, Geoffrey J Gordon, and J Andrew Bagnell. No-regret reductions for imitation learning and structured prediction. In *In AISTATS*. Citeseer, 2011.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pages 1889–1897. PMLR, 2015a.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015b.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Ying Wen, Hui Chen, Yaodong Yang, Zheng Tian, Minne Li, Xu Chen, and Jun Wang. A game-theoretic approach to multi-agent trust region optimization. *arXiv preprint arXiv:2106.06828*, 2021.

Timon Willi, Johannes Treutlein, Alistair Letcher, and Jakob Foerster. Cola: Consistent learning with opponent-learning awareness. *arXiv preprint arXiv:2203.04098*, 2022.

Chongjie Zhang and Victor Lesser. Multi-agent learning with policy prediction. In *Twenty-fourth AAAI conference on artificial intelligence*, 2010.

Yulai Zhao, Yuandong Tian, Jason D Lee, and Simon S Du. Provably efficient policy gradient methods for two-player zero-sum markov games. *arXiv preprint arXiv:2102.08903*, 2021.