Analyzing and Improving Generative Adversarial Training for Generative Modeling and Out-of-Distribution Detection

Abstract

Generative adversarial training (GAT) is a recently introduced adversarial defense method. Previous works have focused on empirical evaluations of its application to training robust predictive models. In this paper we focus on theoretical understanding of the GAT method and extending its application to generative modeling and out-of-distribution detection. We analyze the optimal solutions of the maximin formulation employed by the GAT objective, and make a comparative analysis of the minimax formulation employed by GANs. We use theoretical analysis and 2D simulations to understand the convergence property of the training algorithm. Based on these results, we develop an unconstrained GAT algorithm, and conduct comprehensive evaluations of the algorithm's application to image generation and adversarial out-of-distribution detection. Our results suggest that generative adversarial training is a promising new direction for the above applications.

1 Introduction

Generative adversarial training (GAT) (Yin et al., 2020) is a recently introduced defense mechanism that could be used for adversarial example detection and robust classification. The defense consists of a committee of detectors (binary discriminators), with each one trained to discriminate natural data of a particular class from adversarial examples perturbed from data of other classes. Like most other work in the area of robust machine learning, the defense is specially designed for defending against norm-constrained adversaries — adversaries that are constrained to perturb the data up to a certain amount as measured by some norm. The defense's robustness is achieved by training each detector model against adversarial examples produced by the norm-constrained PGD attack (Madry et al., 2017).

Existing work: training and evaluating robust predictive models A detector trained with GAT has strong interpretability — an unbounded attack that maximizes the detector's output results in images that resemble the target class data — this suggests the detector has learned the target class data distribution. However, all previous works (Yin et al., 2020; Tramer et al., 2020) focus on the empirical evaluations of GAT's application to training robust predictive models; *a theoretical understanding of why this training method causes the detector to learn the data distribution is missing.*

This work: theoretical understanding, improved training algorithm, and extended applications In order to better understand the GAT method, we first analyze the optimal solutions of the training objective. We start with a *maximin* formulation of the objective, and try to connect it with the *minimax* formulation that is employed by GANs (Goodfellow et al., 2014). We find that the differences between solutions of these two formulations become immediately clear when we take a game-theory perspective. We then use theoretical analysis and 2D simulations to understand the convergence property of the GAT training algorithm. Guided by these theoretical and experimental insights, we develop an unconstrained GAT algorithm. Our comprehensive evaluation suggests that this algorithm can serve as an effective tool for image generation and building robust out-of-distribution detection systems. In summary, our key contributions are:

- We analyze the optimal solutions of the GAT objective and convergence property of the training algorithm. We discuss the implications of these results on improved training of robust predictive models, generative modeling, and out-of-distribution detection.

- We develop an unconstrained generative adversarial training algorithm. We conduct a comprehensive evaluation of the algorithm's application to image generation and adversarial out-of-distribution detection.
- Our comparative analysis of the maximin and minimax problem clarifies misconceptions and provides new insights into how they could be utilized to solve different problems.

2 BACKGROUND

Generative adversarial networks (GANs)   The GANs framework (Goodfellow et al., 2014) learns a generator function G and a discriminator function D by solving the following *minimax* problem

$$\min_G \max_D V(D, G) = \mathbb{E}_{\mathrm{x} \sim p_{\mathrm{data}}}[\log D(x)] + \mathbb{E}_{\mathrm{z} \sim p_z}[\log(1 - D(G(z)))]. \tag{1}$$

The generator G implicitly defines a distribution p_g by mapping a prior distribution p_z from a low-dimensional latent space $\mathcal{Z} \subseteq \mathbb{R}^z$ to the high-dimensional data space $\mathcal{X} \subseteq \mathbb{R}^d$. $D : \mathcal{X} \to [0, 1]$ is a function that discriminates the target data distribution p_{data} from the generated distribution p_g. The minimax problem is solved by alternating between the optimization of D and optimization of G; under certain conditions, the alternating training procedure converges to a solution where p_g matches p_{data} (Jensen-Shannon divergence is zero), and D outputs $\frac{1}{2}$ on support of p_{data}.

Generative adversarial training (GAT)   The GAT method (Yin et al., 2020) is designed for training adversarial examples detection and robust classification models. In a K class classification problem, the robust detection/classification system consists of K base detectors, with each one trained by minimizing the following objective

$$L(D) = -\mathbb{E}_{\mathrm{x} \sim p_k}[\log D(x)] - \mathbb{E}_{\mathrm{x} \sim p_{-k}}[\log(1 - \max_{x' \in \mathbb{B}(x, \epsilon)} D(x'))]. \tag{2}$$

In the above objective, p_k is k-th class's data distribution, p_{-k} is the mixture distribution of all other classes: $p_{-k} = \frac{1}{K-1} \sum_{i=1,...,K, i \neq k} p_i$, and $\mathbb{B}(x, \epsilon)$ is a neighborhood of x: $\{x' \in \mathcal{X} : \|x' - x\|_2 \leq \epsilon\}$. The objective is characterized by an *inner maximization* problem and an *outer minimization* problem; when the inner maximization is perfectly solved and D achieves a vanishing loss, D becomes a perfectly robust model capable of separating data p_k, from *any* ϵ-constrained adversarial examples perturbed from data of p_{-k}. A committee of K detectors then provides a complete solution for detecting any adversarial example perturbed from an arbitrary class. Objective 2 is solved using a alternating gradient method (Algorithm 1), with the first step crafting adversarial examples by solving the inner maximization, and the second step improving the D model on these adversarial examples.

Clearly, the detector's robustness depends on how well the inner maximization is solved. Despite the fact that D is a highly non-concave function when it's parameterized by a deep neural network, Madry et al. (2017) showed that the inner problem could be reasonably solved using projected gradient descent (PGD attack) — a first-order method that employs the following iterative gradient update rule (at initialization $x^0 \leftarrow x$, we consider L^2-based attack)

$$x^{i+1} \leftarrow \mathtt{Proj}(x^i + \gamma \frac{\nabla \log D(x^i)}{\|\nabla \log D(x^i)\|_2}), \tag{3}$$

where λ is some step size, and $\mathtt{Proj}$ is the operation of projecting onto the feasible set $\mathbb{B}(x, \epsilon)$. The *normalized steepest ascent* rule inside the $\mathtt{Proj}$ function, was introduced for dealing with the issue of vanishing gradient when optimizing with the cross-entropy loss (Kolter & Madry, 2019). The PGD attack also employs random restarting to improve its effectiveness. The idea is that for a input x, first generate a set of randomized inputs by uniformly sampling from $\mathbb{B}(x, \epsilon)$, perform PGD attack on each of them, and use the most effective one as the actual attack.

3 THEORETICAL RESULTS

In this section we first reformulate objective 2 into a *maximin* problem, and then analyze the optimal solutions of the maximin problem and convergence property of Algorithm 1. We then discuss the optimal solution of the corresponding *minimax* formulation and the differences between the

---

Algorithm 1 GAT Detector Training Method (The Maximin Problem Solver)

1: Sample minibatch of m samples $\{x_1^k, \ldots, x_m^k\}$ from p_k, and m samples $\{x_1^{-k}, \ldots, x_m^{-k}\}$ from p_{-k}.
2: Compute adversarial examples $\{x_1', \ldots, x_m'\}$ by solving $\max_{x' \in \mathbb{B}(x, \epsilon)} D(x')$ for each x_i^{-k}.
3: Train the detector by minimizing $\frac{1}{m} \sum_{i=1}^{m} \left[-\log D(x_i^k) - \log(1 - D(x_i')) \right]$ (single step).
4: Return to step 1.

---

solutions of these two formulations. The popular generative modeling approach of GANs learns a data distribution by solving the minimax problem, but there seems to be a misconception about the differences between solutions of these two problems, and as a results, a false impression that the GANs algorithm could solve the maximin problem (Goodfellow (2016), section 5.1.1). Our analysis of optimal solutions is based on a game-theory interpretation of these problems, and the differences between these solutions are immediately clear under such an analysis.

3.1 THE MAXIMIN PROBLEM

In this section we provide an analysis of the optimal solutions of objective 2. Maximizing D is equivalent to minimizing $\log(1 - D)$, hence equation 2 is equivalent to

$$L(D) = -\mathbb{E}_{\mathbf{x} \sim p_k}[\log D(x)] - \mathbb{E}_{\mathbf{x} \sim p_{-k}}[\min_{x' \in \mathbb{B}(x, \epsilon)} \log(1 - D(x'))]. \tag{4}$$

For the convenience of analysis, instead of using ϵ-balls imposed on individual data samples, we use the notion of a common perturbation space: The perturbation space $\mathcal{S}$ is a subspace of the data space $\mathcal{X}$, and allows any "elementary mass" of p_{-k} to be moved to any location in $\mathcal{S}$. A new distribution p_t can be obtained by transporting the elementary mass of p_{-k} to appropriate locations in $\mathcal{S}$, via a transformation function $T : \mathcal{S} \to \mathcal{S}$. Utilizing the technique of random variable transformation, we can write the density function of p_t as a function of p_{-k}: $p_t(y) = \int_{\mathcal{S}} p_{-k}(x)\delta(y - T(x))dx$. Figure 1 left panel is a schematic illustration of this phenomenon. Let $\mathcal{M}_+^1(\mathcal{S})$ be the set of distributions attainable by applying such transformations to the support of p_{-k}. With the notation of perturbation space, the inner problem in equation 4 could then be interpreted as determining the distribution in $\mathcal{M}_+^1(\mathcal{S})$ that causes the highest (expected) loss of the D function. The interplay of the D model and the adversary can be formulated as a *maximin* problem:

$$\max_D \min_{p_t \in \mathcal{M}_+^1(\mathcal{S})} U(D, p_t) = \mathbb{E}_{\mathbf{x} \sim p_k}[\log D(x)] + \mathbb{E}_{\mathbf{x} \sim p_t}[\log(1 - D(x))]. \tag{5}$$

Figure 1: Left panel: a distribution p_t is obtained by applying a transformation T to the support of p_{-k}. Right panel: three scenarios to consider when analyzing problem 5. Red distribution represents p_{-k} and blue distribution represents p_k. The data space $\mathcal{X}$ is represented by the whole space inside the square, and the perturbation space $\mathcal{S}$ is represented by the gray area.

Table 1: Optimal solutions for the three scenarios in Figure 1

Scenario	Optimal solution (D^*, p_t^*)
$\text{Supp}(p_k) \subset \mathcal{S}$	D^* outputs $\frac{1}{2}$ for $\text{Supp}(p_k)$ and $\leq \frac{1}{2}$ for $\mathcal{S} \setminus \text{Supp}(p_k)$; p_t^* has its mass distributed to locations where D^* outputs $\frac{1}{2}$.
$\text{Supp}(p_k) \cap \mathcal{S} = \emptyset$	D^* outputs 1 for $\text{Supp}(p_k)$ and 0 for $\mathcal{S}$; p_t^* can be an arbitrary distribution in $\mathcal{M}_+^1(\mathcal{S})$.
$\text{Supp}(p_k) \cap \mathcal{S} \neq \emptyset$, and $\text{Supp}(p_k) \not\subset \mathcal{S}$	For $\text{Supp}(p_k)$ outside $\mathcal{S}$, D^* outputs 1, for $\text{Supp}(p_k)$ inside $\mathcal{S}$, D^* outputs $\alpha = \frac{\int_{\mathcal{S}} p_k}{\int_{\mathcal{S}} p_t^* + \int_{\mathcal{S}} p_k}$ (by definition, $\int_{\mathcal{S}} p_t^* = 1$), and for other places inside $\mathcal{S}$, D^* outputs $\leq \alpha$; p_t^* has its mass distributed to locations where D^* outputs α.

Optimal solutions A convenient way of analyzing the above problem is to consider it as a two-player game: player 1 first presents different D configurations, then for each D, player 2 determines a perturbed distribution p_t^D that minimizes U under the considered D. Then over all combinations of (D, p_t^D), player 1 chooses the combination $(D, p_t^D)^*$ that gives the highest U value. By analyzing both players' best strategies for playing the game, we could derive the optimal solutions (Table 1) for the three scenarios [1] depicted in Figure 1. From a game-playing perspective, the claims in Table 1 can be verified by assuming a different D configuration than the claimed one, and show that there always exists a p_t that results in a lower U value than the U value that could be achieved with the claimed D configuration. Mathematical derivations of these optimal solutions are included in Appendix A.

Scenario 2 result and its implication for training robust models In robust machine learning literature, it's common to consider a very small value for ϵ. For instance, one of the most commonly used limit for training L^∞ robust models is $\epsilon = 8/255$ (L^∞ norm). A perturbation space characterized by a small limit can be thought as a semantic-preserving space: translating a sample inside the space doesn't change the sample's underlying label/class membership. A small perturbation limit corresponds to scenario 2, which is also the focus of Yin et al. (2020). We can define robust models as models that output consistent predictions for inputs under semantic-preserving transformations. In this sense, the optimal D for scenario 2 is a robust detector, as it always outputs 0 for the perturbation space. However, the limitation of training against a small ϵ is obvious: because optimal D's outputs outside $\mathcal{S} \cup \mathrm{Supp}(p_k)$ are unspecified, any semantic-preserving operation that has a perturbation that goes beyond $\mathcal{S}$ can result in a high D output, thereby fools the detection. The above analysis suggests that for predictive models based on the generative adversarial training method, their robustness can be improved by training against a larger perturbation space.

3.2 THE MAXIMIN PROBLEM SOLVER

The method (Algorithm 1) for training adversarial-robust detector is in fact a solver for the maximin problem 5: maximizing $D(x)$ is equivalent to minimizing $\log(1 - D(x)$ (step 2), and minimizing the loss is equivalent to maximizing U (step 3). Algorithm 1 has the following convergence property:

Proposition 1. *If step 2 always perfectly solves the inner problem (i.e., the mass of p_t is always moved to the location(s) where D has the largest output(s)), and step 3's updates happen in D's function space, and each update is sufficiently small, then the algorithm converges to the optimal solution of D.*

Proof. We consider scenario 1 in Figure 1. Let $\alpha := \max_{\mathcal{S} \setminus \mathrm{Supp}(p_k)} D$, $A := \{x \in \mathcal{S} \setminus \mathrm{Supp}(p_k) : D(x) = \alpha\}$, and $\beta := \max_{\mathrm{Supp}(p_k)} D$, $B := \{x \in \mathrm{Supp}(p_k) : D(x) = \beta\}$. We focus on the case of $1 > \alpha, \beta > \frac{1}{2}$; other cases can be proved using a similar argument. Recall that in Algorithm 1, step 2 solves the inner minimization by moving mass of p_{-k} to locations where D has the largest outputs, and step 3 updates D by decreasing its outputs on p_t and increasing its outputs on p_k. We further assume when mass of p_{-k} is moved to multiple locations with equal D outputs, the algorithm doesn't have a preference over locations (i.e., mass of p_{-k} will be uniformly distributed to these locations). Algorithm 1 can be interpreted as a finite state machine that constantly switches between the following three states:

- State 1: $\alpha > \beta$. Step 2 moves the mass of p_{-k} to A, and step 3 decreases α while increases β; the algorithm switches to state 2 or state 3.

- State 2: $\alpha < \beta$. Step 2 moves the mass of p_{-k} to B, and step 3 maintains α while decreases β (Appendix B.1); the algorithm switches to state 1 or state 3.

- State 3: $\alpha = \beta$. Step 2 moves the mass of p_{-k} to $A \cup B$, step 3 decreases α. Because of non-zero densities of B's points on p_k, if β is decreased, the decreased amount is always lower than that of α — the algorithm switches to state 2.

In particular, step 3 in state 1 and state 2 always results in an decrease of $\max\{\alpha, \beta\}$ (but β cannot be decreased to below $\frac{1}{2}$, Appendix A), and step 3 in state 3 always results in an decrease of α. The algorithm converges to the D solution of $\alpha \le \frac{1}{2}, \beta = \frac{1}{2}$. $\quad\square$

---

[1] In scenario 2 and 3, D^* doesn't need to be defined on $\mathcal{X} \setminus (\mathcal{S} \cup \mathrm{Supp}(p_k))$.

Practical considerations The above proof relies on the assumption that step 2 always *perfectly* solves the inner minimization (i.e., mass of p_{-k} is always moved to the location(s) where D has the largest output(s)). In practice, as a gradient-based search procedure (see equation 3), step 2 is unlikely able to reach the global maxima when D is a highly non-concave function.

This issue with gradient-based search is alleviated by the alternating optimization procedure: if at step 2 samples of p_{-k} are stuck at local maxima, step 3 immediately decreases D outputs on these samples. In other words, local maxima are constantly being eliminated. We can clearly observe this pattern in a 2D simulation of the algorithm (Figure 4).

However, it appears local maxima elimination cannot solve all the issues. As illustrated in Figure 2(b), the maximin solver could converge to a solution where D has $> \frac{1}{2}$ outputs on places other than Supp(p_k). Inspecting the gradient vector field in Figure 2(b), we find that by starting from p_{-k} and following the gradient of D, p_t is always "trapped" to Supp(p_k). As a result, other local maxima lost the chance of being visited by p_t, and cannot be eliminated.

The above observation points out a straightforward solution: use a p_{-k} that covers more data space. In Figure 2(c) and Figure 5 we can see by using a p_{-k} that is *uniformly distributed* in the data space we can always obtain D solutions with no local maxima and global maxima at Supp(p_k). The fact that these D solutions don't have local maxima also means we can translate an arbitrary data point out of Supp(p_k) to Supp(p_k) by performing gradient ascent on D.

(a) initial positions   (b) maximin solution 1   (c) maximin solution 2   (d) minimax solution

Figure 2: Plots of contours and gradient vector fields of the D functions (gradient vectors are normalized to have the unit length). (a) The initial positions of p_{-k} and p_k. (b) The solution obtained by the maximin problem solver. (c) The solution obtained by the maximin problem solver when p_{-k} is a uniform distribution in the data space. (d) The solution obtained by the minimax problem solver.

3.3 THE MINIMAX PROBLEM

Algorithm 2 Minimax Problem Solver

1: Initialize $p_t \leftarrow p_{-k}$.
2: **repeat**
3:     Train the detector by maximizing $\mathbb{E}_{x \sim p_k}[\log D(x)] + \mathbb{E}_{x \sim p_t}[\log(1 - D(x))]$ (until converge).
4:     For each sample $x \in p_t$, update its value $x \leftarrow x - \gamma \frac{\nabla \log(1 - D(x))}{\|\nabla \log(1 - D(\tilde{x}))\|_2}$.
5: **until** p_t convergences to p_k

The corresponding minimax game $\min_{p_t} \max_D U(D, p_t)$ has a reversed rule: player 1 first presents different p_ts, then for each p_t, player 2 determines a D^{p_t} that maximizes U under the considered p_t. Then over all the combinations of (p_t, D^{p_t}), player 1 chooses the combination that gives the least U value. The solution of the game is analyzed in Goodfellow et al. (2014); Goodfellow (2016): the optimal strategy for player 2 is to choose a D such that U measures the Jensen-Shannon divergence (JSD): $U(D^*, p_t) = -\log(4) + 2 \cdot \text{JSD}(p_t \parallel p_k)$ (the actual solution of D is $D^* = \frac{p_k}{p_k + p_t}$), and optimal strategy for player 1 is to choose a p_t that minimizes the JSD: $p_t^* = \arg\min_{p_t \in \mathcal{M}_+^1(\mathcal{S})} \text{JSD}(p_t \parallel p_k)$. When Supp($p_k$) $\subset \mathcal{S}$ (corresponding to scenario 1 in Figure 1), p_t^* matches p_k (JSD is zero), and D^* outputs $\frac{1}{2}$ on Supp(p_k). A solver (Algorithm 2) for the minimax problem is readily available by removing the "generator" from GANs' training algorithm. It is straightforward to apply GANs algorithm's convergence property to Algorithm 2: if at each step p_t is updated with a sufficiently small step of λ, and D is trained to reach its optimum, then p_t converges to p_k. In Figure 2(d) and Figure 6 we provide 2D simulation results of this algorithm.

3.4 THE DIFFERENCE

There are a few differences between the solutions of the maximin problem and minimax problem.

First, both D^*s output $\frac{1}{2}$ for Supp(p_k). But while D^* in the maximin problem outputs $\leq \frac{1}{2}$ on $\mathcal{S} \setminus \text{Supp}(p_k)$, D^* in the minimax game doesn't need to be defined on $\mathcal{S} \setminus \text{Supp}(p_k)$ (Goodfellow et al., 2014). In other words, D^* in the minimax problem has unpredictable values between 0 and 1 in most of the data space. We can observe this phenomenon in Figure 6. The intuition here is that in the maximin game, p_t^* is decided in the second move, with the knowledge of the current D value; to prevent p_t^* from taking this advantage, the best strategy for player 1 is to specify D outputs for the entire perturbation space. In the minimax game, on the contrary, D^* is decided in the second move, with the knowledge of p_t, hence the player does not need to worry about D^* outputs outside the supports of p_t and p_k.

Another difference, which can also be observed from Figure 2, is that in the minimax game, p_t^* exactly matches p_k, while in the maximin game, mass of p_t^* can be any place where D^* outputs $\frac{1}{2}$.

Overall we find these two formulations give rise to different applications. The minimax formulation, which is the formulation used by GANs, is perfect for learning a generator that produces a distribution that exactly matches the target data distribution. The discriminator (the D model), because of its undefined behavior in most of the data space, may not be very useful. The maximin problem, if well solved (Figure 2(c)), gives a D function that models a *characteristic function* of the data distribution, and could be used to solve problems that require this feature (Section 4).

Algorithm 3 Unconstrained Generative Adversarial Training

1: **for** K in $[0, 1, \ldots, N]$ **do**
2:      **for** number of training iterations **do**
3:          Sample minibatch m samples $\{x_1, \ldots, x_m\}$ from p_k, and m samples $\{\tilde{x}_1, \ldots, \tilde{x}_m\}$ from p_{-k}.
4:          For each sample $\tilde{x}_i$ in $\{\tilde{x}_1, \ldots, \tilde{x}_m\}$, compute the perturbed sample $\tilde{x}_i^K$ by performing K steps
         normalized steepest descent $\tilde{x}_i^{k+1} \leftarrow \tilde{x}_i^k - \gamma \frac{\nabla \log(1 - D(\tilde{x}_i^k))}{\|\nabla \log(1 - D(\tilde{x}_i^k))\|_2}$ (at initialization $\tilde{x}_i^0 \leftarrow \tilde{x}_i$).
5:          Update D by maximizing $\frac{1}{m} \sum_{i=1}^m \left[\log D(x_i) + \log \left(1 - D(\tilde{x}_i^K)\right) \right]$ (single step).
6:      **end for**
7: **end for**

---

4 APPLICATIONS

In Figure 2(c) we show when p_{-k} is uniformly distributed in the data space the maximin problem solver gives us a D function that has no local maxima and global maxima at the support of p_k. This D function is very useful — we can identify at least two important applications:

- **Application 1: out-of-distribution (OOD) detection** The global maxima are at Supp(p_k) means any inputs that have lower D outputs can be correctly identified as OOD inputs.

- **Application 2: generative modeling** New samples of p_k can be generated by first random sampling from the data space and then translating them to the support of p_k by performing gradient ascent on D.

For practical applications, we have to deal with spaces of high dimensionality. In order to cover as much data space as possible, we use ImageNet (Deng et al., 2009) as the p_{-k} dataset. We further improve the dataset's diversity by using aggressive data augmentation. Given such strategies, data of p_{-k} could still be very sparse in a high dimensional space. In order to cause more local maxima to be eliminated, we could use a large perturbation limit in Algorithm 1, preferably an unlimited one.

Unconstrained training To facilitate the training with a potentially unconstrained perturbation limit, we propose Algorithm 3, an unconstrained generative adversarial training algorithm. Because of the steepest descent update rule (Line 4 in Algorithm 3, note there is no `Proj` operation here), for a given K, the perturbation imposed on each sample has a size that is always $\leq \lambda K$; hence the algorithm can be thought as gradually increasing the perturbation limit. We found this incremental training technique necessary for training models in high dimensional space — a phenomenon also

observed by Yin et al. (2020). According to the analysis in Section 3.2, the step size λ should be set to a sufficiently small value in order for step 4 to coverage to local maxima and step 5 to eliminate these local maxima. We observed that training is stable as long as λ is bellow a certain threshold, and this threshold is related to input size and D's architecture. In the algorithm we start K from 0, which means that at the first stage D is trained to discriminate between p_k and p_{-k}; this is not critical, but we found this pre-training causes following optimizations to converge faster.

5 EXPERIMENTS

In this section we evaluate our method on the task of generative modeling and out-of-distribution detection. Following Kurach et al. (2018), we evaluate our method on CIFAR-10 (Krizhevsky et al., 2009), CelebA-HQ-128 (Karras et al., 2017), and LSUN Bedroom-128 (Yu et al., 2015). Details of data preprocessing and dataset statistics are provided in Appendix C.

Model training We use Algorithm 3 to train D models. Depending on the studied dataset, p_k is set to one of the above three datasets, but we always use ImageNet (with data augmentation) as the p_{-k} dataset (images are resized to $32 \times 32 \times 3$ or $128 \times 128 \times 3$ depending on p_k dataset resolution). We also use the same D architectures and batch size as Kurach et al. (2018) (see Appendix C for more details of D architectures).

OOD detection evaluation For each one of the above three datasets, we use multiple OOD datasets (see Table 3) to test a D model's OOD detection performances. We further assume OOD inputs remain OOD under small L^p-norm perturbations. Under this assumption, we consider the problem of detecting *adversarial OOD inputs* — OOD inputs that are adversarially perturbed to cause the detection to fail, and evaluate our method under this challenging scenario. We also observe that increasing K in Algorithm 3 leads to changes in D performances on OOD and adversarial OOD detection. To study this phenomenon, we evaluate D models trained with different Ks using OOD inputs under various levels of perturbations. We use Outlier Exposure (OE, Hendrycks et al. (2018)) as the baseline method. The idea of OE is to use an auxiliary OOD dataset of large amount of diverse data to train the OOD detector. Because we also use a large-scale, diverse dataset (ImageNet) as the p_{-k} dataset, the OE approach can be thought of a special case of Algorithm 3 when we fix K to $K = 0$. We use area under the receiver operating characteristic curve (AUROC) as the performance metric (details of how AUROC and adversarial AUROC are computed are in Appendix C).

Generative modeling evaluation We generate new p_k samples by starting from some seed images and performing gradient ascent on D (Appendix C provides more details on generation). Due to the similarity between the studied approach and GANs (the former solves the maximin problem while the latter solves the minimax problem), we focus on a comparison with GANs. Kurach et al. (2018) is a large-scale study on the effects of various regularization and normalization techniques on GANs, and we compare our results with the best results obtained in their work.

5.1 RESULTS

OOD detection results Table 2 shows the average OOD detection performances of our method (see Appendix E for the complete results on individual OOD datasets). For each dataset, we train multiple D models with different Ks, and test models under various levels of perturbations [2] (ϵ-test, measured by L^2 norm). We can observe a general pattern across all the datasets: training with a larger K causes model performance on lower ϵ to decrease, a phenomenon that is also observed in other adversarial training scenarios (Madry et al., 2017; Tsipras et al., 2018). The baseline method ($K = 0$ models) becomes completely ineffective when models are exposed to adversarial OOD inputs.

On CelebA-HQ-128 and Bedroom-128 datasets our method obtains strong performances on detecting both OOD and adversarial OOD inputs. Performance on CIFAR-10 dataset is relatively low; we conjecture this is caused by the low capacity of the model (4.6MB disk space, Appendix C) and high complexity of the CIFAR-10 dataset. To test this hypothesis, we reduce the data complexity by replacing the CIFAR-10 dataset with the CIFAR-10 class-0 data. As shown in Table 2(b), this leads to considerable improvements on all performance entries. These results suggest that with a high capacity model and proper training, a robust OOD detection system is within reach.

---

[2]ϵ values are based on `https://github.com/MadryLab/robustness`.

Table 2 results are based on perturbations computed using PGD attacks (Madry et al., 2017) of particular combinations of steps and step size. To verify model robustness, we use a testing strategy that is widely adopted in the ML security community: use PGD attacks of different combinations of steps and step size to test model robustness. Appendix E shows that the worst results obtained with grid search are only marginally lower than reported ones in Table 2.

Table 2: Out-of-distribution detection performances (see Appendix E for expanded results)

(a) CIFAR-10				(b) CIFAR-10 class 0				(c) CelebA-HQ-128				(d) Bedroom-128			
	D model				D model				D model				D model		
ϵ-test	$K=0$	$K=15$	$K=25$	ϵ-test	$K=0$	$K=15$	$K=25$	ϵ-test	$K=0$	$K=20$	$K=40$	ϵ-test	$K=0$	$K=20$	$K=40$
0.0	0.974	0.910	0.861	0.0	0.994	0.987	0.976	0.0	1.000	1.000	1.000	0.0	0.996	0.996	0.970
1.0	0.005	0.785	0.764	1.0	0.135	0.932	0.932	5.0	0.001	0.998	0.998	5.0	0.000	0.976	0.938
2.0	0.000	0.519	0.614	2.0	0.008	0.682	0.827	10.0	0.000	0.964	0.988	10.0	0.000	0.815	0.837

Image generation results In Figure 3 shows samples generated by our method. In general we find our results to be more recognizable than GANs' results in Figure 10. We observed that the quality of generated images could be affected by the type of seed images (Appendix F.2), and increasing K in Algorithm 3 generally leads to better generations (Appendix F.1). In Figure 12 we demonstrate the method's application to face retouching. The fact that generated images are not realistic and have various artifacts suggest that the maximin problem is not well solved. This might be due to the model not being exposed to enough p_{-k} data (consider increase the number of iterations in the inner loop of Algorithm 3), or the limitation of model architecture or capacity.

Different from GANs that has various training stability issues, we found Algorithm 3 to be as stable as ordinary supervised training. The only failure mode (gradient ascent on D results in noisy images) that we observed is caused by λ being too large (Appendix D).

Figure 3: *Uncurated* samples generated by our method; GANs results is in Figure 10. Seed images used to generated these results are in Figure 11. The training time for models used to produce these generations are in Table 4.

6   CONCLUSIONS AND FUTURE WORK

In this paper we analyzed the optimal solutions of the GAT training objective and the convergence property of the training algorithm. The analysis of optimal solutions justifies the application of the GAT method to training robust predictive models. We made a comparative analysis of the maximin formulation and minimax formulation that are respectively employed by GAT and GANs. Guided by these theoretical results, we designed an unconstrained GAT algorithm, and evaluated it on the task of image generation and adversarial out-of-distribution detection. The competitive performance and training stability of the algorithm suggest that the studied approach could serve as a new tool for content creation, although we believe its performance could be further improved by optimizing hyperparameters and model architectures. Out-of-distribution detection results indicate that a OOD detection model's robustness could be improved by training the model against an adversary equipped with large-scale, diverse OOD data. The future work includes scaling up the training for larger images and high-capacity models, and extending the method's application to sequential and tabular data.

REFERENCES

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Ian Goodfellow. Nips 2016 tutorial: Generative adversarial networks. *arXiv preprint arXiv:1701.00160*, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. *arXiv preprint arXiv:1812.04606*, 2018.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. *arXiv preprint arXiv:1710.10196*, 2017.

Diederik P Kingma. Fast gradient-based inference with continuous latent variable models in auxiliary form. *arXiv preprint arXiv:1306.0733*, 2013.

Zico Kolter and Aleksander Madry. Adversarial robustness - theory and practice, 2019. URL `https://adversarial-ml-tutorial.org/`.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Karol Kurach, Mario Lucic, Xiaohua Zhai, Marcin Michalski, and Sylvain Gelly. A large-scale study on regularization and normalization in gans. *arXiv preprint arXiv:1807.04720*, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Suvojit Manna. celeba-hq-dataset-download (github repository), 2020. URL `https://github.com/suvojit-0x55aa/celebA-HQ-dataset-download`.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Shibani Santurkar, Andrew Ilyas, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Image synthesis with a single (robust) classifier. In *Advances in Neural Information Processing Systems*, pp. 1260–1271, 2019.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *arXiv preprint arXiv:2002.08347*, 2020.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. *arXiv preprint arXiv:1805.12152*, 2018.

Xuwang Yin, Soheil Kolouri, and Gustavo K Rohde. Gat: Generative adversarial training for adversarial example detection and robust classification. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=SJeQEp4YDH`.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

A MATHEMATICAL ANALYSIS OF OPTIMAL SOLUTIONS OF THE MAXIMIN PROBLEM

Recall that the support of p_t can be any subset of the pertubation space $\mathcal{S}$ and that $U(D, p_t) = \int p_k(x) \log D(x)) dx + \int p_t(x) \log(1 - D(x)) dx$. For convenience, we define the contour set inside $\mathcal{S}$ of D at α as $C_\alpha^D := \{x \in \mathcal{S} : D(x) = \alpha\}$, the region of $\text{Supp}(p_k)$ that is outside of $\mathcal{S}$ as $\Omega_{ko} := \text{Supp}(p_k) \setminus \mathcal{S}$ and the region of $\text{Supp}(p_k)$ that is in $\mathcal{S}$ as $\Omega_{ki} := \text{Supp}(p_k) \cap \mathcal{S}$. Note that $\text{Supp}(p_k) = \Omega_{ko} \cup \Omega_{ki}$. For a fixed D and let $\alpha_o = \max_{\Omega_{ko}} D$ and $\alpha_S = \max_\mathcal{S} D$. It is easy to check that U is minimized when $\text{Supp}(p_t)$ lies in the contour set $C_{\alpha_S}^D$. Let p_t^* be a distribution such that $\text{Supp}(p_t^*) \subset C_{\alpha_S}^D$. By direct computation we have that

$$U(D, p_t^*) = \int_{\Omega_{ko}} p_k(x) \log D(x) dx + \int_{\Omega_{ki}} p_k(x) \log D(x) dx + \log(1 - \alpha_S)$$

$$\leq (\int_{\Omega_{ko}} p_k)(\log \alpha_k) + (\int_{\Omega_{ki}} p_k)(\log \alpha_S) + \log(1 - \alpha_S)$$

$$\leq 0 + \beta_{ki} \log \frac{\beta_{ki}}{1 + \beta_{ki}} + \log \frac{1}{1 + \beta_{ki}},$$

where $\beta_\epsilon = \int_{\Omega_{ki}} p_k$. Note here we have used the fact the the function $f(y) = a \log y + b \log(1 - y)$ achieves its maximum at $y = \frac{a}{a+b}$. It is not difficult to see that the above inequality becomes an equality when

$$D(x) = \begin{cases} \alpha_k & x \in \Omega_{ko} \\ \alpha_S & x \in \Omega_{ki} \\ \leq \alpha_S & x \in \mathcal{S} \setminus \text{Supp}(p_k) \end{cases}, \tag{6}$$

where $\alpha_k = 1$ and $\alpha_S = \frac{\beta_{ki}}{1+\beta_{ki}}$. Note that D does not need to be defined outside $\mathcal{S} \cup \text{Supp}(p_k)$.

Scenario 1   Here we deal with the case when ϵ is large enough such that $\text{Supp}(p_k) \subset \mathcal{S}$, in which case $\Omega_{ko} = \emptyset$, $\Omega_{ki} = \text{Supp}(p_k)$ and $\alpha_S = \frac{1}{2}$. Hence by the above analysis one can check that U achieves its optimum when $D \equiv \alpha_S = \frac{1}{2}$ on $\text{Supp}(p_k)$ and $D \leq \frac{1}{2}$ on $\mathcal{S} \setminus \text{Supp}(p_k)$. In summary, the maximin problem achieves its optimum when D outputs $\frac{1}{2}$ on the support of p_k and and values less or equal to $\frac{1}{2}$ on samples outside the support of p_k but in $\mathcal{S}$.

Scenario 2   Here we deal with the case when ϵ is small enough such that the $\mathcal{S} \cap \text{Supp}(p_k) = \emptyset$, in which case $\Omega_{ko} = \text{Supp}(p_k)$, $\Omega_{ki} = \emptyset$ and $\alpha_S = 0$. Hence U achieves its optimum when $D \equiv 1$ on $\text{Supp}(p_k)$ and $D \equiv 0$ on $\mathcal{S}$. In summary, the maximin problem achieves its optimum when D outputs 1 on the support of p_k and zero on the the perturbation space $\mathcal{S}$.

Scenario 3   Here we deal with the case when $\mathcal{S} \cap \text{Supp}(p_k) \neq \emptyset$ and $\text{Supp}(p_k) \not\subset \mathcal{S}$. In summary, the maximin problem achieves its optimum when D outputs 1 on the set of samples inside the support of p_k but outside of the perturbation space $\mathcal{S}$ and $\frac{\beta_{ki}}{1+\beta_{ki}}$ on the set of samples that are in the intersection of the support of p_k and $\mathcal{S}$ and values less or equal to $\frac{\beta_{ki}}{1+\beta_{ki}}$ on $\mathcal{S}$.

Remark   The first two cases can be seen as the special cases of the third one.

B ALGORITHM 1 CONVERGENCE

B.1 STEP 3 ALWAYS DECREASE β

We assume when $\alpha < \beta$, D has a single global maximum point (i.e., $|B| = 1$).

Lemma 1. *If $\alpha < \beta$ and $|B| = 1$, Algorithm 1 always decreases β.*

Proof. Let $\beta := \max_{\text{Supp}(p_k)} D$, $C := \{x \in \text{Supp}(p_k) : D(x) < \beta\}$, and $\gamma := \max_C D$. (Same as the proof for Proposition 1, we consider the case of $\beta, \gamma > \frac{1}{2}$.) Going back to Algorithm 1, step 2

moves mass of p_{-k} to B. Since B has only one element, the mass is concentrated on this single point. Step 3's optimization causes γ to increase and β to decrease. The intuition here is that if step 3's update is small enough, these two values will meet in an intermediate point. Let the resulting values be γ_1 and β_1. If step 3's update on D is sufficiently small such that $\gamma_1 - \gamma < \beta - \gamma$, then we have $\max\{\beta_1, \gamma_1\} < \beta$ — the maximum value of D on $\mathrm{Supp}(p_k)$ has decreased. $\qquad\square$

B.2 THE EFFECTS OF ALTERNATING OPTIMIZATION

(a) at initialization   (b) step 2 updates p_t (c) step 3 updates D

(d) step 2 updates p_t (e) step 3 updates D (f) step 2 updates p_t

Figure 4: The results of p_t and D in the first few iterations of a 2D simulation of Algorithm 1. Step 2 solves the inner minimization, causes support of p_t (red points) to be concentrated in local maxima points. Step 3 update D by increasing its outputs on the support of p_k and decreasing its outputs on the support of p_t, causes local maxima to be suppressed.

B.3 MORE 2D SIMULATION RESULTS

Figure 5: Solutions obtained by the *maximin* problem solver (Algorithm 1) with different initializations of D. First row are results when p_{-k} is at bottom left (see Figure 2), and second row are results when p_{-k} are uniform distributions.

Figure 6: Solutions obtained by the *minimax* problem solver (Algorithm 2) with different initializations of D. Note that in all cases p_t (red distribution) matches p_k (blue distribution), but D has unpredictable outputs on $\mathcal{X} \setminus \text{Supp}(p_k)$. The initial position of the red distribution is in bottom left corner (see Figure 4(a)).

C   EXPERIMENTAL SETUP

Dataset preprocessing and statistics   CelebA-HQ-128 dataset is downloaded from Manna (2020). The Bedroom-128 dataset is created from the corresponding LSUN dataset by center cropping the images using a square and then resizing to 128×128. CIFAR-10 has 60K training images and 10K test images. We manually split CelebA-HQ-128 into a training split of 27K images and a test split of 3K images, and Bedroom-128 into a training split of 300K images and a test split of 3K images.

Detector architecture   Following Kurach et al. (2018), we use tow network architecture for the experiments. For CIFAR-10 task we use the "ResNet-CIFAR" architecture (Kurach et al. (2018) Table 7a). The architecture has 4 customized ResBlocks and takes 4.6MB disk space. For other $128 \times 128 \times 3$ datasets, we use the "ResNet19 discriminator" architecture (Kurach et al. (2018) Table 5a). The architecture has 6 customized ResBlocks and takes 60MB disk space

More training details   Following Yin et al. (2020), we use a pretrained D model to bootstrap optimization: for CIFAR-10 the D model is pretrained on the CIFAR-10 classification task, and for other datasets it is pretrained on the ImageNet classification task (Russakovsky et al., 2015). For all the datasets, the D update step in Algorithm 3 is performed using a SGD optimizer with momentum of 0.9. The learning rate of the optimizer for CIFAR-10 datast is 0.0005, for CelebA-HQ-128 is 0.001, and for Bedroom-128 is 0.0025. The λ value is set to 0.1 for CIFAR-10, and 0.6 for CelebA-HQ-128 and Bedroom-128. For all the trainings we use a batch size of 64, same as Kurach et al. (2018). The training follows standard supervised training, and doesn't use any regularization or normalization.

Image generation details   We generate a new sample of p_k by starting from some seed sample and performing gradient ascent on D using the update rule in equation 3. In this case, the seed sample is supposed to be out of the distribution of p_k. When using the update rule in equation 3, we need to specify the step size λ, the number of steps, and ϵ for the Proj operation. We use the following configurations for generation:

- For CIFAR-10 generation (Figure 3(a), Figure 13, and Figure 16), we use step size 0.1, steps 200, and $\epsilon = 15$.
- For CelebA-HQ-128 generation (Figure 3(b), Figure 14, and Figure 17), we use step size 1.2, steps 100, and $\epsilon = 40$.
- For CelebA-HQ-128 generation (Figure 3(c), Figure 15, and Figure 18), we use step size 0.8, steps 400, and $\epsilon = 70$.

We note different configurations could lead to different generation results.

AUROC computation   AUROC is a metric that measures a discriminative model's ability to separate two sets of data. To compute the AUROC score of a trained D model for a given p_k and p_{OOD} dataset, we first use the D model to get the logit outputs of samples of these two datasets, and then use scikit-learn (Pedregosa et al., 2011)'s "sklearn.metrics.auc" function to compute the score (with samples in p_k labeled as 1s and samples in p_{OOD} labeled as 0s). We always use the test splits of the p_{OOD} and p_k datasets to do the above calculation.

Adversarial AUROC computation   To compute the adversarial AUROC score of a D model for a given p_{OOD} and p_k dataset, we first compute an adversarial OOD dataset p'_{OOD} by taking samples from p_{OOD} and performing L^2-based PDG attack (Madry et al., 2017) against the D model. We then compute the Adversarial AUROC score by computing the AUROC score on the p'_{OOD} and p_k datasets. Same as the AUROC computation, we always use the test splits of the p_{OOD} and p_k to do the above calculation.

Table 3: In-distribution dataset and corresponding out-of-distribution datasets (images of OOD datasets are resized to the image size of the corresponding in-distribution dataset)

In-distribution dataset (p_k)	Out-of-distribution datasets (p_{OOD})
CIFAR-10	Gaussian noise, Uniform noise, SVHN (Netzer et al., 2011), CIFAR-100 (Krizhevsky et al., 2009), ImageNet, CelebA-HQ-128, Bedroom-128
CelebA-HQ-128	Gaussian noise, Uniform noise, SVHN, CIFAR-100, ImageNet, CIFAR-10, Bedroom-128
Bedroom-128	Gaussian noise, Uniform noise, SVHN, CIFAR-100, ImageNet, CelebA-HQ-128, CIFAR-10

Table 4: Model training time. CIFAR-10 model was trained on a single 2080Ti GPU, the other two models were trained on two 2080Ti GPUs.

Model	Training Time
CIFAR-10 $K = 40$ model	2 days 23 hours
CelebA-HQ-128 $K = 80$ model	7 days 12 hours
Bedroom-128 $K = 55$ model	14 days 15 hours

D FAILURE MODE DIAGNOSIS

We observe that in Algorithm 3, if λ is set to a too large value, the algorithm fails to learn a D that is useful for image generation. In this section we discuss the training dynamics of the case of an appropriate λ value and the case of λ being too large.

λ **is small enough**   In Algorithm 3 as we increase K, p_t gradually converges to p_k. In this process it becomes increasingly difficulty for the D model to differentiate these two distributions. This phenomenon can be observed in Figure 7 : the training loss (binary cross-entropy loss) of the D model becomes larger and larger (left subfigure), and eventually these two distributions become indistinguishable (AUROC ≈ 0.5, middle subfigure). From the right subfigure we can see that D's performance on p_{-k} vs. p_k is also affected by the increase in K value.

Figure 7: CIFAR-10 training curves of $\lambda = 0.1$. Left: training loss curves, middle: AUROC curves (p_t vs. p_k), and right: AUC curves (p_{-k} vs. p_k).

Figure 8: CIFAR-10 training curves of a failed training instance ($\lambda = 0.6$).

λ **is too large**   The failure mode caused by λ being too large is easy to identify (Figure 8): the training loss quickly decreases to 0 as K increases (left subfigure), p_t and p_k become perfectly separable (middle subfigure), and D model becomes unable to separate p_{-k} from p_k (right subfigure).

In general, with a small enough λ value, an increase of sample quality could be expected after model is trained with a larger K. This is the case when λ is 0.1, but not when it is 0.6 (Figure 9).

(a) $\lambda = 0.1$ (b) $\lambda = 0.6$

Figure 9: Generated samples after training with an increasing sequence of K values ($K = 0, 1, 2$). Sample quality improved when $\lambda = 0.1$, but didn't when $\lambda = 0.6$.

E   EXPANDED OOD RESULTS

E.1   CIFAR-10

Table 5: The performances of CIFAR-10 $K = 25$ model under PGD attacks of different combinations of steps and step size. The perturbation limit is $\epsilon = 2.0$ (L^2 norm). Each entry is computed using 500 positive samples and 500 negative samples.

OOD dataset: Gaussian noise

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.6717	0.6679	0.6766	0.7052	0.7179
500	0.6701	0.6652	0.6723	0.6924	0.7023
1000	0.6691	0.6648	0.6704	0.6877	0.6946

OOD dataset: Uniform noise

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.9674	0.9662	0.9658	0.9660	0.9667
500	0.9673	0.9662	0.9657	0.9657	0.9659
1000	0.9673	0.9660	0.9656	0.9657	0.9657

OOD dataset: ImageNet

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.5211	0.5169	0.5192	0.5252	0.5323
500	0.5200	0.5165	0.5182	0.5208	0.5241
1000	0.5199	0.5163	0.5180	0.5205	0.5222

OOD dataset: Bedroom-128

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.5483	0.5439	0.5461	0.5535	0.5611
500	0.5477	0.5433	0.5441	0.5495	0.5523
1000	0.5469	0.5434	0.5439	0.5478	0.5501

OOD dataset: SVHN

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.5519	0.5494	0.5518	0.5589	0.5665
500	0.5510	0.5487	0.5499	0.5546	0.5575
1000	0.5505	0.5479	0.5497	0.5533	0.5549

OOD dataset: CelebA-HQ

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.5660	0.5633	0.5634	0.5673	0.5708
500	0.5658	0.5624	0.5627	0.5649	0.5666
1000	0.5658	0.5622	0.5624	0.5642	0.5655

OOD dataset: CIFAR-100

steps	step size				
	2.0	1.0	0.5	0.1	0.05
200	0.4310	0.4284	0.4288	0.4340	0.4388
500	0.4308	0.4281	0.4285	0.4306	0.4328
1000	0.4306	0.4275	0.4276	0.4299	0.4309

Table 6: OOD detection performances of the CIFAR-10 $K = 0$ model on individual datasets. Each entry in this table and the following two tables is computed using 3000 positive samples and 3000 negative samples. When test $\epsilon > 0$, perturbations are computed using PGD attacks of steps 200 and step size 0.5.

ϵ-test	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	1.0000	0.9992	0.9905	0.9908	0.9956	0.9953	0.8475	0.9741
1.0	0.0000	0.0372	0.0001	0.0000	0.0000	0.0000	0.0001	0.0053
2.0	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

Table 7: OOD detection performances of the CIFAR-10 $K = 15$ model on individual datasets

ϵ-test	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	0.9920	1.0000	0.8593	0.9249	0.9182	0.8731	0.8036	0.9102
1.0	0.9252	1.0000	0.6918	0.7736	0.7590	0.7264	0.6156	0.7845
2.0	0.4693	0.9988	0.4067	0.4520	0.4451	0.5098	0.3505	0.5189

Table 8: OOD detection performances of the CIFAR-10 $K = 25$ model on individual datasets

ϵ-test	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	0.9022	0.9998	0.8138	0.8735	0.8721	0.8248	0.7411	0.8610
1.0	0.8350	0.9942	0.6943	0.7512	0.7510	0.7171	0.6075	0.7643
2.0	0.6851	0.9708	0.5178	0.5493	0.5662	0.5724	0.4380	0.6142

E.2 CIFAR-10 CLASS 0

Table 9: OOD detection performances of the CIFAR-10 $K = 0$ model on individual datasets. Each entry in this table and the following two tables is computed using 1000 positive samples (the test set only has 1000 samples) and 1000 negative samples. PGD attack setting follows the CIFAR-10 experiment.

ϵ-test	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	1.0000	1.0000	0.9917	0.9903	0.9903	0.9996	0.9880	0.9943
1.0	0.0012	0.9113	0.0034	0.0005	0.0007	0.0178	0.0111	0.1351
2.0	0.0000	0.0590	0.0000	0.0000	0.0000	0.0000	0.0000	0.0084

Table 10: OOD detection performances of the CIFAR-10 $K = 15$ model on individual datasets

ϵ-test	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	0.9981	1.0000	0.9779	0.9838	0.9833	0.9999	0.9687	0.9874
1.0	0.9394	0.9999	0.9054	0.9121	0.8920	0.9972	0.8769	0.9319
2.0	0.5993	0.9913	0.6183	0.5881	0.4485	0.9499	0.5764	0.6817

Table 11: OOD detection performances of the CIFAR-10 $K = 25$ model on individual datasets

ϵ-test	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	0.9756	1.0000	0.9644	0.9701	0.9698	0.9997	0.9527	0.9761
1.0	0.8984	0.9963	0.9150	0.9181	0.9073	0.9976	0.8894	0.9317
2.0	0.7627	0.9787	0.7989	0.7868	0.7274	0.9829	0.7526	0.8271

E.3 CELEBA-HQ-128

Table 12: The performances of CelebA-HQ-128 $K = 40$ model under PGD attacks of different combinations of steps and step size. The perturbation limit is $\epsilon = 10$ (L^2 norm). Each entry is computed using 500 positive samples and 500 negative samples.

OOD dataset: Gaussian noise

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	0.9980	0.9980	0.9980	0.9980	0.9980
200	0.9980	0.9980	0.9980	0.9980	0.9980
500	0.9980	0.9980	0.9980	0.9980	0.9980

OOD dataset: Uniform noise

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	1.0000	1.0000	1.0000	1.0000	1.0000
200	1.0000	1.0000	1.0000	1.0000	1.0000
500	1.0000	1.0000	1.0000	1.0000	1.0000

OOD dataset: ImageNet

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	0.9931	0.9922	0.9920	0.9923	0.9929
200	0.9932	0.9921	0.9918	0.9920	0.9923
500	0.9931	0.9917	0.9916	0.9918	0.9920

OOD dataset: Bedroom-128

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	0.9943	0.9928	0.9926	0.9931	0.9941
200	0.9942	0.9925	0.9922	0.9925	0.9932
500	0.9942	0.9924	0.9920	0.9921	0.9925

OOD dataset: SVHN

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	0.9814	0.9777	0.9773	0.9793	0.9824
200	0.9808	0.9769	0.9759	0.9772	0.9793
500	0.9806	0.9763	0.9752	0.9756	0.9770

OOD dataset: CIFAR-10

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	0.9854	0.9826	0.9823	0.9831	0.9851
200	0.9854	0.9823	0.9816	0.9820	0.9833
500	0.9851	0.9819	0.9810	0.9813	0.9821

OOD dataset: CIFAR-100

steps	step size				
	8.0	4.0	2.0	1.0	0.5
100	0.9796	0.9758	0.9753	0.9765	0.9788
200	0.9794	0.9753	0.9744	0.9750	0.9764
500	0.9792	0.9750	0.9738	0.9740	0.9749

Table 13: OOD detection performances of the CelebA-HQ-128 $K = 0$ model on individual datasets. Each entry in this table and the following two tables is computed using 3000 positive samples and 3000 negative samples. When test $\epsilon > 0$, perturbations are computed using PGD attacks of steps 200 and step size 2.0.

ϵ-test	CIFAR-10	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CIFAR-100	mean
0.0	1.0000	1.0000	1.0000	0.9999	1.0000	1.0000	1.0000	1.0000
5.0	0.0000	0.0000	0.0048	0.0004	0.0000	0.0000	0.0000	0.0008
10.0	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

Table 14: OOD detection performances of the CelebA-HQ-128 $K = 20$ model on individual datasets

	CIFAR-10	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CIFAR-100	mean
0.0	0.9999	1.0000	1.0000	1.0000	1.0000	1.0000	0.9999	1.0000
5.0	0.9974	1.0000	1.0000	0.9988	0.9993	0.9965	0.9959	0.9983
10.0	0.9459	0.9903	0.9996	0.9805	0.9809	0.9190	0.9291	0.9636

Table 15: OOD detection performances of the CelebA-HQ-128 $K = 40$ model on individual datasets

	CIFAR-10	Gaussian noise	Uniform noise	ImageNet	Bedroom	SVHN	CIFAR-100	mean
0.0	0.9999	1.0000	1.0000	0.9999	1.0000	0.9999	0.9998	0.9999
5.0	0.9978	0.9997	1.0000	0.9990	0.9992	0.9968	0.9961	0.9984
10.0	0.9829	0.9958	0.9999	0.9925	0.9927	0.9744	0.9744	0.9875

E.4 BEDROOM-128

Table 16: The performances of Bedroom $K = 40$ model under PGD attacks of different combinations of steps and step size. The perturbation limit is $\epsilon = 10$ (L^2 norm). Each entry is computed using 500 positive samples and 500 negative samples.

OOD dataset: Gaussian noise

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.8850	0.8808	0.9022	0.9291	0.9409
200	0.8774	0.8688	0.8754	0.8990	0.9280
500	0.8748	0.8642	0.8645	0.8710	0.8874

OOD dataset: Uniform noise

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.9787	0.9768	0.9771	0.9789	0.9827
200	0.9784	0.9762	0.9762	0.9769	0.9787
500	0.9784	0.9759	0.9756	0.9759	0.9766

OOD dataset: ImageNet

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.8564	0.8516	0.8550	0.8605	0.8679
200	0.8549	0.8490	0.8508	0.8548	0.8598
500	0.8540	0.8474	0.8474	0.8501	0.8532

OOD dataset: CIFAR-10

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.7673	0.7545	0.7619	0.7734	0.7908
200	0.7636	0.7486	0.7532	0.7612	0.7721
500	0.7606	0.7437	0.7465	0.7513	0.7577

OOD dataset: SVHN

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.8133	0.8064	0.8155	0.8266	0.8429
200	0.8075	0.7980	0.8046	0.8131	0.8262
500	0.8022	0.7916	0.7965	0.8021	0.8105

OOD dataset: CelebA-HQ

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.9211	0.9196	0.9220	0.9253	0.9301
200	0.9200	0.9176	0.9195	0.9217	0.9251
500	0.9194	0.9164	0.9175	0.9190	0.9211

OOD dataset: CIFAR-100

	step size				
steps	8.0	4.0	2.0	1.0	0.5
100	0.7999	0.7899	0.7950	0.8062	0.8216
200	0.7954	0.7830	0.7869	0.7946	0.8050
500	0.7918	0.7778	0.7804	0.7855	0.7915

Table 17: OOD detection performances of the Bedroom-128 $K = 0$ model on individual datasets. Each entry in this table and the following two tables is computed using 3000 positive samples and 3000 negative samples. When test $\epsilon > 0$, perturbations are computed using PGD attacks of steps 200 and step size 2.0.

ϵ-test	CIFAR-10	Gaussian noise	Uniform noise	ImageNet	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	1.0000	1.0000	1.0000	0.9713	1.0000	0.9999	1.0000	0.9959
5.0	0.0000	0.0000	0.0010	0.0002	0.0000	0.0000	0.0000	0.0002
10.0	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

Table 18: OOD detection performances of the Bedroom-128 $K = 20$ model on individual datasets

	CIFAR-10	Gaussian noise	Uniform noise	ImageNet	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	0.9959	1.0000	1.0000	0.9892	0.9955	0.9990	0.9946	0.9963
5.0	0.9604	0.9991	1.0000	0.9569	0.9634	0.9900	0.9623	0.9760
10.0	0.6834	0.9085	0.9984	0.7888	0.7061	0.8937	0.7251	0.8148

Table 19: OOD detection performances of the Bedroom-128 $K = 40$ model on individual datasets

	CIFAR-10	Gaussian noise	Uniform noise	ImageNet	SVHN	CelebA-HQ	CIFAR-100	mean
0.0	0.9525	0.9932	0.9993	0.9593	0.9474	0.9824	0.9578	0.9703
5.0	0.8986	0.9649	0.9967	0.9267	0.8995	0.9650	0.9114	0.9376
10.0	0.7274	0.8642	0.9749	0.8417	0.7740	0.9112	0.7651	0.8369

F EXPANDED GENERATION RESULTS

Figure 10: Samples generated by GANs (Kurach et al., 2018); results of our method are in Figure 3.

(a) CIFAR-10 seed images   (b) CelebA-HQ-128 seed images   (c) LSUN-BEDROOM seed images

Figure 11: Seed images used to generated samples in Figure 3. Seed images for CIFAR-10 and Bedroom-128 are generated by applying Gaussian blur to random images from ImageNet test set. Seed images for CelebA-HQ-128 are generated by a VAE model (Kingma, 2013; Rezende et al., 2014) trained on the CelebA-HQ-128 dataset.

Figure 12: Face retouching results. Top row are original images from the CelebA-HQ-128 test set, and bottom row are enhanced images. The strength of retouching could be increased by performing more steps of gradient ascent on D.

F.1 IMAGE GENERATION ABLATION STUDY: EFFECT OF K

(a) Generated by $K = 15$ model   (b) Generated by $K = 25$ model   (c) Generated by $K = 40$ model

Figure 13: Samples generated by CIFAR-10 models trained with different Ks. These generations all use the seed images in Figure 11(a).

(a) Generated by $K = 20$ model   (b) Generated by $K = 40$ model   (c) Generated by $K = 80$ model

Figure 14: Samples generated by CelebA-HQ-128 models trained with different Ks. These generations all use the seed images in Figure 11(b).

(a) Generated by $K = 20$ model   (b) Generated by $K = 40$ model   (c) Generated by $K = 55$ model

Figure 15: Samples generated by Bedroom-128 models trained with different Ks. These generations all use the seed images in Figure 11(c).

F.2 IMAGE GENERATION ABLATION STUDY: EFFECT OF DIFFERENT TYPES OF SEED IMAGES

(a) Seed images   (b) Generated by $K = 40$ model

Figure 16: Samples generated by the CIFAR-10 $K = 40$ model using seed images on the left. Seed images are from OOD datasets (Table 3.

(a) Seed images   (b) Generated by $K = 55$ model

Figure 17: Samples generated by the CelebA-HQ-128 $K = 80$ model using seed images on the left. Seed images are random samples of OOD datasets (Table 3.

(a) Seed images   (b) Generated by $K = 55$ model

Figure 18: Samples generated by the Bedroom-128 $K = 55$ model using seed images on the left. Seed images are random samples of OOD datasets (Table 3).