Towards Robust Referring Expression Segmentation for Complex Reasoning in the Wild

Abstract

Despite the advances in Referring Expression Segmentation (RES) benchmarks, their evaluation protocols remain constrained, primarily focusing on either single targets with short queries (containing minimal attributes) or multiple targets from distinctly different queries on a single domain. This limitation significantly hinders the assessment of more complex reasoning capabilities in RES models. We introduce WildRES, a novel benchmark that incorporates long queries with diverse attributes and non-distinctive queries for multiple targets. This benchmark spans diverse application domains, thus enabling more rigorous evaluation of complex reasoning capabilities in real-world settings. Our analysis reveals that existing RES models demonstrate substantial performance deterioration when evaluated on WildRES. To address this challenge, we introduce SynRES, an automated pipeline generating densely paired compositional synthetic training data through three innovations: (1) a dense caption-driven synthesis for attribute-rich image-mask-expression triplets, (2) reliable semantic alignment mechanisms rectifying caption-pseudo mask inconsistencies via Image-Text Aligned Grouping, and (3) domain-aware augmentations incorporating mosaic composition and superclass replacement to emphasize generalization ability and distinguishing attributes over object categories. Experimental results demonstrate that models trained with SynRES achieve consistent improvements on not only our complex WildRES benchmark but also classic RES benchmarks (e.g. RefCOCO/+/g). Code is available at this link.

1 Introduction

Recent advancements in Large Multimodal Models (LMMs) (Liu et al., 2024b,a) and foundational segmentation models (Kirillov et al., 2023; Ravi et al., 2025) have significantly improved Referring Expression Segmentation (RES) (Lai et al., 2024; Xia et al., 2024; Ren et al., 2024; Rasheed et al., 2024; Zhang et al., 2024b; Chen et al., 2024; Zhang et al., 2024a; Zhu et al., 2026; Dai et al., 2025; Liu et al., 2025, 2026). Compared with traditional RES approaches (Wang et al., 2022; Liu et al., 2023a; Yang et al., 2022b; Zhao et al., 2023b; Xu et al., 2023; Zou et al., 2023) trained on image-mask-expression triplets (Yu et al., 2016; Mao et al., 2016; Liu et al., 2023a), recent models leverage diverse supervision from semantic segmentation, referring image segmentation, and VQA datasets (Caesar et al., 2018; Zhou et al., 2017; Neuhold et al., 2017; Chen et al., 2014; He et al., 2022; Yu et al., 2016; Mao et al., 2016; Liu et al., 2023a, 2024b; Antol et al., 2015; Liu et al., 2024a). This broader supervision improves expression understanding and real-world applicability.

Numerous RES benchmarks (Rohrbach et al., 2016; Yu et al., 2016; Mao et al., 2016; Liu et al., 2023a; Hu et al., 2023) have been proposed to evaluate compositional reasoning and generalization. However, they largely focus on expressions with minimal attributes (Yu et al., 2016; Rohrbach et al., 2016) or distinctive countable targets (Liu et al., 2023a) within the homogeneous COCO domain (Kazemzadeh et al., 2014), as shown in Fig. 1-(a. 1, 5). This limits the evaluation of complex reasoning required in real-world scenarios. To address this limitation, we introduce **WildRES**, a new test benchmark with three key challenges: (1) longer queries with many attributes, (2) shared non-distinctive attributes for multiple targets, and (3) domain-shifted images from crowded scenes (Shao et al., 2018), autonomous driving (Cordts et al., 2016), and robotic applications (Mitash et al., 2023). As shown in Fig. 1-(b), existing RES models such as LISA (Lai et al., 2024) exhibit substantial degradation on WildRES.

A natural solution is to acquire large-scale training data with complex expressions and domain-shifted imagery, but manual annotation is pro-

Figure 1: (a) Comparison of existing RES benchmarks with our proposed WildRES benchmark. Previous RES datasets (Yu et al., 2016; Liu et al., 2023a) mainly focus on short single-target queries (1) or distinctive multi-target queries (5) within similar domains, limiting the evaluation of complex reasoning and generalization. WildRES introduces attribute-rich single-target expressions (2)-(4), shared-attribute multi-target expressions (6)-(8), and domain-shifted subsets. (b) LISA (Lai et al., 2024) suffers notable degradation on WildRES, while with our synthetic data generation method, SynRES, improves compositional reasoning.

hibitively costly. Crowdsourced datasets such as RefCOCO often contain minimal expressions sufficient only for target identification. Existing synthetic segmentation methods (Wu et al., 2023b; Nguyen et al., 2023; Yang et al., 2023; Ye et al., 2024) mainly generate image-mask pairs and lack referring expressions required for RES. Pseudo-RIS (Yu et al., 2024) produces captions and pseudo-masks from SAM (Ravi et al., 2025) trained on COCO (Kazemzadeh et al., 2014), but does not specifically address multi-target or ambiguous queries. Thus, it remains unclear how to generate and utilize synthetic data for complex, attribute-rich RES across diverse domains. Crucially, such data must preserve fine-grained alignment among referring expressions, target masks, and visual attributes to benefit RES models.

We propose **SynRES**, which automatically generates densely paired synthetic image-mask-text triplets with rich referring expressions via generative models. As illustrated in Fig. 3, SynRES produces images containing identical objects with heterogeneous attributes, enabling models to distinguish diverse attribute combinations. SynRES consists of three steps: 1) generating distinctive synthetic expressions and corresponding images for the same object, 2) grouping semantically similar expressions and aligning them with synthetic masks, and 3) applying domain-aware image aug-

mentation and semantic text augmentation. Specifically, we use real images, masks, and captioning models to create attribute-rich captions (Yu et al., 2024), which are then used as prompts for Text-to-Image (T2I) models. To reduce pseudo-mask errors, related expressions are grouped and aligned with corresponding masks. Finally, RES-oriented augmentations, including mosaic augmentation and superclass replacement, improve multi-target reasoning and encourage detailed target descriptions.

Integrating SynRES consistently improves RES across diverse architectures and benchmarks, including both in-domain and domain-shifted WildRES settings. Ablation studies further confirm the importance of both textual and visual augmentation components.

Our contributions are summarized as follows:

1. We propose WildRES, a novel RES benchmark covering single-target many-attribute cases, multi-target shared-attribute cases, and diverse domain-shifted scenarios.

2. We introduce SynRES, an automated pipeline for generating densely paired synthetic datasets with diverse attributes and reliable pseudo-masks.

3. Experiments demonstrate that SynRES is model-agnostic and improves existing RES models on both wild scenarios and classic benchmarks.

2 Related Works

Referring Expression Segmentation with Large Multimodal Models. Recent LMM-based RES models, starting from LISA (Lai et al., 2024), have advanced language-based segmentation by leveraging multimodal reasoning and segmentation capabilities (Xia et al., 2024; Ren et al., 2024; Rasheed et al., 2024; Zhang et al., 2024b; Chen et al., 2024; Zhang et al., 2024a; Wu et al., 2024, 2025). These models are trained with diverse supervision from semantic segmentation (Caesar et al., 2018; Zhou et al., 2017; Neuhold et al., 2017; Chen et al., 2014; He et al., 2022), RES (Yu et al., 2016; Mao et al., 2016; Liu et al., 2023a), VQA (Liu et al., 2024b; Antol et al., 2015; Liu et al., 2024a), and specialized datasets (Lai et al., 2024; Rasheed et al., 2024). Recent works further explore generalized grounding and explicit reasoning (Dai et al., 2025; Liu et al., 2025; Zhu et al., 2026; Liu et al., 2026). Nevertheless, existing models still degrade on our challenging WildRES benchmark, motivating our model-agnostic approach, SynRES.

Synthetic Data and Augmentation for Referring Expression Segmentation. Synthetic segmentation data has evolved from GAN-based generation (Zhang et al., 2021; Li et al., 2022) to diffusion-based image-mask synthesis (Ho et al., 2020; Song et al., 2021; Nguyen et al., 2023; Yang et al., 2023; Ye et al., 2024; Zhao et al., 2023a; Fan et al., 2024; Xie et al., 2024b; Tu et al., 2025). Multimodal and RES-specific augmentation methods have also been studied (Hao et al., 2023; Liu et al., 2023b; Jin et al., 2024; Wu et al., 2023a; Ha et al., 2024; Yu et al., 2024), but they do not fully capture the joint alignment among images, masks, and referring expressions. In contrast, SynRES generates densely aligned image-mask-text triplets and jointly augments all three modalities to improve robustness and generalization. Extended related work is provided in Appendix A.

3 Referring Expression Segmentation in the Wild

3.1 Problem Definition

In RES, given an input image x_{img} and an input language query x_{txt}, the goal is to produce the corresponding binary segmentation mask M. In addition to this traditional RES, we aim to address the three key aspects: i) using referring expressions with diverse attributes to pinpoint a single precise target in Fig. 1-(a, 2-4), ii) identifying specific multiple targets with shared attributes in Fig. 1-(a, 6-8), and iii) extending these two aspects to other domains, as demonstrated in Fig. 1-(a, 3, 4, 7, 8). For multi-target scenarios, we select images containing at least three objects and design the referring expressions so that only a subset of these objects satisfies the specified attributes. Detailed descriptions emphasize unique characteristics of individual objects, compelling segmentation models to discern both shared and distinct features.

3.2 WildRES: A New RES Benchmark for Advanced Reasoning and Generalization

We introduce WildRES, an evaluation benchmark designed to evaluate segmentation models in complex, real-world contexts with 724 images and 941 expressions. WildRES does not contain the training set, only the validation and test set. WildRES includes both in-distribution images (WildRES-ID) sourced from MSCOCO (Caesar et al., 2018) and domain-shifted images (WildRES-DS) representing unseen scenes from datasets such as Crowd-Human (Shao et al., 2018), Cityscapes (Cordts et al., 2016), and ARMBench (Mitash et al., 2023), all aimed at assessing model robustness in challenging environments. WildRES is divided into two subsets: Many Attribute (MA) and Shared Attribute (SA). MA subsets comprise images that contain at least 5 objects, with each caption manually reviewed to ensure precise alignment with its corresponding segmentation mask. SA subsets focus on images featuring multiple, referable objects from the same class that exhibit distinct attributes, thereby evaluating fine-grained segmentation capabilities. In WildRES-ID, both subsets are present; in contrast, within WildRES-DS, datasets are categorized according to their dominant features—CrowdHuman, which contains numerous individuals, corresponds to the Many Attribute subset, while Cityscapes and ARMBench, featuring multiple objects with shared attributes, align with the Shared Attribute subset. The exact quantity for each image and expression constituting WildRES is described in detail in Appendix B.

Existing RES datasets often lack diversity in their attributes. To systematically analyze this limitation, we categorized referring expressions into 8 distinct attributions (more details of each attributions are in Appendix C). Utilizing GPT-4o-mini (Achiam et al., 2023), we classified referring expressions from these datasets into the predefined categories. Fig. 2 illustrates the results of this anal-

Figure 2: Number of attributions in classic RES datasets vs. WildRES. Using GPT-4o-mini (Achiam et al., 2023), we counted the number of attributes shown in Table B. Single-target expressions in WildRES often exceed 11 attributes to specify a target, while multi-target expressions have fewer attributes, similar to classic RES datasets.

ysis. We observed that expressions from traditional RES datasets are composed of simple and easily targetable samples, with a mean attribute count below 4. In contrast, WildRES's Many Attribute expressions exceed an average of 11 attributes, while maintaining a consistent number of attributes in expressions when referring to multiple targets sharing attributes. Detailed differences from previous datasets (Liu et al., 2023a; You et al., 2025) are described in Appendix D.

4 Our Method: SynRES

We propose SynRES, a fully automated synthetic dataset generation and augmentation pipeline for challenging RES, as shown in Fig. 3. As existing data generation approaches (Yang et al., 2023; Yu et al., 2024) do not produce densely paired image-mask-expression triplets, they could be suboptimal for developing models capable of discriminating between objects based on diverse attribute queries extracted from synthetic data. SynRES generates densely paired distinctive synthetic expressions and their corresponding images in Step 1. We obtain reliable pseudo semantic segmentation masks with image-text aligned grouping in Step 2. Our synthetic dataset is subsequently enhanced with data augmentation techniques to train models with improved generalization capabilities in Step 3.

4.1 Step 1: Synthetic Distinctive Referring Expressions and Image Generation

We first aim to generate distinctive synthetic expressions with diverse attributes. Motivated by (Yu et al., 2024), SynRES employs image captioning models to generate distinctive expressions $\{\mathbf{x}_{\text{txt},j}^{\text{syn}}\}_{j=1}^{n}$ for individual referring objects from real image $\mathbf{x}_{\text{img}}^{\text{real}}$ and it's corresponding mask $\mathbf{M}$.

For image synthesis, we construct composite prompts by aggregating the generated expres-

sions to ensure comprehensive feature representation. For example, by combining the expressions "*put the knot behind the ear*" and "*women's hair braided*", the aggregated description "*put the knot behind the ear, women's hair braided*" yields structured inputs with structured template selection per generation instance (see prompt templates in Appendix E). We leverage SANA (Xie et al., 2024a), a text-to-image model that efficiently generates high-fidelity synthetic images $\{\mathbf{x}_{\text{img},i}^{\text{syn}}\}_{i=1}^{m}$ with different m seeds while maintaining visual-semantic alignment.

4.2 Step 2: Reliable Synthetic Mask Generation with Image-Text Aligned Grouping

After the step 1, distinctive synthetic expression may or may not align with identical synthetic masks. This process establishes aligned groupings between synthetic images $\{\mathbf{x}_{\text{img},i}^{\text{syn}}\}_{i=1}^{m}$ and textual expressions $\{\mathbf{x}_{\text{txt},j}^{\text{syn}}\}_{j=1}^{n}$ through semantic-aware mask consensus. This validation process generates refined segmentation masks $\mathbf{M}_{(i,j)}^{\text{syn}}$ for each semantically aligned group as shown in Fig. 4.

First, we generate n pseudo segmentation masks $\hat{\mathbf{M}}_{(i,j)}^{\text{psd}}$ for each synthetic image $\mathbf{x}_{\text{img},i}^{\text{syn}}$ using a pretrained RES model (Lai et al., 2024), producing $m \times n$ candidate masks. An identification function $\mathbb{I}$ converts continuous mask values into binary masks through confidence thresholding:

$$\mathbf{M}_{(i,j)}^{\text{psd}} = \mathbb{I}\left(\hat{\mathbf{M}}_{(i,j)}^{\text{psd}}\right) = \begin{cases} 1 & \text{if } \hat{\mathbf{M}}_{(i,j)}^{\text{psd}} \geq 0.5 \\ 0 & \text{otherwise} \end{cases}.$$

This per-image mask generation ensures high-quality pseudo segmentation masks construction as each synthetic image mostly contains only one primary object (Ha et al., 2024) and at the same time, pretrained RES models are good at generate the masks of a single target.

Next, we compute pairwise Intersection-over-Union (IoU) scores between all binary mask pairs $\mathbf{M}_{(i,j_1)}^{\text{psd}}$ and $\mathbf{M}_{(i,j_2)}^{\text{psd}}$ derived from different textual expressions for the same image. The mean IoU (mIoU) across all images for each expression pair is:

$$\text{mIoU}(j_1, j_2) = \frac{1}{m} \sum_{i=1}^{m} \text{IoU}\left(\mathbf{M}_{(i,j_1)}^{\text{psd}}, \mathbf{M}_{(i,j_2)}^{\text{psd}}\right).$$

Expression pairs achieving mIoU scores exceeding threshold τ are clustered into consensus groups

Figure 3: Overview of the step 1 and 2 in SynRES. The process begins by creating distinctive n synthetic expressions for target objects from real images and masks. These expressions are then concatenated and input into a pre-trained text-to-image generative model to produce m synthetic images. Finally, a grouping step is performed to generate reliable synthetic masks by associating appropriate l segmentation masks with their corresponding expressions, yielding densely paired image-mask-expression triplets for objects with diverse attributes, thereby facilitating the learning of distinctive attribute combinations across objects.

Figure 4: Synthetic images and texts are aligned via pseudo mask generation, binary conversion, and pairwise IoU-based clustering into consensus groups (same-colored rectangles represent text-inferred pseudo masks from synthetic images). Final refined masks are computed by per-group averaging and thresholding, ensuring high-quality alignment.

G_k, while singleton expressions below this threshold are discarded. We then compute refined masks through per-group averaging:

$$\hat{\mathbf{M}}^{\text{syn}}_{(i,j)} = \frac{1}{|G_k|} \sum_{j \in G_k} \hat{\mathbf{M}}^{\text{psd}}_{(i,j)},$$

where G_k denotes the consensus group containing expression $\mathbf{x}^{\text{syn}}_{\text{txt}}$.

Finally, we apply the identification function to these refined masks: $\mathbf{M}^{\text{syn}}_{(i,j)} = \mathbb{I}(\hat{\mathbf{M}}^{\text{syn}}_{(i,j)})$, yielding binary masks where pixels with averaged values > 0.5 are assigned 1, and 0 otherwise. For ease of notation, $\mathbf{M}^{\text{syn}}_{(i,j)}$ is denoted $\mathbf{M}^{\text{syn}}_k$ where k ranges from 1 to l.

By proceeding these things, we generated synthetic triplets consisting of images, text expressions, and segmentation masks: $\{\mathbf{x}^{\text{syn}}_{\text{img},i}\}_{i=1}^m$, $\{\mathbf{x}^{\text{syn}}_{\text{txt},j}\}_{j=1}^n$, and $\{\mathbf{M}^{\text{syn}}_k\}_{k=1}^l$, respectively. These were derived from a single real image and its corresponding mask, denoted as $\mathbf{x}^{\text{real}}_{\text{img}}$ and $\mathbf{M}^{\text{real}}$ (see Appendix I.2 for before and after image-text aligned grouping).

4.3 Step 3: Domain-aware Augmentation for Images-Masks and Text

Step 3 addresses synthetic data limitations: isolated single-object images lack multi-target complexity, and models overfit to specific categories. Mosaic augmentation creates multi-target scenes while reducing synthetic-real domain gaps. Superclass replacement (e.g., woman→person, probability p) shifts focus from categories to attributes, enabling robust vocabulary generalization.

Multi-Target Aimed Image-Mask Augmentation. In RES in the wild, it is important for a model to distinguish the same objects with different attributes. We apply mosaic augmentation (Xie et al., 2024b; Ha et al., 2024) by constructing composite arrangements with synthetic images and masks to facilitate multi-object/target segmentation as shown in Fig. 5. In this process, each mosaic randomly adopts either a 2×2 grid (1 real image $\mathbf{x}^{\text{real}}_{\text{img}}$ + 3 synthetic $\mathbf{x}^{\text{syn}}_{\text{img},i}$) or 3×3 grid (1 real + 8 synthetic), with corresponding masks $\mathbf{M}^{\text{real}}$ and $\mathbf{M}^{\text{syn}}_i$. This approach facilitates the accommodation of multiple target objects within a single augmented scene. Simultaneously, integrating real and synthetic images creates composite visuals that effectively mitigate the domain gap between real-world and synthetically generated images.

Debiased Text Augmentation. We observe that training data commonly demonstrates a signifi-

Figure 5: Augmented examples in the step 3. Mosaic augmentation is applied using synthetic images and masks containing one original real image (blue border) and masks. Specific words (*e.g*, woman) are replaced with their superclass (*e.g*, person), a broader concept, with a probability of p, which could effectively mitigate model bias toward specific terminology and facilitate the learning of broader vocabulary associations. This substitution process may potentially produce false negative masks (magenta arrows) when other objects belonging to the same superclass exist within the image. Although this frequently exists in human expressions (*e.g*, RefCOCO+), we manually mitigate this challenge by generating isolated single objects within our synthetic data.

cant bias toward specific object class terminology. This systematic bias results in segmentation failures when processing input queries containing alternative synonymous expressions. We apply the text augmentation that probabilistically replaces head and sub-nouns with their corresponding superclasses. For instance, the phrase "*woman with hair tied up in a bun*" is transformed into "*person with hair tied up in a bun*" with probability p, thereby shifting the emphasis toward the action and mitigating gender bias (see Appendix F, H.4). This approach is especially useful for our synthetic data, as implementing such augmentation with conventional RES datasets (e.g., RefCOCO) would present significant challenges: these collections typically contain multiple objects and provide only minimal discriminative cues necessary for precise target identification. Consequently, modifying expressions with superclass terminology could inadvertently introduce non-distinctive queries, potentially resulting in imprecise segmentation masks through the inclusion of non-target objects (False negative masks in Fig. 5). In contrast, our method circumvents this issue because our synthetic expressions are richly descriptive (averaging 11.4 words). They contain redundant attributes that preserve sufficient discriminative cues even after superclass replacement.

5 Experiments

5.1 Experimental Setups

RES Models. To demonstrate the effectiveness of our approach, we applied our method to large multimodal models such as LISA-7B/13B (Lai et al., 2024), GSVA-7B (Xia et al., 2024), and GLaMM-8B (Rasheed et al., 2024). These implementations

were selected because they provide fully open-sourced training code, datasets, and pre-trained weights. For other architectural components requiring hyperparameters (*e.g*, projection layer dimensions), we adhered to the configurations specified in the original papers. Additional experiments on the lightweight RES model ReLA (Liu et al., 2023a) are provided in Appendix G.1.

Implementation Details. We utilized 4 NVIDIA A6000 48G GPUs for training. All results are reported from a single run. Other settings, including the optimizer and learning rate scheduler, were consistent with those of the network architecture. Specifically, we generated $m = 6$ synthetic images per referring target and up to $n = 5$ synthetic expressions based on RefCOCO+. This resulted in a total of 129,552 synthetic images, 78,263 expressions, and 151,116 masks. The default mIoU threshold τ in SynRES step 2 was set to 0.65, and the replacement probability p for expression data augmentation was set to 0.7.

Evaluation Metrics. We employed two evaluation metrics: gIoU and cIoU. The gIoU metric represents the average IoU values calculated per image, whereas cIoU is computed as the cumulative intersection over the cumulative union. Given cIoU's high sensitivity to large-area objects and higher-resolution images, gIoU was primarily used for evaluation (Lai et al., 2024).

5.2 WildRES: RES in the Wild

Settings. For LISA, GSVA, and GLaMM, we fine-tune the officially released pretrained weights augmented with SynRES. LISA and GSVA use datasets originally designed for semantic segmentation (Zhou et al., 2017; Caesar et al., 2018; Ramanathan et al., 2023; Chen et al., 2014; He et al.,

Model	Training data		val		test					
			overall		many attribute		shared attribute		overall	
	real	synthetic	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU
LMM based RES Models										
LISA-7B	✓	✗	37.1	40.3	**30.1**	25.0	39.3	36.0	34.5	32.5
	✓	✓ FreeMask (Yang et al., 2023)	38.8	42.0	25.8	25.3	37.1	36.4	31.6	33.3
	✓	✓ SynRES (Ours)	**41.3**	**46.1**	29.4	**26.3**	**43.6**	**43.3**	**36.5**	**38.1**
LISA-13B	✓	✗	44.0	45.1	35.9	31.6	36.9	37.8	37.7	36.0
	✓	✓ SynRES (Ours)	**47.7**	**51.8**	**36.5**	**33.4**	**44.7**	**43.9**	**40.5**	**40.8**
GSVA-7B	✓	✗	38.8	42.8	**32.6**	26.1	37.7	34.8	34.8	32.0
	✓	✓ SynRES (Ours)	**41.3**	**46.5**	32.4	**26.3**	**43.6**	**41.5**	**38.0**	**36.9**
GLaMM-8B	✓	✗	38.6	41.4	34.8	29.7	38.3	36.8	36.0	34.4
	✓	✓ SynRES (Ours)	**42.0**	**44.6**	**38.0**	**31.1**	**38.9**	**38.9**	**39.6**	**37.5**

Table 1: WildRES-ID segmentation results among SynRES (ours) and baselines.

Model	Training data		Domain source						average	
			CrowdHuman		Cityscapes		ARMBench			
	real	synthetic	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU
LMM based RES Models										
LISA-7B	✓	✗	**25.6**	26.3	37.1	39.4	26.9	26.0	29.9	30.6
	✓	✓ FreeMask (Yang et al., 2023)	23.5	26.0	34.4	36.9	24.5	26.1	27.5	29.7
	✓	✓ SynRES (Ours)	24.8	**27.3**	**40.5**	**43.2**	**35.8**	**33.3**	**33.7**	**34.6**
LISA-13B	✓	✗	26.6	29.4	34.1	34.8	28.3	26.9	29.7	30.4
	✓	✓ SynRES (Ours)	**28.8**	**30.0**	**39.9**	**43.6**	**39.1**	**37.7**	**35.9**	**37.1**
GSVA-7B	✓	✗	19.8	24.6	35.9	36.5	25.1	23.6	26.9	28.2
	✓	✓ SynRES (Ours)	**21.4**	**25.5**	**41.2**	**44.7**	**33.6**	**32.6**	**32.1**	**34.2**
GLaMM-8B	✓	✗	35.0	32.2	20.0	24.4	32.4	29.3	29.1	28.6
	✓	✓ SynRES (Ours)	**35.5**	**34.3**	**28.7**	**30.5**	**36.4**	**33.8**	**33.5**	**32.9**

Table 2: WildRES-DS segmentation results among SynRES (ours) and baselines.

2022), RefCOCO(+/g) (Yu et al., 2016; Rohrbach et al., 2016; Mao et al., 2016), VQA (Liu et al., 2024b,a), and ReasonSeg (for LISA). For GSVA, we additionally incorporate gRefCOCO (Liu et al., 2023a) during fine-tuning. We set a 9:3:3:1:4 data ratio across semantic segmentation, classic RES, VQA, ReasonSeg, and SynRES. For GLaMM, following the original setting, we fine-tune on Ref-COCO(+/g) and SynRES with a 3:4 ratio.

All experiments use official pretrained weights for each RES model, training for 5,000 steps with WildRES-ID validation every 100 steps regardless of synthetic data inclusion. Notably, the WildRES-DS remains *unused* during validation.

Results. Tab. 1 shows that real data with SynRES yields consistent, architecture-agnostic gains on the WildRES-ID validation split, mirrored on the held-out test set (including multi-target and attribute-sharing regimes). With validation used for selection and the test set reserved for final reporting, the improvements reflect genuine generalization rather than split-specific tuning.

Tab. 2 evaluates cross-domain robustness on WildRES-DS with CrowdHuman, Cityscapes (autonomous driving), and ARMBench (robotics), where SynRES-added models outperform real-only baselines across all architectures. Gains are especially pronounced on ARMBench and raise the overall averages, indicating resilience to distribution shifts without reliance on a single source domain.

Results show that simply adding more synthetic data does not solve RES. FreeMask, though beneficial for semantic segmentation with real data, lowered performance across domains on WildRES-DS. In contrast, SynRES consistently improved results, showing that RES requires careful handling of synthetic images, text, and masks—an approach realized by SynRES.

We compared the output masks of the LISA fine-tuned with SynRES and the LISA without SynRES on the WildRES dataset, as shown in Fig. 6. The visualization shows that fine-tuning the model with SynRES reduces false negatives by capturing ground truth objects in multi-target scenarios involving shared attributes. Additionally, it prevents false positives by accurately understanding the meaning of each words in cases with many attribute expressions.

5.3 Additional Analysis

WildRES vs. Existing RES Benchmarks. Under identical protocols, WildRES presents sub-

Figure 6: Qualitative results on WildRES, comparing LISA trained w/o and w/ SynRES.

Model w/ LISA-7B	Modifications			wildres-ID val	
	Step 2	Mosaic Aug.	Text Aug.	gIoU	cIoU
SynRES	✓	✓	✓	41.3	46.1
	✓	✓	✗	40.1	44.0
	✗	✓	✓	39.1	41.9
	✓	✗	✗	35.5	38.3
Only Real	✗	✗	✗	37.1	40.3

Table 3: Ablation study on the core designs of SynRES. ✓ means the employment of the component while ✗ means not.

stantially greater challenges than canonical RES benchmarks. Models achieve only 20–50 gIoU on WildRES, a stark contrast to the 60–80 gIoU on single-target RefCOCO/+/g and 70–80 gIoU on multi-target gRefCOCO and RefZOM. This performance gap persists even when applying SynRES, which indicates that WildRES demands more advanced capabilities—specifically, fine-grained disambiguation in multi-target scenes and robust attribute grounding—that are not fully captured by prior benchmarks. For detailed results across different architectures and datasets, see Appendix G.

Ablation Study Tab. 3 presents an ablation study evaluating each component in SynRES. The results show a gradual decline in performance, with the gIoU decreasing from 41.3 to 40.8 and 35.5 when text augmentation and mosaic augmentation were excluded, respectively. Notably, when both vision and text augmentations were omitted, the performance fell below the baseline value of 37.1, which was obtained without training on the synthetic dataset. This performance degradation can be attributed to two primary factors: first, the absence of vision augmentation restricts the model to the Wild RES task, which lacks multiple targets,

leading to poor outcomes in the Shared Attribute portion; second, a domain gap between synthetic and real images further degrades performance.

Moreover, the performance improvement with text augmentation confirms superclass replacement's effectiveness for contextual expression understanding in complex scenes by focusing on the description of the target. These findings underscore the importance of both text and vision augmentation in enhancing the effectiveness of the SynRES pipeline for complex visual grounding tasks. Additionally, adopting only domain-aware augmentation without mask refinement in SynRES step 2 shows limited performance, proving the necessity of refining raw pseudo masks.

6 Conclusion

In this study, we introduce a new RES task aimed at addressing more complex reasoning in the real-world, dynamic scenarios, WildRES. Specifically, we focus on cases where expressions refer to multiple targets with shared attributes settings or require an increased number of attributes to identify a single target within such environments. To benchmark this task, we not only developed WildRES-ID within the same domain as existing RES datasets but also extended its applicability to autonomous driving and robotics domains through the WildRES-DS. Additionally, we propose a method to enhance the performance of existing models in WildRES by leveraging densely paired synthetic image-expression-mask triplet generation and augmentation, SynRES. We hope that our work broadens the scope of language-based segmentation.

Limitation

There are characteristic failure cases involving over-segmentation beyond ground truth boundaries (see Fig. D). These errors typically occur when visually similar objects appear immediately adjacent to the target. Our current mosaic augmentation struggles with such proximate object arrangements, as it limits composite images to 9 components and thereby restricts training exposure to higher object densities. Implementing a targeted copy-and-paste augmentation (Fan et al., 2024) that preserves the original attributes could mitigate these limitations in future work.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C Lawrence Zitnick, and Devi Parikh. 2015. Vqa: Visual question answering. In *ICCV*, pages 2425–2433.

Holger Caesar, Jasper Uijlings, and Vittorio Ferrari. 2018. Coco-stuff: Thing and stuff classes in context. In *CVPR*, pages 1209–1218.

Xianjie Chen, Roozbeh Mottaghi, Xiaobai Liu, Sanja Fidler, Raquel Urtasun, and Alan Yuille. 2014. Detect what you can: Detecting and representing objects using holistic models and body parts. In *CVPR*, pages 1971–1978.

Yi-Chia Chen, Wei-Hua Li, Cheng Sun, Yu-Chiang Frank Wang, and Chu-Song Chen. 2024. Sam4mllm: Enhance multi-modal large language model for referring expression segmentation. In *ECCV*, pages 323–340. Springer.

Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. 2016. The cityscapes dataset for semantic urban scene understanding. In *CVPR*.

Ming Dai, Wenxuan Cheng, Jiang-Jiang Liu, Lingfeng Yang, Zhenhua Feng, Wankou Yang, and Jingdong Wang. 2025. Improving generalized visual grounding with instance-aware joint learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.

Chengxiang Fan, Muzhi Zhu, Hao Chen, Yang Liu, Weijia Wu, Huaqi Zhang, and Chunhua Shen. 2024. Divergen: Improving instance segmentation by learning wider data distribution with more diverse generative data. In *CVPR*, pages 3986–3995.

Seongsu Ha, Chaeyun Kim, Donghwa Kim, Junho Lee, Sangho Lee, and Joonseok Lee. 2024. Finding nemo: Negative-mined mosaic augmentation for referring image segmentation. In *ECCV*, pages 121–137. Springer.

Xiaoshuai Hao, Yi Zhu, Srikar Appalaraju, Aston Zhang, Wanqian Zhang, Bo Li, and Mu Li. 2023. Mixgen: A new multi-modal data augmentation. In *WACV*, pages 379–389.

Ju He, Shuo Yang, Shaokang Yang, Adam Kortylewski, Xiaoding Yuan, Jie-Neng Chen, Shuai Liu, Cheng Yang, Qihang Yu, and Alan Yuille. 2022. Partimagenet: A large, high-quality dataset of parts. In *ECCV*, pages 128–145. Springer.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. 2020. Denoising diffusion probabilistic models. *NeurIPS*, 33:6840–6851.

Yutao Hu, Qixiong Wang, Wenqi Shao, Enze Xie, Zhenguo Li, Jungong Han, and Ping Luo. 2023. Beyond one-to-one: Rethinking the referring image segmentation. In *ICCV*, pages 4067–4077.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Xiaomeng Jin, Jeonghwan Kim, Yu Zhou, Kuan-Hao Huang, Te-Lin Wu, Nanyun Peng, and Heng Ji. 2024. Armada: Attribute-based multimodal data augmentation. *arXiv preprint arXiv:2408.10086*.

Sahar Kazemzadeh, Vicente Ordonez, Mark Matten, and Tamara Berg. 2014. Referitgame: Referring to objects in photographs of natural scenes. In *EMNLP*, pages 787–798.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, and 1 others. 2023. Segment anything. In *ICCV*, pages 4015–4026.

Xin Lai, Zhuotao Tian, Yukang Chen, Yanwei Li, Yuhui Yuan, Shu Liu, and Jiaya Jia. 2024. Lisa: Reasoning segmentation via large language model. In *CVPR*, pages 9579–9589.

Daiqing Li, Huan Ling, Seung Wook Kim, Karsten Kreis, Sanja Fidler, and Antonio Torralba. 2022. Big-datasetgan: Synthesizing imagenet with pixel-wise annotations. In *CVPR*, pages 21330–21340.

Chang Liu, Henghui Ding, and Xudong Jiang. 2023a. Gres: Generalized referring expression segmentation. In *CVPR*, pages 23592–23601.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2024a. Improved baselines with visual instruction tuning. In *CVPR*, pages 26296–26306.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2024b. Visual instruction tuning. *NeurIPS*, 36.

Yuqi Liu, Bohao Peng, Zhisheng Zhong, Zihao Yue, Fanbin Lu, Bei Yu, and Jiaya Jia. 2025. Seg-zero: Reasoning-chain guided segmentation via cognitive reinforcement. *arXiv preprint arXiv:2503.06520*.

Yuqi Liu, Tianyuan Qu, Zhisheng Zhong, Bohao PENG, Shu Liu, Bei Yu, and Jiaya Jia. 2026. Visionreasoner: Unified reasoning-integrated visual perception via reinforcement learning. In *The Fourteenth International Conference on Learning Representations*.

Zichang Liu, Zhiqiang Tang, Xingjian Shi, Aston Zhang, Mu Li, Anshumali Shrivastava, and Andrew Gordon Wilson. 2023b. Learning multimodal data augmentation in feature space. In *ICLR*.

Junhua Mao, Jonathan Huang, Alexander Toshev, Oana Camburu, Alan L Yuille, and Kevin Murphy. 2016. Generation and comprehension of unambiguous object descriptions. In *CVPR*, pages 11–20.

Chaitanya Mitash, Fan Wang, Shiyang Lu, Vikedo Terhuja, Tyler Garaas, Felipe Polido, and Manikantan Nambi. 2023. Armbench: An object-centric benchmark dataset for robotic manipulation. In *ICRA*, pages 9132–9139. IEEE.

Gerhard Neuhold, Tobias Ollmann, Samuel Rota Bulo, and Peter Kontschieder. 2017. The mapillary vistas dataset for semantic understanding of street scenes. In *ICCV*, pages 4990–4999.

Quang Nguyen, Truong Vu, Anh Tran, and Khoi Nguyen. 2023. Dataset diffusion: Diffusion-based synthetic data generation for pixel-level semantic segmentation. *NeurIPS*.

Vignesh Ramanathan, Anmol Kalia, Vladan Petrovic, Yi Wen, Baixue Zheng, Baishan Guo, Rui Wang, Aaron Marquez, Rama Kovvuri, Abhishek Kadian, and 1 others. 2023. Paco: Parts and attributes of common objects. In *CVPR*, pages 7141–7151.

Hanoona Rasheed, Muhammad Maaz, Sahal Shaji, Abdelrahman Shaker, Salman Khan, Hisham Cholakkal, Rao M Anwer, Eric Xing, Ming-Hsuan Yang, and Fahad S Khan. 2024. Glamm: Pixel grounding large multimodal model. In *CVPR*, pages 13009–13018.

Nikhila Ravi, Valentin Gabeur, Yuan-Ting Hu, Ronghang Hu, Chaitanya Ryali, Tengyu Ma, Haitham Khedr, Roman Rädle, Chloe Rolland, Laura Gustafson, Eric Mintun, Junting Pan, Kalyan Vasudev Alwala, Nicolas Carion, Chao-Yuan Wu, Ross Girshick, Piotr Dollar, and Christoph Feichtenhofer. 2025. SAM 2: Segment anything in images and videos. In *ICLR*.

Zhongwei Ren, Zhicheng Huang, Yunchao Wei, Yao Zhao, Dongmei Fu, Jiashi Feng, and Xiaojie Jin. 2024. Pixellm: Pixel reasoning with large multimodal model. In *CVPR*, pages 26374–26383.

Anna Rohrbach, Marcus Rohrbach, Ronghang Hu, Trevor Darrell, and Bernt Schiele. 2016. Grounding of textual phrases in images by reconstruction. In *ECCV*, pages 817–834. Springer.

Shuai Shao, Zijian Zhao, Boxun Li, Tete Xiao, Gang Yu, Xiangyu Zhang, and Jian Sun. 2018. Crowdhuman: A benchmark for detecting human in a crowd. *arXiv preprint arXiv:1805.00123*.

Jiaming Song, Chenlin Meng, and Stefano Ermon. 2021. Denoising diffusion implicit models. In *ICLR*.

Yuanpeng Tu, Xi Chen, Ser-Nam Lim, and Hengshuang Zhao. 2025. Dreammask: Boosting open-vocabulary panoptic segmentation with synthetic data. *arXiv preprint arXiv:2501.02048*.

Zhaoqing Wang, Yu Lu, Qiang Li, Xunqiang Tao, Yandong Guo, Mingming Gong, and Tongliang Liu. 2022. Cris: Clip-driven referring image segmentation. In *CVPR*, pages 11686–11695.

Jiannan Wu, Muyan Zhong, Sen Xing, Zeqiang Lai, Zhaoyang Liu, Zhe Chen, Wenhai Wang, Xizhou Zhu, Lewei Lu, Tong Lu, and 1 others. 2024. Visionllm v2: An end-to-end generalist multimodal large language model for hundreds of vision-language tasks. *NeurIPS*, 37:69925–69975.

Qiyu Wu, Mengjie Zhao, Yutong He, Lang Huang, Junya Ono, Hiromi Wakaki, and Yuki Mitsufuji. 2023a. Towards reporting bias in visual-language datasets: bimodal augmentation by decoupling object-attribute association. *arXiv preprint arXiv:2310.01330*.

Size Wu, Sheng Jin, Wenwei Zhang, Lumin Xu, Wentao Liu, Wei Li, and Chen Change Loy. 2025. F-lmm: Grounding frozen large multimodal models. In *CVPR*, pages 24710–24721.

Weijia Wu, Yuzhong Zhao, Mike Zheng Shou, Hong Zhou, and Chunhua Shen. 2023b. Diffumask: Synthesizing images with pixel-level annotations for semantic segmentation using diffusion models. In *ICCV*, pages 1206–1217.

Zhuofan Xia, Dongchen Han, Yizeng Han, Xuran Pan, Shiji Song, and Gao Huang. 2024. Gsva: Generalized segmentation via multimodal large language models. In *CVPR*, pages 3858–3869.

Enze Xie, Junsong Chen, Junyu Chen, Han Cai, Haotian Tang, Yujun Lin, Zhekai Zhang, Muyang Li, Ligeng Zhu, Yao Lu, and 1 others. 2024a. Sana: Efficient high-resolution image synthesis with linear diffusion transformers. *arXiv preprint arXiv:2410.10629*.

Jiahao Xie, Wei Li, Xiangtai Li, Ziwei Liu, Yew Soon Ong, and Chen Change Loy. 2024b. Mosaicfusion: Diffusion models as data augmenters for large vocabulary instance segmentation. *IJCV*, pages 1–20.

Zunnan Xu, Zhihong Chen, Yong Zhang, Yibing Song, Xiang Wan, and Guanbin Li. 2023. Bridging vision and language encoders: Parameter-efficient tuning for referring image segmentation. In *ICCV*, pages 17503–17512.

Jingkang Yang, Yi Zhe Ang, Zujin Guo, Kaiyang Zhou, Wayne Zhang, and Ziwei Liu. 2022a. Panoptic scene graph generation. In *ECCV*, pages 178–196. Springer.

Lihe Yang, Xiaogang Xu, Bingyi Kang, Yinghuan Shi, and Hengshuang Zhao. 2023. Freemask: Synthetic images with dense annotations make stronger segmentation models. *NeurIPS*.

Zhao Yang, Jiaqi Wang, Yansong Tang, Kai Chen, Hengshuang Zhao, and Philip HS Torr. 2022b. Lavt: Language-aware vision transformer for referring image segmentation. In *CVPR*, pages 18155–18165.

Hanrong Ye, Jason Kuen, Qing Liu, Zhe Lin, Brian Price, and Dan Xu. 2024. Seggen: Supercharging segmentation models with text2mask and mask2img synthesis. In *ECCV*, pages 352–370. Springer.

Zuyao You, Junke Wang, Lingyu Kong, Bo He, and Zuxuan Wu. 2025. Pix2cap-coco: Advancing visual comprehension via pixel-level captioning. *arXiv preprint arXiv:2501.13893*.

Peter Young, Alice Lai, Micah Hodosh, and Julia Hockenmaier. 2014. From image descriptions to visual denotations: New similarity metrics for semantic inference over event descriptions. *Transactions of the Association for Computational Linguistics*, 2:67–78.

Licheng Yu, Patrick Poirson, Shan Yang, Alexander C Berg, and Tamara L Berg. 2016. Modeling context in referring expressions. In *ECCV*, pages 69–85. Springer.

Seonghoon Yu, Paul Hongsuck Seo, and Jeany Son. 2024. Pseudo-ris: Distinctive pseudo-supervision generation for referring image segmentation. In *ECCV*, pages 18–36. Springer.

Zhihan Yu and Ruifan Li. 2024. Revisiting counterfactual problems in referring expression comprehension. In *CVPR*, pages 13438–13448.

Yuxuan Zhang, Tianheng Cheng, Rui Hu, Lei Liu, Heng Liu, Longjin Ran, Xiaoxin Chen, Wenyu Liu, and Xinggang Wang. 2024a. Evf-sam: Early vision-language fusion for text-prompted segment anything model. *arXiv preprint arXiv:2406.20076*.

Yuxuan Zhang, Huan Ling, Jun Gao, Kangxue Yin, Jean-Francois Lafleche, Adela Barriuso, Antonio Torralba, and Sanja Fidler. 2021. Datasetgan: Efficient labeled data factory with minimal human effort. In *CVPR*, pages 10145–10155.

Zheng Zhang, Yeyao Ma, Enming Zhang, and Xiang Bai. 2024b. Psalm: Pixelwise segmentation with large multi-modal model. In *ECCV*, pages 74–91. Springer.

Hanqing Zhao, Dianmo Sheng, Jianmin Bao, Dongdong Chen, Dong Chen, Fang Wen, Lu Yuan, Ce Liu, Wenbo Zhou, Qi Chu, and 1 others. 2023a. X-paste: Revisiting scalable copy-paste for instance segmentation using clip and stablediffusion. In *ICML*, pages 42098–42109. PMLR.

Wenliang Zhao, Yongming Rao, Zuyan Liu, Benlin Liu, Jie Zhou, and Jiwen Lu. 2023b. Unleashing text-to-image diffusion models for visual perception. In *ICCV*, pages 5729–5739.

Bolei Zhou, Hang Zhao, Xavier Puig, Sanja Fidler, Adela Barriuso, and Antonio Torralba. 2017. Scene parsing through ade20k dataset. In *CVPR*.

Lianghui Zhu, Bin Ouyang, Yuxuan Zhang, Tianheng Cheng, Rui Hu, Haocheng Shen, Longjin Ran, Xiaoxin Chen, Li Yu, Wenyu Liu, and 1 others. 2026. Lens: Learning to segment anything with unified reinforced reasoning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 13952–13960.

Xueyan Zou, Jianwei Yang, Hao Zhang, Feng Li, Linjie Li, Jianfeng Wang, Lijuan Wang, Jianfeng Gao, and Yong Jae Lee. 2023. Segment everything everywhere all at once. *NeurIPS*, 36:19769–19782.

A Extended Related Works

Referring Expression Segmentation with Large Multimodal Models. The introduction of LISA (Lai et al., 2024), which leveraged the visual-language capabilities of Large Multimodal Models (LMMs) for the Referring Expression Segmentation (RES) task using <SEG> tokens, has significantly influenced the development of advanced LMM-based RES models (Xia et al., 2024; Ren et al., 2024; Rasheed et al., 2024; Zhang et al., 2024b; Chen et al., 2024; Zhang et al., 2024a; Wu et al., 2024, 2025). Notably, GSVA (Xia et al., 2024) and PixelLM (Ren et al., 2024) have improved multi-target segmentation accuracy by employing strategies such as multiple <SEG> tokens or introducing target refinement loss. To train these models effectively, large-scale datasets from diverse domains are utilized. Examples include semantic segmentation datasets (Caesar et al., 2018; Zhou et al., 2017; Neuhold et al., 2017; Chen et al., 2014; He et al., 2022), classic RES datasets (Yu et al., 2016; Mao et al., 2016), and Visual Question Answering datasets (Liu et al., 2024b; Antol et al., 2015; Liu et al., 2024a). These datasets are adapted for RES tasks using prompt-based transformations or integrated into training pipelines. Such adaptations enhance vocabulary comprehension and reasoning capabilities. Some models employ specialized datasets tailored for generalized RES tasks. For instance, GSVA (Xia et al., 2024) and SAM4LMM (Chen et al., 2024) incorporate gRef-COCO (Liu et al., 2023a) into their training data. Other notable datasets include ReasonSeg (Lai et al., 2024) and GranD (Rasheed et al., 2024), which are derived from automatically annotated SA-1B (Kirillov et al., 2023) or GranD-f (based on Flickr-30K (Young et al., 2014), RefCOCOg (Mao et al., 2016), and PSG (Yang et al., 2022a)). More recent studies further extend RES-related segmentation toward generalized grounding and explicit reasoning. InstanceVG (Dai et al., 2025) jointly addresses generalized referring expression comprehension and segmentation with instance queries, encouraging consistent predictions across points, boxes, and masks. Seg-Zero (Liu et al., 2025) decouples reasoning and segmentation by generating reasoning chains and positional prompts through reinforcement learning, while LENS (Zhu et al., 2026) jointly optimizes chain-of-thought reasoning and mask quality using sentence-, box-, and segment-level rewards. VisionReasoner (Liu et al., 2026) further unifies detection, segmentation, and counting within a shared reasoning-integrated visual perception framework. Existing models exhibit performance degradation when evaluated on our more challenging benchmark, WildRES. Our model-agnostic approach, SynRES, significantly enhances the complex reasoning capabilities of these models.

Synthetic Data and Augmentation for Referring Expression Segmentation. Early efforts on synthetic datasets for segmentation leveraged GANs (Zhang et al., 2021; Li et al., 2022). With the advent of diffusion models (Ho et al., 2020; Song et al., 2021), recent methods generate class-targeted images paired with pseudo-segmentation masks (Nguyen et al., 2023; Yang et al., 2023), and also synthesize masks with corresponding high-fidelity images (Ye et al., 2024), extending to instance and panoptic settings (Zhao et al., 2023a; Fan et al., 2024; Xie et al., 2024b; Tu et al., 2025). However, these approaches predominantly yield image-mask pairs and do not explicitly align textual descriptions with mask semantics. In parallel, multimodal data augmentation has advanced joint image-text learning (Hao et al., 2023; Liu et al., 2023b; Jin et al., 2024; Wu et al., 2023a), while RES-specific augmentation remains comparatively underexplored. NeMo (Ha et al., 2024) forms mosaics from semantically related but non-redundant images, and Pseudo-RIS (Yu et al., 2024) leverages pseudo masks and diverse captions to enable weakly supervised training. Yet these techniques only partially capture the interplay among image content, referring expressions, and segmentation masks, which is critical for RES. We address this gap by generating densely aligned image-mask-text triplets, covering the same objects with diverse attributes and reliable pseudo-masks, and by introducing augmentation strategies that jointly operate on all three modalities to reduce domain discrepancies, enforce semantic consistency across transformations, and improve generalization in RES.

B Details of WildRES

Tab. A provides a detailed number of the WildRES dataset, which consists of the Wildseg-ID and Wildseg-DS subsets. The dataset is categorized based on domain, data split (validation/test), and attribute type (Many Attribute or Shared Attribute). In total, WildRES comprises 724 images and 974 expressions across different domains and attribute

types.

Type	Domain	Split	Attribute	Image	Expression
Wildseg-ID	MSCOCO	Validation	Many Attribute	100	138
			Shared Attribute	104	127
			Total	196	265
		Test	Many Attribute	108	133
			Shared Attribute	115	124
			Total	215	257
Wildseg-DS	CrowdHuman	Test	Many Attribute	101	212
	Cityscapes		Shared Attribute	105	120
	Armbench		Shared Attribute	107	120
Total				724	974

Table A: Detailed Numbers of WildRES

C Count Referring Expression Attributes

Based on (Yu and Li, 2024), we refine eight expression attributes identified in existing datasets: *head noun*, *sub noun*, *color*, *size*, *absolute location relation*, *relative location relation*, *action*, and *generic attribute*. A detailed example is shown in Tab. B. Using these attributes, we conduct quantitative analyses comparing the attribute distribution patterns between classic datasets and WildRES. This counting process is automated using ChatGPT-4o-mini (Achiam et al., 2023). Tab. C shows the prompt template used for the counting process.

ID	Attribute	Word
A1	head noun	*cat*
A2	sub noun	*bench, boat*
A3	color	*green*
A4	size	*big*
A5	absolute location relation	*the center*
A6	relative location relation	*on, next to, in*
A7	action	*sitting*
A8	generic attribute	*wooden*

Table B: Types of attributes and their corresponding words in the referring expression, "*the cat sitting on the bench next to big green wooden boat in the center of the image*"

D Differences with WildRES and Previous datasets

D.1 Differences from Previous Multi-Target RES Datasets

Existing multi-target RES datasets like gRef-COCO (Liu et al., 2023a) and Ref-ZOM (Hu et al., 2023) predominantly rely on enumeration, conjunctions, and plural head nouns. These datasets frequently employ numerical references ("Three persons playing baseball") that assume known referent quantities—an assumption often disconnected from

(a) Non-distinctive Expression   **(b) Attribute Misalignment**

A man in a white naval uniform stands near the cake. His posture is confident, and he wears several medals on his chest. His face reflects a sense of pride and joy as he actively participates in the cake-cutting ceremony. His uniform is crisp, and he holds a ceremonial knife.

*skier dressed in black ski attire stands in the foreground. **The skier wears a red ski jacket**, black ski pants, and red goggles. They hold onto ski poles with gloved hands. The skier's posture suggests readiness for skiing.*

Figure A: Pix2Cap misaligned examples

real-world scenarios where shared attributes drive identification.

While gRefCOCO incorporates attribute-based expressions ("A except B" or "A that has B"), these constructions appear infrequently—only 39 and 78 instances in 259,859 expressions—confirming enumeration dominates. Similarly, Ref-ZOM employs template-based generation that combines expressions from one-to-one datasets or embeds category information into predefined structures, sacrificing natural language flexibility for consistency.

WildRES adopts a fundamentally different approach by eliminating explicit numerical references and plural head nouns. Our dataset relies exclusively on shared attributes with singular head nouns to indicate multiple objects, creating more context-driven references. We focus on identifying subsets within categories based on distinctive attributes rather than comprehensive enumeration. For example, "person holding a camera" may coexist with "person not holding a camera" instances, enabling precise differentiation without explicitly counting targets. This design better reflects natural language patterns where speakers rarely enumerate objects explicitly. Unlike gRefCOCO, WildRES excludes no-target expressions entirely.

D.2 Difference from Pix2Cap

Pix2Cap (You et al., 2025) provides longer and more detailed captions from GPT-4V (Hurst et al., 2024) compared to traditional datasets. However, many captions fail to correspond to their respective objects accurately.

As illustrated in Fig. A, misalignment issues in the Pix2Cap dataset can be categorized into non-distinctive expressions and attribute mismatches.

Non-distinctive expressions due to multiple objects (Fig. A (a)) occur when a referring expression corresponds to multiple objects, making the expression non-distinctive. The red-edged mask represents the Pix2Cap annotation, but additional objects matching the same description (highlighted in orange) result in incomplete coverage. Attribute misalignment (Fig. A (b)) arises when certain attributes within a referring expression do not accurately match the corresponding mask. The red mask represents the Pix2Cap annotation for the given expression, but the skier is not wearing a red ski jacket, leading to attribute misalignment.

To address these issues, we refined Pix2Cap-generated expressions or created new ones for images containing three or more objects, constructing an improved dataset with enhanced caption-to-object alignment while preserving Pix2Cap's rich linguistic diversity.

E   Structured Prompts for T2I Model

We randomly select one of two prompt structures as input for the T2I model in Sec. 4.1:

> - *photo of [aggregated description], hyper-realistic, 4k, realism, highly detailed, natural realistic background*
>
> - *cinematic scene [aggregated description], hyper-realistic, 4k, realism, highly detailed, natural realistic background*

These prompts bridge the synthetic-real domain gap while avoiding stylistic elements like cartoon or pixel art

F   Superclass Replace Words

Tab. D lists superclass replacements for text augmentation. Based on MSCOCO (Caesar et al., 2018) classes and our superclass taxonomy, we select frequently occurring terms from SynRES's synthetic expressions. To maintain expression consistency, gender-specific replacements trigger corresponding pronoun updates. For example, replacing "*boy*" with "*child*" in "*The boy holding his bag*" simultaneously changes "*his*" to "*their*", resulting in "*The child holding their bag*".

G   Additional Experiments

G.1   ReLA

Experimental Settings. Regarding ReLA, since its standard protocol involves training on individual datasets rather than joint training across multiple sources, we focus on gRefCOCO, which features longer expressions and multiple targets compared to RefCOCO(+/g). We compare ReLA trained solely on gRefCOCO against a version trained on both gRefCOCO and SynRES, employing an 8:2 data ratio. The results are summarized in Tab. E.

G.2   Classic RES

Experimental Settings. We leveraged official LISA weights that incorporated the ReasonSeg validation set during training. Performance was evaluated on the ReasonSeg test set for epoch-wise model selection. For GSVA, where official weights exclude the ReasonSeg validation set, we perform model selection using ReasonSeg validation set. Other configurations remain consistent with the previous section.

Since the gRefCOCO was not included during LISA training, there was significant performance degradation on no-target expressions, which are part of gRefCOCO, when evaluated on this dataset. As our goal also included testing multi-target performance on gRefCOCO, no-target expressions were omitted during gRefCOCO evaluation with LISA. In contrast, GSVA utilized the entire gRefCOCO training set, ensuring that all data were equally considered during evaluation.

Results. In Tab. F, we observed that using SynRES mostly achieved the best performance across the not only single-target RefCOCO series but also multi-target and no-target included gRefCOCO. Also, incorporating FreeMask (Yang et al., 2023) led to a decline in performance. This outcome highlights that simply adding synthetic datasets does not guarantee improved performance in RES; instead, it underscores the importance of effectively handling such datasets to achieve positive results.

Performance Reproduction in LISA. We reproduced LISA using the official codebase and released weights. Nevertheless, our results were consistently lower than those reported in the paper (e.g., RefCOCO val 74.1), a discrepancy that has been repeatedly noted by other researchers. For example, the GSVA paper reports a RefCOCO val score of 71.7 for LISA-13B—lower than LISA-7B—with similar trends on RefCOCO+ and RefCOCOg. Likewise, Issue #162 on the official LISA GitHub reports RefCOCO val at 72.2 and notes even lower performance for the 7B model. To account for this variability, we conducted three independent runs for LISA and report the median in

our tables. In contrast, the results for the remaining models closely matched the numbers reported in their original papers.

G.3 Additional Benchmarks

We further conducted experiments on Ref-ZOM (Hu et al., 2023) (multi-target datasets, Tab. G left) and ReasonSeg (Lai et al., 2024) (long and implicit expressions, Tab. G right). Results demonstrate that SynRES maintains or improves baseline performance across diverse scenarios. On Ref-ZOM, GSVA-7B+SynRES preserves strong performance with slight gains of +0.97 gIoU (73.55 vs 72.58). For ReasonSeg, the approach shows consistent stability across model scales: LISA-13B achieves +0.40 gIoU improvement (48.02 vs 47.62), while GSVA-7B maintains competitive performance with +0.65 gIoU on validation and +0.53 gIoU on test data.

H Discussions

H.1 Hyperparameter Choices

Tab. H presents the results of experiments conducted by varying the replacement probability p, a hyperparameter of SynRES, from 0.4 to 0.9. Results demonstrate that the validation set of WildRES-ID consistently achieves gIoU scores above 40 across all configurations, indicating minimal performance sensitivity to p variations. Similarly, when testing the mIoU threshold τ within 0.55-0.75, the minimum observed gIoU remains above 39.6, showing comparable robustness to τ selection.

H.2 Performance Relative to Synthetic Data Quantity

We evaluate LISA's performance using progressively increasing quantities of synthetic training images (25%, 50%, 75%, and 100% of full dataset size). As shown in Tab. I, the gIoU metric demonstrates remarkable stability across data scales, with only 0.6 separating the 25% and 100% conditions. Notably, the 25% configuration achieves 98.5% of the maximum observed performance, suggesting efficient data utilization.

H.3 Computational Cost

The process of generating the synthetic dataset does not incur additional training costs, as it leverages off-the-shelf models. However, the generation process does require time: generating synthetic expressions took approximately 20 hours, creating synthetic images took around 23 hours, and performing step 2 grouping required about 30 hours, all using four A6000 GPUs. Once the synthetic dataset is generated, effective results can be achieved with only 5,000 steps of additional fine-tuning—just 1/10 of the training from scratch.

H.4 Gender Bias Mitigation

To evaluate bias mitigation, we conduct counterfactual consistency analysis on WildRES using the LISA-7B model. We select samples containing gender-specific terms (*man*, *woman*, *boy*, *girl*) and replace them with gender-neutral alternatives (*person*, *child*). As shown in Table J, our SynRES-trained model exhibits only 0.4-point variation ($33.1 \rightarrow 32.7$), while the baseline shows 1.1-point fluctuation ($31.4 \rightarrow 30.3$). This $3\times$ smaller gap demonstrates that our approach successfully reduces dependency on gender cues, relying more on visual attributes.

I More Visualization

I.1 Failure Cases

Fig. D illustrates qualitative failure cases where our model struggles to accurately segment the target.

I.2 Refined Synthetic Mask Example Before and After SynRES Step 2

Fig. B show mask refinement results, comparing synthetic segmentation outputs before and after SynRES in step 2.

I.3 Additional SynRES Examples

Fig. C presents SynRES examples demonstrating synthetic dataset generation. Superclass replacement augmentation applied to these generated expressions following Tab. F.

I.4 Extended Qualitative Results

We present additional visualization results in Fig. E to further demonstrate the effectiveness of the WildRES task with SynRES.

J LLMs Usage Clarification

We used LLMs exclusively for writing assistance and grammar polishing to improve the clarity and presentation of our methods and content. We did not use LLMs for other purposes, such as identifying related work or research ideation.

Real Image & Mask	Synthetic Expression	Synthetic Image	Pseudo Mask Before Grouping	Synthetic Mask After Grouping
	people buying tomatoes - this woman looks a bit sad			
	man with his daughter sitting on a bench			
	messy bun with loose waves			

Figure B: Examples of before and after of SynRES step 2.

Figure C: Examples of SynRES generated training data. Blue border is real image and mask. Zoom-in for closer look.

	Image	Expression		w/o SynRES	w/ SynRES	GT

baby holding a spoon

woman with a bob haircut, not wearing glasses or sunglasses, and wearing a navy hoodie with red lettering

woman at the edge of the photo wearing a patterned top, carrying a bag on her right shoulder, and wearing flip-flops

Figure D: Failure Cases

(a) Visualization of Many Attribute in WildRES-ID

(b) Visualization of Shared Attribute in WildRES-ID

Image	Expression		w/o SynRES	w/ SynRES	GT
	Asian man wearing a red top and bottom, making hand gestures, standing on the grass, wearing sunglasses				
	Small girl in the bottom right corner, tying her hair with a hairband decorated with an orange accessory				
	Man positioned in the bottom right corner, wearing a white shirt, sitting next to the man in a blue shirt.				

(c) Visualization of CrowdHuman in WildRES-DS

Image	Expression		w/o SynRES	w/ SynRES	GT
	Person crossing the road.				
	Person crossing the crosswalk.				
	Red vehicle				
	person with their hair tied back crossing the road				

(d) Visualization of Cityscapes in WildRES-DS

(e) Visualization of ARMBench in WildRES-DS

Figure E: More sampled example from WildRES dataset.

Here's an example analysis:
Example sentence: "Standing on the right side of the image, this individual wears a vibrant red jacket that contrasts sharply against the snowy backdrop. Their black pants provide a stark visual contrast. The person's black beanie covers their head, and they appear to be in a relaxed stance. Their body language suggests a sense of confidence and readiness for outdoor activities."
Example classification:
  "A1 (Head Noun)": ["individual", "person"],
  "A2 (Sub Noun)": ["jacket", "pants", "beanie", "head", "body language", "stance", "backdrop"],
  "A3 (Color)": ["red", "black", "snowy"],
  "A4 (Size)": [],
  "A5 (Absolute Location Relation)": ["right side of the image"],
  "A6 (Relative Location Relation)": ["on"],
  "A7 (Action)": ["standing", "wears", "covers", "appear", "suggests"],
  "A8 (Generic Attribute)": ["vibrant", "relaxed", "confident", "ready"],
  "Total Attributes Count": 7

Now, analyze this new sentence and classify its words into the same attributes: Sentence: "{sentence}"
Please classify into these categories:
1. Head noun: The main noun being described
2. Sub noun: Supporting nouns
3. Color: Color words
4. Size: Size-related words
5. Absolute location: Fixed position words
6. Relative location: Relative position words
7. Action: Action words/verbs
8. Generic attribute: Other descriptive words
Return only a JSON object in this exact format:
{{
  "A1 (Head Noun)": [],
  "A2 (Sub Noun)": [],
  "A3 (Color)": [],
  "A4 (Size)": [],
  "A5 (Absolute Location Relation)": [],
  "A6 (Relative Location Relation)": [],
  "A7 (Action)": [],
  "A8 (Generic Attribute)": [],
  "Total Attributes Count": 0
}}

Table C: Prompt for counting attributes

Idx	Superclass Word	Original Word
1	child	boy, girl, son, daughter
2	kid	boy, girl, son, daughter
3	adult	woman, women, man, men, female, male
4	person	woman, women, man, men, female, male, boy, girl, guy
5	their	his, her
6	vehicle	car, bus, plane, train, airplane, truck, boat, motorcycle
7	animal	bird, cow, bull, rabbit, bunny, dog, puppy, cat, zebra, elephant, horse, giraffe
8	fruit	apple, banana
9	vegetable	broccoli, carrot, cabbage, radish
10	food	sandwich, hot dog, pizza, donut, doughnut, cake, hamburger
11	electronic	tv, television, laptop, computer, keyboard, cell phone, smartphone
12	furniture	chair, couch, sofa, bed, desk

Table D: **Superclass and original words for text augmentation**

Model	Training data		val				test					
			overall		many attribute		shared attribute		overall			
	real	synthetic	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU		
RES Specialized Model												
ReLA	✓	✗	30.0	33.6	15.6	15.6	36.9	37.9	25.9	28.0		
	✓	✓ SynRES (Ours)	**33.9**	**38.1**	**18.2**	**19.9**	**38.0**	**39.8**	**27.8**	**31.7**		

(a) WildRES-ID (ReLA).

Model	Training data		Domain source						average	
			CrowdHuman		Cityscapes		ARMBench			
	real	synthetic	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU	gIoU	cIoU
RES Specialized Model										
ReLA	✓	✗	14.4	13.8	23.5	40.3	26.9	24.4	21.6	26.2
	✓	✓ SynRES (Ours)	**21.4**	**20.7**	**25.9**	**40.5**	**28.4**	**27.0**	**25.2**	**29.4**

(b) WildRES-DS (ReLA).

Table E: ReLA results on WildRES-ID and WildRES-DS.

Model	Training data		RefCOCO			RefCOCO+			RefCOCOg		gRefCOCO		
	real	synthetic	val	testA	testB	val	testA	testB	val(U)	test(U)	val	testA	testB
RES Specialized Model													
CRIS	✓	✗	70.5	73.2	66.1	62.3	68.1	53.7	59.9	60.4	56.3	63.4	51.8
LAVT	✓	✗	72.7	75.8	68.8	62.1	68.4	55.1	61.2	62.1	58.4	65.9	55.8
ReLA	✓	✗	73.8	76.5	70.2	66.0	71.0	57.7	65.0	66.0	63.6	70.0	61.0
X-Decoder	✓	✗	-	-	-	-	-	-	64.6	-	-	-	-
SEEM	✓	✗	-	-	-	-	-	-	65.7	-	-	-	-
LMM based RES Models													
F-LMM	✓	✗	75.2	79.1	71.9	63.7	71.8	54.7	67.1	68.1	-	-	-
VisionLLM v2	✓	✗	76.6	79.3	74.3	64.5	69.8	61.5	70.7	71.2	-	-	-
LISA-7B	✓	✗	73.4	75.7	70.0	62.3	66.8	56.2	67.3	68.1	-	-	-
	✓	✓ FreeMask	72.4	74.8	68.3	59.7	65.3	52.9	65.4	66.0	-	-	-
	✓	✓ SynRES (Ours)	**75.5**	**77.0**	**72.0**	**64.8**	**69.2**	**58.8**	**68.5**	**69.8**	-	-	-
GSVA-7B	✓	✗	**76.0**	**77.8**	**72.7**	63.6	**68.2**	58.3	69.9	70.7	72.6	73.7	66.5
	✓	✓ SynRES (Ours)	**76.0**	77.5	72.6	**64.2**	**68.2**	**59.0**	**70.1**	**70.9**	**73.6**	**74.6**	**67.9**
GLaMM-7B	✓	✗	80.3	**83.3**	77.9	73.9	79.0	**68.0**	75.3	75.2	-	-	-
	✓	✓ SynRES (Ours)	**80.6**	83.0	**78.0**	**74.1**	**79.5**	67.9	**75.5**	**75.9**	-	-	-

Table F: Classic referring segmentation results (gIoU) compared w/ and w/o SynRES on existing RES baselines. All numbers from LISA and GSVA are reproduced using their official repository and weights.

Ref-ZOM test		
	gIoU	cIoU
GSVA-7B	72.58	64.40
GSVA-7B+SynRES	**73.55**	**64.65**

Model	LISA-7B		LISA-13B		GSVA-7B	
	base	+SynRES	base	+SynRES	base	+SynRES
val	–	–	–	–	45.13	**45.78**
test	**44.66**	44.13	47.62	**48.02**	40.19	**40.72**

Table G: Results on Ref-ZOM test set (left) and ReasonSeg (right).

p	gIoU		τ	gIoU
0.5	40.8		0.55	40.5
0.6	40.3		0.6	39.6
0.7	**41.3**		0.65	**41.3**
0.8	41.0		0.7	40.2
0.9	40.4		0.75	40.8

Table H: Hyperparameter ablation study results with replace probability p and mIoU Threshold τ.

Syn. Images (%)	gIoU
25%	40.7
50%	40.8
75%	40.9
100%	**41.3**

Table I: Performance variations of LISA with SynRES on WildRES-ID validation set across different quantities of synthetic images.

SynRES	gender-specific	neutral	Gap ($\downarrow$)
✓	33.1	32.7	**0.4**
✗	31.4	30.3	1.1

Table J: Gender bias evaluation via counterfactual consistency on WildRES with gender-neutral word substitution.