Synthetic Data Generation of Many-to-Many Datasets via Random Graph Generation

Abstract

Synthetic data generation (SDG) has become a popular approach to release private datasets. In SDG, a generative model is fitted on the private real data, and samples drawn from the model are released as the protected synthetic data. While real-world datasets usually consist of multiple tables with potential *many-to-many* relationships (i.e. *many-to-many datasets*), recent research in SDG mostly focuses on modeling tables *independently* or only considers generating datasets with special cases of many-to-many relationships such as *one-to-many*. In this paper, we first study challenges of building faithful generative models for many-to-many datasets, identifying limitations of existing methods. We then present a novel factorization for many-to-many generative models, which leads to a scalable generation framework by combining recent results from random graph theory and representation learning. Finally, we extend the framework to establish the notion of (ϵ, δ)-differential privacy. Through a real-world dataset, we demonstrate that our method can generate synthetic datasets while preserving information within and across tables better than its closest competitor.

1 Introduction

Private data release has gained much attention in recent years due to new regulations in privacy such as General Data Protection Regulation (GDPR). To obey such regulations and to protect privacy, a popular approach from the machine learning community called *synthetic data generation* (SDG) is developed in various domains (Nowok et al., 2016; Montanez et al., 2018; Xu & Veeramachaneni, 2018; Xu et al., 2019; Lin et al., 2020; Tucker et al., 2020; Xu et al., 2021; Ziller et al., 2021). In SDG, synthetic data that is statistically similar but not identical to real data is released as a replacement of the real data to protect. On top of it, special attention has also been paid to make sure these methods work well on tabular data as most real-world datasets are stored as tables in databases (Montanez et al., 2018; Xu & Veeramachaneni, 2018; Xu et al., 2019; Nazabal et al., 2020; Ma et al., 2020).

At the core of most SDG methods are *generative models*—probabilistic models that one can drawn samples from. Usually a generative model is firstly trained to capture the distribution of the private real data, and then samples are drawn from the model so they can be released as protected synthetic data. However, this procedure without extra care does not have guarantees privacy. To tackle this, research in this direction has also been focusing on *differentially private generative models* (Zhang et al., 2017; Xie et al., 2018; Jordon et al., 2018)—generative models that satisfy a notion of privacy called *differential privacy* (Dwork et al., 2014), which controls the amount of information individual datum can reveal.

While real-world datasets usually consist of multiple tables with potential many-to-many relationships, SDG for such type of data is not well-studied. Most of recent work focuses on modeling tables *independently* (Xu & Veeramachaneni, 2018; Xu et al., 2019; Nazabal et al., 2020; Ma et al., 2020) or considers generating many-to-many relationships but only for special cases such as *one-to-many* (Getoor et al., 2007; Montanez et al., 2018). As a side effect, privacy for multi-table SDG with many-to-many relationships is also under-studied. In fact, relationships in real data can also reveal private information (Sala et al., 2011; Proserpio et al., 2012). For example, in a customer-merchant dataset, the number of links to a merchant could reveal its identity because of its uncommon popularity.

This paper studies the challenge of building faithful generative models (Webb et al., 2018) to synthesize data together with their many-to-many relationships, and proposes a novel factorization

(a) Bipartite graph $\mathcal{B}$ with annotations for node degrees

(b) Adjacency matrix $\mathbf{G}$ (left) and biadjacency matrix $\mathbf{B}$ (right)

(c) BJDD matrix $\mathbf{P_J}$ with supports $\mathbf{d}_u = \deg(n_u), \mathbf{d}_v = \deg(n_v)$

Figure 1: An illustration of bipartite graphs and their related representations and statistics.

for many-to-many generative models, which leads to a scalable approach by combining results from random graph theory and representation learning. In short, our paper has the following contributions:

1. We study possible factorization of faithful generative models for many-to-many data and identify limitations of those taken by existing approaches.
2. We propose a novel factorization for modeling distributions over many-to-many data and we use it to develop a synthetic data generation framework using methods from random graph generation, node representation learning and set representation learning.
3. We extend the proposed framework to establish the notion of (ϵ, δ)-differential privacy.
4. We evaluate two model instances from our framework, BayesM2M and NeuralM2M, on the MOVIELENS dataset, demonstrating its superior performance over its closest competitor, SDV, especially on capturing information in many-to-many relationships.

2   BACKGROUND AND NOTATIONS

Bipartite and multipartite graphs   A *bipartite graph* $\mathcal{B} := (\mathbb{U}, \mathbb{V}, \mathbb{L})$ is a tuple of two disjoint node sets $\mathbb{U}, \mathbb{V}$ (called *upper* and *lower* nodes respectively) as well as a set of edges $\mathbb{L}$ between them. Each node is represented by a tuple of its index and attribute, e.g. $n_u^k := (i_u^k, x_u^k) \in \mathbb{U}$ for $k = 1, \ldots, |\mathbb{U}|$. Each edge is represented by a tuple of node indices, i.e. $l^k := (i_u^k, i_v^k) \in \mathbb{L}$ for $k = 1, \ldots, |\mathbb{L}|$. Such edge sets can be represented as *adjacency matrices* $\mathbf{G}$ or *biadjacency matrices* $\mathbf{B}$; see figure 1b for an illustration. A generalised notion of bipartite graphs called *multipartite graphs*, denoted as $\mathcal{M} := (\{\mathbb{T}^{k_1}\}_{k_1=1}^N, \{\mathbb{L}^{k_2}\}_{k_2=1}^M)$, are graphs with N disjoint node sets and $M \leq \binom{N}{2}$ edge sets.

Modeling datasets with many-to-many relationships   [1]Datasets with many-to-many relationships, such as relational databases, can be viewed as multipartite graphs. Denote the generating distribution of a given multipartite graph $\mathcal{M}_{\text{data}}$ as $p_{\text{data}}(\mathcal{M})$. The goal of this paper is to build a generative model $p_\theta(\mathcal{M})$ with learnable parameter θ and to develop a learning algorithm $\mathcal{A}_1$ that takes $\mathcal{M}_{\text{data}}$ as inputs and outputs the optimal model p_{θ^*} with parameter θ^*, s.t. $p_{\theta^*}(\mathcal{M})$ is close to $p_{\text{data}}(\mathcal{M})$. After learning, a sample $\tilde{\mathcal{M}}$ is drawn from the model and used as synthetic data; we denote this sampling process/algorithm as $\mathcal{A}_2$.

Differential privacy   In this work, we are interested in establishing the standard (ϵ, δ)-*differential privacy*, a.k.a. (ϵ, δ)-DP or approximate DP. Denote $\mathcal{A} = \mathcal{A}_2 \circ \mathcal{A}_1$. We say a model p_θ with $\mathcal{A}$ is (ϵ, δ)-DP according to the following definition (Dwork et al., 2014):

Definition 1 ((ϵ, δ)-DP for p_θ with $\mathcal{A}$)**.** *A generative model p_θ with the synthesis algorithm $\mathcal{A}$ is (ϵ, δ)-DP if for all $\mathcal{S} \subseteq \text{Range}(\mathcal{A})$ and for all $\mathcal{B}, \mathcal{B}'$ that differ on a single element:*

$$\mathbb{P}(\mathcal{A}(\mathcal{B}) \in \mathcal{S}) \leq \exp(\epsilon)\mathbb{P}(\mathcal{A}(\mathcal{B}') \in \mathcal{S}) + \delta.$$

In our case, $\mathcal{S}$ is the output of the synthesis algorithm $\mathcal{A}$'s training procedure, while we are interested in the most general case (with strongest privacy protection) and define an element as a single node that could be part of either $\mathbb{U}$ or $\mathbb{V}$. If $\delta = 0$, we also call a model p_θ with $\mathcal{A}$ satisfies ϵ-differential privacy, i.e. ϵ-DP.

---

[1]Note here we are intended to avoid using terms such as primary/foreign keys and parents/children from the relational database literature. This is because in order to model the joint distribution for a given dataset, parent-child directions can be rearranged for modeling convenience in favor of some particular factorization of the joint.

Learning graph distributions Consider the distribution $p_{\text{data}}(\mathbb{L})$ for a given set of edges $\mathbb{L}_{\text{data}}$. Unlike setup in work like Liao et al. (2019) in which multiple samples from p_{data} are given, we are presented with a single sample from p_{data}. Therefore, rather than replying on the standard notion of *learning as probability divergence minimization* using empirical samples, we consider learning a model $p_\theta(\mathbb{L})$ such that samples from it share similar *graph properties* as $\mathbb{L}_{\text{data}}$.

Graph properties We consider the *dK-distributions* from Mahadevan et al. (2006) with $d = 2$, defined as the (joint) degree distribution of all pairs of d nodes in the graph.[2] We call all graphs with a given dK-distributions *dK-graphs*. For example, $0K$-graphs share the same graph density, $1K$-graphs share the same distribution of node degrees, $2K$-graphs share the same joint distributions of degrees of node pairs, etc. We call models that sample dK-graphs *dK-generators*. We consider the same notion for bipartite graphs, defining *bipartite dK-graphs*, and consider learning p_θ that generates bipartite $2K$-graphs of data. For a bipartite graph $\mathcal{B}$, we denote its *bipartite joint degree distribution* (BJDD) as the empirical distribution of samples $\{(\deg(\text{n}(i_u^k)), \deg(\text{n}(i_v^k)))\}_{k=1}^{|\mathbb{L}|}$, where $\text{n}(i)$ denotes the node with index i (similarly $\text{i}(n)$ is the node index for node n) and $\deg(n)$ is the degree of the node n. Such empirical distribution can be represented as a matrix $\mathbf{P_J}$ along with the supports $\mathbf{d}_u, \mathbf{d}_v$ for both dimensions; see figure 1c for an illustration. One can also compute the (marginal) degree distributions of the upper or lower nodes from BJDD. For example, that of upper nodes $\mathbf{p}_u$ is a probability vector (a vector of whose elements sum up to 1) in which its i-th element $\mathbf{p}_u[i] = \sum_j \mathbf{P_J}[i,j]/\mathbf{d}_u[i]$.

3 RELATED WORK

Generative models for tabular data In general, there are two categories of generative models that have been successfully applied to tabular data. One is based on classic *graphical models*. This includes *directed* graphical models such as Bayesian networks PrivBayes (PrivBayes; Zhang et al., 2017) and auto-regressive models (synthpop; Nowok et al., 2016) as well as *undirected* graphical models such as factor graphs (MST; McKenna et al., 2019). For these models, data is usually discretized in order to facilitate efficient learning. Another is based on recently emerged *deep generative models* such as *variational autoencoders* (VAEs; Kingma & Welling, 2013; Rezende et al., 2014) and *generative adversarial networks* (GANs; Goodfellow et al., 2014). Unlike graphical models, work on deep generative models has been mostly focusing on developing methods to directly model *heterogeneous data*, which are mixed-type data with different types of continuous (real, positive real, etc) and discrete variables (categorical, ordinal, etc), which includes specific pre-processing steps, neural network architecture design, improving training, etc (Xu & Veeramachaneni, 2018; Xu et al., 2019; Nazabal et al., 2020; Ma et al., 2020); for surveys, see Fan et al. (2020); Borisov et al. (2021).

Generative models for relational data Probabilistic relational models (PRMs) (Friedman et al., 1999; Getoor et al., 2007) is the most well-established approach to building distributions over relational data. Getoor et al. (2007) describes two ways of dealing with structural uncertainty but only with learning methods for structures, i.e. finding the best structures. While it is possible to extend these methods to samplers by using Markov chain Monte Carlo for sampling, applying them to datasets at scale would be challenging. Mostly related to our work is *Synthetic Data Vault* (SDV) (Patki et al., 2016; Montanez et al., 2018), which is based on PRMs and considers the task of synthesizing relational data with links. However, SDV only models one-to-many relationships by recording the children count per row and generates one-to-many links by sampling the number of children. Because SDV cannot handle many-to-one relationships, the so-called "multiple parents" problem occurs in certain scenarios (Montanez et al., 2018). For example, consider three tables $A - B - C$ forming an *one-many-one* relationship. At generation time, SDV has to generate A and C first and conditionally generates B given A and C, at which stage it is unclear whether the children counts in A or C should be used. Montanez et al. (2018) suggests to either randomly pick a table for the conditional generation or to perform weighted averaging between parents. Another related work based on PRMs is Ben Ishak et al. (2016), which describes a generator for many-to-many data

---

[2] With d increasing, samples from the dK-distributions become more similar to the data but generating dK-graphs is increasingly computationally complex; luckily $2K$-graphs are sufficient for most practical purposes (Mahadevan et al., 2006). Also note that with $d \to \infty$, dK-series describe any given graph completely. In addition, from a privacy perspective, a large d means high sensitivity in the dK-series, which requires much more noise to be added for achieving ϵ-DP for a given ϵ (Sala et al., 2011).

with links. However, the work only targets generating testing data—data used as test examples in a software engineering setup. Thus, the generator is learnable.

Random graph generation   One line of work in this direction is built on the classic *degree sequence problem*, which is the problem of finding some or all graphs with a given degree sequence (Molloy & Reed, 1995). Mahadevan et al. (2006) introduces the notion of dK-graphs and studies generating them via classic random graph methods, such as the *pseudograph* or *configuration* approach (Molloy & Reed, 1995; Aiello et al., 2000). As classic methods in general cannot correctly sample dK-graphs with $d \geq 2$, a few follow-up works improves the sampling for these graphs (Stanton & Pinar, 2012; Gjoka et al., 2013; 2015). Unlike previous work that focuses on general graphs, Boroojeni et al. (2017) specifically considers sampling bipartite graphs that preserves the $2K$-distribution. Another line of methods, unlike above-mentioned methods that can generate arbitrary-sized graphs, can only generate graphs with the same size as the data graph, e.g. spectral-based approach in Baldesi et al. (2018), or expands it by a whole number, e.g. method based on fractal expansions from Belletti et al. (2019).

Differentially private SDG   In terms of DP generative models, a few graphical models discussed above (PrivBayes, MST) are originally proposed in a DP context. For deep generative models, there are two generic training algorithms that make models differentially private: differentially private stochastic gradient descent (DP-SGD; Abadi et al., 2016) and private aggregation of teacher ensembles (PATE; Papernot et al., 2016; 2018), leading to methods such as DP-GAN (Xie et al., 2018) and PATE-GAN (Jordon et al., 2018). Regarding random graph generation, Sala et al. (2011); Proserpio et al. (2012) consider the release of graphs in a differentially private manner based on dK-generators. To the best of our knowledge, there is no work specifically targeting differentially private synthesis of bipartite graphs, nor previous work for differentially private synthesis for many-to-many datasets.

4   MODELING MANY-TO-MANY DATASETS WITH DIFFERENTIAL PRIVACY

In this section, we first discuss the challenges of building faithful generative models (Webb et al., 2018) for many-to-many datasets by studying possible factorization of the joint distribution (section 4.1), during which we also identify the limitations of the factorization that existing approaches are based on. Based on a novel factorization, we use methods from random graph generation, node representation learning and set representation learning to develop a new type of scalable generative model for many-to-many datasets section 4.2. Finally, we extend the model to be (ϵ, δ)-differentially private section 4.3. Also note that in this section, for brevity, we omit the model parameter θ in p_θ unless it is necessary.

4.1   FAITHFUL GENERATIVE MODELS FOR MANY-TO-MANY DATASETS

To simplify the discussion, we first focus on modeling bipartite graph and will later extend it to multipartite graphs. The term "faithful" as in faithful generative models refers to the fact that the model does not introduce any conditional independence that is not true in general (Webb et al., 2018). For the joint distribution $p(\mathbb{U}, \mathbb{V}, \mathbb{L})$, where $\mathbb{U}, \mathbb{V}$ are two tables with rows linked by edges in $\mathbb{L}$, that we are interested in, considering the fact that the roles of $\mathbb{U}$ and $\mathbb{V}$ are exchangeable, there are only three possible factorization of the joint $p(\mathbb{U}, \mathbb{V}, \mathbb{L}) := p_{\text{joint}}$:

	FACTORIZATION S	FACTORIZATION E	FACTORIZATION A
p_{joint}	$p(\mathbb{U})p(\mathbb{L} \mid \mathbb{U})p(\mathbb{V} \mid \mathbb{U}, \mathbb{L})$	$p(\mathbb{U})p(\mathbb{V} \mid \mathbb{U})p(\mathbb{L} \mid \mathbb{U}, \mathbb{V})$	$p(\mathbb{L})p(\mathbb{U} \mid \mathbb{L})p(\mathbb{V} \mid \mathbb{U}, \mathbb{L})$

Within all factorization, there are a 6 sub-models in total to consider.

- $p(\mathbb{U})$ (the single-table model) can be any generative model for single table generation.
- $p(\mathbb{L} \mid \mathbb{U})$ (the semi-conditional edge model) requires to generate edges based on one of the table—the row count generation used in Montanez et al. (2018) is in fact an example of such. However, a general case of this model can be computational challenging: For any subset of $\mathbb{U}$, it requires checking if they together link to an existing or new node in $\mathbb{V}$.
- $p(\mathbb{V} \mid \mathbb{U}, \mathbb{L})$ (the conditional table model) requires to generate each node in $\mathbb{V}$ based on the first table and all connections. As per node in $\mathbb{V}$ is connected to a subset of nodes in $\mathbb{U}$ via $\mathbb{L}$, it requires to condition on a set of varied number of nodes for modelling, which can be done using a *aggregation function* or a *aggregator* (Getoor et al., 2007; Montanez et al., 2018).

(a) Learning (models can be fitted in parallel)   (b) Sampling (generation is sequential)

Figure 2: Illustrations of how the proposed framework works during learning and sampling phases.

- $p(\mathbb{V} \mid \mathbb{U})$ (the table-conditional table model) requires to generate one table conditioned on another (while marginalizing all edges). This model can be computational challenge to implement. A potential work-around is to model the two-table joint $p(\mathbb{U}, \mathbb{V})$ directly by joining two tables and apply a generative model on the joined table. However, this could easily lead to table with an intractable scale. And perhaps more importantly, it is hard to undo this join operation from the synthetic data to recover individual tables in general.[3].
- $p(\mathbb{L} \mid \mathbb{U}, \mathbb{V})$ (the edge prediction model) predicts the existences of edges between node pairs and is essential probabilistic models used in many recommender systems.
- $p(\mathbb{L})$ (the edge model) requires to model the edges (i.e. the graph) unconditionally—this is the type of random graph models that usually studied in random graph theory.
- $p(\mathbb{U} \mid \mathbb{L})$ (the edge-conditional table model) requires to generate one of the table given the topology of edges. One way to achieve such conditioning is by using a node embedding to condition on. This is also related to node attributes generation/prediction in graph models.

As discussed, approaches from Getoor et al. (2007); Montanez et al. (2018) correspond to FACTORIZATION S and there is no easy way to extend $p(\mathbb{L} \mid \mathbb{U})$ to a general many-to-many case. FACTORIZATION E also has the scalability issue in $p(\mathbb{V} \mid \mathbb{U})$ (or similarly in $p(\mathbb{U}, \mathbb{V})$) as discussed. Our approach will then be based on FACTORIZATION A that does not have such concerns/limitations.

Considering edges attributes   So far our discussion assumes there are no edge attributes, which is not true in general, e.g. ratings in MOVIELENS. The way to deal with this is by adding an extra edge attribute model that is similar to $p(\mathbb{L} \mid \mathbb{U}, \mathbb{V})$ but generates edge attributes instead. One can use any edge prediction model for this purpose—rather than predicting the existence of edges it generates the edge attributes—and the corresponding generation step is performed after all other data is generated.

Extending to multipartite graphs   For a given datasets with multiple tables, we assume the links at table level are given. Thus we can impose an *arbitrary* order on the tables and generate the edges and tables in order; this is similar to how an arbitrary order is imposed on random variables as in Bayesian networks. Extra care needs to be taken for graph generation when generating graphs involving tables with more than one connection, which will be explained in section 4.2.1.

4.2   RANDOM GRAPH GENERATION BASED MANY-TO-MANY SYNTHESIS

We now describe how to model the three distributions in our proposed factorization $p_{\text{joint}} = p(\mathbb{L})p(\mathbb{U} \mid \mathbb{L})p(\mathbb{V} \mid \mathbb{U}, \mathbb{L})$: $p(\mathbb{L})$ in section 4.2.1, $p(\mathbb{U} \mid \mathbb{L})$ in section 4.2.2 and $p(\mathbb{V} \mid \mathbb{L}, \mathbb{U})$ in section 4.2.3. Figure 2 also provides an illustration of the learning and sampling process for the proposed method.

4.2.1   GRAPH MODELING VIA RANDOM GRAPH GENERATION

We consider using bipartite dK-generators to model $p(\mathbb{L})$ that take in a target BJD **J** and generate random graph satisfying this **J**. Boroojeni et al. (2017) proves the existence of an algorithm for sampling bipartite graphs with a target BJD **J**, giving rise to bipartite $2K$-generators. The idea is

---

[3]As a concrete example, suppose $\mathbb{U}$ has a single column C_1 with a continuous variable, $\mathbb{V}$ has another column C_2 (with either a continuous or discrete variable) and $\mathbb{L}$ indicates every row in $\mathbb{U}$ is linked with two rows in $\mathbb{V}$. After joining two tables, we will arrive with a table in which two columns C_1, C_2 in which there are duplicated elements in C_1 due to the one-to-many relationship; it is also possible to undo the join operation on this real dataset. However, for any generative model that treats C_1 as continuous variable, the probability of having duplicated elements in C_1 is exactly 0, which means any synthetic dataset would effectively giving a dataset with one-to-one relationship between $\mathbb{U}$ and $\mathbb{V}$, after undoing the join operation.

to first generate a bipartite graph based on random pairing, after which the graph matches the $2K$ distribution but has potentially repeated edges. Then, a rewiring process is performed to make the graph *simple*—a graph is called simple if there is no loop or multiple edges (West et al., 2001). Boroojeni et al. (2017) shows that such rewiring process exists and can always produce a graph with the target BJD. Since the prescribed algorithm of rewiring in Boroojeni et al. (2017) contains a few mistakes/typos, we present a corrected version in algorithm 1 in appendix A.

To complete the description of $p_\theta(\mathbb{L})$, we also need to define how to obtain $\mathbf{J}$ that bipartite algorithm 1 take in. For this, we draw samples from $\mathbf{P_J}$ with a prescribed number of edges. However, as this might invalidate the input to algorithm 1[4], which may cause infinite loops in rewiring, we stop the rewiring process after a predefined maximum number of iterations. To this end, sampling from $\mathbf{J}$ together with algorithm 1 define $p_\theta(\mathbb{L})$ through its generative process, where θ is the BJDD matrix $\mathbf{P_J}$.

"Backward compatibility" of the graph generator   One consideration taken into account while selecting the model for $p(\mathbb{L})$ was "backward compatibility" to one-to-many and many-to-one problems. This refers to the cases where if the data graph contains only one-to-many relationships, the generated graphs shall do so. The $2K$-generator indeed satisfies this property while, in contrast, spectral-based graph generation methods such as Baldesi et al. (2018) usually fail to hold it.

Learning and sampling   Learning of this model only involves computing the BJDD matrix from the data graph; if a table is involved in multiple edges, the joint distribution of all degrees per node is learned. Sampling from the model is defined by sampling from $\mathbf{P_J}$ followed by algorithm 1.

4.2.2 Conditional modeling via node embedding

We now discuss how to model upper nodes $\mathbb{U}$ conditioned on edges $\mathbb{L}$. This distribution essentially models a set of nodes given topology, which can be dealt with the use of node embedding as:

$$p(\mathbb{U} \mid \mathbb{L}) = \prod_{k=1}^{|\mathbb{U}|} p(n_u^i \mid \beta(\mathbb{L}, i)), \tag{1}$$

where the node encoder β computes *node embedding* of node i in graph $\mathbb{L}$; its *range* is $\mathrm{ran}(\beta) = \mathbb{R}^{H_\beta}$, where H_β is the dimension of the node embedding. As such, once given β, this distribution can be modeled by any existing conditional generative model. A few candidates of such β are:

1. Node statistics: d-step neighbour count (number of neighbours of distance d) can be used. As an simple example, $d = 1$ means using node degrees as 1d embeddings. It can be generalised to use a collection of counts with H_β different d, giving to an embedding of size H_β.
2. Node embedding: Methods to learn node embedding such as DeepWalk (Perozzi et al., 2014) and node2vec (Grover & Leskovec, 2016) can also be used as β.

Learning and sampling   Learning of this model involves learning the node embedding (if it is not fixed) and learning the conditional generative model. Sampling from the model is straightforward.

4.2.3 Conditional modeling via set embedding

Consider a node $n_v \in \mathbb{V}$ with neighbors $\mathrm{ne}(n_v) \subseteq \mathbb{U}$. It is easy to see that, given $\mathrm{ne}(n_v)$, n_v is conditionally independent with any other $n_v' \in \mathbb{V}$. Thus, we have $p(\mathbb{V} \mid \mathbb{L}, \mathbb{U}) = \prod_{n_v \in \mathbb{V}} p(n_v \mid \mathrm{ne}(n_v))$, where $p(n_v \mid \mathrm{ne}(n_v))$ is a conditional distribution whose condition is a *multiset*—a set that allows repeated elements. Without imposing any order on $\mathrm{ne}(n_v)$, one way to condition on this through a *fixed-size set embedding* computed by an aggregator γ, which leads to our model

$$p(\mathbb{V} \mid \mathbb{L}, \mathbb{U}) = \prod_{n_v \in \mathbb{V}} p(n_v \mid \gamma(\mathrm{ne}(n_v))). \tag{2}$$

Equation 2 requires an aggregator $\gamma : \mathrm{pow}(\mathbb{U}) \mapsto \mathbb{R}^{H_\gamma}$ where $\mathrm{pow}(\mathbb{U})$ is the *power set* of $\mathbb{U}$ and H_γ is the dimension of the set embedding. A few candidates of such γ are:

---

[4]Algorithm 1 assumes two conditions for the input $\mathbf{J}$: (i) $\mathbf{J}[i, j] \leq (\sum_j \mathbf{J}[i, j]/\mathbf{d}_u[i])(\sum_i \mathbf{J}[i, j]/\mathbf{d}_v[j])$ and (ii) the degree sums for upper and lower nodes are the same (which would be true as long as $\sum_j \mathbf{J}[i, j]/\mathbf{d}_u[i]$ is integer for all i and $\sum_i \mathbf{J}[i, j]/\mathbf{d}_u[j]$ is integer for all j) (Boroojeni et al., 2017).

1. Summary statistics: count, sum, n-th order moments, q-percent quantiles, etc. can be used. If both count and sum are used and d different moments and quantiles are used, the total dimension of the embedding is $D + D + d \times D + d \times D$ for nodes with D-dimensional attributes.
2. Distribution parameters: One can also fit a distribution on the set and use the distribution parameters as the embedding. Montanez et al. (2018) suggests using a Gaussian copula; for nodes with D-dimensional attributes, the dimension of the embedding is $D + D^2$.
3. Set embedding: The deep sets architecture (Zaheer et al., 2017) is specifically proposed to produce a set embedding. If the single table model used is neural based, this architecture can be used to consume a set of nodes and outputs the embedding to condition on. Training of this module in this case is done end-to-end with the neural-based conditional generator.[5].

Learning and sampling   Learning of this model involves learning the set embedding (if it is not fixed) and learning the conditional generative model. Sampling from the model is straightforward.

4.3   Establishing differential privacy

We now describe how to extend the learning of each sub-model in $p_\theta(\mathbb{U}, \mathbb{V}, \mathbb{L}) = p_{\theta_1}(\mathbb{L})p_{\theta_2}(\mathbb{U} \mid \mathbb{L})p_{\theta_3}(\mathbb{V} \mid \mathbb{L}, \mathbb{U})$ such that the learned parameter $\theta = (\theta_1, \theta_2, \theta_3)$ with corresponding privacy budgets ϵ_1, ϵ_2, and ϵ_3 ($\epsilon_1 + \epsilon_2 + \epsilon_3 = \epsilon$) is (ϵ, δ)-DP, which by sequential composition implies the whole synthetic data generation process is (ϵ, δ)-DP. Note that we assume the required privacy budgets for each component in each sub-model are given; how to optimally spend the budget is a question for future work that is out of the scope of this paper.

$p_{\theta_1}(\mathbb{L})$ **with** ϵ_1 For p_{θ_1}, θ_1 is the BJDD matrix $\mathbf{P_J}$. As per the definition in section 2, we are interested in masking the presence of absence of a single node of either $\mathbb{U}$ or $\mathbb{V}$, which is a stronger privacy notion than edge protection. To do so we follow the strategy in Sala et al. (2011); Proserpio et al. (2012) that uses the Laplace mechanism to make $\mathbf{P_J}$ ϵ-DP. The main difference here is that we are operating on bipartite graphs instead of general graphs. Specifically, after measuring the BJD matrix $\mathbf{J}$ from data graphs, to achieve ϵ-DP, we add noise following $\mathcal{L}ap(\frac{S_{ij}}{\epsilon})$ where $S_{ij} = 4\max(d_i, d_j)$ to the i-th row, j-th column entry of $\mathbf{J}$ (Sala et al., 2011; Proserpio et al., 2012).

$p_{\theta_2}(\mathbb{U} \mid \mathbb{L})$ **with** ϵ_2 For p_{θ_2}, θ_2 consists both the parameter of the node embedding model as well as that of the underlying generative model for the conditional. For the former, if such embedding is pre-fixed (referred as "node statistics" in section 4.2.2), there is no learnable parameter for the node embedding model; otherwise we use DP-SGD (Abadi et al., 2016) to train the embedding. For the underlying generative model, we choose some existing DP ones and follow their learning algorithms.

$p_{\theta_3}(\mathbb{V} \mid \mathbb{L}, \mathbb{U})$ **with** ϵ_3 For p_{θ_3}, θ_3 consists both the parameter of the set embedding model as well as that of the underlying generative model for the conditional. For the former, if such embedding is pre-fixed (referred as "statistics" in section 4.2.3), there is no learnable parameter for the node embedding model; if such embedding is from Gaussian copula (the second option in section 4.2.3), we use the differentially private copula from Li et al. (2014); if such embedding is based on the deep sets architecture, which is only defined when it can be trained end-to-end with the generative model, we use DP-SGD (Abadi et al., 2016) for training. For the underlying generative model not trained jointly, we choose some existing DP ones and follow their learning algorithms.

It should be noted that the proposed formulation is flexible enough to allow for the privacy protection of the nodes from only one of $\mathbb{U}$ and $\mathbb{V}$ but not the other. For instance, if we choose to protect only $\mathbb{U}$, we can set $\epsilon_3 = \infty$ when learning $p_{\theta_3}(\mathbb{V} \mid \mathbb{L}, \mathbb{U})$ and $d_j = 0$ for all j when learning $p_{\theta_1}(\mathbb{L})$, making the overall synthetic data generation process (ϵ, δ)-DP ($\epsilon_1 + \epsilon_2 = \epsilon$).

5   Evaluation

Dataset   We consider the MOVIELENS in our evaluation. MOVIELENS is a dataset that contains users' ratings to different movies (Harper & Konstan, 2015). The user and movie tables have their

---

[5]As there is no existing method to train deep sets in an unsupervised manner, it cannot be used with classic models like Bayesian networks. This, however, is an interesting future work that is out of the scope of this paper.

own attributes such as user ages and movie genres and have a many-to-many relationship through existing ratings. We choose MOVIELENS as it is a commonly used datasets to study graph properties (Harper & Konstan, 2015; Baldesi et al., 2018; Belletti et al., 2019).

Pre-processing   We discretize all features into maximally 30 bins. Note this discretization step is optional: for our study, it is meant to make modeling and evaluation easier, which is an orthogonal consideration to the main point of the study which is to assess the performance of many-to-many modelling. Also note we do not use any privacy budget during pre-processing by assuming all information needed are public, which is again a separate concern that is out of the scope of this paper.

5.1   QUALITY OF MANY-TO-MANY MODELING

In this section, we evaluate the quality of the proposed model in terms of synthetic data similarity. We consider a set of baselines as well as two realizations of the proposed method, which we explain next.

Baseline   We consider SDV (Montanez et al., 2018) as the baseline method in our evaluation.[6] SDV decomposes many-to-many relationships into multiple one-to-many ones and has the "multiple parents" (discussed in section 3). To handle this, instead of randomly picking one table as the parent as suggested by Montanez et al. (2018), we experiment both options and report the one with better results.

Two model instances from the proposed framework   The proposed framework enables a range of new generative models with different options in each submodel detailed in section 4.2. In this evaluation, we focus on two typical ones built on different single table models: a Bayesian network with the network building method from Zhang et al. (2017), referred as BN, and an autoregressive model in which each conditional is modelled by a neural network, referred as NeuralAR. The two realizations are then (i) a classic non-parametric approach in which the single table models used are BN, referred as Bayesian many-to-many (BayesM2M) and (ii) a neural-based approach in which the single table models used are NeuralAR, referred as neural many-to-many (NeuralM2M). In both realizations, for $p(\mathbb{L})$, we use the $2K$-generator. In BayesM2M, for $p(\mathbb{U} \mid \mathbb{L})$, we use node statistics with d-step counts for $d = 1, 2$; for $p(\mathbb{V} \mid \mathbb{L}, \mathbb{U})$, we use summary statistics with count, sum, n-th order moments for $n = 1, 2, 3$ and q-percent quantiles for $q = 0.25, 0.5, 0.75$. In NeuralM2M, for $p(\mathbb{U} \mid \mathbb{L})$, we use node2vec to extract node embeddings; for $p(\mathbb{V} \mid \mathbb{L}, \mathbb{U})$, we use the deep sets architecture (Zaheer et al., 2017) to consume a set of node (equivalently a set of rows).

Metrics   We consider three sets of metrics to evaluate the generation quality. The first set consists metrics that specifically evaluate the *quality of relationship generation*, which are one minus the total variation distances between the dK-distributions of real and synthetic data for $d = 1, 2$ (bounded between 0 and 1). The second set consists the pairwise mutual information (MI) similarity for each table to evaluate *the quality of individual tables*. For a pair of real and synthetic tables, we first compute the normalized MI[7] between each pair of columns in each table; for tables with m features, this gives a pair of $m \times m$ matrices. The MI similarity is then defined as the average Jaccard indices between each pair of entries. Compared to alternative metrics such as f-divergences, this metric is bounded between 0 and 1 thus is easy to interpret. The third set consists the metrics to capture correlations between table pairs rooted in their many-to-many relationships, i.e. *cross-table similarity*. For each pair, we join the tables by their links into a single table and compute the pairwise MI similarity for each pair between two tables; for a pair of two tables with m and n features, this gives a pair of $m \times n$ matrices. The MI similarity is then defined as the average Jaccard indices between each pair of entries. To help understand our metrics, we provide detailed definitions with step-by-step examples in appendix B.

Table 1 summarizes the main results from experiments with the above setups. Compared to SDV, both realizations of the proposed method obtains better scores in terms of graph similarity (marginal and joint degree similarity). This supports our choice of using random graph generation as the starting point of the whole generative process. Among two realizations, NeuralM2M has a better score in MI similarity for $\mathbb{U}$, indicating that the node representation from node2vec contains more information

---

[6]We use the official implementation of SDV at `https://github.com/sdv-dev/SDV` in our experiments.

[7]For discrete X, Y, we have $I(X; Y) \leq \min(H(X), H(Y))$. Thus normalized MI is defined as $I(X; Y)/\min(H(X), H(Y))$, which is bounded between 0 and 1.

Table 1: Quality of many-to-many modelling on MOVIELENS. All metrics are bounded between 0 and 1 with 1 being the theoretical maximal value, i.e. higher the better. Numbers are mean and standard deviation based on 5 runs with different random seeds.

Method	Degree Similarity		Mutual Information Similarity		
	Marginal	Joint	$\mathbb{U}$	$\mathbb{V}$	Cross-Table
SDV	0.867 ± 0.003	0.614 ± 0.012	0.547 ± 0.033	0.334 ± 0.017	0.440 ± 0.035
BayesM2M	0.955 ± 0.016	0.634 ± 0.028	0.756 ± 0.041	0.345 ± 0.016	0.561 ± 0.031
NeuralM2M			0.846 ± 0.045	0.562 ± 0.031	0.613 ± 0.016

than a simple-minded node statistics. On top of this, NeuralM2M also has a larger the gain/different between MI similarity for $\mathbb{U}$ and $\mathbb{V}$ than BayesM2M, indicating that deep sets architecture learn better set representation than fixed summary statistics. As a result of using random graph generation and learnable neural-based representations, NeuralM2M has the best cross-table similarity.

5.2 PERFORMANCE UNDER DIFFERENTIAL PRIVACY CONSTRAINTS

For the two typical realizations of the proposed framework, we now evaluate how the generation quality of their differentially private variants changes with different privacy budgets. We focus on the cross-table similarity in this section as it is the most comprehensive metric for many-to-many modelling.

Privacy budgets For both realizations, we vary ϵ in $\{0.1, 10.0, 1,000.0, \infty\}$. For NeuralM2M, as it only satisfies approximate DP, we in addition set $\delta = 1 \times 10^{-5}$.

Figure 3 summarizes the main results from experiments with the above setups. As it can be seen, even though NeuralM2M performs well in a non-DP setup, its performance drops quickly with even a slightly smaller privacy budget. In comparison, BayesM2M has a better privacy-similarity trade-off. The main reason behind this is that the components in NeuralM2M rely on iterative training in which noise is added per iteration in order to establish differential privacy, making it hard to optimally spend the privacy budget or to obtain a tight DP bound. On the other side, most of the component in BayesM2M are pre-fixed and BNs can achieve DP by only adding noises to the measurement (i.e. counting for discreized data) of each table column.

Figure 3: Cross-table similarity with privacy budgets ϵ on MOVIELENS

6 DISCUSSION AND CONCLUSION

Limitation The overall quality of the proposed framework depends on the choice of random graph generation methods. In this paper, we mostly focus on the $2K$-generator that can generate arbitary-sized graphs but it at its best matches the $2K$-distributions of the real data. Some other graph generation methods such as Baldesi et al. (2018); Belletti et al. (2019) can capture more graph statistics but can only generate graphs with the same size as the data graph or expands it by a whole number.

Societal impacts On the positive side, the proposed method improve SDG for many-to-many data and can be used to release such data with DP guarantees, protecting the privacy of relevant individuals. However, as all generative model-based SDG methods, the synthetic data may be different from the real one in certain ways, causing potential fairness issues.

To conclude, this paper studies the challenge of building faithful generative models for many-to-many datasets and present a novel generation framework based on random graph generation, node and set representation learning. The proposed framework is demonstrated to be better than its closest competitor SDV in terms of the generation quality on the widely-studied MOVIELENS dataset. We also study the behaviour of proposed model under different DP constraints, highlighting potential future works.

REFERENCES

Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pp. 308–318, 2016.

William Aiello, Fan Chung, and Linyuan Lu. A random graph model for massive graphs. In *Proceedings of the thirty-second annual ACM symposium on Theory of computing*, pp. 171–180, 2000.

Luca Baldesi, Carter T Butts, and Athina Markopoulou. Spectral graph forge: Graph generation targeting modularity. In *IEEE INFOCOM 2018-IEEE Conference on Computer Communications*, pp. 1727–1735. IEEE, 2018.

Francois Belletti, Karthik Lakshmanan, Walid Krichene, Yi-Fan Chen, and John Anderson. Scalable realistic recommendation datasets through fractal expansions. *arXiv preprint arXiv:1901.08910*, 2019.

Mouna Ben Ishak, Philippe Leray, and Nahla Ben Amor. Probabilistic relational model benchmark generation: Principle and application. *Intelligent Data Analysis*, 20(3):615–635, 2016.

Vadim Borisov, Tobias Leemann, Kathrin Seßler, Johannes Haug, Martin Pawelczyk, and Gjergji Kasneci. Deep neural networks and tabular data: A survey. *arXiv preprint arXiv:2110.01889*, 2021.

Asma Azizi Boroojeni, Jeremy Dewar, Tong Wu, and James M Hyman. Generating bipartite networks with a prescribed joint degree distribution. *Journal of complex networks*, 5(6):839–857, 2017.

Cynthia Dwork, Aaron Roth, et al. The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, 9(3-4):211–407, 2014.

Ju Fan, Junyou Chen, Tongyu Liu, Yuwei Shen, Guoliang Li, and Xiaoyong Du. Relational data synthesis using generative adversarial networks: A design space exploration. *Proc. VLDB Endow.*, 13(12):1962–1975, jul 2020. ISSN 2150-8097. doi: 10.14778/3407790.3407802. URL https://doi.org/10.14778/3407790.3407802.

Nir Friedman, Lise Getoor, Daphne Koller, and Avi Pfeffer. Learning probabilistic relational models. In *IJCAI*, volume 99, pp. 1300–1309, 1999.

Lise Getoor, Nir Friedman, Daphne Koller, and Benjamin Taskar. Probabilistic relational models. *Introduction to statistical relational learning*, 8, 2007.

Minas Gjoka, Maciej Kurant, and Athina Markopoulou. *2.5 k-graphs: from sampling to generation*. IEEE, 2013.

Minas Gjoka, Bálint Tillman, and Athina Markopoulou. Construction of simple graphs with a target joint degree matrix and beyond. In *2015 IEEE Conference on Computer Communications (INFOCOM)*, pp. 1553–1561. IEEE, 2015.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 855–864, 2016.

F. Maxwell Harper and Joseph A. Konstan. The movielens datasets: History and context. *ACM Trans. Interact. Intell. Syst.*, 5(4), dec 2015. ISSN 2160-6455. doi: 10.1145/2827872. URL https://doi.org/10.1145/2827872.

James Jordon, Jinsung Yoon, and Mihaela Van Der Schaar. Pate-gan: Generating synthetic data with differential privacy guarantees. In *International conference on learning representations*, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Haoran Li, Li Xiong, Lifan Zhang, and Xiaoqian Jiang. Dpsynthesizer: differentially private data synthesizer for privacy preserving data sharing. In *Proceedings of the VLDB Endowment International Conference on Very Large Data Bases*, volume 7, pp. 1677. NIH Public Access, 2014.

Renjie Liao, Yujia Li, Yang Song, Shenlong Wang, Will Hamilton, David K Duvenaud, Raquel Urtasun, and Richard Zemel. Efficient graph generation with graph recurrent attention networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Zinan Lin, Alankar Jain, Chen Wang, Giulia Fanti, and Vyas Sekar. Using gans for sharing networked time series data: Challenges, initial promise, and open questions. In *Proceedings of the ACM Internet Measurement Conference*, IMC '20, pp. 464–483, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450381383. doi: 10.1145/3419394.3423643. URL https://doi.org/10.1145/3419394.3423643.

Chao Ma, Sebastian Tschiatschek, Richard Turner, José Miguel Hernández-Lobato, and Cheng Zhang. VAEM: a deep generative model for heterogeneous mixed type data. *Advances in Neural Information Processing Systems*, 33:11237–11247, 2020.

Priya Mahadevan, Dmitri Krioukov, Kevin Fall, and Amin Vahdat. Systematic topology analysis and generation using degree correlations. *ACM SIGCOMM Computer Communication Review*, 36(4): 135–146, 2006.

Ryan McKenna, Daniel Sheldon, and Gerome Miklau. Graphical-model based estimation and inference for differential privacy. In *International Conference on Machine Learning*, pp. 4435–4444. PMLR, 2019.

Michael Molloy and Bruce Reed. A critical point for random graphs with a given degree sequence. *Random structures & algorithms*, 6(2-3):161–180, 1995.

Andrew Montanez et al. *SDV: an open source library for synthetic data generation*. PhD thesis, Massachusetts Institute of Technology, 2018.

Alfredo Nazabal, Pablo M Olmos, Zoubin Ghahramani, and Isabel Valera. Handling incomplete heterogeneous data using VAEs. *Pattern Recognition*, 107:107501, 2020.

Beata Nowok, Gillian M. Raab, and Chris Dibben. synthpop: Bespoke creation of synthetic data in r. *Journal of Statistical Software*, 74(11):1–26, 2016. doi: 10.18637/jss.v074.i11. URL https://www.jstatsoft.org/index.php/jss/article/view/v074i11.

Nicolas Papernot, Martín Abadi, Ulfar Erlingsson, Ian Goodfellow, and Kunal Talwar. Semi-supervised knowledge transfer for deep learning from private training data. *arXiv preprint arXiv:1610.05755*, 2016.

Nicolas Papernot, Shuang Song, Ilya Mironov, Ananth Raghunathan, Kunal Talwar, and Úlfar Erlingsson. Scalable private learning with PATE. *arXiv preprint arXiv:1802.08908*, 2018.

N. Patki, R. Wedge, and K. Veeramachaneni. The synthetic data vault. In *2016 IEEE International Conference on Data Science and Advanced Analytics (DSAA)*, pp. 399–410, Oct 2016. doi: 10.1109/DSAA.2016.49.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 701–710, 2014.

Davide Proserpio, Sharon Goldberg, and Frank McSherry. A workflow for differentially-private graph synthesis. In *Proceedings of the 2012 ACM workshop on Workshop on online social networks*, pp. 13–18, 2012.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International conference on machine learning*, pp. 1278–1286. PMLR, 2014.

Alessandra Sala, Xiaohan Zhao, Christo Wilson, Haitao Zheng, and Ben Y Zhao. Sharing graphs using differentially private graph models. In *Proceedings of the 2011 ACM SIGCOMM conference on Internet measurement conference*, pp. 81–98, 2011.

Isabelle Stanton and Ali Pinar. Constructing and sampling graphs with a prescribed joint degree distribution. *Journal of Experimental Algorithmics (JEA)*, 17:3–1, 2012.

Allan Tucker, Zhenchen Wang, Ylenia Rotalinti, and Puja Myles. Generating high-fidelity synthetic patient data for assessing machine learning healthcare software. *NPJ digital medicine*, 3(1):1–13, 2020.

Stefan Webb, Adam Golinski, Rob Zinkov, Tom Rainforth, Yee Whye Teh, Frank Wood, et al. Faithful inversion of generative models for effective amortized inference. *Advances in Neural Information Processing Systems*, 31, 2018.

Douglas Brent West et al. *Introduction to graph theory*, volume 2. Prentice hall Upper Saddle River, 2001.

Liyang Xie, Kaixiang Lin, Shu Wang, Fei Wang, and Jiayu Zhou. Differentially private generative adversarial network. *arXiv preprint arXiv:1802.06739*, 2018.

Kai Xu, Rajkarn Singh, Marco Fiore, Mahesh K. Marina, Hakan Bilen, Muhammad Usama, Howard Benn, and Cezary Ziemlicki. Spectragan: Spectrum based generation of city scale spatiotemporal mobile network traffic data. In *Proceedings of the 17th International Conference on Emerging Networking EXperiments and Technologies*, CoNEXT '21, pp. 243–258, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450390989. doi: 10.1145/3485983.3494844. URL https://doi.org/10.1145/3485983.3494844.

Lei Xu and Kalyan Veeramachaneni. Synthesizing tabular data using generative adversarial networks. *arXiv preprint arXiv:1811.11264*, 2018.

Lei Xu, Maria Skoularidou, Alfredo Cuesta-Infante, and Kalyan Veeramachaneni. Modeling tabular data using conditional GAN. *Advances in Neural Information Processing Systems*, 32, 2019.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. *Advances in neural information processing systems*, 30, 2017.

Jun Zhang, Graham Cormode, Cecilia M Procopiuc, Divesh Srivastava, and Xiaokui Xiao. Privbayes: Private data release via bayesian networks. *ACM Transactions on Database Systems (TODS)*, 42 (4):1–41, 2017.

Alexander Ziller, Dmitrii Usynin, Rickmer Braren, Marcus Makowski, Daniel Rueckert, and Georgios Kaissis. Medical imaging deep learning with differential privacy. *Scientific Reports*, 11(1):1–8, 2021.

A Bipartite $2K$-generators

The complete algorithm of the bipartite $2K$-generators from Boroojeni et al. (2017) with corrections is given in algorithm 1. The algorithm consists two parts. The first part (Line 4 to Line 18) is called random pairing. It works by first creating stubs for each node based on its degree; the stubs for a node with index i and degree d is a list $[\underbrace{i, \ldots, i}_{d}]$. After stubs for all nodes are created, they are randomly paired based on the joint degree distribution/counts. This is simply done by enumerating the joint degree count: At each iteration for a pair of degree d_1, d_2, we randomly sample d_1 stubs with degree d_1 and d_2 stubs with degree d_2 and pair them accordingly. This step ensures the joint degree distribution matches while with *potential repeated edges*. The second part (Line 20 to Line 52) resolves repeated edges while preserving the joint degree counts. Boroojeni et al. (2017) shows

that there are only two cases how such repeated edges could appear and how to resolve each of them accordingly with the joint degree counts unchanged. Note that the algorithm presented in Boroojeni et al. (2017) contains several mistakes even though their proof is correct; algorithm 1 is based on our own realization of situations in the proof but essentially the same algorithm.

B   DETAILED EXPLANATION OF METRICS USED IN SECTION 5

In section 5 we used a set of metrics that are not commonly used for evaluation. To repeat, the two reasons we prefer these metrics are (i) they are bounded between 0 and 1 and (ii) they are easy to compute once the data is discretized, e.g. not requirement for training a classifier for density ratio estimation in computing f-divergences. We now provide a more formal description of these metrics.

B.1   DEGREE SIMILARITY

Let $\mathbf{p}, \mathbf{q}$ be the probability vectors representing the $1K$-distribution (with the same support) of the real and synthetic graphs. The *marginal degree similarity* is defined as

$$1 - \frac{1}{2}\mathrm{TV}(\mathbf{p}, \mathbf{q}) = 1 - \frac{1}{2}\sum_i |p_i - q_i|$$

where TV is the total variation distance and p_i, q_i are the i-th element of $\mathbf{p}, \mathbf{q}$.

Let $\mathbf{P}, \mathbf{Q}$ be the probability matrices representing the corresponding $2K$-distribution (with the same support). Similarly, the *joint degree similarity* is defined as

$$1 - \frac{1}{2}\mathrm{TV}(\mathbf{P}, \mathbf{Q}) = 1 - \frac{1}{2}\sum_{i,j} |P_{ij} - Q_{ij}|$$

where P_{ij}, Q_{ij} are the i-th row, j-th column entry of $\mathbf{P}, \mathbf{Q}$.

As $\mathrm{TV}(\cdot, \cdot) \in [0, 2]$, it can be easily shown that the two above degree similarity metrics are bounded by 0 and 1 with 1 being the maximal and best value.

B.2   MUTUAL INFORMATION SIMILARITY

Let $\mathbf{X}, \mathbf{Y}$ be two datasets with the same number of discrete columns/features (m). For each dataset, we compute the normalized mutual information between each pair of columns, giving the pairwise MI matrix.

The normalized mutual information between two random variables X, Y is defined as

$$\mathrm{nMI}(X, Y) := \frac{\mathrm{MI}(X, Y)}{\min\{\mathrm{H}(X), \mathrm{H}(Y)\}} = \frac{\mathrm{H}(X) + \mathrm{H}(Y) - \mathrm{H}(X, Y)}{\min\{\mathrm{H}(X), \mathrm{H}(Y)\}}$$

where MI refers to the mutual information and H refers to the Shannon entropy. This quantity is bounded by 0 and 1 due to (i) the positivity of entropy and (ii) the inequality below

$$\begin{aligned}
\mathrm{H}(X, Y) &\geq \max\{\mathrm{H}(X), \mathrm{H}(Y)\} & \text{property of joint entropy} \\
-\mathrm{H}(X, Y) &\leq \min\{-\mathrm{H}(X), -\mathrm{H}(Y)\} & \text{multiply by } -1 \\
\mathrm{H}(X) + \mathrm{H}(Y) - \mathrm{H}(X, Y) &\leq \mathrm{H}(X) + \mathrm{H}(Y) + \min\{-\mathrm{H}(X), -\mathrm{H}(Y)\} & \text{add marginal entropies} \\
\mathrm{MI}(X, Y) &\leq \min\{\mathrm{H}(X), \mathrm{H}(Y)\} & \text{simplification}
\end{aligned}$$

Then the pairwise MI matrix, e.g. $\mathbf{M}$ for $\mathbf{X}$ can be defined by its i-th row, j-th column entries M_{ij}

$$M_{ij} := \mathrm{nMI}(X_i, X_j)$$

where X_i, X_j are the random variables for the i-th and j-th columns of the dataset $\mathbf{X}$. As the dataset is assumed to be given in discrete, the entropy of each column and the joint entropy of a pair of columns can be easily estimated by first estimating the empirical probabilities followed by the definition of Shannon entropy.

Let $\mathbf{M}, \mathbf{N}$ be the pairwise MI matrices for $\mathbf{X}, \mathbf{Y}$ respectively, the MI similarity is then defined as

$$\frac{1}{m^2} \sum_{i,j} \mathrm{J}(M_{ij}, N_{ij})$$

where M_{ij}, N_{ij} the i-th row, j-th column entries accordingly and J is the Jaccard index defined as

$$\mathrm{J}(A, B) = \frac{\min\{A, B\}}{\max\{A, B\}}.$$

It is easy to see this metric is bounded by 0 and 1 with 1 being the maximal and best value.

Cross-table MI similarity   To compute the cross-table MI similarity score, for a pair of real tables X_1, X_2 and synthetic tables Y_1, Y_2, we first join (join as in relational algebra or databases) the two table pairs (X_1, X_2 and Y_1, Y_2) into X and Y by the graph/links between them. Then, we simply follow the MI similarity described above to compute the score.

C   REPRODUCIBILITY

C.1   CODE

We provide the source code for the key uncommon components in the experiments for inspection, namely the $2K$ generator and metrics for evaluation. Unfortunately, as we used proprietary implementation of single table models (Bayesian networks and autoregressive models) that would reveal our identity, we cannot provide source code dependent on them. However, we describe as much details as possible in the next section such that one can reproduce them using other implementation of single table models. We will also make them publicly available upon publication.

C.2   EXPERIMENT DETAILS

In this section we provide some experimental details that are missing in section 5.

Bayesian networks   For BNs, we set the number of parents to be 2. The network building algorithm follows (Zhang et al., 2017) exactly.

Neural autoregressive models   For NeuralARs, the architecture for each classifier is as follows:[8]

1. Each discrete variable is passed to an embedding layer with an embedding size of 20, after which all embeddings are concatenated, giving a input embedding of size d_{e}
2. *(Optional)* When the deep sets architecture is used, each node is passed to a linear layer with output size 10 (i.e. node embedding size), then summed (i.e. summation as the aggregation function) and passed to a linear layer with output size 50 (i.e. set embedding size). We also overload the notation d_{e} by this set embedding size if this step is performed.
3. The input embedding is passed to a multi-layer perceptron of $d_{\mathrm{e}} \xrightarrow{\text{ReLU}} 50 \xrightarrow{\text{ReLU}} 50 \xrightarrow{\text{Softmax}} d_{\mathrm{o}}$ where ReLU refers to the rectified linear unit activation function, Softmax refers to the he softmax function and d_{o} is the output dimension, equal to the number of unique values of the output features.

Data is split by 80/20 into training and validation sets. All training is done using the ADAM optimizer (Kingma & Ba, 2014) for maximally $1,000$ steps with a learning rate of 1×10^{-3} and a batch size of 500. We also use a learning rate scheduler with the sine function with exponential amplitude decay with a minimal learning rate of 2×10^{-4} and a 5-epoch periodicity.[9] Finally, early training is used based on the loss computed on the validation set: if there is no loss drop for 5 epochs, the training is early stopped.

---

[8] All neural networks are implemented using Flux.jl (`https://github.com/FluxML/Flux.jl`.)

[9] This is done using the `SinExp` from `https://github.com/darsnack/ParameterSchedulers.jl`.

node2vec   We use the Julia implementation of node2vec.[10] We keep all default parameters except setting the number of walks to be 10, the walk length to be 100, $p = q = 2$ and an embedding size of 20.

Privacy accountant   We apply a simple-minded way to spread the privacy budget. First, the privacy budget is evenly split among three sub-models. Second, within each sub-model, the budget is further evenly split to each component. For BNs, it means the network building and counting. For NeuralARs, we simply record the number of iterations used for training per classifier in the non-private version and evenly spread the privacy across all iterations. Note this (assuming the number of iterations per classifier is known) is for evaluation purpose only and by no means this strategy is an optimal way to spend the privacy budgets.

C.3   TOTAL COMPUTATION RESOURCES

All experiments are conducted on an Amazon EC2 instance of type `c5.4xlarge` with CPUs only.

---

[10]The code is available at `https://github.com/ollin18/Node2Vec.jl`.

Algorithm 1 Bipartite $2K$-generator (Boroojeni et al., 2017, corrected version)

1: **Input**: BJD $\mathbf{J}$ with supports $\mathbf{d}_u, \mathbf{d}_v$
2: **Output**: Edges $\mathbb{L}$
3: Initialise $\mathbb{L} = \emptyset$ $\triangleright$ Initialise edges as empty set
4: *# Part 1: random pairing*
5: $\mathbf{s}_u \leftarrow [], \mathbf{s}_v \leftarrow []$ $\triangleright$ Initialise stubs as empty lists
6: Compute degree sequences $\mathbf{u}, \mathbf{v}$ from $\mathbf{J}$
7: **for** $i_u \in 1, \ldots, |\mathbf{u}|, k \in 1, \ldots, \mathbf{u}[i_u]$ **do**
8:      Append i_u to $\mathbf{s}_u$
9: **end for**
10: **for** $i_v \in 1, \ldots, |\mathbf{v}|, k \in 1, \ldots, \mathbf{v}[i_v]$ **do**
11:      Append i_v to $\mathbf{s}_v$
12: **end for**
13: **for** $i \in 1, \ldots, |\mathbf{d}_u|, j \in 1, \ldots, |\mathbf{d}_v|$ **do**
14:      $k \leftarrow \mathbf{J}[i, j]$
15:      Randomly pop k node indices $\{i_u^l\}_{l=1}^k$ from $\mathbf{s}_u$ s.t. the corresponding nodes $n(i_u^l)$ has degree $\mathbf{d}_u[i]$
16:      Randomly pop k node indices $\{i_v^l\}_{l=1}^k$ from $\mathbf{s}_v$ s.t. the corresponding nodes $n(i_v^l)$ has degree $\mathbf{d}_v[j]$
17:      Add edges $\{(i_u^l, i_v^l)\}_{l=1}^k$ to $\mathbb{L}$
18: **end for**
19: *# Part 2: rewiring process (corrected version)*
20: $\mathbb{L}_r \leftarrow$ repeated edges in $\mathbb{L}$ $\triangleright$ Repeated edges to resolve
21: **while** $\mathbb{L}_r$ is not empty **do**
22:      Randomly pop edge (i_u, i_v) from $\mathbb{L}_r$
23:      $n_u \leftarrow \mathrm{n}(i_u), n_v \leftarrow \mathrm{n}(i_v), n_u' \leftarrow n_u, n_v' \leftarrow n_v$
24:      $\mathbb{U}' \leftarrow \{n_u : \deg(n_u) = \deg(n_u)\} \setminus \{n_u\}$
25:      $\mathbb{V}' \leftarrow \{n_v : \deg(n_v) = \deg(n_u)\} \setminus \{n_u\}$
26:      **if** $|\mathbb{U}'| = 0$ **then**
27:          $n_v' \leftarrow$ uniform sample from $\{n_v' \in \mathbb{V}' \setminus \mathrm{ne}(n_u') : \mathrm{ne}(n_v') \setminus \mathrm{ne}(n_v) \neq \emptyset\}$
28:      **else if** $|\mathbb{V}'| = 0$ **then**
29:          $n_u' \leftarrow$ uniform sample from $\{n_u' \in \mathbb{U}' \setminus \mathrm{ne}(n_v') : \mathrm{ne}(n_u') \setminus \mathrm{ne}(n_u) \neq \emptyset\}$
30:      **else if** $\mathbb{L}_n' := \{(n_u', n_v') \in \mathbb{V}' \times \mathbb{U}' : \mathrm{ne}(n_v')) \setminus \mathrm{ne}(n_v) \neq \emptyset \text{ and } \mathrm{ne}(n_u') \setminus \mathrm{ne}(n_u) \neq \emptyset\} \neq \emptyset$
     then
31:          $(n_u', n_v') \leftarrow$ uniform sample from $\mathbb{L}_n'$
32:      **else if** $\mathbb{V}'' := \{n_v' \in \mathbb{V}' \setminus \mathrm{ne}(n_u')\} \neq \emptyset$ **then**
33:          $n_v' \leftarrow$ uniform sample from $\mathbb{V}''$
34:      **else** $\triangleright$ Boroojeni et al. (2017) proves that in this branch the set to draw samples is non-empty.
35:          $n_u' \leftarrow$ uniform sample from $\{n_u' \in \mathbb{U}' \setminus \mathrm{ne}(n_v')\}$
36:      **end if**
37:      **if** $n_u' = n_u$ **then** $\triangleright$ Case 2
38:          $n_w' \leftarrow$ uniform sample from $\mathrm{ne}(n_v') \setminus \mathrm{ne}(n_v)$
39:          Remove edge $(\mathrm{i}(n_w'), \mathrm{i}(n_v'))$ from $\mathbb{L}$
40:          Add edges $\{(\mathrm{i}(n_u), \mathrm{i}(n_v')), (\mathrm{i}(n_w'), \mathrm{i}(n_v'))\}$ to $\mathbb{L}$
41:      **else if** $n_v' = n_v$ **then** $\triangleright$ Case 2
42:          $n_w \leftarrow$ uniform sample from $\mathrm{ne}(n_u') \setminus \mathrm{ne}(n_u)$
43:          Remove edge $(\mathrm{i}(n_u'), \mathrm{i}(n_w))$ from $\mathbb{L}$
44:          Add edges $\{(\mathrm{i}(n_u'), \mathrm{i}(n_v)), (\mathrm{i}(n_u), \mathrm{i}(n_w))\}$ to $\mathbb{L}$
45:      **else** $\triangleright$ Case 1
46:          $n_w \leftarrow$ uniform sample from $\mathrm{ne}(n_u') \setminus \mathrm{ne}(n_u)$
47:          $n_w' \leftarrow$ uniform sample from $\mathrm{ne}(n_v') \setminus \mathrm{ne}(n_v)$
48:          Remove edges $\{(\mathrm{i}(n_u'), \mathrm{i}(n_w)), (\mathrm{i}(n_w'), \mathrm{i}(n_v'))\}$ from $\mathbb{L}$
49:          Add edges $\{(\mathrm{i}(n_u), \mathrm{i}(n_w)), (\mathrm{i}(n_w'), \mathrm{i}(n_v)), (\mathrm{i}(n_u'), \mathrm{i}(n_v'))\}$ to $\mathbb{L}$
50:      **end if**
51:      $\mathbb{L}_r \leftarrow$ repeated edges in $\mathbb{L}$
52: **end while**
53: **return** $\mathbb{L}$