Learning in Multi-Stage Decentralized Matching Markets

Abstract

Matching markets are often organized in a multi-stage and decentralized manner. Moreover, participants in real-world matching markets often have uncertain preferences. This article develops a framework for learning optimal strategies in such settings, based on a nonparametric statistical approach and variational analysis. We propose an efficient algorithm, built upon concepts of "lower uncertainty bound" and "calibrated decentralized matching," for maximizing the participants' expected payoff. We show that there exists a welfare-versus-fairness trade-off that is characterized by the uncertainty level of acceptance. Participants will strategically act in favor of a low uncertainty level to reduce competition and increase expected payoff. We prove that participants can be better off with multi-stage matching compared to single-stage matching. We demonstrate aspects of the theoretical predictions through simulations and an experiment using real data from college admissions.

1 Introduction

Two-sided matching markets have played an important role in microeconomics for several decades [27]. Matching markets are used to allocate indivisible "goods" to multiple decision-making agents based on mutual compatibility as assessed via sets of preferences. Such a market does not clear through prices. For example, a student applicant cannot simply demand the college she prefers but must also be chosen by the college. Matching markets are often organized in a decentralized way. Each agent makes their decision independently of others' decisions, and each agent can have multiple stages of interactions with the other side of the market. College admissions with waiting lists and academic job markets are notable examples. We refer to such markets as *multi-stage decentralized matching markets*.

Uncertain preference is ubiquitous in multi-stage decentralized matching markets. For instance, colleges competing for students lack information on students' preferences. An admitted student may receive offers from other colleges. She needs to accept one or reject all offers within a short period during each stage of early, regular, and waiting-list admissions [4]. This admission process provides little opportunity for colleges to learn students' preferences, which are uncertain due to competition among colleges and variability in the relative popularity of colleges over time. Such uncertain preferences pose a challenge for colleges in their attempt to formulate an optimal admission strategy. Consequently, colleges may end up enrolling too many or too few students relative to their capacity or having enrolled students overly far from the attainable optimum in quality.

This paper addresses the following two research questions: (i) Given the uncertain preferences on one side of the market (e.g., students), how can agents (e.g., colleges) learn an optimal strategy that maximizes expected payoffs based on historical data? (ii) What are the fundamental implications of multi-stage decentralized matching on the welfare and fairness for both sides of the market? We study these two questions using *nonparametric statistical methodology* and *variational analysis*.

We propose a new algorithm for maximizing agents' expected payoffs that is based on learning stage-wise optimal strategies and calibrating state parameters based on historical data. In particular, our algorithm balances the opportunity cost and the penalty for exceeding the quota for calibration. Based on the calibrated state, the algorithm efficiently learns an optimal strategy using statistical machine learning methods. The statistical model not only provides a foundation for the algorithm but it also provides an analytical framework for understanding the implications of the approach for welfare and fairness. We show that agents will favor arms with realistic and stable opportunities for matching instead of only targeting the top-ranked arms. Moreover, we show that agents are better off with multi-stage decentralized matching as compared to single-stage decentralized matching.

Adopting literature from the bandit literature, our model has a set of *agents*, each with limited capacity, and a set of *arms*. Each agent values two attributes of an arm: a "score" that is common to all agents and a "fit" that is agent-specific and independent across agents. Agents rank arms according to their scores and fits. An agent's strategy consists of how many and which arms to pull at each stage. On the other hand, there is no restriction on the preferences of arms. The model allows uncertainty in the preferences, which is incorporated into the arms' stage-wise acceptance probabilities. The acceptance probability depends on the unknown state of the world and the competition of agents at each stage. We consider a simple timeline for multi-stage markets. At each stage, agents simultaneously pull sets of arms. Each arm accepts at most one of the agents that pulled it. The arms have to make irreversible decisions at each stage without knowing which other agents might select them in later stages.

Our contributions   There are two main contributions in this paper, which correspond to the two questions above. Our first contribution is to propose a new algorithm that maximizes the agent's expected payoff in multi-stage decentralized matching markets. The algorithm sequentially learns the optimal strategy at each stage and is built upon notions of *lower uncertainty bound* (LUB) and *calibrated decentralized matching* (CDM). The key idea is to calibrate the state parameter in a data-driven approach and take the opportunity cost and penalty for exceeding the quota into account. The calibration can be performed under both average-case and worst-case metrics, depending on whether we are maximizing the averaged or minimal expected payoff with respect to the uncertain state. Given the calibrated state, the algorithm efficiently learns the optimal strategy using historical data via statistical machine learning methods.

The second contribution is providing an analytical framework for understanding the welfare and fairness implications. We show that agents favor arms with low uncertainty in levels of acceptance, suggesting that agents prefer arms with a realistic and stable chance for matching instead of only targeting the top-ranked arms. Such strategic behavior improves the agent's expected payoff since otherwise, by the time that arms have rejected that agent, the next-best arms that the agent has in mind may already have accepted other agents. However, the strategic behavior leads to unfair outcomes for arms because some arms are not pulled by their favorite agents even though these agents pull arms ranked below them. We prove that agents are better off in multi-stage decentralized matching markets compared to single-stage decentralized matching markets.

Other related work   This paper is related to two strands of literature. The first line of work is on the decentralized interactions in matching markets [13–15, 23, 28] and search literature [22, 24]. Our paper contributes to this line of work via its analysis of multi-stage markets that allow uncertain preferences. Moreover, we develop a statistical model to learn the optimal strategy using historical data and we analyze the implications for strategic behavior in multi-stage decentralized markets.

The second related body of literature is on algorithmic studies of college admissions. The celebrated work in [18] introduced the deferred acceptance algorithm implemented under central clearinghouses. Recent works have been focused on equilibrium admissions and students' efforts [6, 9–11, 16, 17, 19]. By contrast, we emphasize students' multidimensional abilities and consider multiple colleges that compete for students. Moreover, we develop a statistical model for learning the optimal strategies using historical data.

2   Problem formulation

Multi-stage decentralized matching markets   Let $\mathcal{P} = \{P_1, P_2, \ldots, P_m\}$ be a set of m agents. Let $\mathcal{A} = \{A_1, A_2, \ldots, A_n\}$ the a set of n arms. Here $\mathcal{P}$ and $\mathcal{A}$ are the sets of participants on the two sides of the matching market. Each agent P_i has a quota $q_i \geq 1$. We assume that $q_1 + q_2 + \cdots + q_m \leq n$.

There are total of $K \geq 1$ stages of the matching process. At each stage, an agent who has not used up its quota can pull available arms in the market. When multiple agents select the same arm, only one agent can successfully pull the arm according to the arm's preference. We denote $[m] \equiv \{1, \ldots, m\}, [n] \equiv \{1, \ldots, n\}$, and $[K] \equiv \{1, \ldots, K\}$. Decentralized matching markets require participants to make their decisions independently of others' decisions [26, 28]. Notable examples of such markets include college admissions in the United States, Korea, and Japan, where $\mathcal{P}$ and $\mathcal{A}$ represent the sets of colleges and students, respectively [4, 5]. Our goal is to learn the agent's optimal strategy for maximizing the expected payoff. A strategy consists of deciding how many and which arms to pull at each stage. Agent's decision-making in decentralized markets faces incomplete information about other agents' decisions and arms' preferences.

Participants' preferences The agents' preferences are based on the arms' latent utilities. Consider the following latent utility model:

$$U_i(A_j) = v_j + e_{ij}, \quad \forall i \in [m], j \in [n], \tag{1}$$

where $v_j \in [0, 1]$ is arm A_j's *systematic score* considered by all agents, and $e_{ij} \in [0, 1]$ is an agent-specific *idiosyncratic fit* considered only by agent P_i, $i \in [m]$. A utility model with a similar separable structure has been widely used in the matching market literature [3, 11, 13].

The arms' preferences have no restrictions and can involve uncertainty. From an agent's perspective, arms accept offers with probabilities dependent on opponents' strategies and arms' preferences. Let the parameter $s_{i,k} \in [0, 1]$ be the *state of the world* [29] for agent P_i, such that the probability that an arm A_j accepts P_i at stage k is $\pi_{i,k}(s_{i,k}, v_j), \forall i \in [m], j \in [n], k \in [K]$. Since agents compete for arms with a higher score, the acceptance probability $\pi_{i,k}(s_{i,k}, v_j)$ models the agents' competition through the dependence on the score v_j. Moreover, $\pi_{i,k}(s_{i,k}, v_j)$ incorporates the arm's uncertain preference into the state $s_{i,k}$. It is known that there exists a valid probability mass function $\pi_{i,k}(s_{i,k}, v_j)$ [13]. We assume that $\pi_{i,k}(s_{i,k}, v_j)$ is strictly increasing and continuous in $s_{i,k}$. Thus, a larger value of the state $s_{i,k}$ corresponds to the case that agent P_i is more popular. In practice, the true state is unknown a priori to P_i and needs to be estimated from data. For instance, the *yield* in college admissions is defined as the rate at which a college's admitted students accept the offers. However, the yield is unknown a priori to the college in the current year [11]. Colleges can only estimate the distribution of the yield from historical data. In this paper, we study a nonparametric model of $\pi_{i,k}(\cdot, \cdot)$ by assuming it belongs to a reproducing kernel Hilbert space (RKHS) [2, 31]. Later, in Section 3.2, we propose an algorithm for calibrating $s_{i,k}$ and efficiently estimating $\pi_{i,k}(\cdot, \cdot)$ using historical data. Given the latent utility $U_i(A_j)$ and the acceptance probability $\pi_{i,k}(s_{i,k}, v_j)$, agent P_i's expected utility of pulling arm A_j at stage k is $(v_j + e_{ij})\pi_{i,k}(s_{i,k}, v_j)$.

Timeline of the matching First, Nature draws a state such that arms' preferences are realized. Denote by $s_{i,k}^*$ the true state for agent P_i at stage k. Next, arms display their interests to all agents. For example, students apply to colleges in a given period. Under the assumption that students incur negligible application costs, submitting applications to all colleges is the dominant strategy as students lack information on how colleges evaluate their academic ability or personal essays [5, 11]. Next, at each stage $k \in [K]$, agents simultaneously pull available arms that have not previously rejected them. Each arm either accepts one of the agents that pulled it (if any) or rejects all. An arm exits the market once it accepts an agent, and agents are allowed to exit the market at any time. The arms act simultaneously at each stage. They cannot "hold" offers for accepting or rejecting at a later stage. Hence, agents make "exploding" offers, and arms have to make irreversible decisions without knowing what other offers are coming in later stages. Finally, this multi-stage matching process ends when all agents have exited or when a pre-specified number of stages has been reached. If there remain arms in the market when the matching has terminated, these arms are unmatched.

Agent's expected payoff An agent's goal is to maximize the expected payoff, which consists of two parts: the expected utilities and the penalty for exceeding the quota. Let $\mathcal{A}_k$ be the set of arms that are available in the market at stage $k \in [K]$. Suppose that agent P_i pulls arms from the set $\mathcal{B}_{i,k} \subseteq \{\mathcal{A}_k \setminus \cup_{l \leq k-1} \mathcal{B}_{i,l}\}$ at stage k, where $\mathcal{A} \setminus \mathcal{B}$ denotes that set $\mathcal{A}$ minus set $\mathcal{B}$. Let $\mathcal{C}_{i,k} \subseteq \mathcal{B}_{i,k}$ be the set of arms that accept P_i at stage k. Then $\mathcal{C}_{i,k}$ is unknown until stage $k+1$, where $k \leq K-1$, and $\mathcal{C}_{i,K}$ is unknown until the end of the matching process. Then P_i's expected payoff at stage $k \in [K]$ is lower bounded by

$$\mathcal{U}_{i,k}[\mathcal{B}_{i,k}] \equiv \sum_{j \in \mathcal{B}_{i,k}} (v_j + e_{ij})\, \pi_{i,k}(s_{i,k}^*, v_j) - \gamma_i \max\{\mathcal{N}_{i,k}(\mathcal{B}_{i,k}) - q_i, \, 0\}. \tag{2}$$

142 Here $\mathcal{N}_{i,k}(\mathcal{B}_{i,k}) \equiv \sum_{j \in \mathcal{B}_{i,k}} \pi_{i,k}(s^*_{i,k}, v_j) + \text{card}(\cup_{l \leq k-1} \mathcal{C}_{i,l})$ with $\text{card}(\cdot)$ denoting the set size. We
143 assume that the marginal penalty γ_i satisfies $\gamma_i > \max_{j \in \mathcal{A}}\{v_j + e_{ij}\}$, which implies that the penalty
144 is greater than arm's latent utility. Since our model involves unknown strategies of the opponents and
145 uncertain arms' preferences, we consider the optimal expected payoff in (2) instead of the optimal
146 realized payoff. Similar expected payoffs of single-stage matching have been studied in [11, 13].

3 Learning the optimal strategy

148 We consider a variational formulation of the optimal strategy in Section 3.1 and propose a two-step
149 algorithm using a statistical machine learning method in Section 3.2.

3.1 A variational formulation

151 The problem of finding the optimal set of arms, and the corresponding optimal value $\bar{\mathcal{U}}_i$, can be
152 described as follows:

$$\bar{\mathcal{U}}_i = \max_{\mathcal{B}_{i,k} \subseteq \{\mathcal{A}_k \setminus \cup_{l \leq k-1} \mathcal{B}_{i,l}\}, k \in [K]} \sum_{k \in [K]} \mathcal{U}_{i,k}[\mathcal{B}_{i,k}], \tag{3}$$

153 where the expected payoff $\mathcal{U}_{i,k}$ is defined in (2). Finding and checking an optimal solution to (3) is
154 difficult. Suppose that an arm set $\cup_{k \in [K]} \bar{\mathcal{B}}_{i,k}$ is given and that it is claimed to be the optimal solution
155 to (3). It is clear that the problem of verifying that $\cup_{k \in [K]} \bar{\mathcal{B}}_{i,k}$ is optimal is NP-complete [21];
156 because we need to individually check a significant fraction of the combinations of $\text{card}(\cup_{k \in [K]} \mathcal{A}_k)$
157 arms to determine which combination might give a larger expected payoff than the given arm set
158 $\cup_{k \in [K]} \bar{\mathcal{B}}_{i,k}$. Since the number of combinations grows exponentially with the number of arms, the
159 complexity of any systematic algorithm becomes impractically large. Moreover, the expected payoff
160 $\mathcal{U}_{i,k}$ depends on the unknown true state $s^*_{i,k}$.

161 **Variational problem** We introduce the following notation: $\delta_{i,k}(v) \equiv \frac{1}{2}[\max_{s_{i,k}} \pi_{i,k}(s_{i,k}, v) - \min_{s_{i,k}} \pi_{i,k}(s_{i,k}, v)]$, which measures the uncertainty of the acceptance probability with respect to
163 the unknown state. Using this notation, we show that a variational formulation gives a practical
164 methodology for finding the optimal strategy.

165 **Theorem 1.** *There exist parameters $\eta_{i,k} > 0$, for $k \leq K - 1$, and $\eta_{i,K} = 0$ such that with high*
166 *probability, the minimizer of the following variational loss, $\forall k \in [K]$,*

$$\mathcal{L}^{\dagger}_{i,k}[\mathcal{B}_{i,k}] = \sum_{j \in \mathcal{B}_{i,k}} (v_j + e_{ij})[\eta_{i,k}\delta_{i,k}(v_j) - \pi_{i,k}(s^*_{i,k}, v_j)] + \gamma_i \max\{\mathcal{N}_{i,k}(\mathcal{B}_{i,k}) - q_i, 0\}, \tag{4}$$

167 *gives a maximizer of the total expected payoff $\sum_{k=1}^{K} \mathcal{U}_{i,k}[\mathcal{B}_{i,k}]$. Here the expected payoff $\mathcal{U}_{i,k}[\mathcal{B}_{i,k}]$*
168 *is given in (2), and $\mathcal{B}_{i,k} \subseteq \{\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l}\}$ for any $k \in [K]$.*

169 We make two remarks regarding this theorem. First, the parameter $\eta_{i,k} \geq 0$ in (4) is induced by the
170 *hierarchical structure* in the sense that the arms available at subsequent stages are worse than the
171 current ones; see Appendix S2.1. Hence, each agent prefers arms with a stable acceptance probability,
172 and for which $\eta_{i,k}$ controls the penalty on the uncertainty. Second, there exists a main difference
173 between the multi-stage decentralized matching problem and the multi-armed bandit problem [8]. A
174 bandit problem is a sequential allocation problem in which an environment repeatedly provides an
175 agent with a fixed set of arms. Although similar in that it involves sequential decision making under
176 limited information, the multi-stage matching market involves multiple agents competing for arms.
177 An arm exits the market once it accepts an offer. The competition induces a hierarchical structure
178 which makes the optimization in (4) different from the optimization in multi-armed bandits.

179 **Greedy strategy** Although the variational problem in (4) requires only stage-wise optimization and
180 can be solved sequentially for each $k \in [K]$, the finding and checking of an optimal solution is still
181 NP-complete. This is because we need to individually check a significant fraction of the combinations
182 of $\text{card}(\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l})$ arms at each stage $k \in [K]$ to determine the optimal solution for (4). The
183 number of combinations grows exponentially with $\text{card}(\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l})$ for $k \in [K]$.

We propose a greedy algorithm that gives an approximate solution to the optimization problem in (4). Suppose the true state is fixed at $s_{i,k}^* = s_{i,k}$. We refer to $(v_j + e_{ij})[\pi_{i,k}(s_{i,k}, v_j) - \eta_{i,k}\delta_{i,k}(v_j)]$ as arm A_j's *variational expected utility*. For each $A_j \in \{\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l}\}$, the greedy algorithm computes the variational expected utility per unit of acceptance probability, that is,

$$r(A_j) \equiv (v_j + e_{ij})[\pi_{i,k}(s_{i,k}, v_j) - \eta_{i,k}\delta_{i,k}(v_j)]/\pi_{i,k}(s_{i,k}, v_j).$$

Then the algorithm ranks arms according to its associated value of r so that $r_{(1)} \geq r_{(2)} \cdots \geq r_{(\text{card}(\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l}))}$. Starting with the first arm corresponding to $r_{(1)}$ and continuing in order, the algorithm selects the arm if its variational expected utility is larger than the expected penalty of exceeding the quota. This algorithm terminates when it arrives at a cutoff value of r. Then only arms whose associated r value are better than or equal to the cutoff are selected for agent P_i to pull at stage $k \in [K]$. We present the formalized cutoff $r = r_*$ in Appendix S2.2. Then using the greedy algorithm, agent P_i pulls arms from the following set,

$$\widehat{\mathcal{B}}_{i,k}(s_{i,k}) = \{j \mid A_j \in \{\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l}\} \text{ satisfying } r(A_j) \geq r_*\}. \tag{5}$$

Theorem 2. *Suppose the true state is fixed at $s_{i,k}^* = s_{i,k}$. The arm set $\widehat{\mathcal{B}}_{i,k}(s_{i,k})$ in (5) is near-optimal as its loss satisfies*

$$\min_{\mathcal{B}_{i,k} \subseteq \{\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l}\}} \mathcal{L}_i^\dagger[\mathcal{B}_{i,k}] \leq \mathcal{L}_i^\dagger[\widehat{\mathcal{B}}_{i,k}(s_{i,k})] \leq \min_{\mathcal{B}_{i,k} \subseteq \{\mathcal{A}_k \setminus \cup_{l \leq k-1}\mathcal{B}_{i,l}\}} \mathcal{L}_i^\dagger[\mathcal{B}_{i,k}] + UE^\dagger,$$

where the loss function $\mathcal{L}_i^\dagger$ is defined in (4). The quantity $UE^\dagger \geq 0$ and it equals 0 if there is a continuum of arms and $\pi_{i,k}(\cdot, v)$ is continuous in v.

3.2 A two-step learning algorithm

Since the true state and the acceptance probability are unknown a priori in practice, the greedy strategy in (5) is unknown a priori to the agent P_i. We propose a two-step algorithm to learning the greedy strategy by using historical data and statistical machine learning methods. The two-step algorithm is built upon the concepts of *lower uncertainty bound* (LUB) and *calibrated decentralized matching* (CDM) [13]. In the first step, we compute an estimated expected utility of each arm and its lower uncertainty bound. Many machine learning methods can be applied here for the modeling of historical data. In the second step, we calibrate the state parameter in a data-driven approach that takes the opportunity cost and penalty for exceeding the quota into account. Based on the calibrated state, an agent selects arms with the largest lower uncertainty bounds of the expected utility. The key idea is to select arms which have large expected utility or little uncertainty in the expected utility.

Step 1: Lower uncertainty bound Let $\mathcal{A}^t = \{A_1^t, A_2^t, \ldots, A_{n^t}^t\}$ be the arm set at $t \in [T] \equiv \{1, \ldots, T\}$. Let $s_{i,k}^t$ be the state of agent P_i at stage k and time t. The state $s_{i,k}^t$ is *unknown* until the next stage or the next time point, and the state $s_{i,k}^t$ varies over time. For instance, the yield rate of a college may change over the years. For any arm $A_j^t \in \mathcal{A}^t$, there are an associated pair of the score and fit values (v_j^t, e_{ij}^t) obtained from (1), where $i \in [m], j \in [n^t]$. Let (v_j^t, e_{ij}^t) denote the attributes of arm A_j^t. Define the set $\mathcal{B}_{i,k}^t = \{j \mid P_i \text{ pulls arm } A_j^t \text{ at time } t \text{ and step } k, 1 \leq j \leq n^t\}$, where $\text{card}(\mathcal{B}_{i,k}^t) = n_{i,k}^t \leq n^t$. For any $j \in \mathcal{B}_{i,k}^t$, the outcome that P_i observes is whether an arm A_j^t accepted P_i, that is, $y_{ij}^t = \mathbf{1}\{A_j^t \text{ accepts } P_i\}$. We want to estimate $\pi_{i,k}$ based on the historical data, $\mathcal{D} = \{(s_{i,k}^t, v_j^t, e_{ij}^t, y_{ij}^t) : i \in [m]; j \in \cup_{k=1}^K \mathcal{B}_{i,k}^t; t \in [T]\}$.

A wide range of machine learning methods, e.g., reproducing kernel methods, random forests, or neural networks, can be applied here to learn $\pi_{i,k}$ (cf. [20]). For concreteness, we consider a penalized estimator in RKHS. Let the log odds ratio $f_{i,k}(s_{i,k}, v) = \log\{\pi_{i,k}(s_{i,k}, v)/[1 - \pi_{i,k}(s_{i,k}, v)]\}$, which is assumed to reside in an RKHS $\mathcal{H}_{\mathcal{K}_{i,k}}$ with the kernel $\mathcal{K}_{i,k}$. Then we solve for $\widehat{f}_{i,k} \in \mathcal{H}_{\mathcal{K}_{i,k}}$ that minimizes the objective function:

$$\sum_{t=1}^T \frac{1}{n_{i,k}^t} \sum_{j \in \mathcal{B}_{i,k}^t} \left[-y_{ij}^t f_{i,k}(s_{i,k}^t, v_j^t) + \log\left(1 + \exp\left(f_{i,k}(s_{i,k}^t, v_j^t)\right)\right)\right] + \lambda_{i,k}\|f_{i,k}\|_{\mathcal{H}_{\mathcal{K}_{i,k}}}^2,$$

where $\lambda_{i,k} \geq 0$ is a tuning parameter. Consider the tensor product structure of $\mathcal{H}_{\mathcal{K}_{i,k}}$, where $\mathcal{K}_{i,k}((s_i, v), (s_i', v')) = \mathcal{K}_{i,k}^s(s_i, s_i')\mathcal{K}_{i,k}^v(v, v')$ with some kernel functions $\mathcal{K}_{i,k}^s$ and $\mathcal{K}_{i,k}^v$ [32]. It is

---

Algorithm 1 The two-step algorithm for multi-stage decentralized matching

---
1: **Inputs**: Historical data for an agent P_i: $\{(s_{i,k}^t, v_j^t, e_{ij}^t, y_{ij}^t) : j \in \mathcal{B}_{i,k}^t; t = 1, 2, \ldots, T\}$; New
   arm set $\mathcal{A}^{T+1}$ at time $T + 1$, where the arms have attributes $\{(v_j, e_{ij}) : j \in [n]\}$; Penalty γ_i for
   exceeding the quota. Regularization parameter $\eta_{i,k} \geq 0$.
2: **for** stage $k = 1, 2, \ldots, K$ **do**
3:     Construct the lower uncertainty bound $\widehat{\pi}_{i,k}^{\mathsf{L}}(s_{i,k}, v_j)$ by (6)
4:     Estimate the distribution $F_{s_{i,k}^*}(\cdot)$ by the kernel density method [30]
5:     Calibrate the state $s_{i,k}$ according to Theorem 3
6:     Determine the arm set $\widehat{\mathcal{B}}_{i,k}^{\mathsf{L}}(s_{i,k})$ in (8)
7:     Calculate the remaining quota: $q_i - \text{card}(\cup_{l \leq k-1} \mathcal{C}_{i,l})$ and the available arms
8: **end for**
9: **Outputs**: The arm set $\widehat{\mathcal{B}}_{i,k}^{\mathsf{L}}(s_{i,k})$ for agent P_i at each stages.

---

known that $\widehat{f}_{i,k}$ is minimax rate-optimal and satisfies $\mathbb{E}[(\widehat{f}_{i,k} - f_{i,k})^2] \leq c_f[T(\log T)^{-1}]^{-2r/(2r+1)}$
for any $i \in [m]$ (cf. [13]). Here, $c_f > 0$ is a constant independent of T, and $r \geq 1$ denotes the order
of smoothness. The value of learning from historical data is particularly significant when a new arm
is introduced into the problem. Let $\mathcal{A}^{T+1} = \{A_1, \ldots, A_n\}$ be the new arm set at time $T + 1$, where
A_j has attributes obtained from (1). Then the probability that A_j accepts P_i at stage k is estimated by
$\widehat{\pi}_{i,k}(s_{i,k}, v_j) = \{1 + \exp[-\widehat{f}_{i,k}(s_{i,k}, v_j)]\}^{-1}$. The expected utility of A_j is $\widehat{\pi}_{i,k}(s_{i,k}, v_j)(v_j + e_{ij})$
for any $j \in [n]$. Finally, we construct a lower uncertainty bound for $\pi_{i,k}(s_{i,k}, v_j)$ as,

$$\widehat{\pi}_{i,k}^{\mathsf{L}}(s_{i,k}, v_j) = \begin{cases} \widehat{\pi}_{i,k}(s_{i,k}, v_j) - \eta_{i,k}\widehat{\delta}_{i,k}(v_j), \\ \qquad \text{if } v_j \in [\min\{v_j^t \mid j \in \cup_{t=1}^T \mathcal{B}_i^t\}, \max\{v_j^t \mid j \in \cup_{t=1}^T \mathcal{B}_i^t\}]; \\ 1, \qquad \text{o.w.}, \end{cases} \tag{6}$$

where $\widehat{\delta}_{i,k}(v_j) = \frac{1}{2}[\max_{s_{i,k}} \widehat{\pi}_{i,k}(s_{i,k}, v_j) - \min_{s_{i,k}} \widehat{\pi}_{i,k}(s_{i,k}, v_j)]$. The parameter $\eta_{i,k} \geq 0$ is defined
in (4). Note that (6) assigns probability one to arms with scores that agent P_i has never pulled. Hence
it encourages the exploration of previously untried arms. A *lower uncertainty bound* for the expected
utility is then given by $\widehat{\pi}_{i,k}^{\mathsf{L}}(s_{i,k}, v_j)(v_j + e_{ij})$ for any $j \in [n]$.

Step 2: Calibrated decentralized matching   Since the true state $s_{i,k}^*$ is unknown in practice,
a natural question is how to calibrate the state parameter $s_{i,k}$ in (5). Consider the average-case
loss, $\mathbb{E}_{s_{i,k}^*}\{\mathcal{L}_{i,k}^{\dagger}[\widehat{\mathcal{B}}_{i,k}(s_{i,k})]\}$, where the loss $\mathcal{L}_{i,k}^{\dagger}$ is defined in (4). Define the *marginal set* as
$\partial\widehat{\mathcal{B}}_{i,k}(s_{i,k}) \equiv \lim_{\delta_s \to 0_+} \{\widehat{\mathcal{B}}_{i,k}(s_{i,k} - \delta_s) \setminus \widehat{\mathcal{B}}_{i,k}(s_{i,k})\}$. Hence $\partial\widehat{\mathcal{B}}_{i,k}(s_{i,k})$ represents the change of
$\widehat{\mathcal{B}}_{i,k}(s_{i,k})$ with a perturbation of $s_{i,k}$.

Theorem 3. *The average-case loss* $\mathbb{E}_{s_{i,k}^*}\{\mathcal{L}_{i,k}^{\dagger}[\widehat{\mathcal{B}}_{i,k}(s_{i,k})]\}$ *is minimized if* $s_{i,k} \in (0, 1)$ *is chosen as*
the solution to

$$\mathbb{P}(s_{i,k}^* \neq s_{i,k}) \sum_{j \in \partial\widehat{\mathcal{B}}_{i,k}(s_{i,k})} (v_j + e_{ij})\mathbb{E}_{s_{i,k}^*}\left[\pi_{i,k}(s_{i,k}^*, v_j) - \eta_{i,k}\delta_{i,k}(v_j) \mid s_{i,k}^* \neq s_{i,k}\right]$$
$$= \gamma_i[1 - F_{s_{i,k}^*}(s_{i,k})] \sum_{j \in \partial\widehat{\mathcal{B}}_{i,k}(s_{i,k})} \mathbb{E}_{s_{i,k}^*}[\pi_{i,k}(s_{i,k}^*, v_j) \mid s_{i,k} < s_{i,k}^* \leq 1], \tag{7}$$

where $F_{s_{i,k}^*}$ *is the cumulative distribution function of* $s_{i,k}^* \in [0, 1]$.

The key idea of (7) is to balance the trade-off between opportunity cost and penalty for exceeding
the quota. If (7) has more than one solution, then $s_{i,k}$ is chosen as the largest one. If the distribution
$F_{s_{i,k}^*}$ has discrete support, the objective in Theorem 3 needs to be changed as follows: choosing the
minimal $s_{i,k} \in [0, 1]$ such that the left side of (7) is not less than the right side of (7), where the
search of $s_{i,k}$ starts from the maximum value in the support and decreases to the minimal value. We
note that instead of the average-case loss in Theorem 3, we can also perform the calibration under the
worst-case loss, which is discussed in Appendix S2.3.

Summary of the two-step algorithm Using (6) and (7), we can obtain the cutoff estimate $\widehat{r}_*$ and calibrated state $s_{i,k}$, which suggests agent P_i to pull arms from the following set at stage k:

$$\widehat{\mathcal{B}}^{\mathsf{L}}_{i,k}(s_{i,k}) = \{j \mid A_j \in \{\mathcal{A}^{T+1}_k \setminus \cup_{l \leq k-1} \mathcal{B}_{i,l}\} \text{ satisfying } r(A_j) \geq \widehat{r}_*\}. \tag{8}$$

Here $\mathcal{A}^{T+1}_k$ is the set of arms that are available at stage k of time $T+1$. Due to the minimax optimality of $\widehat{f}_{i,k}$, we have the consistency result that $\widehat{\mathcal{B}}^{\mathsf{L}}_{i,k}(s_{i,k}) \rightarrow \widehat{\mathcal{B}}_{i,k}(s_{i,k})$ as $T \rightarrow \infty$, where the set $\widehat{\mathcal{B}}_{i,k}(s_{i,k})$ is defined in (5). We summarize the above two-step algorithm in Algorithm 1.

4 Strategic behavior and economic implications

Agents in a multi-stage decentralized matching markets cannot observe other agents' quotas or the choices of the arms that accept other agents. Each agent only observes the arms that are left in the market at each stage. Theorem 1 implies that agents prefer arms with stable acceptance probability. This preference lead to strategic behavior on the part of the agents as follows. Define the *uncertainty level* as the uncertainty measure $\delta_{i,k}(v)$ in Section 3.1 relative to the acceptance probability $\pi_{i,k}(s_{i,k}, v)$. That is,

$$\text{uncertainty level} \equiv \delta_{i,k}(v)/\pi_{i,k}(s_{i,k}, v). \tag{9}$$

We show in Appendix S2.2 that the cutoff r_* in (5) is strictly increasing in the uncertainty level for any $v \in [0, 1]$ and $k \leq K - 1$, which implies that an agent favors arms with a low uncertainty level. Hence, an agent's *strategic behavior* in this market is to strategically select arms with a low uncertainty level. We now study the implications of such strategic behavior on fairness and welfare.

No justified envy The fairness studied here is defined in terms of *no justified envy* [1, 7]. Specifically, an arm A_j has justified envy if, at a stage $k \in [K]$, A_j prefers an agent $P_{i'}$ to another agent P_i that pulls A_j, even though $P_{i'}$ pulls an arm $A_{j'}$ which ranks below A_j according to the true preference of $P_{i'}$. We define a multi-stage matching procedure to be fair if there is no arm having justified envy at any stage.

Proposition 1. *The probability that an arm has justified envy is strictly increasing in the arm's uncertainty level defined in (9).*

The fairness issue has been noted in practical multi-stage matching markets. For example, candidates in job markets may "fall through the cracks"—an employer that values a candidate highly perceives that the candidate is unlikely to accept the job offer and hence decides to conduct an interview with the candidate; hence, candidates may have justified envy [12].

Fairness vs. welfare trade-off We note that by Theorem 1, an agent has increased expected payoff under $\eta_{i,k} > 0$ than under $\eta_{i,k} = 0$ for all stages $k \leq K - 1$. Define the *level of unfairness* as the number of arms with justified envy.

Proposition 2. *The level of unfairness is strictly increasing in $\eta_{i,k} \geq 0$.*

This proposition implies a trade-off between welfare and fairness since both the level of unfairness and welfare increase when changing $\eta_{i,k} = 0$ to $\eta_{i,k} > 0$.

Comparison with single-stage matching markets Different from multi-stage matching markets, the optimal strategy in single-stage matching gives a fair outcome for arms [13]. However, we show that agents are better off in multi-stage markets compared to single-stage markets.

Proposition 3. *Agents have improved welfare under multi-stage decentralized matching than under single-stage decentralized matching.*

Comparison with centralized matching markets Many centralized matching markets are implemented by employing the celebrate deferred acceptance (DA) algorithm [18]; see examples in [1, 25]. In the arm-proposing version of DA (e.g., student-proposing in college admissions), agents and arms report their ordinal preferences to a clearinghouse, which simulates the following multi-stage procedure. Every arm shows its interest to the most preferred agent that has not yet rejected it at each stage. Every agent tentatively pulls the most preferred arms up to its quota limit and permanently

rejects the remaining arms that have indicated their interest to the agent. Once the process terminates, each arm is assigned to the agent that has tentatively pulled it or otherwise remains unmatched. The multi-stage decentralized matching is different from DA in practice, mainly due to the acceptance is not tentative (i.e., non-deferrable) in decentralized matching. Moreover, there is usually a restriction on the number of stages in decentralized matching. For example, the time cost at each stage of multi-stage decentralized matching is not negligible. We show in a numerical example of Appendix S1.3 that some agents are better off in decentralized markets than centralized markets.

5 Numerical studies

In this section we demonstrate aspects of the theoretical predictions through a simulation and a real data application in college admissions. We provide extensive numerical comparisons of Algorithm 1 with other methods in Appendix. We also give additional real data analysis in Appendix. The total computing hour is within one hour in personal laptop with Intel Core i5.

Simulated graduate school admissions Consider 50 graduate schools from three tiers of colleges: five top colleges $\{P_1, \ldots, P_5\}$, ten good colleges $\{P_6, \ldots, P_{15}\}$, and 35 other colleges $\{P_{16}, \ldots, P_{50}\}$. Each has the same quota $q = 5$ and penalty $\gamma = 2.5$. The simulation generates students' preferences with ten different states $\{s_1, \ldots, s_{10}\} \subset [0, 1]$. For any state, students' preferences for colleges from the same tier are random. However, students prefer top colleges to good colleges, and the other colleges are the least favorite. The random preferences depend on the state due to colleges' uncertain reputation and popularity in the current year. We consider varying numbers of students $\{250, 260, 270, 280, 290, 300\}$. For each size of students, there are ten students having score v_j chosen uniformly and i.i.d. from $[0.9, 1]$ and 100 students having score v_j i.i.d. uniformly chosen from $[0.7, 0.9]$. The rest of the students have score v_j randomly chosen from $[0, 0.7)$. The fits e_{ij} for all college-student pairs are drawn uniformly and i.i.d. from $[0, 1]$.

Figure 1: Performance of the proposed Algorithm 1 (i.e., LUB-CDM) and the Simple Cutoff Strategies with varying numbers of students. The results are averaged over 500 data replications. (a): College P_1 from tier 1. (b): College P_6 from tier 2. (c): College P_{16} from tier 3.

We compare the college's expected payoff achieved by the proposed Algorithm 1 with the *simple cutoff strategy*, where the latter method has each college choosing the most preferred students up to the remaining quota at each stage. The training data are simulated from colleges' random proposing by pulling a random number of arms according to the latent utilities. We train 20 times of random proposing under each of the arms' preference structures, which simulates admission over 20 years. The testing data draws a random state from $\{s_1, \ldots, s_{10}\}$ which gives the corresponding arms' preferences. Figure 1 reports the averaged payoffs of three colleges P_1, P_6, and P_{16} over 500 data replications. Here colleges P_1, P_6, and P_{16} belong to the three different tiers, respectively. In Figure 1, all colleges except P_1 use Algorithm 1 while P_1 uses one of the two methods: Algorithm 1 and the simple cutoff strategy. It is seen that Algorithm 1 gives the largest average payoffs for all of P_1, P_6 and P_{16}. In particular, Algorithm 1 performs significantly better for P_6 and P_{16} compared to the simple cutoff strategy.

U.S. college admissions   We study a public data on college admissions from the *New York Times* "The Choice" blog. In this dataset, 37 U.S. colleges reported their admission yields and waiting list offers for 2015–17 applicants without personally identifiable information. As we discussed in Section 2, a college's yield is a proxy for the state $s_{i,k}$ as it indicates the college's popularity. The set of 37 colleges consists of liberal arts colleges, national universities, and other undergraduate programs.

Figure 2: Regression of uncertainty level on the size of admitted class and the ranking, respectively. Two dashed curves are fitted using smoothing splines with the tuning parameter chosen by GCV.

We estimate the uncertainty level $\delta_{i,k}(v)\pi_{i,k}^{-1}(s_{i,k}, v)$ defined in (9) and study colleges' strategic responses. While conclusive evidence on the individual students' acceptance probability is difficult to obtain, we estimate the college-wise uncertainty on the yield: $\sqrt{\text{Var}(s_{i,k})}s_{i,k}^{-1}$. Since the choice set for admitted students differs across years, the yield's uncertainty underestimates the uncertainty facing a college. Figure 2 shows that colleges' uncertainty levels are much smaller than one, which, together with Theorem 1, implies that students face limited unfairness. In particular, the yield uncertainty is robust to the size of admitted students; see the left plot of Figure 2. On the other hand, top-ranked national universities may have higher uncertainty levels; see the right plot of Figure 2, where the outlier is the University of Chicago at the .19 uncertainty level. We verify the higher uncertainty level for top universities using the waiting list data. We perform Fisher's exact test for the rank data on the difference of rates of accepted waiting list students to total enrolled students over 2015–16. This statistic reflects the uncertainty on both the regular admission yield and the wait-listed students' quality. We reject the null hypothesis that the uncertainty of acceptance is the same for all national universities at the .05 significance level. The higher uncertainty for top-ranked national universities may arise due to the intense competition. Those universities are better off by employing strategic admission to reduce the enrollment uncertainty. This result implies that students are more likely to experience unfairness when applying for top national universities.

6   Conclusions

This paper develops a nonparametric statistical model to learn optimal strategies in multi-stage decentralized matching markets. The model provides insight into the interplay between learning and economic objectives in decentralized matching markets. In the model, arms have uncertain preferences that depend on the unknown state of the world and competition among the agents. We propose an algorithm, built upon the ideas of lower uncertainty bound and calibrated decentralized matching, for learning optimal strategies using historical data. We find that agents act strategically in favor of arms with low uncertainty levels of acceptance. The strategic targeting improves an agent's welfare but leads to unfairness for arms. Our theory allows analytical comparisons between single-stage decentralized markets and centralized markets. We also note that this work has no potential negative societal impact as it aims to deepen the understanding of matching markets from a learning perspective. We have not studied algorithmic strategies when agents' preferences show complementarities or indifference. For instance, firms demand workers that complement one another in terms of their skills and roles, or some applicants are indistinguishable to a firm. We leave these questions for future work.

References

[1] ABDULKADIROĞLU, A., AND SÖNMEZ, T. School choice: A mechanism design approach. *American Economic Review 93*, 3 (2003), 729–747.

[2] ARONSZAJN, N. Theory of reproducing kernels. *Transactions of the American Mathematical Society 68*, 3 (1950), 337–404.

[3] ASHLAGI, I., BRAVERMAN, M., KANORIA, Y., AND SHI, P. Clearing matching markets efficiently: Informative signals and match recommendations. *Management Science 66*, 5 (2020), 2163–2193.

[4] AVERY, C., FAIRBANKS, A., AND ZECKHAUSER, R. J. *The Early Admissions Game: Joining the Elite*. Harvard University Press, Cambridge, MA, 2003.

[5] AVERY, C., AND LEVIN, J. Early admissions at selective colleges. *American Economic Review 100*, 5 (2010), 2125–56.

[6] AZEVEDO, E. M., AND LESHNO, J. D. A supply and demand framework for two-sided matching markets. *Journal of Political Economy 124*, 5 (2016), 1235–1268.

[7] BALINSKI, M., AND SÖNMEZ, T. A tale of two mechanisms: Student placement. *Journal of Economic Theory 84*, 1 (1999), 73–94.

[8] BUBECK, S., AND CESA-BIANCHI, N. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends in Machine Learning 5*, 1 (2012), 1–122.

[9] CHADE, H., LEWIS, G., AND SMITH, L. Student portfolios and the college admissions problem. *Review of Economic Studies 81*, 3 (2014), 971–1002.

[10] CHADE, H., AND SMITH, L. Simultaneous search. *Econometrica 74*, 5 (2006), 1293–1307.

[11] CHE, Y.-K., AND KOH, Y. Decentralized college admissions. *Journal of Political Economy 124*, 5 (2016), 1295–1338.

[12] COLES, P., CAWLEY, J., LEVINE, P. B., NIEDERLE, M., ROTH, A. E., AND SIEGFRIED, J. J. The job market for new economists: A market design perspective. *Journal of Economic Perspectives 24*, 4 (2010), 187–206.

[13] DAI, X., AND JORDAN, M. I. Learning the strategy in decentralized matching markets under uncertain preferences. *arXiv preprint arXiv:2011.00159.* (2020).

[14] DAS, S., AND KAMENICA, E. Two-sided bandits and the dating market. In *Proceedings of the 19th International Joint Conference on Artificial Intelligence* (New York, 2005), vol. 5, AAAI Press, p. 19.

[15] DIAMANTOUDI, E., MIYAGAWA, E., AND XUE, L. Decentralized matching: The role of commitment. *Games and Economic Behavior 92* (2015), 1–17.

[16] EPPLE, D., ROMANO, R., AND SIEG, H. Admission, tuition, and financial aid policies in the market for higher education. *Econometrica 74*, 4 (2006), 885–928.

[17] FU, C. Equilibrium tuition, applications, admissions, and enrollment in the college market. *Journal of Political Economy 122*, 2 (2014), 225–281.

[18] GALE, D., AND SHAPLEY, L. S. College admissions and the stability of marriage. *The American Mathematical Monthly 69*, 1 (1962), 9–15.

[19] HAFALIR, I. E., HAKIMOV, R., KÜBLER, D., AND KURINO, M. College admissions with entrance exams: Centralized versus decentralized. *Journal of Economic Theory 176* (2018), 886–934.

[20] HASTIE, T., TIBSHIRANI, R., AND FRIEDMAN, J. *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*. Springer Science & Business Media, New York, 2009.

[21] LADNER, R. E. On the structure of polynomial time reducibility. *Journal of the ACM 22*, 1 (1975), 155–171.

[22] MONTGOMERY, J. D. Equilibrium wage dispersion and interindustry wage differentials. *The Quarterly Journal of Economics 106*, 1 (1991), 163–179.

[23] NIEDERLE, M., AND YARIV, L. Decentralized matching with aligned preferences. Tech. rep., National Bureau of Economic Research, 2009.

[24] PETERS, M. Ex ante price offers in matching games non-steady states. *Econometrica 49*, 5 (1991), 1425–1454.

[25] ROTH, A. E. The evolution of the labor market for medical interns and residents: A case study in game theory. *Journal of Political Economy 92*, 6 (1984), 991–1016.

[26] ROTH, A. E. Deferred acceptance algorithms: History, theory, practice, and open questions. *International Journal of Game Theory 36*, 3-4 (2008), 537–569.

[27] ROTH, A. E., AND SOTOMAYOR, M. *Two-Sided Matching: A Study in Game-Theoretic Modeling and Analysis*, vol. 18. Econometric Society Monographs, Cambridge University Press, Cambridge, 1990.

[28] ROTH, A. E., AND XING, X. Turnaround time and bottlenecks in market clearing: Decentralized matching in the market for clinical psychologists. *Journal of Political Economy 105*, 2 (1997), 284–329.

[29] SAVAGE, L. J. *The Foundations of Statistics*. Dover Publications, Inc., New York, 1972.

[30] SILVERMAN, B. W. *Density Estimation for Statistics and Data Analysis*, vol. 26. Chapman and Hall, London, 1986.

[31] WAHBA, G. *Spline Models for Observational Data*. SIAM, Philadelphia, PA, 1990.

[32] WAHBA, G., WANG, Y., GU, C., KLEIN, R., AND KLEIN, B. Smoothing spline anova for exponential families, with application to the wisconsin epidemiological study of diabetic retinopathy. *Annals of Statistics 23*, 6 (1995), 1865–1895.